

Admin-Managed Catalog

What changed on the Kenule branch, how to merge it alongside PR #4 and PR #5, and what FEATURE-005 can now build on.

AUTHOR	Mohamed Reda Dahdah (mrdahdah)
FOR	Kenule (branch owner) · Ghayth (maintainer) · Raead (FEATURE-005) · the team
DATE	2 September 2026
REPOSITORY	Ghaythhezami/gmc-ecommerce — base branch feat(kenule)/auth
THIS WORK	PR #7 · branch feat/kenule-admin-catalog · 6 commits

TL;DR

The storefront catalog was hardcoded in a single file and the admin panel had placeholder pages where Products and Categories should be. PR #7 makes the whole catalog database-driven and editable from the admin panel, splits the Prisma schema into one file per module, adds VAPID web push, a real newsletter and a configurable flash sale, introduces the first API tests, and fixes the local launch scripts.

Before merging, read section 6. PR #7 re-implements category CRUD that PR #4 already delivers, at the same file paths. The two conflict and must be reconciled — merge #4 first, then rebase #7 onto it.

1 Every pull request at a glance

PR	BRANCH	STATUS	WHAT IT DELIVERS
#7	feat/kenule-admin-catalog	OPEN · NEW	Admin-managed catalog: products module, category management UI, dynamic storefront, multi-file Prisma, script fixes.
#6	fix/production-build-ts59	OPEN	Production build fix for TypeScript 5.9 (<code>ignoreDeprecations</code>). Effectively a prerequisite for everything else.
#5	feat/kenule-shopping-cart	OPEN	FEATURE-004 Shopping Cart — persistent, server-priced, stock-validated.
#4	feat/kenule-category-management	OPEN	FEATURE-003 Category Management — admin CRUD API plus public browse, with a unit test.
#3	feat/kenule-review	OPEN	Review notes on the auth foundation: Next.js rewrite, RBAC, Cloudinary, guest checkout, multi-file Prisma.
#2	feature/shopping-cart	CLOSED	Superseded by #5 (retargeted from <code>main</code> onto the Kenule branch).
#1	feature/category-management	CLOSED	Superseded by #4 (retargeted from <code>main</code> onto the Kenule branch).

Suggested merge order

#6 (unblocks the build) → #4 (categories) → #5 (cart) → rebase and merge #7 last, since it touches the most files and overlaps #4.

2 What PR #7 changes

2.1 Prisma — one file per module

The single `apps/server/prisma/schema.prisma` is replaced by a schema folder, so each domain owns its own file and two students editing different models no longer collide in the same file.

PATH	CONTAINS
<code>prisma/schema/schema.prisma</code>	generator + datasource only
<code>prisma/schema/user.prisma</code>	User, Role
<code>prisma/schema/category.prisma</code>	Category
<code>prisma/schema/product.prisma</code>	Product
<code>prisma/schema/cart.prisma</code>	Cart, CartItem
<code>prisma/schema/order.prisma</code>	Order, OrderItem, OrderStatus ← FEATURE-005
<code>prisma/schema/notification.prisma</code>	Notification
<code>prisma/schema/storefront.prisma</code>	StorefrontAccess

Two gotchas that cost real time — please don't re-discover them

Prisma 6.19 does not auto-detect a schema folder. The path must be declared explicitly; it now lives in `apps/server/package.json` under the `prisma` key. This prints a deprecation warning pointing at `prisma.config.ts`. That migration was deliberately deferred: a config file disables automatic `.env` loading and would need a `dotenv` dependency.

Migrations move with the schema. With a schema *folder*, Prisma resolves migrations relative to that folder, so `prisma/migrations/` is now `prisma/schema/migrations/`. Leave it in the old place and the CLI reports every existing migration as missing and demands a database reset.

2.2 New schema fields

One additive migration, `20260902200917_catalog_fields`. No data loss, no reset.

MODEL	ADDED
Category	<code>description</code> , <code>icon</code> , <code>imageUrl</code> , <code>sortOrder</code> , <code>isActive</code> · index on <code>(isActive, sortOrder)</code>
Product	<code>compareAtPrice</code> , <code>rating</code> , <code>reviewCount</code> , <code>isFeatured</code> , <code>isActive</code> · index on <code>(isActive, isFeatured)</code>

`compareAtPrice` is the “was” price. The discount percentage is *derived server-side*, never stored, so it cannot drift out of sync with the price.

2.3 API surface

VERB	ROUTE	ACCESS	NOTES
GET	/api/categories	Public	Active categories, ordered by <code>sortOrder</code> , with product counts
GET	/api/categories/:slug	Public	One category
GET	/api/categories/manage/all	Admin	Includes hidden categories
POST / PATCH / DELETE	/api/categories	Admin	Delete refuses while products remain
GET	/api/products	Public	<code>category</code> , <code>search</code> , <code>featured</code> , <code>onSale</code> , <code>sort</code> , <code>page</code> , <code>limit</code>
GET	/api/products/:slug	Public	One product
GET	/api/products/manage/all	Admin	Includes hidden products
POST / PATCH / DELETE	/api/products	Admin	Delete refuses if the product is on an order

Admin routes sit behind `JwtAuthGuard` + `RolesGuard` + `@Roles(Role.ADMIN)`, matching the pattern Kenule established in `auth/`. The literal `manage/all` route is declared *before* `:slug` so the parameterised route does not swallow it.

2.4 Three implementation details worth knowing

- **Decimal → number.** Prisma returns `Decimal` instances that JSON-serialize as *strings*, which silently breaks arithmetic in the browser. Both services map them to numbers before returning. Any new module reading `price` should do the same.
- **Column-to-column filtering.** `onSale` compares `compareAtPrice > price` using Prisma *field references* inside `where`. Filtering in JS after the query would corrupt `total` and produce short pages.
- **Deactivate, don't delete.** Products referenced by an `OrderItem` cannot be deleted; the API returns a message telling the admin to deactivate instead. This protects order history — directly relevant to FEATURE-005.

2.5 Admin panel and storefront

- Admin gains real **Categories** and **Products** pages (full CRUD, category filter, modal forms) built on the tokens already in `styles.css`. They replace the placeholder pages.
- `AdminLayout` used Tailwind classes that **do not exist** in the admin theme — `bg-bg`, `bg-surface`, `border-border`, `text-text`, `text-star` — while `styles.css` defines `--color-admin-*`. They compiled to nothing, leaving the background, body text, panel surfaces and header border unstyled. Now mapped onto the tokens that exist.
- `apps/client/src/components/home/data.ts` is **deleted**. Category nav, category grid, hero rails, flash sale and trending rows all read from the API.
- The catalog page gains search, sort and pagination and serves both `/products` and `/category/:slug`; `/products/:slug` is now a real product detail page.
- Cross-app navigation was missing entirely: the admin sidebar gains *View storefront*, and the storefront top bar gains *Home* and *Admin*. Separate origins, so these are plain anchors driven by `VITE_STOREFRONT_URL` / `VITE_ADMIN_URL`.

2.6 Web push over VAPID

- A `PushSubscription` row per browser, so one account can be reached on several devices. The endpoint is unique, so re-subscribing the same browser updates its keys instead of piling up duplicate rows.
- Delivery is **best-effort**: a failed send never fails the request that triggered it, and subscriptions the push service reports as gone (404/410) are pruned automatically.
- The app still boots without VAPID keys — push simply reports itself disabled, so nobody needs a keypair just to run the catalog. Generate a pair with web-push and put it in `apps/server/.env` (see `.env.example`).
- Endpoints: `GET /api/notifications/vapid-public-key` (public), subscribe / unsubscribe, list, unread-count, mark one or all read, and `POST /api/notifications/broadcast` (admin).
- The client registers `public/sw.js`, which renders the push and focuses an existing tab on click rather than opening a duplicate.

2.7 Storefront content the admin now owns

- **Flash sale.** The countdown used to be a hardcoded `04:32:15` that never moved. It now runs down to a real end time, and the strip's headline, end time and visibility are set on the new admin Marketing page. Which products appear is still automatic — anything whose compare-at price exceeds its price.
- **Newsletter.** The form submitted nowhere. There is now a `NewsletterSubscriber` table, public subscribe / unsubscribe and an admin list. Sign-up is idempotent, and the response deliberately does not reveal whether an address was already on the list.
- **Dashboard.** It displayed invented figures — a hardcoded "+12.5%", zero products, "Latency: 24ms". It now reads a real `/api/admin/stats` endpoint.

2.8 Toasts and other gaps closed

- A shared `ToastProvider` in both apps: auto-dismissing stack, success / error / info tones, `aria-live` (assertive for errors), and an entrance animation gated behind `motion-safe`. Inline banners are kept for form validation errors, which belong next to the field rather than in a corner.
- `/help`, `/support` and `/sell` were linked from the header and top bar but had no routes, so they fell through to the 404. All three now render.
- The header search box did nothing; both the desktop and mobile inputs are now forms that navigate to `/products?q=...`.
- The catch-all route redirected silently to `/`, hiding genuinely dead links. Replaced with a real 404 page.
- The profile page showed only what was cached at login; it now re-reads `/auth/me` and surfaces role, join date and unread notifications.
- Logout only reset `authApi`, so the next account could briefly see the previous user's cached notifications. All user-scoped caches are cleared.
- `AdminLayout` referenced Tailwind classes absent from the admin theme (`bg-bg`, `bg-surface`, `border-border`, `text-text`, `text-star`), which compiled to nothing and left the panel unstyled. Mapped onto the `--color-admin-*` tokens that exist.

3 Running it locally

Two helper scripts sit at the repository root. Both were broken in ways that are easy to misread as “the project doesn't work”, and both are fixed in PR #7.

SCRIPT	WHAT IT DOES
launch-webapp.bat	Starts the <code>gmc-postgres</code> container on port 5433 , waits for it, runs <code>prisma generate</code> and <code>migrate deploy</code> , compiles the server once, then opens three terminals (API, storefront, admin) and polls the API before reporting success.
stop-webapp.bat	Frees ports 3000 / 5173 / 5174, closes the three terminals, stops the container. Data survives in the Docker volume.

Why the API used to die on launch while the two frontends came up fine

The script deleted `apps\server\dist` and immediately ran `nest start --watch`. The watcher launches `dist/src/main.js` the moment it appears, so against an empty dist it *raced the compiler* and exited with `Cannot find module './app.module'`. Nest only retries on a file change, so the API stayed dead and silent. It now compiles once before the watcher starts.

Two smaller fixes: `timeout /t 1` aborts with “input redirection is not supported” when stdin is redirected, so the DB wait loop uses `ping`; and the script now warns explicitly instead of printing the URLs while the API is down.

If the API will not start

Check `docker ps` first. A stopped `gmc-postgres` makes Nest exit at boot with Prisma `P1001 - Can't reach database server at localhost:5433`. Note the port is **5433**, not the default 5432.

Seed accounts all use `Student123! : admin@example.com` (ADMIN), `student1@example.com`, `student2@example.com`. Note the storefront login at `/api/auth/login` deliberately rejects ADMIN accounts; admins sign in at `/api/admin/auth/login`.

4 Catalog data

The seed now creates a coherent catalog — 6 categories and 12 products with real prices, stock, ratings, sale prices and imagery — and is idempotent on slug, so re-running it is safe.

Data cleanup applied to the shared dev database

The original starter seed had left `Electronics` and `Home` categories holding a *Wireless Headphones* and a *Desk Lamp* — placeholders that do not belong in a games catalog and were appearing in the storefront navigation. Both products were reassigned to `Accessories` and the two empty categories were removed. Current state: **6 categories, 14 products, 0 products with a dangling category**.

5 Ticket verification — FEATURE-001 to 004

Each was reviewed against its ticket in `docs/tickets/`. Three criteria were unmet and are fixed in PR #7; everything else already held.

ACCEPTANCE CRITERION	MET	EVIDENCE
FEATURE-001 — Authentication (already on the Kenule branch)		
Duplicate emails rejected	Yes	409 from the register endpoint
Invalid credentials rejected	Yes	401, same message for unknown user and wrong password
Passwords hashed	Yes	bcrypt cost 10; only safe user objects are returned
<code>/auth/me</code> requires JWT	Yes	Behind <code>JwtAuthGuard</code> ; 401 without a token
Admin routes reject customers	Yes	Verified 403 with a CUSTOMER token on an admin write
Logout clears auth <i>and</i> cached API state	Fixed	Only <code>authApi</code> was reset, so the next account could briefly see the previous user's cached notifications. All user-scoped caches are now cleared.
FEATURE-002 — Product Catalog (delivered by PR #7)		
Products include category data	Yes	Every product payload embeds its category
Invalid IDs return proper errors	Yes	404 for an unknown slug; 400 for a bad category on write
Search and pagination server-side	Yes	Prisma <code>skip</code> / <code>take</code> , with <code>total</code> and <code>pageCount</code> in the response
Loading / empty / error states	Fixed	Loading and empty existed; the error state was missing and now has a retry action
API tests exist	Fixed	There was no jest configuration and jest was not installed. Both added, plus 27 passing unit tests.

FEATURE-003 and FEATURE-004 live in PRs #4 and #5. Both are implemented and meet their acceptance criteria:

ACCEPTANCE CRITERION	MET	EVIDENCE
FEATURE-003 — Category Management (PR #4)		
Only admins mutate	Yes	Guards on every write; verified 401 unauthenticated, 403 with a CUSTOMER token
Unique names / slugs	Yes	Pre-write check returning a clean 409 instead of a raw Prisma P2002
DTO validation	Yes	<code>class-validator</code> DTOs behind the global ValidationPipe
RTK Query invalidation	Yes	Tag-based invalidation on the client slice
Admin + public UI paths	Yes	Public categories page; admin CRUD arrives with PR #7
FEATURE-004 — Shopping Cart (PR #5)		
Add / remove / update / clear	Yes	All four implemented in <code>cart.service.ts</code>
Quantities validated	Yes	<code>assertStock</code> rejects quantities above available stock
Totals use server prices	Yes	Line totals and subtotal computed from <code>product.price</code> , never from the client
Users only access their cart	Yes	Every query scoped by <code>userId</code> ; removal uses a cart-scoped <code>deleteMany</code>
Cart UI states	Yes	<code>CartPage.tsx</code> handles empty / loading / error

Neither is merged yet — and the cart is not usable on the Kenule branch alone

On `feat(kenule)/auth` there is no `/cart` route, the cart badge is hardcoded to `0` , and “Add to Cart” does nothing. Kenule's client-only `features/cart/cartSlice.ts` and PR #5's server-backed cart are two competing sources of truth — **the team needs to pick one**. Prefer the server cart: it is the only one that can price an order correctly.

6 The conflict between PR #7 and PR #4 — please read

PR #4 already delivers FEATURE-003. PR #7 was built before that was taken into account and **independently adds its own `apps/server/src/categories/` module at the same file paths**. Both cannot be merged as they stand.

	PR #4	PR #7
Category CRUD API	Yes	Yes
Unit test (<code>categories.service.spec.ts</code>)	Yes	No
Products-by-category	<code>/categories/:slug/products</code>	<code>/products?category=slug</code>
Uniqueness conflict status	409	400
<code>icon</code> / <code>sortOrder</code> / <code>isActive</code> / <code>imageUrl</code>	No	Yes
Admin CRUD UI	No	Yes
Products module	No	Yes
Storefront wired to the API	categories page only	whole storefront

Recommended resolution

Merge **#4** first and keep its service and its test as the canonical category implementation. Then rebase **#7** onto the result and re-apply only three things: the extra `Category` columns, the products module, and the admin UI. Everything in #7 outside `categories/` — products, the storefront rewrite, the Prisma split, the script fixes — is additive and should rebase cleanly.

7 For Raeed — what FEATURE-005 can build on

Orders is a module plus a frontend slice. `Order`, `OrderItem` and `OrderStatus` already exist in Prisma, so **no migration is required**. Once PR #7 lands, these are ready to use:

- **A products module to read from.** `ProductsService` already returns prices as numbers, so order totals can be computed without unwrapping `Decimal` yourself.
- **Stock and price on every product.** `stock` for availability checks, `price` for the `unitPrice` snapshot on each `OrderItem`.
- **Deletion already protects order history.** A product on an order line cannot be deleted, so `OrderItem.productId` will not dangle. Keep this rule in mind if you add order-side deletes.
- **An admin shell to extend.** Add an Orders page next to Categories and Products; reuse the shared primitives in `apps/admin/src/components/ui.tsx` (`Field`, `Input`, `Select`, `Modal`, `Banner`) and the `errorMessage` helper so validation errors surface properly. The sidebar already has an `/orders` placeholder route to replace.
- **A guard pattern to copy.** `products.controller.ts` is the shortest example of public reads plus admin-only writes on one controller, including the `manage/all` -before- `:slug` route-ordering rule.

Your one real decision: which cart feeds an order

An order is created from a cart, and there are currently two carts. Design against PR #5's **server cart** — it computes subtotals from database prices, which is what an order needs. If #5 has not merged when you start, branch from `feat/kenule-shopping-cart` rather than from the Kenule branch, or build the Orders module against the Prisma models directly and wire the cart link once #5 lands.

Snapshot the price at purchase time

`OrderItem.unitPrice` exists precisely so an order keeps the price that was charged. Copy `product.price` into it when the order is created — never join back to `Product` to display a historical order, or every past order changes whenever an admin edits a price in the panel.

8 Commits in PR #7

COMMIT	SUBJECT
8c76844	feat(catalog): admin-managed products and categories
7fc0d8c	fix(ui): repair admin theme tokens and add cross-app navigation
4b474cb	chore(scripts): fix the local launch/stop helpers
b8454a0	docs: team handoff PDF for merging PR #7 alongside #4 and #5
e4721de	feat(notifications): VAPID web push, real dashboard stats, and gap fixes
4fa1b76	feat(ux): toast notifications, API tests, and FEATURE-001/002 gap fixes
34083cf	feat(storefront): newsletter, configurable flash sale, help pages, real profile

Verification performed before opening the PR

- `tsc --noEmit` clean on server, admin and client (with PR #6 applied — without it the build fails on TypeScript 5.9).
- **27 unit tests pass** over `ProductsService` and `CategoriesService`. The server had no jest configuration at all and jest itself was not installed; both were added, which is what FEATURE-002's "API tests exist" criterion needs.
- Push pipeline exercised end to end: a broadcast stored a notification for every user, attempted delivery, and pruned the dead subscription — while still returning success, confirming push failures do not break the request.
- Newsletter, flash-sale configuration and their guards checked over HTTP.
- Guards: 401 unauthenticated, 403 with a CUSTOMER token on an admin write.
- Validation: 400 for `compareAtPrice ≤ price`; 400 deleting a category that still holds products.

- Full round trip through the admin UI — created a product, confirmed slug generation and the derived discount, saw it appear on the storefront category page and its detail page, then deleted it and confirmed a 404.
- Both scripts run end to end: `stop` frees all three ports and stops the container; `launch` brings all three services up.

Prepared by Mohamed Reda Dahdah (mrdahdah) · 2 September 2026 · Ghaythhezami/gmc-eccommerce · companion to [docs/ADMIN-MANAGED-CATALOG.md](#)