

Functional and logic programming

- written exam -

Important:

1. Subjects are graded as follows: of - 1p; A – 1.5p; B - 2.5p; C - 2.5p; D - 2.5p.
2. Prolog problems will be resolved using SWI Prolog. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for all the predicates used; (3) specification of every predicate (parameters and their meaning, flow model, type of the predicate - deterministic/non-deterministic).
3. Lisp problems will be resolved using Common Lisp. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for each function used; (3) specification of every function (parameters and their meaning).

A. Given the following PROLOG predicate definition **f(integer, integer)**, with the flow model (i, o):

f(100, 0):-!.
f(I,Y):-J is I+1, **f(J,V)**, V>2, !, K is I-2, Y is K+V-1.

f(I,Y):-J is I+1, **f(J,V)**, Y is V+1.

Rewrite the definition in order to avoid the recursive call **f(J,V)** in both clauses. Do NOT redefine the predicate. Justify your answer.

B. Given a nonlinear list containing both numerical and non-numerical atoms, write a LISP program that builds a list that contains on even levels the greatest numerical atom, and for odd levels the lowest numerical atom (we assume that each level of the list contains at least a numerical atom), but in reverse order (so the minimum on level 1 is the last element, the maximum on level 2 is the penultimate element, etc.). For example, for the list (A B 12 (5 D (A F (10 B) D (5 F) 1)) C 9 (F 4 (D) 9 (F (H 7) K) (P 4)) X) the result will be (10 1 9 9). You are not allowed to use function *reverse* from Lisp.

C. Write a PROLOG program that determines from a list made of integer numbers, the list of subsets with at least 2 elements, composed of numbers in strictly increasing order. Write the mathematical models and flow models for the predicates used. For example for the list [1, 8, 6, 4] \Rightarrow [[1,8],[1,6],[1,4],[6,8],[4,8],[4,6],[1,4,6],[1,4,8],[1,6,8],[4,6,8],[1,4,6,8]] (not necessarily in this order).

D. An n-ary tree is represented in Lisp as (node subtree1 subtree2 ...).. Write a function to return the list of nodes on even levels, in increasing level order (0, 2, ...). The root level is assumed zero. **A MAP function shall be used.**

Example for the tree (a (b (g)) (c (d (e (h))) (f))) => (a g d f h)