Functional and logic programming written exam -

Important:

- 1. Subjects are graded as follows: of 1p; A 1.5p; B 2.5p; C 2.5p; D 2.5p.
- 2. Prolog problems will be resolved using SWI Prolog. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for all the predicates used; (3) specification of every predicate (parameters and their meaning, flow model, type of the predicate deterministic/non-deterministic).
- 3. Lisp problems will be resolved using Common Lisp. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for each function used; (3) specification of every function (parameters and their meaning).
- **A.** Let L be a list of numbers and given the following PROLOG predicate definition **f(list, integer)**, with the flow model (i, o):

```
f([], 0).

f([H|T],S):-f(T,S1), H<S1,!,S is H+S1.

f([_|T],S):-f(T,S1), S is S1+2.
```

Rewrite the definition in order to avoid the recursive call **f(T,S)** in both clauses. Do NOT redefine the predicate. Justify your answer.

B. Given a nonlinear liverifies if the average atoms on odd levels. Fresult will be true.	of the numerical	atoms on even	levels is equal to	the average of t	ne numerical

C. Write a PROLOG program that generates the list of all subsets of k elements (all elements being odd numbers) in arithmetic progression. Write the mathematical models and flow models for the predicates used. For example, for L=[1,5,2,9,3] and k=3 \Rightarrow [[1,5,9],[1,3,5]] (not necessarily in this order).

D. Given a nonlinear list, write a Lisp function to replace all the odd values from even levels with their natural successor. The superficial level is assumed 1. **A MAP function shall be used. Example** for the list (1 s 4 (3 f (7))) the result is (1 s 4 (4 f (7))).