



Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	The company experienced a security event when all network services suddenly stopped responding. The cybersecurity team found the disruption was caused by a DDOS attack through a flood of incoming ICMP packets. The team responded by blocking the attack and stopping all non-critical network services, so that critical network services could be restored.
Identify	The cybersecurity team discovered that a malicious actor or actors had sent a flood of ICMP Pings into the company's network through an unconfigured firewall. All critical network resources needed to be secured and restored to a functioning state.
Protect	The cybersecurity team implemented a new firewall rule to limit the rate of incoming ICMP packets and an IDS/IPS system to filter out some ICMP traffic to the internal network based on suspicious characteristics.
Detect	The cybersecurity team configured source IP address verification on the firewall to check for spoofed IP addresses on incoming ICMP packets and also installed network monitoring software to detect abnormal traffic patterns.
Respond	For future security events, the cybersecurity team will isolate affected systems to prevent further disruption to the network. They will attempt to restore any critical systems and services that were disrupted by the event. Then, the team will analyze network logs to check for suspicious and abnormal activity. The team will also report all incidents to upper management and appropriate legal authorities, if applicable.
Recover	To recover from a DDoS attack by ICMP flooding, access to network services need to be restored to a normal functioning state. In the future, external ICMP flood attacks can be blocked at the firewall itself. Then, all non-critical network services should be stopped to reduce internal network traffic. Next, critical network services should be restored first. Finally, once the flood of ICMP packets have timed out, all non-critical network systems and services can be brought back online.

