

wizz-flight-selector

The FlightSelector component.

data

- selected *initial value*: 'Please select...'
- selectedConnections *initial value*: [object Object]
- departureIata *initial value*: ''
- destinationIata *initial value*: ''
- selectedDestination *initial value*: 'Please select...'
- departureDate *initial value*: [object Object]
- returnDate *initial value*: ''
- destinationDate *initial value*: ''
- dateSelected *initial value*: ''
- secondSelected *initial value*: false
- airports *initial value*: [object Object]
- flights *initial value*: [object Object]
- returnFlights *initial value*: [object Object]
- isFirstSelected *initial value*: false
- localConnections *initial value*: [object Object]
- isLoading *initial value*: false
- isDepartureSelected *initial value*: false
- isReturnNeeded *initial value*: false
- isBackSelected *initial value*: false
- date *initial value*: [object Object]
- configDeparture *initial value*: [object Object]
- configReturn *initial value*: [object Object]

computed properties

- `getToday` Getting today's date.

methods

- `selectReturnClicked()`
- `selectedConnect()` Getting the iata's on the departure select change.
- `destinationSelect()` Storing the destination iata's.
- `getFullNames(iata)` Based on the selected departure connections (destinations) iata's look for the shortName (e.g. the full name) in the list from the API.
- `dateChanged()` Storing and setting the value on the departure selector.

wizz-header

The Header component.

data

- `departureCity` *initial value:* 'Budapest'
- `destinationCity` *initial value:* 'Barcelona El Prat'
- `departureIata` *initial value:* 'BUD'
- `destinationIata` *initial value:* 'BCN'

wizz-tickets-moredates

The MoreDates static component.

wizz-select-backdate

The SelectBackDates component.

data

- `returnDate` *initial value:* ""
- `departureDateSelected` *initial value:* ""
- `isReturnNeeded` *initial value:* false
- `isShowingDateselect` *initial value:* false
- `configReturn` *initial value:* [object Object]
- `animation` *initial value:* [object Object]

events

- `selectbackdate` undefined

methods

- `selectReturnDate()` Selecting the returndate, setting the minimal selectable value to the departure date +1 day.
- `getReturnFlights()`
- `dateChanged()` Trigger only if data changes.

wizz-sidebar

The Sidebar component.

data

- `selectedTicket` *initial value:* ""
- `returnSelectedTicket` *initial value:* ""
- `isReturnTicketSelected` *initial value:* false
- `isTicketSelected` *initial value:* false
- `total` *initial value:* '0'

computed properties

- `getTotal` Calculating the single and total price of the selected tickets. *dependencies:* `isReturnTicketSelected` `selectedTicket` `returnSelectedTicket` `selectedTicket`
- `getOriginalPrice` Adding 19.5% to the price to get a higher price than the calculated, this way the discount is visible and separable *dependencies:* `isReturnTicketSelected` `selectedTicket` `returnSelectedTicket` `selectedTicket`

wizz-summary

The Summary component.

data

- `flight` *initial value:* "
- `selectedTicket` *initial value:* "
- `departureCity` *initial value:* "
- `destinationCity` *initial value:* "
- `returnFlight` *initial value:* "
- `returnSelectedTicket` *initial value:* "
- `isReturnTicketSelected` *initial value:* `false`
- `returnDepartureCity` *initial value:* "
- `returnDestinationCity` *initial value:* "
- `total` *initial value:* "

computed properties

- `getTotal` Getting the single or the calculated ticket price. *dependencies:*
`isReturnTicketSelected` `selectedTicket` `returnSelectedTicket`
`selectedTicket`

methods

- `hideModal()` Hiding the modal on close.

wizz-tickets

The Tickets component.

data

- actualFlight *initial value:* [object Object]
- isTicketsShow *initial value:* false
- departureCity *initial value:* "
- destinationCity *initial value:* "
- selectedDate *initial value:* "
- departureIata *initial value:* "
- destinationIata *initial value:* "
- isReturn *initial value:* false
- isTicketSelected *initial value:* false
- isBackSelectorShow *initial value:* false
- returnActualFlight *initial value:* [object Object]
- returnDepartureCity *initial value:* "
- returnDestinationCity *initial value:* "
- returnSelectedDate *initial value:* "
- returnDepartureIata *initial value:* "
- returnDestinationIata *initial value:* "

wizz-tickets-descriptions

The TicketDescriptions static component.

wizz-discounts

The Discounts static component.

wizz-tickets-row

TicketsRow component.

data

- `selectedTicket` *initial value:* ""
- `selectedFlight` *initial value:* ""
- `outboundTicketSelected` *initial value:* false

events

- `ticketdata` undefined

methods

- `busData(flight)` Setting the selected flight informations and emitting the data.
- `selectTicket(ticket, event, key)`

wizz-tickets-row-return

TicketsRowReturn component.

data

- `returnSelectedTicket` *initial value:* "
- `returnSelectedFlight` *initial value:* "
- `returnTicketSelected` *initial value:* false

events

- `returnticketdata` undefined

methods

- `busData(flight)` Setting the selected flight informations and emitting the data.
- `returnSelectTicket(ticket, event)`

wizz-title-bar

The TitleBar static component.