

TO, M/S K B Creation
PANDESARA,SURAT.

Price list Effected Date:- 01.04.2026

Qtn No-SFVC/KBC/01/0526-27
DT-01/04/2026

KIND ATTN:-

QUOTATION FOR :- "SUNFORD" BRAND INDUSTRIAL VALVES

COMPANY PROFILE



Sunford valves company is a Bureau Veritas Certified leading Industrial Valves Manufacturers based in Surat, India, managed by dynamic and highly technically qualified partners and professionals Sunford Valves is a truly integrated and incredible innovative company performing activities include the design, material procurement, manufacturing, assembly and testing of valves. Our experience of 3 decades in valve industry is the key to our success & recognition in the Indian market.

SUNFORD manufactures Gate, Globe, Check, Ball, Butterfly, Wafer Type Check Valve, Strainers etc. in all size and class with any material of construction as per customer requirement like Carbon Steel, Alloy Steel, Stainless Steel, Duplex, Monel etc. adhering to National and International Standards such as API 600, API 602, BS 1873, BS 1868, BS 5351, BS 5352 etc. The organization has excellent in house manufacturing and testing facilities with state of art technology for Design and Manufacture of Industrial Valves. The organization has an added advantage of experienced and trained personnel working with the motto of Quality Products, Best Services and Timely Delivery at competitive Prices to remain customer's first choice.

Design and Engineering

Sunford engineering department's mission is design innovation. Our ability, experience and expertise through the use of sophisticated technology and CAD/CAM equipment results in the manufacturing high quality industrial valves for wide range of applications.

Manufacturing

Sunford valves manufacturing unit is equipped with latest machineries, equipments includes CNC machines as well as semi automatic machine and test facilities spread over 14000 sq.ft area. Our production team of skilled workers ensure to employee latest state of art modern techniques in the entire cycle of production under stringent quality control procedures. All industrial valves manufactured to the highest degree of accuracy to ensure trouble free long life and guaranteed interchangeability of valves and spares.

Quality

Certified by ISO 9001:2015
Lean Manufacturing Practices Follows
Six Sigma, Kaizen, 5S, TQM & Total
customer Satisfaction. In-house Full Scale
Testing Facility.

Customer Service

Sunford has fully integrated customer services division, which fully geared to react speedily to all customers inquiries and serve them by providing best solution suitable for their requirements.

Industries We Serve

Textile, Chemical, Pharmaceutical,
Oil & Gas Processing, Petrochemical,
Power Plants, Marine, Packaging,
Steel and Cement, Water Treatment,
Food & Beverages, Cooling Plants,
Pulp & Paper Industries.



Sunford Valves Advantages

- Strong management team, stable company
- Products proven to offer:
- Low emissions
- Easy maintenance
- Long and reliable service
- Low total cost of ownership
- Quality that lasts

What Gives Us An Edge Over Others?

- Latest cutting edge technology
- Safe and sound operations
- Customized solutions
- Premium quality valves of variegated types
- Cost-effective
- Timely delivery
- End-to-end solutions
- Innovative products

Our Commitment

- To understand customers' NEEDs first before proposing our product.
- To keep providing competitive RATES by continuously improvement in process without compromising in quality.
- To provide continuously support to our customer and go beyond their expectations in terms of quality, delivery and after sales services.



SUNFORD VALVES COMPANY



PLOT NO. D- 9/21, ROAD NO. 2, NEAR SACHIN PAPER MILL, HOJIWALA INDUSTRIAL
ESTATE, SACHIN, SURAT - 394 230, GUJARAT, INDIA.

Bureau Veritas Certification Holding SAS - UK Branch certifies that the
Management System of the above organization has been audited and found to
be in accordance with the requirements of the Management System standard
detailed below.

Standard

ISO 9001:2015

Scope of certification

**MANUFACTURE AND SUPPLY OF GATE VALVE, GLOBE VALVE,
MANUAL AND AUTO BALL VALVE, CHECK VALVE, CONTROL VALVE,
BUTTERFLY VALVE, STRAINER, FLUSH BOTTOM VALVE**

Original cycle start date: 19 November 2019

Expiry date of previous cycle: Not Applicable

Certification Audit date: 19 September 2019

Certification cycle start date: 19 November 2019

Subject to the continued satisfactory operation of the organization's Management System,
this certificate expires on: 18 November 2022

Certificate No. IND.19.10523U Version : 1 Revision date: 19 November 2019



0008

Signed on behalf of BVCH SAS - UK Branch
Jagdish N. MANIAN
Head - CERTIFICATION, South Asia
Commodities, Industry & Facilities Division

Certification body
address: 5th Floor, 66 Prescott Street, London, E1 6HQ, United Kingdom.

Local office:

Bureau Veritas (India) Private Limited (Certification Business)
72 Business Park, Marol Industrial Area, MIDC Cross Road 'C',
Andheri (East), Mumbai - 400 038, India.

Further clarifications regarding the scope of this certificate and the applicability of the
management system requirements may be obtained by consulting the organization.
To check this certificate validity please call +91 22 3274 2000.



Price list:- 01.04.2026

1 “SUNFORD BRAND” CAST CARBON STEEL (ASTM A 216 Gr. WCB) OUT SIDE SCREWE & YOKE TYPE BOLTED BONNET NON ROTATING RISING SPINDLE GATE VALVE FLANGED END HAND WHEEL OPERATED ASA 150 #

Design Standard :- API 600

Body:- ASTM A 216 Gr WCB

Trims:- 13% Cr SS 410 (Trim-1)

Flange to Flange Standard:- ASME B 16.10

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)



Size	1"	1.5"	2"	2.5"	3"	4"	5"	6"	8"	10"	12"
Rate	5755	8855	11355	15555	18555	26555	34555	40955	65555	91155	On req

2 “SUNFORD BRAND” CAST CARBON STEEL (ASTM A 216 Gr. WCB) OUT SIDE SCREWE & YOKE TYPE BOLTED BONNET GLOBE VALVE FLANGED END HANDWHEEL OPERATED ASA 150 #

Design Standard :- BS 1873 / API 6D

Body:- ASTM A 216 Gr WCB

Trims:- 13% Cr SS 410 (Trim-1)

Flange to Flange Standard:- ASME B 16.10

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)



Size	1"	1.5"	2"	2.5"	3"	4"	5"	6"	8"	10"	12" GEAR OPP.
Rate	5555	7655	11355	15355	18155	26955	34655	41155	67955	115655	On req

3 “SUNFORD BRAND” CAST CARBON STEEL (ASTM A 216 Gr. WCB) INVESTMENT CASTING(I.C.) 3/2 WAY GLOBE TYPE PNEUCMATIC CYLINDER OPERATED CONTROL VALVE F/ENDS ASA 150#

Design Standard :- MFG STD

Body:- ASTM A 216 Gr WCB

Trims:- S.S. 304 (TRIM- 2)

Flange to Flange Standard:- MFG STD

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)

Size	Operating	1"	1.5"	2"	2.5"	3"	4"	6"	8"
Rate	Cylinder	14655	21955	26955	35855	39555	65555	113555	171965



4 “SUNFORD BRAND” FORGED STEEL OUT SIDE SCREWE & YOKE TYPE BOLTED BONNET NON ROTATING RISING SPINDLE GATE VALVE SCREWED ENDS/ SOCKET WELD ENDS/ BUTT WELD HAND WHEEL OPERATED ASA 800#

Design Standard :- API 602

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 200 Kg/Cm², SEAT: 157Kg/Cm²

MOC(Body + Trims)	1/2"	3/4"	1"	1.5"	2"
ASTM A 105+13%Cr(Trim- 1)	1855	2055	2795	5555	7555



5 “SUNFORD BRAND” CAST CARBON STEEL (ASTM A 216 Gr. WCB) "Y" TYPE STRAINER WITH BOLTED COVER FLANGED ENDS ASA 150#

Design Standard :- MFG STD

Body:- ASTM A 216 Gr WCB

Trims:- S.S. 304

Flange to Flange Standard:- ASME B 16.10/ DIN 3202 (PART-1)

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm²

Size	1"	1.5"	2"	2.5"	3"	4"	5"	6"	8"	10"
Rate	3955	5355	6955	9555	11955	19655	25555	35155	59655	95655



6 “SUNFORD BRAND” CAST CARBON STEEL (ASTM A 216 Gr. WCB) SWING TYPE NON RETURN VALVE WITH BOLTED COVER FLANGED ENDS ASA 150#

Design Standard :- BS 1868 / API 602

Body:- ASTM A 216 Gr WCB

Trims:- 13% Cr SS 410 (Trim-1)

Flange to Flange Standard:- ASME B 16.10

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)



Size	1"	1.5"	2"	2.5"	3"	4"	5"	6"	8"	10"
Rate	4955	6955	8755	12155	14955	21955	31955	37555	59155	96555

7 “SUNFORD BRAND” CAST CARBON STEEL (ASTM A 216 Gr. WCB) GLOBE TYPE SAFETY VALVE FLANGED END ASA 150

Design Standard :- BS 1873

Body:- ASTM A 216 Gr WCB

Trims:- 13% Cr SS 410 (Trim-1)

Flange to Flange Standard:- ASME B 16.10

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)

MOC(Body + Trims)	1"	1.5"	2"	3"	4"
ASTM A 105+13%Cr(Trim- 1)	On req	13155	15155	25155	33755



8 “SUNFORD BRAND” 2PC/3 PC DESIGN WITH BLOW OUT PROOF STEM FULL BORE HANDLE OPERATED INVESTMENT CASTING(I.C.) BALL VALVE F/ENDS ASA 150 #

Design Standard :- BS 5351/ API 6D

Body:- ASTM A 216 Gr WCB/ CF8/ CF8M/ CF3/ CF3M

Trims:- S.S. 304/ S.S. 316/ S.S. 304 L / S.S. 316L

Flange to Flange Standard:- ASME B 16.10

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)



MOC(Body + Trims)	1/2"	3/4"	1"	1.5"	2"	2.5"	3"	4"	5"	6"	8"
CF8M (S.S. 316)+ CF8M (S.S.316)	2895	3395	4555	7815	11955	19555	23555	38655	58955	82155	On req
CF8 (S.S. 304)+ CF8 (S.S.304)	2395	2795	3595	6415	9655	15355	18755	31655	47655	65155	On req

9 “SUNFORD BRAND” ROTARY ACTUATED(DOUBLE ACTING) 2 PC/3PC DESIGN FULL BORE INVESTMENT CASTING(I.C.) BALL VALVE F/ENDS ASA 150 # WITH BLOW OUT PROOF STEM

Design Standard :- BS 5351/ API 6D

Body:- ASTM A 216 Gr WCB/ CF8/ CF8M/ CF3/ CF3M

Trims:- S.S. 304/ S.S. 316/ S.S. 304 L / S.S. 316L

Flange to Flange Standard:- ASME B 16.10

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)



MOC(Body + Trims)	1/2"	3/4"	1"	1.5"	2"	2.5"	3"	4"	5"	6"
CF8M (S.S. 316)+ CF8M (S.S.316)	8355	9255	11155	16555	21955	33155	39155	67155	149555	175555
CF8 (S.S. 304)+ CF8 (S.S.304)	7655	8355	10355	14655	19755	26650	33955	53955	137555	155655

10 “SUNFORD BRAND” 3 PC DESIGN WITH BLOW OUT PROOF STEM FULL BORE INVESTMENT CASTING(I.C.) HANDLE OPERATED BALL VALVE SCREWED ENDS

Design Standard :- BS 5351/ API 6D
Body:- ASTM A 216 Gr WCB/ CF8/ CF8M/ CF3/ CF3M
Trims:- S.S. 304/ S.S. 316/ S.S. 304 L / S.S. 316L
Pressure Rating :- ASME B 16.34
Inspection & Testing:- API 598
Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²
Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)



MOC(Body + Trims)	1/2"	3/4"	1"	1.5"	2"
CF8M (S.S. 316)+ CF8M (S.S.316)	1555	1995	2595	4955	7455
CF8 (S.S. 304)+ CF8 (S.S.304)	1325	1695	2195	4155	6155

11 “SUNFORD BRAND” ROTARY ACTUATED(DOUBLE ACTING) 3 PC DESIGN FULL BORE INVESTMENT CASTING(I.C.) BALL VALVE SCREWED ENDS WITH BLOW OUT PROOF STEM

Design Standard :- BS 5351/ API 6D
Body:- ASTM A 216 Gr WCB/ CF8/ CF8M/ CF3/ CF3M
Trims:- S.S. 304/ S.S. 316/ S.S. 304 L / S.S. 316L
Pressure Rating :- ASME B 16.34
Inspection & Testing:- API 598
Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²
Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)



MOC(Body + Trims)	1/2"	3/4"	1"
CF8M (S.S. 316)+ CF8M (S.S.316)	7455	8155	10355
CF8 (S.S. 304)+ CF8 (S.S.304)	6855	7585	9555

12 "SUNFORD BRAND" 1 PC DESIGN WITH BLOW OUT PROOF STEM FULL BORE HANDLE OPERATED INVESTMENT CASTING(I.C.) BALL VALVE SCREWED

Design Standard :- BS 5351/ API 6D

Body:- ASTM A 216 Gr WCB/ CF8/ CF8M/ CF3/ CF3M

Trims:- S.S. 304/ S.S. 316/ S.S. 304 L / S.S. 316L

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)



MOC(Body + Trims)	1/2"	3/4"	1"	1.5"	2"
CF8M (S.S. 316)+ CF8M (S.S.316)	1115	1455	2155	3955	5555
CF8 (S.S. 304)+ CF8 (S.S.304)	975	1255	1795	3255	4555

13 SANDWICH TYPE DISC CHECK VALVE(NRV)

MOC	15MM	20MM	25MM	40MM	50MM	65MM	80MM	100MM	125MM	150MM	200MM
S.S. 304(CF8)	995	1155	1455	2455	3255	4195	5655	8355	16955	21155	35655



14 "SUNFORD BRAND" CAST CARBON STEEL (ASTM A 216 Gr. WCB) INVESTMENT CASTING(I.C.) 2/2 WAY GLOBE TYPE PNEUMATIC CYLINDER OPERATED CONTROL VALVE F/ENDS ASA 150#

Design Standard :- MFG STD

Body:- ASTM A 216 Gr WCB

Seat:- Virgin PTFE, CFT, GFT

Trims:- S.S. 304 (TRIM- 2)

Flange to Flange Standard:- MFG STD

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)

Size	Operating	1"	1.5"	2"	2.5"	3"
Rate	Cylinder	8195	10355	17955	28955	30655



15 "SUNFORD BRAND" S.S. 304 (CF8) INVESTMENT CASTING(I.C.) "Y" TYPE PNEUMATIC CYLINDER OPERATED CONTROL VALVE FLANGED ENDS ASA 150#

Body & Trims- S.S 304

Seat :- Virgin PTFE / CFT/ GFT

Flange to Flange Standard:- ASME B 16.10/ DIN 3202 (PART-1)

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Size	1"	1.5"	2"
Rate	8355	9855	12355



16 "SUNFORD BRAND" S.S. 304 (CF8) INVESTMENT CASTING(I.C.) "Y" TYPE PNEUMATIC (AIR) OPERATED CONTROL VALVE FLANGED ENDS ASA 150#

Body & Trims- S.S 304

Seat :- Virgin PTFE / CFT/ GFT

Flange to Flange Standard:- ASME B 16.10/ DIN 3202 (PART-1)

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Size	1/2"	3/4"	1"	1.5"	2"
Rate	5255	5895	6155	8755	10655



17 "SUNFORD BRAND" S.S. 304 (CF8) INVESTMENT CASTING(I.C.) "Y" TYPE PNEUMATIC (AIR) OPERATED CONTROL VALVE SCREWEDED ENDS

Body & Trims- S.S 304

Seat :- Virgin PTFE / CFT/ GFT

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Size	1/2"	3/4"	1"	1.5"	2"
Rate	4155	5155	5755	7355	8755



18 "SUNFORD BRAND" NON IBR FORGED STEEL (ASTM A 216 Gr. WCB) PISTON VALVE SCREWED ENDS/ SOCKET WELD ENDS 800#

Body:- ASTM A 105

Trims:- S.S. 410

Flange to Flange Standard:- ASME B 16.10

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 78Kg/Cm², SEAT: 59Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)

Size	15mm	20mm	25mm	40mm
Rate	3195	3355	5355	10655

19 "SUNFORD BRAND" NON IBR CAST CARBON STEEL (ASTM A 216 Gr. WCB) PISTON VALVE F/ENDS 150#

Body:- ASTM A 216 Gr WCB

Trims:- S.S. 410

Flange to Flange Standard:- ASME B 16.10

Pressure Rating :- ASME B 16.34

Inspection & Testing:- API 598

Hydrolic Test Pressure :- BODY: 32Kg/Cm², SEAT: 23Kg/Cm²

Pneumatic Test:- Air Pressure :- 8 Kg/Cm² (Seat)

Size	15mm	20mm	25mm	40mm	50mm
Rate	4195	5155	5755	11655	16155

20 “SUNFORD BRAND” WAFER TYPE BUTTERFLY VALVE SUITABLE FOR 150#

Design Standard :- BS 5155/ API 609/ EN 593/ IS 13095

Flange to Flange Standard:- ASME B 16.5

Inspection & Testing:- API 598

CAST IRON BUTTERFLY VALVE, NITRILE/EPDM RUBBER MOULDED SEAT , LEAVER OPERATED

MOC(Body + Trims)	40MM	50MM	65MM	80MM	100MM	125MM	150MM	200MM	250MM	300MM
S.S. 304(CF8) DISC	1955	2355	2655	3155	4355	6155	7555	15155	19655	29655

21 “SUNFORD BRAND” ROTARY ACTUATED (DOUBLE ACTING)CAST IRON BUTTERFLY VALVE, NITRILE/EPDM RUBBER MOULDED SEAT

MOC(Body + Trims)	40MM	50MM	65MM	80MM	100MM	125MM	150MM	200MM
S.S. 304(CF8) DISC	7355	8195	10555	11655	14655	18355	23955	37155

22 “SUNFORD BRAND” SPHERICAL DISC (DOUBLE OFFSET)INVESTMENT CASTING(I.C.) WAFER TYPE TEFFLON SEATED BUTTERFLY VALVE LEVER OPERATED

MOC(Body + Trims)	40MM	50MM	65MM	80MM	100MM	125MM	150MM	200MM
S.S.304(CF8)+ S.S.304(CF8)	5755	6555	8555	10855	13955	18155	24155	33955
S.S.316(CF8M)+S.S.316(CF8M)	6555	7355	9955	13155	15655	21555	28555	39655

23 “SUNFORD BRAND” ROTARY ACTUATED(DOUBLE ACTING) SPHERICAL DISC (DOUBLE OFFSET) INVESTMENT CASTING(I.C.)WAFER TYPE TEFFLON SEATED BUTTERFLY VALVE

MOC(Body + Trims)	40MM	50MM	65MM	80MM	100MM	125MM	150MM	200MM
S.S.304(CF8)+ S.S.304(CF8)	12155	13155	17155	19655	24155	30555	41955	51955
S.S.316(CF8M)+S.S.316(CF8M)	12555	14155	18555	21955	26155	33955	46955	61955



TERMS & CONDITIONS:

1	VALIDITY	15 DAYS
2	PRICES	PRICES QUOTED ARE EX-WORKS ,SURAT PACKING AND FORWARDING WILL BE EXTRA AT 3% FREIGHT/INSURANCE/OCTROI SHALL BE EXTRA AT ACTUALS TO YOUR ACCOUNT
3	TAXES	GST: 18% OR ACTUALS AT THE TIME OF DELIVERY. GST IS APPLICABLE ON TOTAL OF P&F+FREIGHT+INSURANCE+IF ANY WITH PRODUCT VALUE.
4	PAYMENT TERMS	30% ADVANCE AGAINST ORDER & BALANCE AGAINST PROFORMA INVOICE BEFORE DISPATCH
5	DELIVERY	F.O.R. OUR WORKS,EX-WORKS SURAT FROM THE DATE OF RECEIPT OF YOUR FIRM TECHNICALLY AND COMMERCIALY CLEAR ORDER.
6	INSPECTION	THIRD PARTY INSPECTION WILL BE ACCEPTED AND WILL COST 2% EXTRA OR ELSE PARTY INSPECTION BEFORE DELIVERY
7	GARANTEE	THE MATERIAL OFFERED ARE GUARANTEED AGAINST ANY MANUFACTURING DEFECTS FOR A PERIOD OF 12 MONTHS FROM THE DATE OF COMMISSIONING OR 18 MONTHS FROM THE DATE OF SUPPLY, WHICHEVER IS EARLIER, SUBJECT TO NORMAL WEAR AND TEAR
8	JURIDICTION	ANY DISPUTES ARE SUBJECTED TO SURAT JURIDICTION