



100

Performance

89

Accessibility

96

Best
Practices

90

SEO

100

Performance

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)



0–49

50–89

90–100

HRnet
View Current Employees
Create Employee

First Name:
Last Name:
Date of Birth:
Start Date:
Address:
Street:
City:
State:
Zip Code:
Department:

METRICS

[Expand view](#)

First Contentful Paint

0.6 s

Largest Contentful Paint

0.6 s

Total Blocking Time

0 ms

Cumulative Layout Shift

0.005

Speed Index

0.6 s



Show audits relevant to: All [FCP](#) [LCP](#) [CLS](#)

INSIGHTS

▲ Render-blocking requests — Est savings of 450 ms



Requests are blocking the page's initial render, which may delay LCP. [Deferring or inlining](#) can move these network requests out of the critical path. FCP LCP Unscored

☒ Show 3rd-party resources (5)

URL	Transfer size	Duration
Cloudflare CDN Cdn	4.1 KiB	450 ms
...0.9.1/jquery.modal.min.js (cdnjs.cloudflare.com)	2.0 KiB	230 ms
...0.9.1/jquery.modal.min.css (cdnjs.cloudflare.com)	2.1 KiB	230 ms
Google CDN Cdn	30.4 KiB	300 ms
...3.5.1/jquery.min.js (ajax.googleapis.com)	30.4 KiB	300 ms
jQuery CDN Cdn	130.0 KiB	450 ms
...1.12.1/jquery-ui.js (code.jquery.com)	121.8 KiB	200 ms
...base/jquery-ui.css (code.jquery.com)	8.2 KiB	250 ms
127.0.0.1 First Party	84.6 KiB	690 ms
/HRnet/app.js (127.0.0.1)	6.0 KiB	120 ms
/HRnet/app.css (127.0.0.1)	0.6 KiB	80 ms
/HRnet/jquery.datetimepicker.css (127.0.0.1)	18.3 KiB	160 ms
/HRnet/jquery.datetimepicker.full.min.js (127.0.0.1)	59.7 KiB	320 ms

▲ Legacy JavaScript — Est savings of 27 KiB



Polyfills and transforms enable older browsers to use new JavaScript features. However, many aren't necessary for modern browsers. Consider modifying your JavaScript build process to not transpile [Baseline](#) features, unless you

know that you must support older browsers. [Learn why most sites can deploy ES6+ code without transpiling](#) LCP Unscored

URL	Wasted bytes
127.0.0.1 First Party	26.5 KiB
/HRnet/jquery.datetimepicker.full.min.js (127.0.0.1)	26.5 KiB
jquery.datetimepicker.full.min.js:1 Array.prototype.indexOf	

▲ Network dependency tree

^

[Avoid chaining critical requests](#) by reducing the length of chains, reducing the download size of resources or deferring the download of unnecessary resources to improve page load. LCP Unscored

Maximum critical path latency: **61 ms**

Initial Navigation

- /HRnet/index.html (127.0.0.1) - **30 ms**, 4.33 KiB
- ...0.9.1/jquery.modal.min.js (cdnjs.cloudflare.com) - **61 ms**, 1.98 KiB
- ...0.9.1/jquery.modal.min.css (cdnjs.cloudflare.com) - **61 ms**, 2.11 KiB
- ...3.5.1/jquery.min.js (ajax.googleapis.com) - **54 ms**, 30.37 KiB
- ...1.12.1/jquery-ui.js (code.jquery.com) - **46 ms**, 121.77 KiB
- ...base/jquery-ui.css (code.jquery.com) - **46 ms**, 8.24 KiB
- /HRnet/app.js (127.0.0.1) - **38 ms**, 6.05 KiB
- /HRnet/app.css (127.0.0.1) - **37 ms**, 0.59 KiB
- /HRnet/jquery.datetimepicker.css (127.0.0.1) - **37 ms**, 18.28 KiB
- /HRnet/jquery.datetimepicker.full.min.js (127.0.0.1) - **37 ms**, 59.70 KiB

Preconnected origins

[preconnect](#) hints help the browser establish a connection earlier in the page load, saving time when the first request for that origin is made. The following are the origins that the page preconnected to.

no origins were preconnected

Preconnect candidates

Add [preconnect](#) hints to your most important origins, but try to use no more than 4.
No additional origins are good candidates for preconnecting



Your first network request is the most important. [Reduce its latency](#) by avoiding redirects, ensuring a fast server response and enabling text compression. FCP LCP Unscored

Avoids redirects


Server responds quickly (observed 3 ms)

No compression applied

Layout shift culprits



Layout shifts occur when elements move absent any user interaction. [Investigate the causes of layout shifts](#), such as elements being added, removed or their fonts changing as the page loads. CLS Unscored

Element	Layout shift score
Total	0.005
 form#create-employee	0.005

LCP breakdown



Each [sub-part has specific improvement strategies](#). Ideally, most of the LCP time should be spent on loading the resources, not within delays. LCP Unscored

Sub-part	Duration
Time to First Byte	0 ms
Element render delay	130 ms
 h2	

Third parties



Third-party code can significantly impact load performance. [Reduce and defer loading of third-party code](#) to prioritise your page's content. Unscored

Third party	Transfer size	Main thread time
Google CDN Cdn	30 KiB	13 ms
...3.5.1/jquery.min.js (ajax.googleapis.com)	30 KiB	13 ms
jQuery CDN Cdn	137 KiB	11 ms
...1.12.1/jquery-ui.js (code.jquery.com)	122 KiB	11 ms
...base/jquery-ui.css (code.jquery.com)	8 KiB	0 ms
...images/ui-icons_777777_256x240.png (code.jquery.com)	7 KiB	0 ms
Cloudflare CDN Cdn	4 KiB	0 ms
...0.9.1/jquery.modal.min.js (cdnjs.cloudflare.com)	2 KiB	0 ms
...0.9.1/jquery.modal.min.css (cdnjs.cloudflare.com)	2 KiB	0 ms

These insights are also available in the Chrome DevTools performance panel – [record a trace](#) to view more detailed information.

DIAGNOSTICS

▲

Minify JavaScript — Est savings of 29 KiB

^

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript.](#) FCP

LCP

Unscored

☒

Show 3rd-party resources (1)

URL	Transfer size	Est savings
jQuery CDN Cdn	73.6 KiB	26.5 KiB
...1.12.1/jquery-ui.js (code.jquery.com)	73.6 KiB	26.5 KiB
127.0.0.1 First Party	5.7 KiB	2.1 KiB
/HRnet/app.js (127.0.0.1)	5.7 KiB	2.1 KiB

▲

Reduce unused JavaScript — Est savings of 81 KiB

^

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn how to reduce unused JavaScript.](#) FCP LCP Unscored

☒

Show 3rd-party resources (1)

URL	Transfer size	Est savings
jQuery CDN Cdn	73.6 KiB	59.7 KiB
...1.12.1/jquery-ui.js (code.jquery.com)	73.6 KiB	59.7 KiB
127.0.0.1 First Party	56.1 KiB	20.9 KiB
/HRnet/jquery.datetimepicker.full.min.js (127.0.0.1)	56.1 KiB	20.9 KiB

Reduce unused CSS — Est savings of 17 KiB

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn how to reduce unused CSS.](#) FCP LCP Unscored

URL	Transfer size	Est savings
127.0.0.1 First Party	18.0 KiB	17.4 KiB
/HRnet/jquery.datetimepicker.css (127.0.0.1)	18.0 KiB	17.4 KiB

More information about the performance of your application. These numbers don't [directly affect](#) the performance score.

PASSED AUDITS (19) Hide

Use efficient cache lifetimes

A long cache lifetime can speed up repeat visits to your page. [Learn more about caching.](#) FCP LCP Unscored

Optimise DOM size

A large DOM can increase the duration of style calculations and layout reflows, impacting page responsiveness. A large DOM will also increase memory usage. [Learn how to avoid an excessive DOM size.](#) Unscored

Statistic	Element	Value
Total elements		609
DOM depth	div	9
Most children	div	101

Duplicated JavaScript



Remove large, [duplicate JavaScript modules](#) from bundles to reduce unnecessary bytes consumed by network activity. FCP LCP Unscored

Font display



Consider setting [font-display](#) to swap or optional to ensure that text is consistently visible. swap can be further optimised to mitigate layout shifts with [font metric overrides](#). Unscored

Forced reflow



A forced reflow occurs when JavaScript queries geometric properties (such as `offsetWidth`) after styles have been invalidated by a change to the DOM state. This can result in poor performance. Learn more about [forced reflows](#) and possible mitigations. Unscored

Improve image delivery



Reducing the download time of images can improve the perceived load time of the page and LCP. [Learn more about optimising image size](#) FCP LCP Unscored

☐ INP breakdown



Start investigating [how to improve INP](#) by looking at the longest subpart. Unscored

☐ LCP request discovery



[Optimise LCP](#) by making the LCP image discoverable from the HTML immediately, and avoiding lazy loading Unscored

Modern HTTP



HTTP/2 and HTTP/3 offer many benefits over HTTP/1.1, such as multiplexing. [Learn more about using modern HTTP](#). FCP LCP Unscored

Optimise viewport for mobile



Tap interactions may be [delayed by up to 300 ms](#) if the viewport is not optimised for mobile. Unscored

Minify CSS



Minifying CSS files can reduce network payload sizes. [Learn how to minify CSS](#). FCP LCP Unscored



Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes.](#) Unscored

☒ Show 3rd-party resources (6)

URL	Transfer size
jQuery CDN Cdn	137.0 KiB
...1.12.1/jquery-ui.js (code.jquery.com)	121.8 KiB
...base/jquery-ui.css (code.jquery.com)	8.2 KiB
...images/ui-icons_777777_256x240.png (code.jquery.com)	7.0 KiB
127.0.0.1 First Party	88.3 KiB
/HRnet/jquery.datetimepicker.full.min.js (127.0.0.1)	59.7 KiB
/HRnet/jquery.datetimepicker.css (127.0.0.1)	18.3 KiB
/HRnet/app.js (127.0.0.1)	6.0 KiB
/HRnet/index.html (127.0.0.1)	4.3 KiB
Google CDN Cdn	30.4 KiB
...3.5.1/jquery.min.js (ajax.googleapis.com)	30.4 KiB
Cloudflare CDN Cdn	4.1 KiB
...0.9.1/jquery.modal.min.css (cdnjs.cloudflare.com)	2.1 KiB
...0.9.1/jquery.modal.min.js (cdnjs.cloudflare.com)	2.0 KiB

○ User Timing marks and measures



Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more about User Timing marks.](#) Unscored

○ JavaScript execution time



Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads

helps with this. [Learn how to reduce Javascript execution time.](#) TBT Unscored

Minimises main-thread work — 0.1 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimise main-thread work](#) TBT Unscored

Category	Time Spent
Other	40 ms
Script Evaluation	27 ms
Style & Layout	20 ms
Script Parsing & Compilation	11 ms
Parse HTML & CSS	3 ms
Rendering	1 ms

☐ Avoid long main-thread tasks

Lists the longest tasks on the main thread – useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#) TBT Unscored

☐ Avoid non-composited animations

Animations that are not composited can be poor, slow and increase CLS. [Learn how to avoid non-composited animations](#) CLS Unscored

Image elements have explicit **width** and **height**

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn how to set image dimensions](#) CLS Unscored

Page didn't prevent back-forward cache restoration

Many navigations are performed by going back to a previous page, or forwards again. The back-forward cache (bfcache) can speed up these return navigations. [Learn more about the bfcache](#) Unscored

Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

ARIA

▲ ARIA input fields do not have accessible names



When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels](#).

Failing elements



span#state-button.ui-selectmenu-button.ui-selectmenu-button-closed.ui-corner-all.ui-button....



span#department-button.ui-selectmenu-button.ui-selectmenu-button-closed.ui-corner-all.ui-...

These are opportunities to improve the usage of ARIA in your application which may enhance the experience for users of assistive technology, such as a screen reader.

INTERNATIONALISATION AND LOCALISATION

▲ `<html>` element does not have a `[lang]` attribute



If a page doesn't specify a `lang` attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more about the `lang` attribute](#).

Failing elements



html

These are opportunities to improve the interpretation of your content by users in different locales.


BEST PRACTICES

- ▲ Document does not have a main landmark.



One main landmark helps screen reader users navigate a web page. [Learn more about landmarks.](#)

Failing elements



html

These items highlight common accessibility best practices.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

- ☐ Interactive controls are keyboard focusable



Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable.](#) Unscored

- ☐ Interactive elements indicate their purpose and state



Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints.](#) Unscored

- ☐ The page has a logical tab order



Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering.](#) Unscored

- ☐ Visual order on the page follows DOM order



DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering.](#) Unscored

☐ User focus is not accidentally trapped in a region ^

A user can tab into and out of any control or region without accidentally trapping their focus. [Learn how to avoid focus traps.](#) Unscored

☐ The user's focus is directed to new content added to the page ^

If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn how to direct focus to new content.](#) Unscored

☐ HTML5 landmark elements are used to improve navigation ^

Landmark elements (`<main>`, `<nav>`, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more about landmark elements.](#) Unscored

☐ Offscreen content is hidden from assistive technology ^

Offscreen content is hidden with `display: none` or `aria-hidden=true`. [Learn how to properly hide offscreen content.](#) Unscored

☐ Custom controls have associated labels ^

Custom interactive controls have associated labels, provided by `aria-label` or `aria-labelledby`. [Learn more about custom controls and labels.](#) Unscored

☐ Custom controls have ARIA roles ^

Custom interactive controls have appropriate ARIA roles. [Learn how to add roles to custom controls.](#) Unscored

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review](#).

PASSED AUDITS (18)

Hide

`[aria-*)` attributes match their roles ^

Each ARIA role supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. [Learn how to match ARIA attributes to their roles.](#)

`[aria-hidden="true"]` is not present on the document `<body>` ^

Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. [Learn how `aria-hidden` affects the document body.](#)

`[role]`s have all required `[aria-*)` attributes



Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#)

`[role]` values are valid



ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more about valid ARIA roles.](#)

`[aria-*)` attributes have valid values



Assistive technologies, such as screen readers, can't interpret ARIA attributes with invalid values. [Learn more about valid values for ARIA attributes.](#)

`[aria-*)` attributes are valid and not misspelled



Assistive technologies, such as screen readers, can't interpret ARIA attributes with invalid names. [Learn more about valid ARIA attributes.](#)

Buttons have an accessible name



When a button doesn't have an accessible name, screen readers announce it as 'button', making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible.](#)

Form elements have associated labels



Labels ensure that form controls are announced properly by assistive technologies, such as screen readers. [Learn more about form element labels.](#)

ARIA attributes are used as specified for the element's role



Some ARIA attributes are only allowed on an element under certain conditions. [Learn more about conditional ARIA attributes.](#)

`[aria-hidden="true"]` elements do not contain focusable descendents



Focusable descendants within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn how `aria-hidden` affects focusable elements.](#)

Elements use only permitted ARIA attributes



Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. [Learn more about prohibited ARIA roles.](#)

Background and foreground colours have a sufficient contrast ratio



Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient colour contrast.](#)

Document has a `<title>` element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles.](#)

Links have a discernible name



Link text (and alternative text for images, when used as links) that is discernible, unique and focusable improves the navigation experience for screen reader users. [Learn how to make links accessible.](#)

No element has a `[tabindex]` value greater than 0



A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more about the tabindex attribute.](#)

Touch targets have sufficient size and spacing.



Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. [Learn more about touch targets.](#)

Heading elements appear in a sequentially-descending order



Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more about heading order.](#)

Deprecated ARIA roles were not used



Deprecated ARIA roles may not be processed correctly by assistive technology. [Learn more about deprecated ARIA roles.](#)

NOT APPLICABLE (42)

Hide

☐ `[accesskey]` values are unique



Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more about access keys.](#) Unscored

- ☐ [button](#), [link](#) and [menuitem](#) elements have accessible names



When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to make command elements more accessible.](#) Unscored

- ☐ Elements with `role="dialog"` or `role="alertdialog"` have accessible names.



ARIA dialogue elements without accessible names may prevent screen reader users from discerning the purpose of these elements. [Learn how to make ARIA dialog elements more accessible.](#) Unscored

- ☐ ARIA [meter](#) elements have accessible names



When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#) Unscored

- ☐ ARIA [progressbar](#) elements have accessible names



When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#) Unscored

- ☐ Elements with an ARIA [\[role\]](#) that require children to contain a specific [\[role\]](#) have all required children.



Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements.](#) Unscored

- ☐ [\[role\]](#)s are contained by their required parent element



Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more about ARIA roles and required parent element.](#) Unscored

- ☐ Elements with the `role=text` attribute do not have focusable descendents.



Adding `role=text` around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. [Learn more about the role=text attribute.](#) Unscored

- ☐ ARIA toggle fields have accessible names



When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about toggle fields.](#) Unscored

- ☐ ARIA [tooltip](#) elements have accessible names



When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name tooltip elements.](#) Unscored

☐ ARIA `treeitem` elements have accessible names ^

When a `treeitem` element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about labelling `treeitem` elements.](#) Unscored

☐ The page contains a heading, skip link or landmark region ^

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more about bypass blocks.](#) Unscored

☐ `<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn how to structure definition lists correctly.](#) Unscored

☐ Definition list items are wrapped in `<dl>` elements ^

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. [Learn how to structure definition lists correctly.](#) Unscored

☐ ARIA IDs are unique ^

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#) Unscored

☐ No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies, like screen readers, which use either the first, the last or all of the labels. [Learn how to use form labels.](#) Unscored

☐ `<frame>` or `<iframe>` elements have a title ^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#) Unscored

☐ `<html>` element has a valid value for its `[lang]` attribute ^

Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn how to use the `lang` attribute.](#) Unscored

☐ `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute. ^

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the `lang` attribute.](#) Unscored

○ Image elements have `[alt]` attributes ^

Informative elements should aim for short, descriptive alternative text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#) Unscored

○ Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users to understand the purpose of the input button. [Learn more about input buttons.](#) Unscored

○ `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#) Unscored

○ Links are distinguishable without relying on colour. ^

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#) Unscored

○ Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#) Unscored

○ List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements ^

Screen readers require list items (`<li>`) to be contained within a parent `<ul>`, `<ol>` or `<menu>` to be announced properly. [Learn more about proper list structure.](#) Unscored

○ The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#) Unscored

○ `[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5. ^

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more about the viewport meta tag.](#) Unscored

○ `<object>` elements have alternative text ^

Screen readers cannot translate non-text content. Adding alternative text to `<object>` elements helps screen readers convey meaning to users. [Learn more about alt text for object elements.](#) Unscored

-
- ☐ Select elements have associated label elements. ^

Form elements without effective labels can create frustrating experiences for screen reader users. [Learn more about the select element.](#) Unscored

-
- ☐ Skip links are focusable. ^

Including a skip link can help users skip to the main content to save time. [Learn more about skip links.](#) Unscored

-
- ☐ Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table. ^

Screen readers have features to make navigating tables easier. Ensuring that `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more about the headers attribute.](#) Unscored

-
- ☐ `<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring that table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more about table headers.](#) Unscored

-
- ☐ `[lang]` attributes have a valid value ^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn how to use the lang attribute.](#) Unscored

-
- ☐ `<video>` elements contain a `<track>` element with `[kind="captions"]` ^

When a video provides a caption it is easier for deaf and hearing-impaired users to access its information. [Learn more about video captions.](#) Unscored

-
- ☐ `autocomplete` attributes are used correctly ^

The `autocomplete` attribute values must be valid and correctly applied for screen readers to function correctly. [Learn more about valid autocomplete values.](#) Unscored

-
- ☐ Elements with `role="none"` or `role="presentation"` do not have conflicts ^

There are certain cases where the semantic role of an element with `role="none"` or `role="presentation"` does not resolve to none or presentation. To ensure that the element remains removed from the accessibility tree, you should not add any global ARIA attributes to the element or make it focusable. [Learn more about presentation role conflict.](#) Unscored

-
- ☐ SVG elements with an `img` role have an accessible text alternative ^
-

Ensures that SVG elements with an `img`, `graphics-document` or `graphics-symbol` role have an accessible text alternative. [Learn more about SVG alt text.](#) Unscored

- Tables have different content in the `summary` attribute and `<caption>`. ^

The `summary` attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#) Unscored

- All heading elements contain content. ^

A heading with no content or inaccessible text prevents screen reader users from accessing information on the page's structure. [Learn more about headings.](#) Unscored

- Uses ARIA roles only on compatible elements ^

Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. [Learn more about ARIA roles.](#) Unscored

- Image elements do not have `[alt]` attributes that are redundant text. ^

Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. [Learn more about the alt attribute.](#) Unscored

- Identical links have the same purpose. ^

Links with the same destination should have the same description, to help users understand the link's purpose and decide whether to follow it. [Learn more about identical links.](#) Unscored

96

Best Practices

BROWSER COMPATIBILITY

- ▲ Page lacks the HTML doctype, thus triggering quirks mode **Document must contain a doctype** ^

Specifying a DOCTYPE prevents the browser from switching to quirks mode. [Learn more about the doctype declaration.](#)

- Baseline features ^

Lists web features used on the page and their Baseline status as of 2026-07-15. [Learn more about Baseline.](#)

Unscored

☒ Show 3rd-party resources (3)

Web features	Baseline status	Source
127.0.0.1 First Party		
page-visibility-state	Limited Availability	index.html:2
long-animation-frames	Limited Availability	index.html:2
layout-instability	Limited Availability	index.html:2
requestidlecallback	Limited Availability	index.html:2
weak-references	Widely Available (2021-04-26)	index.html:2
nullish-coalescing	Widely Available (2020-09-16)	index.html:1
aborting	Widely Available (2019-03-25)	index.html:2
flexbox	Widely Available (2015-09-30)	index.html:-1
Google CDN Cdn		
background-clip-text	Limited Availability	jquery.min.js:2
slot	Widely Available (2020-01-15)	jquery.min.js:2
text-indent	Widely Available (2015-07-29)	jquery.min.js:2

TRUST AND SAFETY

☐ Ensure CSP is effective against XSS attacks

^

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn how to use a CSP to prevent XSS](#)

Unscored

Description	Directive	Severity
No CSP found in enforcement mode		High

○ Use a strong HSTS policy ^

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. [Learn more about using a strong HSTS policy.](#) Unscored

Description	Directive	Severity
No HSTS header found		High

○ Ensure proper origin isolation with COOP ^

The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. [Learn more about deploying the COOP header.](#) Unscored

Description	Directive	Severity
No COOP header found		High

○ Mitigate clickjacking with XFO or CSP ^

The X-Frame-Options (XFO) header or the frame-ancestors directive in the Content-Security-Policy (CSP) header control where a page can be embedded. These can mitigate clickjacking attacks by blocking some or all sites from embedding the page. [Learn more about mitigating clickjacking.](#) Unscored

Description	Severity
No frame control policy found	High

○ Mitigate DOM-based XSS with trusted types ^

The require-trusted-types-for directive in the Content-Security-Policy (CSP) header instructs user agents to control the data passed to DOM XSS sink functions. [Learn more about mitigating DOM-based XSS with trusted types.](#) Unscored

Description	Severity
No `Content-Security-Policy` header with trusted types directive found	High

○ Detected JavaScript libraries



All front-end JavaScript libraries detected on the page. [Learn more about this JavaScript library detection diagnostic audit.](#) Unscored

Name	Version
jQuery	3.5.1
jQuery UI	1.12.1

PASSED AUDITS (12)

Hide

Uses HTTPS



All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding [mixed content](#), where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more about HTTPS.](#)

Avoids deprecated APIs



Deprecated APIs will eventually be removed from the browser. [Learn more about deprecated APIs.](#)

Avoids third-party cookies



Third-party cookies may be blocked in some contexts. [Learn more about preparing for third-party cookie restrictions.](#)

Allows users to paste into input fields



Preventing input pasting is bad practice for the UX and weakens security by blocking password managers. [Learn more about user-friendly input fields.](#)

Avoids requesting the geolocation permission on page load



Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. [Learn more about the geolocation permission.](#) Also consider using the [<geolocation> element](#).

Avoids requesting the notification permission on page load



Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the

request to user gestures instead. [Learn more about responsibly getting permission for notifications.](#)

Displays images with correct aspect ratio



Image display dimensions should match natural aspect ratio. [Learn more about image aspect ratio.](#)

Serves images with appropriate resolution



Image natural dimensions should be proportional to the display size and the pixel ratio to maximise image clarity. [Learn how to provide responsive images.](#)

Properly defines charset



A character encoding declaration is required. It can be done with a <meta> tag in the first 1,024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more about declaring the character encoding.](#)

No browser errors logged to the console



Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more about this errors in console diagnostic audit](#)

No issues in the [Issues](#) panel in Chrome DevTools



Issues logged to the Issues panel in Chrome DevTools indicate unresolved problems. They can come from network request failures, insufficient security controls and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Page has valid source maps



Source maps translate minified code to the original source code. This helps developers to debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps.](#) Unscored

NOT APPLICABLE (1)

Hide

☐ Redirects HTTP traffic to HTTPS



Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. [Learn more.](#) Unscored

90

SEO

These checks ensure that your page is following basic search engine optimisation advice. There are many additional factors that Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more about Google Search essentials](#).

CONTENT BEST PRACTICES

▲ Document does not have a meta description



Meta descriptions may be included in search results to concisely summarise page content. [Learn more about the meta description](#).

Format your HTML in a way that enables crawlers to better understand your app's content.

ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

○ Structured data is valid



Run the [Structured Data Testing Tool](#) to validate structured data. [Learn more about structured data](#). Unscored

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (6)

Hide

Page isn't blocked from indexing



Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more about crawler directives](#).

Document has a `<title>` element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles](#).

Page has successful HTTP status code



Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more about HTTP status codes](#).

Links have descriptive text



Descriptive link text helps search engines understand your content. [Learn how to make links more accessible.](#)

Links are crawlable



Search engines may use href attributes on links to crawl websites. Ensure that the href attribute of anchor elements links to an appropriate destination so that more pages of the site can be discovered. [Learn how to make links crawlable](#)

Document has a valid hreflang



hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more about hreflang.](#)

NOT APPLICABLE (3)

Hide

○ robots.txt is valid



If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. [Learn more about robots.txt.](#) Unscored

○ Image elements have [alt] attributes



Informative elements should aim for short, descriptive alternative text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#) Unscored

○ Document has a valid rel=canonical



Canonical links suggest which URL to show in search results. [Learn more about canonical links.](#) Unscored



Captured at 25 Sept 2026,
12:23 CEST



Initial page load



Emulated desktop with
Lighthouse 13.4.1



Custom throttling



Single-page session



Using Chromium 153.0.0.0
with devtools