

AI Lab - Session 5

Model-Free Reinforcement Learning

Riccardo Sarteà

University of Verona
Department of Computer Science

June 7th 2019



UNIVERSITÀ
di **VERONA**

Dipartimento
di **INFORMATICA**

Start the previously installed (Session 1) conda environment *ai-lab*

Listing 1: Upgrade and spin up

```
cd ai-lab  
git pull  
conda activate ai-lab  
jupyter notebook
```

There is no specific tutorial for this session since there is nothing new with respect to what you have already used before

Assignments

- Your assignments for this session are at: *session5/session5_mfml.ipynb*. You will be required to implement Q-Learning and SARSA algorithms
- In the following you can find the pseudocodes

Q-Learning

Input: *environment* $[A, S]$, *problem*, *episodes*, α, γ , *expl_func*, *expl_param*

Output: *policy*, *rewards*, *lengths*

```
1:  $\forall a \in A, \forall s \in S$  initialize  $Q(s, a)$  arbitrarily
2:  $rewards, lengths \leftarrow [0, \dots, 0]$  ▷ Null vectors of length episodes
3: for  $i \leftarrow 0$  to episodes do
4:   Initialize  $s$ 
5:   repeat
6:      $a \leftarrow \text{EXPL\_FUNC}(Q, s, \text{expl\_param})$ 
7:      $s', r \leftarrow \text{take action } a \text{ from state } s$  ▷ Act and observe
8:      $Q(s, a) \leftarrow Q(s, a) + \alpha(R + \gamma \max_{a \in A_s} Q(s', a) - Q(s, a))$  ▷ TD
9:      $s \leftarrow s'$ 
10:  until  $s$  is terminal
11:  Update rewards, lengths
12:  $\pi \leftarrow [0, \dots, 0]$  ▷ Null vector of length  $|S|$ 
13: for each  $s$  in  $S$  do ▷ Extract policy
14:    $\pi_s \leftarrow \operatorname{argmax}_{a \in A_s} Q(s, a)$ 
15: return  $\pi, rewards, lengths$ 
```

SARSA

Input: *environment* $[A, S]$, *problem*, *episodes*, α , γ , *expl_func*, *expl_param*

Output: *policy*, *rewards*, *lengths*

```
1:  $\forall a \in A, \forall s \in S$  initialize  $Q(s, a)$  arbitrarily
2:  $rewards, lengths \leftarrow [0, \dots, 0]$  ▷ Null vectors of length episodes
3: for  $i \leftarrow 0$  to episodes do
4:   Initialize  $s$ 
5:    $a \leftarrow \text{EXPL\_FUNC}(Q, s, \text{expl\_param})$ 
6:   repeat
7:      $s', r \leftarrow$  take action  $a$  from state  $s$  ▷ Act and observe
8:      $a' \leftarrow \text{EXPL\_FUNC}(Q, s', \text{expl\_param})$ 
9:      $Q(s, a) \leftarrow Q(s, a) + \alpha(R + \gamma Q(s', a') - Q(s, a))$  ▷ TD
10:     $s \leftarrow s'$ 
11:     $a' \leftarrow a$ 
12:   until  $s$  is terminal
13:   Update rewards, lengths
14:  $\pi \leftarrow [0, \dots, 0]$  ▷ Null vector of length  $|S|$ 
15: for each  $s$  in  $S$  do ▷ Extract policy
16:    $\pi_s \leftarrow \underset{a \in A_s}{\text{argmax}} Q(s, a)$ 
17: return  $\pi, rewards, lengths$ 
```