

Outline


Classic networks:

- LeNet-5 ←
- AlexNet ←
- VGG ←

ResNet (152)

Inception


LeNet - 5



[LeCun et al., 1998. Gradient-based learning applied to document recognition]

Andrew Ng

AlexNet



- Similar to LeNet, but much bigger.
 - ReLU
 - Multiple GPUs.
 - Local Response Normalization (LRN)
- Handwritten notes:
- 160M parameters
 - 9216
 - 13 13 256


[Krizhevsky et al., 2012. ImageNet classification with deep convolutional neural networks]

Andrew Ng

VGG - 16

CONV $\leq 3 \times 3$ filter, $s = 1$, same


MAX-POOL = 2×2 , $s = 2$



[Simonyan & Zisserman 2015. Very deep convolutional networks for large-scale image recognition]

Andrew Ng


Residual block



[He et al., 2015. Deep residual networks for image recognition]

Andrew Ng


Residual Network



[He et al., 2015. Deep residual networks for image recognition]


Andrew Ng

Why do residual networks work?



Andrew Ng


ResNet




[He et al., 2015. Deep residual networks for image recognition]

Andrew Ng

Why does a 1×1 convolution do?




Using 1x1 convolutions



[Lin et al., 2013. Network in network]

Andrew Ng


Motivation for inception network



[Szegedy et al. 2014. Going deeper with convolutions]


Andrew Ng

The problem of computational cost




Andrew Ng

Using 1x1 convolution




Andrew Ng

Inception module




Andrew Ng


Inception network




Transfer Learning




Common augmentation method



Color shifting




Implementing distortions during training



Andrew Ng

Data vs. hand-engineering



Two sources of knowledge

- • Labeled data (x, y)
- • Hand engineered features/network architecture/other components

Andrew Ng

Tips for doing well on benchmarks/winning competitions

Ensembling

- Train several networks independently and average their outputs


3-15 networks

→ \hat{y} Average 3, not weights

Multi-crop at test time

- Run classifier on multiple versions of test images and average results

10-crop



Andrew Ng

Use open source code

- Use architectures of networks published in the literature
- Use open source implementations if possible
- Use pretrained models and fine-tune on your dataset