

Assignment 3: Question Answering

Welcome to this week's assignment of course 4. In this you will explore question answering. You will implement the "Text to Text Transfer from Transformers" (better known as T5). Since you implemented transformers from scratch last week you will now be able to use them.

□

Outline

- [Overview](#)
- [Part 0: Importing the Packages](#)
- [Part 1: C4 Dataset](#)
 - [1.1 Pre-Training Objective](#)
 - [1.2 Process C4](#)
 - [1.2.1 Decode to natural language](#)
 - [1.3 Tokenizing and Masking](#)
 - [Exercise 01](#)
 - [1.4 Creating the Pairs](#)
- [Part 2: Transformer](#)
 - [2.1 Transformer Encoder](#)
 - [2.1.1 The Feedforward Block](#)
 - [Exercise 02](#)
 - [2.1.2 The Encoder Block](#)
 - [Exercise 03](#)
 - [2.1.3 The Transformer Encoder](#)
 - [Exercise 04](#)

Overview

This assignment will be different from the two previous ones. Due to memory and time constraints of this environment you will not be able to train a model and use it for inference. Instead you will create the necessary building blocks for the transformer encoder model and will use a pretrained version of the same model in two ungraded labs after this assignment.

After completing these 3 (1 graded and 2 ungraded) labs you will:

- Implement the code necessary for Bidirectional Encoder Representation from Transformer (BERT).
- Understand how the C4 dataset is structured.
- Use a pretrained model for inference.
- Understand how the "Text to Text Transfer from Transformers" or T5 model works.

Part 0: Importing the Packages

In [1]:

```
import ast
import string
import textwrap
import itertools
import numpy as np

import trax
from trax import layers as tl
from trax.supervised import decoding

# Will come handy later.
wrapper = textwrap.TextWrapper(width=70)

# Set random seed
np.random.seed(42)
```

```
INFO:tensorflow:tokens_length=568 inputs_length=512 targets_length=114 noise_density=0.15
mean_noise_span_length=3.0
```

Part 1: C4 Dataset

The [C4](#) is a huge data set. For the purpose of this assignment you will use a few examples out of it which are present in `data.txt`. C4 is based on the [common crawl](#) project. Feel free to read more on their website.

Run the cell below to see how the examples look like.

In [2]:

```
# load example jsons
example_jsons = list(map(ast.literal_eval, open('data.txt')))
```

In [3]:

```
# Printing the examples to see how the data looks like
for i in range(5):
    print(f'example number {i+1}: \n\n{example_jsons[i]} \n')
```

example number 1:

```
{'content-length': b'1970', 'content-type': b'text/plain', 'text': b'Beginners BBQ Class Taking Pl
ace in Missoula!\nDo you want to get better at making delicious BBQ? You will have the
opportunity, put this on your calendar now. Thursday, September 22nd join World Class BBQ
Champion, Tony Balay from Lonestar Smoke Rangers. He will be teaching a beginner level class for e
veryone who wants to get better with their culinary skills.\nHe will teach you everything you need
to know to compete in a KCBS BBQ competition, including techniques, recipes, timelines, meat selec
tion and trimming, plus smoker and fire information.\nThe cost to be in the class is $35 per perso
n, and for spectators it is free. Included in the cost will be either a t-shirt or apron and you w
ill be tasting samples of each meat that is prepared.', 'timestamp': b'2019-04-25T12:57:54Z',
'url': b'https://klyq.com/beginners-bbq-class-taking-place-in-missoula/'}
```

example number 2:

```
{'content-length': b'12064', 'content-type': b'text/plain', 'text': b'Discussion in \'Mac OS X
Lion (10.7)\'' started by axboi87, Jan 20, 2012.\nI\'ve got a 500gb internal drive and a 240gb SSD.
\nWhen trying to restore using disk utility i\'m given the error "Not enough space on disk ____ to
restore"\nBut I shouldn\'t have to do that!!!\nAny ideas or workarounds before resorting to the ab
ove?\nUse Carbon Copy Cloner to copy one drive to the other. I\'ve done this several times going f
rom larger HDD to smaller SSD and I wound up with a bootable SSD drive. One step you have to remem
ber not to skip is to use Disk Utility to partition the SSD as GUID partition scheme HFS+ before d
oing the clone. If it came Apple Partition Scheme, even if you let CCC do the clone, the resulting
drive won\'t be bootable. CCC usually works in "file mode" and it can easily copy a larger drive (
that\'s mostly empty) onto a smaller drive. If you tell CCC to clone a drive you did NOT boot from
, it can work in block copy mode where the destination drive must be the same size or larger than
the drive you are cloning from (if I recall).\nI\'ve actually done this somehow on Disk Utility se
veral times (booting from a different drive (or even the dvd) so not running disk utility from the
drive your cloning) and had it work just fine from larger to smaller bootable clone. Definitely fo
rmat the drive cloning to first, as bootable Apple etc..\nThanks for pointing this out. My only ex
perience using DU to go larger to smaller was when I was trying to make a Lion install stick and I
was unable to restore InstallESD.dmg to a 4 GB USB stick but of course the reason that wouldn\'t f
it is there was slightly more than 4 GB of data.', 'timestamp': b'2019-04-21T10:07:13Z', 'url': b'
https://forums.macrumors.com/threads/restore-from-larger-disk-to-smaller-disk.1311329/'}
```

example number 3:

```
{'content-length': b'5235', 'content-type': b'text/plain', 'text': b'Foil plaid lycra and spandex
shortall with metallic slinky insets. Attached metallic elastic belt with O-ring. Headband include
d. Great hip hop or jazz dance costume. Made in the USA.', 'timestamp': b'2019-04-25T10:40:23Z',
'url': b'https://awishcometrue.com/Catalogs/Clearance/Tweens/V1960-Find-A-Way'}
```

example number 4:

```
{'content-length': b'4967', 'content-type': b'text/plain', 'text': b"How many backlinks per day fo
r new site?\nDiscussion in 'Black Hat SEO' started by Omoplata, Dec 3, 2010.\n1) for a newly creat
ed site, what's the max # backlinks per day I should do to be safe?\n2) how long do I have to let
my site age before I can start making more blinks?\nI did about 6000 forum profiles every 24 hours
for 10 days for one of my sites which had a brand new domain.\nThere is three backlinks for every
of these forum profile so thats 18 000 backlinks every 24 hours and nothing happened in terms of
being penalized or sandboxed. This is now maybe 3 months ago and the site is ranking on first page
```

being penalized or sandboxed. This is now maybe 3 months ago and the site is ranking on first page for a lot of my targeted keywords.\nbuild more you can in starting but do manual submission and no t spammy type means manual + relevant to the post.. then after 1 month you can make a big blast..\nWow, dude, you built 18k backlinks a day on a brand new site? How quickly did you rank up? What kind of competition/searches did those keywords have?", 'timestamp': b'2019-04-21T12:46:19Z', 'url': b'https://www.blackhatworld.com/seo/how-many-backlinks-per-day-for-new-site.258615/'}

example number 5:

```
{'content-length': b'4499', 'content-type': b'text/plain', 'text': b'The Denver Board of Education opened the 2017-18 school year with an update on projects that include new construction, upgrades, heat mitigation and quality learning environments.\nWe are excited that Denver students will be the beneficiaries of a four year, $572 million General Obligation Bond. Since the passage of the bond, our construction team has worked to schedule the projects over the four-year term of the bond.\nDenver voters on Tuesday approved bond and mill funding measures for students in Denver Public Schools, agreeing to invest $572 million in bond funding to build and improve schools and $56.6 million in operating dollars to support proven initiatives, such as early literacy.\nDenver voters say yes to bond and mill levy funding support for DPS students and schools. Click to learn more about the details of the voter-approved bond measure.\nDenver voters on Nov. 8 approved bond and mill funding measures for DPS students and schools. Learn more about what\xe2\x80\x99s included in the mill levy measure.', 'timestamp': b'2019-04-20T14:33:21Z', 'url': b'http://bond.dpsk12.org/category/news/'}
```

Notice the `b` before each string? This means that this data comes as bytes rather than strings. Strings are actually lists of bytes so for the rest of the assignments the name `strings` will be used to describe the data.

To check this run the following cell:

```
In [4]:
```

```
type(example_jsons[0].get('text'))
```

```
Out[4]:
```

```
bytes
```

1.1 Pre-Training Objective

Note: The word "mask" will be used throughout this assignment in context of hiding/removing word(s)

You will be implementing the BERT loss as shown in the following image.

Assume you have the following text: **Thank you for inviting me to your party last week**

Now as input you will mask the words in red in the text:

Input: Thank you X me to your party Y week.

Output: The model should predict the words(s) for X and Y.

Z is used to represent the end.

1.2 Process C4

C4 only has the plain string `text` field, so you will tokenize and have `inputs` and `targets` out of it for supervised learning. Given your inputs, the goal is to predict the targets during training.

You will now take the `text` and convert it to `inputs` and `targets`.

```
In [5]:
```

```
# Grab text field from dictionary
natural_language_texts = [example_json['text'] for example_json in example_jsons]
```

```
In [6]:
```

```
# Print out the first 5 elements
```

```
# First text example
natural_language_texts[4]
```

Out [6]:

```
b'The Denver Board of Education opened the 2017-18 school year with an update on projects that include new construction, upgrades, heat mitigation and quality learning environments.\nWe are excited that Denver students will be the beneficiaries of a four year, $572 million General Obligation Bond. Since the passage of the bond, our construction team has worked to schedule the projects over the four-year term of the bond.\nDenver voters on Tuesday approved bond and mill funding measures for students in Denver Public Schools, agreeing to invest $572 million in bond funding to build and improve schools and $56.6 million in operating dollars to support proven initiatives, such as early literacy.\nDenver voters say yes to bond and mill levy funding support for DPS students and schools. Click to learn more about the details of the voter-approved bond measure.\nDenver voters on Nov. 8 approved bond and mill funding measures for DPS students and schools. Learn more about what's included in the mill levy measure.'
```

1.2.1 Decode to natural language

The following functions will help you `detokenize` and `tokenize` the text data.

The `sentencepiece` vocabulary was used to convert from text to ids. This vocabulary file is loaded and used in this helper functions.

`natural_language_texts` has the text from the examples we gave you.

Run the cells below to see what is going on.

In [7]:

```
# Special tokens
PAD, EOS, UNK = 0, 1, 2

def detokenize(np_array):
    return trax.data.detokenize(
        np_array,
        vocab_type='sentencepiece',
        vocab_file='sentencepiece.model',
        vocab_dir='.')

def tokenize(s):
    # The trax.data.tokenize function operates on streams,
    # that's why we have to create 1-element stream with iter
    # and later retrieve the result with next.
    return next(trax.data.tokenize(
        iter([s]),
        vocab_type='sentencepiece',
        vocab_file='sentencepiece.model',
        vocab_dir='.'))
```

In [8]:

```
# printing the encoding of each word to see how subwords are tokenized
tokenized_text = [(tokenize(word).tolist(), word) for word in natural_language_texts[0].split()]
print(tokenized_text, '\n')
```

```
[[([12847, 277], b'Beginners'), ([15068], b'BBQ'), ([4501], b'Class'), ([3, 12297], b'Taking'), ([3399], b'Place'), ([16], b'in'), ([5964, 7115, 9, 55], b'Missoula!'), ([531], b'Do'), ([25], b'you'), ([241], b'want'), ([12], b'to'), ([129], b'get'), ([394], b'better'), ([44], b'at'), ([492], b'making'), ([3326], b'delicious'), ([15068, 58], b'BBQ?'), ([148], b'You'), ([56], b'will'), ([43], b'have'), ([8], b'the'), ([1004, 6], b'opportunity'), ([474], b'put'), ([48], b'this'), ([30], b'on'), ([39], b'your'), ([4793], b'calendar'), ([230, 5], b'now'), ([2721, 6], b'Thursday'), ([1600], b'September'), ([1630, 727], b'22nd'), ([1715], b'join'), ([1150], b'World'), ([4501], b'Class'), ([15068], b'BBQ'), ([16127, 6], b'Champion'), ([9137], b'Tony'), ([2659, 5595], b'Balay'), ([45], b'from'), ([301, 782, 3624], b'Lonestar'), ([14627, 15], b'Smoke'), ([12612, 277, 5], b'Rangers'), ([216], b'He'), ([56], b'will'), ([36], b'be'), ([2119], b'teaching'), ([3, 9], b'a'), ([19529], b'beginner'), ([593], b'level'), ([853], b'class'), ([21], b'for'), ([921], b'everyone'), ([113], b'who'), ([2746], b'wants'), ([12], b'to'), ([129], b'get'), ([394], b'better'), ([28], b'with'), ([70], b'their'), ([17712], b'culinary'), ([1098, 5], b'skills'), ([216], b'He'), ([56], b'will'), ([3884], b'teach'), ([25], b'you'), ([762], b'everything'), ([25], b'you'), ([174], b'need'), ([12], b'to'), ([214], b'know'), ([12], b'to'), ([5978], b'compete'), ([16], b'in'), ([3, 9], b'a'), ([3, 23405, 4547], b'KCBS'), ([15068], b'
```

```
BBQ'), ([2259, 6], b'competition,'), ([379], b'including'), ([2097, 6], b'techniques,'), ([5459, 6], b'recipes,'), ([13618, 7, 6], b'timelines,'), ([3604], b'meat'), ([1801], b'selection'), ([11], b'and'), ([27856, 6], b'trimming,'), ([303], b'plus'), ([24190], b'smoker'), ([11], b'and'), ([1472], b'fire'), ([251, 5], b'information.'), ([37], b'The'), ([583], b'cost'), ([12], b'to'), ([36], b'be'), ([16], b'in'), ([8], b'the'), ([853], b'class'), ([19], b'is'), ([25264], b'$35'), ([399], b'per'), ([568, 6], b'person,'), ([11], b'and'), ([21], b'for'), ([21380, 7], b'spectators'), ([34], b'it'), ([19], b'is'), ([339, 5], b'free.'), ([15746, 26], b'Included'), ([16], b'in'), ([8], b'the'), ([583], b'cost'), ([56], b'will'), ([36], b'be'), ([893], b'either'), ([3, 9], b'a'), ([3, 17, 18, 9486], b't-shirt'), ([42], b'or'), ([3, 9, 1409, 29], b'apron'), ([11], b'and'), ([25], b'you'), ([56], b'will'), ([36], b'be'), ([12246], b'tasting'), ([5977], b'samples'), ([13], b'of'), ([284], b'each'), ([3604], b'meat'), ([24], b'that'), ([19], b'is'), ([2657, 5], b'prepared.')]


```

In [9]:

```
# We can see that detokenize successfully undoes the tokenization
print(f"tokenized: {tokenize('Beginners')}\ndetokenized: {detokenize(tokenize('Beginners'))}")


```

```
tokenized: [12847 277]
detokenized: Beginners


```

As you can see above, you were able to take a piece of string and tokenize it.

Now you will create `input` and `target` pairs that will allow you to train your model. T5 uses the ids at the end of the vocab file as sentinels. For example, it will replace:

- `vocab_size - 1` by `<Z>`
- `vocab_size - 2` by `<Y>`
- and so forth.

It assigns every word a `chr`.

The `pretty_decode` function below, which you will use in a bit, helps in handling the type when decoding. Take a look and try to understand what the function is doing.

Notice that:

```
string.ascii_letters = 'abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ'


```

NOTE: Targets may have more than the 52 sentinels we replace, but this is just to give you an idea of things.

In [10]:

```
vocab_size = trax.data.vocab_size(
    vocab_type='sentencepiece',
    vocab_file='sentencepiece.model',
    vocab_dir='.')

def get_sentinels(vocab_size=vocab_size, display=False):
    sentinels = {}
    for i, char in enumerate(reversed(string.ascii_letters), 1):
        decoded_text = detokenize([vocab_size - i])

        # Sentinels, ex: <Z> - <a>
        sentinels[decoded_text] = f'<{char}>'

        if display:
            print(f'The sentinel is <{char}> and the decoded token is:', decoded_text)

    return sentinels


```

In [11]:

```
sentinels = get_sentinels(vocab_size, display=True)


```

```
The sentinel is <Z> and the decoded token is: Internatıonal
The sentinel is <Y> and the decoded token is: erwachsene
The sentinel is <X> and the decoded token is: Cushion
The sentinel is <W> and the decoded token is: imunitar
The sentinel is <V> and the decoded token is: Intellectual
The sentinel is <U> and the decoded token is: traditi


```

The sentinel is <U> and the decoded token is: ciaduit
 The sentinel is <T> and the decoded token is: disguise
 The sentinel is <S> and the decoded token is: exerce
 The sentinel is <R> and the decoded token is: nourishe
 The sentinel is <Q> and the decoded token is: predominant
 The sentinel is <P> and the decoded token is: amitié
 The sentinel is <O> and the decoded token is: erkennt
 The sentinel is <N> and the decoded token is: dimension
 The sentinel is <M> and the decoded token is: inférieur
 The sentinel is <L> and the decoded token is: refugi
 The sentinel is <K> and the decoded token is: cheddar
 The sentinel is <J> and the decoded token is: unterlieg
 The sentinel is <I> and the decoded token is: garanteaz
 The sentinel is <H> and the decoded token is: făcute
 The sentinel is <G> and the decoded token is: réglage
 The sentinel is <F> and the decoded token is: pedepse
 The sentinel is <E> and the decoded token is: Germain
 The sentinel is <D> and the decoded token is: distinctly
 The sentinel is <C> and the decoded token is: Schraub
 The sentinel is and the decoded token is: emanat
 The sentinel is <A> and the decoded token is: trimestre
 The sentinel is <Z> and the decoded token is: disrespect
 The sentinel is <y> and the decoded token is: Erasmus
 The sentinel is <x> and the decoded token is: Australia
 The sentinel is <w> and the decoded token is: permeabil
 The sentinel is <v> and the decoded token is: deseori
 The sentinel is <u> and the decoded token is: manipulated
 The sentinel is <t> and the decoded token is: suggér
 The sentinel is <s> and the decoded token is: corespund
 The sentinel is <r> and the decoded token is: nitro
 The sentinel is <q> and the decoded token is: oyons
 The sentinel is <p> and the decoded token is: Account
 The sentinel is <o> and the decoded token is: échéan
 The sentinel is <n> and the decoded token is: laundering
 The sentinel is <m> and the decoded token is: genealogy
 The sentinel is <l> and the decoded token is: QuickBooks
 The sentinel is <k> and the decoded token is: constituted
 The sentinel is <j> and the decoded token is: Fertigung
 The sentinel is <i> and the decoded token is: goutte
 The sentinel is <h> and the decoded token is: regulă
 The sentinel is <g> and the decoded token is: overwhelmingly
 The sentinel is <f> and the decoded token is: émerg
 The sentinel is <e> and the decoded token is: broyeur
 The sentinel is <d> and the decoded token is: povești
 The sentinel is <c> and the decoded token is: emulator
 The sentinel is and the decoded token is: halloween
 The sentinel is <a> and the decoded token is: combustibil

In [12]:

```
def pretty_decode(encoded_str_list, sentinels=sentinels):
    # If already a string, just do the replacements.
    if isinstance(encoded_str_list, (str, bytes)):
        for token, char in sentinels.items():
            encoded_str_list = encoded_str_list.replace(token, char)
        return encoded_str_list

    # We need to decode and then prettyfy it.
    return pretty_decode(detokenize(encoded_str_list))
```

In [13]:

```
pretty_decode("I want to dress up as an Intellectual this halloween.")
```

Out[13]:

```
'I want to dress up as an <V> this <b>.'
```

The functions above make your `inputs` and `targets` more readable. For example, you might see something like this once you implement the masking function below.

- **Input sentence:** Younes and Lukasz were working together in the lab yesterday after lunch.
- **Input:** Younes and Lukasz **Z** together in the **Y** yesterday after lunch.

- **Target:** Z were working Y lab.

1.3 Tokenizing and Masking

You will now implement the `tokenize_and_mask` function. This function will allow you to tokenize and mask input words with a noise probability. We usually mask 15% of the words.

Exercise 01

In [14]:

```
# UNQ_C1
# GRADED FUNCTION: tokenize_and_mask
def tokenize_and_mask(text, vocab_size=vocab_size, noise=0.15,
                      randomizer=np.random.uniform, tokenize=tokenize):
    """Tokenizes and masks a given input.

    Args:
        text (str or bytes): Text input.
        vocab_size (int, optional): Size of the vocabulary. Defaults to vocab_size.
        noise (float, optional): Probability of masking a token. Defaults to 0.15.
        randomizer (function, optional): Function that generates random values. Defaults to
        np.random.uniform.
        tokenize (function, optional): Tokenizer function. Defaults to tokenize.

    Returns:
        tuple: Tuple of lists of integers associated to inputs and targets.
    """

    # current sentinel number (starts at 0)
    cur_sentinel_num = 0
    # inputs
    inps = []
    # targets
    targs = []

    ### START CODE HERE (REPLACE INSTANCES OF 'None' WITH YOUR CODE) ###

    # prev_no_mask is True if the previous token was NOT masked, False otherwise
    # set prev_no_mask to True
    prev_no_mask = True

    # loop through tokenized `text`
    for token in tokenize(text):
        # check if the `noise` is greater than a random value (weighted coin flip)
        if randomizer() < noise:
            # check to see if the previous token was not masked
            if prev_no_mask==True: # add new masked token at end_id
                # number of masked tokens increases by 1
                cur_sentinel_num += 1
                # compute `end_id` by subtracting current sentinel value out of the total vocabular
                end_id = vocab_size - cur_sentinel_num
                # append `end_id` at the end of the targets
                targs.append(end_id)
                # append `end_id` at the end of the inputs
                inps.append(end_id)
            # append `token` at the end of the targets
            targs.append(token)
            # set prev_no_mask accordingly
            prev_no_mask = False
        else: # don't have two masked tokens in a row
            # append `token` at the end of the inputs
            inps.append(token)
            # set prev_no_mask accordingly
            prev_no_mask = True

    ### END CODE HERE ###

    return inps, targs
```

In [15]:

```
# Some logic to mock a np.random value generator
# Needs to be in the same cell for it to always generate same output
def testing_rnd():
    def dummy_generator():
        vals = np.linspace(0, 1, 10)
        cyclic_vals = itertools.cycle(vals)
        for _ in range(100):
            yield next(cyclic_vals)

    dumr = itertools.cycle(dummy_generator())

    def dummy_randomizer():
        return next(dumr)

    return dummy_randomizer

input_str = natural_language_texts[0]
print(f"input string:\n\n{input_str}\n")
inps, targs = tokenize_and_mask(input_str, randomizer=testing_rnd())
print(f"tokenized inputs:\n\n{inps}\n")
print(f"targets:\n\n{targs}")
```

input string:

b'Beginners BBQ Class Taking Place in Missoula!\nDo you want to get better at making delicious BBQ ? You will have the opportunity, put this on your calendar now. Thursday, September 22nd join World Class BBQ Champion, Tony Balay from Lonestar Smoke Rangers. He will be teaching a beginner level class for everyone who wants to get better with their culinary skills.\nHe will teach you everything you need to know to compete in a KCBS BBQ competition, including techniques, recipes, timelines, meat selection and trimming, plus smoker and fire information.\nThe cost to be in the class is \$35 per person, and for spectators it is free. Included in the cost will be either a t-shirt or apron and you will be tasting samples of each meat that is prepared.'

tokenized inputs:

[31999, 15068, 4501, 3, 12297, 3399, 16, 5964, 7115, 31998, 531, 25, 241, 12, 129, 394, 44, 492, 31997, 58, 148, 56, 43, 8, 1004, 6, 474, 31996, 39, 4793, 230, 5, 2721, 6, 1600, 1630, 31995, 1150, 4501, 15068, 16127, 6, 9137, 2659, 5595, 31994, 782, 3624, 14627, 15, 12612, 277, 5, 216, 31993, 2119, 3, 9, 19529, 593, 853, 21, 921, 31992, 12, 129, 394, 28, 70, 17712, 1098, 5, 31991, 3884, 25, 762, 25, 174, 12, 214, 12, 31990, 3, 9, 3, 23405, 4547, 15068, 2259, 6, 31989, 6, 5459, 6, 13618, 7, 6, 3604, 1801, 31988, 6, 303, 24190, 11, 1472, 251, 5, 37, 31987, 36, 16, 8, 853, 19, 25264, 399, 568, 31986, 21, 21380, 7, 34, 19, 339, 5, 15746, 31985, 8, 583, 56, 36, 893, 3, 9, 3, 31984, 9486, 42, 3, 9, 1409, 29, 11, 25, 31983, 12246, 5977, 13, 284, 3604, 24, 19, 2657, 31982]

targets:

[31999, 12847, 277, 31998, 9, 55, 31997, 3326, 15068, 31996, 48, 30, 31995, 727, 1715, 31994, 45, 301, 31993, 56, 36, 31992, 113, 2746, 31991, 216, 56, 31990, 5978, 16, 31989, 379, 2097, 31988, 11, 27856, 31987, 583, 12, 31986, 6, 11, 31985, 26, 16, 31984, 17, 18, 31983, 56, 36, 31982, 5]

Expected Output:

b'Beginners BBQ Class Taking Place in Missoula!\nDo you want to get better at making delicious BBQ? You will have the opportunity, put **this** on your calendar now. Thursday, September 22nd join World Class BBQ Champion, Tony Balay from Lonestar Smoke Rangers. He will be teaching a beginner level **class for** everyone who wants to get better with their culinary skills.\nHe will teach you everything you need to know to compete in a KCBS BBQ competition, including techniques, recipes, timelines, meat selection and trimming, plus smoker and fire information.\n\nThe cost to be in the **class is** \$35 per person, and **for** spectators it is free. Included in the cost will be either a t-shirt or apron and you will be tasting samples of each meat that is prepared.'

tokenized inputs:

[31999, 15068, 4501, 3, 12297, 3399, 16, 5964, 7115, 31998, 531, 25, 241, 12, 129, 394, 44, 492, 31997, 58, 148, 56, 43, 8, 1004, 6, 474, 31996, 39, 4793, 230, 5, 2721, 6, 1600, 1630, 31995, 1150, 4501, 15068, 16127, 6, 9137, 2659, 5595, 31994, 782, 3624, 14627, 15, 12612, 277, 5, 216, 31993, 2119, 3, 9, 19529, 593, 853, 21, 921, 31992, 12, 129, 394, 28, 70, 17712, 1098


```
, 5, 31991, 3884, 25, 762, 25, 174, 12, 214, 12, 31990, 3, 9, 3, 23405, 4547, 15068, 2259, 6, 31989, 6, 5459, 6, 13618, 7, 6, 3604, 1801, 31988, 6, 303, 24190, 11, 1472, 251, 5, 37, 31987, 36, 16, 8, 853, 19, 25264, 399, 568, 31986, 21, 21380, 7, 34, 19, 339, 5, 15746, 31985, 8, 583, 56, 36, 893, 3, 9, 3, 31984, 9486, 42, 3, 9, 1409, 29, 11, 25, 31983, 12246, 5977, 13, 284, 3604, 24, 19, 2657, 31982]
```

targets:

```
[31999, 12847, 277, 31998, 9, 55, 31997, 3326, 15068, 31996, 48, 30, 31995, 727, 1715, 31994, 45, 301, 31993, 56, 36, 31992, 113, 2746, 31991, 216, 56, 31990, 5978, 16, 31989, 379, 2097, 31988, 11, 27856, 31987, 583, 12, 31986, 6, 11, 31985, 26, 16, 31984, 17, 18, 31983, 56, 36, 31982, 5]
```

You will now use the inputs and the targets from the `tokenize_and_mask` function you implemented above. Take a look at the masked sentence using your `inps` and `targs` from the sentence above.

In [16]:

```
print('Inputs: \n\n', pretty_decode(inps))
print('\nTargets: \n\n', pretty_decode(targs))
```

Inputs:

```
<Z> BBQ Class Taking Place in Missoul <Y> Do you want to get better at making <X>? You will have the opportunity, put <W> your calendar now. Thursday, September 22 <V> World Class BBQ Champion, Tony Balay <U>onestar Smoke Rangers. He <T> teaching a beginner level class for everyone<S> to get better with their culinary skills.<R> teach you everything you need to know to <Q> a KCBS BBQ competition,<P>, recipes, timelines, meat selection <O>, plus smoker and fire information. The<N> be in the class is $35 per person <M> for spectators it is free. Include <L> the cost will be either a <K>shirt or apron and you <J> tasting samples of each meat that is prepared <I>
```

Targets:

```
<Z> Beginners <Y>a! <X> delicious BBQ <W> this on <V>nd join <U> from L <T> will be<S> who wants<R> He will <Q> compete in<P> including techniques <O> and trimming<N> cost to <M>, and <L>d in <K> t- <J> will be <I>.
```

1.4 Creating the Pairs

You will now create pairs using your dataset. You will iterate over your data and create (inp, targ) pairs using the functions that we have given you.

In [17]:

```
# Apply tokenize_and_mask
inputs_targets_pairs = [tokenize_and_mask(text) for text in natural_language_texts]
```

In [18]:

```
def display_input_target_pairs(inputs_targets_pairs):
    for i, inp_tgt_pair in enumerate(inputs_targets_pairs, 1):
        inps, tgts = inp_tgt_pair
        inps, tgts = pretty_decode(inps), pretty_decode(tgts)
        print(f'[{i}]\n\n'
              f'inputs:\n{wrapper.fill(text=inps)}\n\n'
              f'targets:\n{wrapper.fill(text=tgts)}\n\n\n\n')
```

In [19]:

```
display_input_target_pairs(inputs_targets_pairs)
```

[1]

inputs:

```
Beginners BBQ Class Taking <Z> in Missoul <Y>! Do you want to get better at making delicious <X>? You will have the opportunity <W>
```

better at making delicious <x>? you will have the opportunity, <w> this on <v> calendar now. Thursday <u> September 22 <t> join<s> Class BBQ Champion, Tony Balay from Lonestar Smoke<r>ers <q> He will be teaching a beginner<p> class <o> everyone who wants<n> get better with their <m> skills <l> He will teach <k> everything you need to know to <j> in a KCBS BBQ <i> techniques, recipes, timelines, meat<h> and trimming, plus smoker and fire information. The cost to be<g> the class is \$35 <f> person, and<e> spectators it is free. Included in the cost will<d> either <c> t- or apron and you will be tasting samples <a> each meat that <z> prepared.

targets:

<z> Place <y>a <x> BBQ <w> put <v> your <u>, <t>nd<s> World<r> Rang <q>. <p> level <o> for<n> to <m> culinary <l>. <k> you <j> compete <i> competition, including<h> selection<g> in <f> per<e> for<d> be<c>a shirt <a> of <z> is

[2]

inputs:

<z> in 'Mac OS X <y> (10 <x>7)' started by axb <w>i87, Jan 20, 2012. I've got <v>a 500g <u> drive <t> a 240gb SSD. When trying to restore using<s> utility i'm given the error "Not enough space on disk<r> ____ to restore <q> But I shouldn't have to do that!!! Any ideas or work<p>s before <o>ing to the above? Use Carbon Copy Cloner to copy one drive to the other. I'<n> done <m> several times going from <l>D to <k> SSD and I wound <j> a bootable SSD drive. One step you <i> remember not to skip is to use Disk Utility to partition the SSD as GUID partition scheme<h> doing the <g>ne. If it came Apple <f>ition Scheme, even if<e> let<d>CC do the clone, the resulting drive<c> boot . C <a> usually works <z> "file mode" and it can easily copy a larger drive (that's mostly empty <y> onto a smaller drive.<x> you<w> CCC to clone a drive you did<v> boot<u>, it can work <t> copy mode <s> destination<r> must be<q> size or larger than the drive you are<p>cloning from <o>if <n> recall <m>ve actually done this somehow on Disk Utility <l> times<k>booting from <j>a different drive (or even the dvd)<i> not running disk utility from the drive your clo<h>ing) and had it work just fine from larger to smaller bootable clo<g>. Definitely format the drive cloning to first <f> as bootable Apple etc.. Thanks for <e> this out. My only experience <d> DU to go larger to smaller was when <c> trying to make install stick and I was unable to restore InstallESD <a>dmg to a 4 GB Théâtre ofKeep the reason that wouldn't fit isdürftig was slightly moreutti GB of data.

targets:

<z> Discussion <y> Lion <x>. <w>o <v> <u>b internal <t> and<s> disk<r> <q>"<p>around <o> resort<n>ve <m> this <l> larger HD <k> smaller <j> up with <i> have to<h> HFS+ before<g>clo <f> Part<e> you<d> C<c> won't be able <a>CC <z> in <y>)<x> If<w> tell<v> NOT<u> from <t> in block <s> where the<r> drive<q> the same<p> <o> (<n> I <m>). I' <l> several<k> (<j> <i> so<h>n<g>ne <f>,<e>pointing <d> using <c> I was a Lion <a>. Théâtre USB stick butKeep coursedürftig thereutti than 4

[3]

inputs:

<z>il plaid <y>lycra <x> spandex shortall with metallic slinky <w>sets. Attache <v> metallic elastic belt with O <u>ring. Head <t> included. Great hip hop<s> jazz dance costume.<r> in the USA.

targets:

<z> Fo <y> <x> and <w> in <v>d <u>- <t>band<s> or<r> Made

[4]

inputs:

How many backlink <z> per day for new site? Discussion <y> 'Black <x> 370' <w> <v> <u> <t> <s> <r> <q> <p> <o> <n> <m> <l> <k> <j> <i> <h> <g> <f> <e> <d> <c> <a>

SEO' started by Omoplata, Dec 3, 2010. 1) for a <W> created site, what's <V> max <U>links per day I should do to be safe? 2) how <T> do I have<S> let my site<R> before I can start making more blinks? I did about 6000 forum profiles every 24 hours for 10 days for <Q> of my sites<P> had a brand new domain. There is <O> backlinks for every<N> these <M> profile so <L>s 18 000 backlinks every 24 hours and nothing happened in terms of being penalized <K> sandboxed. This is now maybe 3 months ago <J> the site <I> ranking on first page for<H>a lot<G> my targeted keywords. build more you can in starting <F> do manual submission and not spammy<E> means manual +<D> to<C> post.. after 1 month you can <A> a <z> blast.. Wow, dude, you built 18k backlink <y> a day<x> a brand<w>? How quickly did<v> rank up? What kind of competition/search<u> did <t> keywords have?

targets:

<Z>s <Y> in <X> Hat <W> newly <V> the <U> # back <T> long<S> to<R> age <Q> one<P> which <O> three<N> of <M> forum <L> that <K> or <J> and <I> is<H> <G> of <F> but<E> type<D> relevant<C> the then <A> make <z> big <y>s<x> on<w> new site<v> you<u>es <t> those

[5]

inputs:

The Denver Board of Education opened the 2017-18 school year with an update <Z> projects that include new construction <Y> upgrades, heat mitigation <X> quality learning environments. We <W> excited <V> Denver students will be the beneficiaries <U>a four year, \$572 million General Oblig <T> Bond.<S> the passage of the bond, our construction team has worked to schedule<R> projects over <Q> four-year term<P> bond. Denver voters on Tuesday approved bond and mill funding <O> for<N> in Denver Public Schools, agreeing to invest \$572 million in bond funding <M> build and improve schools and <L>6.6 million in operating dollars to support proven initiatives, <K> as early <J> Denver voters say <I> to bond and mill levy funding<H> for<G>PS students and schools. Click to learn more about the details of the voter-approved <F> measure. Denver voters<E>. 8 approved bond and mill funding<D> for DPS students and schools. Learn more about what's included in the mill <C>y measure.

targets:

<Z> on <Y>, <X> and <W> are <V> that <U> of <T>ation<S> Since<R> the <Q> the<P> of the <O> measures<N> students <M> to <L> \$5 <K> such <J> literacy. <I> yes<H> support<G> D <F> bond<E> on Nov<D> measures<C>lev

Part 2: Transformer

We now load a Transformer model checkpoint that has been pre-trained using the above C4 dataset and decode from it. This will save you a lot of time rather than have to train your model yourself. Later in this notebook, we will show you how to fine-tune your model.

Start by loading in the model. We copy the checkpoint to local dir for speed, otherwise initialization takes a very long time. Last week you implemented the decoder part for the transformer. Now you will implement the encoder part. Concretely you will implement the following.

2.1 Transformer Encoder

You will now implement the transformer encoder. Concretely you will implement two functions. The first function is

```
FeedForwardBlock.
```

2.1.1 The Feedforward Block

The `FeedForwardBlock` function is an important one so you will start by implementing it. To do so, you need to return a list of the following:

- `tl.LayerNorm()` = layer normalization.
- `tl.Dense(d_ff)` = fully connected layer.
- `activation` = activation relu, tanh, sigmoid etc.
- `dropout_middle` = we gave you this function (don't worry about its implementation).
- `tl.Dense(d_model)` = fully connected layer with same dimension as the model.
- `dropout_final` = we gave you this function (don't worry about its implementation).

You can always take a look at [trax documentation](#) if needed.

Instructions: Implement the feedforward part of the transformer. You will be returning a list.

Exercise 02

In [20]:

```
# UNQ_C2
# GRADED FUNCTION: FeedForwardBlock
def FeedForwardBlock(d_model, d_ff, dropout, dropout_shared_axes, mode, activation):
    """Returns a list of layers implementing a feed-forward block.

    Args:
        d_model: int: depth of embedding
        d_ff: int: depth of feed-forward layer
        dropout: float: dropout rate (how much to drop out)
        dropout_shared_axes: list of integers, axes to share dropout mask
        mode: str: 'train' or 'eval'
        activation: the non-linearity in feed-forward layer

    Returns:
        A list of layers which maps vectors to vectors.
    """

    dropout_middle = tl.Dropout(rate=dropout,
                                shared_axes=dropout_shared_axes,
                                mode=mode)

    dropout_final = tl.Dropout(rate=dropout,
                                shared_axes=dropout_shared_axes,
                                mode=mode)

    ### START CODE HERE (REPLACE INSTANCES OF 'None' WITH YOUR CODE) ###

    ff_block = [
        # trax Layer normalization
        tl.LayerNorm(),
        # trax Dense layer using `d_ff`
        tl.Dense(d_ff),
        # activation() layer - you need to call (use parentheses) this func!
        activation(),
        # dropout middle layer
        dropout_middle,
        # trax Dense layer using `d_model`
        tl.Dense(d_model),
        # dropout final layer
        dropout_final,
    ]

    ### END CODE HERE ###

    return ff_block
```

In [21]:

```
# Print the block layout
feed_forward_example = FeedForwardBlock(d_model=512, d_ff=2048, dropout=0.8, dropout_shared_axes=0,
mode = 'train', activation = tl.Relu)
print(feed_forward_example)
```

[LayerNorm, Dense_2048, Relu, Dropout, Dense_512, Dropout]

Expected Output:

```
[LayerNorm, Dense_2048, Relu, Dropout, Dense_512, Dropout]
```

2.1.2 The Encoder Block

The encoder block will use the `FeedForwardBlock`.

You will have to build two residual connections. Inside the first residual connection you will have the `tl.LayerNorm()`, `attention`, and `dropout` layers. The second residual connection will have the `feed_forward`.

You will also need to implement `feed_forward`, `attention` and `dropout` blocks.

So far you haven't seen the `tl.Attention()` and `tl.Residual()` layers so you can check the docs by clicking on them.

Exercise 03

In [24]:

```
# UNQ_C3
# GRADED FUNCTION: EncoderBlock
def EncoderBlock(d_model, d_ff, n_heads, dropout, dropout_shared_axes,
                 mode, ff_activation, FeedForwardBlock=FeedForwardBlock):
    """
    Returns a list of layers that implements a Transformer encoder block.
    The input to the layer is a pair, (activations, mask), where the mask was
    created from the original source tokens to prevent attending to the padding
    part of the input.

    Args:
        d_model (int): depth of embedding.
        d_ff (int): depth of feed-forward layer.
        n_heads (int): number of attention heads.
        dropout (float): dropout rate (how much to drop out).
        dropout_shared_axes (int): axes on which to share dropout mask.
        mode (str): 'train' or 'eval'.
        ff_activation (function): the non-linearity in feed-forward layer.
        FeedForwardBlock (function): A function that returns the feed forward block.
    Returns:
        list: A list of layers that maps (activations, mask) to (activations, mask).
    """

    ### START CODE HERE (REPLACE INSTANCES OF 'None' WITH YOUR CODE) ###

    # Attention block
    attention = tl.Attention(
        # Use dimension of the model
        d_feature=d_model,
        # Set it equal to number of attention heads
        n_heads=n_heads,
        # Set it equal `dropout`
        dropout=dropout,
        # Set it equal `mode`
        mode=mode
    )

    # Call the function `FeedForwardBlock` (implemented before) and pass in the parameters
    feed_forward = FeedForwardBlock(
        d_model,
        d_ff,
        dropout,
        dropout_shared_axes,
        mode,
        ff_activation
    )

    # Dropout block
    dropout_ = tl.Dropout(
```

```

        # set it equal to `dropout`
        rate=dropout,
        # set it equal to the axes on which to share dropout mask
        shared_axes=dropout_shared_axes,
        # set it equal to `mode`
        mode=mode
    )

    encoder_block = [
        # add `Residual` layer
        tl.Residual(
            # add norm layer
            tl.LayerNorm(),
            # add attention
            attention,
            # add dropout
            dropout_,
        ),
        # add another `Residual` layer
        tl.Residual(
            # add feed forward
            feed_forward,
        ),
    ]

    ### END CODE HERE ###

    return encoder_block

```

In [25]:

```

# Print the block layout
encoder_example = EncoderBlock(d_model=512, d_ff=2048, n_heads=6, dropout=0.8, dropout_shared_axes=
0, mode = 'train', ff_activation=tl.Relu)
print(encoder_example)

```

```

[Serial_in2_out2[
  Branch_in2_out3[
    None
    Serial_in2_out2[
      LayerNorm
      Serial_in2_out2[
        Dup_out2
        Dup_out2
        Serial_in4_out2[
          Parallel_in3_out3[
            Dense_512
            Dense_512
            Dense_512
          ]
          PureAttention_in4_out2
          Dense_512
        ]
      ]
      Dropout
    ]
  ]
  Add_in2
], Serial[
  Branch_out2[
    None
    Serial[
      LayerNorm
      Dense_2048
      Relu
      Dropout
      Dense_512
      Dropout
    ]
  ]
  Add_in2
]]

```

Expected Output:

```
[Serial_in2_out2[
  Branch_in2_out3[
    None
    Serial_in2_out2[
      LayerNorm
      Serial_in2_out2[
        Dup_out2
        Dup_out2
        Serial_in4_out2[
          Parallel_in3_out3[
            Dense_512
            Dense_512
            Dense_512
          ]
          PureAttention_in4_out2
          Dense_512
        ]
      ]
    ]
  ]
  Dropout
]
]
Add_in2
], Serial[
  Branch_out2[
    None
    Serial[
      LayerNorm
      Dense_2048
      Relu
      Dropout
      Dense_512
      Dropout
    ]
  ]
]
Add_in2
]]
```

2.1.3 The Transformer Encoder

Now that you have implemented the `EncoderBlock`, it is time to build the full encoder. BERT, or Bidirectional Encoder Representations from Transformers is one such encoder.

You will implement its core code in the function below by using the functions you have coded so far.

The model takes in many hyperparameters, such as the `vocab_size`, the number of classes, the dimension of your model, etc. You want to build a generic function that will take in many parameters, so you can use it later. At the end of the day, anyone can just load in an API and call transformer, but we think it is important to make sure you understand how it is built. Let's get started.

Instructions: For this encoder you will need a `positional_encoder` first (which is already provided) followed by `n_layers` encoder blocks, which are the same encoder blocks you previously built. Once you store the `n_layers` `EncoderBlock` in a list, you are going to encode a `Serial` layer with the following sublayers:

- `tl.Branch`: helps with the branching and has the following sublayers:
 - `positional_encoder`.
 - `tl.PaddingMask()`: layer that maps integer sequences to padding masks.
- Your list of `EncoderBlock`s
- `tl.Select([0], n_in=2)`: Copies, reorders, or deletes stack elements according to indices.
- `tl.LayerNorm()`.
- `tl.Mean()`: Mean along the first axis.
- `tl.Dense()` with `n_units` set to `n_classes`.
- `tl.LogSoftmax()`

Exercise 04

In [28]:

```
# UNQ_C4
# GRADED FUNCTION: TransformerEncoder
def TransformerEncoder(vocab_size=vocab_size,
                      n_classes=10,
                      d_model=512,
                      d_ff=2048,
                      n_layers=6,
                      n_heads=8,
                      dropout=0.1,
                      dropout_shared_axes=None,
                      max_len=2048,
                      mode='train',
                      ff_activation=tl.Relu,
                      EncoderBlock=EncoderBlock):

    """
    Returns a Transformer encoder model.
    The input to the model is a tensor of tokens.

    Args:
        vocab_size (int): vocab size. Defaults to vocab_size.
        n_classes (int): how many classes on output. Defaults to 10.
        d_model (int): depth of embedding. Defaults to 512.
        d_ff (int): depth of feed-forward layer. Defaults to 2048.
        n_layers (int): number of encoder/decoder layers. Defaults to 6.
        n_heads (int): number of attention heads. Defaults to 8.
        dropout (float): dropout rate (how much to drop out). Defaults to 0.1.
        dropout_shared_axes (int): axes on which to share dropout mask. Defaults to None.
        max_len (int): maximum symbol length for positional encoding. Defaults to 2048.
        mode (str): 'train' or 'eval'. Defaults to 'train'.
        ff_activation (function): the non-linearity in feed-forward layer. Defaults to tl.Relu.
        EncoderBlock (function): Returns the encoder block. Defaults to EncoderBlock.

    Returns:
        trax.layers.combinators.Serial: A Transformer model as a layer that maps
        from a tensor of tokens to activations over a set of output classes.
    """

    positional_encoder = [
        tl.Embedding(vocab_size, d_model),
        tl.Dropout(rate=dropout, shared_axes=dropout_shared_axes, mode=mode),
        tl.PositionalEncoding(max_len=max_len)
    ]

    ### START CODE HERE (REPLACE INSTANCES OF 'None' WITH YOUR CODE) ###

    # Use the function `EncoderBlock` (implemented above) and pass in the parameters over `n_layer
s`
    encoder_blocks = [EncoderBlock(d_model, d_ff, n_heads, dropout, dropout_shared_axes, mode,
                                   ff_activation) for _ in range(n_layers)]

    # Assemble and return the model.
    return tl.Serial(
        # Encode
        tl.Branch(
            # Use `positional_encoder`
            positional_encoder,
            # Use trax padding mask
            tl.PaddingMask(),
        ),
        # Use `encoder_blocks`
        encoder_blocks,
        # Use select layer
        tl.Select([0], n_in=2),
        # Use trax layer normalization
        tl.LayerNorm(),
        # Map to output categories.
        # Use trax mean. set axis to 1
        tl.Mean(axis=1),
```



```

        # Use trax Dense using `n_classes`
        tl.Dense(n_classes),
        # Use trax log softmax
        tl.LogSoftmax(),
    )

    ### END CODE HERE ###

```

In [29]:

```

# Run this cell to see the structure of your model
# Only 1 layer is used to keep the output readable
TransformerEncoder(n_layers=1)

```

Out[29]:

```

Serial[
  Branch_out2[
    [Embedding_32000_512, Dropout, PositionalEncoding]
    PaddingMask(0)
  ]
  Serial_in2_out2[
    Branch_in2_out3[
      None
      Serial_in2_out2[
        LayerNorm
        Serial_in2_out2[
          Dup_out2
          Dup_out2
          Serial_in4_out2[
            Parallel_in3_out3[
              Dense_512
              Dense_512
              Dense_512
            ]
            PureAttention_in4_out2
            Dense_512
          ]
        ]
        Dropout
      ]
    ]
    Add_in2
  ]
  Serial[
    Branch_out2[
      None
      Serial[
        LayerNorm
        Dense_2048
        Relu
        Dropout
        Dense_512
        Dropout
      ]
    ]
    Add_in2
  ]
  Select[0]_in2
  LayerNorm
  Mean
  Dense_10
  LogSoftmax
]

```

Expected Output:

```

Serial[
  Branch_out2[
    [Embedding_32000_512, Dropout, PositionalEncoding]
    PaddingMask(0)
  ]
  Serial_in2_out2[

```

```

Serial_in2_out2[
  Branch_in2_out3[
    None
  ]
  Serial_in2_out2[
    LayerNorm
    Serial_in2_out2[
      Dup_out2
      Dup_out2
      Serial_in4_out2[
        Parallel_in3_out3[
          Dense_512
          Dense_512
          Dense_512
        ]
        PureAttention_in4_out2
        Dense_512
      ]
    ]
  ]
  Dropout
]
]
Add_in2
]
Serial[
  Branch_out2[
    None
  ]
  Serial[
    LayerNorm
    Dense_2048
    Relu
    Dropout
    Dense_512
    Dropout
  ]
]
Add_in2
]
Select[0]_in2
LayerNorm
Mean
Dense_10
LogSoftmax
]

```

NOTE Congratulations! You have completed all of the graded functions of this assignment. Since the rest of the assignment takes a lot of time and memory to run we are providing some extra ungraded labs for you to see this model in action.

Keep it up!

To see this model in action continue to the next 2 ungraded labs. **We strongly recommend you to try the colab versions of them as they will yield a much smoother experience.** The links to the colabs can be found within the ungraded labs or if you already know how to open files within colab here are some shortcuts (if not, head to the ungraded labs which contain some extra instructions):

[BERT Loss Model Colab](#)

[T5 SQuAD Model Colab](#)