



Assignment 3


Quantum Information and Computing

Giacomo Gasparotto
25 November 2025, A.Y. 2025/2026

Scaling of the matrix-matrix multiplication

Automatisation of the compiling and the execution of the matrix-matrix multiplication Fortran file.

- Matrix dimensions tested: $N = [500, 1000, 1500, \dots, 5000]$
- Computing performances in term of *CPUtime*
- Fit the resulting point with a polynomial: expect complexity $O(N^3)$



Eigenproblem

Two functions:

- `generate_hermitian_matrix`

```
def generate_hermitian_matrix(dim, distr="uniform", low=0.0, high=1.0, mean=0.0, std=1.0, complex=False):  
    . . .  
  
    # Make the matrix hermitian  
    A = A + A.T
```


- `compute_eigenvals_spacing`

```
def compute_eigenvals_spacing(A, k=None):  
    . . .  
  
    eigenval = np.sort(eigsh(A, k=k, which="LM")[0])  
  
    # compute the space between the eigenvalues  
    Lambda_i = np.diff(eigenval)  
    Lambda_i = Lambda_i[:-1] # discard the largest eigenvalue  
    Lambda_mean = np.mean(Lambda_i)  
  
    # normalize space between the eigenvalues  
    s = Lambda_i/Lambda_mean  
  
    return s
```

`scipy.sparse.linalg.eigsh`

↓
ARPACK
↓

Implicit Restarted Lanczos Method



Same pdfs for each distribution
due to normalisation.

Random matrix Theory

Theory

Compute the normalised eigenvalue spacing for 4 different cases:

1. **Real hermitian matrix**
2. **Real diagonal matrix**
3. **Complex hermitian matrix**
4. **Sparse matrix**





Statistics based on generating 50 1000x1000 matrices for each type.

Overlapped with:

- **Generic 4-parameters fit:** $P(s) = as^\alpha e^{-bs^\beta}$
- **Wigner surmise distribution** - expected to be the theoretical distribution for hermitian matrices eigenvalues spacing (exact for 2x2 matrices):

$$P(s) = \frac{32}{\pi^2} s^2 e^{-\frac{4s^2}{\pi}}$$

Random matrix Theory



Random matrix Theory

Computational time increasing matrices dimensions

Diagonalization time comparison between different matrices.

