


Approximating Solutions of the Time Independent Schrödinger Equation

Gian Laager
November 11, 2022



Maturaarbeit
Kantonsschule Glarus
Betreuer: Linus Romer
Referent: Elena Borisova

Contents

Vorwort	iii
1. Introduction	1
1.1. Goals	1
2. Preliminary	2
2.1. Schrödinger Equation	2
2.2. Rust	2
2.3. Interpretation of Quantum Mechanics	3
2.4. Complex Numbers	3
2.5. Gnuplot	4
2.6. Planck Units	4
3. Methods	5
3.1. Program Architecture	5
3.2. Newtons Method	5
3.3. Regula Falsi with Bisection	7
3.4. Derivatives	7
3.5. Integration	8
3.6. Transition Regions	12
3.6.1. Implementation in Rust	14
4. Calculation	16
4.1. Energy Levels	16
4.1.1. Accuracy	17
4.2. Approximation Scheme	19
4.2.1. Validity	21
4.2.2. Implementation	22
4.3. Turning Points	22
4.4. Wave Function Parts	25
4.5. Wave Function	25
4.5.1. Super Position	26
5. Program Manual	27
5.1. Wave Function	27
5.2. SuperPosition	28
5.3. Plotting	28
5.3.1. WaveFunction	29

5.4. Potentials	29
5.4.1. Custom Potentials	31
A. Detailed Calculations	33
A.1. Proofs	33
A.1.1. Smoothness of Transitionfunction	33
B. Data Files	35
B.1. Energies	35
C. Source Code	37

Vorwort

Der Rest der Arbeit wird in Englisch sein aber ich habe mich entschieden eine kleine Zusammenfassung zu schreiben, so dass jeder zumindest die Grundlagen meiner Arbeit versteht. Zu begin des 20. Jahrhunderts gab es einen Umschwung in der Physik, Quantenmechanik wurde entdeckt. Diese neue Theorie kann nicht mehr präzise voraussagen machen wie es zuvor der Fall war. Man kann nur noch sagen mit welcher Wahrscheinlichkeit etwas passiert und ein Partikel kann an zwei Orten gleichzeitig sein.

Vielleicht haben Sie schon einmal von Schrödingers Katze gehört. Dies war ein Gedankenexperiment von Schrödinger um auf zu zeigen wie absurd seine Theorie wirklich ist und dass sie nicht stimmen könne. Stell dir vor du schliesst deine Katze in eine Box ein. In dieser Box ist ein Atom das entweder zerfallen kann oder nicht. Dazu gibt es einen Detektor der misst ob das Atom zerfallen ist, in diesem Fall wird ein Gift frei gelassen und die Katze stirbt. Das Problem ist jetzt aber, dass dieses Atom den Regeln der Quanten Mechanik folgt und deshalb gleichzeitig bereits zerfallen ist und nicht zerfallen ist, die einzig logische Schlussfolgerung ist deshalb, dass *die Katze gleichzeitig Tod und am leben ist* (Schrödinger, 1935).

In der Realität funktioniert es wahrscheinlich jedoch nicht so. Heisst das Universum “entscheidet” ob die Katze gestorben ist oder nicht, jedoch weiss man bis Heute nicht wann das Universum “entscheidet”.

Damit die Katze gleichzeitig Tod und Lebendig sein kann brauchen wir die Wellenfunktion. Sie beschreibt alles was in unserem Universum gerade passiert und “speichert” wie wahrscheinlich es ist, dass die Katze tot ist.

In meiner Maturaarbeit habe ich ein Programm geschrieben das genau diese Wellenfunktion ausrechnet in einem sehr vereinfachten Universum. Weil ich schon lange mal wissen möchte wie genau dieses bizarre Objekt aussieht. Auf der Titel Seite ist eine dieser Wellenfunktionen abgebildet.

1. Introduction

Richard Feynmann one of the core people behind our modern theory of quantum mechanics repeatedly said: “I think I can safely say that nobody understands quantum mechanics.”. Nothing behaves like in our every day lives. Everything is just a probability and nothing certain. Even Schrödinger the inventor of the equation that governs all of those weird phenomena rejected the idea that there are just probabilities.

In this paper we will try to understand this world a little bit better by looking at wave functions in a simplified universe. This universe only has 1 dimension and there will not be any sense of time. This means we will be able to actually see how the wave function looks like in a graph.

1.1. Goals

The goal of this Maturaarbeit is to write a program, schroeding-approx that calculates solutions to the time independent Schrödinger equation in 1 dimension for a large verity of potentials. We assume that the wave function, $\Psi(x)$ will converge to 0 as x goes to $\pm\infty$. The program should be reasonably fast, meaning that for simple potentials and low energies it should be done in under 1 minute. The architecture should be able to support improvements.

Making the program user friendly is not a main focus. Meaning that a clear and simple API that can be extended in the future is enough. Even dough the user will have to edit the code to for example change between energies.

The program should also follow the UNIX philosophy, “do one thing and one thing well”. As a consequence the program will only do the calculations and not the plotting. But it provides a simple and clear interface for a plotting program such as GNU Plot.

The main focus will be to balance performance and accuracy. Accuracy manly meaning that the visualizations should be visually accurate and give some insight into quantum mechanics. The user should also be able to tune the balance between performance and accuracy to some degree.

2. Preliminary

2.1. Schrödinger Equation

In 1926 Erwin Schrödinger changed our understanding of quantum physics with the Schrödinger equation. Based on the observations of de Broglie that particles behave like waves he developed a wave equation which describes how the waves move and change in a given potential $V(x)$ or Hamiltonian \hat{H} .

$$i\hbar \frac{\partial}{\partial t} \Psi(x, t) = \left[-\frac{\hbar^2}{2m} \frac{\partial^2}{\partial x^2} + V(x, t) \right] \Psi(x, t)$$

Or more general

$$i\hbar \frac{\partial}{\partial t} \Psi(x, t) = \hat{H} \Psi(x, t)$$

The time independent version that is going to be used later, ignores the change over time and is much simpler to solve since it is **only** an ordinary differential equation instead of a partial differential equation.

$$E\psi(x) = \hat{H}\psi(x)$$

or

$$-\frac{\hbar^2}{2m} \frac{d^2\psi}{dx^2}(x) + V(x)\psi(x) = E\psi(x)$$

Even with the time independent equation it is very difficult to get analytical solutions, because of this there are mainly three approaches to approximate solutions of $\psi(x)$, perturbation theory, density functional field theory and WKB approximation. Perturbation theory's goal is to give an analytical approximation which means it is extremely difficult to implement for a computer. WKB on the other hand is much better since it is to some degree a step by step manual.

2.2. Rust

Rust is one of the newer programming languages and attempts to replace C/C++ which are notoriously difficult to work with. It supports both functional and object-oriented paradigms. It is much safer in terms of memory and promises the same performance as C. One of the goals of Rust is fearless concurrency which means everybody should be able to write concurrent

code without deadlocks and data races. This means calculations can utilize the full potential of the CPU without countless hours of debugging.

Functional programming languages are especially useful for mathematical problems, because they are based on the same mathematics as the problem.

Rust as of the time of writing this document is not yet standardized meaning the code provided might no longer be correct with one of the newer Rust versions.

In case you aren't familiar with Rust, it has excellent documentation on <https://doc.rust-lang.org/book/>.

2.3. Interpretation of Quantum Mechanics

The author believes in the many worlds interpretation of Hugh Everett. *“The wave interpretation. This is the position proposed in the present thesis, in which the wave function itself is held to be the fundamental entity, obeying at all times a deterministic wave equation.”* (DeWitt und Graham, 2015, p. 115). This means that the observer is also quantum mechanical and gets entangled with one particular state of the system that is being measured (DeWitt und Graham, 2015, p. 116). This is some what different to the popular explanation of many worlds but has the same results and is, at least to the author more reasonable.

An important point for the author also was that the theory accepts quantum mechanics as it is and doesn't make unreasonable assumption such as that the observer plays an important role.

On top of that this interpretation also discards the need for an “observation” in the program which would also be mathematically impossible (DeWitt und Graham, 2015, p. 111).

2.4. Complex Numbers

In quantum mechanics it's customary to work with complex numbers. Complex numbers are an extension to the real numbers, since Rust will do most of the heavy lifting here are the most important things that you should know

$$i^2 = -1$$

$$z = a + bi$$

$$\operatorname{Re}(z) = a$$

$$\operatorname{Im}(z) = b$$

$$\bar{z} = a - bi$$

$$\|z\|^2 = a^2 + b^2$$

$$e^{\theta i} = \cos(\theta) + i\sin(\theta)$$

i is the imaginary unit, z is the general form of a complex number where $\{a, b\} \in \mathbb{R}$, \bar{z} is the complex conjugate and $\|z\|^2$ is the norm square of z . The last equation is the Euler's formula, it rotates a number in the complex plane by θ radians.

The complex plane is similar to the real number line, every complex number can be represented on this plane where $\text{Re}(z)$ is the x-coordinate and $\text{Im}(z)$ is the y-coordinate.

2.5. Gnuplot

Gnuplot is a cross platform plotting program that is very simple to use. `schroedinger-approx` will output a file `data.txt`, you can plot the function by typing `gnuplot` and then typing

```
1 call "plot.gnuplot"
```

to plot the real part of the wave function, or

```
1 call "plot_3d.gnuplot"
```

to see the full complex wave function.

If you'd like to learn more about Gnuplot you can read there user manual on <http://www.gnuplot.info/>

2.6. Planck Units

By using Planck units the equations get a little bit easier. Working in Planck units means that all fundamental constants are equal to 1.

$$c = k_B = G = \hbar = 1.$$

This means that the constants will usually cancel out.

To convert to SI units we can just multiply powers of the constants such that there unit results in one of the base units.

$$\begin{aligned} l_{\text{Planck}} &= l_{\text{SI}} \sqrt{\frac{G\hbar}{c^3}} & 1 \text{ m}_{\text{Planck}} &\approx 1.616255(18) \cdot 10^{-35} \text{ m} & (\text{CODATA, 2022a}) \\ m_{\text{Planck}} &= m_{\text{SI}} \sqrt{\frac{c\hbar}{G}} & 1 \text{ kg}_{\text{Planck}} &\approx 2.176434(24) \cdot 10^{-8} \text{ kg} & (\text{CODATA, 2022b}) \\ t_{\text{Planck}} &= t_{\text{SI}} \sqrt{\frac{G\hbar}{c^5}} & 1 \text{ s}_{\text{Planck}} &\approx 5.391247(60) \cdot 10^{-44} \text{ s} & (\text{CODATA, 2022c}) \end{aligned}$$

(Gaarder Haug, 2016, Table 1)

The program will take all of its in- and outputs in Planck units.

3. Methods

3.1. Program Architecture

The program has multiple interfaces or traits as they are called in Rust that give the program some abstraction. In C is a UML diagram of the architecture. Since current version of Rust does not support manual implementations of `std::ops::Fn` we have to define our own trait for functions `Func<A, R>` where A is the type of the argument and R is the return type. Later we will use this trait to implement functions for integration, evaluation and more useful utilities.

`WaveFunction` is at the heart of the program, it contains all the functionality to build wave functions. It is composed of `WaveFunctionPart` which represent either a `Joint`, `PureWkb` or an `ApproxPart`. With the `range` function we can check when they are valid.

3.2. Newtons Method

Newton's method, also called the Newton-Raphson method, is a root-finding algorithm that uses the first few terms of the Taylor series of a function $f(x)$ in the vicinity of a suspected root (Weisstein, 2022). It makes a sequence of approximations of a root x_n that in certain cases converges to the exact value where

$$\lim_{n \rightarrow \infty} f(x_n) = 0$$

The sequence is defined as

$$x_0 = a$$
$$x_{n+1} = x_n - \frac{f(x_n)}{f'(x_n)}$$

Visually this looks like figure 3.1 $f(x) = (x - 2)(x - 1)(x + 1)$.




Figure 3.1.: Illustration of Newtons method, $f(x) = (x - 1)(x - 2)(x + 1)$.

The blue line indicates the initial guess which in this case is 2.5 the black line ($g(x)$) is a tangent to $f(x)$ at $(guess, f(guess))$ the next guess will be where the tangent intersects the x-Axis (solution of $g(x) = 0$). This will converge rather quickly compared to other methods such as Regula falsi.

```

1 pub fn newtons_method<F>(f: &F, mut guess: f64, precision: f64) -> f64
2     where
3         F: Fn(f64) -> f64,
4     {
5         loop {
6             let step = f(guess) / derivative(f, guess);
7             if step.abs() < precision {
8                 return guess;
9             } else {
10                 guess -= step;
11             }
12         }
13     }

```

In Rust the sequence is implemented with a function that takes a closure f , the initial guess $guess$ and a stop condition $precision$ the function will return if $\| \frac{f(x_n)}{f'(x_n)} \|$ is less than $precision$.

From the structure of the algorithm it is very tempting to implement it recursively, but by using a loop it is much faster since there are no unnecessary jumps and the precision can (at least in theory) be 0 without causing a stack overflow.

3.3. Regula Falsi with Bisection

Newtons method fails if the first guess is at a maximum, since the step would go to infinity. For this case we can first use a bisection search to detect a sign change. We need to do a bisection search since Regula falsi requires two guesses.

The algorithm itself is quite simple. To start we need

$$f(x) : \mathbb{R} \rightarrow \mathbb{R} \quad (3.1)$$

$$\{a \in \mathbb{R} \mid f(a) \leq 0\} \quad (3.2)$$

$$\{b \in \mathbb{R} \mid f(b) \geq 0\}. \quad (3.3)$$

Then we can draw a line between the two points $(a, f(a))$ and $(b, f(b))$. Then a becomes the x-value where the line intersects the x-axis becomes the new b , when we do the process again with the new b we will get our new value for a . We can repeat this process until we cross a fresh hold for the accuracy and the result will be the last inter section of the line with the x-axis.

3.4. Derivatives

Derivatives can be calculated numerically as in the C++ library Boost (John Maddock, 2022). The author implemented a analytical system for derivatives in Go. From that experience the benefit is negligible compared to the increase in performance and in development time since every function is a special object.

```

1 pub fn derivative<F, R>(func: &F, x: f64) -> R
2 where
3     F: Fn(f64) -> R + ?Sized,
4     R: Sub<R, Output = R> + Div<f64, Output = R> + Mul<f64, Output = R> + Add<R,
        Output = R>,
5 {
6     let dx = f64::epsilon().sqrt();
7     let dx1 = dx;
8     let dx2 = dx1 * 2.0;
9     let dx3 = dx1 * 3.0;
10
11     let m1 = (func(x + dx1) - func(x - dx1)) / 2.0;
12     let m2 = (func(x + dx2) - func(x - dx2)) / 4.0;
13     let m3 = (func(x + dx3) - func(x - dx3)) / 6.0;
14
15     let fifteen_m1 = m1 * 15.0;
16     let six_m2 = m2 * 6.0;
17     let ten_dx1 = dx1 * 10.0;
18
19     return ((fifteen_m1 - six_m2) + m3) / ten_dx1;
20 }

```

`f64::epsilon().sqrt()` is approximately 0.000000014901161. `f64::epsilon()` is the smallest double precision floating point number where $1 + \epsilon \neq 1$. this has been chosen for dx because it should be fairly precise.

3.5. Integration

The same principles apply to integrals as to derivative it would not be a great benefit to implement an analytic integration system. Integrals would also be much more difficult to implement than derivatives since integrals can not be broken down in to many smaller integrals that can be computed easily instead it needs to be solved as is.

One approach would be to use the same method as with the derivative, take the definition with the limit and use a small value but this method can be improved in this case, since integrals calculate areas under curves a trapeze is more efficient and accurate then the rectangle that results from the definition.




Figure 3.2.: Illustration of integration with trapeze from Wikipedia (2022).

Figure 3.2 shows visually how the methods work, each blue trapeze from start (a) to end (b) has an area of

$$\int_a^b f(x) dx \approx (b-a)f\left(\frac{a+b}{2}\right).$$

One trapeze would be fairly inaccurate to calculate the area under the function but as the area from a to b is subdivided further the result become better and better.

The general structure of the algorithm can very easily be run in parallel since it doesn't matter in which order the segments are added together and the segments also don't dependent on one another. In Rust this is implemented using rayon. Rayon is an implementation for parallel iterators meaning that normal data structures that implement `std::iter` can be run in parallel *just* by changing `::iter()` to `::par_iter()`. This might not work in all cases because of memory safety but in this case the borrow checker will throw an error and the code wont compile.

```
1 pub trait Func<A, R>: Sync + Send {
2     fn eval(&self, x: A) -> R;
3 }
4
5 pub struct Point {
6     pub x: f64,
7     pub y: Complex64,
8 }
```

Such that functions with states, like wave functions that store parameters, can be integrated there is a trait `Func<A, R>`.

`Point` stores both the input, x and the output, y of a function.

```
1 pub fn evaluate_function_between<X, Y>(f: &dyn Func<X, Y>, a: X, b: X, n: usize) ->
    Vec<Point<X, Y>>
2 where
3     X: Copy
4         + Send
5         + Sync
6         + std::cmp::PartialEq
7         + From<f64>
8         + std::ops::Add<Output = X>
9         + std::ops::Sub<Output = X>
10        + std::ops::Mul<Output = X>
11        + std::ops::Div<Output = X>,
12     Y: Send + Sync,
13 {
14     if a == b {
15         return vec![];
16     }
17
18     (0..n)
19         .into_par_iter()
20         .map(|i| {
```

```

21         index_to_range(
22             X::from(i as f64),
23             X::from(0.0_f64),
24             X::from((n - 1) as f64),
25             a,
26             b,
27         )
28     })
29     .map(|x: X| Point { x, y: f.eval(x) })
30     .collect()
31 }

```

Func<X, Y> can be passed to `evaluate_function_between` it calculates n points between an interval from a to b and returns a vector of Point. X and Y are general data types such that it supports as many types of numbers as possible.

```

1 pub fn integrate<
2   X: Sync + std::ops::Add<Output = X> + std::ops::Sub<Output = X> + Copy,
3   Y: Default
4     + Sync
5     + std::ops::AddAssign
6     + std::ops::Div<f64, Output = Y>
7     + std::ops::Mul<Output = Y>
8     + std::ops::Add<Output = Y>
9     + Send
10    + std::iter::Sum<Y>
11    + Copy
12    + From<X>,
13 > (
14   points: Vec<Point<X, Y>>,
15   batch_size: usize,
16 ) -> Y {
17   if points.len() < 2 {
18     return Y::default();
19   }
20
21   let batches: Vec<&[Point<X, Y>]> = points.chunks(batch_size).collect();
22
23   let parallel: Y = batches
24     .par_iter()
25     .map(|batch| {
26       let mut sum = Y::default();
27       for i in 0..(batch.len() - 1) {
28         sum += trapezoidal_approx(&batch[i], &batch[i + 1]);
29       }
30       return sum;
31     })
32     .sum();
33
34   let mut rest = Y::default();
35
36   for i in 0..batches.len() - 1 {
37     rest += trapezoidal_approx(&batches[i][batches[i].len() - 1], &batches[i + 1][0]);
38   }
39
40   return parallel + rest;
41 }

```

The actual integration happens in `integrate`, it calculates the areas of the trapezes between the points passed to it. For optimization 1000 trapezes are calculated per thread because it would take more time to create a new thread then to actually do the calculation, this has to be further investigated and 1000 might not be optimal. The calculations performed per thread are called a batch, after all batches have been calculated the boundaries between batches also has to be considered therefor they are added in the end with `rest`.

3.6. Transition Regions

The approximation that will be used splits $\Psi(x)$ into multiple parts that do not match perfectly together.




Figure 3.3.: Example for joining functions

Lets consider an example, in figure 3.6 we can see two Taylor series of cosine. Now we have to join the two functions at $x = \pi/2$ such that its a mathematically smooth transition.

$$f(x) = 1 - \frac{x^2}{2} \quad (3.4)$$

$$g(x) = \frac{(x - \pi)^2}{2} - 1 \quad (3.5)$$

As a first guess lets join $f(x)$ and $g(x)$ with a step function, this means that the joint function $h(x)$ will be

$$h(x) = \begin{cases} f(x) & x < \frac{\pi}{2} \\ g(x) & x > \frac{\pi}{2} \end{cases}.$$

This gives us 3.6 which is obviously not smooth.




Figure 3.4.: Plot of $h(x)$ with step joint

If we use the formula from (Hall, 2013, p. 325, section 15.6.4) with

$$\begin{aligned}\delta &= 0.5 \\ \alpha &= \frac{\pi}{2} - \frac{\delta}{2} \\ \chi(x) &= \sin^2\left(x \frac{\pi}{2}\right)\end{aligned}$$

this results in

$$h(x) = \begin{cases} f(x) & x < \alpha \\ g(x) & x > \alpha + \delta \\ f(x) + (g(x) - f(x))\chi\left(\frac{x - \alpha}{\delta}\right) & \text{else} \end{cases}$$

which is mathematically smooth as we can see in figure 3.6 (proof in Appendix A.1.1).




Figure 3.5.: Plot of $h(x)$ with Hall joint

3.6.1. Implementation in Rust

In the program we can define a struct `Joint` that implements `Func<f64, Complex64>`. As in the example we need two functions $f(x)$ and $g(x)$ which we will rename to `left` and `right`. We will also need a variable α and δ which will be named `cut` and `delta`.

```

1  #[derive(Clone)]
2  pub struct Joint {
3      pub left: Arc<dyn Func<f64, Complex64>>,
4      pub right: Arc<dyn Func<f64, Complex64>>,
5      pub cut: f64,
6      pub delta: f64,
7  }
8
9  impl Func<f64, Complex64> for Joint {
10     fn eval(&self, x: f64) -> Complex64 {
11         let chi = |x: f64| f64::sin(x * f64::consts::PI / 2.0).powi(2);
12         let left_val = left.eval(x);
13         return left_val + (right.eval(x) - left_val) * chi((x - self.cut) / self.
            delta)
14     }

```

15 }

In the proof we assume that $f(x)$ and $g(x)$ are continuous of first order in the interval $(\alpha, \alpha + \delta)$. In the code we will not check this requirement since it would have a major impact on performance to check the derivative on every point.

4. Calculation

4.1. Energy Levels

Solving the Schrödinger equation is an eigenvalue problem. This means that only certain energies will result in physically correct results. For an energy to be valid it has to satisfy the Maslov-corrected Bhor-Sommerfeld condition which states that

$$n \in \mathbb{N}_0 \quad (4.1)$$

$$C = \{x \in \mathbb{R} \mid V(x) < E\} \quad (4.2)$$

$$\int_C \sqrt{2m(E - V(x))} dx = 2\pi(n + 1/2) \quad (4.3)$$

this condition does not (in most cases) give the exact energy levels (Hall, 2013). It can be interpreted such that the oscillating part of the wave function has to complete all half oscillation.

To solve this problem for an arbitrary potential in a computer the set C and the fact that n has to be a non negative integer is not really helpful, but the condition can be rewritten to

$$p(x) = \begin{cases} \sqrt{2m(E - V(x))} & V(x) < E \\ 0 & \text{else} \end{cases} \quad (4.4)$$

$$\frac{1}{2\pi} \int_{-\infty}^{\infty} p(x) dx - \frac{1}{2} \mod 1 = 0 \quad (4.5)$$

Unfortunately 4.5 is not continuous which means that Newtons method can't be applied. Further on the bounds of integration have to be finite, this means the user of the program will have to specify a value for the constant APPROX_INF where any value for x out side of that range should satisfy $V(x) > E$. But it shouldn't be to big since the integrate function can only evaluate a relatively small number (default 64000) of trapezes before the performance will suffer enormously. The default value for APPROX_INF is $(-200.0, 200.0)$.

The implementation is quite strait forward we evaluate 4.5 for a number of energies and then check for discontinuities.

```
1 pub fn nth_energy<F: Fn(f64) -> f64 + Sync>(n: usize, mass: f64, pot: &F, view: (f64, f64)) -> f64 {
2     const ENERGY_STEP: f64 = 10.0;
3     const CHECKS_PER_ENERGY_STEP: usize = INTEG_STEPS;
4     let sommerfeld_cond = SommerfeldCond { mass, pot, view };
5
6     let mut energy = 0.0;
7     let mut i = 0;
```

```

8
9     loop {
10         let vals = evaluate_function_between(
11             &sommerfeld_cond,
12             energy,
13             energy + ENERGY_STEP,
14             CHECKS_PER_ENERGY_STEP,
15         );
16         let mut int_solutions = vals
17             .iter()
18             .zip(vals.iter().skip(1))
19             .collect::<Vec<&Point<f64, f64>>>>()
20             .par_iter()
21             .filter(|(p1, p2)| (p1.y - p2.y).abs() > 0.5 || p1.y.signum() != p2.y.
22                 signum())
23             .map(|ps| ps.1)
24             .collect::<Vec<&Point<f64, f64>>>>();
25         int_solutions.sort_by(|p1, p2| cmp_f64(&p1.x, &p2.x));
26         if i + int_solutions.len() > n {
27             return int_solutions[n - i].x;
28         }
29         energy += ENERGY_STEP - (ENERGY_STEP / (CHECKS_PER_ENERGY_STEP as f64 + 1.0))
30         ;
31         i += int_solutions.len();
32     }
33 }

```

First we check over the interval $(0.0, \text{ENERGY_STEP})$ if there are not enough zeros we check the next interval of energies and so on until we found n zeros. It's also possible that 4.5 is negative before the 0th energy there for we also have to check for normal zeros by comparing the signs of the values.

The struct `SommerfeldCond` is a `Func<f64, f64>` that evaluates 4.5.

4.1.1. Accuracy

For a benchmark we will use

$$\begin{aligned}
 m &= 1 \\
 V(x) &= x^2 \\
 (-\infty, \infty) &\approx (-200, 200).
 \end{aligned}$$

To get the actual values we will use Wolfram Language with WolframScript a programming language similar to Wolframalpha that can calculate the integral analytically. In Rust we can rewrite main to

```

1 fn main() {
2     let output_dir = Path::new("output");
3 }

```

```

4   let values = (0..=50)
5       .into_iter()
6       .map(|n: usize| Point::<usize, f64> {
7           x: n,
8           y: energy::nth_energy(n, 1.0, &potentials::square, APPROX_INF),
9       })
10      .collect::<Vec<Point<usize, f64>>>();
11
12      std::env::set_current_dir(&output_dir).unwrap();
13      File::create("energy.txt")
14          .unwrap()
15          .write_all(plot::to_gnuplot_string(values).as_bytes())
16          .unwrap();
17  }

```

This will output all energy levels from $n = 0$ to $n = 50$. We can implement the same thing in WolframScript

```

1  m = 1
2  V[x_] = x^2
3
4  nthEnergy[n_] = Module[{energys, energy},
5      sommerfeldIntegral[en_] = Integrate[Sqrt[2*m*(en - V[x])],
6                                          {x, -Sqrt[en], Sqrt[en]}]
7      energys = Solve[sommerfeldIntegral[en] == 2*Pi*(n + 1/2), en] // N;
8      energy = en /. energys[[1]];
9      energy
10 ]
11
12 energys = Table[{n, N@nthEnergy[n]}, {n, 0, 50}]
13
14 csv = ExportString[energys, "CSV"]
15 csv = StringReplace[csv, "," -> " "]
16 Export["output/energies_exact.dat", csv]

```

These programs will output two files `energy.txt` (Appendix B.1) for our implementation in Rust and `energies_exact.dat` (Appendix B.1) for WolframScript. As a ruff estimate we would expect an error of $\pm \frac{10}{64000} \approx \pm 1.56 \times 10^{-4}$, because the program checks for energies with that step size.




Figure 4.1.: Absolute error of energy levels in square potential

When we plot the absolute error we get figure 4.1.1. The error is a little higher than expected which is probably due to errors in the integral. Still the algorithm should be precise enough. If you'd like you could pick a lower value for `ENERGY_STEP` in `src/energy.rs:49`, but this will impact the performance for calculating energies with higher numbers for n .

4.2. Approximation Scheme

There are mainly three approximation methods used to solve for the actual wave function itself. There is perturbation theory which breaks the problem down in to ever smaller sub-problems that then can be solved exactly. This can be achieved by adding something to the Hamiltonian operator \hat{H} which can then be solved exactly. But *perturbation theory is inefficient compared to other approximation methods when calculated on a computer* (Van Mourik et al., 2014, Introduction).

The second is Density functional field theory, it has evolved over the years and is used heavily in chemistry to calculate properties of molecules and is also applicable for the time dependent Schrödinger equation. It is something that might be interesting to add to the program in the future.

The program uses the third method WKB approximation, it is applicable to a wide verity of linear differential equations and works very well in the case of the Schrödinger equation. Originally it was developed by Wentzel, Kramers and Brillouin in 1926. It gives an approximation to the eigenfunctions of the Hamiltonian \hat{H} in one dimension. The approximation is best understood as applying to a fixed range of energies as \hbar tends to zero (Hall, 2013,

p. 305).

WKB splits $\Psi(x)$ into tree parts that can be connected to form the full solution. The tree parts are described as

$$p(x) = \sqrt{2m(|E - V(x)|)} \quad (4.6)$$

$$V(t) - E = 0 \quad (4.7)$$

$$\psi_{exp}^{WKB}(x) = \frac{c_1}{2\sqrt{p(x)}} \exp\left(-\left|\int_x^t p(y)dy\right|\right) \quad (4.8)$$

$$\psi_{osz}^{WKB}(x) = \frac{c_1}{\sqrt{p(x)}} \cos\left(\int_x^t p(y)dy - \delta\right) \quad (4.9)$$

$$u_1 = -2m \frac{dV}{dx}(t) \quad (4.10)$$

$$\psi^{Airy}(x) = \frac{c_1 \sqrt{\pi}}{\sqrt[6]{u_1}} \text{Ai}\left(\sqrt[3]{u_1}(t-x)\right). \quad (4.11)$$

Since equation 4.7 might have more than one solution for turning points t , we have to consider each one of them individually and in the end join them into one function.

The factor of $1/2$ in equation 4.8 is analogous to (Littlejohn, 2020, eq. 92). This means that it's only valid if the turning points aren't "too close together" (Littlejohn, 2020). This will be a problem later when we look at some solutions. Littlejohn (2020) also mentions that there are extensions to WKB that can handle these cases. It would be interesting to add those to the program in the future.




Figure 4.2.: Left half of wave function with $N_{Energy} = 5 \Rightarrow E = 11.0$, $m = 2$, $V(x) = x^2$

In figure 4.2 the three parts are visualized. The purple section on the left is the exponential decaying part $\psi_{exp}^{WKB}(x)$, equation 4.8 is a modified version of the original version as described in (Hall, 2013, p. 317, eq. 15.25) where b and a are different solutions for t of equation 4.7. The absolute symbol makes it possible to not differentiate between the case where $x < t$ and $x > t$. Further on a factor of $e^{\delta i}$ was added such that the imaginary part of $\psi_{exp}^{WKB}(x)$ is the same as in $\psi_{osz}^{WKB}(x)$.

The blue part on the right is $\psi_{osz}^{WKB}(x)$. Again equation 4.9 was expanded to result in the more general complex solution and it also works for both ψ_1 and ψ_2 in (Hall, 2013, p. 316-317, Claim 15.7). Hall (2013) assumes that $\delta = \pi/4$ which doesn't work in the simple case of $V(x) = x^2$, in figure 4.2 $\delta = 0$ was used. This will be further discussed in section ??.

4.2.1. Validity

When we look at the derivation of WKB we will see that equations 4.8 and 4.9 can only be valid if

$$p(x) = \sqrt{V(x) - E}$$

$$\left| \frac{dp}{dx}(x) \right| \ll p^2(x)$$

as Zwiebach (2018) showed in his lecture. But this would mean that WKB is only valid iff $V(x) > E$ because $p^2(x)$ would be negative otherwise. If this is the case this would imply that 4.8 can't be valid.

We will assume that this contradiction is wrong and assume that WKB is valid if

$$\left| \frac{d}{dx}(\sqrt{|V(x) - E|}) \right| < |V(x) - E|$$

4.2.2. Implementation

4.3. Turning Points

A point x where $V(x) = E$ is called a turning point. We assume that the WKB function is a good approximation in the region where

$$-\frac{1}{2m} \frac{dV}{dx}(x) \ll (V(x) - E)^2. \quad (4.12)$$

In order to do the actual calculation we need a range where the Airy function is valid. From equation 4.12 we can infer that the Airy function is valid where

$$-\frac{a}{2m} \frac{dV}{dx}(x) - (V(x) - E)^2 > 0 \quad (4.13)$$

We can assume that the Airy function is only valid in a closed interval, this means that there must be at least two roots of equation 4.13. These roots will be called turning point boundaries from now on. The factor of a is used to emulate the behavior of \ll .

The left boundary point must have a positive and the right a negative derivative. This means we can solve for roots and group them together by their derivatives.

In order to find all roots we will use a modification of Newton's method. When we find a solution, x_0 we can divide the original function by $(x - x_0)$ this means that Newton's method won't be able to find x_0 again.

Further on since we check for roots inside the interval of APPROX_INF we don't have a good first guess where the turning point might be. Because of this we will make 1000 guesses evenly distributed over the interval and invent a system that can rate how good of a guess this point could be. Newton's method works well if the value of $f(x)$ is small and $f'(x)$ is neither too small nor too big. We will assume that $f'(x) = 1$ is optimal. As a rating we will use

$$\sigma(x) = \frac{|f(x)|}{-\exp\left(\left(\frac{df}{dx}(x)\right)^2 + 1\right)}$$

where lower is better. This function is just an educated guess, but it has to have some properties, as the derivative of f tends to 0, $\sigma(x)$ should diverge to infinity.

$$\lim_{\frac{df}{dx} \rightarrow 0} \sigma(x) = \infty$$

If $f(x) = 0$ we found an actual root in the first guess meaning that $\sigma(x)$ should be 0. Formula 4.3 doesn't satisfy this property since it's undefined if $f'(x) = 0$ and $f(x) = 0$, but we can extend it's definition such that

$$\sigma(x) = \begin{cases} \frac{|f(x)|}{-\exp\left(\left(\frac{df}{dx}(x)\right)^2 + 1\right)} & f(x) \neq 0 \text{ and } \frac{df}{dx} \neq 0 \\ 0 & \text{else} \end{cases}$$




Figure 4.3.: Logarithmic heat diagram of $\sigma(x)$, darker/bluer is better

As we can see in figure 4.3 where darker/bluer values are better than yellow/red areas that $\sigma(x)$ indeed has all of the desired properties.

After we rated all of the 1000 guesses we can pick the best one as a first guess and use the modified Newtons method with it. We do this process 256 times by default. In theory we could therefor use the WKB approximation for potentials with up to 256 turning points.

```
1 fn find_zeros(phase: &Phase, view: (f64, f64)) -> Vec<f64> {
2   let phase_clone = phase.clone();
3   let validity_func = Arc::new(move |x: f64| {
```

```

4      1.0 / (2.0 * phase_clone.mass).sqrt() * derivative(&|t| (phase_clone.
      potential)(t), x).abs()
5      - ((phase_clone.potential)(x) - phase_clone.energy).pow(2)
6  });
7  let mut zeros = NewtonsMethodFindNewZero::new(ValidityFunc, ACCURACY, 1e4 as
      usize);
8
9  (0..MAX_TURNING_POINTS).into_iter().for_each(|_| {
10     let modified_func = |x| zeros.modified_func(x);
11
12     let guess = make_guess(&modified_func, view, 1000);
13     guess.map(|g| zeros.next_zero(g));
14 });
15
16 let view = if view.0 < view.1 {
17     view
18 } else {
19     (view.1, view.0)
20 };
21 let unique_zeros = zeros
22     .get_previous_zeros()
23     .iter()
24     .filter(|x| **x > view.0 && **x < view.1)
25     .map(|x| *x)
26     .collect::<Vec<f64>>();
27 return unique_zeros;
28 }

```

Here `make_guess` uses $\sigma(x)$ and returns the best guess. `NewtonsMethodFindNewZero` is the modified version of Newton's method where all the roots are stored and its implementation of `Func<f64, f64>` is just defined as

$$\frac{f(x)}{\prod_{r \in Z} (x - r)} \quad (4.14)$$

Where the set Z is the set of all the zeros that have been found previously. After the 256 iterations we filter out all the zeros that aren't in the view. Equation 4.14 is implemented in `NewtonsMethodFindNewZero`. Unfortunately this procedure can't be implemented asynchronously since you have to know all previous zeros before you can find a new one.

Once we found the zeros we need to group them as previously mentioned the derivative of the validity function (4.13) must be positive if the boundary point is on the left and negative when it's on the right side of the turning point. It could be the case that if the turning point is in the view that one of the boundary points is actually outside the view. For this we can use Regula falsi combined with bisection. We will do this for both the left and right most turning point if there was only one boundary found.

4.4. Wave Function Parts

All the equations of

4.5. Wave Function

To combine all the WaveFunctionPart structs, we will define the WaveFunction struct. Under the hood it will also calculate all the variables and construct all the WaveFunctionPart structs.

First we need to calculate the energy for the given parameters that are passed to the constructor. Note the this energy will also be printed to the terminal.

```
1 let energy = energy::nth_energy(n_energy, mass, &potential, approx_inf);
2 println!("{}", Energy::{: .9}, Ordinal(n_energy).to_string(), energy);
```

Using the energy we can calculate the view. For this we need to find the two outermost turning points. This can be done by applying Newtons method to

$$V(x) - E$$

with initial guesses `approx_inf.0` for `lower_bound` and `approx_inf.1` for `upper_bound`. The view will then be

```
1 (
2     lower_bound * (upper_bound - lower_bound) * view_factor,
3     upper_bound * (upper_bound - lower_bound) * view_factor,
4 )
```

If Newtons method fails we will define the view to be `approx_inf`.

Once we've got the view, we can calculate all the turning points and there Airy functions along with them, using `AiryWaveFunction::new`. In the case that there are turning points we can then take go through each turning point and also copy it's neighbors. For the outer most turning points we will take `approx_inf`.

With these groups of 3 we can construct a `WkbWaveFunction` for each of the turning points. However there were issues when dividing the oscillating part of the wave function was split into two parts with different turning points. According to Hall (2013) it should be mathematically indistinguishable when using either of the turning points, but there arise discontinuities at the transition region. Because of that it has been decided that only the left turning point will be used.

Unfortunately in this method even though the function is continuous it will not be symmetric about the mid point of the oscillating region. This has the effect that the probabilities will be lower on the right none the less they should have the same probability. Because of the architecture of the program the oscillating part will still be split into two distinct regions.

While iterating over the turning points we can also calculate the ranges in which the functions are valid.

Once we have all the `WkbWaveFunction` instances we need to group them with the `AiryWaveFunction` instances. Using those pairs we can finally construct all the `ApproxPart` instances.

Finally we need to apply the scaling which may be one of the following options (where $a \in \mathbb{C}$):

None The solution wont be multiplied by anything.

Mul(a) The solution will be multiplied by a .

Renormalize(a) $\Psi(x)$ will be renormalized such that $\int_{-\infty}^{\infty} |a\Psi(x)|^2 dx = 1$. This can be useful to add a phase to the wave function.

In the case that no turning points are found WKB will be inaccurate. But for completeness we will assume that `approx_inf` is a turning point. Then we can insert two `WkbWaveFunction` instances without the Airy functions. This behavior is implemented in `PureWkb`. Afterwards we apply the same scaling procedure (4.5) as if there were turning points.

In this case you'll also get a warning in the terminal that no turning points were found. Because the results can be inaccurate.

4.5.1. Super Position

Because the super position principal is also applicable to energies it is possible that $\Psi(x)$ is a sum of wave functions with different energies.

On the implementation side this means that we can create a struct `SuperPosition` that is constructed with a list of energy levels and `ScalingType` that can be used to construct the previously discussed `WaveFunction`. Its implementation of `Func<f64, Complex64>` will then sum over all the results of the individual `WaveFunction` structs.

5. Program Manual

In the `src` directory you will find the `main.rs` file. After the imports (lines with `use`) you can find all the constants that can be configured. In the description below, (E) stands for “expert” and means that you should use the default unless you really know what you’re doing.

Concurrency Configurations Tune accuracy and performance

INTEG_STEPS The number of steps that will be used to integrate over an interval

TRAPEZE_PER_THREAD (E) The number of trapezes that are calculated on a thread in sequence. This number must be smaller than `INTEG_STEPS`.

NUMBER_OF_POINTS The number of points that will be written to the output file.

APPROX_INF These are the values for “ $\pm\infty$ ”. Where the first number is $-\infty$ and the second number is ∞ . Most importantly outside of this interval $V(x) > E$.

Joint configuration Adjust the width of joints

AIRY_TRANSITION_FRACTION (E) When a joint between an Airy and a WKB function has to be added, we have to know how wide the joint should be. The width is calculated by taking the distance between the turning point boundaries and multiplying it by this number.

ENABLE_WKB_JOINTS If set to `true` joints will be added between Airy and WKB wave function parts. If set to `false` no joints will be added at this boundary.

VALIDITY_LL_FACTOR (E) This factor gets used as a in 4.13. Higher values will create larger ranges for Airy functions.

5.1. Wave Function

When you only have one energy level you should use `WaveFunction::new`.

```
1  let wave_function = wave_function_builder::WaveFunction::new(  
2      &/*potential*/,  
3      /*mass*/,  
4      /*nth energy*/,  
5      APPROX_INF,  
6      1.5,  
7      ScalingType::/*Scaling*/,  
8  );
```

The example above has to be placed right after the `fn main()` line. You have to replace all the commentaries (`/*...*/`) with the values you want. For the first you can choose a potential from section 5.4 for this you can type `potentials::/*potential*/`.

For the Mass you can just use a normal float.

“nth energy ” must be a positive integer (including 0) and is the nth energy level of the potential.

And as for the scaling type, choose one of the options described at the end of section ??.

5.2. SuperPosition

To construct a super position you can add this to your main function

```
1 let wave_function = wave_function_builder::SuperPosition::new(  
2     &/*potential*/,  
3     /*mass*/,  
4     &[  
5         (/*nth energy*/, /*phase*/),  
6         (/*nth energy*/, /*phase*/),  
7         // ...  
8     ],  
9     APPROX_INF,  
10    1.5, // view factor  
11    ScalingType::/*scaling*/),  
12 );
```

Just like in section 5.1 you have to replace all the commentaries (`/*...*/`) with the values you want.

“potential” you have to choose a potential from section 5.4.

“mass” your mass as a float.

“nth energy ” must be a positive integer (including 0) and is the nth energy level of the potential.

“phase” a complex number that the wave function with the corresponding energy will be multiplied by. To make a complex number you can use `complex(/*Re*/, /*Im*/)`.

“// ...” you can add as many energies as your computer can handle.

And as for the scaling type, choose one of the options described at the end of section ??.

5.3. Plotting

For all the plotting methods mentioned below you’ll need an output directory in which the files will be placed.

```
1 let output_dir = Path::new("output");
```

The default is `output`, you can choose any directory name that you’d like. The folder will be located where you ran the program. The data calculated by the program will be stored as space separated values like in the example below (the first line will not be in the output file).

x	Re	Im
1.0	2.718	3.141
2.0	1.414	1.465

Every line is a data point where the first number is the x-coordinate, the second the real part of $\Psi(x)$ and the third the imaginary part of $\Psi(x)$

5.3.1. WaveFunction

For a WaveFunction as we've seen in section 5.1 you have three options.

plot_wavefunction

With `plot::plot_wavefunction` the result will be plotted as one function in gnuplot.

```
1 plot::plot_wavefunction(&wave_function, output_dir, "data.txt");
```

You can replace *data.txt* with another file name.


plot_wavefunction_parts

plot_probability

5.4. Potentials


square Normal square potential as used in Hall (2013).

$$x^2$$




mexican_hat 4th degree polynomial that looks like a mexican hat, with 2 minima.

$$(x-4)^2(x+4)^2$$




double_mexican_hat 6th degree polynomial that has 3 minima.

$$(x-4)^2x^2(x+4)^2$$



triple_mexican_hat 8th degree polynomial that has 4 minima.

$$(x-6)^2(x-3)^2(x+3)^2(x+6)^2$$



smooth_step Step function that goes to `ENERGY_INF` outside the interval $(-5, 5)$. Joints were added at ± 5 to make the function differentiable.

5.4.1. Custom Potentials

To create a custom potential you'll have to define a function like shown below.

```
1 fn my_potential(x: f64) -> f64 {  
2     return /*some calculation*/;  
3 }
```

`my_potential` is the name that you can choose and have to use later when you're passing it to `WaveFunction::new`. `/*some calculation*/` can be any Rust code that results in a `f64`.

Examples

Negative bell curve $(-e^{-x^2} + 1)$

```
1 fn neg_bell(x: f64) -> f64 {  
2     return -(-x.powi(2)).exp();  
3 }
```

General polynomial (might not work for all configurations)

```
1 const COEFFICIENTS: [f64;4] = [a, b, c, d]  
2 fn polynomial(x: f64) -> f64 {
```

```
3   let mut result = 0.0;
4   for n in 0..COEFFICIENTS.len() {
5       result += x.powi(n) * COEFFICIENTS[n];
6   }
7   return result;
8 }
```

You need to set values for a, b, etc. and they need to be floating point numbers or you'll get error E0308. For example 1 would cause an error but 1.0 or 3.141 are correct. You can add even more coefficients if you'd like. The 4 in the square brackets is the degree of the polynomial plus 1. The potential above would mathematically be $a + bx + cx^2 + dx^3$.

A. Detailed Calculations

A.1. Proofs

A.1.1. Smoothness of Transitionfunction

Given that

$$f : \mathbb{R} \rightarrow \mathbb{C} \quad (\text{A.1})$$

$$g : \mathbb{R} \rightarrow \mathbb{C} \quad (\text{A.2})$$

$$\{f, g\} \in C^1 \quad (\text{A.3})$$

$$\{\alpha, \delta\} \in \mathbb{C} \quad (\text{A.4})$$

define (Hall, 2013)

$$\chi(x) = \sin^2\left(\frac{\pi(x - \alpha)}{2\delta}\right) \quad (\text{A.5})$$

$$(f \sqcup g)(x) = f(x) + (g(x) - f(x))\chi(x) \quad (\text{A.6})$$

and proof that

$$\frac{d(f \sqcup g)}{dx}(\alpha) = \frac{df}{dx}(\alpha) \quad (\text{A.7})$$

$$\frac{d(f \sqcup g)}{dx}(\alpha + \delta) = \frac{dg}{dx}(\alpha + \delta). \quad (\text{A.8})$$

Calculate derivatives

$$\frac{d\chi}{dx}(x) = \frac{\pi}{2\delta} \sin\left(\frac{\pi(x - \alpha)}{\delta}\right) \quad (\text{A.9})$$

$$\frac{d(f \sqcup g)}{dx}(x) = \frac{df}{dx}(x) + \left(\frac{dg}{dx}(x) - \frac{df}{dx}(x)\right)\chi(x) + (g(x) - f(x))\frac{d\chi}{dx}(x). \quad (\text{A.10})$$

Note that

$$\frac{d\chi}{dx}(\alpha) = 0 \quad (\text{A.11})$$

$$\chi(\alpha) = 0 \quad (\text{A.12})$$

$$\frac{d\chi}{dx}(\alpha + \delta) = 0 \quad (\text{A.13})$$

$$\chi(\alpha + \delta) = 1 \quad (\text{A.14})$$

therefor

$$\frac{d(f \sqcup g)}{dx}(\alpha) = \frac{df}{dx}(\alpha) + 0 \left(\frac{dg}{dx}(\alpha) - \frac{df}{dx}(\alpha) \right) + 0(g(x) - f(x)) = \frac{df}{dx}(\alpha) \quad (\text{A.15})$$

and

$$\frac{d(f \sqcup g)}{dx}(\alpha + \delta) = \frac{df}{dx}(\alpha + \delta) + 1 \left(\frac{dg}{dx}(\alpha + \delta) - \frac{df}{dx}(\alpha + \delta) \right) + 0(g(x) - f(x)) \quad (\text{A.16})$$

$$\frac{d(f \sqcup g)}{dx}(\alpha + \delta) = \frac{df}{dx}(\alpha + \delta) + \frac{dg}{dx}(\alpha + \delta) - \frac{df}{dx}(\alpha + \delta) = \frac{dg}{dx}(\alpha + \delta) \blacksquare. \quad (\text{A.17})$$

B. Data Files

B.1. Energies

energy.txt	energies_exact.dat
1 0 1.4143970999546869	1 0 1.4142135623730951
2 1 4.2427225425397275	2 1 4.242640687119286
3 2 7.071360490007656	3 2 7.0710678118654755
4 3 9.89984218503414	4 3 9.899494936611665
5 4 12.727855127619105	5 4 12.727922061357857
6 5 15.55633682264559	6 5 15.556349186104047
7 6 18.384818517672073	7 6 18.38477631085024
8 7 21.213143965139928	8 7 21.213203435596427
9 8 24.041938165049302	9 8 24.041630560342618
10 9 26.870419860075785	10 9 26.870057685088806
11 10 29.69843279777794	11 10 29.698484809834998
12 11 32.52722700257012	12 11 32.526911934581186
13 12 35.35570869759661	13 12 35.35533905932738
14 13 38.18372163529877	14 13 38.18376618407357
15 14 41.012203335208056	15 14 41.01219330881976
16 15 43.84099753511743	16 15 43.84062043356595
17 16 46.66901047281958	17 16 46.66904755831214
18 17 49.49733591540462	18 17 49.49747468305833
19 18 52.32628637263825	19 18 52.32590180780452
20 19 55.15445556278185	20 19 55.15432893255071
21 20 57.98309351024977	21 20 57.9827560572969
22 21 60.811106452834736	22 21 60.81118318204309
23 22 63.64005690518555	23 22 63.63961030678928
24 23 66.46853860021204	24 23 66.46803743153548
25 24 69.29639528547274	25 24 69.29646455628166
26 25 72.1247207329406	26 25 72.12489168102785
27 26 74.95335868040853	27 26 74.95331880577405
28 27 77.78168412299357	28 27 77.78174593052023
29 28 80.61047832778574	29 28 80.61017305526643
30 29 83.43927252769512	30 29 83.43860018001261
31 30 86.26697296051438	31 30 86.2670273047588
32 31 89.09561090798232	32 31 89.095454429505
33 32 91.92378010300872	33 32 91.92388155425118
34 33 94.75288680780098	34 33 94.75230867899738
35 34 97.58121225038602	35 34 97.58073580374356
36 35 100.40938144541242	36 35 100.40916292848975
37 36 103.23739438311458	37 36 103.23759005323595
38 37 106.06587607814106	38 37 106.06601717798213

39 38 108.89435777316754
40 39 111.72299572551829
41 40 114.55178992542766
42 41 117.38027162045414
43 42 120.2082845630391
44 43 123.0364537531827
45 44 125.86493544820918
46 45 128.69341714323565
47 46 131.52174259070352
48 47 134.35053679061292
49 48 137.17854972831506
50 49 140.0071876806658
51 50 142.83566937569228

39 38 108.89444430272833
40 39 111.72287142747452
41 40 114.5512985522207
42 41 117.3797256769669
43 42 120.20815280171308
44 43 123.03657992645928
45 44 125.86500705120547
46 45 128.69343417595167
47 46 131.52186130069785
48 47 134.35028842544403
49 48 137.17871555019022
50 49 140.00714267493643
51 50 142.83556979968262

C. Source Code




Figure C.1.: UML diagram of program architecture

The source code is also available on the authors GitHub
<https://github.com/Gian-Laager/Schroedinger-Approximation>

src/main.rs

```
1  #![allow(dead_code)]
2
3  mod airy;
4  mod airy_wave_func;
5  mod check;
6  mod energy;
7  mod integrals;
8  mod newtons_method;
9  mod plot;
10 mod potentials;
11 mod tui;
12 mod turning_points;
13 mod utils;
14 mod wave_function_builder;
15 mod wkb_wave_func;
16
17 use crate::airy::airy_ai;
18 use crate::airy_wave_func::AiryWaveFunction;
19 use crate::integrals::*;
20 use crate::newtons_method::derivative;
21 use crate::utils::Func;
22 use crate::utils::*;
23 use crate::wave_function_builder::*;
24 use crate::wkb_wave_func::WkbWaveFunction;
25 use num::complex::Complex64;
26 use num::pow::Pow;
27 use rayon::iter::*;
28 use std::f64;
29 use std::fs::File;
30 use std::io::Write;
31 use std::path::Path;
32 use std::sync::Arc;
33
34 const INTEG_STEPS: usize = 64000;
35 const TRAPEZE_PER_THREAD: usize = 1000;
36 const NUMBER_OF_POINTS: usize = 100000;
37
38 const AIRY_TRANSITION_FRACTION: f64 = 0.5;
39 const ENABLE_AIRY_JOINTS: bool = true;
40
41 const VALIDITY_LL_FACTOR: f64 = 3.5;
42
43 const APPROX_INF: (f64, f64) = (-200.0, 200.0);
```

```

44
45 fn main() {
46     // let wave_function = wave_function_builder::WaveFunction::new(
47     //     &potentials::square,
48     //     1.0,
49     //     17,
50     //     APPROX_INF,
51     //     0.15,
52     //     ScalingType::Renormalize(1.0.into()),
53     // );
54
55     let wave_function = wave_function_builder::SuperPosition::new(
56         &potentials::mexican_hat,
57         1.0,
58         &[
59             (15, 1.0.into()),
60             (16, complex(0.0, 1.0 * f64::consts::PI / 8.0).exp()),
61             (17, complex(0.0, 2.0 * f64::consts::PI / 8.0).exp()),
62             (18, complex(0.0, 3.0 * f64::consts::PI / 8.0).exp()),
63             // (15, complex(0.0, 2.0 * f64::consts::PI / 3.0).exp()),
64         ],
65         APPROX_INF,
66         0.15,
67         ScalingType::Renormalize(complex(1.0, 0.0)),
68     );
69
70     let output_dir = Path::new("output");
71
72     // For WaveFunction
73     // plot::plot_wavefunction(&wave_function, output_dir, "data.txt");
74     // plot::plot_wavefunction_parts(&wave_function, output_dir, "data.txt");
75     // plot::plot_probability(&wave_function, output_dir, "data.txt");
76
77     // For SuperPosition
78     plot::plot_superposition(&wave_function, output_dir, "data.txt");
79     // plot::plot_probability_super_pos(&wave_function, output_dir, "data.txt");
80 }

```

src/airy.rs

```

1  /* automatically generated by rust-bindgen 0.59.2 */
2  #![allow(non_snake_case)]
3  #![allow(deref_nullptr)]
4  #![allow(non_camel_case_types)]
5
6  #[derive(PartialEq, Copy, Clone, Hash, Debug, Default)]
7  #[repr(C)]
8  pub struct __BindgenComplex<T> {
9      pub re: T,

```

```

10     pub im: T,
11 }
12 pub type size_t = ::std::os::raw::c_ulong;
13 pub type wchar_t = ::std::os::raw::c_int;
14 #[repr(C)]
15 #[repr(align(16))]
16 #[derive(Debug, Copy, Clone)]
17 pub struct max_align_t {
18     pub __clang_max_align_nonce1: ::std::os::raw::c_longlong,
19     pub __bindgen_padding_0: u64,
20     pub __clang_max_align_nonce2: u128,
21 }
22 #[test]
23 fn bindgen_test_layout_max_align_t() {
24     assert_eq!(
25         ::std::mem::size_of::<max_align_t>(),
26         32usize,
27         concat!("Size of: ", stringify!(max_align_t))
28     );
29     assert_eq!(
30         ::std::mem::align_of::<max_align_t>(),
31         16usize,
32         concat!("Alignment of ", stringify!(max_align_t))
33     );
34     assert_eq!(
35         unsafe {
36             &(*(::std::ptr::null::<max_align_t>())).__clang_max_align_nonce1 as *
37                 const _ as usize
38         },
39         0usize,
40         concat!(
41             "Offset of field: ",
42             stringify!(max_align_t),
43             ":",
44             stringify!(__clang_max_align_nonce1)
45         )
46     );
47     assert_eq!(
48         unsafe {
49             &(*(::std::ptr::null::<max_align_t>())).__clang_max_align_nonce2 as *
50                 const _ as usize
51         },
52         16usize,
53         concat!(
54             "Offset of field: ",
55             stringify!(max_align_t),
56             ":",
57             stringify!(__clang_max_align_nonce2)
58         )
59     );

```

```

57     );
58 }
59 #[repr(C)]
60 #[derive(Debug, Copy, Clone)]
61 pub struct _GoString_ {
62     pub p: *const ::std::os::raw::c_char,
63     pub n: isize,
64 }
65 #[test]
66 fn bindgen_test_layout__GoString_() {
67     assert_eq!(
68         ::std::mem::size_of::<_GoString_>(),
69         16usize,
70         concat!("Size_of: ", stringify!(_GoString_))
71     );
72     assert_eq!(
73         ::std::mem::align_of::<_GoString_>(),
74         8usize,
75         concat!("Alignment_of ", stringify!(_GoString_))
76     );
77     assert_eq!(
78         unsafe { &(*(::std::ptr::null::<_GoString_>())).p as *const _ as usize },
79         0usize,
80         concat!(
81             "Offset_of_field: ",
82             stringify!(_GoString_),
83             "::",
84             stringify!(p)
85         )
86     );
87     assert_eq!(
88         unsafe { &(*(::std::ptr::null::<_GoString_>())).n as *const _ as usize },
89         8usize,
90         concat!(
91             "Offset_of_field: ",
92             stringify!(_GoString_),
93             "::",
94             stringify!(n)
95         )
96     );
97 }
98 pub type GoInt8 = ::std::os::raw::c_schar;
99 pub type GoUint8 = ::std::os::raw::c_uchar;
100 pub type GoInt16 = ::std::os::raw::c_short;
101 pub type GoUint16 = ::std::os::raw::c_ushort;
102 pub type GoInt32 = ::std::os::raw::c_int;
103 pub type GoUint32 = ::std::os::raw::c_uint;
104 pub type GoInt64 = ::std::os::raw::c_longlong;
105 pub type GoUint64 = ::std::os::raw::c_ulonglong;

```

```

106 pub type GoInt = GoInt64;
107 pub type GoUint = GoUint64;
108 pub type GoUintptr = ::std::os::raw::c_ulong;
109 pub type GoFloat32 = f32;
110 pub type GoFloat64 = f64;
111 pub type GoComplex64 = __BindgenComplex<f32>;
112 pub type GoComplex128 = __BindgenComplex<f64>;
113 pub type _check_for_64_bit_pointer_matching_GoInt = [::std::os::raw::c_char; 1usize];
114 pub type GoString = _GoString_;
115 pub type GoMap = *mut ::std::os::raw::c_void;
116 pub type GoChan = *mut ::std::os::raw::c_void;
117 #[repr(C)]
118 #[derive(Debug, Copy, Clone)]
119 pub struct GoInterface {
120     pub t: *mut ::std::os::raw::c_void,
121     pub v: *mut ::std::os::raw::c_void,
122 }
123 #[test]
124 fn bindgen_test_layout_GoInterface() {
125     assert_eq!(
126         ::std::mem::size_of::<GoInterface>(),
127         16usize,
128         concat!("Size of: ", stringify!(GoInterface))
129     );
130     assert_eq!(
131         ::std::mem::align_of::<GoInterface>(),
132         8usize,
133         concat!("Alignment of ", stringify!(GoInterface))
134     );
135     assert_eq!(
136         unsafe { &(*(::std::ptr::null::<GoInterface>())).t as *const _ as usize },
137         0usize,
138         concat!(
139             "Offset of field: ",
140             stringify!(GoInterface),
141             ":",
142             stringify!(t)
143         )
144     );
145     assert_eq!(
146         unsafe { &(*(::std::ptr::null::<GoInterface>())).v as *const _ as usize },
147         8usize,
148         concat!(
149             "Offset of field: ",
150             stringify!(GoInterface),
151             ":",
152             stringify!(v)
153         )
154     );

```

```

155 }
156 #[repr(C)]
157 #[derive(Debug, Copy, Clone)]
158 pub struct GoSlice {
159     pub data: *mut ::std::os::raw::c_void,
160     pub len: GoInt,
161     pub cap: GoInt,
162 }
163 #[test]
164 fn bindgen_test_layout_GoSlice() {
165     assert_eq!(
166         ::std::mem::size_of::<GoSlice>(),
167         24usize,
168         concat!("Size of: ", stringify!(GoSlice))
169     );
170     assert_eq!(
171         ::std::mem::align_of::<GoSlice>(),
172         8usize,
173         concat!("Alignment of ", stringify!(GoSlice))
174     );
175     assert_eq!(
176         unsafe { &(*(::std::ptr::null::<GoSlice>())).data as *const _ as usize },
177         0usize,
178         concat!(
179             "Offset of field: ",
180             stringify!(GoSlice),
181             ":",
182             stringify!(data)
183         )
184     );
185     assert_eq!(
186         unsafe { &(*(::std::ptr::null::<GoSlice>())).len as *const _ as usize },
187         8usize,
188         concat!(
189             "Offset of field: ",
190             stringify!(GoSlice),
191             ":",
192             stringify!(len)
193         )
194     );
195     assert_eq!(
196         unsafe { &(*(::std::ptr::null::<GoSlice>())).cap as *const _ as usize },
197         16usize,
198         concat!(
199             "Offset of field: ",
200             stringify!(GoSlice),
201             ":",
202             stringify!(cap)
203         )

```



```

204     );
205 }
206 #[repr(C)]
207 #[derive(Debug, Copy, Clone)]
208 pub struct airy_ai_return {
209     pub r0: GoFloat64,
210     pub r1: GoFloat64,
211 }
212 #[test]
213 fn bindgen_test_layout_airy_ai_return() {
214     assert_eq!(
215         ::std::mem::size_of::<airy_ai_return>(),
216         16usize,
217         concat!("Size of: ", stringify!(airy_ai_return))
218     );
219     assert_eq!(
220         ::std::mem::align_of::<airy_ai_return>(),
221         8usize,
222         concat!("Alignment of ", stringify!(airy_ai_return))
223     );
224     assert_eq!(
225         unsafe { &(*(::std::ptr::null::<airy_ai_return>())).r0 as *const _ as usize },
226         0usize,
227         concat!(
228             "Offset of field: ",
229             stringify!(airy_ai_return),
230             "::",
231             stringify!(r0)
232         )
233     );
234     assert_eq!(
235         unsafe { &(*(::std::ptr::null::<airy_ai_return>())).r1 as *const _ as usize },
236         8usize,
237         concat!(
238             "Offset of field: ",
239             stringify!(airy_ai_return),
240             "::",
241             stringify!(r1)
242         )
243     );
244 }
245 extern "C" {
246     pub fn airy_ai(zr: GoFloat64, zi: GoFloat64) -> airy_ai_return;
247 }

```

src/airy_wave_func.rs

```

1 use crate::newtons_method::newtons_method;
2 use crate::newtons_method::*;
3 use crate::turning_points::*;
4 use crate::wkb_wave_func::Phase;
5 use crate::*;
6 use num::signum;
7 use std::sync::Arc;
8
9 #[allow(non_snake_case)]
10 fn Ai(x: Complex64) -> Complex64 {
11     let go_return;
12     unsafe {
13         go_return = airy_ai(x.re, x.im);
14     }
15     return complex(go_return.r0, go_return.r1);
16 }
17
18 #[allow(non_snake_case)]
19 fn Bi(x: Complex64) -> Complex64 {
20     return -complex(0.0, 1.0) * Ai(x)
21         + 2.0 * Ai(x * complex(-0.5, 3.0_f64.sqrt() / 2.0)) * complex(3_f64.sqrt() /
22             2.0, 0.5);
23 }
24
25 #[derive(Clone)]
26 pub struct AiryWaveFunction {
27     c: Complex64,
28     u_1: f64,
29     pub turning_point: f64,
30     phase: Arc<Phase>,
31     pub ts: (f64, f64),
32     op: fn(Complex64) -> Complex64,
33     phase_off: f64,
34 }
35
36 impl AiryWaveFunction {
37     pub fn get_op(&self) -> Box<fn(Complex64) -> Complex64> {
38         Box::new(self.op)
39     }
40
41     fn get_u_1_cube_root(u_1: f64) -> f64 {
42         signum(u_1) * u_1.abs().pow(1.0 / 3.0)
43     }
44
45     pub fn new<'a>(phase: Arc<Phase>, view: (f64, f64)) -> (Vec<AiryWaveFunction>,
46         TGroup) {
47         let phase = phase;
48         let turning_point_boundaries = turning_points::calc_ts(phase.as_ref(), view);

```

```

48     let funcs: Vec<AiryWaveFunction> = turning_point_boundaries
49         .ts
50         .iter()
51         .map(|((t1, t2), _)| {
52             let x_1 = newtons_method(
53                 &|x| (phase.potential)(x) - phase.energy,
54                 (*t1 + *t2) / 2.0,
55                 1e-7,
56             );
57             let u_1 = 2.0 * phase.mass * -derivative(phase.potential.as_ref(),
58                 x_1);
59             // let u_1 = |x| -2.0 * phase.mass * ((phase.potential)(&x) - phase.
60                 energy) / (H_BAR * H_BAR * (x - x_1));
61
62             AiryWaveFunction {
63                 u_1,
64                 turning_point: x_1,
65                 phase: phase.clone(),
66                 ts: (*t1, *t2),
67                 op: identity,
68                 c: 1.0.into(),
69                 phase_off: 0.0,
70             }
71         })
72         .collect::<Vec<AiryWaveFunction>>();
73     return (funcs, turning_point_boundaries);
74 }
75
76 pub fn with_op(&self, op: fn(Complex64) -> Complex64) -> AiryWaveFunction {
77     AiryWaveFunction {
78         u_1: self.u_1,
79         turning_point: self.turning_point,
80         phase: self.phase.clone(),
81         ts: self.ts,
82         op,
83         c: self.c,
84         phase_off: self.phase_off,
85     }
86 }
87
88 pub fn with_c(&self, c: Complex64) -> AiryWaveFunction {
89     AiryWaveFunction {
90         u_1: self.u_1,
91         turning_point: self.turning_point,
92         phase: self.phase.clone(),
93         ts: self.ts,
94         op: self.op,
95         c,
96         phase_off: self.phase_off,

```

```

95     }
96 }
97
98 pub fn with_phase_off(&self, phase_off: f64) -> AiryWaveFunction {
99     AiryWaveFunction {
100         u_1: self.u_1,
101         turning_point: self.turning_point,
102         phase: self.phase.clone(),
103         ts: self.ts,
104         op: self.op,
105         c: self.c,
106         phase_off,
107     }
108 }
109 }
110
111 impl Func<f64, Complex64> for AiryWaveFunction {
112     fn eval(&self, x: f64) -> Complex64 {
113         let u_1_cube_root = Self::get_u_1_cube_root(self.u_1);
114
115         if self.u_1 < 0.0 {
116             return self.c
117                 * ((std::f64::consts::PI.sqrt() / (self.u_1).abs().pow(1.0 / 6.0))
118                   * Ai(complex(u_1_cube_root * (self.turning_point - x), 0.0)))
119                 as Complex64;
120         } else {
121             return self.c
122                 * ((std::f64::consts::PI.sqrt() / (self.u_1).abs().pow(1.0 / 6.0))
123                   * Ai(complex(u_1_cube_root * (self.turning_point - x), 0.0)))
124                 as Complex64;
125         }
126     }
127 }
128
129 #[cfg(test)]
130 mod test {
131     use super::*;
132
133     #[test]
134     fn airy_func_plot() {
135         let output_dir = Path::new("output");
136         std::env::set_current_dir(&output_dir).unwrap();
137
138         let airy_ai = Function::new(|x| Ai(complex(x, 0.0)));
139         let airy_bi = Function::new(|x| Bi(complex(x, 0.0)));
140         let values = evaluate_function_between(&airy_ai, -10.0, 5.0, NUMBER_OF_POINTS
141         );
142
143         let mut data_file = File::create("airy.txt").unwrap();

```

```

143
144     let data_str_ai: String = values
145         .par_iter()
146         .map(|p| -> String { format!("{}", p.x, p.y.re, p.y.im) })
147         .reduce(|| String::new(), |s: String, current: String| s + &*current);
148
149     let values_bi = evaluate_function_between(&airy_bi, -5.0, 2.0,
        NUMBER_OF_POINTS);
150
151     let data_str_bi: String = values_bi
152         .par_iter()
153         .map(|p| -> String { format!("{}", p.x, p.y.re, p.y.im) })
154         .reduce(|| String::new(), |s: String, current: String| s + &*current);
155
156     data_file
157         .write_all((data_str_ai + "\n\n" + &*data_str_bi).as_ref())
158         .unwrap()
159 }
160 }

```

src/check.rs

```

1 use crate::*;
2
3 pub struct SchroedingerError<'a> {
4     pub wave_func: &'a WaveFunction,
5 }
6
7 impl Func<f64, Complex64> for SchroedingerError<'_> {
8     fn eval(&self, x: f64) -> Complex64 {
9         complex(-1.0 / (2.0 * self.wave_func.get_phase().mass), 0.0)
10             * Derivative {
11                 f: &Derivative { f: self.wave_func },
12             }
13             .eval(x)
14             + ((self.wave_func.get_phase().potential)(x) - self.wave_func.get_phase()
15                 .energy)
16                 * self.wave_func.eval(x)
17 }

```

src/energy.rs

```

1 use crate::*;
2
3 struct Integrand<'a, F: Fn(f64) -> f64 + Sync> {
4     mass: f64,
5     pot: &'a F,
6     energy: f64,

```

```

7 }
8
9 impl<F: Fn(f64) -> f64 + Sync> Func<f64, f64> for Integrand<'_, F> {
10     fn eval(&self, x: f64) -> f64 {
11         let pot = (self.pot)(x);
12
13         if !pot.is_finite() {
14             return 0.0;
15         }
16
17         if pot < self.energy {
18             return (2.0 * self.mass * (self.energy - pot)).sqrt();
19         } else {
20             return 0.0;
21         }
22     }
23 }
24
25 struct SommerfeldCond<'a, F: Fn(f64) -> f64 + Sync> {
26     mass: f64,
27     pot: &'a F,
28     view: (f64, f64),
29 }
30
31 impl<F: Fn(f64) -> f64 + Sync> Func<f64, f64> for SommerfeldCond<'_, F> {
32     fn eval(&self, energy: f64) -> f64 {
33         let integrand = Integrand {
34             mass: self.mass,
35             pot: self.pot,
36             energy,
37         };
38         let integral = integrate(
39             evaluate_function_between(&integrand, self.view.0, self.view.1,
40                                     INTEG_STEPS),
41             TRAPEZE_PER_THREAD,
42         );
43         return ((integral - f64::consts::PI) / f64::consts::PI) % 1.0;
44     }
45 }
46
47 pub fn nth_energy<F: Fn(f64) -> f64 + Sync>(n: usize, mass: f64, pot: &F, view: (f64,
48     f64)) -> f64 {
49     const ENERGY_STEP: f64 = 10.0;
50     const CHECKS_PER_ENERGY_STEP: usize = INTEG_STEPS;
51     let sommerfeld_cond = SommerfeldCond { mass, pot, view };
52
53     let mut energy = 0.0; // newtons_method_non_smooth(&|e| sommerfeld_cond.eval(e),
54         1e-7, 1e-7);
55     let mut i = 0;

```

```

53
54     loop {
55         let vals = evaluate_function_between(
56             &sommerfeld_cond,
57             energy,
58             energy + ENERGY_STEP,
59             CHECKS_PER_ENERGY_STEP,
60         );
61         let mut int_solutions = vals
62             .iter()
63             .zip(vals.iter().skip(1))
64             .collect::<Vec<&Point<f64, f64>, &Point<f64, f64>>>()
65             .par_iter()
66             .filter(|(p1, p2)| (p1.y - p2.y).abs() > 0.5 || p1.y.signum() != p2.y.
67                 signum())
68             .map(|ps| ps.1)
69             .collect::<Vec<&Point<f64, f64>>>();
70         int_solutions.sort_by(|p1, p2| cmp_f64(&p1.x, &p2.x));
71         if i + int_solutions.len() > n {
72             return int_solutions[n - i].x;
73         }
74         energy += ENERGY_STEP - (ENERGY_STEP / (CHECKS_PER_ENERGY_STEP as f64 + 1.0))
75         ;
76         i += int_solutions.len();
77     }
78 }

```

src/integrals.rs

```

1  use crate::*;
2  use rayon::prelude::*;
3
4  #[allow(non_camel_case_types)]
5  #[derive(Clone)]
6  pub struct Point<T_X, T_Y> {
7      pub x: T_X,
8      pub y: T_Y,
9  }
10
11 pub fn trapezoidal_approx<X, Y>(start: &Point<X, Y>, end: &Point<X, Y>) -> Y
12 where
13     X: std::ops::Sub<Output = X> + Copy,
14     Y: std::ops::Add<Output = Y>
15         + std::ops::Mul<Output = Y>
16         + std::ops::Div<f64, Output = Y>
17         + Copy
18         + From<X>,
19 {
20     return Y::from(end.x - start.x) * (start.y + end.y) / 2.0_f64;

```

```

21 }
22
23 pub fn index_to_range<T>(x: T, in_min: T, in_max: T, out_min: T, out_max: T) -> T
24 where
25     T: Copy
26         + std::ops::Sub<Output = T>
27         + std::ops::Mul<Output = T>
28         + std::ops::Div<Output = T>
29         + std::ops::Add<Output = T>,
30 {
31     return (x - in_min) * (out_max - out_min) / (in_max - in_min) + out_min;
32 }
33
34 pub fn integrate<
35     X: Sync + std::ops::Add<Output = X> + std::ops::Sub<Output = X> + Copy,
36     Y: Default
37         + Sync
38         + std::ops::AddAssign
39         + std::ops::Div<f64, Output = Y>
40         + std::ops::Mul<Output = Y>
41         + std::ops::Add<Output = Y>
42         + Send
43         + std::iter::Sum<Y>
44         + Copy
45         + From<X>,
46 >(
47     points: Vec<Point<X, Y>>,
48     batch_size: usize,
49 ) -> Y {
50     if points.len() < 2 {
51         return Y::default();
52     }
53
54     let batches: Vec<&[Point<X, Y>]> = points.chunks(batch_size).collect();
55
56     let parallel: Y = batches
57         .par_iter()
58         .map(|batch| {
59             let mut sum = Y::default();
60             for i in 0..(batch.len() - 1) {
61                 sum += trapezoidal_approx(&batch[i], &batch[i + 1]);
62             }
63             return sum;
64         })
65         .sum();
66
67     let mut rest = Y::default();
68
69     for i in 0..batches.len() - 1 {

```



```

70         rest += trapezoidal_approx(&batches[i][batches[i].len() - 1], &batches[i +
71             1][0]);
72     }
73     return parallel + rest;
74 }
75
76 pub fn evaluate_function_between<X, Y>(f: &dyn Func<X, Y>, a: X, b: X, n: usize) ->
77     Vec<Point<X, Y>>
78 where
79     X: Copy
80     + Send
81     + Sync
82     + std::cmp::PartialEq
83     + From<f64>
84     + std::ops::Add<Output = X>
85     + std::ops::Sub<Output = X>
86     + std::ops::Mul<Output = X>
87     + std::ops::Div<Output = X>,
88     Y: Send + Sync,
89 {
90     if a == b {
91         return vec![];
92     }
93     (0..n)
94         .into_par_iter()
95         .map(|i| {
96             index_to_range(
97                 X::from(i as f64),
98                 X::from(0.0_f64),
99                 X::from((n - 1) as f64),
100                 a,
101                 b,
102             )
103         })
104         .map(|x: X| Point { x, y: f.eval(x) })
105         .collect()
106 }
107
108 #[cfg(test)]
109 mod test {
110     use super::*;
111
112     fn square(x: f64) -> Complex64 {
113         return complex(x * x, 0.0);
114     }
115
116     fn square_integral(a: f64, b: f64) -> Complex64 {

```

```

117     return complex(b * b * b / 3.0 - a * a * a / 3.0, 0.0);
118 }
119
120 #[tokio::test(flavor = "multi_thread")]
121 async fn integral_of_square() {
122     let square_func: Function<f64, Complex64> = Function::new(square);
123     for i in 0..100 {
124         for j in 0..10 {
125             let a = f64::from(i - 50) / 12.3;
126             let b = f64::from(j - 50) / 12.3;
127
128             if i == j {
129                 assert_eq!(
130                     integrate(
131                         evaluate_function_between(&square_func, a, b, INTEG_STEPS
132                             ),
133                         TRAPEZE_PER_THREAD,
134                     ),
135                     complex(0.0, 0.0)
136                 );
137                 continue;
138             }
139
140             let epsilon = 0.00001;
141             assert!(complex_compare(
142                 integrate(
143                     evaluate_function_between(&square_func, a, b, INTEG_STEPS),
144                     TRAPEZE_PER_THREAD,
145                 ),
146                 square_integral(a, b),
147                 epsilon,
148             ));
149         }
150     }
151
152     #[test]
153     fn evaluate_square_func_between() {
154         let square_func: Function<f64, Complex64> = Function::new(square);
155         let actual = evaluate_function_between(&square_func, -2.0, 2.0, 5);
156         let expected = vec![
157             Point {
158                 x: -2.0,
159                 y: complex(4.0, 0.0),
160             },
161             Point {
162                 x: -1.0,
163                 y: complex(1.0, 0.0),
164             },

```

```

165         Point {
166             x: 0.0,
167             y: complex(0.0, 0.0),
168         },
169         Point {
170             x: 1.0,
171             y: complex(1.0, 0.0),
172         },
173         Point {
174             x: 2.0,
175             y: complex(4.0, 0.0),
176         },
177     ];
178
179     for (a, e) in actual.iter().zip(expected) {
180         assert_eq!(a.x, e.x);
181         assert_eq!(a.y, e.y);
182     }
183 }
184
185 fn sinusoidal_exp_complex(x: f64) -> Complex64 {
186     return complex(x, x).exp();
187 }
188
189 fn sinusoidal_exp_complex_integral(a: f64, b: f64) -> Complex64 {
190     //  $(-1/2 + i/2) (e^{(1+i)a} - e^{(1+i)b})$ 
191     return complex(-0.5, 0.5) * (complex(a, a).exp() - complex(b, b).exp());
192 }
193
194 #[tokio::test(flavor = "multi_thread")]
195 async fn integral_of_sinusoidal_exp() {
196     let sinusoidal_exp_complex: Function<f64, Complex64> =
197         Function::new(sinusoidal_exp_complex);
198     for i in 0..10 {
199         for j in 0..10 {
200             let a = f64::from(i - 50) / 12.3;
201             let b = f64::from(j - 50) / 12.3;
202
203             if i == j {
204                 assert_eq!(
205                     integrate(
206                         evaluate_function_between(&sinusoidal_exp_complex, a, b,
207                             INTEG_STEPS),
208                         TRAPEZE_PER_THREAD,
209                     ),
210                     complex(0.0, 0.0)
211                 );
212                 continue;
213             }

```

```

213         let epsilon = 0.0001;
214         assert!(complex_compare(
215             integrate(
216                 evaluate_function_between(&sinusoidal_exp_complex, a, b,
217                                         INTEG_STEPS),
218                 TRAPEZE_PER_THREAD,
219             ),
220             sinusoidal_exp_complex_integral(a, b),
221             epsilon,
222         ));
223     }
224 }
225 }

```

src/main.rs

```

1  #![allow(dead_code)]
2
3  mod airy;
4  mod airy_wave_func;
5  mod check;
6  mod energy;
7  mod integrals;
8  mod newtons_method;
9  mod plot;
10 mod potentials;
11 mod tui;
12 mod turning_points;
13 mod utils;
14 mod wave_function_builder;
15 mod wkb_wave_func;
16
17 use crate::airy::airy_ai;
18 use crate::airy_wave_func::AiryWaveFunction;
19 use crate::integrals::*;
20 use crate::newtons_method::derivative;
21 use crate::utils::Func;
22 use crate::utils::*;
23 use crate::wave_function_builder::*;
24 use crate::wkb_wave_func::WkbWaveFunction;
25 use num::complex::Complex64;
26 use num::pow::Pow;
27 use rayon::iter::*;
28 use std::f64;
29 use std::fs::File;
30 use std::io::Write;
31 use std::path::Path;
32 use std::sync::Arc;

```

```

33
34 const INTEG_STEPS: usize = 64000;
35 const TRAPEZE_PER_THREAD: usize = 1000;
36 const NUMBER_OF_POINTS: usize = 100000;
37
38 const AIRY_TRANSITION_FRACTION: f64 = 0.5;
39 const ENABLE_AIRY_JOINTS: bool = true;
40
41 const VALIDITY_LL_FACTOR: f64 = 3.5;
42
43 const APPROX_INF: (f64, f64) = (-200.0, 200.0);
44
45 fn main() {
46     // let wave_function = wave_function_builder::WaveFunction::new(
47     //     &potentials::square,
48     //     1.0,
49     //     17,
50     //     APPROX_INF,
51     //     0.15,
52     //     ScalingType::Renormalize(1.0.into()),
53     // );
54
55     let wave_function = wave_function_builder::SuperPosition::new(
56         &potentials::mexican_hat,
57         1.0,
58         &[
59             (15, 1.0.into()),
60             (16, complex(0.0, 1.0 * f64::consts::PI / 8.0).exp()),
61             (17, complex(0.0, 2.0 * f64::consts::PI / 8.0).exp()),
62             (18, complex(0.0, 3.0 * f64::consts::PI / 8.0).exp()),
63             // (15, complex(0.0, 2.0 * f64::consts::PI / 3.0).exp()),
64         ],
65         APPROX_INF,
66         0.15,
67         ScalingType::Renormalize(complex(1.0, 0.0)),
68     );
69
70     let output_dir = Path::new("output");
71
72     // For WaveFunction
73     // plot::plot_wavefunction(&wave_function, output_dir, "data.txt");
74     // plot::plot_wavefunction_parts(&wave_function, output_dir, "data.txt");
75     // plot::plot_probability(&wave_function, output_dir, "data.txt");
76
77     // For SuperPosition
78     plot::plot_superposition(&wave_function, output_dir, "data.txt");
79     // plot::plot_probability_super_pos(&wave_function, output_dir, "data.txt");
80 }

```

src/newtons_method.rs

```
1 use crate::integrals::*;
2 use crate::utils::cmp_f64;
3 use num::Float;
4 use rayon::prelude::*;
5 use std::cmp::Ordering;
6 use std::fmt::Debug;
7 use std::ops::*;
8 use std::sync::Arc;
9
10 #[derive(Default, Debug)]
11 pub struct Vec2 {
12     x: f64,
13     y: f64,
14 }
15
16 impl Vec2 {
17     pub fn dot(&self, other: &Vec2) -> f64 {
18         return self.x * other.x + self.y * other.y;
19     }
20
21     pub fn mag(&self) -> f64 {
22         return (self.x.powi(2) + self.y.powi(2)).sqrt();
23     }
24
25     pub fn pseudo_inverse(&self) -> CoVec2 {
26         CoVec2(self.x, self.y) * (1.0 / (self.x.powi(2) + self.y.powi(2)))
27     }
28 }
29
30 impl Add for Vec2 {
31     type Output = Vec2;
32
33     fn add(&self, other: Self) -> Self::Output {
34         Vec2 {
35             x: self.x + other.x,
36             y: self.y + other.y,
37         }
38     }
39 }
40
41 impl Sub for Vec2 {
42     type Output = Vec2;
43
44     fn sub(&self, other: Self) -> Self::Output {
45         Vec2 {
46             x: self.x - other.x,
```

```

47         y: self.x - other.y,
48     }
49 }
50 }
51
52 impl Mul<f64> for Vec2 {
53     type Output = Vec2;
54
55     fn mul(self, s: f64) -> Self::Output {
56         Vec2 {
57             x: self.x * s,
58             y: self.y * s,
59         }
60     }
61 }
62
63 #[derive(Debug)]
64 pub struct CoVec2(f64, f64);
65
66 impl Add for CoVec2 {
67     type Output = CoVec2;
68
69     fn add(self, other: Self) -> Self::Output {
70         CoVec2(self.0 + other.0, self.1 + other.1)
71     }
72 }
73
74 impl Sub for CoVec2 {
75     type Output = CoVec2;
76
77     fn sub(self, other: Self) -> Self::Output {
78         CoVec2(self.0 - other.0, self.1 - other.1)
79     }
80 }
81
82 impl Mul<Vec2> for CoVec2 {
83     type Output = f64;
84
85     fn mul(self, vec: Vec2) -> Self::Output {
86         return self.0 * vec.x + self.1 * vec.y;
87     }
88 }
89
90 impl Mul<f64> for CoVec2 {
91     type Output = CoVec2;
92
93     fn mul(self, s: f64) -> Self::Output {
94         CoVec2(self.0 * s, self.1 * s)
95     }

```

```

96 }
97
98 fn gradient<F>(f: F, x: f64) -> Vec2
99 where
100     F: Fn(f64) -> Vec2,
101 {
102     let x_component = |x| f(x).x;
103     let y_component = |x| f(x).y;
104     return Vec2 {
105         x: derivative(&x_component, x),
106         y: derivative(&y_component, x),
107     };
108 }
109
110 // pub fn derivative<F, R>(f: &F, x: f64) -> R
111 // where
112 //     F: Fn(f64) -> R + ?Sized,
113 //     R: Sub<R, Output = R> + Div<f64, Output = R>,
114 // {
115 //     let epsilon = f64::epsilon().sqrt();
116 //     (f(x + epsilon / 2.0) - f(x - epsilon / 2.0)) / epsilon
117 // }
118
119 pub fn derivative<F, R>(func: &F, x: f64) -> R
120 where
121     F: Fn(f64) -> R + ?Sized,
122     R: Sub<R, Output = R> + Div<f64, Output = R> + Mul<f64, Output = R> + Add<R,
123         Output = R>,
124 {
125     let dx = f64::epsilon().sqrt();
126     let dx1 = dx;
127     let dx2 = dx1 * 2.0;
128     let dx3 = dx1 * 3.0;
129
130     let m1 = (func(x + dx1) - func(x - dx1)) / 2.0;
131     let m2 = (func(x + dx2) - func(x - dx2)) / 4.0;
132     let m3 = (func(x + dx3) - func(x - dx3)) / 6.0;
133
134     let fifteen_m1 = m1 * 15.0;
135     let six_m2 = m2 * 6.0;
136     let ten_dx1 = dx1 * 10.0;
137
138     return ((fifteen_m1 - six_m2) + m3) / ten_dx1;
139 }
140
141 pub fn newtons_method<F>(f: &F, mut guess: f64, precision: f64) -> f64
142 where
143     F: Fn(f64) -> f64,
144 {

```



```

144     loop {
145         let step = f(guess) / derivative(f, guess);
146         if step.abs() < precision {
147             return guess;
148         } else {
149             guess -= step;
150         }
151     }
152 }
153
154 pub fn newtons_method_2d<F>(f: &F, mut guess: f64, precision: f64) -> f64
155 where
156     F: Fn(f64) -> Vec2,
157     F::Output: Debug,
158 {
159     loop {
160         let jacobian = gradient(f, guess);
161         let step: f64 = jacobian.pseudo_inverse() * f(guess);
162         if step.abs() < precision {
163             return guess;
164         } else {
165             guess -= step;
166         }
167     }
168 }
169
170 pub fn newtons_method_max_iters<F>(
171     f: &F,
172     mut guess: f64,
173     precision: f64,
174     max_iters: usize,
175 ) -> Option<f64>
176 where
177     F: Fn(f64) -> f64,
178 {
179     for _ in 0..max_iters {
180         let step = f(guess) / derivative(f, guess);
181         if step.abs() < precision {
182             return Some(guess);
183         } else {
184             guess -= step;
185         }
186     }
187     None
188 }
189
190 fn sigmoid(x: f64) -> f64 {
191     1.0 / (1.0 + (-x).exp())
192 }

```

```

193
194 fn check_sign(initial: f64, new: f64) -> bool {
195     if initial == new {
196         return false;
197     }
198     return (initial <= -0.0 && new >= 0.0) || (initial >= 0.0 && new <= 0.0);
199 }
200
201 pub fn bisection_search_sign_change<F>(f: &F, initial_guess: f64, step: f64) -> (f64,
    f64)
202 where
203     F: Fn(f64) -> f64 + ?Sized,
204 {
205     let mut result = initial_guess;
206     while !check_sign(f(initial_guess), f(result)) {
207         result += step
208     }
209     return (result - step, result);
210 }
211
212 fn regula_falsi_c<F>(f: &F, a: f64, b: f64) -> f64
213 where
214     F: Fn(f64) -> f64 + ?Sized,
215 {
216     return (a * f(b) - b * f(a)) / (f(b) - f(a));
217 }
218
219 pub fn regula_falsi_method<F>(f: &F, mut a: f64, mut b: f64, precision: f64) -> f64
220 where
221     F: Fn(f64) -> f64 + ?Sized,
222 {
223     if a > b {
224         let temp = a;
225         a = b;
226         b = temp;
227     }
228
229     let mut c = regula_falsi_c(f, a, b);
230     while f64::abs(f(c)) > precision {
231         b = regula_falsi_c(f, a, b);
232         a = regula_falsi_c(f, a, b);
233         c = regula_falsi_c(f, a, b);
234     }
235     return c;
236 }
237
238 pub fn regula_falsi_bisection<F>(f: &F, guess: f64, bisection_step: f64, precision:
    f64) -> f64
239 where

```

```

240     F: Fn(f64) -> f64 + ?Sized,
241 {
242     let (a, b) = bisection_search_sign_change(f, guess, bisection_step);
243     return regula_falsi_method(f, a, b, precision);
244 }
245
246 #[derive(Clone)]
247 pub struct NewtonsMethodFindNewZero<F>
248 where
249     F: Fn(f64) -> f64 + ?Sized + Clone,
250 {
251     f: Arc<F>,
252     precision: f64,
253     max_iters: usize,
254     previous_zeros: Vec<(i32, f64)>,
255 }
256
257 impl<F: Fn(f64) -> f64 + ?Sized + Clone> NewtonsMethodFindNewZero<F> {
258     pub(crate) fn new(f: Arc<F>, precision: f64, max_iters: usize) ->
259         NewtonsMethodFindNewZero<F> {
260         NewtonsMethodFindNewZero {
261             f,
262             precision,
263             max_iters,
264             previous_zeros: vec![],
265         }
266     }
267
268     pub(crate) fn modified_func(&self, x: f64) -> f64 {
269         let divisor = self
270             .previous_zeros
271             .iter()
272             .fold(1.0, |acc, (n, z)| acc * (x - z).powi(*n));
273         let divisor = if divisor == 0.0 {
274             divisor + self.precision
275         } else {
276             divisor
277         };
278         (self.f)(x) / divisor
279     }
280
281     pub(crate) fn next_zero(&mut self, guess: f64) -> Option<f64> {
282         let zero = newtons_method_max_iters(
283             &|x| self.modified_func(x),
284             guess,
285             self.precision,
286             self.max_iters,
287         );

```

```

288         if let Some(z) = zero {
289             // to avoid hitting maxima and minima twice
290             if derivative(&|x| self.modified_func(x), z).abs() < self.precision {
291                 self.previous_zeros.push((2, z));
292             } else {
293                 self.previous_zeros.push((1, z));
294             }
295         }
296
297         return zero;
298     }
299
300     pub(crate) fn get_previous_zeros(&self) -> Vec<f64> {
301         self.previous_zeros
302             .iter()
303             .map(|(_, z)| *z)
304             .collect::<Vec<f64>>()
305     }
306 }
307
308 pub fn make_guess<F>(f: &F, (start, end): (f64, f64), n: usize) -> Option<f64>
309 where
310     F: Fn(f64) -> f64 + Sync,
311 {
312     let sort_func = |(_, y1): &(f64, f64), (_, y2): &(f64, f64)| -> Ordering {
313         cmp_f64(&y1, &y2) };
314     let mut points: Vec<(f64, f64)> = (0..n)
315         .into_par_iter()
316         .map(|i| index_to_range(i as f64, 0.0, n as f64, start, end))
317         .map(move |x| {
318             let der = derivative(f, x);
319             (x, f(x) / (-(-der * der).exp() + 1.0))
320         })
321         .map(|(x, y)| (x, y.abs()))
322         .collect();
323     points.sort_by(sort_func);
324     points.get(0).map(|point| point.0)
325 }
326
327 pub fn newtons_method_find_new_zero<F>(
328     f: &F,
329     guess: f64,
330     precision: f64,
331     max_iters: usize,
332     known_zeros: &Vec<f64>,
333 ) -> Option<f64>
334 where
335     F: Fn(f64) -> f64,
336 {

```

```

336     let f_modified = |x| f(x) / known_zeros.iter().fold(0.0, |acc, &z| acc * (x - z))
337     ;
338     newtons_method_max_iters(&f_modified, guess, precision, max_iters)
339 }
340 #[cfg(test)]
341 mod test {
342     use super::*;
343     use crate::utils::cmp_f64;
344
345     fn float_compare(expect: f64, actual: f64, epsilon: f64) -> bool {
346         let average = (expect.abs() + actual.abs()) / 2.0;
347         if average != 0.0 {
348             (expect - actual).abs() / average < epsilon
349         } else {
350             (expect - actual).abs() < epsilon
351         }
352     }
353
354     #[test]
355     fn derivative_square_test() {
356         let square = |x| x * x;
357         let actual = |x| 2.0 * x;
358
359         for i in 0..100 {
360             let x = index_to_range(i as f64, 0.0, 100.0, -20.0, 20.0);
361             assert!(float_compare(derivative(&square, x), actual(x), 1e-4));
362         }
363     }
364
365     #[test]
366     fn derivative_exp_test() {
367         let exp = |x: f64| x.exp();
368
369         for i in 0..100 {
370             let x = index_to_range(i as f64, 0.0, 100.0, -20.0, 20.0);
371             assert!(float_compare(derivative(&exp, x), exp(x), 1e-4));
372         }
373     }
374
375     #[test]
376     fn newtons_method_square() {
377         for i in 0..100 {
378             let zero = index_to_range(i as f64, 0.0, 100.0, 0.1, 10.0);
379             let func = |x| x * x - zero * zero;
380             assert!(float_compare(
381                 newtons_method(&func, 100.0, 1e-7),
382                 zero,
383                 1e-4,

```

```

384         ));
385         assert!(float_compare(
386             newtons_method(&func, -100.0, 1e-7),
387             -zero,
388             1e-4,
389         ));
390     }
391 }
392
393 #[test]
394 fn newtons_method_cube() {
395     for i in 0..100 {
396         let zero = index_to_range(i as f64, 0.0, 100.0, 0.1, 10.0);
397         let func = |x| (x - zero) * (x + zero) * (x - zero / 2.0);
398         assert!(float_compare(
399             newtons_method(&func, 100.0, 1e-7),
400             zero,
401             1e-4,
402         ));
403         assert!(float_compare(
404             newtons_method(&func, -100.0, 1e-7),
405             -zero,
406             1e-4,
407         ));
408         assert!(float_compare(
409             newtons_method(&func, 0.0, 1e-7),
410             zero / 2.0,
411             1e-4,
412         ));
413     }
414 }
415
416 #[test]
417 fn newtons_method_find_next_polynomial() {
418     for i in 0..10 {
419         for j in 0..10 {
420             for k in 0..10 {
421                 let a = index_to_range(i as f64, 0.0, 10.0, -10.0, 10.0);
422                 let b = index_to_range(j as f64, 0.0, 10.0, -100.0, 0.0);
423                 let c = index_to_range(k as f64, 0.0, 10.0, -1.0, 20.0);
424                 let test_func = |x: f64| (x - a) * (x - b) * (x - c);
425
426                 for _guess in [a, b, c] {
427                     let mut finder =
428                         NewtonsMethodFindNewZero::new(Arc::new(test_func), 1e-15,
429                             10000000);
430
431                     finder.next_zero(1.0);
432                     finder.next_zero(1.0);

```

```

432         finder.next_zero(1.0);
433
434         let mut zeros_expected = [a, b, c];
435         let mut zeros_actual = finder.get_previous_zeros().clone();
436
437         zeros_expected.sort_by(cmp_f64);
438         zeros_actual.sort_by(cmp_f64);
439
440         assert_eq!(zeros_actual.len(), 3);
441
442         for (expected, actual) in zeros_expected.iter().zip(
443             zeros_actual.iter()) {
444             assert!((*expected - *actual).abs() < 1e-10);
445         }
446     }
447 }
448 }
449 }
450
451 #[test]
452 fn newtons_method_find_next_test() {
453     let interval = (-10.0, 10.0);
454
455     let test_func = |x: f64| 5.0 * (3.0 * x + 1.0).abs() - (1.5 * x.powi(2) + x -
456         50.0).powi(2);
457
458     let mut finder = NewtonsMethodFindNewZero::new(Arc::new(test_func), 1e-11,
459         100000000);
460
461     for _i in 0..4 {
462         let guess = make_guess(&|x| finder.modified_func(x), interval, 1000);
463         finder.next_zero(guess.unwrap());
464     }
465
466     let mut zeros = finder.get_previous_zeros().clone();
467     zeros.sort_by(cmp_f64);
468     let expected = [-6.65276132415, -5.58024707627, 4.91358040961,
469         5.98609465748];
470
471     println!("zeros:_{:#?}", zeros);
472
473     assert_eq!(zeros.len(), expected.len());
474
475     for (expected, actual) in expected.iter().zip(zeros.iter()) {
476         assert!((*expected - *actual).abs() < 1e-10);
477     }
478 }

```

```

477     #[test]
478     fn regula_falsi_bisection_test() {
479         let func = |x: f64| x * (x - 2.0) * (x + 2.0);
480
481         let actual = regula_falsi_bisection(&func, -1e-3, -1e-3, 1e-5);
482         let expected = -2.0;
483
484         println!("expected: {}, actual: {}", expected, actual);
485         assert!(float_compare(expected, actual, 1e-3));
486     }
487 }

```

src/plot.rs

```

1  use crate::*;
2  use std::fmt;
3
4  pub fn to_gnuplot_string_complex<X>(values: Vec<Point<X, Complex64>>) -> String
5  where
6      X: fmt::Display + Send + Sync,
7  {
8      values
9          .par_iter()
10         .map(|p| -> String { format!("{}", p.x, p.y.re, p.y.im) })
11         .reduce(|| String::new(), |s: String, current: String| s + &*current)
12     }
13
14  pub fn to_gnuplot_string<X, Y>(values: Vec<Point<X, Y>>) -> String
15  where
16      X: fmt::Display + Send + Sync,
17      Y: fmt::Display + Send + Sync,
18  {
19      values
20          .par_iter()
21          .map(|p| -> String { format!("{}", p.x, p.y) })
22          .reduce(|| String::new(), |s: String, current: String| s + &*current)
23     }
24
25  pub fn plot_wavefunction_parts(wave_function: &WaveFunction, output_dir: &Path,
26                                output_file: &str) {
27      std::env::set_current_dir(&output_dir).unwrap();
28
29      let wkb_values = wave_function
30          .get_wkb_ranges_in_view()
31          .iter()
32          .map(|range| evaluate_function_between(wave_function, range.0, range.1,
33                                                NUMBER_OF_POINTS))
34          .collect::<Vec<Vec<Point<f64, Complex64>>>>();
35
36 }

```



```

34 let airy_values = wave_function
35   .get_airy_ranges()
36   .iter()
37   .map(|range| {
38       evaluate_function_between(
39           wave_function,
40           f64::max(wave_function.get_view().0, range.0),
41           f64::min(wave_function.get_view().1, range.1),
42           NUMBER_OF_POINTS,
43       )
44   })
45   .collect::();
46
47 let wkb_values_str = wkb_values
48   .par_iter()
49   .map(|values| to_gnuplot_string_complex(values.to_vec()))
50   .reduce(
51       || String::new(),
52       |s: String, current: String| s + "\n\n" + &*current,
53   );
54
55 let airy_values_str = airy_values
56   .par_iter()
57   .map(|values| to_gnuplot_string_complex(values.to_vec()))
58   .reduce(
59       || String::new(),
60       |s: String, current: String| s + "\n\n" + &*current,
61   );
62
63 let mut data_full = File::create(output_file).unwrap();
64 data_full.write_all(wkb_values_str.as_ref()).unwrap();
65 data_full.write_all("\n\n".as_bytes()).unwrap();
66 data_full.write_all(airy_values_str.as_ref()).unwrap();
67
68 let mut plot_3d_file = File::create("plot_3d.gnuplot").unwrap();
69
70 let wkb_3d_cmd = (1..=wkb_values.len())
71   .into_iter()
72   .map(|n| {
73       format!(
74           "\"{}\" \"u1:2:3i{}t{}\"WKB{}\"w_l",
75           output_file,
76           n - 1,
77           n
78       )
79   })
80   .collect::

```

```

83     let airy_3d_cmd = (1..=airy_values.len())
84         .into_iter()
85         .map(|n| {
86             format!(
87                 "{}{}1:2:3i{}t{}Airy{}{}w{}",
88                 output_file,
89                 n + wkb_values.len() - 1,
90                 n
91             )
92         })
93         .collect::<Vec<String>>()
94         .join(",");
95     let plot_3d_cmd: String = "splot".to_string() + &wkb_3d_cmd + "," + &
        airy_3d_cmd;
96     plot_3d_file.write_all(plot_3d_cmd.as_ref()).unwrap();
97
98     let mut plot_file = File::create("plot.gnuplot").unwrap();
99     let wkb_cmd = (1..=wkb_values.len())
100         .into_iter()
101         .map(|n| {
102             format!(
103                 "{}{}1:2i{}t{}Re(WKB{}{}w{}",
104                 output_file,
105                 n - 1,
106                 n
107             )
108         })
109         .collect::<Vec<String>>()
110         .join(",");
111
112     let airy_cmd = (1..=airy_values.len())
113         .into_iter()
114         .map(|n| {
115             format!(
116                 "{}{}1:2i{}t{}Re(Airy{}{}w{}",
117                 output_file,
118                 n + wkb_values.len() - 1,
119                 n
120             )
121         })
122         .collect::<Vec<String>>()
123         .join(",");
124     let plot_cmd: String = "plot".to_string() + &wkb_cmd + "," + &airy_cmd;
125
126     plot_file.write_all(plot_cmd.as_ref()).unwrap();
127
128     let mut plot_imag_file = File::create("plot_im.gnuplot").unwrap();
129
130     let wkb_im_cmd = (1..=wkb_values.len())

```

```

131         .into_iter()
132         .map(|n| {
133             format!(
134                 "\"{}\"_u1:3_i_{}_t_\"Im(WKB_{})\"_w_l",
135                 output_file,
136                 n - 1,
137                 n
138             )
139         })
140         .collect::<Vec<String>>()
141         .join(",_");
142
143     let airy_im_cmd = (1..=airy_values.len())
144         .into_iter()
145         .map(|n| {
146             format!(
147                 "\"{}\"_u1:3_i_{}_t_\"Im(Airy_{})\"_w_l",
148                 output_file,
149                 n + wkb_values.len() - 1,
150                 n
151             )
152         })
153         .collect::<Vec<String>>()
154         .join(",_");
155     let plot_imag_cmd: String = "plot_".to_string() + &wkb_im_cmd + ",_" + &
        airy_im_cmd;
156
157     plot_imag_file.write_all(plot_imag_cmd.as_ref()).unwrap();
158 }
159
160 pub fn plot_complex_function(
161     func: &dyn Func<f64, Complex64>,
162     view: (f64, f64),
163     title: &str,
164     output_dir: &Path,
165     output_file: &str,
166 ) {
167     std::env::set_current_dir(&output_dir).unwrap();
168     let values = evaluate_function_between(func, view.0, view.1, NUMBER_OF_POINTS);
169
170     let values_str = to_gnuplot_string_complex(values);
171
172     let mut data_file = File::create(output_file).unwrap();
173
174     data_file.write_all(values_str.as_bytes()).unwrap();
175
176     let mut plot_3d_file = File::create("plot_3d.gnuplot").unwrap();
177     plot_3d_file
178         .write_all(format!("splot_\"{}\"_u1:2:3_t_{}\"_w_l", output_file, title).

```

```

        as_bytes())
179     .unwrap();
180
181     let mut plot_file = File::create("plot.gnuplot").unwrap();
182     plot_file
183         .write_all(format!("plot \"{}\" \"u1:2,t\" \"Re({})\" \"w\", output_file, title).
184                     as_bytes())
185         .unwrap();
186
187     let mut plot_im_file = File::create("plot_im.gnuplot").unwrap();
188     plot_im_file
189         .write_all(format!("plot \"{}\" \"u1:3,t\" \"Im({})\" \"w\", output_file, title).
190                     as_bytes())
191         .unwrap();
192 }
193
194 pub fn plot_wavefunction(wave_function: &WaveFunction, output_dir: &Path, output_file
195 : &str) {
196     plot_complex_function(
197         wave_function,
198         wave_function.get_view(),
199         "Psi",
200         output_dir,
201         output_file,
202     );
203 }
204
205 pub fn plot_superposition(wave_function: &SuperPosition, output_dir: &Path,
206 output_file: &str) {
207     plot_complex_function(
208         wave_function,
209         wave_function.get_view(),
210         "Psi",
211         output_dir,
212         output_file,
213     );
214 }
215
216 pub fn plot_probability(wave_function: &WaveFunction, output_dir: &Path, output_file:
217 &str) {
218     std::env::set_current_dir(&output_dir).unwrap();
219     let values = evaluate_function_between(
220         wave_function,
221         wave_function.get_view().0,
222         wave_function.get_view().1,
223         NUMBER_OF_POINTS,
224     )
225     .par_iter()
226     .map(|p| Point {

```

```

222         x: p.x,
223         y: p.y.norm_sqr(),
224     })
225     .collect();
226
227     let values_str = to_gnuplot_string(values);
228
229     let mut data_file = File::create(output_file).unwrap();
230
231     data_file.write_all(values_str.as_bytes()).unwrap();
232
233     let mut plot_file = File::create("plot.gnuplot").unwrap();
234     plot_file
235         .write_all(format!("plot \"{}\" \"u 1:2,t\" \"|Psi|^2\" \"w l\", output_file).
236             as_bytes())
237         .unwrap();
238 }
239
240 pub fn plot_probability_super_pos(
241     wave_function: &SuperPosition,
242     output_dir: &Path,
243     output_file: &str,
244 ) {
245     std::env::set_current_dir(&output_dir).unwrap();
246     let values = evaluate_function_between(
247         wave_function,
248         wave_function.get_view().0,
249         wave_function.get_view().1,
250         NUMBER_OF_POINTS,
251     )
252     .par_iter()
253     .map(|p| Point {
254         x: p.x,
255         y: p.y.norm_sqr(),
256     })
257     .collect();
258
259     let values_str = to_gnuplot_string(values);
260
261     let mut data_file = File::create(output_file).unwrap();
262
263     data_file.write_all(values_str.as_bytes()).unwrap();
264
265     let mut plot_file = File::create("plot.gnuplot").unwrap();
266     plot_file
267         .write_all(format!("plot \"{}\" \"u 1:2,t\" \"|Psi|^2\" \"w l\", output_file).
268             as_bytes())
269         .unwrap();
270 }

```

src/potentials.rs

```
1 use crate::*;
2
3 const ENERGY_INF: f64 = 1e6;
4
5 #[allow(unused)]
6 pub fn smooth_step(x: f64) -> f64 {
7     const TRANSITION: f64 = 0.5;
8     let step = Arc::new(Function::new(|x: f64| -> Complex64 {
9         if x.abs() < 2.0 {
10             complex(10.0, 0.0)
11         } else {
12             complex(0.0, 0.0)
13         }
14     }));
15     let zero = Arc::new(Function::new(|_: f64| -> Complex64 { complex(0.0, 0.0) }));
16     let inf = Arc::new(Function::new(|x: f64| -> Complex64 {
17         if x.abs() > 5.0 {
18             complex(ENERGY_INF, 0.0)
19         } else {
20             complex(0.0, 0.0)
21         }
22     }));
23
24     let joint_inf_zero_l = wave_function_builder::Joint {
25         left: inf.clone(),
26         right: zero.clone(),
27         cut: -5.0 + TRANSITION / 2.0,
28         delta: TRANSITION,
29     };
30
31     let joint_zero_step_l = wave_function_builder::Joint {
32         left: zero.clone(),
33         right: step.clone(),
34         cut: -2.0 + TRANSITION / 2.0,
35         delta: TRANSITION,
36     };
37
38     let joint_zero_inf_r = wave_function_builder::Joint {
39         left: zero.clone(),
40         right: inf.clone(),
41         cut: 5.0 - TRANSITION / 2.0,
42         delta: TRANSITION,
43     };
44
45     let joint_step_zero_r = wave_function_builder::Joint {
46         left: step.clone(),
```

```

47     right: zero.clone(),
48     cut: 2.0 - TRANSITION / 2.0,
49     delta: TRANSITION,
50 };
51
52 if wave_function_builder::is_in_range(joint_zero_inf_r.range(), x) {
53     return joint_zero_inf_r.eval(x).re;
54 }
55
56 if wave_function_builder::is_in_range(joint_inf_zero_l.range(), x) {
57     return joint_inf_zero_l.eval(x).re;
58 }
59
60 if wave_function_builder::is_in_range(joint_step_zero_r.range(), x) {
61     return joint_step_zero_r.eval(x).re;
62 }
63
64 if wave_function_builder::is_in_range(joint_zero_step_l.range(), x) {
65     return joint_zero_step_l.eval(x).re;
66 }
67
68 return zero.eval(x).re.max(joint_inf_zero_l.eval(x).re.max(joint_step_zero_r.eval(x).re));
69 }
70
71 #[allow(unused)]
72 pub fn mexican_hat(x: f64) -> f64 {
73     (x - 4.0).powi(2) * (x + 4.0).powi(2)
74 }
75
76 #[allow(unused)]
77 pub fn double_mexican_hat(x: f64) -> f64 {
78     (x - 4.0).powi(2) * x.powi(2) * (x + 4.0).powi(2)
79 }
80
81 #[allow(unused)]
82 pub fn triple_mexican_hat(x: f64) -> f64 {
83     (x - 6.0).powi(2) * (x - 3.0).powi(2) * (x + 3.0).powi(2) * (x + 6.0).powi(2)
84 }
85
86 pub fn square(x: f64) -> f64 {
87     x * x
88 }

```

src/tui.rs

```

1 use std::io;
2
3 fn get_float_from_user(message: &str) -> f64 {
4     loop {

```

```

5     println!("{}", message);
6     let mut input = String::new();
7
8     // io::stdout().lock().write(message.as_ref()).unwrap();
9     io::stdin()
10        .read_line(&mut input)
11        .expect("Not a valid string");
12    println!("");
13    let num = input.trim().parse();
14    if num.is_ok() {
15        return num.unwrap();
16    }
17 }
18 }
19
20 fn get_user_bounds() -> (f64, f64) {
21     let user_bound_lower: f64 = get_float_from_user("Lower_Bound:");
22
23     let user_bound_upper: f64 = get_float_from_user("Upper_bound:");
24     return (user_bound_lower, user_bound_upper);
25 }
26 fn ask_user_for_view(lower_bound: Option<f64>, upper_bound: Option<f64>) -> (f64, f64) {
27     println!("Failed to determine boundary of the graph automatically.");
28     println!("Please enter values manually.");
29     lower_bound.map(|b| println!("(Suggestion for lower bound: {})", b));
30     upper_bound.map(|b| println!("(Suggestion for upper bound: {})", b));
31
32     return get_user_bounds();
33 }

```

src/turning_points.rs

```

1 use crate::cmp_f64;
2 use crate::newtons_method::*;
3 use crate::wkb_wave_func::*;
4 use crate::*;
5 use num::signum;
6
7 const MAX_TURNING_POINTS: usize = 256;
8 const ACCURACY: f64 = 1e-9;
9
10 pub struct TGroup {
11     pub ts: Vec<((f64, f64), f64)>,
12     // pub tn: Option<f64>,
13 }
14
15 impl TGroup {
16     pub fn new() -> TGroup {

```



```

17     TGroup { ts: vec![] }
18 }
19
20 pub fn add_ts(&mut self, new_t: ((f64, f64), f64)) {
21     self.ts.push(new_t);
22 }
23 }
24
25 fn validity_func(phase: Phase) -> Arc<dyn Fn(f64) -> f64> {
26     Arc::new(move |x: f64| {
27         1.0 / (2.0 * phase.mass).sqrt() * derivative(&|t| (phase.potential)(t), x).
28             abs() * VALIDITY_LL_FACTOR
29         - ((phase.potential)(x) - phase.energy).pow(2)
30     })
31 }
32
33 fn group_ts(zeros: &Vec<f64>, phase: &Phase) -> TGroup {
34     let mut zeros = zeros.clone();
35     let valid = validity_func(phase.clone());
36
37     zeros.sort_by(cmp_f64);
38     let mut derivatives = zeros
39         .iter()
40         .map(|x| derivative(valid.as_ref(), *x))
41         .map(signum)
42         .zip(zeros.clone())
43         .collect::<Vec<(f64, f64)>>();
44
45     let mut groups = TGroup { ts: vec![] };
46
47     if let Some((deriv, z)) = derivatives.first() {
48         if *deriv < 0.0 {
49             let mut guess = z - ACCURACY.sqrt();
50             let mut new_deriv = *deriv;
51             let mut missing_t = *z;
52
53             while new_deriv < 0.0 {
54                 missing_t =
55                     regula_falsi_bisection(valid.as_ref(), guess, -ACCURACY.sqrt(),
56                         ACCURACY);
57                 new_deriv = signum(derivative(valid.as_ref(), missing_t));
58                 guess -= ACCURACY.sqrt();
59             }
60
61             derivatives.insert(
62                 0,
63                 (signum(derivative(valid.as_ref(), missing_t)), missing_t),
64             );
65         }
66     }
67 }

```

```

64     }
65
66     if let Some((deriv, z)) = derivatives.last() {
67         if *deriv > 0.0 {
68             let mut guess = z + ACCURACY.sqrt();
69             let mut new_deriv = *deriv;
70             let mut missing_t = *z;
71
72             while new_deriv > 0.0 {
73                 missing_t =
74                     regula_falsi_bisection(valid.as_ref(), guess, ACCURACY.sqrt(),
75                                             ACCURACY);
76                 new_deriv = signum(derivative(valid.as_ref(), missing_t));
77                 guess += ACCURACY.sqrt();
78             }
79             derivatives.push((signum(derivative(valid.as_ref(), missing_t)),
80                             missing_t));
81         }
82     }
83     assert_eq!(derivatives.len() % 2, 0);
84
85     for i in (0..derivatives.len()).step_by(2) {
86         let (t1_deriv, t1) = derivatives[i];
87         let (t2_deriv, t2) = derivatives[i + 1];
88         assert!(t1_deriv > 0.0);
89         assert!(t2_deriv < 0.0);
90
91         let turning_point = newtons_method(
92             &|x| phase.energy - (phase.potential)(x),
93             (t1 + t2) / 2.0,
94             1e-7,
95         );
96         groups.add_ts((t1, t2), turning_point);
97     }
98
99     return groups;
100 }
101
102 pub fn calc_ts(phase: &Phase, view: (f64, f64)) -> TGroup {
103     let zeros = find_zeros(phase, view);
104     let groups = group_ts(&zeros, phase);
105     println!(
106         "Turning_Points:_{:.7?}",
107         groups.ts.iter().map(|(_, t)| *t).collect:<Vec<f64>>()
108     );
109     return groups;
110 }

```

```

111
112 fn find_zeros(phase: &Phase, view: (f64, f64)) -> Vec<f64> {
113     let phase_clone = phase.clone();
114     let validity_func = Arc::new(move |x: f64| {
115         1.0 / (2.0 * phase_clone.mass).sqrt()
116             * derivative(&|t| (phase_clone.potential)(t), x).abs()
117             * VALIDITY_LL_FACTOR
118             - ((phase_clone.potential)(x) - phase_clone.energy).pow(2)
119     });
120     let mut zeros = NewtonsMethodFindNewZero::new(validity_func, ACCURACY, 1e4 as
        usize);
121
122     (0..MAX_TURNING_POINTS).into_iter().for_each(|_| {
123         let modified_func = |x| zeros.modified_func(x);
124
125         let guess = make_guess(&modified_func, view, 1000);
126         guess.map(|g| zeros.next_zero(g));
127     });
128
129     let view = if view.0 < view.1 {
130         view
131     } else {
132         (view.1, view.0)
133     };
134     let unique_zeros = zeros
135         .get_previous_zeros()
136         .iter()
137         .filter(|x| **x > view.0 && **x < view.1)
138         .map(|x| *x)
139         .collect::<Vec<f64>>();
140     return unique_zeros;
141 }

```

src/utils.rs

```

1 use crate::newtons_method::derivative;
2 use crate::Complex64;
3 use std::cmp::Ordering;
4
5 pub fn cmp_f64(a: &f64, b: &f64) -> Ordering {
6     if a < b {
7         return Ordering::Less;
8     } else if a > b {
9         return Ordering::Greater;
10    }
11    return Ordering::Equal;
12 }
13
14 pub fn complex(re: f64, im: f64) -> Complex64 {

```

```

15     return Complex64 { re, im };
16 }
17
18 pub fn sigmoid(x: f64) -> f64 {
19     1.0 / (1.0 + (-x).exp())
20 }
21
22 pub fn identity(c: Complex64) -> Complex64 {
23     c
24 }
25
26 pub fn conjugate(c: Complex64) -> Complex64 {
27     c.conj()
28 }
29
30 pub fn negative(c: Complex64) -> Complex64 {
31     -c
32 }
33
34 pub fn negative_conj(c: Complex64) -> Complex64 {
35     -c.conj()
36 }
37
38 pub fn complex_compare(expect: Complex64, actual: Complex64, epsilon: f64) -> bool {
39     let average = (expect.norm() + actual.norm()) / 2.0;
40     return (expect - actual).norm() / average < epsilon;
41 }
42
43 pub fn float_compare(expect: f64, actual: f64, epsilon: f64) -> bool {
44     let average = (expect + actual) / 2.0;
45
46     if average < epsilon {
47         return expect == actual;
48     }
49
50     return (expect - actual) / average < epsilon;
51 }
52
53 pub trait Func<A, R>: Sync + Send {
54     fn eval(&self, x: A) -> R;
55 }
56
57 pub trait ReToC: Sync + Func<f64, Complex64> {}
58
59 pub trait ReToRe: Sync + Func<f64, f64> {}
60
61 pub struct Function<A, R> {
62     pub(crate) f: fn(A) -> R,
63 }

```

```

64
65 impl<A, R> Function<A, R> {
66     pub const fn new(f: fn(A) -> R) -> Function<A, R> {
67         return Function { f };
68     }
69 }
70
71 impl<A, R> Func<A, R> for Function<A, R> {
72     fn eval(&self, x: A) -> R {
73         (self.f)(x)
74     }
75 }
76 pub struct Derivative<'a> {
77     pub f: &'a dyn Func<f64, Complex64>,
78 }
79
80 impl Func<f64, Complex64> for Derivative<'_> {
81     fn eval(&self, x: f64) -> Complex64 {
82         derivative(&|x| self.f.eval(x), x)
83     }
84 }
85
86 fn get_wavefunc_exp_sign(x: f64) -> f64 {
87     if -0.5 <= x && x <= 0.5 {
88         return 1.0;
89     } else {
90         return -1.0;
91     }
92 }

```

src/wave_function_builder.rs

```

1 use crate::wkb_wave_func::Phase;
2 use crate::*;
3 use ordinal::Ordinal;
4 use std::sync::*;
5
6 pub enum ScalingType {
7     Mul(Complex64),
8     Renormalize(Complex64),
9     None,
10 }
11
12 pub trait WaveFunctionPart: Func<f64, Complex64> + Sync + Send {
13     fn range(&self) -> (f64, f64);
14     fn as_func(&self) -> Box<dyn Func<f64, Complex64>>;
15 }
16
17 pub trait WaveFunctionPartWithOp: WaveFunctionPart {

```

```

18     fn get_op(&self) -> Box<fn(Complex64) -> Complex64>;
19     fn with_op(&self, op: fn(Complex64) -> Complex64) -> Box<dyn
    WaveFunctionPartWithOp>;
20     fn as_wave_function_part(&self) -> Box<dyn WaveFunctionPart>;
21 }
22
23 pub fn is_in_range(range: (f64, f64), x: f64) -> bool {
24     return range.0 <= x && range.1 > x;
25 }
26
27 #[derive(Clone)]
28 pub struct Joint {
29     pub left: Arc<dyn Func<f64, Complex64>>,
30     pub right: Arc<dyn Func<f64, Complex64>>,
31     pub cut: f64,
32     pub delta: f64,
33 }
34
35 impl WaveFunctionPart for Joint {
36     fn range(&self) -> (f64, f64) {
37         if self.delta > 0.0 {
38             (self.cut, self.cut + self.delta)
39         } else {
40             (self.cut + self.delta, self.cut)
41         }
42     }
43     fn as_func(&self) -> Box<dyn Func<f64, Complex64>> {
44         return Box::new(self.clone());
45     }
46 }
47
48 impl Func<f64, Complex64> for Joint {
49     fn eval(&self, x: f64) -> Complex64 {
50         let (left, right) = if self.delta > 0.0 {
51             (&self.left, &self.right)
52         } else {
53             (&self.right, &self.left)
54         };
55
56         let delta = self.delta.abs();
57
58         let chi = |x: f64| f64::sin(x * f64::consts::PI / 2.0).powi(2);
59         let left_val = left.eval(x);
60         return left_val + (right.eval(x) - left_val) * chi((x - self.cut) / delta);
61     }
62 }
63
64 #[derive(Clone)]
65 struct PureWkb {

```

```

66     wkb: Arc<WkbWaveFunction>,
67     range: (f64, f64),
68 }
69
70 impl WaveFunctionPart for PureWkb {
71     fn range(&self) -> (f64, f64) {
72         self.range
73     }
74     fn as_func(&self) -> Box<dyn Func<f64, Complex64>> {
75         Box::new(self.clone())
76     }
77 }
78
79 impl WaveFunctionPartWithOp for PureWkb {
80     fn as_wave_function_part(&self) -> Box<dyn WaveFunctionPart> {
81         Box::new(self.clone())
82     }
83
84     fn get_op(&self) -> Box<fn(Complex64) -> Complex64> {
85         self.wkb.get_op()
86     }
87
88     fn with_op(&self, op: fn(Complex64) -> Complex64) -> Box<dyn
89         WaveFunctionPartWithOp> {
90         Box::new(PureWkb {
91             wkb: Arc::new(self.wkb.with_op(op)),
92             range: self.range,
93         })
94     }
95
96 impl Func<f64, Complex64> for PureWkb {
97     fn eval(&self, x: f64) -> Complex64 {
98         self.wkb.eval(x)
99     }
100 }
101
102 #[derive(Clone)]
103 struct ApproxPart {
104     airy: Arc<AiryWaveFunction>,
105     wkb: Arc<WkbWaveFunction>,
106     airy_join_l: Joint,
107     airy_join_r: Joint,
108     range: (f64, f64),
109 }
110
111 impl WaveFunctionPart for ApproxPart {
112     fn range(&self) -> (f64, f64) {
113         self.range

```

```

114     }
115     fn as_func(&self) -> Box<dyn Func<f64, Complex64>> {
116         Box::new(self.clone())
117     }
118 }
119
120 impl WaveFunctionPartWithOp for ApproxPart {
121     fn as_wave_function_part(&self) -> Box<dyn WaveFunctionPart> {
122         Box::new(self.clone())
123     }
124
125     fn get_op(&self) -> Box<fn(Complex64) -> Complex64> {
126         self.wkb.get_op()
127     }
128
129     fn with_op(&self, op: fn(Complex64) -> Complex64) -> Box<dyn
130         WaveFunctionPartWithOp> {
131         Box::new(ApproxPart::new(
132             self.airy.with_op(op),
133             self.wkb.with_op(op),
134             self.range,
135         ))
136     }
137 }
138
139 impl ApproxPart {
140     fn new(airy: AiryWaveFunction, wkb: WkbWaveFunction, range: (f64, f64)) ->
141         ApproxPart {
142         let airy_rc = Arc::new(airy);
143         let wkb_rc = Arc::new(wkb);
144         let delta = (airy_rc.ts.1 - airy_rc.ts.0) * AIRY_TRANSITION_FRACTION;
145         ApproxPart {
146             airy: airy_rc.clone(),
147             wkb: wkb_rc.clone(),
148             airy_join_l: Joint {
149                 left: wkb_rc.clone(),
150                 right: airy_rc.clone(),
151                 cut: airy_rc.ts.0 + delta / 2.0,
152                 delta: -delta,
153             },
154             airy_join_r: Joint {
155                 left: airy_rc.clone(),
156                 right: wkb_rc.clone(),
157                 cut: airy_rc.ts.1 - delta / 2.0,
158                 delta,
159             },
160             range,
161         }
162     }
163 }

```



```

161 }
162
163 impl Func<f64, Complex64> for ApproxPart {
164     fn eval(&self, x: f64) -> Complex64 {
165         if is_in_range(self.airy_join_l.range(), x) && ENABLE_AIRY_JOINTS {
166             return self.airy_join_l.eval(x);
167         } else if is_in_range(self.airy_join_r.range(), x) && ENABLE_AIRY_JOINTS {
168             return self.airy_join_r.eval(x);
169         } else if is_in_range(self.airy.ts, x) {
170             return self.airy.eval(x);
171         } else {
172             return self.wkb.eval(x);
173         }
174     }
175 }
176
177 #[derive(Clone)]
178 pub struct WaveFunction {
179     phase: Arc<Phase>,
180     view: (f64, f64),
181     parts: Vec<Arc<dyn WaveFunctionPart>>,
182     airy_ranges: Vec<(f64, f64)>,
183     wkb_ranges: Vec<(f64, f64)>,
184     scaling: Complex64,
185 }
186
187 fn sign_match(f1: f64, f2: f64) -> bool {
188     return f1.signum() == f2.signum();
189 }
190
191 fn sign_match_complex(mut c1: Complex64, mut c2: Complex64) -> bool {
192     if c1.re.abs() < c1.im.abs() {
193         c1.re = 0.0;
194     }
195
196     if c1.im.abs() < c1.re.abs() {
197         c1.im = 0.0;
198     }
199
200     if c2.re.abs() < c2.im.abs() {
201         c2.re = 0.0;
202     }
203
204     if c2.im.abs() < c2.re.abs() {
205         c2.im = 0.0;
206     }
207
208     return sign_match(c1.re, c2.re) && sign_match(c1.im, c2.im);
209 }

```

```

210
211 impl WaveFunction {
212     pub fn get_energy(&self) -> f64 {
213         self.phase.energy
214     }
215
216     pub fn new<F: Fn(f64) -> f64 + Sync + Send>(
217         potential: &'static F,
218         mass: f64,
219         n_energy: usize,
220         approx_inf: (f64, f64),
221         view_factor: f64,
222         scaling: ScalingType,
223     ) -> WaveFunction {
224         let energy = energy::nth_energy(n_energy, mass, &potential, approx_inf);
225         println!("{}", Energy::{:9}, Ordinal(n_energy).to_string(), energy);
226
227         let lower_bound = newtons_method::newtons_method_max_iters(
228             &|x| potential(x) - energy,
229             approx_inf.0,
230             1e-7,
231             100000,
232         );
233         let upper_bound = newtons_method::newtons_method_max_iters(
234             &|x| potential(x) - energy,
235             approx_inf.1,
236             1e-7,
237             100000,
238         );
239
240         let view = if lower_bound.is_some() && upper_bound.is_some() {
241             (
242                 lower_bound.unwrap() * (upper_bound.unwrap() - lower_bound.unwrap())
243                     * view_factor,
244                 upper_bound.unwrap() * (upper_bound.unwrap() - lower_bound.unwrap())
245                     * view_factor,
246             )
247         } else {
248             println!("Failed to determine view automatically, using APPROX_INF as view");
249             (
250                 approx_inf.0 - f64::EPSILON.sqrt(),
251                 approx_inf.1 + f64::EPSILON.sqrt(),
252             )
253         };
254
255         let phase = Arc::new(Phase::new(energy, mass, potential));
256
257         let (airy_wave_funcs, boundaries) = AiryWaveFunction::new(phase.clone(), (

```

```

        view.0, view.1));
256   let (parts, airy_ranges, wkb_ranges): (
257       Vec<Arc<dyn WaveFunctionPart>>,
258       Vec<(f64, f64)>,
259       Vec<(f64, f64)>,
260   ) = if boundaries.ts.len() == 0 {
261       println!("No turning points found in view! Results might be inaccurate")
262       ;
263       let wkb1 = WkbWaveFunction::new(
264           phase.clone(),
265           1.0.into(),
266           INTEG_STEPS,
267           approx_inf.0,
268           approx_inf.0,
269           f64::consts::PI / 4.0,
270       );
271       let wkb2 = WkbWaveFunction::new(
272           phase.clone(),
273           1.0.into(),
274           INTEG_STEPS,
275           approx_inf.0,
276           approx_inf.1,
277           f64::consts::PI / 4.0,
278       );
279       let center = (view.0 + view.1) / 2.0;
280       let wkb1 = Box::new(PureWkb {
281           wkb: Arc::new(wkb1),
282           range: (approx_inf.0, center),
283       });
284       let wkb2 = Box::new(PureWkb {
285           wkb: Arc::new(wkb2),
286           range: (center, approx_inf.1),
287       });
288       let wkb1_range = wkb1.range();
289       (
290           vec![
291               Arc::from(wkb1.as_wave_function_part()),
292               Arc::from(wkb2.as_wave_function_part()),
293           ],
294           vec![],
295           vec![wkb1_range, wkb2.range()],
296       )
297   } else {
298       let turning_points: Vec<f64> = [
299           vec![2.0 * approx_inf.0 - boundaries.ts.first().unwrap().1],
300           boundaries.ts.iter().map(|p| p.1).collect(),
301       ]
302   }

```

```

303     vec![2.0 * approx_inf.1 - boundaries.ts.last().unwrap().1],
304   ]
305   .concat();
306
307   let wave_funcs = turning_points
308     .iter()
309     .zip(turning_points.iter().skip(1))
310     .zip(turning_points.iter().skip(2))
311     .map(
312       |((previous, boundary), next)| -> (WkbWaveFunction, (f64, f64)) {
313         (
314           if derivative(phase.potential.as_ref(), *boundary) > 0.0
315           {
316             WkbWaveFunction::new(
317               phase.clone(),
318               1.0.into(),
319               INTEG_STEPS,
320               *boundary,
321               *previous,
322               f64::consts::PI / 4.0,
323             )
324           } else {
325             WkbWaveFunction::new(
326               phase.clone(),
327               1.0.into(),
328               INTEG_STEPS,
329               *boundary,
330               *boundary,
331               f64::consts::PI / 4.0,
332             )
333           },
334           ((boundary + previous) / 2.0, (next + boundary) / 2.0),
335         ),
336     )
337     .collect::<Vec<(WkbWaveFunction, (f64, f64))>>();
338
339   let wkb_airy_pair: Vec<(&(WkbWaveFunction, (f64, f64)), AiryWaveFunction)>
340     = wave_funcs
341       .iter()
342       .zip(airy_wave_funcs.iter())
343       .map(|(w, a)| {
344         (
345           w,
346           a.with_phase_off(w.0.phase_off)
347             .with_c(w.0.get_exp_sign().into()),
348         )
349       })
350       .collect();

```

```

350
351     let wkb_ranges = wkb_airpair
352         .iter()
353         .map(|((_, wkb_range), _)| *wkb_range)
354         .collect();
355     let airy_ranges = wkb_airpair.iter().map(|(_, airy)| airy.ts).collect()
356         ;
357
358     let approx_parts: Vec<Arc<dyn WaveFunctionPartWithOp>> = wkb_airpair
359         .iter()
360         .map(|((wkb, range), airy)| -> Arc<dyn WaveFunctionPartWithOp> {
361             Arc::new(ApproxPart::new(airy.clone(), wkb.clone(), *range))
362         })
363         .collect();
364
365     (
366         approx_parts
367         .iter()
368         .map(|p| Arc::from(p.as_wave_function_part()))
369         .collect(),
370         airy_ranges,
371         wkb_ranges,
372     )
373 };
374
375 match scaling {
376     ScalingType::Mul(s) => WaveFunction {
377         phase,
378         view,
379         parts,
380         airy_ranges,
381         wkb_ranges,
382         scaling: s,
383     },
384     ScalingType::None => WaveFunction {
385         phase,
386         view,
387         parts,
388         airy_ranges,
389         wkb_ranges,
390         scaling: complex(1.0, 0.0),
391     },
392     ScalingType::Renormalize(s) => {
393         let unscaled = WaveFunction {
394             phase: phase.clone(),
395             view,
396             parts: parts.clone(),
397             airy_ranges: airy_ranges.clone(),
398             wkb_ranges: wkb_ranges.clone(),

```

```

398         scaling: s,
399     };
400     let factor = renormalize_factor(&unscaled, approx_inf);
401     WaveFunction {
402         phase,
403         view,
404         parts,
405         airy_ranges,
406         wkb_ranges,
407         scaling: s * factor,
408     }
409 }
410 }
411 }
412
413 pub fn calc_psi(&self, x: f64) -> Complex64 {
414     for part in self.parts.as_slice() {
415         if is_in_range(part.range(), x) {
416             return part.eval(x);
417         }
418     }
419     panic!(
420         "[WkbWaveFunction::calc_psi]_x_out_of_range_(x={},_ranges:{:#?})",
421         x,
422         self.parts
423             .iter()
424             .map(|p| p.range())
425             .collect::<Vec<(f64, f64)>>()
426     );
427 }
428
429 pub fn get_airy_ranges(&self) -> &[(f64, f64)] {
430     self.airy_ranges.as_slice()
431 }
432
433 pub fn get_wkb_ranges(&self) -> &[(f64, f64)] {
434     self.wkb_ranges.as_slice()
435 }
436
437 pub fn get_wkb_ranges_in_view(&self) -> Vec<(f64, f64)> {
438     self.wkb_ranges
439         .iter()
440         .map(|range| {
441             (
442                 f64::max(self.get_view().0, range.0),
443                 f64::min(self.get_view().1, range.1),
444             )
445         })
446     .collect::<Vec<(f64, f64)>>()

```

```

447     }
448
449     pub fn is_wkb(&self, x: f64) -> bool {
450         self.wkb_ranges
451             .iter()
452             .map(|r| is_in_range(*r, x))
453             .collect::<Vec<bool>>()
454             .contains(&true)
455     }
456
457     pub fn is_airy(&self, x: f64) -> bool {
458         self.airy_ranges
459             .iter()
460             .map(|r| is_in_range(*r, x))
461             .collect::<Vec<bool>>()
462             .contains(&true)
463     }
464
465     pub fn get_view(&self) -> (f64, f64) {
466         self.view
467     }
468
469     pub fn set_view(&mut self, view: (f64, f64)) {
470         self.view = view
471     }
472
473     pub fn get_phase(&self) -> Arc<Phase> {
474         self.phase.clone()
475     }
476 }
477
478 impl Func<f64, Complex64> for WaveFunction {
479     fn eval(&self, x: f64) -> Complex64 {
480         self.scaling * self.calc_psi(x)
481     }
482 }
483
484 pub struct SuperPosition {
485     wave_funcs: Vec<WaveFunction>,
486     scaling: Complex64,
487 }
488
489 impl SuperPosition {
490     pub fn new<F: Fn(f64) -> f64 + Send + Sync>(
491         potential: &'static F,
492         mass: f64,
493         n_energies_scaling: &[(usize, Complex64)],
494         approx_inf: (f64, f64),
495         view_factor: f64,

```

```

496     scaling: ScalingType,
497 ) -> SuperPosition {
498     let wave_funcs = n_energies_scaling
499     .iter()
500     .map(|(e, scale)| {
501         let wave = WaveFunction::new(
502             potential,
503             mass,
504             *e,
505             approx_inf,
506             view_factor,
507             ScalingType::Mul(*scale),
508         );
509         println!("Calculated_{}_Energy\n", Ordinal(*e).to_string());
510         return wave;
511     })
512     .collect();
513
514     match scaling {
515         ScalingType::Mul(s) => SuperPosition {
516             wave_funcs,
517             scaling: s,
518         },
519         ScalingType::None => SuperPosition {
520             wave_funcs,
521             scaling: 1.0.into(),
522         },
523         ScalingType::Renormalize(s) => {
524             let unscaled = SuperPosition {
525                 wave_funcs: wave_funcs.clone(),
526                 scaling: s,
527             };
528             let factor = renormalize_factor(&unscaled, approx_inf);
529             println!("factor: {}", factor);
530             SuperPosition {
531                 wave_funcs,
532                 scaling: s * factor,
533             }
534         }
535     }
536 }
537
538 pub fn get_view(&self) -> (f64, f64) {
539     let view_a = self
540         .wave_funcs
541         .iter()
542         .map(|w| w.get_view().0)
543         .min_by(cmp_f64)
544         .unwrap();

```



```

545         let view_b = self
546             .wave_funcs
547             .iter()
548             .map(|w| w.get_view().1)
549             .max_by(cmp_f64)
550             .unwrap();
551         (view_a, view_b)
552     }
553 }
554
555 impl Func<f64, Complex64> for SuperPosition {
556     fn eval(&self, x: f64) -> Complex64 {
557         self.scaling * self.wave_funcs.iter().map(|w| w.eval(x)).sum:::<Complex64>()
558     }
559 }
560
561 struct Scaled<A, R>
562 where
563     R: std::ops::Mul<R, Output = R> + Sync + Send + Clone,
564 {
565     scale: R,
566     func: Box<dyn Func<A, R>>,
567 }
568
569 impl<A, R> Func<A, R> for Scaled<A, R>
570 where
571     R: std::ops::Mul<R, Output = R> + Sync + Send + Clone,
572 {
573     fn eval(&self, x: A) -> R {
574         self.func.eval(x) * self.scale.clone()
575     }
576 }
577
578 fn renormalize_factor(wave_func: &dyn Func<f64, Complex64>, approx_inf: (f64, f64))
579     -> f64 {
580     1.0 / integrate(
581         evaluate_function_between(
582             wave_func,
583             approx_inf.0 * (1.0 - f64::EPSILON),
584             approx_inf.1 * (1.0 - f64::EPSILON),
585             INTEG_STEPS,
586         )
587         .par_iter()
588         .map(|p| Point {
589             x: p.x,
590             y: p.y.norm_sqr(),
591         })
592         .collect(),
593     TRAPEZE_PER_THREAD,

```

```

593     )
594 }
595
596 pub fn renormalize(
597     wave_func: Box<dyn Func<f64, Complex64>>,
598     approx_inf: (f64, f64),
599 ) -> Box<dyn Func<f64, Complex64>> {
600     let area = renormalize_factor(wave_func.as_ref(), approx_inf);
601     return Box::new(Scaled::<f64, Complex64> {
602         scale: area.into(),
603         func: wave_func,
604     });
605 }
606
607 #[cfg(test)]
608 mod test {
609     use super::*;
610
611     #[test]
612     fn sign_check_complex_test() {
613         let range = (-50.0, 50.0);
614         let n = 100000;
615         for ri1 in 0..n {
616             for ii1 in 0..n {
617                 for ri2 in 0..n {
618                     for ii2 in 0..n {
619                         let re1 = index_to_range(ri1 as f64, 0.0, n as f64, range.0,
620                             range.1);
621                         let im1 = index_to_range(ii1 as f64, 0.0, n as f64, range.0,
622                             range.1);
623                         let re2 = index_to_range(ri2 as f64, 0.0, n as f64, range.0,
624                             range.1);
625                         let im2 = index_to_range(ii2 as f64, 0.0, n as f64, range.0,
626                             range.1);
627
628                         assert_eq!(
629                             sign_match_complex(complex(re1, im1), complex(re2, im2)),
630                             sign_match_complex(complex(re2, im2), complex(re1, im1))
631                         );
632                     }
633                 }
634             }
635         }
636     }
637 }

```

src/wkb_wave_func.rs

```
1 use crate::*;
```

```

2 use std::fmt::Display;
3 use std::sync::Arc;
4
5 #[derive(Clone)]
6 pub struct Phase {
7     pub energy: f64,
8     pub mass: f64,
9     pub potential: Arc<dyn Fn(f64) -> f64 + Send + Sync>,
10 }
11
12 impl Display for Phase {
13     fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
14         write!(
15             f,
16             "Phase_{{energy:_{},_mass:_{},_potential:_[func]}}",
17             self.energy, self.mass
18         )
19     }
20 }
21
22 impl Phase {
23     fn default() -> Phase {
24         Phase {
25             energy: 0.0,
26             mass: 0.0,
27             potential: Arc::new(|_x| 0.0),
28         }
29     }
30
31     pub fn new<F: Fn(f64) -> f64 + Sync + Send>(
32         energy: f64,
33         mass: f64,
34         potential: &'static F,
35     ) -> Phase {
36         return Phase {
37             energy,
38             mass,
39             potential: Arc::new(potential),
40         };
41     }
42
43     fn sqrt_momentum(&self, x: f64) -> f64 {
44         self.eval(x).abs().sqrt()
45     }
46 }
47
48 impl Func<f64, f64> for Phase {
49     fn eval(&self, x: f64) -> f64 {
50         (2.0 * self.mass * ((self.potential)(x) - self.energy))

```

```

51         .abs()
52         .sqrt()
53     }
54 }
55
56 #[derive(Clone)]
57 pub struct WkbWaveFunction {
58     pub c: Complex64,
59     pub turning_point_exp: f64,
60     pub turning_point_osz: f64,
61     pub phase: Arc<Phase>,
62     integration_steps: usize,
63     op: fn(Complex64) -> Complex64,
64     pub phase_off: f64,
65 }
66
67 impl WkbWaveFunction {
68     pub fn get_c(&self) -> Complex64 {
69         self.c
70     }
71
72     pub fn with_c(&self, c: Complex64) -> WkbWaveFunction {
73         WkbWaveFunction {
74             c,
75             turning_point_exp: self.turning_point_exp,
76             turning_point_osz: self.turning_point_osz,
77             phase: self.phase.clone(),
78             integration_steps: self.integration_steps,
79             op: self.op,
80             phase_off: self.phase_off,
81         }
82     }
83
84     pub fn new(
85         phase: Arc<Phase>,
86         c: Complex64,
87         integration_steps: usize,
88         turning_point_exp: f64,
89         turning_point_osz: f64,
90         phase_off: f64,
91     ) -> WkbWaveFunction {
92         return WkbWaveFunction {
93             c,
94             turning_point_exp,
95             turning_point_osz,
96             phase: phase.clone(),
97             integration_steps,
98             op: identity,
99             phase_off,

```

```

100     };
101 }
102
103 pub fn with_op(&self, op: fn(Complex64) -> Complex64) -> WkbWaveFunction {
104     return WkbWaveFunction {
105         c: self.c,
106         turning_point_exp: self.turning_point_exp,
107         turning_point_osz: self.turning_point_osz,
108         phase: self.phase.clone(),
109         integration_steps: self.integration_steps,
110         op,
111         phase_off: self.phase_off,
112     };
113 }
114
115 pub fn get_op(&self) -> Box<fn(Complex64) -> Complex64> {
116     Box::new(self.op)
117 }
118
119 pub fn get_exp_sign(&self) -> f64 {
120     let limit_sign = if self.turning_point_exp == self.turning_point_osz {
121         1.0
122     } else {
123         -1.0
124     };
125
126     self.psi_osz(self.turning_point_exp + limit_sign * f64::EPSILON.sqrt())
127         .re
128         .signum()
129 }
130
131 fn psi_osz(&self, x: f64) -> Complex64 {
132     let integral = integrate(
133         evaluate_function_between(
134             self.phase.as_ref(),
135             x,
136             self.turning_point_osz,
137             self.integration_steps,
138         ),
139         TRAPEZE_PER_THREAD,
140     );
141     -self.c * complex((integral - self.phase_off).cos(), 0.0) / self.phase.
        sqrt_momentum(x)
142 }
143
144 fn psi_exp(&self, x: f64) -> Complex64 {
145     let integral = integrate(
146         evaluate_function_between(
147             self.phase.as_ref(),

```

```

148         x,
149         self.turning_point_exp,
150         self.integration_steps,
151     ),
152     TRAPEZE_PER_THREAD,
153 );
154 let exp_sign = self.get_exp_sign();
155
156 exp_sign * (self.c * 0.5 * (-integral.abs()).exp())
157 }
158 }
159
160 impl Func<f64, Complex64> for WkbWaveFunction {
161     fn eval(&self, x: f64) -> Complex64 {
162         let val = if self.phase.energy < (self.phase.potential)(x) {
163             self.psi_exp(x)
164         } else {
165             self.psi_osz(x)
166         };
167
168         return (self.op)(val);
169     }
170 }
171
172 #[cfg(test)]
173 mod test {
174     use super::*;
175     use std::cmp::Ordering;
176
177     fn pot(x: f64) -> f64 {
178         1.0 / (x * x)
179     }
180
181     fn pot_in(x: f64) -> f64 {
182         1.0 / x.sqrt()
183     }
184
185     #[test]
186     fn phase_off() {
187         let energy_cond = |e: f64| -> f64 { (0.5 * (e - 0.5)) % 1.0 };
188
189         let integ = Function::<f64, f64>::new(energy_cond);
190         let mut values = evaluate_function_between(&integ, 0.0, 5.0, NUMBER_OF_POINTS);
191
192         let sort_func =
193             |p1: &Point<f64, f64>, p2: &Point<f64, f64>| -> Ordering { cmp_f64(&p1.x, &p2.x) };
194         values.sort_by(sort_func);

```

```

195     let mut data_file = File::create("energy.txt").unwrap();
196
197     let data_str: String = values
198         .par_iter()
199         .map(|p| -> String { format!("{}", p.x, p.y) })
200         .reduce(|| String::new(), |s: String, current: String| s + &*current);
201
202     data_file.write_all((data_str).as_ref()).unwrap()
203 }
204 }

```

lib/build.sh

```

1 #!/bin/bash
2
3 go get main
4 go build -o libairy.a -buildmode=c-archive main.go

```

lib/go.mod

```

1 module main
2
3 go 1.18
4
5 require gonum.org/v1/gonum v0.11.0

```

lib/main.go

```

1 package main
2
3 import "C"
4 import "gonum.org/v1/gonum/mathext"
5
6 //export airy_ai
7 func airy_ai(zr float64, zi float64) (float64, float64) {
8     z := mathext.AiryAi(complex(zr, zi))
9     return real(z), imag(z)
10 }
11
12 func main() {
13
14 }

```

build.rs

```

1 use std::env;
2 use std::path::PathBuf;
3 use std::process::Command;

```

```

4
5 fn main() {
6     Command::new("sh")
7         .arg("build.sh")
8         .current_dir("./lib/")
9         .status()
10        .unwrap();
11
12    let path = "./lib";
13    let lib = "airy";
14
15    println!("cargo:rustc-link-search=native={}", path);
16    println!("cargo:rustc-link-lib=static={}", lib);
17
18    // The bindgen::Builder is the main entry point
19    // to bindgen, and lets you build up options for
20    // the resulting bindings.
21    let bindings = bindgen::Builder::default()
22        // The input header we would like to generate
23        // bindings for.
24        .header("lib/libairy.h")
25        // Tell cargo to invalidate the built crate whenever any of the
26        // included header files changed.
27        .parse_callbacks(Box::new(bindgen::CargoCallbacks))
28        // Finish the builder and generate the bindings.
29        .generate()
30        // Unwrap the Result and panic on failure.
31        .expect("Unable to generate bindings");
32
33    // Write the bindings to the $OUT_DIR/bindings.rs file.
34    let out_path = PathBuf::from(env::var("OUT_DIR").unwrap());
35    bindings
36        .write_to_file(out_path.join("bindings.rs"))
37        .expect("Couldn't write bindings!");
38 }

```

Cargo.toml

```

1 [package]
2 name = "shroedinger_approx"
3 version = "0.1.0"
4 edition = "2021"
5
6 # See more keys and their definitions at https://doc.rust-lang.org/cargo/reference/manifest.html
7
8 [dependencies]
9 num = "0.4.0"
10 tokio = { version = "1.0.3", features = ["full"] }

```



```

11 rayon = "1.5.3"
12 scilib = "0.5.0"
13 ordinal = "0.3.1"
14
15 [build-dependencies]
16 bindgen = "0.60.1"

```

energy.wsl

```

1 m = 1
2 V[x_] = x^2
3
4 nthEnergy[n_] = Module[{energys, energy},
5   energys = Solve[Integrate[Sqrt[2*m*(en - V[x])], {x, -Sqrt[en], Sqrt[en]}] == 2*
6     Pi*(n + 1/2), en] // N;
7   energy = en /. energys[[1]];
8   energys
9 ]
10 energys = Table[{n, N@nthEnergy[n]}, {n, 0, 50}]
11
12 csv = ExportString[energys, "CSV"]
13 csv = StringReplace[csv, "," -> " "]
14 Export["output/energys_exact.dat", csv]

```

exact.wsl

```

1 c1 = -5.0
2 c2 = 1.0
3 numberOfPoints = 1000
4 m = 2
5 n = 5
6 viewFactor = 1.5
7
8 V[x_] := x^2
9
10 energys = Solve[Integrate[Sqrt[2*m*(en - V[x])], {x, -Sqrt[en], Sqrt[en]}] == 2*Pi*(n
11   + 1/2), en] // N
12
13 energy = en /. energys[[1]]
14
15 view = Solve[energy == V[x], x]
16 view = Function[l, x /. l] /@ view
17 view = Function[x, x*viewFactor] /@ view
18
19 Print["Energy = ", energy]
20 Print["view = ", view]
21

```

```

22 solution := DSolve[{V[x] psi[x] - psi''[x]/(2 m) == energy psi[x]}, psi[x], x]
23 psi[x_] = psi[x] /. solution[[1]] /. C[1] -> c1 /. C[2] -> c2
24
25 Print["psi[x] = ", psi[x]]
26
27 (*psi[x_] = c2*ParabolicCylinderD[(-1 - 50*Sqrt[m])/2, *)
28   (*I*2^(3/4)*m^(1/4)*x] + c1*ParabolicCylinderD[(-1 + 50*Sqrt[m])/2, *)
29   (*2^(3/4)*m^(1/4)*x]*)
30
31
32
33 step = (Abs[view[[1]]] + Abs[view[[2]]]) / numberOfPoints
34
35
36 vals = Table[{x, N@psi[x]}, {x, view[[1]], view[[2]], step}]
37 vals = Function[p, {p[[1]], Re[p[[2]]], Im[p[[2]]]}] /@ vals
38 Print["psi[0] = ", psi[0]]
39
40 total = N@Integrate[Re[psi[x]]^2 + Im[psi[x]]^2, {x, -Sqrt[energy], Sqrt[energy]}]
41
42 Print["area under solution = ", total]
43 total = N@Integrate[Abs[psi[x]], {x, -Sqrt[energy], Sqrt[energy]}]
44 Print["area under solution after renormalization = ", N@Integrate[Re[psi[x]]^2 + Im[
    psi[x]]^2, {x, -Sqrt[energy], Sqrt[energy]}]]
45
46 vals = Function[p, {p[[1]], p[[2]] / total, p[[3]] / total}] /@ vals
47
48 csv = ExportString[vals, "CSV"]
49 csv = StringReplace[csv, "," -> " "]
50 Export["output/exact.dat", csv]

```

Bildquellen

Wo nicht anders angegeben, sind die Bilder aus dieser Arbeit selbst erstellt worden.

Bibliography

CODATA. CODATA Value: Planck Length. <https://physics.nist.gov/cgi-bin/cuu/Value?plkl>, 2022a.

CODATA. CODATA Value: Planck Mass. <https://physics.nist.gov/cgi-bin/cuu/Value?plkm>, 2022b.

CODATA. CODATA Value: Planck Time. <https://physics.nist.gov/cgi-bin/cuu/Value?plkt>, 2022c.

Bryce Seligman DeWitt und Neill Graham. *The many-worlds interpretation of quantum mechanics*, volume 63. Princeton University Press, 2015.

Espen Gaarder Haug. The gravitational constant and the Planck units. A simplification of the quantum realm. *Physics Essays*, 29(4):558–561, 2016.

Brain C. Hall. *Quantum Theory for Mathematicians*. Springer New York, NY, 1 edition, 2013. ISBN 978-1461471158.

Christopher Kormanyos John Maddock. Calculating a Derivative - 1.58.0. https://www.boost.org/doc/libs/1_58_0/libs/multiprecision/doc/html/boost_multiprecision/tut/floats/fp_ 2022.

Robert G. Littlejohn. Physics 221A, 2020. URL [url{https://www.pas.rochester.edu/~passage/resources/prelim/Quantum/UCB%20Notes/7%20wkb.pdf}](https://www.pas.rochester.edu/~passage/resources/prelim/Quantum/UCB%20Notes/7%20wkb.pdf).

Erwin Schrödinger. Die gegenwärtige Situation in der Quantenmechanik. *Naturwissenschaften*, 23, 1935.

Tanja Van Mourik, Michael Bühl, und Marie-Pierre Gageot. Density functional theory across chemistry, physics and biology, 2014.

Eric W. Weisstein. Newton’s Method, 2022. URL <https://mathworld.wolfram.com/NewtonsMethod.html>. [Online; accessed 10-August-2022].

Wkipedia. Numerical integration, 2022. URL https://en.wikipedia.org/wiki/Numerical_integration. [Online; accessed 10-August-2022].

Barton Zwiebach. MIT 8.06 Quantum Physics III, 2018. URL [url{https://ocw.mit.edu/courses/8-06-quantum-physics-iii-spring-2018/resources/l7-3/}](https://ocw.mit.edu/courses/8-06-quantum-physics-iii-spring-2018/resources/l7-3/).

Selbständigkeitserklärung

Hiermit bestätige ich, Gian Laager, meine Maturaarbeit selbständig verfasst und alle Quellen angegeben zu haben.

Ich nehme zur Kenntnis, dass meine Arbeit zur Überprüfung der korrekten und vollständigen Angabe der Quellen mit Hilfe einer Software (Plagiaterkennungstool) geprüft wird. Zu meinem eigenen Schutz wird die Software auch dazu verwendet, später eingereichte Arbeiten mit meiner Arbeit elektronisch zu vergleichen und damit Abschriften und eine Verletzung meines Urheberrechts zu verhindern. Falls Verdacht besteht, dass mein Urheberrecht verletzt wurde, erkläre ich mich damit einverstanden, dass die Schulleitung meine Arbeit zu Prüfzwecken herausgibt.

Ort

Datum

Unterschrift