



PROTECTION										<table><tr><td>R0-B L/R</td><td>25.4</td><td>273.1</td><td>1</td><td>12"</td></tr><tr><td>DC9</td><td>14</td><td>86.3</td><td>2</td><td>4"</td></tr><tr><td>DC3 + DC8</td><td>31</td><td>344</td><td>1</td><td>16"</td></tr><tr><td>DC1 - DC2</td><td>35</td><td>387</td><td>1</td><td>18"</td></tr><tr><td>R5</td><td>14</td><td>140</td><td>2</td><td>6"</td></tr><tr><td>R1 + R4</td><td>46</td><td>518</td><td>1</td><td>24"</td></tr><tr><td>N2</td><td>21</td><td>669</td><td>1</td><td>28"</td></tr></table>										R0-B L/R	25.4	273.1	1	12"	DC9	14	86.3	2	4"	DC3 + DC8	31	344	1	16"	DC1 - DC2	35	387	1	18"	R5	14	140	2	6"	R1 + R4	46	518	1	24"	N2	21	669	1	28"											<table><tr><td>LATO TUBI</td><td>TUBE SIDE</td><td>20012</td><td>Lt.</td></tr><tr><td>APPARECCHIO VUOTO</td><td>TOTAL EMPTY (Without refractory)</td><td>103900</td><td>kg.</td></tr><tr><td>APPARECCHIO VUOTO</td><td>TOTAL EMPTY (With refractory)</td><td>110000</td><td>kg.</td></tr></table>										LATO TUBI	TUBE SIDE	20012	Lt.	APPARECCHIO VUOTO	TOTAL EMPTY (Without refractory)	103900	kg.	APPARECCHIO VUOTO	TOTAL EMPTY (With refractory)	110000	kg.	SPECIFICHE CLIENTE CARICHI AMM. MATER.										CLIENT SPECIFICATION MATER. ALLOW. STRESS										ASME II PART D ED.2010 ASME VIII DIV.2-2010+Ad.2011										ASME II PART D ED.2010 ASME VIII DIV.2-2010+Ad.2011										2103-ESS-01-PR-101 rev.2/2103-REQ-A-HM-255 rev.4										APPROVED _____																			
R0-B L/R	25.4	273.1	1	12"																																																																																																																																																								
DC9	14	86.3	2	4"																																																																																																																																																								
DC3 + DC8	31	344	1	16"																																																																																																																																																								
DC1 - DC2	35	387	1	18"																																																																																																																																																								
R5	14	140	2	6"																																																																																																																																																								
R1 + R4	46	518	1	24"																																																																																																																																																								
N2	21	669	1	28"																																																																																																																																																								
LATO TUBI	TUBE SIDE	20012	Lt.																																																																																																																																																									
APPARECCHIO VUOTO	TOTAL EMPTY (Without refractory)	103900	kg.																																																																																																																																																									
APPARECCHIO VUOTO	TOTAL EMPTY (With refractory)	110000	kg.																																																																																																																																																									
INTERNAL SURFACES: DRAINED AND THOROUGHLY CLEANED. N2 FILLED FOR SHIPMENT. INSULATION BY OTHERS - INSULATION SUPPORT BY OLMI ACC. TO 7523-01-500-03. STUB END BEVEL: COATED WITH SUITABLE CORROSION INHIBITOR.										** : INCLUDING REFRACTORY INLET CHANNEL										NORME & CODICI CODES & NORMS -- COLLAUDO APPAR. EXCH. INSP. & TEST CERTIFICAZIONE CODE TESTING										OLMI Q.C. / CLIENT OLMI Q.C. / CLIENT										DISEGNO DEFINITIVO Il cliente ha già preso visione del disegno ed ha approvato le parti non evidenziate dall'ultima rev. VALID FOR CONSTRUCTION Drawing already approved by client except where										<table><tr><th>REV.</th><th>DATE</th><th>DESCRIPTION</th><th>BY</th><th>CHECKED</th><th>STATUS</th></tr><tr><td>6</td><td>22/01/15</td><td>REVISED WHERE MARKED & REISSUED FOR FINAL APPROVAL</td><td>SP</td><td>SS</td><td>SS</td></tr><tr><td>5</td><td>19/11/14</td><td>REVISED WHERE MARKED & REISSUED FOR FINAL APPROVAL</td><td>GPS</td><td>SP</td><td>SS</td></tr><tr><td>4</td><td>15/05/14</td><td>REVISED AS INDICATED</td><td>SP</td><td>SS</td><td>SS</td></tr><tr><td>3</td><td>25/10/13</td><td>REVISED AS INDICATED</td><td>PM</td><td>FG</td><td>SS</td></tr><tr><td>2</td><td>20/04/13</td><td>GENERAL PURPOSE</td><td>PM</td><td>FG</td><td>SS</td></tr></table>										REV.	DATE	DESCRIPTION	BY	CHECKED	STATUS	6	22/01/15	REVISED WHERE MARKED & REISSUED FOR FINAL APPROVAL	SP	SS	SS	5	19/11/14	REVISED WHERE MARKED & REISSUED FOR FINAL APPROVAL	GPS	SP	SS	4	15/05/14	REVISED AS INDICATED	SP	SS	SS	3	25/10/13	REVISED AS INDICATED	PM	FG	SS	2	20/04/13	GENERAL PURPOSE	PM	FG	SS																																																													
																																																		REV.	DATE	DESCRIPTION	BY	CHECKED	STATUS																																																																																																					
																																																		6	22/01/15	REVISED WHERE MARKED & REISSUED FOR FINAL APPROVAL	SP	SS	SS																																																																																																					
5	19/11/14	REVISED WHERE MARKED & REISSUED FOR FINAL APPROVAL	GPS	SP	SS																																																																																																																																																							
4	15/05/14	REVISED AS INDICATED	SP	SS	SS																																																																																																																																																							
3	25/10/13	REVISED AS INDICATED	PM	FG	SS																																																																																																																																																							
2	20/04/13	GENERAL PURPOSE	PM	FG	SS																																																																																																																																																							

		#2 SET GASKET.		IBD1/IBD2	2	2"	1500Lb. LWN-RTJ	Inter. Blow down Heating system	M1	1	24"	PAD+COVER	Manhole	LATO MANTELLO	ATTACCHI EST.	EXT. ATTACHMENTS	CORROSIONE				3	mm.	3	mm.
				HPS	1	2"	1500Lb. LWN-RTJ								BOCCHE/VIROLA			TEMP. ENT./USCITA	INL./OUT. TEMPERATURE	323.3 / 323.3	°C	967.5 / 355	°C	
				DC9	1	4"	STUB END	Downcomers	K1	1	4"	SPECIAL SEE DWG.	By-Pass Actuator					TEMP. DI PROGETTO	DESIGN TEMPERATURE	335	°C	1010 Inlet / 410 Outlet	°C	
				DC3+DC8	6	16"	STUB END	Downcomers	DR1	1	2"	600Lb. LWN-RF	Drain					TEMP. MIN. PROGETTO	M.D.M.T.	-27	°C	-27	°C	
				DC1-DC2	2	18"	STUB END	Downcomers	T	1	1 1/2"	600Lb. LWN-RF	Thermowell											
				R5	1	6"	STUB END	Risers	N2	1	28"	STUB END	Gas outlet											
				R1+R4	4	24"	STUB END	Risers	N1	1	Ø1500	STUB END	Gas inlet											
														ULTIMA SALDATURA										