


```
In [1]: #make necesarry imports
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
from math import sqrt
import sys, os
from contextlib import contextmanager
import matplotlib as mpl
import seaborn as sns
import sklearn
```

Forecasting

1. Visualize and interpret the pattern of this time-series

```
In [2]: df = pd.read_csv('data.csv')
df.head()
plt.plot(df['Sales'])
plt.show()
```




2. Predict future demand in the four next quarters without seasonality

Using moving average

```
In [3]: # Using moving average
def moving_average(df, k, to_period):
    moving_average_df = pd.DataFrame(columns=['Period', 'Sales'])
    num_df = len(df)
    for m in range(0, to_period):
        if m < k:
            sale_predict = float('nan')
        else:
            history = df['Sales'][m-k:m]
            sale_predict = history.mean()
            moving_average_df.loc[m] = [m+1, sale_predict]

    moving_average_df['Period'] = moving_average_df['Period'].astype(int)
    return moving_average_df

f, ax = plt.subplots(1, 1)
ma_df = moving_average(df, 3, 16)
sns.pointplot(x='Period', y='Sales', data=df, color='b')
sns.pointplot(x='Period', y='Sales', data=ma_df, color='g')
ax.legend(handles=ax.lines[:,len(df)+1], labels=["Actual", "3-MA"])
plt.show()
```



Using linear regression


```
In [4]: def linear_regression(df):
    linear_df = df.copy()
    linear_df['PeriodSales'] = linear_df['Period'] * linear_df['Sales']
    linear_df['Period_2'] = linear_df['Period'] * linear_df['Period']
    linear_df['Sales_2'] = linear_df['Sales'] * linear_df['Sales']
    linear_sum = linear_df.sum()
    linear_mean = linear_df.mean()

    b = (linear_sum['PeriodSales'] - len(df) * linear_mean['Period'] * linear_mean['Sales']) \
        / (linear_sum['Period_2'] - len(df) * linear_mean['Period'] * linear_mean['Period'])
    a = linear_mean['Sales'] - b * linear_mean['Period']
    return a,b

a,b = linear_regression(df)
linear_df = pd.DataFrame(columns=['Period', 'Sales'])
for m in range(1, 17):
    sale = a + b * m
    linear_df.loc[m-1] = [m,sale]
linear_df['Period'] = linear_df['Period'].astype(int)

f, ax = plt.subplots(1, 1)
sns.pointplot(ax=ax, x='Period', y='Sales', data=df, color='b')
sns.pointplot(ax=ax, x='Period', y='Sales', data=linear_df, color='g')


ax.legend(handles=ax.lines[:,len(df)+2], labels=["Actual", "Linear Regression"])
plt.show()
```



4.Evaluation: compare the above implemented methods

```
In [5]: eval_df = pd.read_csv('actual.csv')
eval_df = pd.concat([df, eval_df], ignore_index=True)
sns.pointplot(x='Period', y='Sales', data=eval_df, color='b')
```

Out[5]: <matplotlib.axes._subplots.AxesSubplot at 0x1b9415cbf98>



```
In [6]: MSE = (eval_df['Sales'][12:16] - moving_average(eval_df, 3, 16)['Sales'][12:16])**2
MSE = MSE.mean()
MSE = (eval_df['Sales'][12:16] - linear_df['Sales'][12:16])**2
MSE = MSE.mean()
print("MSE of {0}: {1}".format("Linear Regression", MSE))
```

MSE of Linear Regression: 5629390.883826157