





Master Thesis

## DeepFake Detection Exploiting Self-Attention Maps

**Supervisor:** Prof. Lorenzo Seidenari

Co-supervisor: Luca Cultrera, PhD

Gianmarco Santoro

24/04/2024



## università degli studi FIRENZE

#### **REAL or FAKE?**

**Benefit** → **Special effects** 

**Problem**  $\rightarrow$  **Disinformation** 











### **Supervised methods**

- **Trained on specific forgeries** → **cannot detect unseen ones**
- Very high accuracy in detection






**DeepFakes** 



**FaceShifter** 



Face2Face



**NeuralTextures** 










#### **Out-of-Distribution Detection**

- Identifying data different from training distribution
- In this case between 2 classes
  - $\circ$  Real images  $\rightarrow$  In-Distribution
  - $\circ$  Fake images  $\rightarrow$  Out-of-Distribution






# FIRENZE

### **Unsupervised method**

- → extract Attention
- Conv-AE → discern between In-distribution and Out-of-Distribution images








#### ViT Face-Transformer

- Originally → Face recognition: identity
- Out method → Feature extraction: Attention








#### **Example - Vision Attention in Vision Transformer**

Architecture

- → Original ViT
- Vision Attention → from this research


## **Transformer Encoder** Lx MLP Norm Multi-Head Attention Norm Embedded Patches

#### **Attention Heatmap**



### **Heatmap on Frame**








#### Conv-AE

- Architecture trained to reconstruct its input accurately
- How:
  - Encoder compresses input in lower-dimensional latent space
  - Decoder reconstruct original input from compressed representation






#### $Data \to ViT \to Attention \ extraction \to HeatMaps \ Dataset \to$

- $\rightarrow$  Train Conv-AE on REALs  $\rightarrow$  Test on All Images  $\rightarrow$
- → Reconstruction Error: Real or Fake

Trained on In-Distribution images only







#### FaceForensics++ dataset

- 1000 videos from YouTube
  - 1 person per video
- ~ 100 frames per video
- 5 Forgeries + Real
- Dataset split on videos
  - $\circ$  Train  $\rightarrow$  80 %
  - Validation  $\rightarrow$  10 %
  - $\circ \quad \textbf{Test} \qquad \rightarrow \textbf{10 \%}$


11	EGEND:	DATASETS		
	IN DISTRIBUTION OUT-OF-DISTRIBUTION	TRAINING	VALIDATION	TEST
	REAL	79′954	9'995	10'000
	DEEPFAKES	*	*	10'000
I M A G E S	FACE2FACE	*	*	10'000
	FACESHIFTER	*	*	10'000
3	FACESWAP	*	*	10'000
	NEURAL TEXTURES	*	*	10'000

**SCHOOL** FOR ADVANCED LUCCA





FIRENZE


#### **AUROC** $\rightarrow$ **AUC** calculated on ROCs




False Positive Rate

















### On the method proposed

- **Validated**
- Independent from specific forgery
  - Transfer learning to new forgeries
- **Performance** 
  - Better than RGB-based random chance
  - Minor than Supervised SotA methods

AUROC   Real vs Forged Images Models Detection Ability					
Forgery	Attention-based	RGB-based			
Deepfakes	0.62	0.51			
Face2Face	0.62	0.51			
FaceShifter	0.59	0.58			
FaceSwap	0.61	0.50			
NeuralTextures	0.54	0.50			
All forgeries	$\rightarrow$ 0.60	> 0.49			

#### **Future advancements**

- Try on ViT for demographic classification
  - E.g. MiVOLO: Multi-input Transformer for Age and Gender Estimation







UNIVERSITÀ DEGLI STUDI FIRENZE



## Thanks for your Attention







### UNIVERSITÀ DEGLI STUDI FIRENZE

#### **REFERENCES:**

- 1. Luca Cultrera, Lorenzo Seidenari, and Alberto Del Bimbo | "Leveraging Visual Attention for out-of-Distribution Detection" | Proceedings of the IEEE/CVF International Conference on Computer Vision | 2023
- 2. Zhong, Yaoyao, and Weihong Deng | "Face transformer for recognition" | arXiv preprint arXiv:2103.14803 | 2021
- 3. Kuprashevich, Maksim, and Irina Tolstykh | "MiVOLO: Multi-input Transformer for Age and Gender Estimation" | arXiv preprint arXiv:2307.04616 | 2023
- 4. Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., ... & Polosukhin, I. | 2017 | "Attention is All You Need" | In Advances in Neural Information Processing Systems (pp. 5998-6008)
- 5. Alexey Dosovitskiy\*,†, Lucas Beyer\*, Alexander Kolesnikov\*, Dirk Weissenborn\*, Xiaohua Zhai\*, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, Neil Houlsby\*,† \* equal technical contribution, † equal advising Google Research, Brain Team | "An Image is Worth 16 x 16 Words: Transformers for Image Recognition at Scale" | at ICLR 2021
- 6. <a href="https://niessnerlab.org/projects/roessler2018faceforensics.html">https://niessnerlab.org/projects/roessler2018faceforensics.html</a>
- 7. <a href="https://medium.com/@birla.deepak26/autoencoders-76bb49ae6a8f">https://medium.com/@birla.deepak26/autoencoders-76bb49ae6a8f</a>
- 8. <a href="https://seeflection.com/22579/viral-deepfake-on-tiktok-causes-outrage/">https://seeflection.com/22579/viral-deepfake-on-tiktok-causes-outrage/</a>
- $9. \qquad \underline{https://towardsdatascience.com/using-transformers-for-computer-vision-6f764c5a078b}$
- 10. <a href="https://encord.com/blog/what-is-out-of-distribution-ood-detection/">https://encord.com/blog/what-is-out-of-distribution-ood-detection/</a>