

# Deep Imbalanced Regression

Yang Y, Zha K, Chen Y, Wang H, Katabi D

ICML 2021

Presenter: Gianmarco Midenia

26 November 2024

## Deep Imbalanced Regression






Image credit: [Yang et al. \(2021\)](#)

# Test Error on Categorical vs. Continuous Label Space



(a) CIFAR-100 (subsamped)



(b) IMDB-WIKI (subsamped)

Image credit: [Yang et al. \(2021\)](#)

# Problem Settings

- $\{(\mathbf{x}_i, y_i)\}_{i=1}^N$ : training set
- $\mathbf{x}_i \in \mathbb{R}^d$ : input
- $y_i \in \mathcal{Y}$ : continuous label or target
- $b_i \in \mathcal{B}$ : discrete label or target
- $\mathcal{Y} \subset \mathbb{R}$ : continuous label space
- $\mathcal{B} = \{1, \dots, M\} \subset \mathbb{Z}^+$ : index space
  - ▶ divides  $\mathcal{Y}$  into  $M$  groups (bins) with equal intervals  $[t_j, t_{j+1})$
  - ▶  $\{[t_0, t_1), \dots, [t_{M-1}, t_M)\}$ : discrete label space
  - ▶  $t_k \in \mathcal{Y}$
  - ▶ minimum resolution
    - ★ e.g.,  $\delta y \triangleq t_{j+1} - t_j = 1$  in age estimation
- $\hat{y}_i = g(\mathbf{z}_i) \in \mathbb{R}$ : predicted continuous label
- $\mathbf{z}_i = f(\mathbf{x}_i; \theta) \in \mathbb{R}^{d'}$ : learned representation
- $\theta$ : trainable model parameters

# Label Distribution Smoothing




Image credit: [Yang et al. \(2021\)](#)

# Feature Distribution Smoothing




Image credit: [Yang et al. \(2021\)](#)

# Baselines (1/2)

- Vanilla: neglects data imbalance
- Synthetic samples
  - ▶ SMOTER ([Torgo et al. 2013](#))
    - ① Defines frequent and rare regions using label density.
    - ② Creates synthetic samples for pre-defined rare regions by linearly interpolating both inputs and labels.
  - ▶ SMOGN ([Branco et al. 2017](#)): augments SMOTER with Gaussian noise
- Focal-R

$$\frac{1}{n} \sum_{i=1}^n \sigma(|\beta e_i|)^{\gamma} e_i$$

- ▶ Error-aware loss
- ▶ Maps the absolute error into  $[0, 1]$ .
- ▶  $e_i$ :  $L_1$  error for the  $i$ -th sample
- ▶  $\beta, \gamma$ : hyper-parameters
- ▶ Inspired by Focal Loss ([Lin 2017](#)) for classification

# Baselines (2/2)

- Regressor re-training (RRT)
  - ▶ Two-stage training
    - 1 Train encoder
    - 2 Re-train regressor with inverse re-weighting and frozen encoder.
  - ▶ Inspired by [Kang et al. 2019](#)
- Cost-sensitive re-weighting: re-weighting schemes based on label distribution
  - ▶ Inverse-frequency weighting (INV)
  - ▶ Square-root weighting variant (SQINV)



# Evaluation

- Divide target space into disjoint regions (bins)

- ▶ *Many-shot*: > 100 training examples
- ▶ *Medium-shot*: 20-100 training examples
- ▶ *Few-shot*: < 20 training examples
- ▶ *Zero-shot*: 0 training examples
- Inspired by [Liu et al. 2019](#)

- Metrics

- ▶ Mean Absolute Error (MAE)
- ▶ Mean Squared Error (MSE)
- ▶ Pearson Correlation (PCC)
- ▶ Geometric Mean Error (GME)

$$GME = \sqrt[n]{\prod_{i=1}^n |y_i - \hat{y}_i|}$$

★ Pros: + fairness (uniformity) in prediction

# References

- Branco, Paula, Luís Torgo, and Rita P Ribeiro (2017). "SMOGLN: a pre-processing approach for imbalanced regression". In: *First international workshop on learning with imbalanced domains: Theory and applications*. PMLR, pp. 36–50.
- Kang, Bingyi et al. (2019). "Decoupling representation and classifier for long-tailed recognition". In: *arXiv preprint arXiv:1910.09217*.
- Lin, T (2017). "Focal Loss for Dense Object Detection". In: *arXiv preprint arXiv:1708.02002*.
- Liu, Ziwei et al. (2019). "Large-scale long-tailed recognition in an open world". In: *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 2537–2546.
- Torgo, Luís et al. (2013). "Smote for regression". In: *Portuguese conference on artificial intelligence*. Springer, pp. 378–389.
- Yang, Yuzhe et al. (2021). "Delving into deep imbalanced regression". In: *International conference on machine learning*. PMLR, pp. 11842–11851.