Project Plan Document - v1.0

Gianpaolo Branca

Luca Butera

Andrea Cini



POLITECNICO MILANO 1863

Contents

1 Introduction		3
1.1 Purpose and Scope	 	 . 3
1.2 Definitions, Acronyms, Abbreviations		
1.3 Reference documents		
2 Project size, cost and effort estimation		3
2.1 Size estimation: function points	 	 . 3
2.1.1 Internal Logic Files (ILFs)	 	 . 4
2.1.2 External Logic Files (ELFs)		
2.1.3 External Inputs (EIs)		
2.1.4 External Inquiries (EQs)		
2.1.5 External Outputs (EOs)		
2.1.6 Overall Estimation		
2.2 Cost and effort estimation: COCOMO II		
2.2.1 Scale drivers	 	 . 10
2.2.2 Cost drivers		
$2.2.3$ Effort equation $\dots \dots \dots \dots \dots$		
2.2.4 Schedule estimation		

1 Introduction

1.1 Purpose and Scope

1.2 Definitions, Acronyms, Abbreviations

- Data element type (DET): a unique user recognizable, non recursive, field.
- Record element type (RET): Record elements type, a user recognizable subgroup of data elements.
- File types referenced (FRT): files updated or referenced in a transaction.
- MSO: Money saving option.
- SA: Safe Areas.

1.3 Reference documents

2 Project size, cost and effort estimation

In this section we will use well known approaches to project planning to estimate di dimension and the cost in time and money that our project will have. We will use the Function Points approach for the size estimation and than COCOMO for the cost and effort estimation and we will not consider, for the most part, the presentation layer.

2.1 Size estimation: function points

In the following tables the reference tables we are going to use for the size estimation, they classify the complexity of each element counting the numbers of file types referenced, data element types and record element types. Obviously we are going to consider these reference values, but we are also going to estimate the complexity of the components based on the specific knowledge that we have acquired about the domain of our system.

Table 1: Logic Files

	Data Elements		
Record Elements	1-19	20-50	51+
1	Low	Low	Avg
2-5	Low	Avg	High
6+	Avg	High	High

Table 2: My caption

	Data Elements		
File Types	1-5	6-19	20+
0-1	Low	Low	Avg
2-3	Low	Avg	High
4+	Avg	High	High

Table 3: External Input


	Data Elements		
File Types	1-4	5-15	16+
0-1	Low	Low	Avg
2-3	Low	Avg	High
4+	Avg	High	High

Table 4: Function Points

	Complexity Weight		
Function Type	Low	Average	High
Internal Logic Files	7	10	15
External Logic Files	5	7	10
External Inputs	3	4	6
External Outputs	4	5	7
External Inquiries	3	4	6

2.1.1 Internal Logic Files (ILFs)

In this section we are going to analyze the complexity of our ILFs, we are going to refer to this simplified version of the model of the internal representation of our data (some attributes of the classes in the pictures are obviously not persistent but representative of the complexity of the informations related with the single entity):



• Users:

- Estimated complexity: Average

The first type of internal data our system will have to deal with are the user related ones. The handling of the user data, even if well standardized, requires a lot of care and because of the personalization functionality of the user's profile and periodic checks to be performed on driving licenses and PayPal accounts they will not be entirely static.

• Rides:

Estimated complexity: Low

The rides data handling will be straight forward with the creation of the entity at the start of a ride and the update of the main fields when the ride is ended. The only dynamic aspect of the ride is the "paid" field that has to be updated when the payment is obtained.

• Bookings:

Estimated complexity: Low

The information about cars bookings are static and easy to manage.

• Cars:

- Estimated complexity: High

The status of the cars are is the most critical type of data that our system will have to handle, informations about the cars dynamic and complex to retrieve.

• Assistance requests:

Estimated complexity: Low

Easy informations to handle, static once generated (only the status changes only once).

• Fares/PriceVariations:

- Estimated complexity: Low

Static informations that can be updated by the management system, easy to handle and maintain.

- Safe and RechargingArea:
 - Estimated complexity: Average

Static information about the position of safe areas and dynamic updated to the number of plugs available, average complexity (high complexity only for the creation of the objects)

Table 5: ILF

ILF	Complexity	FPs
Users Data	Average	10
Rides Data	Low	7
Bookings Data	Low	7
Cars Data	High	15
Assistance Requests Data	Low	7
System parameters	Low	7
Areas Data	Low	10
Total		63

2.1.2 External Logic Files (ELFs)

The external data sources we rely on are PayPal, for the payments handling and GoogleMaps for the maps and navigation related services.

- PayPal:
 - Estimated complexity: Low

Simple files containing payment informations.

- GoogleMaps:
 - Estimated complexity: High


We heavily rely on the files produced by the GoogleMaps service, for both the navigation and the maps functionalities, we consider that both of this elements have to be considered to have an high complexity.

Table 6: ELF

ELF	Complexity	FPs
Payment info	(Very)Low	2
Navigation Data	High	10
Maps Data	High	10
Total		22

2.1.3 External Inputs (EIs)

We report here the component interfaces diagrams that will become handy in the next sections.



Our system will have to deal mainly with the following kinds of inputs:

• Login/logout of operators and users: simple operations. Both low complexity.

From the users:

- Login/logout operation: simple operations with simple operations of validations on data. Both operations have a low complexity.
- Registration: operation of an average complexity, it requires only a small amount of checks.
- QR-code check-in: simple operation but that requires some components to be handled. Average complexity.
- car locking/unlocking: simple operations that involve a good number of components. Both average complexity.
- Search for car: complex operation that needs the collaboration of a good number of components. High complexity.
- Book/un-book a car: simple operations but that change the status of car. Both average complexity.
- Payment: simple operation. Low complexity.
- Money saving option: a complex operation that involves multiple components. High complexity.

• Ride data: data that the system receive during the ride. Hard to handle, high complexity.

From the operator:

- Get car overview: complex operation of data retrieval. High complexity.
- Assistance request: not so complex operation that generates a request form to be sent to the legacy system. Average complexity.
- Insertion/delation of safe or recharging areas: they are crucial parameters for the system. Both high complexity.
- Insertion/delation of a car: complex operations involving multiple components. Both high complexity.
- Overall view: overall view of all the cars and their position. High complexity.
- Parameters modification: simple modification but they have to be notified to the users. Average complexity.

Tabl		7.	\mathbf{F}	S
Tab	+	1:	1771	כו

EIs	Complexity	FPs
Login/Logout	Low	2*3
Registration	Average	4
Qr-code check-in	Average	4
Car locking/unlocking	Average	2*4
Search for a car	High	6
Book/unbook	Average	2*4
Payment	Low	3
MSO	High	6
Ride data	High	6
Overall view	High	6
Car overview	High	6
Assistance request	Average	4
Insert/delete SA	High	2*6
Insert/delete car	High	2*6
Parameters modification	Average	4
Total		95

2.1.4 External Inquiries (EQs)

The main operations of simple data retrieval are:

- User profile: operation of average complexity.
- System parameters and safe area: both operation of average complexity.
- Payment history: low complexity operation, simple interaction with PayPal.
- Ride history: low complexity operation.

Table 8: EQ

10010 0. 11 0		
EIs	Complexity	FPs
User Profile	Average	4
Payment history	Low	3
Ride history	Low	3
System parameters and SA	Average	2*4
Total		18

2.1.5 External Outputs (EOs)

The external output that our system produce are the mainly correlated with the notification system that we estimate having a cost of 12 function points. The other output is the assistance request sent to the legacy system, operation that has an average complexity.

Table 9: EOS

Eos	Complexity	FPs
Notification system		12
Assistance request	Average	5
Total		17

2.1.6 Overall Estimation

Our analysis has produced the following data:

Table 10: Total function points

Function Type	Value
Internal Logic Files	63
External Logic Files	22
External Inputs	95
External Inquiries	18
External Outputs	17
Total	215

With Java Enterprise edition as development platform and without considering in depth the aspects of the development of the mobile and web applications, we end up with the following results:

Average estimation: SLOC = 46 * 215 = 9890

High estimation: SLOC = 67 * 215 = 14405

(Function point language table from www.qsm.com)

2.2 Cost and effort estimation: COCOMO II

In this section we are going to use the COCOMO II model to estimate the cost and effort needed for our project.

2.2.1 Scale drivers

Table 11: Scale factors values

SFs	Very Low	Low	Nominal	High	Very High	Extra high
PREC	thoroughly	largely	somewhat	generally	largely	thoroughly
	unprecedented	unprecedented	unprecedented	familiar	familiar	familiar
SFj	6.20	4.96	3.72	2.48	1.24	0.00
FLEX	rigorous	occasional	some	general	some	general
		relaxation	relaxation	conformity	conformity	goals
SFj	5.07	4.05	3.04	2.03	1.01	0.00
TEAM	very difficult	some difficult	basically	largely	highly	seamless
	interactions	interactions	cooperative	cooperative	cooperative	interactions
			interactions			
SFj	5.48	4.38	3.29	2.19	1.10	0.00
RESL	little	some	often	generally	mostly	full
	(20%)	(40%)	(60%)	(75%)	(90%)	(100%)
Sfj	7.07	5.65	4.24	2.83	1.41	0.00
PMAT	Level 1	Level 1	Level 2	Level 3	Level 4	Level 5
	Lower	Upper				
SFj	7.80	6.24	4.68	3.12	1.56	0.00

Brief description of the Scale Factors and motivation for our choices:

- **Precedentedness**: reflects the experience of the development team in similar projects. Since our team has no experience in developing large web applications in our case will be Low.
- Flex: reflects the degree of freedom in the development process in relation to constraints in requirements and external interfaces to use. In our case the requirements are quite strict, but we have a good degree of choice from an implementation point and in some functionalities. We think Nominal it's the correct value.
- **Team**: reflects the level of cooperation between the team members. In our case the correct value is High.

- Risk resolution: reflects how good the architecture as been defined and if risks has been taken into account. Since we are not expert in designing systems like this one, even if we have a good risk plan, to be conservative, we think that Nominal is the right value.
- **Process maturity**: after problems faced during the first phases of the project have been overcome, we are q confident of our team capabilities even if we are unexperienced, but it's better to be conservative even in this case. The correct value is Nominal.

Table 12: Scale drivers values

Table 12. Scale drivers	s varues	
Scale Driver	Factor	Value
Precedentedness (PREC)	Very low	6.20
Development flexibility (FLEX)	Nominal	3.04
Team cohesion (TEAM)	High	2.19
Risk resolution (RESL)	Nominal	4.24
Process maturity (PMAT)	Nominal	4.68
Total		20.35

2.2.2 Cost drivers

• Required Software reliability

Reliability issues in our system could lead to the loss of resources, but as long as we are quick in detecting the issues relying on a assistance service provided by the legacy system could mitigate the losses. The correct value for the RELY cost driver is Nominal.

Table 13: RELY

	RELY Cost Driver								
RELY Descriptors	slightly inconvenience	easily recoverable losses	moderate recoverable losses	High financial loss	risk to human life				
Rating level	Very low	Low	Nominal	High	Very High	Extra high			
Effort multipliers	0.82	0.92	1.00	1.10	1.26	n/a			

• Database size:

We expect the effective size of out database to be high in relation to the expected SLOC. An High value is probably the most sensible choice.

Table 14: DATA

	DATA Cost Driver								
DATA		D/P <	10 < D/P <	100 < D/P	D/P >				
Descriptors		10	100	<1000	1000				
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high			
Effort multipliers	n/a	0.90	1.00	1.14	1.28	n/a			

• Required reusability:

The software produced in our project could be reusable for a car sharing service of a larger scale. The right RUSE cost driver is High.

Table 15: RUSE

	RUSE Cost Driver								
RUSE Descriptors		None	Access project	Across program	Across product line	Across multiple product line			
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high			
Effort multipliers	n/a	0.95	1.00	1.07	1.15	1.24			

• Documentation match to life-cycle needs

The documentation in our project covers the life cycle need of the system with care. The value is set to Nominal.

Table 16: DOCU

DOCU Cost Driver								
DOCU Descriptors	Many life-cycle needs uncovered	Some life-cycle needs uncovered	Right-sized to life-cycle needs	Excessive for life-cycle needs	Very excessive for life-cycle needs			
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high		
Effort multipliers	0.81	0.91	1.00	1.11	1.23	n/a		

• Execution time constraint:

Since we will have part of the logic distributed over cars, the workload of the system should not be too heavy. TIME is set to Nominal.

Table 17: TIME

	TIME Cost Driver								
			<50%use of	70% use of	85% use of	95% use of			
TIME			available	available	available	available			
Descriptors			execution	execution	execution	execution			
			time	time	time	time			
Rating level	Ver Low	Low	Nominal	High	Very High	Extra			
Ttating level	Vel Low	LOW	Nommai	Iligii	very mgn	high			
Effort	n/e	n/a	1.00	1.11	1.29	1.63			
multipliers	n/a	п/а	1.00	1.11	1.29	1.05			

• Storage constraint:

Even if our system will have to deal with a reasonable amount of data, we do not expect problems related to the storage availability. STOR is set to Nominal.

Table 18: STOR

	STOR Cost Driver											
STOR Descriptors			<50%use of available storage	70% use of available storage	85% use of available storage	95% use of available storage						
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high						
Effort multipliers	n/a	n/a	1.00	Effort n/2 n/2 100 105 117 146								

• Platform Volatility:

We do not expect the system to be under constant evolution. Nominal is the right value for the PVOL cost driver.

Table 10: PVOL

	Table 19: PVOL									
	PVOL Cost Driver									
		Major change	Major change	Major change	Major change					
PVOL		e. 12mo.	e. 6mo	e. 2mo	e. 2wk					
Descriptors		Minor change	Minor change	Minor change	Minor change					
		e. mo.	e. 2wk.	e. 1wk.	e. 2 days					
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high				
Effort multipliers	n/a	0.87	1.00	1.15	1.30	n/a				

• Analyst Capability:

We are confident to have done a good work in analyzing the domain of our system. The ACAP driver is set to High.

Table 20: ACAP

	ACAP Cost Driver								
ACAP	15th	35th	55th	75th	90th				
Descriptors	percentile	percentile	percentile	percentile	percentile				
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high			
Effort multipliers	1.42	1.19	1.00	0.85	0.71	n/a			

• Programmer Capability:

We confident in our team ability in programming. PCAP is set to high.

Table 21: PCAP

PCAP Cost Driver								
PCAP	15th	35th	55th	75th	90th			
Descriptors	percentile	percentile	percentile	percentile	percentile			
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high		
Effort multipliers	1.34	1.15	1.00	0.88	0.76	n/a		

• Application experience:

Even if we are experienced in Java, this is our first JEE application, so to be conservative, APEX is set to Low.

Table 22: APEX

	APEX Cost Driver								
Apex	<2	6	1	3	6				
Descriptors	months	months	years	years	years				
Rating level	Very Low	Low	Nominal	High	Very High	Extra High			
Effort multipliers	1.22	1.10	1.00	0.88	0.81	n/a			

• Platform Experience:

As already said, we are not experienced in JEE and web development, PLEX is set to Low.

Table 23: PLEX

PLEX Cost Driver						
PLEXDescriptors	<2	6	1	3	6	
1 LEADescriptors	months	months	year	years	years	
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high
Effort multipliers	1.19	1.09	1.00	0.91	0.85	n/a

• Language and Tool experience:

We are not familiar with the kind of development tools needed for our project. LTEX is set to Low.

Table 24: LTEX

LTEX Cost Driver							
LTEX	<2	6	1	3	6		
Descriptors	months	months	year	years	years		
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high	
Effort multipliers	1.20	1.09	1.00	0.91	0.84	n/a	

• Personnel continuity:

We don't expect an high turnover in our small team. PCON is set to High.

Table 25: PCON

PCON Cost Driver							
PCON	48%	24%	12%	6%	3%		
Descriptors	year	year	year	year	year		
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high	
Effort multipliers	1.29	1.12	1.00	0.90	0.81	n/a	

• Usage of Software Tools:

We have well documented the tools that we are going to use in development, we think the right value for TOOL is High.

Table 26: TOOL

	TOOL Cost Driver						
TOOL Descriptors	edit, code, debug	simple, frontend, backend, CASE, little integration	basic life-cycle tools, moderately integrated	strong, mature life-cycle tools, moderately integrated	string, mature, proactive life-cycle tools, well integrated with processes, methods, reuse		
Rating leve	el Ver Low	Low	Nominal	High	Very High	Extra high	
Effort multipliers	1.17	1.09	1.00	0.90	0.78	n/a	

• Multisite development:

We will work in the same city with frequent meetings and simplicity in communications. SITE is set to High.

Table 27: SITE

		SITI	E Cost Drive	r		
SITE		Multi-city	Multi-city	Same city	Same	
Collocation	International	or multi-	or multi-	or metro	building	Fullycollocated
Descriptors		company	company	area	or complex	
					Wideband	
SITE	Some phone,	Individual	Narrow	Wideband	electr.	Interactive
Communications	mail	phone,	band	electronic	comm.,	multimedia
Descriptors		fax	email	comm.	occasional	munimedia
					video conf.	
Rating level	Ver Low	Low	Nominal	High	Very High	Extra
Trating level	Ver Low	LOW	Nominai	Iligii	very mgn	high
Effort	1.22	1.09	1.00	0.93	0.86	0.80
multipliers		1.00	1.00	0.00	0.00	0.00

$\bullet\,$ Required development schedule:

The schedule for our project was not particularly stretched out. SCED is set to Nominal.

Tab.	le	28:	SCED

SCED Cost Driver							
SCED	75% of	85% of	100% of	130% of	160% of		
descriptors	nominal	nominal	nominal	nominal	nominal		
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high	
Effort multipliers	1.43	1.14	1.00	1.00	1.00	n/a	

• Product complexity:

Referencing to the COCOMO II classification, we think that the right value fort the complexity of our system is High.

Table 29: CPLEX

CPLX Cost Driver							
Rating level	Ver Low	Low	Nominal	High	Very High	Extra high	
Effort multipliers	0.73	0.87	1.00	1.17	1.34	1.74	

Overall results:

Table 30: Results

Cost Driver	Factor	Value
Required Software Reliability (RELY)	Nominal	1.00
Database size (DATA)	High	1.14
Required Reusability (RUSE)	High	1.07
Documentation match to life-cycle needs (DOCU)	Nominal	1.00
Execution Time Constraint (TIME)	Nominal	1.00
Main storage constraint (STOR)	Nominal	1.00
Platform volatility (PVOL)	Nominal	1.00
Analyst capability (ACAP)	High	0.85
Programmer capability (PCAP)	High	0.88
Application Experience (APEX)	Low	1.15
Platform Experience (PLEX)	Low	1.09
Language and Tool Experience (LTEX)	Low	1.09
Personnel continuity (PCON)	High	0.90
Usage of Software Tools (TOOL)	High	0.90
Multisite development schedule (SITE)	High	0.93
Required development schedule (SCED)	Nominal	1.00
Product complexity (CPLEX)	High	1.17
Total (Product)		1.09874

2.2.3 Effort equation

Finally we can use the values produced by our analysis to get the final estimation in PM (Person Months). (Simple calculations in Python)

```
A = 2.94
EAF = 1.09874
SF = [6.20, 3.04, 2.19, 4.24, 4.68]
KSLOC_avg = 9890.0 / 1000.0
KSLOC_max = 14405.0 / 1000.0
B = 0.91
E = B + 0.01 * sum(SF)

effort_avg = A * EAF * KSLOC_avg ** E #PM effort_max = A * EAF * KSLOC_max ** E #PM
With results:

>>>effort_avg
41.43748003927392

>>>effort_max
62.9863995508225
```

2.2.4 Schedule estimation

The estimation of the duration of the project is:

```
F = 0.28 + 0.3 * (E - B)
duration_avg = 3.67 * effort_avg ** F #months
duration_max = 3.67 * effort_max ** F #months
With results:
>>>duration_avg
13.070074457743738
>>>duration_max
15.076453059081716
```

We will use these values in the next sections to produce a proper schedule for our project.