

usage: `autopep8 [-h] [--version] [-v] [-d] [-i] [--global-config filename]`
`[--ignore-local-config] [-r] [-j n] [-p n] [-a]`
`[--experimental] [--exclude globs] [--list-fixes]`
`[--ignore errors] [--select errors] [--max-line-length n]`
`[--line-range line line] [--hang-closing] [--exit-code]`
`[files [files ...]]`

Automatically formats Python code to conform to the PEP 8 style guide.

positional arguments:

files files to format or '-' for standard in

optional arguments:

-h, --help show this help message and exit

--version show program's version number and exit

-v, --verbose print verbose messages; multiple -v result in more
 verbose messages

-d, --diff print the diff for the fixed source

-i, --in-place make changes to files in place

--global-config filename
 path to a global pep8 config file; if this file does
 not exist then this is ignored (default:
 C:\Users\Giddi\.pep8)

--ignore-local-config
 don't look for and apply local config files; if not
 passed, defaults are updated with any config files in
 the project's root directory

-r, --recursive run recursively over directories; must be used with
 --in-place or --diff

-j n, --jobs n number of parallel jobs; match CPU count if value is
 less than 1

-p n, --pep8-passes n
 maximum number of additional pep8 passes (default:
 infinite)

-a, --aggressive enable non-whitespace changes; multiple -a result in
 more aggressive changes

--experimental enable experimental fixes

--exclude globs exclude file/directory names that match these comma-
 separated globs

--list-fixes list codes for fixes; used by --ignore and --select

--ignore errors do not fix these errors/warnings (default:
 E226,E24,W50,W690)

--select errors fix only these errors/warnings (e.g. E4,W)

--max-line-length n set maximum allowed line length (default: 79)

--line-range line line, --range line line

only fix errors found within this inclusive range of
line numbers (e.g. 1 99); line numbers are indexed at
1

--hang-closing hang-closing option passed to pycodestyle

--exit-code change to behavior of exit code. default behavior of
return value, 0 is no differences, 1 is error exit.
return 2 when add this option. 2 is exists
differences.