The name, on a post

One panel, the name only — no service list, no photograph. Built to the client's measurement of 3.10 ft × 2.11 ft, landscape, which is 945 × 643 mm. Double-sided: both faces carry the same artwork.

H 2.11 FT / 643 MM



W 3.10 FT / 945 MM

MEASUREMENTS

- Trim: 944.9 × 643.1 mm — 3.10 ft × 2.11 ft at 304.8 mm to the foot.
- Bleed: 10 mm all round, so the printed sheet is 965 × 663 mm. Safe area 25 mm in from trim.
- Artwork is supplied at 1 : 1 in millimetres — plot it, do not scale it.
- Both faces are in the one PDF: print the file twice for a two-sided panel, or once per face for two single-sided panels back to back.

Two ways to set the name

A is the recommendation: the badge sits above a centred name, so the words are the widest thing on the sign and the eye lands on MEDICAL CENTRE. B repeats the lockup used on the door panes, badge left, name right, for continuity between the sign post and the stickers.



OPTION A — CENTRED (RECOMMENDED)



OPTION B — BADGE-LEFT LOCKUP

How it sits at the entrance

Drawn to scale: panel centre 1500 mm above finished ground level, posts at 520 mm centres. Mounting height and post centres are proposals — confirm on site.



DAY — MATTE FACE, STREET LIGHT



NIGHT — IF THE PANEL IS LIT

DRAWN TO SCALE · PANEL CENTRE 1500 MM ABOVE FINISHED GROUND LEVEL

Production specification

SUBSTRATE — CONFIRM WITH THE SIGNWRITER

- 3 mm aluminium composite (ACM) panel, matte white, direct-to-substrate UV print, or 3 mm ACM with cast vinyl applied and laminated — industry-typical, not a quotation.
- Double-sided: either two printed faces bonded back to back on one ACM core, or two panels on a frame. The artwork is identical on both faces.
- Edges: 3 mm radius, sealed. The artwork bleeds 10 mm and is cut back to trim, so no white edge shows.
- Finish: matte anti-glare laminate. Gloss will mirror the sky and kill the contrast the navy depends on.

FIXING — CONFIRM WITH THE INSTALLER

- Two 76 mm galvanised posts at 520 mm centres, set 600 mm into a concrete footing; panel centre 1500 mm above finished ground level.
- Stainless fixings through the face into a bracket, or a channel frame behind the panel — both keep the face free of bolts. Do not drill the printed face.
- Wind loading: a 0.61 m² panel on two posts is a modest sail, but the footing and the bracket still need the signwriter's own calculation for the site.

BEFORE PLOT

- Measurement is the client's: 3.10 ft × 2.11 ft. Check it against the panel the signwriter is actually making before the file is plotted.
- The monogram is a recreation, not BCM's official logo — swap the vector in.
- Confirm the fascia wording: the clinic's own board reads Community Health Centre; this sign uses BCM Medical Centre as instructed.
- The two help-line numbers, if they go on, come off the clinic's premises boards.