The name, on a post

One panel, the name only — no service list, no photograph. Trim 5055 × 1245 mm, the client's 16 ft 7 in × 4 ft 1 in, double-sided. EDDWALIRO heads the panel above the badge: the road reads Luganda first, and the English name keeps the widest line.

HIGH 4 FT 1 IN / 1244.6 MM



LONG 16 FT 7 IN / 5054.6 MM

MEASUREMENTS

- Trim: 5054.6 × 1244.6 mm — 16 ft 7 in × 4 ft 1 in, i.e. 199 × 49 in (25.4 mm to the inch).
- Bleed: 10 mm all round, so the printed sheet is 5075 × 1265 mm. Safe area 25 mm in from trim.
- Artwork is supplied at 1 : 1 in millimetres — plot it, do not scale it.
- Both faces are in the one PDF: print the file twice for a two-sided panel, or once per face for two single-sided panels back to back.

Three ways to set the name

A is the recommendation and it is what the print files carry. B repeats the badge-left lockup used on the door panes, for continuity. C is the fascia setting: at this length the stacked lockup fills only a little over a third of the panel, so C lets the name run the length at about four times the size.



OPTION A — CENTRED STACK · IN THE PRINT FILES



OPTION B — BADGE-LEFT, AS ON THE DOOR PANES

EDDWALIRO HEADS THE PANEL, BOLD AND IN CYAN: THE LUGANDA WORD IS READ FIRST.

BCM STAYS SMALL AND CYAN BESIDE THE BADGE: THE INITIALS, NOT THE HEADLINE.



OPTION C — FASCIA: THE NAME ACROSS THE LENGTH

THE MOTTO SITS UNDER THE NAME AND CAN BE DROPPED FOR A NAME-ONLY PANEL.

THE TELEPHONE CAN BE ADDED AT THE FOOT, ON BOTH FACES, ON REQUEST.

How it sits at the entrance

A 5.1 m fascia is a structure, not a sticker: panel centre 1500 mm above finished ground level and four posts under it are a proposal — the post centres and the frame must come from the signwriter who builds it.



DAY — MATTE FACE, STREET LIGHT



NIGHT — IF THE PANEL IS LIT

DRAWN TO SCALE · PANEL CENTRE 1500 MM ABOVE FINISHED GROUND LEVEL · FOUR POSTS SHOWN AS A PROPOSAL

- The face is 6.29 m² of panel. At that size the sign is read from well down the road, so the name is set to be legible from 100 m or more.
- Two posts would leave a 5 m span unsupported between them; the drawing shows four. A rail or cleat frame behind the panel is the alternative, and it keeps the face free of fixings.
- If the panel is to be read from one direction only, one face is enough — the artwork is the same on both.

Production specification

SUBSTRATE — CONFIRM WITH THE SIGNWRITER

- The face is 6.29 m². At this size 3 mm ACM on its own is marginal over a long span: propose 4 mm ACM, or 3 mm ACM on a rail frame. Industry-typical values, not a quotation — the signwriter decides.
- Direct-to-substrate UV print, or cast vinyl applied and laminated, on a matte white core. Edges cut back to trim and sealed.
- Double-sided: either two printed faces on one core, or two panels on a frame. The artwork is identical on both faces.
- Finish: matte anti-glare laminate. Gloss will mirror the sky and kill the contrast the navy depends on.
- Allow for roughly 25 kg of 4 mm sheet before the frame — it is a two-person lift, not a one-person one.

FIXING — CONFIRM WITH THE INSTALLER

- Proposal: four galvanised posts under the panel, set into concrete footings, panel centre 1500 mm above finished ground level. A rail or cleat frame carrying the panel on four posts is the cleaner build at this length.
- Stainless fixings into a bracket or frame behind the panel, never through the printed face. Do not drill the face.
- Wind loading: 6.29 m² is a real sail — the footing, the post gauge and the bracket need the signwriter's own calculation for the site.

BEFORE PLOT

- Measurement is the client's: 16 ft 7 in × 4 ft 1 in. Check it against the panel the signwriter is actually making before the file is plotted.
- The sheet is supplied at 1 : 1 in millimetres and is close to the largest page a PDF can hold — do not add margins to the file and do not scale it on the plotter.
- The monogram is a recreation, not BCM's official logo — swap the vector in.
- Confirm the fascia wording and the spelling of EDDWALIRO with the client before plot.

THE FILE

- Trim 5054.6 × 1244.6 mm, bleed 10 mm all round, so the page is 5074.6 × 1286.6 mm — 1 : 1, no scaling.
- A 22 mm slug runs along the foot with the file name, the trim and the colour note — trim it off. At 5075 mm the page is close to the largest page a PDF can hold (5080 mm), so nothing may be added around it.
- Safe area 25 mm inside trim. Crop marks at the four corners, outside the bleed.
- Colour: navy #16233F, cyan #2BA9E0, mist #E8EEF4, white. Supply as CMYK or let the printer convert — do not colour-manage the navy towards black.