Production specification — door 1

Eight panes, two widths, one film. Values marked “confirm with printer” are industry-typical placeholders, not something the printer has agreed to.

ITEM	VALUE
TRIM SIZE	900 × 500 MM (4 PANES) AND 900 × 400 MM (4 PANES)
WITH BLEED	920 × 520 MM AND 920 × 420 MM
BLEED	10 MM ALL ROUND
LIVE / SAFE	25 MM INSIDE TRIM — 20 MM ON THE 400 MM PANES
CROP MARKS	OFFSET 4 MM, 4 MM LONG, OUTSIDE BLEED
SLUG	20 MM AT THE FOOT, OUTSIDE BLEED
SERVICE NAME	CAP HEIGHT 13.5 % OF PANE WIDTH — 64 MM ON THE WIDE PANE, 54 MM ON THE NARROW; LONG NAMES BREAK TO TWO LINES RATHER THAN SHRINK
SMALLEST LIVE TYPE	6 MM CAP — THE PERFORATION IS THE LIMIT
RESOLUTION	75 PPI FLOOR, 100 PPI TARGET IN THE PLACED CROP
COLOUR	CMYK, COATED PROFILE; NAVY #16233F, CYAN #2BA9E0
FONTS	MANROPE + INTER, SIL OFL, EMBEDDED
FILM	PERFORATED ONE-WAY VISION VINYL, WHITE-BACKED, 140–160 M

FILM

- Perforated one-way vision vinyl, white-backed, 140–160 µm plus liner — confirm with printer.
- 1.6 mm holes on a 2.3 mm staggered pitch, 44 % open by geometry. The mesh, not the file, is the limit on detail.
- Matte anti-glare face, UV or latex print, four colour plus white backing layer.
- Eight pieces per door. Cut from one roll run so the navy matches across all eight.
- Doors 1 and 2 use the same film and should be printed in the same run if the schedule allows; door 3 is a different substrate and will not match it exactly.

ABOUT THE FILES IN THIS PACKAGE

The PDFs are the artwork: true size, 10 mm bleed, 4 mm marks and a 20 mm slug, in CMYK with the fonts embedded. The placed photographs are desktop previews, roughly 25–40 ppi at final size, so plot from the full-size originals recorded in the README rather than from this package — every frame has its Pexels ID and link listed. If BCM prefers its own team on the door, one morning with a phone on the same eight subjects beats any stock image, and the artwork takes new files without a single change.

Installation — door 1

- Re-measure every pane with a tape, corner to corner, before plotting. Measured figures were supplied for these doors; the next one may not match.
- Number the panes on the back of each print in pencil as they are cut — eight pieces, two sizes, and they all look alike in a stack.
- Clean the glass and apply one pane as a control: the narrowest, most awkward one, low on the leaf, where mistakes are least visible.
- Keep the perforation grid square to the frame, not to the handle. On two 900 mm rows stacked, a skewed grid reads as a crooked poster.
- Trim inside the rebate, 2 mm clear of the glass edge. Clear 25 mm around handles, locks and hinges.
- Do not stretch the film to fit a pane. If a pane is out of square by more than 3 mm, re-cut the artwork to the measured diagonal — the design has room for it.
- Leave 24 hours before cleaning or closing the door against the film.

OPEN ITEMS

- Confirm the column order on the leaf: 500 mm on the left as drawn, or mirrored?
- BCM's vector logo, for the plate on all eight panes.
- Telephone numbers, if they are to appear — currently none do.
- The printer's own film standard, to replace the flagged values.
- Print-resolution originals: the working files are desktop previews. Pull the full-size files from the recorded Pexels links, or shoot the real team.