Production specification

This document states how the eight panels are to be produced, applied and inspected. Everything marked PROVISIONAL is an industry-typical value used because the printer's own sheet has not yet been issued; each such value is repeated in the RFQ on page 6 and must be replaced by the printer's figure before release. Nothing in this document should be read as a printer-approved specification.

1 MATERIAL

- Perforated one-way vision film, white gloss face, grey-back adhesive. PROVISIONAL hole geometry 1.6 mm on a 2.3 mm pitch (~38% open area).
- No laminated over-laminate unless requested — a matte over-laminate reduces the see-through performance and increases the drop in outside contrast.
- Film must be supplied in a width that covers the tallest dimension in one piece (2100 mm panels) so no horizontal join crosses a headline.
- Warranty: minimum 5 years vertical exterior/interior glazing, manufacturer-backed.

2 COLOUR & INK

- Print CMYK, colour-managed to the printer's ICC profile for the specified film; solvent, UV or latex as the printer recommends. No RGB files released.
- Target values: navy #0A2642 C100 M88 Y40 K38; teal #0F8C8C C78 M22 Y48 K2; medical green #2E7A5F C80 M30 Y65 K20. Treat as starting points for a proof, not as absolute conversion.
- Total ink coverage: hold the deep navy field at or below the film maker's stated maximum. Heavy coverage on perforated film causes blocking and slows drying — confirm the limit.
- White ink underbase: NOT used. The design relies on the film's own white face; adding a white layer would kill the one-way effect.
- Provide a colour-managed proof at 100% on the actual film before the production run.

3 ARTWORK CONSTRUCTION

PARAMETER	VALUE USED HERE	STATUS	NOTE
BLEED	10 MM ALL ROUND	PROVISIONAL	APPLIED TO GRAPHICS AND PHOTOGRAPHY; TRIMMED BEFORE MOUNTING
SAFE ZONE	25 MM INSIDE TRIM	PROVISIONAL	LIVE TYPE, LOGO AND FACES KEPT INSIDE THIS LINE
HARDWARE CLEARANCE	40 MM AROUND FITTINGS	PROVISIONAL	HANDLES, CLOSERS, HINGES AND MEETING STILES
KICK ZONE	120 MM FROM FLOOR	PROVISIONAL	NO LIVE CONTENT; SCUFF AND MOP DAMAGE AREA
RESOLUTION	150 PPI TARGET / 110 PPI FLOOR AT FINAL SIZE	AGREED	SEE RESOLUTION AUDIT IN THE PANEL SCHEDULE
COLOUR SPACE	CMYK, PRINTER ICC PROFILE	PROVISIONAL	CONFIRM PROFILE NAME BEFORE OUTPUT
FILE FORMAT	PDF/X-4 PREFERRED; PDF 1.6 ACCEPTABLE	PROVISIONAL	FONTS EMBEDDED, IMAGES LINKED THEN FLATTENED BY THE PRINTER
SLUG STRIP	20 MM OUTSIDE THE BLEED	PROJECT RULE	PANEL ID, SIZE, ORIENTATION, REVISION — TRIMMED OFF

One-way vision specific requirements

These are the constraints that separate a one-way vision job from an ordinary vinyl print. They govern the design as much as the production.

IMAGE DENSITY

Dark, saturated areas hide the perforation best; pale, busy photographs read as a mesh. Every photograph in this set is graded down towards navy in shadow, and no panel places light type or light detail over a mid-tone.

VISIBILITY BALANCE

The client must be able to see out. Photography covers 40–45% of a door; sidelights carry none. The remainder is a solid navy field which, being dark, is the most transparent zone on the panel.

EDGE CONTRAST

Perforation erodes edges by roughly one hole diameter. Type is set in 600–800 weights at 70–78 mm cap height; hairline rules are decorative and carry no information.

NO FINE PATTERNS

No fine stripes, small maps, dot screens or thin iconography anywhere in the artwork. The ghost numerals are set at 6% tint purely as a large-scale texture and are not intended to be read.

INSIDE APPEARANCE

From inside, the panel reads as a dark grey field with a faint photographic ghost. Plan interior lighting accordingly; the panels should not be relied on for privacy after dark.

CLEANING

Perforated film traps dust in the holes. Specify a non-abrasive, solvent-free cleaner and a soft cloth; no squeegee pressure over type.

INK COVERAGE BY PANEL TYPE (TARGET)



PERCENTAGE FIGURES ARE THE DESIGNED INTENTION ON A 100% K-OUT BASIS, NOT MEASURED VALUES. THE PRINTER'S LIMIT GOVERNS WHAT IS RELEASED.

Installation schedule

Sequence assumes the glazing is complete, clean and within tolerance. Each panel is an independent plot; the site is measured twice — once for the schedule and once after glazing — before release.

PANEL	LOCATION	TRIM (CM)	PLOT SIZE INCL. BLEED (MM)	PIECES	FIXING	SEQUENCE
P-01	RECEPTION ENTRANCE, ACTIVE LEAF	100 × 210	1020 × 2120	1	WET APPLY, SQUEEGEE, TRIMMED IN SITU	STEP 1
P-02	RECEPTION ENTRANCE, SIDELIGHT	45 × 210	470 × 2120	1	WET APPLY, SQUEEGEE, TRIMMED IN SITU	STEP 2
P-03	CONSULTATION ROOM 01	90 × 210	920 × 2120	1	WET APPLY, SQUEEGEE, TRIMMED IN SITU	STEP 3
P-04	CONSULTATION ROOM 02	90 × 210	920 × 2120	1	WET APPLY, SQUEEGEE, TRIMMED IN SITU	STEP 4
P-05	LABORATORY ENTRANCE	90 × 210	920 × 2120	1	WET APPLY, SQUEEGEE, TRIMMED IN SITU	STEP 5
P-06	PHARMACY ENTRANCE	100 × 210	1020 × 2120	1	WET APPLY, SQUEEGEE, TRIMMED IN SITU	STEP 6
P-07	IMAGING SUITE, DOUBLE LEAF	120 × 210	1220 × 2120	2 (SPLIT)	DRY APPLY PER LEAF, TRIMMED AT STILE	STEP 7
P-08	IMAGING SUITE, SIDELIGHT	45 × 210	470 × 2120	1	WET APPLY, SQUEEGEE, TRIMMED IN SITU	STEP 8

SITE PREPARATION AND SIGN-OFF

- Glass cleaned with a two-stage method (detergent, then pure water) and fully dry; surface temperature between 10 °C and 30 °C.
- Ambient conditions recorded on the day: temperature, humidity, and whether the space is dust-controlled. Wet application only in a dust-free interior.
- Hardware removed and refitted by the door contractor, not the film installer, where the film must pass behind a closer or hinge cover.
- Each panel inspected at 1 m under raking light: no bubbles over 1 mm, no lifted edges, no trim deviation greater than 1 mm from the frame line.
- Client walk-through and written acceptance; retain one A4 offcut per panel for future colour matching.

Printer RFQ — questions to settle before release

Send this page with the artwork. The answers replace every PROVISIONAL value in this specification and in the panel schedule; the artwork is then re-issued at the same revision number with the confirmed figures.

01 FILM

Exact product, hole diameter, pitch and open-area percentage. Roll width and whether 2100 mm panels can be produced in one piece without a join.

02 ADHESIVE

Grey-back or clear adhesive? Is a removable or bubble-free adhesive available for glass doors that may need re-glazing?

03 INK LIMIT

Maximum total ink coverage for this film, and any restriction on large solid dark fields.

04 WHITE INK

Confirm no white underbase is applied. If it is mandatory for durability, state the effect on the one-way performance.

05 BLEED

Required bleed and safe-zone allowance, and whether artwork should be supplied with marks and slug or trimmed to a fixed sheet size.

06 COLOUR

ICC profile name, proofing route (contract proof on film or soft proof), and who signs off colour.

07 FILE SPEC

Preferred PDF standard, maximum file size, and whether the printer imposes its own imposition.

08 PROOF

Cost and lead time for a 1:1 proof of one panel on the specified film.

09 INSTALL

Who installs, what surface tolerance is accepted, and what the warranty covers — material only or material and labour?

10 LEAD TIME

Production and installation lead time for eight panels, and any minimum order or sheet waste charge.

Approval record and assumptions

REVISION HISTORY

REV	DATE	ISSUE	CHANGE	BY
R1	2026-10-28	CLIENT REVIEW — PROVISIONAL MODULE SET	FIRST ISSUE: 8 PANELS, SYSTEM, SCHEDULE, SPEC	DESIGN

ASSUMPTIONS ON WHICH THIS ISSUE RESTS

- Doors are glazed with clear float or low-iron glass; no tinted, frosted, wired or Low-E coating that would change the appearance of the film.
- Each glass section is flat, vertical and within ±3 mm of the stated dimensions.
- Film is applied to the outside face of the glass unless the printer advises otherwise; the design is orientation-independent apart from the photographic crop.
- No internal signage, manifestation strips or privacy band is required on the same glass. If a manifestation band is required for safety glazing compliance, it must be designed with the panel, not applied over it.
- Department names, room numbers and the identity lockup are placeholders pending the client's own brand assets.
- Photographs are licensed stock imagery, not portraits of staff or patients of the centre. They may not be captioned or implied to depict named individuals.

SIGN-OFF

CLIENT

NAME / DATE

DESIGN

NAME / DATE

PRINTER

NAME / DATE