
The name, on a post

One panel: the name, and the two facts a passer-by needs — open all night, and the numbers to ring. No service list, no photograph. Trim 1168 × 559 mm, the client's 3 ft 10 in × 1 ft 10 in, double-sided, for a lighting board. EDDWALIRO heads the panel, BCM stands under it, and the English name keeps the widest line.

HIGH 1 FT 10 IN / 558.8 MM




LONG 3 FT 10 IN / 1168.4 MM

MEASUREMENTS


- Trim: 1168.4 × 558.8 mm — 3 ft 10 in × 1 ft 10 in, i.e. 46 × 22 in (25.4 mm to the inch).
- Bleed: 10 mm all round, so the printed sheet is 1188 × 579 mm. Safe area 25 mm in from trim.
- Artwork is supplied at 1 : 1 in millimetres — plot it, do not scale it.
- Both faces are in the one PDF: print the file twice for a two-sided panel, or once per face for two single-sided panels back to back.

Built to the sign you already have


The clinic's own lit box is on the road already, so the new face keeps that arrangement rather than inventing one: BCM on a white band, MEDICAL CENTRE in navy on a light blue band, EDDWALIRO knocked out of a full-width red block, OPEN 24 HRS between two arrows, and a navy foot strip with the numbers. Only what has to changes — the numbers are the client's current ones, and the motto is off. The navy sits in two thin bands with white either side, so the box still lights evenly.



THE CLINIC'S SIGN · IN THE PRINT FILES



CYAN FIELD · SPARE



THE OLD NAVY FACE · NOT FOR THE BOX

WHAT CHANGED

- The arrangement is the one already standing at the roadside: brand band, MEDICAL CENTRE on its light blue band, the red EDDWALIRO block, OPEN 24 HRS, foot strip. People on this road already read that sign, so the new face does not make them learn it again.
- EDDWALIRO is set across 94 % of the panel — the whole measure — and knocked out of the red block in white, so it is the loudest thing on the face, lit or not.
- Red #ED1B24 carries the colour: the block behind the name and the OPEN 24 HRS row. Everything else is the clinic's navy and white, so nothing competes with the name.
- The motto is off this face, as asked. The OPEN 24 HRS row takes the room it used.
- The foot strip carries the numbers — 0788 323 815 · 0754 132 715 — with BUSSABALA at the right.
- Nothing here is invented: the brand line, the community name, the branch, the arrows and the foot strip are all read off the client's own sign photograph.

IF THE RED IS TOO LOUD


- Say so and I will pull the red back to the clinic's cyan #2BA9E0 at the same size — the layout does not care which colour it is set in.

How it sits at the entrance

1.17 m of panel, 0.65 m² of face: panel centre 1500 mm above finished ground level and 2 posts under it are a proposal — the post centres and the frame must come from the signwriter who builds it.



DAY — MATTE FACE, STREET LIGHT



NIGHT — IF THE PANEL IS LIT

DRAWN TO SCALE · PANEL CENTRE 1500 MM ABOVE FINISHED GROUND LEVEL · TWO POSTS SHOWN AS A PROPOSAL

- The face is 0.65 m² of panel, 1168 mm long. The name is set to read from the road, so it stays legible well past the gate.
- Two posts carry it at 520 mm centres, or the whole panel sits in the lighting board's own carcass — the box carries it.
- A lit face is read from further off at night than an unlit one by day, so the name is set as large as the panel takes.

Production specification

SUBSTRATE — CONFIRM WITH THE SIGNWRITER

- The face is going into a lighting board, so it must be printed on a diffusing, backlit-grade material — translucent white acrylic or a backlit film for the box's own face, or backlit banner media if the box takes a soft face. Not vinyl on opaque composite: that blocks the light.
- The face is 0.65 m². The artwork is supplied at 1 : 1 in millimetres, so it can go straight onto the box's print or be plotted as a spare.
- Double-sided: the artwork is identical on both faces, so the same file prints twice.
- Print the white field and the navy bands as flat, even coats — no gradient, no vignette. Banding in a large flat field shows up far more when it is lit from behind, and navy is the field most likely to show it.
- Red is the colour to watch: #ED1B24 bleeds slightly into white when it is lit from behind, so the letter edges soften and the red can warm towards orange. Hold it as a flat spot colour if the process allows, and check a lit sample before the run.

FIXING — CONFIRM WITH THE INSTALLER

- Illumination: internally lit box, face lit from behind. Panel centre 1500 mm above finished ground level is a proposal — confirm it against the box and the kerb line, and check that the box takes this face size before it is ordered.
- The face fits the box's aperture, not its outer frame: trim is 1168 × 559 mm, so the visible opening should be that size or the artwork will be cropped by the rebate.
- One rule for a lit face: the light must be even across the whole panel. That is why the bands are thin, the gaps between them are white, and no band is set in a dense tint.
- If it is also to stand on posts rather than in the box, two galvanised posts at 520 mm centres, 600 mm into concrete, is the industry-typical proposal. Not a quotation.

BEFORE PLOT

- Measurement is the client's: 3 ft 10 in × 1 ft 10 in. Check it against the panel the signwriter is actually making before the file is plotted.
- The sheet is supplied at 1 : 1 in millimetres — plot it, do not scale it on the plotter, and leave the crop marks outside the bleed.
- Confirm the fascia wording and the spelling of EDDWALIRO with the client before plot. The old navy face kept a recreated monogram; the lit faces carry BCM instead.
- Check the red against a printed sample lit from behind before the full run.

THE FILE

- Trim 1168.4 × 558.8 mm, bleed 10 mm all round, so the page is 1188.4 × 600.8 mm — 1 : 1, no scaling.
- A 22 mm slug runs along the foot with the file name, the trim and the colour note — trim it off.
- Safe area 25 mm inside trim. Crop marks at the four corners, outside the bleed.
- Colour: red #ED1B24 on white, nothing else. Supply as CMYK or let the printer convert — do not let the red drift towards orange.