Production specification — door 3

Eight panes, two widths, one film. Values marked “confirm with printer” are industry-typical placeholders, not something the printer has agreed to.

ITEM	VALUE
TRIM SIZE	900 × 500 MM (4 PANES) AND 900 × 400 MM (4 PANES)
WITH BLEED	920 × 520 MM AND 920 × 420 MM
BLEED	10 MM ALL ROUND
LIVE / SAFE	25 MM INSIDE TRIM — 20 MM ON THE 400 MM PANES
CROP MARKS	OFFSET 4 MM, 4 MM LONG, OUTSIDE BLEED
SLUG	20 MM AT THE FOOT, OUTSIDE BLEED
SERVICE NAME	CAP HEIGHT 13.5 % OF PANE WIDTH — 64 MM ON THE WIDE PANE, 54 MM ON THE NARROW; LONG NAMES BREAK TO TWO LINES RATHER THAN SHRINK
SMALLEST LIVE TYPE	4 MM CAP — OPAQUE VINYL, NO MESH LIMIT
RESOLUTION	75 PPI FLOOR, 100 PPI TARGET IN THE PLACED CROP
COLOUR	CMYK, COATED PROFILE; NAVY #16233F, CYAN #2BA9E0
FONTS	MANROPE + INTER, SIL OFL, EMBEDDED
FILM	OPAQUE WHITE BLOCKOUT VINYL — NO PERFORATION, NO SEE-THROUGH

FILM

- Opaque white blockout self-adhesive vinyl, 100–140 µm plus liner, grey-backed so nothing shows through from either side — confirm with printer.
- No perforation, so no mesh limit: detail, gradients and type below 6 mm cap all hold. Treat it as a poster on glass, not as a mesh.
- Matte anti-glare face, UV or latex print, four colour plus white. White backing layer is still needed where the navy sits on clear glass at the edges.
- Eight pieces per door, cut from one roll run. The opaque door cannot be mixed with offcuts from the one-way doors — the substrate is different and the colour will read differently.
- Because the glass is now blocked, check the door's function: a solid pane hides the room behind it from outside and hides the street from inside. Confirm this is wanted on this particular door.

WHAT OPAQUE CHANGES

- Nothing shows through: not the room behind the glass, not the street from inside. The pane becomes a flat poster on both faces.
- Print at full detail. There is no mesh to break up fine type, gradients or skin, so the 6 mm minimum on the perforated doors does not apply here.
- The navy will read slightly denser than on the one-way doors, because it is printed on solid white rather than over 44 % open holes. Judge it against door 1 before signing off, and expect a small difference rather than a match.
- Clean with a soft cloth and water only. Opaque vinyl on glass cannot be wiped with solvent, and a blade to remove it later will scratch the glass — plan the removal.

ABOUT THE FILES IN THIS PACKAGE

REV B · 2026-10-29

The PDFs are the artwork: true size, 10 mm bleed, 4 mm marks and a 20 mm slug, in CMYK with the fonts embedded. The placed photographs are desktop previews, roughly 25–40 ppi at final size, so plot from the full-size originals recorded in the README rather than from this package — every frame has its Pexels ID and link listed. If BCM prefers its own team on the door, one morning with a phone on the same eight subjects beats any stock image, and the artwork takes new files without a single change.

Installation — door 3

- Re-measure every pane with a tape, corner to corner, before plotting. Measured figures were supplied for these doors; the next one may not match.
- Number the panes on the back of each print in pencil as they are cut — eight pieces, two sizes, and they all look alike in a stack.
- Clean the glass and apply one pane as a control: the narrowest, most awkward one, low on the leaf, where mistakes are least visible.
- Opaque vinyl shows every air bubble and every speck of dust under a flat colour: use a felt squeegee and wet or dry application exactly as the printer specifies, and never a heat gun on the glass.
- Trim inside the rebate, 2 mm clear of the glass edge. Clear 25 mm around handles, locks and hinges.
- Do not stretch the film to fit a pane. If a pane is out of square by more than 3 mm, re-cut the artwork to the measured diagonal — the design has room for it.
- Leave 24 hours before cleaning or closing the door against the film.

OPEN ITEMS

- Confirm the column order on the leaf: 500 mm on the left as drawn, or mirrored?
- BCM's own vector logo, to replace the recreated badge on all eight panes.
- Telephone: panes 1-18, the sign post and the three roadside banners print 0788 323 815 and 0754 132 715; panes 19-24 print 0771 240 104 and 0754 132 715. Confirm which lines are current before plotting.
- Confirm the client wants a solid pane on this door — it blocks the view in and out.
- The printer's own film standard, to replace the flagged values.
- Print-resolution originals: the working files are desktop previews. Pull the full-size files from the recorded Pexels links, or shoot the real team.