# Production specification — door 1

Eight panes, two widths, one film. Values marked “confirm with printer” are industry-typical placeholders, not something the printer has agreed to.

| ITEM | VALUE |
|---|---|
| TRIM SIZE | 900 × 500 MM (4 PANES) AND 900 × 400 MM (4 PANES) |
| WITH BLEED | 920 × 520 MM AND 920 × 420 MM |
| BLEED | 10 MM ALL ROUND |
| LIVE / SAFE | 25 MM INSIDE TRIM — 20 MM ON THE 400 MM PANES |
| CROP MARKS | OFFSET 4 MM, 4 MM LONG, OUTSIDE BLEED |
| SLUG | 20 MM AT THE FOOT, OUTSIDE BLEED |
| SERVICE NAME | CAP HEIGHT 13.5 % OF PANE WIDTH — 64 MM ON THE WIDE PANE, 54 MM ON THE NARROW |
| SMALLEST LIVE TYPE | 6 MM CAP |
| RESOLUTION | 75 PPI FLOOR, 100 PPI TARGET IN THE PLACED CROP |
| COLOUR | CMYK, COATED PROFILE; NAVY #16233F, CYAN #2BA9E0 |
| FONTS | MANROPE + INTER, SIL OFL, EMBEDDED |

## FILM

- Perforated one-way vision vinyl, white-backed, 140–160 µm plus liner — confirm with printer.
- 1.6 mm holes on a 2.3 mm staggered pitch, 44 % open by geometry. The mesh, not the file, is the limit on detail.
- Matte anti-glare face, UV or latex print, four colour plus white backing layer.
- Eight pieces per door. Cut from one roll run so the navy matches across all eight.

# Installation — door 1

- Re-measure every pane with a tape, corner to corner, before plotting. Measured figures were supplied for this door; the next door may not match.
- Number the panes on the back of each print in pencil as they are cut — eight pieces, two sizes, and they all look alike in a stack.
- Clean the glass and apply one pane as a control: the narrowest, most awkward one, low on the leaf, where mistakes are least visible.
- Keep the perforation grid square to the frame, not to the handle. On two 900 mm rows stacked, a skewed grid reads as a crooked poster.
- Trim inside the rebate, 2 mm clear of the glass edge. Clear 25 mm around handles, locks and hinges.
- Do not stretch the film to fit a pane. If a pane is out of square by more than 3 mm, re-cut the artwork to the measured diagonal — the design has room for it.
- Leave 24 hours before cleaning or closing the door against the film.

## OPEN ITEMS

- Confirm the column order on the leaf: 500 mm on the left as drawn, or mirrored?
- BCM's vector logo, for the plate on all eight panes.
- Telephone numbers, if they are to appear — currently none do.
- The printer's own film standard, to replace the flagged values.
- Full-resolution originals for the six retouched photographs, or a shoot of the real team. The current files are proof resolution.