Insole / Carbon Fiber Board Test Results

中底 / 碳纤片测试结果

SATRA Accredited Laboratory No.18B23

Form # : Lab VF 018

ETRF.No:

Lab Ref.No:

Supplier/Factory(厂商) :	
Supplier's country(国家):	O New/Development 开发段新材料
Material Description(材料):	o Tech 1 o Tech 2 o Tech 3 o Tech 4
Color (颜色):	O Sales Sample (销售样品)
Model No./Style(型体): /	Received Date (收到日期):
P.O/Lot No(编号): /	Tested Date (测试时间):
Quantity(数量):	Finished Date (完成时间):
Send by (提供方):	Technician (技术人员):

Test Items 测试项目	VF Test Method	Units 单位	Test results 测试结果	Max/Min 最大/小值	Average 平均值	Standard 标准	Tolerance 容许量	Rating 等级
Gauge 规格	VF-A03 (2014/04)	mm				*Refer Specific Requirements*		
Weight 重量	VF-A02 (2018/11)	g/m²				*Refer Specific Requirements*		
Tensile 抗拉	VF-B01 (2022/11)	kgf/cm	L=					
			W=					
Elongation 延伸	VF-B01 (2022/11)	%	L=					
			W=					
Mullen Burst 爆破	VF-B02 (2019/05)	kgf/cm²						
Trouser Tear - 裤形撕裂	VF-B07 (2022/11)	kgf	L=					
			W=					
Water Sw elling 膨胀性	VF-E18 (2008/05)	%						
Water Absorption吸水率	VF-E10 (2014/07)	%						
Moiture Content 100℃ 16 Hrs	VF-E12 (2008/05)	%						
Shrinkage 收缩率(1hr, 60 ℃)	VF-E13 (2016/03)	%	L=					
			W=					
Laminar Peel Strength 剥离强度	VF-F04 (2019/05)	kgf/cm	Dry干=					
			Wet湿=					
Martindale Abrasion Martindale 耐磨	VF-C04 (2024/12)	cycles	Dry干=					
			Wet湿=					
Flexing Ross Ross曲折	VF-D02 (2019/05)	Rating						
Colorfastness to Perspiration - (Grain side) 耐汗测试(正面)	VF-E16 (2018/11)	AATCC	Wool 毛料 / Acrylic 丙烯酸 / Polyester 聚酯 / Nylon 尼龙 / Cotton / Acetate 醋酸纤维					
Colorfastness to Perspiration - Back side耐汗测试(反面)			Wool 毛料 / Acrylic 丙烯酸 / Polyester 聚酯 / Nylon 尼龙 / Cotton / Acetate 醋酸纤维					
Colorfastness to Water (Grain side) 耐水测试(正面) VFM-	VF-E01 (2008/05)	AATCC	Wool 毛料 / Acrylic 丙烯酸 / Polyester 聚酯 / Nylon 尼龙 / Cotton / Acetate 醋酸纤维					
Colorfastness to Water Back side耐水测试(反面) VFM-030-1/VFM-032-1			Wool 毛料 / Acrylic 丙烯酸 / Polyester 聚酯 / Nylon 尼龙 / Cotton / Acetate 醋酸纤维					
Colorfastness to Crocking 摩擦褪色	VF-E02 (2024/08)	AATCC	Dry干=					
			Wet湿=					
UV Light紫外线 (24hrs, 50℃)	VF-E03 (2019/05)	AATCC						
Heat Aging 热老化 (72hrs,70℃)	VF-E04 (2022/09)							
Hydrolysis 水解 (7Days,60℃ 95%RH)	VF-E19 (2024/12)							
Wicking 虹吸	VF-E14 (2014/07)	mm						

Comments 备注:

Reviewed by 审查:

Approved by 核准: