VelcroTest Results
魔术带测试报告

Form # : Lab VF 013	**ETRF.No:**
	Lab Ref.No:

Supplier/Factory(厂商) :	
Supplier's country(国家):	O New/Development 开发段新材料
Material Description(材料):	o Tech 1 o Tech 2 o Tech 3 o Tech 4
Color (颜色):	O Sales Sample (销售样品)
Model No./Style(型体): /	Received Date (收到日期):
P.O/Lot No(订单): /	Tested Date (测试时间):
Quantity(数量):	Finished Date (完成时间):
Send by (提供方):	Technician (技术人员):

Test Items 测试项目	VF Test Method	Units 单位	Test results 测试结果	Max/Min 最大/小值	Average 平均值	Standard 标准	Tolerance 容许量	Rating 等级
Gauge 规格 (Loop)	VF-A03 (2014/04)	mm						
Gauge 规格 (Hook)								
Weight 重量(Loop)	VF-A02 (2018/11)	g/cm^2						
Weight 重量(Hook)								
Tensile 抗拉 (Loop)	VF-B01 (2019/05)	kgf						
Tensile 抗拉 (Hook)								
Elongation 延伸 (Loop)	VF-B01 (2022/11)	%				20		
Elongation 延伸 (Hook)								
Trouser Tear - 裤形撕裂(Loop)	VF-B07 (2022/11)	kgf						
Trouser Tear - 裤形撕裂(Hook)								
Stich tear 车缝撕裂(Loop)	VF-B08 (2019/05)	kgf/cm						
Stich tear 车缝撕裂(Hook)								
Peel Stength剥离initial	VF-B03 (2019/05)	kgf/cm						
Peel Stength剥离 after 10000 cycles								
Shear Strength剪力 Initial	VF-B03 (2019/05)	kgf/cm2						
Shear Strength剪力 after 10000 cycles								
Mullen Burst 爆破	VF-B02 (2019/05)	kgf/cm^2						
Colorfastness to Perspiration (Top Side/Finished Surface Only) 耐汗测试(正面)	VF-E16 (2018/11)	AATCC	Wool 毛料 / Acrylic 丙烯酸树脂纤维 / Polyester 聚酯 / Nylon 尼龙 / Cotton 棉 / Acetate 醋酸纤维					
Colorfastness to Perspiration Back side耐汗测试(反面)			Wool 毛料 / Acrylic 丙烯酸树脂纤维 / Polyester 聚酯 / Nylon 尼龙 / Cotton 棉 / Acetate 醋酸纤维					
Colorfastness to Water (Top Side/Finished Surface Only) 耐水测试(正面)	VF-E01 (2008/05)	AATCC	Wool 毛料 / Acrylic 丙烯酸树脂纤维 / Polyester 聚酯 / Nylon 尼龙 / Cotton 棉 / Acetate 醋酸纤维					
Colorfastness to Water Back side耐水测试(反面)			Wool 毛料 / Acrylic 丙烯酸树脂纤维 / Polyester 聚酯 / Nylon 尼龙 / Cotton 棉 / Acetate 醋酸纤维					
Colorfastness to Crocking 摩擦褪色	VF-E02 (2024/08)	AATCC	Dry干=					
			Wet湿=					
UV light紫外线 (24hrs, 50℃)	VF-E03 (2019/05)	AATCC						
Heat Aging 热老化 (72hrs,70℃)	VF-E04 (2022/09)							
Shrinkage 收缩率(1 hr, 70 ℃)	VF-E13 (2016/03)	%						
Hydrolysis 水解(7Days,60℃ 95%RH)	VF-E19 (2024/12)							

Comments 备注:

Reviewed by 审查:

Approved by 核准: