Eyelet & Lable & Brand & Packaging Test Results

眼扣 & 布标 & 商标 & 包装袋测试报告

SATRA Accredited Laboratory No.18B23

Form # : Lab VF 011

ETRF.No:

Lab Ref.No:

Supplier/Factory(厂商):
Supplier's country(国家):
Material Description(材料):
Color (颜色):
Model No./Style(型体):
P.O/Lot No(订单):
Quantity(数量):
Send by (提供方):

O Proto Material 量产材料 O Proto Product 量产重测
O New/Development 开发段新材料

o Tech 1 o Tech 2 o Tech 3 o Tech 4
O Sales Sample (销售样品)
Received Date (收到日期):
Tested Date (测试时间):
Finished Date (完成时间):
Technician (技术人员):

Test Items 测试项目	VF Test Method	Units 单位	Test results 测试结果	Average 平均值	Standard 标准	Tolerance 容许量	Rating 等级
Gauge 规格	VF-A03	mm					
Weight 重量	VF-A02	g/m^2					
Tensile 抗拉	VF-B01	kg					
Tensile 抗拉	VF-B01	kg					
Elongation 延伸	VF-B01	%					
Die- C tear C型撕裂	VF-B05	kg					
Trouser Tear - 裤形撕裂	VF-B07	kg					
Elongation 延伸	VF-B01	%					
10 kg Load Elongation伸长率	VF-B01	%					
Load at 50% extension 伸长50%抗拉	VF-B01	kg					
Heat Aging 热老化 (72hrs,70℃)	VF-E04	ASTM					
Corrosion Resistance 腐蚀	VF-E09	ASTM					
Hydrolysis 水解(7Days,70℃ 95%RH)	VF-E17						
Martindale Abrasion Martindale 耐磨	VF-C04	cycles	Dry干=				
			Wet湿=				
Mullen Burst 爆破	VF-B02	kg/cm^2					
Colorfastness to Perspiration (Top Side/Finished Surface Only) 耐汗测试(正面)	VF-E16	AATCC	Wool 毛料 / Orlon 奥龙 / Dacron 涤纶 / Nylon 尼龙 / Cotton 棉 / Acetate 合成纤				
Colorfastness to Perspiration Back side耐汗测试(反面)			Wool 毛料 / Orlon 奥龙 / Dacron 涤纶 / Nylon 尼龙 / Cotton 棉 / Acetate 合成纤				
Colorfastness to Water (Top Side/Finished Surface Only) 耐水测试(正面)	VF-E01	AATCC	Wool 毛料 / Orlon 奥龙 / Dacron 涤纶 / Nylon 尼龙 / Cotton 棉 / Acetate 合成纤				
Colorfastness to Water Back side耐水测试(反面)			Wool 毛料 / Orlon 奥龙 / Dacron 涤纶 / Nylon 尼龙 / Cotton 棉 / Acetate 合成纤				
Colorfastness to Crocking 摩擦褪色	VF-E02	AATCC	Dry干=				
			Wet湿=				
UV light紫外线 (24hrs, 5℃)	VF-E03	AATCC					
Phenolic Yellowing 酚黄							
Peeling Strength 剥离强度	VF-F02	kg/cm					
PH Value PH值	VF-A05	AATCC					
PVC Contact Discoloration PVC 移色	VF-E06	AATCC					

Comments 备注:

Reviewed by 审查:

Approved by 核准: