Zipper Test Results
拉链测试结果

Form # : Lab VF 016	**ETRF.No:**
	Lab Ref.No:

Supplier/Factory(厂商):			
Supplier's country(国家):		O New/Development 开发段新材料	
Material Description(材料):		o Tech 1 o Tech 2 o Tech 3 o Tech 4	
Color (颜色):		O Sales Sample (销售样品)	
Model No./Style(型体):	/	Received Date (收到日期):	
P.O/Lot No(订单):	/	Tested Date (测试时间):	
Quantity(数量):		Finished Date (完成时间):	
Send by (提供方):		Technician (技术人员):	

Test Items 测试项目	VF Test Method	Units 单位	Test results 测试结果	Max/Min 最大/小值	Average 平均值	Standard 标准	Tolerance 容许量	Rating 等级
Gauge 规格	VF-A03 (2014/04)	mm						
Weight 重量	VF-A02 (2018/11)	g/m^2						
Crossw ise Strength	VF-B17 (2019/05)	kgf						
Element Pull -Off	VF-B17 (2019/05)	kgf						
Element slippage , Lengthw ise	VF-B17 (2019/05)	kgf						
Slider Pulling	VF-B17 (2019/05)	kgf						
Top Stop Holding Strength	VF-B17 (2019/05)	kgf						
Bottom Stop Holding Strength , Slider	VF-B17 (2019/05)	kgf						
Bridge Top Stop Strength , Stringer Separation	VF-B17 (2019/05)	kgf						
Separable Pin Pull-off	VF-B17 (2019/05)	kgf						
Fixed Retainer Pull -off	VF-B17 (2019/05)	kgf						
Separating Unit , Crossw ise	VF-B17 (2019/05)	kgf						
Resistance to tw ist of Pull and Slider	VF-B17 (2019/05)	kgf						
Resistance to Pull - Off slider Pull	VF-B17 (2019/05)	kgf						
Resistance to Angular Pull-Off Slider	VF-B17 (2019/05)	kgf						
Holding strength of Slider Lock	VF-B17 (2019/05)	kgf						
Slide Fasteners Reciprocating	VF-B26 (2011/06)	cycles						
Stitch Tear 车缝撕裂	VF-B08 (2019/05)	kgf/cm						
Colorfastness to Perspiration(Top side/Finished Surface Only) 耐汗测试(正面)	VF-E16 (2018/11)	AATCC	Wool 毛料 / Acrylic 丙烯酸树脂纤维 / Polyester 聚酯 / Nylon 尼龙 / Cotton 棉 / Acetate 醋酸纤维					
Colorfastness to Water(Top side/Finished Surface Only) 耐水测试(正面)	VF-E01 (2008/05)	AATCC	Wool 毛料 / Acrylic 丙烯酸树脂纤维 / Polyester 聚酯 / Nylon 尼龙 / Cotton 棉 / Acetate 醋酸纤维					
Colorfastness to Crocking 摩擦褪色	VF-E02 (2024/08)	AATCC	Dry干= / Wet湿=					
UV Light紫外线 (24hrs, 50℃)	VF-E03 (2019/05)	AATCC						
Wicking 虹吸	VF-E14 (2014/07)	mm						
Heat Aging 热老化 (72hrs,70℃)	VF-E04 (2022/09)							
Shrinkage 收缩率 (1 hr, 70 ℃)	VF-E13 (2016/03)	%	L= / W=					
Hydrolysis 水解(7Days,60℃ 95%RH)	VF-E19 (2024/12)				No peeling off coating and no deformation of material			
Corrosion Resistance 腐蚀	VF-E09 (2014/12)	AATCC				No Corrosion		

Comments 备注:

Reviewed by 审查:

Approved by 核准: