HTML TEXT FORMATING

HTML text Formatting

- HTML also defines special **elements**, for defining text with a special **meaning**.
- HTML uses elements like <b> and <i> for formatting output, like **bold** or *italic* text.
- Formatting elements were designed to display special **types of text**:

1. Bold text
2. Important text
3. Italic text
4. Emphasized text
5. Marked text
6. Small text
7. Deleted text
8. Inserted text
9. Subscripts
10. Superscripts

HTML Text Formatting

This text is bold

This text is italic

This is computer output

This is $_{\text{subscript}}$ and ^{superscript}

HTML Formatting Tags

- HTML uses tags like **<b>** and **<i>** for formatting output, like **bold** or *italic* text.
- These HTML tags are called formatting tags (look at the bottom of this page for a complete reference).
- **Example:**

Often renders as <b>, and renders as <i>.

- However, there is a difference in the meaning of these tags:

  <b> or <i> defines bold or italic text only.
- **** or **** means that you want the text to be rendered in a way that the user understands as "important".
- Today, all major browsers render strong as bold and em as italics. However, if a browser one day wants to make a text highlighted with the strong feature, it might be cursive for example and not bold!

HTML **Bold** and **Strong** Formatting

- The HTML **<b>** element defines **bold** text, without any extra importance.

```
<html>
<head><title>Bold</title></head>
<body>
<p>This text is normal.</p>
<p><b>This text is bold.</b></p>
</body>
</html>
```

The HTML **** element defines **strong** text, with added semantic "strong" importance.

```
<html>
<head><title>strong</title></head>
<body>
<p>This text is normal.</p>
<p><strong>This text is strong.</strong></p>
</body>
</html>
```

HTML *Italic* and *Emphasized* Formatting

- The HTML **<i>** element defines *italic* text, without any extra importance.

```
<html>
<head><title>italics</title></head>
<body>
<p>This text is normal.</p>
<p><i>This text is italic.</i></p>
</body>
</html>
```

- the HTML **** element defines *emphasized* text, with added semantic importance.

```
<html>
<head><title>Emphasis</title></head>
<body>
<p>This text is normal.</p>
<p><em>This text is emphasized.</em></p>
</body>
</html>
```

-

HTML Small Formatting

- The HTML **<small>** element defines **small** text:

```
<html>
<head><title>Small</title></head>
<body>
<h2>HTML <small>Small</small> Formatting</h2>
</body>
</html>
```

HTML Marked Formatting

- The HTML **<mark>** element defines **marked** or highlighted text:

```
<html>
<head><title>Marked</title>
<body>
<h2>Html<mark>Marked</mark>Formating</h2>

</body>
</html>
```

HTML ~~Deleted~~ Formatting

- The HTML **<del>** element defines **deleted** (removed) text.
- Example

```
<html>
<head><title>Deleted</title></head>
<body>
<p>My favorite color is <del>blue</del> red.</p>
 </body>
</html>
```

HTML Subscript Formatting

- The HTML **<sub>** element defines **subscripted** text.
- Example

```
<html>
<head><title>Subdcript</title></head>
<body>
<p>This is <sub>subscripted</sub> text.</p>
</body>
</html>
```

HTML Superscript Formatting

- The HTML <sup> element defines superscripted text.
- **Example**

```
<html>
<head><title>Superscript</title></head>
<body>
<p>This is <sup>superscripted</sup> text.</p>
</body>
</html>
```

HTML Head

The Head Element

The head element contains general information, also called meta-information, about a document.

Meta means "information about".

You can say that meta-data means information about data, or meta-information means information about information.

Information Inside the Head Element

- The elements inside the head element should not be displayed by a browser.
- According to the HTML standard, only a few tags are legal inside the head section.
- These are: <base>, <link>, <meta>, <title>, <style>, and <script>.

- Look at the following illegal construct:

```
<head>
<p>This is some text</p>
</head>
```

- In this case the browser has two options:
  1. Display the text because it is inside a paragraph element
  2. Hide the text because it is inside a head element
- If you put an HTML element like <h1> or <p> inside a head element like this, most browsers will display it, even if it is illegal.

Head Tags

Tag	Description
<head>	Defines information about the document
<title>	Defines the document title
<base>	Defines a base URL for all the links on a page
<link>	Defines a resource reference
<meta>	Defines meta information
<!DOCTYPE>	Defines the document type. This tag goes before the <html> start tag.

HTML Layout

Everywhere on the Web you will find pages that are formatted like newspaper pages using HTML columns.

- One very common practice with HTML, is to use HTML tables to format the layout of an HTML page.
- An HTML <table> is used to divide a part of this Web page into two columns. The trick is to use a table without borders, and maybe a little extra cell-padding.
- No matter how much text you add to this page, it will stay inside its column borders.

Examples

- Dividing a part of an HTML page into table columns is very easy to do. To let you experiment with it, we have put together

HTML Tables

- Tables are defined with the <table> tag.
- A table is divided into rows (with the **<tr>** tag), and each row is divided into data cells (with the **<td>** tag).

- The letters **td** stands for "table data," which is the content of a data cell.
- A data cell can contain text, images, lists, paragraphs, forms, horizontal rules, tables, etc.

example

```
<table border="1">
<tr>
<td>row 1, cell 1</td>
<td>row 1, cell 2</td>
</tr>
<tr>
<td>row 2, cell 1</td>
<td>row 2, cell 2</td>
</tr>
</table>
```

How it looks in a browser:

row 1, cell 1	row 1, cell 2
row 2, cell 1	row 2, cell 2

Tables and the Border Attribute

- If you do not specify a border attribute the table will be displayed without any borders.
- Sometimes this can be useful, but most of the time, you want the borders to show.
- To display a table with borders, you will have to use the border attribute:

```
table border="1">
<tr>
<td>Row <1, cell 1</td>
<td>Row 1, cell 2</td>
</tr>
</table>
```

Headings in a Table

- Headings in a table are defined with the **<th>** tag.

```
<table border="1">
<tr>
<th>Heading</th>
<th>Another Heading</th>
</tr>
<tr>
<td>row 1, cell 1</td>
<td>row 1, cell 2</td>
</tr>
<tr>
<td>row 2, cell 1</td>
<td>row 2, cell 2</td>
</tr>
</table>
```

How it looks in a browser:

Heading	Another Heading
row 1, cell 1	row 1, cell 2
row 2, cell 1	row 2, cell 2

Empty Cells in a Table

- Table cells with no content are not displayed very well in most browsers.

```
<table border="1">
<tr>
<td>row 1, cell 1</td>
<td>row 1, cell 2</td>
</tr>
<tr>
<td>row 2, cell 1</td>
<td></td>
</tr>
</table>
```

How it looks in a browser:

row 1, cell 1	row 1, cell 2
row 2, cell 1	

- Note that the borders around the empty table cell are missing (NB! Mozilla Firefox displays the border).
- To avoid this, add a non-breaking space ( ) to empty data cells, to make the borders visible:

```
<table border="1">
<tr>
<td>row 1, cell 1</td>
<td>row 1, cell 2</td>
</tr>
<tr>
<td>row 2, cell 1</td>
<td> </td>
</tr>
</table>
```

How it looks in a browser:

row 1, cell 1	row 1, cell 2
row 2, cell 1	

HTML Frames

- With frames, you can display more than one Web page in the same browser window.

- With frames, you can display more than one HTML document in the same browser window. Each HTML document is called a frame, and each frame is independent of the others.

The disadvantages of using frames are:

1. The web developer must keep track of more HTML documents
2. It is difficult to print the entire page

The Frameset Tag

- The **<frameset>** tag defines how to divide the window into frames
- Each frameset defines a set of rows **or** columns
- The values of the rows/columns indicate the amount of screen area each row/column will occupy
- The <frame> tag defines what HTML document to put into each frame
- In the example below we have a frameset with two columns. The first column is set to 25% of the width of the browser window.

- The second column is set to 75% of the width of the browser window. The HTML document "frame_a.htm" is put into the first column, and the HTML document "frame_b.htm" is put into the second column:

```
<frameset cols="25%,75%">
    <frame src="frame_a.htm">
    <frame src="frame_b.htm">
</frameset>
```

Note: The frameset column size value can also be set in pixels (cols="200,500"), and one of the columns can be set to use the remaining space (cols="25%,*").

Basic Notes - Useful Tips

- If a frame has visible borders, the user can resize it by dragging the border.
- To prevent a user from doing this, you can add noresize="noresize" to the <frame> tag.
- Add the <noframes> tag for browsers that do not support frames.

- **Important:** You cannot use the <body></body> tags together with the <frameset></frameset> tags! However, if you add a <noframes> tag containing some text for browsers that do not support frames, you will have to enclose the text in <body></body> tags!

HTML Marquee Code

- You can create scrolling text (or anything else for that matter) by using the **<marquee>** tag.

Example Marquee Code

- Note that if you can't view the examples, it's likely that your browser doesn't support the marquee tag.

1) Slide-in text:

- This text slides in from the right, then stays where it is. You will need to refresh this page to see the effect again.

```
<marquee behavior="slide" direction="left">
Your slide-in text goes here
</marquee>
```

2) Continuous scrolling text:

```
<marquee behavior="scroll" direction="left">
Your scrolling text goes here
</marquee>
```

3) Text bouncing back and forth:

```
<marquee behavior="alternate">
Your bouncing text goes here
</marquee>
```

4) Text Scrolling Upwards:

```
<marquee  behavior="scroll" direction="up">
Your upward scrolling text goes here
</marquee>
```

5) Change the Scrolling Speed:

```
<marquee behavior="scroll" direction="left" scrollamount="1">
Slow scroll speed</marquee>
<marquee behavior="scroll" direction="left" scrollamount="10">
Medium scroll speed</marquee>
<marquee behavior="scroll" direction="left" scrollamount="20">
Fast scroll speed</marquee>
```

6) Scrolling Images:

Simply replace the src="... part with the location of your own image.

```
<marquee behavior="scroll" direction="left">
<img src="/pix/smile.gif" width="100" height="100" alt="smile" />
</marquee>
```

7) Images & Text (Both Scrolling):

Simply add your text under the image tag (but still within the marquee tags).

```
<marquee behavior="scroll" direction="left">
<img src="/pix/smile.gif" width="100" height="100" alt="smile" />
<p>Sample text under a marquee image.</p></marquee>
```

HTML Character Entities

- Some characters are reserved in HTML.

- For example, you cannot use the greater than or less than signs within your text because the browser could mistake them for markup.

- If we want the browser to actually display these characters we must insert character entities in the HTML source.

- A character entity looks like this: &*entity_name*; OR &#*entity_number*;
- To display a less than sign we must write: **<** or **<**
- The advantage of using an entity name instead of a number is that the name often is easier to remember.

- However, the disadvantage is that browsers may not support all entity names (while the support for entity numbers is very good).

Non-breaking Space

- The most common character entity in HTML is the non-breaking space.
- Normally HTML will truncate spaces in your text.
- If you write 10 spaces in your text HTML will remove 9 of them.
- To add lots of spaces to your text, use the   character entity.

Commonly Used Character Entities

Note Entity names are case sensitive!

Result	Description	Entity Name	Entity Number
	non-breaking space		
<	less than	<	<
>	greater than	>	>
&	ampersand	&	&
¢	cent	¢	¢
£	pound	£	£
¥	yen	¥	¥
€	euro	€	€
§	section	§	§
©	copyright	©	©
®	registered trademark	®	®

Summary of html formatting tags

Tag	Description
<b>	Defines bold text
	Defines emphasized text
<i>	Defines a part of text in an alternate voice or mood
<small>	Defines smaller text
	Defines important text
<sub>	Defines subscripted text
<sup>	Defines superscripted text
<ins>	Defines inserted text
<del>	Defines deleted text
<mark>	Defines marked/highlighted text

HTML "Computer Output" Tags

Tag	Description
<code>	Defines computer code text
<kbd>	Defines keyboard text
<samp>	Defines sample computer code
<var>	Defines a variable
<pre>	Defines preformatted text

HTML Citations, Quotations, and Definition Tags

Tag	Description
<abbr>	Defines an abbreviation or acronym
<address>	Defines contact information for the author/owner of a document
<bdo>	Defines the text direction
<blockquote>	Defines a section that is quoted from another source
<q>	Defines an inline (short) quotation
<cite>	Defines the title of a work
<dfn>	Defines a definition term