


University of Nottingham UK | CHINA | MALAYSIA

Introduction to Image Processing

Lecture 7
Segmentation



Learning Outcomes





What is Segmentation?



Image Segmentation

?

A common task in image analysis & computer vision

To identify **meaningful** regions

Why do it?

We can partition or group pixels according to local image properties


- Intensity or colour from original images, or computed values based on image operators
- Textures or patterns that are unique to each type of region
- Spectral profiles that provide multidimensional image data


Elaborate systems may use a combination of properties







Applications













Approaches

Many different approaches have been taken to the segmentation problem

Seeks groups of similar pixels, with no regard for where they are – views images as uncorrelated data

Clustering

- Focus on finding physically connected sets of pixels
- E.g., region growing, split and merge

Region-based

Emphasise the boundaries between regions

E.g., watersheds

Edge-based

Thresholding + connected components is a form of segmentation, but treats grey/colour and spatial information independently

Note



Region-Based Segmentation



Region-based Segmentation

We want smooth regions in the image

- We still want the pixels in each region to be similar, and those in adjacent regions to be different
- One way to do this is to work with regions rather than pixels

Region Growing

Start with a small 'seed' and expand by adding similar pixels

Split & Merge

- Splitting divides regions that are inconsistent
- Merging combines adjacent regions that are consistent



Region Growing

Region growing starts with a small patch of seed pixels



- Compute statistics about the region
- Check neighbours to see if they can be added
- Recompute the statistics

Algorithm

This procedure repeats until the region stops growing

- Simple example: we compute the mean grey level of pixels in the region
- Neighbours are added if their grey level is near the average






Region Growing Example













Output 2



Output 3

Output 1

COMP 2005


Segmentation



Split and Merge - Split

We start by taking the whole image to be one region

- We compute some measure of internal similarity
- If this indicates there is too much variety, we divide the region
- Repeat until no more splits, or we reach a minimum region size




Some details are needed



- How to we measure similarity? standard deviation are commonly used
- How do we determine whether to split or not? thresholding is easy
- How do we split regions? quadtrees are a common method




Quadtrees



F	G	J	R	S
			Т	U
Н	I	L	М	
N	0	E		
Р	Q			



Example - Splitting



We'll use the tree image again

- Splitting based on intensity (could use something else)
- Splitting based on standard deviation, with a threshold of 25

13


Split using quadtree with a maximum of 5 level



Split and Merge - Merge

Splitting give us...

- Regions that are small, consistent, or both
- Rather too many regions, as adjacent ones may be very similar
- We can now combine adjacent regions to make bigger ones






- We merge two regions if they are adjacent and similar
- Need a measure of similarity can compare their mean grey level, or use statistical tests
- Repeat the merging until you can do no more



Example - Merging



We consider merging adjacent regions

- Two regions are merged if their mean grey levels differ by less than 25
- This leads to less regularly shaped regions, but they are larger and still consistent



Break






Edge-based Segmentation (Watersheds)



Edge-based Segmentation

- Do region-based methods focus too much on regions?
- Edge represent discontinuities in image intensity
- Regions should then be areas without edges, and should be bounded by edges
- One class of edge-based segmentation uses watersheds



In geography, a watershed is a ridge which divides rainfall into basins on either side



Catchments in images

We can view the **gradient** image as a terrain

- Areas of high gradient are high points on the terrain
- Catchment basins are regions in the image
- Watersheds are the lines dividing them

We don't have to use the usual intensity gradient


- Gradients can be computed from hue etc., if we want
- Any value that is low within a region and high at boundaries could be used




Using gradients is common, though....




Gradients in Highlight Edges


















COMP 2005 Segmentation

23
















26










COMP 2032 Segmentation


28







Watersheds in Images




We start by finding images gradients

- Using methods like Sobel operators, we get a value – for the gradient magnitude
- This can be viewed as a 3D 'terrain'

$$\sqrt{I_X^2 + I_y^2}$$



Watersheds in Images



We then slowly flood the terrain

- Flat areas of the image become areas of low gradient, so are valleys in the terrain
- Edges in the image have high gradient and so are ridges in the terrain



Watershed Algorithm

1. Sort the pixels: low to high

2. For each pixels

- 1

If it's neighbours are all unlabelled, give it a new label

If it has neighbours with a single label, it gets that label


- If it has neighbours with two or more labels, it is a watershed

This is a very basic version

- It has certain problems in that it can give 'thick' watersheds rather than fine lines
- It is sensitive to noise and so can generate lots of small regions
- It does show the basic plan, though

COMP 2005





Sorted list:

$$(3,4) = 1$$

 $(4,4) = 1$

$$(4,3) = 1$$

$$(1,2) = 1$$

$$(2,4) = 2$$

 $(1,3) = 2$

$$(1,3) = 2$$

$$(3,3) = 2$$

$$(4,2) = 2$$

$$(1,1) = 2$$

$$(2,1) = 2$$

$$(1,4) = 3$$


$$(2,3) = 3$$

$$(2,2) = 3$$

$$(3,2) = 3$$


$$(4,1) = 3$$

$$(3,1) = 4$$



Labels





Sorted list:

$$(3,4) = 1$$

$$(4,4) = 1$$

$$(4,3) = 1$$

$$(1,2) = 1$$

$$(2,4) = 2$$

$$(1,3) = 2$$

$$(3,3) = 2$$

$$(4,2) = 2$$

$$(1,1) = 2$$

$$(2,1) = 2$$


$$(1,4) = 3$$

$$(2,3) = 3$$


$$(2,2) = 3$$

$$(3,2) = 3$$

(4,1) = 3(3,1) = 4







Sorted list:

$$(3,4) = 1$$

$$(4,4) = 1$$

$$(4,3) = 1$$

$$(1,2) = 1$$

$$(2,4) = 2$$

$$(1,3) = 2$$

$$(3,3) = 2$$

$$(4,2) = 2$$

$$(1,1) = 2$$

$$(2,1) = 2$$

$$(1,4) = 3$$


$$(2,3) = 3$$

$$(2,2) = 3$$


$$(3,2) = 3$$

$$(4,1) = 3$$

$$(3,1) = 4$$



Labels



Sorted list:

$$(3,4) = 1$$

$$(4,4) = 1$$

$$(4,3) = 1$$

$$(1,2) = 1$$

$$(2,4) = 2$$

$$(1,3) = 2$$

$$(3,3) = 2$$

$$(4,2) = 2$$

$$(1,1) = 2$$

$$(2,1) = 2$$

$$(1,4) = 3$$


$$(2,3) = 3$$

$$(2,2) = 3$$


$$(3,2) = 3$$

$$(4,1) = 3$$

$$(3,1) = 4$$








Sorted list:


Sorted list:

$$(3,4) = 1$$

 $(4,4) = 1$
 $(4,3) = 1$
 $(1,2) = 1$
 $(2,4) = 2$
 $(1,3) = 2$
 $(3,3) = 2$
 $(4,2) = 2$
 $(1,1) = 2$
 $(2,1) = 2$
 $(1,4) = 3$
 $(2,3) = 3$
 $(2,2) = 3$
 $(3,2) = 3$

(4,1) = 3(3,1) = 4





Sorted list:

$$(3,4) = 1$$

$$(4,4) = 1$$

$$(4,3) = 1$$

$$(1,2) = 1$$

$$(2,4) = 2$$

$$(1,3) = 2$$

$$(3,3) = 2$$

$$(4,2) = 2$$

$$(1,1) = 2$$

$$(2,1) = 2$$


$$(1,4) = 3$$

$$(2,3) = 3$$

$$(2,2) = 3$$

(3,2) = 3 (4,1) = 3(3,1) = 4

		Α	Α
			А
В			
Labels			



Sorted list:

$$(3,4) = 1$$

$$(4,4) = 1$$

$$(4,3) = 1$$

$$(1,2) = 1$$

$$(2,4) = 2$$

$$(1,3) = 2$$

$$(3,3) = 2$$

$$(4,2) = 2$$

$$(1,1) = 2$$


$$(2,1) = 2$$


$$(1,4) = 3$$

$$(2,3) = 3$$

$$(2,2) = 3$$

(3,2) = 3(4,1) = 3(3,1) = 4





Sorted list:

$$(3,4) = 1$$

 $(4,4) = 1$
 $(4,3) = 1$
 $(1,2) = 1$
 $(2,4) = 2$
 $(1,3) = 2$
 $(3,3) = 2$
 $(4,2) = 2$
 $(1,1) = 2$

$$(2,1) = 2$$

$$(1,4) = 3$$


 $(2,3) = 3$

$$(2,2) = 3$$

$$(3,2) = 3$$


$$(4,1) = 3$$

$$(3,1) = 4$$



COMP 2005 Segmentation





$$(3,4) = 1$$


 $(4,4) = 1$
 $(4,3) = 1$
 $(1,2) = 1$
 $(2,4) = 2$
 $(1,3) = 2$
 $(3,3) = 2$
 $(4,2) = 2$
 $(1,1) = 2$
 $(2,1) = 2$
 $(1,4) = 3$
 $(2,3) = 3$
 $(2,2) = 3$

	Α	Α	A
		Α	Α
В			
Labels			

$$(4,1) = 3$$

$$(3,1) = 4$$






$$(3,4) = 1$$

 $(4,4) = 1$
 $(4,3) = 1$
 $(1,2) = 1$
 $(2,4) = 2$
 $(1,3) = 2$
 $(3,3) = 2$
 $(4,2) = 2$
 $(1,1) = 2$
 $(2,1) = 2$
 $(1,4) = 3$


(1,4)	=	3
(2,3)	=	3
(2,2)	=	3
(3,2)	=	3

$$(4,1) = 3$$


 $(3,1) = 4$









Sorted list:



(3,2) = 3 (4,1) = 3(3,1) = 4







Sorted list:

Sorted list.

$$(3,4) = 1$$


 $(4,4) = 1$
 $(4,3) = 1$
 $(1,2) = 1$
 $(2,4) = 2$
 $(1,3) = 2$
 $(3,3) = 2$
 $(4,2) = 2$
 $(4,2) = 2$
 $(1,1) = 2$
 $(2,1) = 2$
 $(1,4) = 3$
 $(2,3) = 3$
 $(2,2) = 3$

(3,2) = 3 (4,1) = 3(3,1) = 4


	Α	А	А
		А	А
В			Α
В	В		

Labels






Sorted list:




(4,1) = 3(3,1) = 4

А	Α	Α	А
		Α	Α
В			Α
В	В		
Labels			






Sorted list:




(4,1) = 3(3,1) = 4



COMP 2005 Segmentation





Sorted list:

$$(3,4) = 1$$

$$(4,4) = 1$$

$$(4,3) = 1$$

$$(1,2) = 1$$

$$(2,4) = 2$$

$$(1,3) = 2$$

$$(3,3) = 2$$

$$(4,2) = 2$$

$$(1,1) = 2$$

$$(2,1) = 2$$


$$(1,4) = 3$$

$$(2,3) = 3$$


$$(2,2) = 3$$

$$(3,2) = 3$$

(4,1) = 3(3,1) = 4










Solite	ว แอเ
(3,4)	= 1
(4,4)	= 1
(4,3)	= 1
(1,2)	= 1
(2,4)	= 2
(1,3)	= 2
(3,3)	= 2
(4,2)	= 2
(1,1)	= 2
(2,1)	= 2
(1,4)	= 3
(2,3)	= 3
(2,2)	= 3
(3,2)	= 3
(4,1)	= 3
(3,1)	= 4

А	Α	Α	А
		Α	Α
В			Α
В	В		
Labels			














Sorte	ו ג	ISU
(3,4)	=	1
(4,4)	=	1
(4,3)	=	1
(1,2)	=	1
(2,4)	=	2
(1,3)	=	2
(3,3)	=	2
(4,2)	=	2
(1,1)	=	2
(2,1)	=	2
(1,4)	=	3
(2,3)	=	3
(2,2)	=	3
(2.2)	_	2

А	A	A	А
		Α	Α
В			Α
В	В		Α
Labels			



Computing Watersheds

Watershed based segmentations can

be very efficient



- It is possible to implement it in O(n) time, where n is the number of pixels
- Since it takes *O*(*n*) time to read or write an image, this is as good as it can get in most situations


To implement watersheds we need to sort the pixels

- They need to be sorted from highest to lowest gradient
- Sorting is $O(n \log(n))$, so how do we get an O(n) algorithm?

COMP 2005 Segmentation




Sorting in Linear Time





- Those values are drawn from a smaller set of possibilities

We can sort in linear time with a bin sort



2. For each item: put it in the appropriate bin


Bin Sort



The items are now SORTED!



Example - Watershed




Segmenting the tree image

- The basic algorithm has been modified to avoid the effects of noise
- The gradient has been quantised to remove small variations
- Above a threshold water level, no more new segments are introduced as the water rises

COMP 2005 Segmentation



Example - Watershed




- Watersheds can also be applied to some greyscale images directly
- For example, in many medical and biological images the regions are dark or light regions against a light or dark background

COMP 2005 Segmentation 5




Summary



- 1. What is Segmentation?
- 2. Region-based Segmentation
- 3. Edge-based Segmentation







NEXT:

Interactive Segmentation

COMP2005

Segmentation and Superpixels

An Alternative? Superpixels

- Segmentation has motivated development of some useful techniques, but:
 - 'segmentation' is poorly defined
 - trying to achieve meaningful, semantically correct results without knowledge of the application domain is optimistic at best
 - segmentation methods really just divide the image into similar regions
- So let's accept that and forget the semantics......



Simple Linear Iterative Clustering

- High-quality, compact, nearly uniform superpixels
- Simple, efficient algorithm based on K-means
- Only parameter is number of superpixels required (K)

1. Initialize cluster centers on pixel grid in steps S

- Image has N pixels, you want K superpixels
- Each superpixel is a roughly square area of roughly N/K pixels
- Each superpixel is roughly sqrt(N/K) by sqrt(N/K)
- S = sqrt(N/K)

2. Move centres to the position in a 3x3 window with the <u>smallest</u> intensity (or colour) gradient

- Move centres away from edges, onto flattest area available
- Only a small move, these are still initial positions


SLIC

- 3. Compare each pixel to all cluster centres within 2S pixels and assign it to the best matching centre
 - Best matching = nearby and similar in colour
 - Distance measure is sum of colour distance and image plane distance

See the paper on Moodle for details

- 4. Recompute cluster centres as mean colour and position of the pixels belonging to each cluster
- 5. Repeat 3 and 4 until total change made to position and colour of centres is below a threshold, or for a fixed number of iterations


SLIC



- Evaluated on
 - similarity of pixels in superpixels vs variation of values between adjacent superpixels
 - proportion of object boundaries marked by a superpixel boundary
- E.g. EM images of brain mitochondria (linked to degenerative diseases)
- Segmentation meets edge detection?

SLIC in Matlab

```
A = imread('kobi.png');
[L,N] = superpixels(A,500);
  // L is a label image
  // N number of superpixels actually produced
figure
BW = boundarymask(L);
  // marks transitions from one label to another
imshow(imoverlay(A,BW,'cyan'),
                 'InitialMagnification',67);
  //overlays boundary mask on original image
        in cyan
```



https://www.mathworks.com/help/images/ref/superpixels.html