


COB LED STRIP



Specifications



Model No.	S5000-784-DRGBXK-V24-W20-P10
LED Type	COB
LED Qty(pcs/m)	784 pcs/m
IC	WS2814
Pixel Qty(pcs/m)	14PCS
Color	/
CCT	DigitalRGB+6500K RGB+4000K RGB+3000K
Ra	90
Work Voltage	24V DC
Peak Power (w/m)	20W/M
Power Per Roll (5 meters)	100W
SDCM	3

Lumen (Lm)	1200-1300lm
Cutting Unit	71.4mm (24V)
Adhesive Tape	3M 9495LE 300MP
PCB Type/Color	2 oz , White PCB
Dimension:	5000*10mm
Package	5m/bag
Max Run Length	5m
IP Grade	IP20/IP67
Warranty	3 Years
Certification	UL CE RoHS
Ta	-25~40°C; Tc: 75°C (max)

Remark: data with 15% tolerance

Typical Color

Digital RGB+6500K	
Digital RGB+4000K	
Digital RGB+3000K	

CCT Available :

NOTES: More customized colors, please contact our sales .

Packing Information

Standard Packing Per Bag

5 meters/reel, 1 reel/anti-static bag

G.W. : Non-waterproof-0.126KG

Standard Packing Per Outer Carton

outer carton size: 59*39*23cm 100rolls 500 m

G.W of Carton: 14.6 kg

Volume of Carton: 0.053 m³

Remark: data with 10% tolerance

Precautions

*Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.

*Do not fold it in case any damage of LED beads.

*Risk of electric shock, installation MUST be operated by a well-qualified electrician, if the LED strip is damaged, the product must be replaced.

*Make sure the supply voltage meets the requirements and the circuit is installed correctly before power supply.

*Make sure the electric connection reliable and be well protected.

*Cut off the power before operating the product.

*Forbidden to use in water.

NOTES

1. COXO LED Strip maintains a tester tolerance of $\pm 5\%$ on Color Temperature and Lumen, tolerance of ± 3 on CRI-Ra

2. The test is based on the COXO's laboratory and testing equipment.

3. We reserve the right to modify and improve the design of our fixtures without prior notice.

SHENZHEN COXO TECHNOLOGY

www.coxotech.com

info@coxotech.com