Oracle

サブクエリ

```
select * from BOARD
where id > (select id
from BOARD where writer = 'tester1');
```

DBにあるBOARDテーブルを使ってwriterがtester1のid列を呼び出すサブクエリをつくる。

```
ORA-01427: 단일 행 하위 질의에 2개 이상의 행이 리턴되었습니다.
01427, 00000 - "single-row subquery returns more than one row"
*Cause:
*Action:
```

エラーを確認すると、単一行演算子を使用しているがサブクエリは複数行の値だ。

```
select * from BOARD
where id in (select id
                from BOARD where writer = 'tester1');
```

それで複数演算子に変えると

	ID	MEMBER_ID	TITLE	CONTENT	VIEW_CNT	CREATED_DATE	MODIFIED_DATE	WRITER
1	3	1	サンプル投稿 01	サンプル投稿 内容 01	0	26/03/28	(null)	tester1
2	4	1	サンプル投稿 01	サンプル投稿 内容zzzzz	0	26/03/28	26/04/03	tester1

値が表示される。

複数演算子

サブクエリの結果

ANY, SOME

```
select * from BOARD
where writer = ANY (select writer from BOARD where member_id = 1);
```

サブクエリの結果について、一つでも条件に当てると、条件式がtrueになる。

ALL

```
select * from BOARD
where id > ALL (select id from BOARD where member_id = 1);
```

ALLは結果について、すべての条件を見て、全部正しいとtrueになる。

	ID	MEMB...	TITLE	CONTENT	VIEW_...	CREAT...	MODIF...	WRITER

	ID
82	89
83	90
84	91
85	92
86	93
87	94
88	95
89	96
90	97
91	98
92	99
93	...
94	...
95	...
96	

```
select id from BOARD where member_id = 1;
```

サブクエリを実行するとIDがない場合もあるので、結果は何もない。

Fromに使う

```
select * from (select * from BOARD where member_id = 1) m1,
        (select * from BOARD where writer = 'tester1') w1
where m1.id = w1.id;
```

Fromに使用するサブクエリはInlineViewである。

Fromの次に作れる。

```
WITH m1 as(select * from BOARD where member_id = 1),
     w1 as(select * from BOARD where writer = 'tester1')
select * from m1, w1 where m1.id = w1.id;
```

WITHはFromにサブクエリが多くなることを考えて、先にサブクエリをつくることである。