

Type of Submission: Article

Title: IBM Case Manager

Subtitle: Add documents with an Entry Template using ICM 5.2. Pass properties into the Entry Template and add the committed document into the current Case.

Keywords: icm, entry template, add document

Author: Dave Ward

Job Title: Solution Architect

Email: dave.ward@insight2value.co.uk

Company: Insight 2 Value, IBM Business Partner based in the UK

Abstract: This article builds upon an excellent article found here (https://www.ibm.com/developerworks/community/blogs/e8206aad-10e2-4c49-b00c-fee572815374/entry/learn_how_to_customize_your_case_manager_client_using_scripts?lang=en)

and expands upon it to deliver the following:

- Adding menus to the Case Info widget.
- Use of Script Actions.
- Use of the Properties Controller Manager to get the most up to date property values.
- Use of ICN API to invoke an Entry Template.
- Pass values from the current ICM case / work object into the Entry Template.
- Make Entry Template property fields read-only (meaning the user cannot amend a value that has been passed into the Entry Template from the corresponding Case property).
- Add the document back into the current Case.

Pre-Requisites

Open Case Builder.
Create a new solution / Edit an existing solution.
Create a Role.
Create a Case Type / Task / etc.
Create some test cases / work items.

Create Entry Template

Create an Entry Template that contains at least one “Editable” field.

Workplace XT: Entry Template Designer - Mozilla Firefox

ecmdemo1.ecm.ibm.local:9080/WorkplaceXT/wizards/WcmEntryDesigner.jsp?windowId=_1.T144884180a58&eventTarget=WcmWi

P8Admin | Monday, March 3, 2014

Help | Close

Modify Entry Template

Modify Template

- 1. Select Folder
- 2. Set Properties**
- 3. Set Security
- Define Workflow
- 4. Select Workflow
- 5. Set Properties
- Define Declare Records
- 6. Set Declare Records
- Save Template
- 7. Set Properties
- 8. Set Security

Class:

Order Class properties

Required	Property	Default Value	Access Level
<input checked="" type="checkbox"/>	Document Title	<input type="text"/>	Editable
<input type="checkbox"/>	CaseID	<input type="text"/>	Editable
<input type="checkbox"/>	Customer ID	<input type="text"/>	Editable

Compound Document

* Compound Document:

Options

Add as major version:

Auto classify the content:

Allow duplicate file names:

Entry template setting:

☒ Show Set Properties step ☐ Hide Set Properties step

☒ Yes, use entry template for checkin.

Summary:

Object Store: CMTOS

Folder: KYC


Previous Next Finish

You need to get the Version Series Id of this Entry Template as it will be used in the JavaScript throughout this example.


Work Details Integration

Create the Work Details menu event action

Open Case Builder.
Edit your solution.
Click on the “Pages” tab.
Expand the “Work Details Pages” group.
Open the “Work Details” page.



On the Case Information widget, click the “Edit Settings” icon.




Click the “Toolbars” tab.

Make sure “Documents view” is selected in the “Toolbar for:” list.

Select the existing “Add” row in the Grid.

Click the “Add Menu Item” toolbar button.



Create a new toolbar item similar to the following:

Case Information








Settings

Menus

Toolbars

Toolbar for:

Documents view

Action:

Script Action

Alignment:

Left

Label:

Add Document from Entry Template

Execute:

OK

Cancel

In the “Execute:” box, paste the following code:

NOTE: You need to add the vsld of your Entry Template to line 9 of the script (the line beginning "`var entryTemplateId =`")

NOTE: You need to add the Id of your Entry Template property to line 53 of the script (the line beginning `"var etPropId ="`)

NOTE: You need to add the Id of your Work Item property to line 54 of the script (the line beginning `"var modelPropId ="`)

```

try {
    var ScriptAdaptorScope = this;

    /*Get the currently selected folder in the Case Info widget*/
    var currentFolder = this.getActionContext().CurrentFolder[0];

    /*The vsId of the Entry Template*/
    /*===== NOTE - CHANGE THIS LINE TO THE VSID OF YOUR ENTRY TEMPLATE =====*/
    var entryTemplateId = "{D4DFCDA1-C9DC-4240-A197-B3036CFFDDDD6}";
    /*===== NOTE - CHANGE THIS LINE TO THE VSID OF YOUR ENTRY TEMPLATE =====*/

    var repositoryId = this.getWidget().getSolution().getTargetOS().id;

    /*Get the Work Item Editable*/
    var myWorkItemEditable = this.getWidget().model.payload.workItemEditable;

    require([
        "dojo/_base/declare",
        "dojo/_base/lang",
        "ecm/widget/dialog/AddContentItemDialog"
    ], function(
        declare,
        lang,
        AddContentItemDialog
    )
    {
        /*Get Repository*/
        var repository = ecm.model.desktop.getRepository(repositoryId);

        /*Retrieve the Entry Template*/
        repository.retrieveItem(entryTemplateId, function(item) {
            /*Check the MIME Type to make sure it is an Entry Template*/
            if (item && item.mimetype) {
                switch (item.mimetype) {
                    case "application/x-filenet-documententrytemplate":
                    case "application/x-filenet-folderentrytemplate":
                    case "application/x-filenet-entrytemplate":
                    case "application/x-filenet-customobjectentrytemplate":
                    case "application/x-filenet-declarerecordentrytemplate":

                        /*Get Entry Template*/
                        var entryTemplate = repository.getEntryTemplateById(item.id,
item.name, item.objectStore);

                        /*Retrieve Entry Template Handler*/
                        var entryTemplateRetrievedHandler = lang.hitch(this,

function(entryTemplate) {

```

```

/*Create AddContentItemDialog*/
var myDialog = new AddContentItemDialog();

if (entryTemplate) {

    /*===== NOTE - CHANGE THIS SECTION TO REFLECT THE ENTRY
TEMPLATE FIELD ID AND THE CORRESPONDING CASE PROPERTY =====*/
    var etPropId = "Customer_ID";
    var modelPropId = "Customer_ID";
    var modelCurrentValue;
    /*===== NOTE - CHANGE THIS SECTION TO REFLECT THE ENTRY
TEMPLATE FIELD ID AND THE CORRESPONDING CASE PROPERTY =====*/

    /*Get the current values in the work item or case to pass
into the Entry Template*/

    require(["icm/model/properties/controller/ControllerManager"], function(ControllerManager){
        /*Retrieve prop value using property controller API*/
        var theController =
ControllerManager.bind(myWorkItemEditable);
        var propController =
theController.getPropertyController(modelPropId);
        modelCurrentValue = propController.get("value");
        /*Unbind is necessary to prevent mem leak.*/
        ControllerManager.unbind(myWorkItemEditable);

        /*Set the values in the Entry Template*/
        setDefaultValue
(entryTemplate,etPropId,modelCurrentValue, true);

        var folder = entryTemplate.folder;
        if (folder && !folder.hasPrivilege("privAddToFolder")
&& !entryTemplate.allowUserSelectFolder) {
            var message =
ecm.model.Message.createErrorMessage("entry_template_folder_restricted_error", [
                entryTemplate.name,
                folder.name
            ]);
            if (message) {
                ecm.model.desktop.addMessage(message);
            }
        } else {
            myDialog.show(
                repository,
                null,
                (entryTemplate.type ==
ecm.model.EntryTemplate.TYPE.DOCUMENT),
                false,
                function(newItem) {
                    try {
                        /*Add new content item / document to
the current case root/sub folder*/
                        currentFolder.addToFolder(newItem,
function() {
                            console.log('Document added to
folder');
                        });
                    } catch (Error) {
                        alert ("Oops! Error in callback");
                    }
                },
                null,
                true,
                entryTemplate);
        }
    });

}

});

if (!entryTemplate.isRetrieved) {

entryTemplate.retrieveEntryTemplate(entryTemplateRetrievedHandler, false, false);
    } else {
        entryTemplateRetrievedHandler(entryTemplate);
    }
    break;
}

},
"EntryTemplate",

```

```

        "current",
        entryTemplateId);
    });
}
catch (Error) {
    alert ("Source Module: " + ScriptAdaptorScope.arguments.label + " Script
Adaptor\r\n\r\n"+Error.name+" - "+Error.description+"\r\n"+Error.message);
}

function setDefaultValue (entryTemp,propIdName,propDefaultValue,makeReadOnly) {
    try {
        var i;
        var len;

        if (entryTemp) {
            len = entryTemp.propertiesOptions.length;


            for(i=0; i<len; i++) {
                if (entryTemp.propertiesOptions[i].id == propIdName) {
                    entryTemp.propertiesOptions[i].defaultValue = [propDefaultValue];
                    if (makeReadOnly) {
                        /*Make the field read only*/
                        entryTemp.propertiesOptions[i].readOnly = true;
                    }
                    break;
                }
            }
        }

    }

    catch (Error) {
        alert ("Source Module: " + ScriptAdaptorScope.arguments.label + " Script Adaptor -
setDefaultValue Function\r\n\r\n"+Error.name+" - "+Error.description+"\r\n"+Error.message);
    }
}


```

Click “OK” to add the menu item.



The new toolbar item will be visible in the “Toolbar for: Documents View” list.


Click “OK” to close the Case Information settings dialog.



In the Page Designer, Click “Save” and then “Close”.

In your Solution click “Save and Close”.

In the Case Builder home page, “Deploy” your solution.




Test the Script


Open the Work Details page

Make a change to the Customer ID field (or whatever the field was called in your solution) in the Properties widget.

In the Case Info widget, click “Add” → “Add Document from Entry Template”




The Entry Template is displayed. The Customer_ID value has been passed from the Work Item into the Entry Template and the field has been made read-only.




Browse to a suitable file name and select it.

Add a suitable Document Title to the Entry Template.

Click the “Add” button.



The document has been added to the Case folder / sub-folder that was selected in the Case Information widget when the Entry template was invoked.



Case Details Integration

You can achieve the same results in the Case Details page with one slight amendment. Use this JavaScript instead, which references the current case properties and not the current work item properties.

In the "Execute:" box, paste the following code:

NOTE: You need to add the vsId of your Entry Template to line 9 of the script (the line beginning "var entryTemplateId =")

NOTE: You need to add the Id of your Entry Template property to line 53 of the script (the line beginning "var etPropId =")

NOTE: You need to add the Id of your Work Item property to line 55 of the script (the line beginning "var modelPropId =")

```
try {
    var ScriptAdaptorScope = this;

    /*Get the currently selected folder*/
    var currentFolder = this.getActionContext().CurrentFolder[0];

    /*The vsId of the Entry Template*/
    /*===== NOTE - CHANGE THIS LINE TO THE VSID OF YOUR ENTRY TEMPLATE =====*/
    var entryTemplateId = "{D4DFCDA1-C9DC-4240-A197-B3036CFFDDD6}";
    /*===== NOTE - CHANGE THIS LINE TO THE VSID OF YOUR ENTRY TEMPLATE =====*/

    var repositoryId = this.getWidget().getSolution().getTargetOS().id;

    /*Get current Case*/
    var currentCase = this.getActionContext().Case[0];

    require([
        "dojo/_base/declare",
        "dojo/_base/lang",
        "ecm/widget/dialog/AddContentItemDialog"
    ], function(
        declare,
        lang,
        AddContentItemDialog
    ) {
        {
            /*Get Repository*/
            var repository = ecm.model.desktop.getRepository(repositoryId);

            /*Retrieve the Entry Template*/
            repository.retrieveItem(entryTemplateId, function(item) {
                /*Check the MIME Type to make sure it is an Entry Template*/
                if (item && item.mimetype) {
                    switch (item.mimetype) {
                        case "application/x-filenet-documententrytemplate":
                        case "application/x-filenet-folderentrytemplate":
                        case "application/x-filenet-entrytemplate":
                        case "application/x-filenet-customobjectentrytemplate":
```



```

        case "application/x-filenet-declarerecordentrytemplate":

            /*Get Entry Template*/
            var entryTemplate = repository.getEntryTemplateById(item.id,
item.name, item.objectStore);

            /*Retrieve Entry Template Handler*/
            var entryTemplateRetrievedHandler = lang.hitch(this,

function(entryTemplate) {

                /*Create AddContentItemDialog*/
                var myDialog = new AddContentItemDialog();

                if (entryTemplate) {

                    /*===== NOTE - CHANGE THIS SECTION TO REFLECT THE ENTRY
TEMPLATE FIELD ID AND THE CORRESPONDING CASE PROPERTY =====*/
                    var etPropId = "Customer_ID";
                    var modelPropId = "Customer_ID";
                    var modelCurrentValue;
                    /*===== NOTE - CHANGE THIS SECTION TO REFLECT THE ENTRY
TEMPLATE FIELD ID AND THE CORRESPONDING CASE PROPERTY =====*/

                    /*Get the current values in the work item or case to pass
into the Entry Template*/

                    require(["icm/model/properties/controller/ControllerManager"], function(ControllerManager) {
                        /*Retrieve prop value using property controller API*/
                        var theController =

ControllerManager.bind(currentCase);

                        var propController =
theController.getPropertyController(modelPropId);
                        modelCurrentValue = propController.get("value");
                        /*Unbind is necessary to prevent mem leak.*/
                        ControllerManager.unbind(currentCase);

                        /*Set the values in the Entry Template*/
                        setDefaultValue
(entryTemplate,etPropId,modelCurrentValue, true);

                        var folder = entryTemplate.folder;
                        if (folder && !folder.hasPrivilege("privAddToFolder")
&& !entryTemplate.allowUserSelectFolder) {
                            var message =
ecm.model.Message.createErrorMessage("entry_template_folder_restricted_error", [
                                entryTemplate.name,
                                folder.name
                            ]);
                            if (message) {
                                ecm.model.desktop.addMessage(message);
                            }
                        } else {
                            myDialog.show(
                                repository,
                                null,
                                (entryTemplate.type ==

ecm.model.EntryTemplate.TYPE.DOCUMENT),

                                false,
                                function(newItem) {
                                    try {
                                        /*Add new content item / document to
the current case root/sub folder*/

                                        currentFolder.addToFolder(newItem,

function() {

                                            console.log('Document added to
folder');

                                        });
                                    }
                                    catch (Error) {
                                        alert ("Oops! Error in callback");
                                    }
                                },
                                null,
                                true,
                                entryTemplate);
                        }
                    });
                }
            });
            if (!entryTemplate.isRetrieved) {

entryTemplate.retrieveEntryTemplate(entryTemplateRetrievedHandler, false, false);
            } else {

```

```

        entryTemplateRetrievedHandler(entryTemplate);
    }
    break;
}
    }
},
"EntryTemplate",
"current",
entryTemplateId);
});
}
catch (Error) {
    alert ("Source Module: "+ ScriptAdaptorScope.arguments.label +" Script
Adaptor\r\n\r\n"+Error.name+" - "+Error.description+"\r\n"+Error.message);
}

function setDefaultValue (entryTemp,propIdName,propDefaultValue,makeReadOnly) {
    try {
        var i;
        var len;

        if (entryTemp) {
            len = entryTemp.propertiesOptions.length;

            for(i=0; i<len; i++) {
                if (entryTemp.propertiesOptions[i].id == propIdName) {
                    entryTemp.propertiesOptions[i].defaultValue = [propDefaultValue];
                    if (makeReadOnly) {
                        /*Make the field read only*/
                        entryTemp.propertiesOptions[i].readOnly = true;
                    }
                    break;
                }
            }
        }
    }

    catch (Error) {
        alert ("Source Module: "+ ScriptAdaptorScope.arguments.label +" Script Adaptor -
setDefaultValue Function\r\n\r\n"+Error.name+" - "+Error.description+"\r\n"+Error.message);
    }
}
}

```