

ID: 311151138  
Name: Gilad Deutch

## 1 Question 1

### 1.3

Time (in seconds) to complete standard training: 1381.1138.

Time (in seconds) to complete free adversarial training: 386.9370.

### 1.4

Model/Task	Accuracy	PGD Success rate
Standard	0.9168	0.9025
Adv.-trained	0.8225	0.3695

Adversarial training significantly decreases the PGD success rate, i.e. increases robustness with the price of a some (around 10%) decrease in accuracy.


### 1.5

m/metric	Time	Accuracy	PGD Success rate
4	383.8422	0.8077	0.3808
5	323.3860	0.7900	0.3828
6	276.1508	0.7713	0.3963
7	258.2459	0.7460	0.4073

It seems that both the benign accuracy, robustness and training time decrease as m increases.

## 2 Question 2

### 2.2



Let us recall the equation that we've seen in class:

$$R = \sigma \Phi^{-1}(p_c)$$

where  $R$  is the radius,  $\sigma$  is the standard deviation of the Gaussian noise,  $\Phi^{-1}$  is the inverse of the CDF of the Gaussian distribution and  $p_c$  is the confidence level of class  $c$ .

Note that there are two competing factors here: sigma multiplies the value of  $R$ , hence as  $\sigma$  grows larger  $R$  grows larger. On the other hand, as  $\sigma$  grows larger, the Gaussian distribution becomes more spread out, this means that the probability of two predictions having the same maximum class decreases, hence  $p_c$  decreases, which in turn decreases  $\Phi^{-1}(p_c)$ .

It seems that in the range of  $\sigma$  that we've tested, the lower value of  $\sigma$ , i.e.  $\sigma = 0.05$  has higher accuracy for a given radius, i.e. a larger number of samples with radii bigger than the radius. This means that the second factor we described dominates.

## 3 Question 3


### 3.2

Model 1 is backdoored, the backdoor forces it to output class 0.

### 3.3

#### 3.3.1

mask:



trigger:



#### 3.3.2

Yes. The accuracy of Model 1 is only very slightly lower than that of Model 2 (0.9107 vs 0.9168).

#### 3.3.3

Very successful, its success rate is 0.9980.