

Apply filters to SQL queries

Project description

My organization is working to make their system more secure. It is my job to ensure the system is safe, investigates all potential security issues, and updates employee computers as needed. The following steps provide examples of how I used SQL with filters to perform security-related tasks.

Retrieve after hours failed login attempts

The Purpose: Extract rows based on specific time values or ranges, using the AND operator.

The query below shows how to retrieve all the data from the 'log_in_attempts' table, and filter only unsuccessful login(can be seen as 0) attempts after 18:00.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE login_time > '18:00' AND success = 0;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
52	cjackson	2022-05-10	22:07:07	CAN	192.168.58.57	0
69	wjaffrey	2022-05-11	19:55:15	USA	192.168.100.17	0
82	abernard	2022-05-12	23:38:46	MEX	192.168.234.49	0
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
96	ivelasco	2022-05-09	22:36:36	CAN	192.168.84.194	0
104	asundara	2022-05-11	18:38:07	US	192.168.96.200	0
107	bisles	2022-05-12	20:25:57	USA	192.168.116.187	0
111	aestrada	2022-05-10	22:00:26	MEXICO	192.168.76.27	0
127	abellmas	2022-05-09	21:20:51	CANADA	192.168.70.122	0
131	bisles	2022-05-09	20:03:55	US	192.168.113.171	0
155	cgriffin	2022-05-12	22:18:42	USA	192.168.236.176	0
160	jclark	2022-05-10	20:49:00	CANADA	192.168.214.49	0
199	yappiah	2022-05-11	19:34:48	MEXICO	192.168.44.232	0

19 rows in set (0.001 sec)

Retrieve login attempts on specific dates

Purpose: Extract rows based on specific date values or ranges, using the OR operator.

The query below shows how to retrieve all the data from the 'log_in_attempts' table, and filter the login_date to 2022/05/08/09.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE login_date = '2022-05-08' OR login_date = '2022-05-09';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
24	arusso	2022-05-09	06:49:39	MEXICO	192.168.171.192	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1

Retrieve login attempts outside of Mexico

Purpose: The LIKE operator allows you to find rows where text or character data matches a specific pattern.

The query below shows how to retrieve all the data from the 'log_in_attempts' table, and remove any result from the country column that starts with 'MEX'.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0

Retrieve employees in Marketing

Purpose: Using the AND operator at the same time to use two filters at the same time.

The query below shows how to retrieve all the data from the “employees” table, shows only the marketing department, and offices that start with ‘EAST’.

```
MariaDB [organization]> SELECT *
-> FROM employees
-> WHERE department LIKE 'marketing'
-> AND office LIKE 'EAST%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

7 rows in set (0.001 sec)

Retrieve employees in Finance or Sales

Purpose: Use the OR operator to use only one of two filters for the same column.

The query below shows how to retrieve all the data from the ‘employees’ table, and shows only the Finance and Sales departments

```
MariaDB [organization]> SELECT *
-> FROM employees
-> WHERE department LIKE 'Finance'
-> OR department LIKE 'Sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109

Retrieve all employees not in IT

Purpose: Use the NOT operator to clean the output of certain data.

The query below shows how to retrieve all the data from the employees' table, apart from data related to the information technology department.

```
MariaDB [organization]> SELECT *  
-> FROM employees  
-> WHERE department NOT LIKE 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127

Summary

I applied filters to SQL queries to get specific information on login attempts and employee machines. I used two different tables, log_in_attempts and employees. I used the AND, OR, and NOT operators to filter for the specific information needed for each task. I also used LIKE and the percentage sign (%) wildcard to filter for patterns.