

Basic Mobile UI Test

I can imagine the first thing you will want to do is to write a very simple and basic test - to heat up the engines. This page will guide you through the code:

```
1 @Execution(ExecutionMode.CONCURRENT)
```

▼ Click here to expand...

This line tells the JUnit engine that the tests in this class were designed to run one after the other, without paralleling. Note! In order use JUnit parallel mechanism, there is a property file named [junit-platform.properties](#) located at `src/test/resources` folder

```
1 public class BasicMobileExampleTests extends BaseTest {
```

▼ Click here to expand...

We extend the class `BaseTest`. `BaseTest` is a class that was created in the examples repo. It mainly holds the annotations and keeps this code clean.

```
1 @DriverUrl
2 private URL url = new URL("http://127.0.0.1:4723/wd/hub/");
```

▼ Click here to expand...

There are 3 main annotations you will need to be familiar with in order to get your driver up without any issues: `@DriverCapabilities`, `@DriverUrl`, and `@DriverCommandExecutor`.

The `@DriverUrl` tells the `VeriSoftDriver` where to find the url to use when starting up. We use dependency injection for injecting the `WebDriver` directly into the test. More on our dependency injection mechanism for the driver can be found [here](#). Note the `/wd/hub` at the end.

```
1 @DriverCapabilities
2 private DesiredCapabilities capabilities = new DesiredCapabilities();
```

▼ Click here to expand...

The `@DriverCapabilities` tells the `VeriSoftDriver` where to find the `DesiredCapabilities` to use when starting up. We use dependency injection for injecting the `WebDriver` directly into the test.

```
1 @Test
2 @DisplayName("Click On Element")
```

▼ Click here to expand...

Both lines are JUnit lines. The `@DisplayName` line is very important since if you use this annotation, then most of the report mechanisms will use it as the test name, rather than the method name.

```
1 public void clickOnElement(VerisoftMobileDriver driver) {
```

▼ Click here to expand...

We use a dependency injection mechanism, which takes the `@DriverCapabilities`, `@DriverUrl`, and `@DriverCommandExecutor` (if present) and creates an instance of `VerisoftDriver`. The `VerisoftDriver` object is an instance of `WebDriver` and follows its interfaces and more. More about the `VeriSoftDriver` and `VerisoftMobileDriver` can be found [here](#).

```
1 // Note!! Verisoft Assert
2 String phrase = "No thanks";
```

```
3 Asserts.assertTrue(e.getText().contains(phrase), "Page should contain the phrase: " + phrase);
```

▼ Click here to expand...

Asserts in the Verisoft framework do pretty much the same as regular asserts. The difference here is that we log the message to the various logging and reporting mechanisms that are listening to our Observer Report mechanism. More about the Report in the following line. You may choose to use a different Assert mechanism (and there are plenty of those in Java, but you will lose this nice logging feature.

```
1 Report.info("Got to this point - We are operating Google chrome on mobile deviceS");
```

▼ Click here to expand...

There are many places we want to write reports to - logging, report mechanism, perhaps a global logging system like Splunk, Jira,, etc. If we would write a line of code for each of the mechanisms we support, we would have more logging lines of code than actual code. So, we use the Observer pattern and use one single Report object to write to all of them. More about the Report object [here](#).

Well, that's it! We made it through a basic web UI test. Here is the complete code, and you can also [view it on Bitbucket](#)

```
1 @Execution(ExecutionMode.SAME_THREAD)
2 public class BasicMobileExampleTests extends BaseTest {
3
4     @DriverUrl
5     private URL url = new URL("http://127.0.0.1:4723/wd/hub/");
6
7     @DriverCapabilities
8     private DesiredCapabilities capabilities = new DesiredCapabilities();
9
10    {
11        capabilities.setCapability(MobileCapabilityType.PLATFORM_NAME, "Android");
12        capabilities.setCapability("appPackage", "com.android.chrome");
13        capabilities.setCapability("appActivity",
14                                "com.google.android.apps.chrome.Main");
15        capabilities.setCapability("automationName", "UIAutomator2");
16    }
17
18
19    public BasicMobileExampleTests() throws MalformedURLException {
20    }
21
22
23    @Test
24    @DisplayName("Click On Element")
25    public void clickOnElement(VerisoftMobileDriver driver) {
26
27        driver.findElement(By.id("com.android.chrome:id/terms_accept")).click();
28        WebElement e =
29            Waits.visibilityOfElementLocated(driver, 30,
30                                           By.id("com.android.chrome:id/negative_button"));
31
32        // Note!! Verisoft Assert
33        String phrase = "No thanks";
34        Asserts.assertTrue(e.getText().contains(phrase),
35                            "Page should contain the phrase: " + phrase);
36
37        Report.info("Got to this point - We are operating Google chrome on mobile");
38    }
```

