

# Software Architectures

## Distributed Systems

# Software Architectures to Handle Complexity

## Distributed systems are complex

- In order to manage their intrinsic complexity, distributed systems should be properly organised
- Organisation of a distributed system is mostly expressed in terms of its software components

## Software architectures expresses component organisation

- Many ways to organise components of a distributed system, classified as *software architectures*
- Many instantiations where components have their actual placed in a distributed system—often called *system architectures*

# Architectural Style

## An architectural style is formulated in terms of...

- components
- the way in which components are connected to each other
- the data flowing through the components
- the way in which all the above things are configured altogether to build the system

## The notion of architectural style...

- encompasses a way to cluster and classify groups of similar systems, that is, having the same sort of organisation
- allow distributed systems to be compared
- but also provide general patterns for their overall design

# Components & Connectors I

## Components

- A component is a modular unit with well-defined *interfaces*
- which is *replaceable* within its environment
- interfaces are both *required* and *provided*—both ways, then

## Connectors

- A connector is an abstraction *mediating* communication, coordination, cooperation among components
- that is, anything providing a *mechanism for interaction* among components

# Components & Connectors II

## Putting together components and connectors

- ... produces a huge range of possible organisations and configurations
- that are then classified in terms of architectural styles

# Architectural Styles for Distributed Systems

## Identification of architectural styles

- **Architectural styles** – like patterns in software engineering – are to be *devised out* rather than invented
- Today, four different architectural styles have been identified as the main ones for distributed systems

## The main architectural styles for distributed systems

- *Layered* architectures
- *Object-based* architectures
- *Data-centered* architectures
- *Event-based* architectures

# Layered Architectures


## Basic idea

- Components are organised in a *layered fashion*
- where components of a layer *only* call components of the layer below, and are *only* called by the components of the layer above

## Data flow

- The request-response flow is always top-down / bottom-up
- Control flow follow the same pattern along with data

# Layered Architecture Style





# Object-based Architectures

## Basic idea

- Components are objects
- Components are connected through a RPC mechanism


## Client-server architectures

- ... are built out of this style

## Layered and object-based architectures

- are the most important styles for distributed systems today
- However, a lot of things are going to happen in the future, which may change such an overall picture

# Object-based Architecture Style



# Data-centred Architectures I

## Basic idea

- Communication among processes occurs through a shared repository
- The repository might be either passive (reactive) or (pro)active

## Main features

- ... depends on the choice made for the shared repository
- how information is represented
- how events are handled
- how the shared repository behave in response to interaction
- how processes interact with / through the shared repository

# Data-centred Architectures II

## Examples are everywhere

- Web-based systems, for instance, are largely data-centric
- Also, many distributed applications still work by sharing files around the network

# Event-based Architectures

## Basic idea

- Processes communicate through an event bus
- through which events are propagated
- possibly carrying data along


## Main example: Publish / subscribe systems

- Publishers publish events through the middleware
- Subscribers receive events to which they have subscribed

## Main feature

- Processes can communicate with no need of reference each other / to know each other, they are *referentially decoupled*
- Processes can communicate with no need to share the same space, they are *decoupled in space*

# Event-based Architecture Style



# Shared Data-space Architectures I


## Basic idea

- Putting together Data-centric and Event-based architectures
- The shared repository is a shared persistent data-space, and also an event bus
- where data is stored and accessed
- along with related events

## Main example: Blackboard systems

- Processes put data in the blackboard
- The blackboard aggregates knowledge, implements policies and drive the coordination of processes

# Shared Data-space Architecture Style





# Architectural Styles for Distributed Systems

## Identification of architectural styles

- *Architectural styles* – like patterns in software engineering – are to be *devised out* rather than invented
- Today, four different architectural styles have been identified as the main ones for distributed systems

## The main architectural styles for distributed systems

- *Layered* architectures
- *Object-based* architectures
- *Data-centered* architectures
- *Event-based* architectures



# Clients & Servers

## Main feature

- In a centralised architecture, *clients* request *services* from *servers*—and that is all, more or less
- In the basic client-server model, processes are classified in two groups—obviously, clients and servers
- Possibly, the two groups may overlap


## Servers

A server is a process implementing a specific service—like, say, a database service

## Clients


A client is a process requiring a specific service from a server

# Client-server Interaction



Scheme of client-server interaction: *request-reply behaviour*

# Example: Internet Search Engine



The simplified organisation of an Internet search engine into three different layers

# References I



Ozalp Babaoglu, Márk Jelasity, Alberto Montresor, Christof Fetzer, Stefano Leonardi, Aad van Moorsel, and Maarten van Steen, editors. *Self-star Properties in Complex Information Systems: Conceptual and Practical Foundations*, volume 3460 of *Lecture Notes in Computer Science*.

Springer, 2005.



Jeffrey O. Kephart and David M. Chess.

The vision of autonomic computing.

*IEEE Computer*, 36(1):41–50, January 2003.



Philip K. McKinley, Seyed Masoud Sadjadi, Eric P. Kasten, and Betty H.C. Cheng.

Composing adaptive software.

*IEEE Computer*, 37(7):56–64, 2004.



## References II



Andrew S. Tanenbaum and Marteen van Steen.

*Distributed Systems. Principles and Paradigms.*

Pearson Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2007.