Virtual memory - Paging

Johan Montelius

KTH

2019

The process



Memory layout for a 32-bit Linux process

Segments - a could be solution

Processes in virtual space

Address translation by MMU
(base and bounds)

Physical memory

Segments - a could be solution

Processes in virtual space

Address translation by MMU
(base and bounds)

Physical memory

Segments - a could be solution

Processes in virtual space

Address translation by MMU
(base and bounds)

Physical memory

Segments - a could be solution



Segments - a could be solution



Segments - a could be solution



Segments - a could be solution



Segments - a could be solution



Segments - a could be solution

Processes in virtual space

Address translation by MMU
(base and bounds)

Physical memory

Segments - a could be solution



Segments - a could be solution



Segments - a could be solution



Segments - a could be solution



Segments - a could be solution



Segments - a could be solution

Processes in virtual space



Address translation by MMU
(base and bounds)

Physical memory

one problem



Physical memory

one problem



Physical memory

External fragmentation: free areas of free space that is hard to utilize.

one problem



Physical memory

External fragmentation: free areas of free space that is hard to utilize.

Solution: allocate larger segments ...

one problem



Physical memory

External fragmentation: free areas of free space that is hard to utilize.

Solution: allocate larger segments ... internal fragmentation.

another problem



another problem



another problem



another problem



another problem



another problem



another problem



We're reserving physical memory that is not used.



Let's try again

Let's try again

It's easier to handle fixed size memory blocks.

Let's try again

It's easier to handle fixed size memory blocks.

Can we map a process virtual space to a set of equal size blocks?

Let's try again

It's easier to handle fixed size memory blocks.

Can we map a process virtual space to a set of equal size blocks?

An address is interpreted as a *virtual page number* (VPN) and an *offset*.

Remember the segmented MMU



The paging MMU



The paging MMU



The paging MMU



The paging MMU



The paging MMU



The paging MMU



The paging MMU



The paging MMU



the MMU



the MMU



the MMU


exception
virtual address
within bounds
Segmentation
linear address

the MMU


exception
virtual address
within bounds
Segmentation
Paging
linear address

the MMU


exception
virtual address
within bounds
Segmentation
Paging
linear address

the MMU


exception
virtual address
within bounds
Segmentation
Paging
linear address
physical address

the MMU


virtual address
exception
within bounds
Segmentation
linear address
exception
page available
Paging
physical address

a note on the X86 architecture

The x86-32 architecture supports both segmentation and paging. A virtual address is translated to a *linear address* using a segmentation table. The linear address is then translated to a physical address by paging.

a note on the X86 architecture

The x86-32 architecture supports both segmentation and paging. A virtual address is translated to a *linear address* using a segmentation table. The linear address is then translated to a physical address by paging.

a note on the X86 architecture

The x86-32 architecture supports both segmentation and paging. A virtual address is translated to a *linear address* using a segmentation table. The linear address is then translated to a physical address by paging.

Linux and Windows do not use use segmentation to separate code, data nor stack.

a note on the X86 architecture

The x86-32 architecture supports both segmentation and paging. A virtual address is translated to a *linear address* using a segmentation table. The linear address is then translated to a physical address by paging.

Linux and Windows do not use use segmentation to separate code, data nor stack.

a note on the X86 architecture

The x86-32 architecture supports both segmentation and paging. A virtual address is translated to a *linear address* using a segmentation table. The linear address is then translated to a physical address by paging.

Linux and Windows do not use use segmentation to separate code, data nor stack.

The X86-64 (the 64-bit version of the x86 architecture) has drooped many features for segmentation.

a note on the X86 architecture

The x86-32 architecture supports both segmentation and paging. A virtual address is translated to a *linear address* using a segmentation table. The linear address is then translated to a physical address by paging.

Linux and Windows do not use use segmentation to separate code, data nor stack.

The X86-64 (the 64-bit version of the x86 architecture) has drooped many features for segmentation.

Still used to manage *thread local storage* and *CPU specific data*.

Processes in virtual space

Physical memory

Processes in virtual space



Physical memory

Processes in virtual space



Physical memory

Processes in virtual space



Physical memory


Processes in virtual space
Physical memory


Processes in virtual space
Physical memory


Processes in virtual space
Physical memory


Processes in virtual space
Physical memory


Processes in virtual space
Physical memory


Processes in virtual space
Physical memory


Processes in virtual space
Physical memory


Processes in virtual space
Physical memory


Processes in virtual space
Physical memory


Processes in virtual space
Physical memory


Processes in virtual space
Only pages actually used need to be in memory.
Physical memory

three pages



three pages

three pages



three pages



three pages


virtual space
available
not available
(page fault)
physical memory

three pages


virtual space
available
not available
(page fault)
not allocated
(segmentation fault)
physical memory

The pagetable

The MMU page module



The pagetable

The MMU page module



The page table

- provides translation from page numbers to frame numbers
- kernel or user space
- read and write access rights
- available in memory or on disk

The pagetable

The MMU page module



The page table

- provides translation from page numbers to frame numbers
- kernel or user space
- read and write access rights
- available in memory or on disk

Note: the page table is to large to fit into the MMU hardware, it is in main memory.

The page table entry

example Linux on (32bit) x86

31

The page table entry

example Linux on (32bit) x86



The page table entry

example Linux on (32bit) x86



The page table entry

example Linux on (32bit) x86



The page table entry

example Linux on (32bit) x86



If the page index is 20 bits, does the frame number need to be 20 bits?

The page table entry

example Linux on (32bit) x86



If the page index is 20 bits, does the frame number need to be 20 bits?

The page table entry

example Linux on (32bit) x86



If the page index is 20 bits, does the frame number need to be 20 bits?

The page table entry

example Linux on (32bit) x86



If the page index is 20 bits, does the frame number need to be 20 bits?

Physical Address Extension (PAE)

Physical Address Extension (PAE)

In 1995 the x86 architecture provided 24-bit frame numbers. The CPU could thus address 64 Gibyte of physical address space (24-bit frame, 12-bit offset).

Physical Address Extension (PAE)

In 1995 the x86 architecture provided 24-bit frame numbers. The CPU could thus address 64 Gibyte of physical address space (24-bit frame, 12-bit offset).

Each process still had a 32-bit virtual address space, (20-bit page number, 12-bit offset) i.e. 4 Gibyte.

Physical Address Extension (PAE)

In 1995 the x86 architecture provided 24-bit frame numbers. The CPU could thus address 64 Gibyte of physical address space (24-bit frame, 12-bit offset).

Each process still had a 32-bit virtual address space, (20-bit page number, 12-bit offset) i.e. 4 Gibyte.

The x86_64 architecture supports 48-bit virtual address space and up to 52-bit physical address space.

Physical Address Extension (PAE)

In 1995 the x86 architecture provided 24-bit frame numbers. The CPU could thus address 64 Gibyte of physical address space (24-bit frame, 12-bit offset).

Each process still had a 32-bit virtual address space, (20-bit page number, 12-bit offset) i.e. 4 Gibyte.

The x86_64 architecture supports 48-bit virtual address space and up to 52-bit physical address space.

Linux supports 48-bit virtual address (47-bit user space) and up to 46-bit physical address space (64 Tibyte). Check your address space in `/proc/cpuinfo`.

Physical Address Extension (PAE)

In 1995 the x86 architecture provided 24-bit frame numbers. The CPU could thus address 64 Gibyte of physical address space (24-bit frame, 12-bit offset).

Each process still had a 32-bit virtual address space, (20-bit page number, 12-bit offset) i.e. 4 Gibyte.

The x86_64 architecture supports 48-bit virtual address space and up to 52-bit physical address space.

Linux supports 48-bit virtual address (47-bit user space) and up to 46-bit physical address space (64 Tibyte). Check your address space in `/proc/cpuinfo`.

Physical memory is in reality limited by chipset, motherboard, memory modules etc. Check your available memory in `/proc/meminfo`.

largest server



Largest server on the market, SGI 3000, can scale up to 256 CPUs and 64 Tibyte of RAM (NUMA) - running Linux.

Speed matters

```
movl 0x11111222, %eax
```

Speed matters

- we need a page table base register, PTBR

```
movl 0x11111222, %eax
```

Speed matters

- we need a page table base register, PTBR
- the *virtual page number*, VPN, is 0x11111

```
movl 0x11111222, %eax
```

Speed matters

```
movl 0x11111222, %eax
```

- we need a page table base register, PTBR
- the *virtual page number*, VPN, is 0x11111
- read the page table entry from PTBR + (0x11111 * 8)

Speed matters

```
movl 0x11111222, %eax
```

- we need a page table base register, PTBR
- the *virtual page number*, VPN, is 0x11111
- read the page table entry from PTBR + (0x11111 * 8)
- extract *frame number* PFN from the entry

Speed matters

```
movl 0x11111222, %eax
```

- we need a page table base register, PTBR
- the *virtual page number*, VPN, is 0x11111
- read the page table entry from PTBR + (0x11111 * 8)
- extract *frame number* PFN from the entry
- the offset is 0x222

Speed matters

```
movl 0x11111222, %eax
```

- we need a page table base register, PTBR
- the *virtual page number*, VPN, is 0x11111
- read the page table entry from PTBR + (0x11111 * 8)
- extract *frame number* PFN from the entry
- the offset is 0x222
- read the memory location at (PFN << 12) + 0x222

Speed matters

```
movl 0x11111222, %eax
```

- we need a page table base register, PTBR
- the *virtual page number*, VPN, is 0x11111
- read the page table entry from PTBR + (0x11111 * 8)
- extract *frame number* PFN from the entry
- the offset is 0x222
- read the memory location at (PFN << 12) + 0x222

Speed matters

```
movl 0x11111222, %eax
```

- we need a page table base register, PTBR
- the *virtual page number*, VPN, is 0x11111
- read the page table entry from PTBR + (0x11111 * 8)
- extract *frame number* PFN from the entry
- the offset is 0x222
- read the memory location at (PFN << 12) + 0x222

An extra memory operation for each memory reference.

TLB: hardware support

The CPU keeps a *translation look-aside buffer*, TLB, with the most recent page table entries.

TLB: hardware support

The CPU keeps a *translation look-aside buffer*, TLB, with the most recent page table entries.

The buffer is implemented using a *content-addressable memory* keyed by the *virtual page number*.

TLB: hardware support

The CPU keeps a *translation look-aside buffer*, TLB, with the most recent page table entries.

The buffer is implemented using a *content-addressable memory* keyed by the *virtual page number*.

If the page table entry is found - great!

TLB: hardware support

The CPU keeps a *translation look-aside buffer*, TLB, with the most recent page table entries.

The buffer is implemented using a *content-addressable memory* keyed by the *virtual page number*.

If the page table entry is found - great!

If the page table entry is not found - access the real page table in memory.

TLB: hardware support

The CPU keeps a *translation look-aside buffer*, TLB, with the most recent page table entries.

The buffer is implemented using a *content-addressable memory* keyed by the *virtual page number*.

If the page table entry is found - great!

If the page table entry is not found - access the real page table in memory.

Who handles a TLB miss

RISC architecture

- MIPS, Sparc, ARM

Who handles a TLB miss

RISC architecture

- MIPS, Sparc, ARM
- The hardware rises an interrupt.

Who handles a TLB miss

RISC architecture

- MIPS, Sparc, ARM
- The hardware rises an interrupt.
- The operating system jumps to a *trap handler*.

Who handles a TLB miss

RISC architecture

- MIPS, Sparc, ARM
- The hardware rises an interrupt.
- The operating system jumps to a *trap handler*.
- The operating system will access the TLB and update the TLB.

Who handles a TLB miss

RISC architecture

- MIPS, Sparc, ARM
- The hardware rises an interrupt.
- The operating system jumps to a *trap handler*.
- The operating system will access the TLB and update the TLB.

CISC architecture

- x86

Who handles a TLB miss

RISC architecture

- MIPS, Sparc, ARM
- The hardware rises an interrupt.
- The operating system jumps to a *trap handler*.
- The operating system will access the TLB and update the TLB.

CISC architecture

- x86
- The hardware "knows" where to find the page table (CR3 register).

Who handles a TLB miss

RISC architecture

- MIPS, Sparc, ARM
- The hardware rises an interrupt.
- The operating system jumps to a *trap handler*.
- The operating system will access the TLB and update the TLB.

CISC architecture

- x86
- The hardware "knows" where to find the page table (CR3 register).
- The hardware will access the page table and updates the TLB.

Process switching

What happens when we switch process?

Process switching

What happens when we switch process?

The TLB contains the cached translations of the running process, when switching process the TLB must (in general) be flushed.

Process switching

What happens when we switch process?

The TLB contains the cached translations of the running process, when switching process the TLB must (in general) be flushed.

Do we have to flush the whole TLB?

Process switching

What happens when we switch process?

The TLB contains the cached translations of the running process, when switching process the TLB must (in general) be flushed.

Do we have to flush the whole TLB?

Is this best handled by the hardware or operating system?

Process switching

What happens when we switch process?

The TLB contains the cached translations of the running process, when switching process the TLB must (in general) be flushed.

Do we have to flush the whole TLB?

Is this best handled by the hardware or operating system?

Can we do pre-fetching of page table entries?

Process switching

What happens when we switch process?

The TLB contains the cached translations of the running process, when switching process the TLB must (in general) be flushed.

Do we have to flush the whole TLB?

Is this best handled by the hardware or operating system?

Can we do pre-fetching of page table entries?

The paging MMU with TLB



The paging MMU with TLB



The paging MMU with TLB



The paging MMU with TLB



The paging MMU with TLB



The paging MMU with TLB



The paging MMU with TLB



The paging MMU with TLB



The paging MMU with TLB



Size matters

Using 4 Kibyte pages (12 bits) for a 4 Gibyte address space (32 bits) will result in 1Mi (20 bits) page table entries.

Size matters

Using 4 Kibyte pages (12 bits) for a 4 Gibyte address space (32 bits) will result in 1Mi (20 bits) page table entries.

Each page table entry is 4 bytes.

Size matters

Using 4 Kibyte pages (12 bits) for a 4 Gibyte address space (32 bits) will result in 1Mi (20 bits) page table entries.

Each page table entry is 4 bytes.

A page table has the size of 4 Mibyte.

Size matters

Using 4 Kibyte pages (12 bits) for a 4 Gibyte address space (32 bits) will result in 1Mi (20 bits) page table entries.

Each page table entry is 4 bytes.

A page table has the size of 4 Mibyte.

Each process has its own page table.

Size matters

Using 4 Kibyte pages (12 bits) for a 4 Gibyte address space (32 bits) will result in 1Mi (20 bits) page table entries.

Each page table entry is 4 bytes.

A page table has the size of 4 Mibyte.

Each process has its own page table.

For 100 processes we need room for 400 Mibyte of page tables.

Size matters

Using 4 Kibyte pages (12 bits) for a 4 Gibyte address space (32 bits) will result in 1Mi (20 bits) page table entries.

Each page table entry is 4 bytes.

A page table has the size of 4 Mibyte.

Each process has its own page table.

For 100 processes we need room for 400 Mibyte of page tables.

Problem!

The solution - not.

Why not use pages of size 4 Mibyte?

The solution - not.

Why not use pages of size 4 Mibyte?

- Use a 22 bit offset and 10 bit virtual page number.

The solution - not.

Why not use pages of size 4 Mibyte?

- Use a 22 bit offset and 10 bit virtual page number.
- Page table 4 Kibyte (1024 entries, 4 byte each).

The solution - not.

Why not use pages of size 4 Mibyte?

- Use a 22 bit offset and 10 bit virtual page number.
- Page table 4 Kibyte (1024 entries, 4 byte each).
- Case closed!

The solution - not.

Why not use pages of size 4 Mibyte?

- Use a 22 bit offset and 10 bit virtual page number.
- Page table 4 Kibyte (1024 entries, 4 byte each).
- Case closed!

4 Mibyte pages are used and do have advantages but it is not a general solution.

Mostly empty space



Mostly empty space



Mostly empty space



Map only the areas that are actually used.

Hybrid approach - paged segmented memory

What if each segment was rarely larger than 1Ki pages of 4Kibyte.

Hybrid approach - paged segmented memory

What if each segment was rarely larger than 1Ki pages of 4Kibyte.



Hybrid approach - paged segmented memory

What if each segment was rarely larger than 1Ki pages of 4Kibyte.



Hybrid approach - paged segmented memory

What if each segment was rarely larger than 1Ki pages of 4Kibyte.



Hybrid approach - paged segmented memory

What if each segment was rarely larger than 1Ki pages of 4Kibyte.





Hybrid approach - paged segmented memory

What if each segment was rarely larger than 1Ki pages of 4Kibyte.



Hybrid approach - paged segmented memory

What if each segment was rarely larger than 1Ki pages of 4Kibyte.



Hybrid approach - paged segmented memory

What if each segment was rarely larger than 1Ki pages of 4Kibyte.



Hybrid approach - paged segmented memory

What if each segment was rarely larger than 1Ki pages of 4Kibyte.



Hybrid approach - paged segmented memory

What if each segment was rarely larger than 1Ki pages of 4Kibyte.



Multi-level page table

Used by Intel 80386

Multi-level page table

Used by Intel 80386

Multi-level page table

Used by Intel 80386

Multi-level page table

Used by Intel 80386

Multi-level page table



Used by Intel 80386

Multi-level page table



Used by Intel 80386

Multi-level page table



Used by Intel 80386

Multi-level page table



Used by Intel 80386

Multi-level page table



Used by Intel 80386

Multi-level page table



Used by Intel 80386

Mostly empty space

page directory

Mostly empty space



Mostly empty space



Mostly empty space



Mostly empty space



Mostly empty space



Mostly empty space



More than two levels



More than two levels



More than two levels



More than two levels



More than two levels



More than two levels



Scheme used in PAE, where each entry has a 24-bit physical base address. Each page table entry was 8 bytes whide.

More than two levels



Scheme used in PAE, where each entry has a 24-bit physical base address. Each page table entry was 8 bytes whide.

Trace the translation of a 32-bit virtual address to a 36-bit physical address.

The x86_64 architectures

- A 64-bit address but only 48-bits are used.

The x86_64 architectures

- A 64-bit address but only 48-bits are used.
- Bits 63-47 are either 1, kernel space, or 0, user space.
- The 48 bits are divided into:
  - 9-bit page global directory index
  - 9-bit page upper directory index
  - 9-bit page lower directory index
  - 9-bit page table index
  - 12-bit offset
- A page table entry is 8 bytes and contains a 40-bit physical address base address.

The x86_64 architectures

- A 64-bit address but only 48-bits are used.
- Bits 63-47 are either 1, kernel space, or 0, user space.
- The 48 bits are divided into:
  - 9-bit page global directory index
  - 9-bit page upper directory index
  - 9-bit page lower directory index
  - 9-bit page table index
  - 12-bit offset
- A page table entry is 8 bytes and contains a 40-bit physical address base address.
- The 40-bit base is combined with the 12-bit index to a 52-bit physical address.

The x86_64 architectures

- A 64-bit address but only 48-bits are used.
- Bits 63-47 are either 1, kernel space, or 0, user space.
- The 48 bits are divided into:
  - 9-bit page global directory index
  - 9-bit page upper directory index
  - 9-bit page lower directory index
  - 9-bit page table index
  - 12-bit offset
- A page table entry is 8 bytes and contains a 40-bit physical address base address.
- The 40-bit base is combined with the 12-bit index to a 52-bit physical address.

Linux can only handle a physical base addres of 34 bits i.e 46 bit physical address.

Inverted page tables

Inverted page tables

Why not do something completely different?

Inverted page tables

Why not do something completely different?

- We will probably not have more than say 8 Gibyte of main memory.

Inverted page tables

Why not do something completely different?

- We will probably not have more than say 8 Gibyte of main memory.
- If we divide this into 4 Kibyte frames we have 2 Mi frames.

Inverted page tables

Why not do something completely different?

- We will probably not have more than say 8 Gibyte of main memory.
- If we divide this into 4 Kibyte frames we have 2 Mi frames.
- Assume maintain a table with 2 Mi entries that describes which process and page that occupies the frame.

Inverted page tables

Why not do something completely different?

- We will probably not have more than say 8 Gibyte of main memory.
- If we divide this into 4 Kibyte frames we have 2 Mi frames.
- Assume maintain a table with 2 Mi entries that describes which process and page that occupies the frame.
- To translating a virtual address we simply search the table (efficient if we use a hash table).

Inverted page tables

Why not do something completely different?

- We will probably not have more than say 8 Gibyte of main memory.
- If we divide this into 4 Kibyte frames we have 2 Mi frames.
- Assume maintain a table with 2 Mi entries that describes which process and page that occupies the frame.
- To translating a virtual address we simply search the table (efficient if we use a hash table).
- Used by some models of PowerPC, Ultra Sparc and Itanium.

Summary

- Segmentation is not an ideal solution (why?).

Summary

- Segmentation is not an ideal solution (why?).
- Small fixed size pages is a solution.

Summary

- Segmentation is not an ideal solution (why?).
- Small fixed size pages is a solution.
- Speed of translation is a problem (what is the solution?)

Summary

- Segmentation is not an ideal solution (why?).
- Small fixed size pages is a solution.
- Speed of translation is a problem (what is the solution?)
- The size of the page table is a problem (and you know how to solve it).

Summary

- Segmentation is not an ideal solution (why?).
- Small fixed size pages is a solution.
- Speed of translation is a problem (what is the solution?)
- The size of the page table is a problem (and you know how to solve it).
- Inverted page tables - an alternative approach.

AC/DC - TLB

TLB - dynamite, makes paging possible.