Scope tags Edit

Selected tags	Default

Configuration settings Edit

Administrative Templates

Windows Components > BitLocker Drive Encryption

Choose drive encryption method and cipher strength (Windows 10 [Version 1511] and later)	Enabled
Select the encryption method for removable data drives:	AES-CBC 256-bit
Select the encryption method for operating system drives:	XTS-AES 256-bit
Select the encryption method for fixed data drives:	XTS-AES 256-bit

Windows Components > BitLocker Drive Encryption > Operating System Drives

Enforce drive encryption type on operating system drives	Enabled
Select the encryption type: (Device)	Used Space Only encryption
Require additional authentication at startup	Enabled
Configure TPM startup key:	Do not allow startup key with TPM

Configure TPM startup key and PIN:	Do not allow startup key and PIN with TPM
Configure TPM startup:	Allow TPM
Allow BitLocker without a compatible TPM (requires a password or a startup key on a USB flash drive)	False
Configure TPM startup PIN:	Allow startup PIN with TPM
Configure minimum PIN length for startup	Enabled
Minimum characters:	6
Allow enhanced PINs for startup	Enabled
Disallow standard users from changing the PIN or password	Disabled
Choose how BitLocker-protected operating system drives can be recovered	Enabled
Omit recovery options from the BitLocker setup wizard	True
Allow 256-bit recovery key	
Save BitLocker recovery information to AD DS for operating system drives	True
Do not enable BitLocker until recovery information is stored to AD DS for operating system drives	True

Configure user storage of BitLocker recovery information:	Allow 48-digit recovery password
Allow data recovery agent	True
Configure storage of BitLocker recovery information to AD DS:	Store recovery passwords and key packages

Windows Components > BitLocker Drive Encryption > Fixed Data Drives

Enforce drive encryption type on fixed data drives	Enabled
Select the encryption type: (Device)	Used Space Only encryption
Choose how BitLocker-protected fixed drives can be recovered	Enabled
Do not enable BitLocker until recovery information is stored to AD DS for fixed data drives	True
Allow data recovery agent	True
Configure storage of BitLocker recovery information to AD DS:	Backup recovery passwords and key packages
Allow 256-bit recovery key	
Omit recovery options from the BitLocker setup wizard	True
Save BitLocker recovery information to AD DS for fixed data drives	True
	Allow 48-digit recovery password

Configure user storage of BitLocker recovery information:

Deny write access to fixed drives not protected by BitLocker — Disabled

Windows Components > BitLocker Drive Encryption > Removable Data Drives

Control use of BitLocker on removable drives — Disabled

Deny write access to removable drives not protected by BitLocker — Disabled

BitLocker

Require Device Encryption — Enabled

Allow Warning For Other Disk Encryption — Disabled

Allow Standard User Encryption — Enabled