

Ex 1	Linear Regression
27.12.2023	

Q1 : Create a random 2-D numpy array with 1500 values. Simulate different lines of fit using 1000 values from the array and find the errors for each of these lines. Find the line with the least error among these lines and store it as the line of best fit. Using this line of best fit, predict the target variable for the other 500 values.

CODE :

```
import numpy as np
from sklearn.linear_model import LinearRegression

np.random.seed(42)
random_array = np.random.rand(1500)

random_array = random_array.reshape(-1, 1)

X_train = random_array[:1000]
y_train = 3 * X_train.squeeze() + np.random.normal(0, 0.1,
size=1000)

best_fit_line = None
min_error = float('inf')

for _ in range(1000):
    indices = np.random.choice(1000, size=1000, replace=True)
```

```
X_subset = X_train[indices]
y_subset = y_train[indices]

model = LinearRegression()
model.fit(X_subset, y_subset)

X_test = random_array[1000:]
y_test = 3 * X_test.squeeze()

error = np.mean((model.predict(X_test) - y_test) ** 2)

if error < min_error:
    min_error = error
    best_fit_line = model

print(f"Line of best fit coefficients: {best_fit_line.coef_}")
print(f"Intercept: {best_fit_line.intercept_}")
print(f"Minimum Error: {min_error}")

X_remaining = random_array[1000:]
predicted_values = best_fit_line.predict(X_remaining)
```

```
Python 3.10.9 | packaged by Anaconda, Inc. | (main, Mar 1 2023, 18:18:15) [MSC v.1916 64 bit (AMD64)]
Type "copyright", "credits" or "license" for more information.

IPython 8.10.0 -- An enhanced Interactive Python.

In [1]: runfile('C:/Users/rsath/untitled0.py', wdir='C:/Users/rsath')
Line of best fit coefficients: [2.99994273]
Intercept: -0.00013211732722329117
Minimum Error: 2.645536076745418e-08

In [2]:
```

Q2 : Use the data1.csv to build a simple linear regression from scratch without using sklearn libraries and print the RMSE and mean absolute error values. Use both the equations available in the slides (in theory page) to build the model and compare the intercept and coefficient values.

CODE :

```
import csv
import math
import numpy as np
data = []
with open('data1.csv', 'r') as file:
    csv_reader = csv.reader(file)
    next(csv_reader)
    for row in csv_reader:
        data.append([float(row[0]), float(row[1])])

def calculate_coefficients_partial_derivative(data):
    x = [row[0] for row in data]
    y = [row[1] for row in data]

    x_mean = sum(x) / len(x)
    y_mean = sum(y) / len(y)
```

```

        numerator = sum((x[i] * y[i] - y_mean * x[i]) for i in
range(len(data)))
        denominator = sum((x[i] ** 2 - x_mean * x[i]) for i in
range(len(data)))

    b1 = numerator / denominator
    b0 = y_mean - b1 * x_mean
    return b0, b1

def calculate_metrics(data, b0, b1):
    mse = 0
    mae = 0
    n = len(data)

    for i in range(n):
        x, y = data[i]
        y_pred = b0 + b1 * x
        mse += (y - y_pred) ** 2
        mae += abs(y - y_pred)

    mse /= n
    rmse = math.sqrt(mse)
    mae /= n
    return rmse, mae

def calculate_coefficients_correlation(data):
    x = [row[0] for row in data]
    y = [row[1] for row in data]
    x_mean, y_mean = np.mean(x), np.mean(y)
    r = np.corrcoef(x, y)[0, 1]
    Sx = np.std(x)
    Sy = np.std(y)
    b1 = r * Sy / Sx
    b0 = y_mean - b1 * x_mean
    return b0, b1

```

```

intercept_partial, coefficient_partial =
calculate_coefficients_partial_derivative(data)


intercept_correlation, coefficient_correlation =
calculate_coefficients_correlation(data)

rmse_partial, mae_partial = calculate_metrics(data,
intercept_partial, coefficient_partial)

rmse_correlation, mae_correlation = calculate_metrics(data,
intercept_correlation, coefficient_correlation)

print("Using Partial Derivative Equations:")
print(f"Intercept (b0): {intercept_partial}")
print(f"Coefficient (b1): {coefficient_partial}")
print(f"Root Mean Squared Error (RMSE): {rmse_partial}")
print(f"Mean Absolute Error (MAE): {mae_partial}")
print("\nUsing Correlation Coefficient and Standard Deviation:")
print(f"Intercept (b0): {intercept_correlation}")
print(f"Coefficient (b1): {coefficient_correlation}")
print(f"Root Mean Squared Error (RMSE): {rmse_correlation}")
print(f"Mean Absolute Error (MAE): {mae_correlation}")

```



```

Console 1/A X
In [10]: runfile('D:/snu/academic/sem6/ML_Lab/Lab1/q2.py', wdir='D:/snu/academic/sem6/ML_Lab/Lab1')
Using Partial Derivative Equations:
Intercept (b0): 30.10377358490593
Coefficient (b1): 3.179245283018851
Root Mean Squared Error (RMSE): 8.817810022046611
Mean Absolute Error (MAE): 7.305660377358496

Using Correlation Coefficient and Standard Deviation:
Intercept (b0): 30.103773584905674
Coefficient (b1): 3.1792452830188673
Root Mean Squared Error (RMSE): 8.81781002204661
Mean Absolute Error (MAE): 7.305660377358487

In [11]:

```

IPython Console History