JCC_WALLET DOCUMENT

一、Installtion2
二、Usage2
1 Create jingtum wallet or consortium chain wallet2
1.1 Example2
2 Valiate jingtum or consortium chain address if is valid2
2.1 Example2
3 Valiate jingtum or consortium chain secretif is valid 3
3.1 Example
4 Derive address from jingtum or consortium chain secret
3
4.1 Example

一、Installtion

Github source: https://github.com/JCCDex/jcc_wallet

npm install jcc_wallet

二、Usage

1 Create jingtum wallet or consortium chain wallet

1.1 Example

const jtWallet = require("jcc_wallet").jtWallet

const wallet = jtWallet.createWallet(chain)

Parameters:

chain: chain name, swt (jingtum chain) or bwt(bizain chain), default swt

Result:

{"secret":"ssfd6zheHp6y8SEv5imhqvMoiQLiw","address":"jaR7yuA6TA3aAh1d4gSUKgchh

7KYyrUL98"}

Result parameters:

Parameters		Туре	Description
wallet		Object	Wallet Object
	address	String	Wallet address
	secret	String	Wallet secret

2 Validate jingtum or consortium chain address if is valid

2.1 Example

const isValid = jtWallet.isValidAddress(address,chain)

Parameters:

address: wallet address

chain: chain name, swt (jingtum chain) or bwt(bizain chain), default swt

Result:

true or false

Result parameters:

Parameter	Туре	Description
isValid	Boolean	True if is valid

3 Valid jingtum or consortium chain secret if is valid

3.1 Example

const isValid = jtWallet.isValidSecret(secret,chain)

Parameters:

secret: wallet secret

chain: chain's name, swt (jingtum chain) or bwt(bizain chain), default swt

Result:

true or false

Result parameters:

Parameters	Туре	Description
isValid	Boolean	True if is valid

4 Derive address from jingtum or consortium chain secret

4.1 Example

const address = await jtWallet.getAddress(secret,chain)

Parameters:

secret: wallet secret

chain: chain name, swt (jingtum chain) or bwt(bizain chain), default swt

Result:

address:"jaR7yuA6TA3aAh1d4gSUKgchh7KYyrUL98" | null

Result parameters:

Parameters	Туре	Description	
address	String	Wallet address	