

## Draftable Comparison Export

This document is an exported comparison with limited functionality, generated by Draftable Desktop. To access full functionality, use Draftable's powerful comparison viewer in any of our products.

**Left document:** 2b-SysML\_v1\_to\_v2\_Transformation\_Beta\_2.pdf

**Right document:** 2b-SysML\_v1\_to\_v2\_Transformation\_Beta\_3.pdf

### What is this document?

This is a comparison of two documents. The two documents are interleaved such that the left document is displayed on even pages and the right document is displayed on odd pages.

### Is there a specific way I should view this file?

This document is intended to be viewed in Two Page Continuous mode (or sometimes called 'Two Page Scrolling'). It should open in this mode by default when using Adobe Acrobat and most popular PDF readers.

If the document opens in a different view, you can often change this in the settings. In Adobe Acrobat, go to **View > Page Display > Two Page Scrolling**.

### Why are there blank pages?

Blank pages are inserted to keep both documents as aligned as much as possible.

### How do I read the changes?

Text deleted from the left document and, hence, not in right document is highlighted red. Text added to the right document and, hence, not in left document is highlighted green.

### Tip for printing

When printing this document, we recommend printing double-sided and include this first page. This will result in the matching text being displayed on different pages and easily readable, much like a book.

### For more information

Draftable offers powerful document comparison solutions for all use-cases. To view our products, please visit our website: [draftable.com](https://draftable.com).



# OMG Systems Modeling Language™ (SysML®)

Version 2.0 Beta 2  
(Revision 2024-02)

## Part 2: SysML v1 to SysML v2 Transformation

---

OMG Document Number: None

Date: February 2024

Standard document URL: <https://www.omg.org/spec/SysML/2.0/Transformation/>

Machine Readable File(s): <https://www.omg.org/spec/SysML/20240201/>

Normative:

<https://www.omg.org/spec/SysML/20240201/SysMLv1Tov2.xmi>

---



An OMG® Systems Modeling Publication



# OMG Systems Modeling Language™ (SysML®)

Version 2.0 Beta 3  
(Release 2025-02)

## Part 2: SysML v1 to SysML v2 Transformation

---

OMG Document Number: ptc/2025-02-13

Date: February 2025

Standard document URL: <https://www.omg.org/spec/SysML/2.0/Transformation/>

Machine Readable File(s): <https://www.omg.org/spec/SysML/20250201/>

Normative:

<https://www.omg.org/spec/SysML/20250201/SysMLv1Tov2.xmi>

---

Copyright © 2019-2024, 88solutions Corporation  
Copyright © 2019-2024, Airbus  
Copyright © 2019-2024, Aras Corporation  
Copyright © 2019-2024, Association of Universities for Research in Astronomy (AURA)  
Copyright © 2019-2024, BigLever Software  
Copyright © 2019-2024, Boeing  
Copyright © 2022-2024, Budapest University of Technology and Economics  
Copyright © 2021-2024, Commissariat à l'énergie atomique et aux énergies alternatives (CEA)  
Copyright © 2019-2024, Contact Software GmbH  
Copyright © 2019-2024, Dassault Systèmes (No Magic)  
Copyright © 2019-2024, DSC Corporation  
Copyright © 2020-2024, DEKonsult  
Copyright © 2020-2024, Delligatti Associates LLC  
Copyright © 2019-2024, The Charles Stark Draper Laboratory, Inc.  
Copyright © 2020-2024, ESTACA  
Copyright © 2022-2024, Galois, Inc.  
Copyright © 2019-2024, GfSE e.V.  
Copyright © 2019-2024, George Mason University  
Copyright © 2019-2024, IBM  
Copyright © 2019-2024, Idaho National Laboratory  
Copyright © 2019-2024, INCOSE  
Copyright © 2019-2024, Intercax LLC  
Copyright © 2019-2024, Jet Propulsion Laboratory (California Institute of Technology)  
Copyright © 2019-2024, Kenntnis LLC  
Copyright © 2020-2024, Kungliga Tekniska högskolan (KTH)  
Copyright © 2019-2024, LightStreet Consulting LLC  
Copyright © 2019-2024, Lockheed Martin Corporation  
Copyright © 2019-2024, Maplesoft  
Copyright © 2021-2024, MID GmbH  
Copyright © 2020-2024, MITRE  
Copyright © 2019-2024, Model Alchemy Consulting  
Copyright © 2019-2024, Model Driven Solutions, Inc.  
Copyright © 2019-2024, Model Foundry Pty. Ltd.  
Copyright © 2023-2024, Object Management Group, Inc.  
Copyright © 2019-2024, On-Line Application Research Corporation (OAC)  
Copyright © 2019-2024, oose Innovative Informatik eG  
Copyright © 2019-2024, Østfold University College  
Copyright © 2019-2024, PTC  
Copyright © 2020-2024, Qualtech Systems, Inc.  
Copyright © 2019-2024, SAF Consulting  
Copyright © 2019-2024, Simula Research Laboratory AS  
Copyright © 2019-2024, System Strategy, Inc.  
Copyright © 2019-2024, Thematrix Partners, LLC  
Copyright © 2019-2024, Tom Sawyer  
Copyright © 2022-2024, Tucson Embedded Systems, Inc.  
Copyright © 2019-2024, Universidad de Cantabria  
Copyright © 2019-2024, University of Alabama in Huntsville  
Copyright © 2019-2024, University of Detroit Mercy  
Copyright © 2019-2024, University of Kaiserslautern  
Copyright © 2020-2024, Willert Software Tools GmbH (SodiusWillert)

Copyright © 2019-2025, 88solutions Corporation  
Copyright © 2019-2025, Airbus  
Copyright © 2019-2025, Aras Corporation  
Copyright © 2019-2025, Association of Universities for Research in Astronomy (AURA)  
Copyright © 2019-2025, BigLever Software  
Copyright © 2019-2025, Boeing  
Copyright © 2022-2025, Budapest University of Technology and Economics  
Copyright © 2021-2025, Commissariat à l'énergie atomique et aux énergies alternatives (CEA)  
Copyright © 2019-2025, Contact Software GmbH  
Copyright © 2019-2025, Dassault Systèmes (No Magic)  
Copyright © 2019-2025, DSC Corporation  
Copyright © 2020-2025, DEKonsult  
Copyright © 2020-2025, Delligatti Associates LLC  
Copyright © 2019-2025, The Charles Stark Draper Laboratory, Inc.  
Copyright © 2020-2025, ESTACA  
Copyright © 2022-2025, Galois, Inc.  
Copyright © 2019-2025, GfSE e.V.  
Copyright © 2019-2025, George Mason University  
Copyright © 2019-2025, IBM  
Copyright © 2019-2025, Idaho National Laboratory  
Copyright © 2019-2025, INCOSE  
Copyright © 2019-2025, Intercax LLC  
Copyright © 2019-2025, Jet Propulsion Laboratory (California Institute of Technology)  
Copyright © 2019-2025, Kenntnis LLC  
Copyright © 2020-2025, Kungliga Tekniska högskolan (KTH)  
Copyright © 2019-2025, LightStreet Consulting LLC  
Copyright © 2019-2025, Lockheed Martin Corporation  
Copyright © 2019-2025, Maplesoft  
Copyright © 2021-2025, MID GmbH  
Copyright © 2020-2025, MITRE  
Copyright © 2019-2025, Model Alchemy Consulting  
Copyright © 2019-2025, Model Driven Solutions, Inc.  
Copyright © 2019-2025, Model Foundry Pty. Ltd.  
Copyright © 2023-2025, Object Management Group, Inc.  
Copyright © 2019-2025, On-Line Application Research Corporation (OAC)  
Copyright © 2019-2025, oose Innovative Informatik eG  
Copyright © 2019-2025, Østfold University College  
Copyright © 2019-2025, PTC  
Copyright © 2020-2025, Qualtech Systems, Inc.  
Copyright © 2019-2025, SAF Consulting  
Copyright © 2019-2025, Simula Research Laboratory AS  
Copyright © 2019-2025, System Strategy, Inc.  
Copyright © 2019-2025, Thematrix Partners, LLC  
Copyright © 2019-2025, Tom Sawyer  
Copyright © 2022-2025, Tucson Embedded Systems, Inc.  
Copyright © 2019-2025, Universidad de Cantabria  
Copyright © 2019-2025, University of Alabama in Huntsville  
Copyright © 2019-2025, University of Detroit Mercy  
Copyright © 2019-2025, University of Kaiserslautern  
Copyright © 2020-2025, Willert Software Tools GmbH (SodiusWillert)

## USE OF SPECIFICATION - TERMS, CONDITIONS & NOTICES

The material in this document details an Object Management Group specification in accordance with the terms, conditions and notices set forth below. This document does not represent a commitment to implement any portion of this specification in any company's products. The information contained in this document is subject to change without notice.

## LICENSES

The companies listed above have granted to the Object Management Group, Inc. (OMG) a nonexclusive, royalty-free, paid up, worldwide license to copy and distribute this document and to modify this document and distribute copies of the modified version. Each of the copyright holders listed above has agreed that no person shall be deemed to have infringed the copyright in the included material of any such copyright holder by reason of having used the specification set forth herein or having conformed any computer software to the specification.

Subject to all of the terms and conditions below, the owners of the copyright in this specification hereby grant you a fully-paid up, non-exclusive, nontransferable, perpetual, worldwide license (without the right to sublicense), to use this specification to create and distribute software and special purpose specifications that are based upon this specification, and to use, copy, and distribute this specification as provided under the Copyright Act; provided that: (1) both the copyright notice identified above and this permission notice appear on any copies of this specification; (2) the use of the specifications is for informational purposes and will not be copied or posted on any network computer or broadcast in any media and will not be otherwise resold or transferred for commercial purposes; and (3) no modifications are made to this specification. This limited permission automatically terminates without notice if you breach any of these terms or conditions. Upon termination, you will destroy immediately any copies of the specifications in your possession or control.

## PATENTS

The attention of adopters is directed to the possibility that compliance with or adoption of OMG specifications may require use of an invention covered by patent rights. OMG shall not be responsible for identifying patents for which a license may be required by any OMG specification, or for conducting legal inquiries into the legal validity or scope of those patents that are brought to its attention. OMG specifications are prospective and advisory only. Prospective users are responsible for protecting themselves against liability for infringement of patents.

## GENERAL USE RESTRICTIONS

Any unauthorized use of this specification may violate copyright laws, trademark laws, and communications regulations and statutes. This document contains information which is protected by copyright. All Rights Reserved. No part of this work covered by copyright herein may be reproduced or used in any form or by any means--graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems--without permission of the copyright owner.

## DISCLAIMER OF WARRANTY

WHILE THIS PUBLICATION IS BELIEVED TO BE ACCURATE, IT IS PROVIDED "AS IS" AND MAY CONTAIN ERRORS OR MISPRINTS. THE OBJECT MANAGEMENT GROUP AND THE COMPANIES LISTED ABOVE MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS PUBLICATION, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF TITLE OR

## USE OF SPECIFICATION - TERMS, CONDITIONS & NOTICES

The material in this document details an Object Management Group specification in accordance with the terms, conditions and notices set forth below. This document does not represent a commitment to implement any portion of this specification in any company's products. The information contained in this document is subject to change without notice.

## LICENSES

The companies listed above have granted to the Object Management Group, Inc. (OMG) a nonexclusive, royalty-free, paid up, worldwide license to copy and distribute this document and to modify this document and distribute copies of the modified version. Each of the copyright holders listed above has agreed that no person shall be deemed to have infringed the copyright in the included material of any such copyright holder by reason of having used the specification set forth herein or having conformed any computer software to the specification.

Subject to all of the terms and conditions below, the owners of the copyright in this specification hereby grant you a fully-paid up, non-exclusive, nontransferable, perpetual, worldwide license (without the right to sublicense), to use this specification to create and distribute software and special purpose specifications that are based upon this specification, and to use, copy, and distribute this specification as provided under the Copyright Act; provided that: (1) both the copyright notice identified above and this permission notice appear on any copies of this specification; (2) the use of the specifications is for informational purposes and will not be copied or posted on any network computer or broadcast in any media and will not be otherwise resold or transferred for commercial purposes; and (3) no modifications are made to this specification. This limited permission automatically terminates without notice if you breach any of these terms or conditions. Upon termination, you will destroy immediately any copies of the specifications in your possession or control.

## PATENTS

The attention of adopters is directed to the possibility that compliance with or adoption of OMG specifications may require use of an invention covered by patent rights. OMG shall not be responsible for identifying patents for which a license may be required by any OMG specification, or for conducting legal inquiries into the legal validity or scope of those patents that are brought to its attention. OMG specifications are prospective and advisory only. Prospective users are responsible for protecting themselves against liability for infringement of patents.

## GENERAL USE RESTRICTIONS

Any unauthorized use of this specification may violate copyright laws, trademark laws, and communications regulations and statutes. This document contains information which is protected by copyright. All Rights Reserved. No part of this work covered by copyright herein may be reproduced or used in any form or by any means--graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems--without permission of the copyright owner.

## DISCLAIMER OF WARRANTY

WHILE THIS PUBLICATION IS BELIEVED TO BE ACCURATE, IT IS PROVIDED "AS IS" AND MAY CONTAIN ERRORS OR MISPRINTS. THE OBJECT MANAGEMENT GROUP AND THE COMPANIES LISTED ABOVE MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS PUBLICATION, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF TITLE OR

OWNERSHIP, IMPLIED WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR USE. IN NO EVENT SHALL THE OBJECT MANAGEMENT GROUP OR ANY OF THE COMPANIES LISTED ABOVE BE LIABLE FOR ERRORS CONTAINED HEREIN OR FOR DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL, RELIANCE OR COVER DAMAGES, INCLUDING LOSS OF PROFITS, REVENUE, DATA OR USE, INCURRED BY ANY USER OR ANY THIRD PARTY IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS MATERIAL, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

The entire risk as to the quality and performance of software developed using this specification is borne by you. This disclaimer of warranty constitutes an essential part of the license granted to you to use this specification.

## RESTRICTED RIGHTS LEGEND

Use, duplication or disclosure by the U.S. Government is subject to the restrictions set forth in subparagraph (c) (1) (ii) of The Rights in Technical Data and Computer Software Clause at DFARS 252.227-7013 or in subparagraph (c)(1) and (2) of the Commercial Computer Software - Restricted Rights clauses at 48 C.F.R. 52.227-19 or as specified in 48 C.F.R. 227-7202-2 of the DoD F.A.R. Supplement and its successors, or as specified in 48 C.F.R. 12.212 of the Federal Acquisition Regulations and its successors, as applicable. The specification copyright owners are as indicated above and may be contacted through the Object Management Group, 9C Medway Road, PMB 274, Milford, MA 01757, U.S.A.

## TRADEMARKS

CORBA<sup>®</sup>, CORBA logos<sup>®</sup>, FIBO<sup>®</sup>, Financial Industry Business Ontology<sup>®</sup>, Financial Instrument Global Identifier<sup>®</sup>, IIOP<sup>®</sup>, IMM<sup>®</sup>, Model Driven Architecture<sup>®</sup>, MDA<sup>®</sup>, Object Management Group<sup>®</sup>, OMG<sup>®</sup>, OMG Logo<sup>®</sup>, SoaML<sup>®</sup>, SOAML<sup>®</sup>, SysML<sup>®</sup>, UAF<sup>®</sup>, Unified Modeling Language<sup>™</sup>, UML<sup>®</sup>, UML Cube Logo<sup>®</sup>, VSIPL<sup>®</sup>, and XMI<sup>®</sup> are registered trademarks of the Object Management Group, Inc.

For a complete list of trademarks, see: [https://www.omg.org/legal/tm\\_list.htm](https://www.omg.org/legal/tm_list.htm). All other products or company names mentioned are used for identification purposes only, and may be trademarks of their respective owners.

## COMPLIANCE

The copyright holders listed above acknowledge that the Object Management Group (acting itself or through its designees) is and shall at all times be the sole entity that may authorize developers, suppliers and sellers of computer software to use certification marks, trademarks or other special designations to indicate compliance with these materials.

Software developed under the terms of this license may claim compliance or conformance with this specification if and only if the software compliance is of a nature fully matching the applicable compliance points as stated in the specification. Software developed only partially matching the applicable compliance points may claim only that the software was based on this specification, but may not claim compliance or conformance with this specification. In the event that testing suites are implemented or approved by Object Management Group, Inc., software developed using this specification may claim compliance or conformance with the specification only if the software satisfactorily completes the testing suites.



OWNERSHIP, IMPLIED WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR USE. IN NO EVENT SHALL THE OBJECT MANAGEMENT GROUP OR ANY OF THE COMPANIES LISTED ABOVE BE LIABLE FOR ERRORS CONTAINED HEREIN OR FOR DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL, RELIANCE OR COVER DAMAGES, INCLUDING LOSS OF PROFITS, REVENUE, DATA OR USE, INCURRED BY ANY USER OR ANY THIRD PARTY IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS MATERIAL, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

The entire risk as to the quality and performance of software developed using this specification is borne by you. This disclaimer of warranty constitutes an essential part of the license granted to you to use this specification.

## RESTRICTED RIGHTS LEGEND

Use, duplication or disclosure by the U.S. Government is subject to the restrictions set forth in subparagraph (c) (1) (ii) of The Rights in Technical Data and Computer Software Clause at DFARS 252.227-7013 or in subparagraph (c)(1) and (2) of the Commercial Computer Software - Restricted Rights clauses at 48 C.F.R. 52.227-19 or as specified in 48 C.F.R. 227-7202-2 of the DoD F.A.R. Supplement and its successors, or as specified in 48 C.F.R. 12.212 of the Federal Acquisition Regulations and its successors, as applicable. The specification copyright owners are as indicated above and may be contacted through the Object Management Group, 9C Medway Road, PMB 274, Milford, MA 01757, U.S.A.

## TRADEMARKS

CORBA<sup>®</sup>, CORBA logos<sup>®</sup>, FIBO<sup>®</sup>, Financial Industry Business Ontology<sup>®</sup>, Financial Instrument Global Identifier<sup>®</sup>, IIOP<sup>®</sup>, IMM<sup>®</sup>, Model Driven Architecture<sup>®</sup>, MDA<sup>®</sup>, Object Management Group<sup>®</sup>, OMG<sup>®</sup>, OMG Logo<sup>®</sup>, SoaML<sup>®</sup>, SOAML<sup>®</sup>, SysML<sup>®</sup>, UAF<sup>®</sup>, Unified Modeling Language<sup>™</sup>, UML<sup>®</sup>, UML Cube Logo<sup>®</sup>, VSIPL<sup>®</sup>, and XMI<sup>®</sup> are registered trademarks of the Object Management Group, Inc.

For a complete list of trademarks, see: [https://www.omg.org/legal/tm\\_list.htm](https://www.omg.org/legal/tm_list.htm). All other products or company names mentioned are used for identification purposes only, and may be trademarks of their respective owners.

## COMPLIANCE

The copyright holders listed above acknowledge that the Object Management Group (acting itself or through its designees) is and shall at all times be the sole entity that may authorize developers, suppliers and sellers of computer software to use certification marks, trademarks or other special designations to indicate compliance with these materials.

Software developed under the terms of this license may claim compliance or conformance with this specification if and only if the software compliance is of a nature fully matching the applicable compliance points as stated in the specification. Software developed only partially matching the applicable compliance points may claim only that the software was based on this specification, but may not claim compliance or conformance with this specification. In the event that testing suites are implemented or approved by Object Management Group, Inc., software developed using this specification may claim compliance or conformance with the specification only if the software satisfactorily completes the testing suites.

## OMG'S ISSUE REPORTING PROCEDURE

All OMG specifications are subject to continuous review and improvement. As part of this process we encourage readers to report any ambiguities, inconsistencies, or inaccuracies they may find by completing the Issue Reporting Form listed on the main web page <https://www.omg.org>, under Documents, Report a Bug/Issue.





## OMG'S ISSUE REPORTING PROCEDURE

All OMG specifications are subject to continuous review and improvement. As part of this process we encourage readers to report any ambiguities, inconsistencies, or inaccuracies they may find by completing the Issue Reporting Form listed on the main web page <https://www.omg.org>, under Documents, Report a Bug/Issue.



# Table of Contents

0 Preface.....	23
1 Scope.....	1
2 Conformance.....	3
3 Normative References.....	5
4 Terms and Definitions.....	7
5 Symbols .....	9
6 Introduction.....	11
6.1 Mapping Approach .....	11
6.2 Acknowledgements.....	11
7 Mappings.....	13
7.1 Overview.....	13
7.2 Foundations.....	13
7.2.1 Overview .....	13
7.2.2 Foundational class specifications.....	14
7.2.2.1 UniqueMapping.....	14
7.2.2.2 Factory.....	14
7.2.2.3 Mapping .....	14
7.2.2.4 MainMapping .....	15
7.2.2.5_INITIALIZER .....	16
7.3 Mapping Helper and Library.....	16
7.3.1 Helper.....	16
7.3.2 SysML v1 Library .....	22
7.4 Initializers.....	24
7.4.1 Overview .....	24
7.4.2 Mapping Specifications.....	24
7.4.2.1 KerML Initializers.....	25
7.4.2.1.1 ToAnnotatingElement_Init.....	25
7.4.2.1.2 ToAnnotation_Init.....	25
7.4.2.1.3 ToAssociation_Init.....	25
7.4.2.1.4 ToBehavior_Init.....	26
7.4.2.1.5 ToClassifier_Init.....	26
7.4.2.1.6 ToComment_Init.....	26
7.4.2.1.7 ToConjugation_Init.....	27
7.4.2.1.8 ToConnector_Init.....	27
7.4.2.1.9 ToDocumentation_Init.....	27
7.4.2.1.10 ToElement_Init.....	28
7.4.2.1.11 ToEndFeatureMembership_Init.....	28
7.4.2.1.12 ToExpression_Init.....	29
7.4.2.1.13 ToFeature_Init.....	29
7.4.2.1.14 ToFeatureChainExpression_Init.....	30
7.4.2.1.15 ToFeatureChaining_Init.....	30
7.4.2.1.16 ToFeatureMembership_Init.....	31
7.4.2.1.17 ToFeatureReferenceExpression_Init.....	31
7.4.2.1.18 ToFeatureTyping_Init.....	31
7.4.2.1.19 ToFeatureValue_Init.....	32
7.4.2.1.20 ToFlow_Init.....	32
7.4.2.1.21 ToFunction_Init.....	33
7.4.2.1.22 ToImport_Init.....	33
7.4.2.1.23 ToInteraction_Init.....	33
7.4.2.1.24 ToInvocationExpression_Init.....	34
7.4.2.1.25 ToMembership_Init.....	34
7.4.2.1.26 ToMembershipImport_Init.....	35
7.4.2.1.27 ToNamespace_Init.....	35
7.4.2.1.28 ToNamespaceImport_Init.....	35

# Table of Contents

0 Preface.....	23
1 Scope.....	1
2 Conformance.....	3
3 Normative References.....	5
4 Terms and Definitions.....	7
5 Symbols .....	9
6 Introduction.....	11
6.1 Mapping Approach .....	11
6.2 Acknowledgements.....	11
7 Mappings.....	13
7.1 Overview.....	13
7.2 Foundations.....	13
7.2.1 Overview.....	13
7.2.2 Foundational class specifications.....	14
7.2.2.1 UniqueMapping.....	14
7.2.2.2 Factory.....	14
7.2.2.3 Mapping .....	14
7.2.2.4 MainMapping.....	15
7.2.2.5 Initializer .....	16
7.3 Mapping Helper and Library.....	16
7.3.1 Helper.....	16
7.3.2 SysML v1 Library .....	22
7.4 Initializers.....	25
7.4.1 Overview.....	25
7.4.2 Mapping Specifications.....	25
7.4.2.1 KerML Initializers.....	25
7.4.2.1.1 AnnotatingElement_Init.....	25
7.4.2.1.2 Annotation_Init.....	26
7.4.2.1.3 Association_Init.....	26
7.4.2.1.4 Behavior_Init.....	26
7.4.2.1.5 Classifier_Init.....	27
7.4.2.1.6 Comment_Init.....	27
7.4.2.1.7 Conjugation_Init.....	27
7.4.2.1.8 Connector_Init.....	28
7.4.2.1.9 Documentation_Init.....	28
7.4.2.1.10 Element_Init.....	28
7.4.2.1.11 EndFeatureMembership_Init.....	29
7.4.2.1.12 Expression_Init.....	29
7.4.2.1.13 Feature_Init.....	30
7.4.2.1.14 FeatureChainExpression_Init.....	31
7.4.2.1.15 FeatureChaining_Init.....	31
7.4.2.1.16 FeatureMembership_Init.....	31
7.4.2.1.17 FeatureReferenceExpression_Init.....	32
7.4.2.1.18 FeatureTyping_Init.....	32
7.4.2.1.19 FeatureValue_Init.....	32
7.4.2.1.20 Function_Init.....	33
7.4.2.1.21 Import_Init.....	33
7.4.2.1.22 Interaction_Init.....	34
7.4.2.1.23 InvocationExpression_Init.....	34
7.4.2.1.24 ItemFlow_Init.....	34
7.4.2.1.25 Membership_Init.....	34





7.4.2.1.26 MembershipImport_Init.....	35
7.4.2.1.27 Namespace_Init.....	35
7.4.2.1.28 NamespaceImport_Init.....	36
7.4.2.1.29 OperatorExpression_Init.....	36
7.4.2.1.30 OwningMembership_Init.....	36
7.4.2.1.31 Package_Init.....	37
7.4.2.1.32 ParameterMembership_Init.....	37
7.4.2.1.33 Predicate_Init.....	37
7.4.2.1.34 Redefinition_Init.....	38
7.4.2.1.35 ReferenceSubsetting_Init.....	38
7.4.2.1.36 Relationship_Init.....	38
7.4.2.1.37 ReturnParameterMembership_Init.....	39
7.4.2.1.38 Specialization_Init.....	39
7.4.2.1.39 Step_Init.....	40
7.4.2.1.40 Subclassification_Init.....	40
7.4.2.1.41 Subsetting_Init.....	40
7.4.2.1.42 Succession_Init.....	41
7.4.2.1.43 SuccessionItemFlow_Init.....	41
7.4.2.1.44 TextualRepresentation_Init.....	41
7.4.2.1.45 Type_Init.....	41
7.4.2.1.46 TypeFeaturing_Init.....	42
7.4.2.2 System Initializers.....	42
7.4.2.2.1 ActionUsage_Init.....	42
7.4.2.2.2 ActorMembership_Init.....	43
7.4.2.2.3 AssignmentActionUsage_Init.....	43
7.4.2.2.4 ConjugatedPortDefinition_Init.....	43
7.4.2.2.5 ConjugatedPortTyping_Init.....	43
7.4.2.2.6 ConnectionUsage_Init.....	44
7.4.2.2.7 ConstraintDefinition_Init.....	44
7.4.2.2.8 ConstraintUsage_Init.....	44
7.4.2.2.9 Definition_Init.....	45
7.4.2.2.10 EventOccurrenceUsage_Init.....	45
7.4.2.2.11 FlowConnectionUsage_Init.....	45
7.4.2.2.12 ItemDefinition_Init.....	45
7.4.2.2.13 ItemFeature_Init.....	46
7.4.2.2.14 MetadataUsage_Init.....	46
7.4.2.2.15 ObjectiveMembership_Init.....	46
7.4.2.2.16 OccurrenceDefinition_Init.....	46
7.4.2.2.17 OccurrenceUsage_Init.....	47
7.4.2.2.18 PartUsage_Init.....	47
7.4.2.2.19 PortConjugation_Init.....	48
7.4.2.2.20 PortDefinition_Init.....	48
7.4.2.2.21 ReferenceUsage_Init.....	48
7.4.2.2.22 RequirementUsage_Init.....	48
7.4.2.2.23 StateUsage_Init.....	49
7.4.2.2.24 SubjectMembership_Init.....	49
7.4.2.2.25 Usage_Init.....	49
7.5 Factories.....	49
7.5.1 Overview.....	50
7.5.2 Mapping Specifications.....	50
7.5.2.1 LiteralString_Factory.....	50
7.5.2.2 StringParameterFeature_Factory.....	50
7.5.2.3 StringParameterFeatureValue_Factory.....	51
7.5.2.4 StringParameterMembership_Factory.....	51

7.4.2.1.29	ToOperatorExpression_Init	36
7.4.2.1.30	ToOwningMembership_Init	36
7.4.2.1.31	ToPackage_Init	36
7.4.2.1.32	ToParameterMembership_Init	37
7.4.2.1.33	ToPredicate_Init	37
7.4.2.1.34	ToRedefinition_Init	37
7.4.2.1.35	ToReferenceSubsetting_Init	38
7.4.2.1.36	ToRelationship_Init	38
7.4.2.1.37	ToReturnParameterMembership_Init	39
7.4.2.1.38	ToSpecialization_Init	39
7.4.2.1.39	ToStep_Init	39
7.4.2.1.40	ToSubclassification_Init	40
7.4.2.1.41	ToSubsetting_Init	40
7.4.2.1.42	ToSuccession_Init	41
7.4.2.1.43	ToSuccessionItemFlow_Init	41
7.4.2.1.44	ToTextualRepresentation_Init	41
7.4.2.1.45	ToType_Init	41
7.4.2.1.46	ToTypeFeaturing_Init	42
7.4.2.2	System Initializers	42
7.4.2.2.1	ToActionUsage_Init	42
7.4.2.2.2	ToActorMembership_Init	43
7.4.2.2.3	ToAssignmentActionUsage_Init	43
7.4.2.2.4	ToBindingConnectorAsUsage_Init	43
7.4.2.2.5	ToCalculationUsage_Init	44
7.4.2.2.6	ToConjugatedPortDefinition_Init	44
7.4.2.2.7	ToConjugatedPortTyping_Init	44
7.4.2.2.8	ToConnectionUsage_Init	45
7.4.2.2.9	ToConstraintDefinition_Init	45
7.4.2.2.10	ToConstraintUsage_Init	45
7.4.2.2.11	ToDefinition_Init	45
7.4.2.2.12	ToEventOccurrenceUsage_Init	46
7.4.2.2.13	ToFlowUsage_Init	46
7.4.2.2.14	ToItemDefinition_Init	46
7.4.2.2.15	ToItemFeature_Init	47
7.4.2.2.16	ToItemUsage_Init	47
7.4.2.2.17	ToMetadataUsage_Init	47
7.4.2.2.18	ToObjectiveMembership_Init	48
7.4.2.2.19	ToOccurrenceDefinition_Init	48
7.4.2.2.20	ToOccurrenceUsage_Init	48
7.4.2.2.21	ToPartUsage_Init	49
7.4.2.2.22	ToPerformActionUsage_Init	49
7.4.2.2.23	ToPortConjugation_Init	49
7.4.2.2.24	ToPortDefinition_Init	49
7.4.2.2.25	ToReferenceUsage_Init	50
7.4.2.2.26	ToRequirementUsage_Init	50
7.4.2.2.27	ToStateSubactionMembership_Init	50
7.4.2.2.28	ToStateUsage_Init	51
7.4.2.2.29	ToSubjectMembership_Init	51
7.4.2.2.30	ToTransitionUsage_Init	51
7.4.2.2.31	ToTriggerInvocationExpression_Init	51
7.4.2.2.32	ToUsage_Init	52
7.5	Factories	52
7.5.1	Overview	52
7.5.2	Mapping Specifications	52
7.5.2.1	LiteralString_Factory	52
7.5.2.2	StringParameterFeature_Factory	53

7.5.2.5 SubjectMembership_Factory .....	51
7.5.2.6 AssignmentActionUsage_Factory .....	52
7.5.2.7 AssignmentActionUsageFeatureMembership2_Factory .....	52
7.5.2.8 AssignmentActionUsageFeatureMembership3_Factory .....	53
7.5.2.9 AssignmentActionUsageOwningMembership_Factory .....	53
7.5.2.10 AssignmentActionUsageParameterMembership_Factory .....	53
7.5.2.11 AssignmentActionUsageReferenceUsageIn1_Factory .....	54
7.5.2.12 AssignmentActionUsageTargetReferenceUsageIn2_Factory .....	54
7.5.2.13 AssignmentActionUsageTargetReferenceUsageIn3_Factory .....	54
7.5.2.14 DirectedReferenceUsage_Factory .....	55
7.5.2.15 DirectedReferenceUsageParameterMembership_Factory .....	55
7.5.2.16 EmptyObjectiveMembership_Factory .....	56
7.5.2.17 EmptyRequirementUsage_Factory .....	56
7.5.2.18 EmptySubject_Factory .....	56
7.5.2.19 EmptySubjectMembership_Factory .....	57
7.5.2.20 FeatureTyping_Factory .....	57
7.5.2.21 FlowConnectionUsage_Factory .....	57
7.5.2.22 FlowConnectionUsageFeatureMembership_Factory .....	58
7.5.2.23 FlowEndParameterMembership_Factory .....	59
7.5.2.24 FlowItem_Factory .....	59
7.5.2.25 FlowItemFeatureMembership_Factory .....	60
7.5.2.26 InformationFlowEventOccurrenceUsage_Factory .....	60
7.5.2.27 InformationFlowReferenceSubsetting_Factory .....	60
7.5.2.28 LiteralBoolean_Factory .....	61
7.5.2.29 LiteralNull_Factory .....	61
7.5.2.30 LiteralRational_Factory .....	62
7.5.2.31 ObjectFlowItemFlowEndRedefinition_Factory .....	62
7.5.2.32 ReferenceSubsetting_Factory .....	63
7.5.2.33 ReturnParameterFeature_Factory .....	63
7.5.2.34 ReturnParameterFeatureMembership_Factory .....	63
7.5.2.35 Subsetting_Factory .....	64
7.6 Generic Mappings .....	64
7.6.1 Overview .....	64
7.6.2 Common Mappings .....	64
7.6.2.1 CommonFeatureReferenceExpression_Mapping .....	64
7.6.2.2 CommonMembership_Mapping .....	65
7.6.2.3 CommonParameterReferenceUsageInMembership_Mapping .....	66
7.6.2.4 CommonParameterReferenceUsageIn_Mapping .....	66
7.6.2.5 CommonParameterReferenceUsageInFeatureTyping_Mapping .....	67
7.6.2.6 CommonParameterReferenceUsageInUntyped_Mapping .....	68
7.6.2.7 CommonReturnParameterFeature_Mapping .....	68
7.6.2.8 CommonReturnParameterFeatureTyping_Mapping .....	69
7.6.2.9 CommonReturnParameterFeatureUntyped_Mapping .....	70
7.6.2.10 CommonReturnParameterFeatureMembership_Mapping .....	71
7.6.2.11 CommonReturnParameterReferenceUsageMembership_Mapping .....	71
7.6.2.12 CommonReturnParameterReferenceUsage_Mapping .....	72
7.6.2.13 CommonReturnParameterReferenceUsageFeatureTyping_Mapping .....	73
7.6.2.14 CommonReturnParameterReferenceUsageUntyped_Mapping .....	73
7.6.2.15 CommonReferenceUsageIn_Mapping .....	74
7.6.2.16 CommonReferenceUsageInFeatureMembership_Mapping .....	75
7.6.2.17 CommonReferenceUsageInFeatureTyping_Mapping .....	75
7.6.2.18 CommonReferenceUsageInUntyped_Mapping .....	76
7.6.3 Generic Mappings To KerML .....	77
7.6.3.1 GenericToAnnotatingElement_Mapping .....	77

7.5.2.3 StringParameterFeatureValue_Factory .....	53
7.5.2.4 StringParameterMembership_Factory .....	54
7.5.2.5 SubjectMembership_Factory .....	54
7.5.2.6 AssignmentActionUsage_Factory .....	55
7.5.2.7 AssignmentActionUsageFeatureMembership2_Factory .....	55
7.5.2.8 AssignmentActionUsageFeatureMembership3_Factory .....	55
7.5.2.9 AssignmentActionUsageOwningMembership_Factory .....	56
7.5.2.10 AssignmentActionUsageParameterMembership_Factory .....	56
7.5.2.11 AssignmentActionUsageReferenceUsageIn1_Factory .....	56
7.5.2.12 AssignmentActionUsageTargetReferenceUsageIn2_Factory .....	57
7.5.2.13 AssignmentActionUsageTargetReferenceUsageIn3_Factory .....	57
7.5.2.14 DirectedReferenceUsage_Factory .....	58
7.5.2.15 DirectedReferenceUsageParameterMembership_Factory .....	58
7.5.2.16 EmptyObjectiveMembership_Factory .....	59
7.5.2.17 EmptyRequirementUsage_Factory .....	59
7.5.2.18 EmptySubject_Factory .....	59
7.5.2.19 EmptySubjectMembership_Factory .....	60
7.5.2.20 FeatureTyping_Factory .....	60
7.5.2.21 FlowEndParameterMembership_Factory .....	61
7.5.2.22 FlowItem_Factory .....	61
7.5.2.23 FlowItemFeatureMembership_Factory .....	62
7.5.2.24 FlowUsage_Factory .....	62
7.5.2.25 FlowUsageFeatureMembership_Factory .....	63
7.5.2.26 InformationFlowEventOccurrenceUsage_Factory .....	63
7.5.2.27 InformationFlowReferenceSubsetting_Factory .....	64
7.5.2.28 LiteralBoolean_Factory .....	64
7.5.2.29 LiteralNull_Factory .....	65
7.5.2.30 LiteralRational_Factory .....	65
7.5.2.31 LowerBound_Factory .....	66
7.5.2.32 MultiplicityElement_Factory .....	66
7.5.2.33 MultiplicityLowerBoundMembership_Factory .....	67
7.5.2.34 MultiplicityMembership_Factory .....	67
7.5.2.35 MultiplicityUpperBoundMembership_Factory .....	68
7.5.2.36 ObjectFlowItemFlowEndRedefinition_Factory .....	68
7.5.2.37 ParameterMembership_Factory .....	69
7.5.2.38 ReferenceSubsetting_Factory .....	69
7.5.2.39 ReferenceUsage_Factory .....	69
7.5.2.40 ReturnParameterFeature_Factory .....	70
7.5.2.41 ReturnParameterFeatureMembership_Factory .....	70
7.5.2.42 Subsetting_Factory .....	71
7.5.2.43 UpperBound_Factory .....	71
7.6 Generic Mappings .....	72
7.6.1 Overview .....	72
7.6.2 Common Mappings .....	72
7.6.2.1 CommonFeatureReferenceExpression_Mapping .....	72
7.6.2.2 CommonMembership_Mapping .....	73
7.6.2.3 CommonParameterReferenceUsageInMembership_Mapping .....	73
7.6.2.4 CommonParameterReferenceUsageIn_Mapping .....	74
7.6.2.5 CommonParameterReferenceUsageInFeatureTyping_Mapping .....	75
7.6.2.6 CommonParameterReferenceUsageInUntyped_Mapping .....	76
7.6.2.7 CommonReturnParameterFeature_Mapping .....	76
7.6.2.8 CommonReturnParameterFeatureTyping_Mapping .....	77
7.6.2.9 CommonReturnParameterFeatureUntyped_Mapping .....	78
7.6.2.10 CommonReturnParameterFeatureMembership_Mapping .....	78
7.6.2.11 CommonReturnParameterReferenceUsageMembership_Mapping .....	79
7.6.2.12 CommonReturnParameterReferenceUsage_Mapping .....	80

7.6.3.2	GenericToAnnotation_Mapping	77
7.6.3.3	GenericToAssociation_Mapping	78
7.6.3.4	GenericToBehavior_Mapping	79
7.6.3.5	GenericToClassifier_Mapping	79
7.6.3.6	GenericToComment_Mapping	79
7.6.3.7	GenericToConjugation_Mapping	80
7.6.3.8	GenericToConnector_Mapping	81
7.6.3.9	GenericToDocumentation_Mapping	81
7.6.3.10	GenericToElement_Mapping	82
7.6.3.11	GenericToEndFeatureMembership_Mapping	83
7.6.3.12	GenericToExpression_Mapping	83
7.6.3.13	GenericToFeature_Mapping	83
7.6.3.14	GenericToFeatureChainExpression_Mapping	84
7.6.3.15	GenericToFeatureChaining_Mapping	85
7.6.3.16	GenericToFeatureMembership_Mapping	85
7.6.3.17	GenericToFeatureReferenceExpression_Mapping	86
7.6.3.18	GenericToFeatureTyping_Mapping	87
7.6.3.19	GenericToFeatureValue_Mapping	87
7.6.3.20	GenericToFunction_Mapping	88
7.6.3.21	GenericToImport_Mapping	88
7.6.3.22	GenericToInvocationExpression_Mapping	89
7.6.3.23	GenericToInteraction_Mapping	90
7.6.3.24	GenericToItemFlow_Mapping	90
7.6.3.25	GenericToMembership_Mapping	90
7.6.3.26	GenericToMembershipImport_Mapping	91
7.6.3.27	GenericToNamespace_Mapping	92
7.6.3.28	GenericToNamespaceImport_Mapping	92
7.6.3.29	GenericToOperatorExpression_Mapping	93
7.6.3.30	GenericToOwningMembership_Mapping	93
7.6.3.31	GenericToPackage_Mapping	94
7.6.3.32	GenericToParameterMembership_Mapping	94
7.6.3.33	GenericToPredicate_Mapping	95
7.6.3.34	GenericToRedefinition_Mapping	96
7.6.3.35	GenericToReferenceSubsetting_Mapping	96
7.6.3.36	GenericToRelationship_Mapping	97
7.6.3.37	GenericToReturnParameterMembership_Mapping	98
7.6.3.38	GenericToSpecialization_Mapping	98
7.6.3.39	GenericToStep_Mapping	99
7.6.3.40	GenericToSubclassification_Mapping	99
7.6.3.41	GenericToSubsetting_Mapping	100
7.6.3.42	GenericToSuccession_Mapping	101
7.6.3.43	GenericToSuccessionItemFlow_Mapping	101
7.6.3.44	GenericToTextualRepresentation_Mapping	101
7.6.3.45	GenericToType_Mapping	102
7.6.3.46	GenericToTypeFeaturing_Mapping	103
7.6.4	Generic Mappings to Systems	103
7.6.4.1	GenericToActionUsage_Mapping	103
7.6.4.2	GenericToActorMembership_Mapping	104
7.6.4.3	GenericToAssignmentActionUsage_Mapping	105
7.6.4.4	GenericToConnectionUsage_Mapping	105
7.6.4.5	GenericToConjugatedPortDefinition_Mapping	105
7.6.4.6	GenericToConjugatedPortTyping_Mapping	106
7.6.4.7	GenericToConstraintDefinition_Mapping	106
7.6.4.8	GenericToConstraintUsage_Mapping	107

7.6.2.13 CommonReturnParameterReferenceUsageFeatureTyping_Mapping .....	81
7.6.2.14 CommonReturnParameterReferenceUsageUntyped_Mapping .....	81
7.6.2.15 CommonReferenceUsageIn_Mapping .....	82
7.6.2.16 CommonReferenceUsageInFeatureMembership_Mapping .....	83
7.6.2.17 CommonReferenceUsageInFeatureTyping_Mapping .....	84
7.6.2.18 CommonReferenceUsageInUntyped_Mapping .....	84
7.7 Mappings from UML4SysML metaclasses .....	85
7.7.1 Overview .....	85
7.7.2 Actions .....	85
7.7.2.1 Overview .....	85
7.7.2.2 UML4SysML::Actions elements not mapped .....	87
7.7.2.3 Mapping Specifications .....	88
7.7.2.3.1 Accept Event Actions .....	88
7.7.2.3.1.1 AcceptCallAction_Mapping .....	88
7.7.2.3.1.2 AcceptEventAction_Mapping .....	88
7.7.2.3.1.3 AEChangeExpressionMembership_Mapping .....	89
7.7.2.3.1.4 AEChangeParameter_Mapping .....	90
7.7.2.3.1.5 AEChangeParameterFeatureValue_Mapping .....	91
7.7.2.3.1.6 AEChangeParameterTrigger_Mapping .....	91
7.7.2.3.1.7 AEChangeParameterTriggerExpression_Mapping .....	92
7.7.2.3.1.8 AEChangeParameterResultExpressionMembership_Mapping .....	93
7.7.2.3.1.9 AEChangeParameterFeatureChainExpression_Mapping .....	93
7.7.2.3.1.10 AEChangeParameterFeatureMembership_Mapping .....	94
7.7.2.3.1.11 AEChangeParameterFeature_Mapping .....	95
7.7.2.3.1.12 AEChangeParameterExpressionFeatureValue_Mapping .....	95
7.7.2.3.1.13 AEChangeParameterFeatureReferenceExpression_Mapping .....	96
7.7.2.3.1.14 AEChangeParameterMembership_Mapping .....	97
7.7.2.3.1.15 AEChangeParameterParameterMembership_Mapping .....	97
7.7.2.3.1.16 AEAReceiverParameter_Mapping .....	98
7.7.2.3.1.17 AEAReceiverParameterMembership_Mapping .....	99
7.7.2.3.1.18 AEAReceiverFeatureValue_Mapping .....	100
7.7.2.3.1.19 AEASignalParameter_Mapping .....	100
7.7.2.3.1.20 AEASignalParameterFeatureTyping_Mapping .....	101
7.7.2.3.1.21 AEAParameterMembership_Mapping .....	102
7.7.2.3.1.22 AEAReceiverFeatureReferenceExpression_Mapping .....	103
7.7.2.3.1.23 AEAReceiverFeatureReferenceExpressionMembership_Mapping .....	103
7.7.2.3.1.24 ReplyAction_Mapping .....	104
7.7.2.3.1.25 UnmarshallAction_Mapping .....	104
7.7.2.3.2 Actions .....	105
7.7.2.3.2.1 CommonAction_Mapping .....	105
7.7.2.3.2.2 OpaqueAction_Mapping .....	106
7.7.2.3.2.3 OABody_Mapping .....	107
7.7.2.3.2.4 OABodyMembership_Mapping .....	108
7.7.2.3.2.5 Pin_Mapping .....	108
7.7.2.3.2.6 ValuePin_Mapping .....	109
7.7.2.3.2.7 ValuePinFeatureValue_Mapping .....	110
7.7.2.3.2.8 ValuePinUntyped_Mapping .....	111
7.7.2.3.3 Invocation Actions .....	112
7.7.2.3.3.1 BroadcastSignalAction_Mapping .....	112
7.7.2.3.3.2 CallBehaviorAction_Mapping .....	112
7.7.2.3.3.3 CBAFeatureTyping_Mapping .....	113
7.7.2.3.3.4 CallOperationAction_Mapping .....	114
7.7.2.3.3.5 COAOutputPinFeature_Mapping .....	114
7.7.2.3.3.6 COAOutputPinFeatureChainExpression_Mapping .....	115
7.7.2.3.3.7 COAOutputPinFeatureChainExpressionMembership_Mapping .....	116
7.7.2.3.3.8 COAOutputPinFeatureFeature_Mapping .....	117

7.6.4.9 GenericToDefinition_Mapping .....	107
7.6.4.10 GenericToEventOccurrenceUsage_Mapping .....	108
7.6.4.11 GenericToItemDefinition_Mapping .....	108
7.6.4.12 GenericToItemUsage .....	109
7.6.4.13 GenericToMetadataUsage_Mapping .....	109
7.6.4.14 GenericToObjectiveMembership_Mapping .....	109
7.6.4.15 GenericToOccurrenceDefinition_Mapping .....	110
7.6.4.16 GenericToOccurrenceUsage_Mapping .....	110
7.6.4.17 GenericToPartUsage_Mapping .....	111
7.6.4.18 GenericToPortConjugation_Mapping .....	111
7.6.4.19 GenericToPortDefinition_Mapping .....	112
7.6.4.20 GenericToReferenceUsage_Mapping .....	112
7.6.4.21 GenericToRequirementUsage_Mapping .....	113
7.6.4.22 GenericToStateUsage_Mapping .....	113
7.6.4.23 GenericToSubjectMembership_Mapping .....	114
7.6.4.24 GenericToTransitionUsage_Mapping .....	114
7.6.4.25 GenericToUsage_Mapping .....	114
7.7 Mappings from UML4SysML metaclasses .....	115
7.7.1 Overview .....	115
7.7.2 Actions .....	115
7.7.2.1 Overview .....	115
7.7.2.2 UML4SysML::Actions elements not mapped .....	117
7.7.2.3 Mapping Specifications .....	118
7.7.2.3.1 Accept Event Actions .....	118
7.7.2.3.1.1 AcceptCallAction_Mapping .....	118
7.7.2.3.1.2 AcceptEventAction_Mapping .....	118
7.7.2.3.1.3 AEChangeExpressionMembership_Mapping .....	119
7.7.2.3.1.4 AEChangeParameter_Mapping .....	120
7.7.2.3.1.5 AEChangeParameterFeatureValue_Mapping .....	121
7.7.2.3.1.6 AEChangeParameterTrigger_Mapping .....	121
7.7.2.3.1.7 AEChangeParameterTriggerExpression_Mapping .....	122
7.7.2.3.1.8 AEChangeParameterResultExpressionMembership_Mapping .....	123
7.7.2.3.1.9 AEChangeParameterFeatureChainExpression_Mapping .....	123
7.7.2.3.1.10 AEChangeParameterFeature_Mapping .....	124
7.7.2.3.1.11 AEChangeParameterExpressionFeatureValue_Mapping .....	125
7.7.2.3.1.12 AEChangeParameterFeatureReferenceExpression_Mapping .....	125
7.7.2.3.1.13 AEChangeParameterMembership_Mapping .....	126
7.7.2.3.1.14 AEChangeParameterParameterMembership_Mapping .....	126
7.7.2.3.1.15 AEReceiverParameter_Mapping .....	127
7.7.2.3.1.16 AEReceiverParameterMembership_Mapping .....	128
7.7.2.3.1.17 AEReceiverFeatureValue_Mapping .....	128
7.7.2.3.1.18 AESignalParameter_Mapping .....	129
7.7.2.3.1.19 AESignalParameterFeatureTyping_Mapping .....	130
7.7.2.3.1.20 AEAParameterMembership_Mapping .....	130
7.7.2.3.1.21 AEReceiverFeatureReferenceExpression_Mapping .....	131
7.7.2.3.1.22 AEReceiverFeatureReferenceExpressionMembership_Mapping .....	132
7.7.2.3.1.23 ReplyAction_Mapping .....	133
7.7.2.3.1.24 UnmarshallAction_Mapping .....	133
7.7.2.3.2 Actions .....	133
7.7.2.3.2.1 CommonAction_Mapping .....	133
7.7.2.3.2.2 OpaqueAction_Mapping .....	134
7.7.2.3.2.3 OABody_Mapping .....	135
7.7.2.3.2.4 OABodyMembership_Mapping .....	136
7.7.2.3.2.5 Pin_Mapping .....	137





7.7.2.3.2.6 ValuePin_Mapping.....	138
7.7.2.3.2.7 ValuePinFeatureValue_Mapping .....	139
7.7.2.3.2.8 ValuePinUntyped_Mapping.....	139
7.7.2.3.3 Invocation Actions .....	140
7.7.2.3.3.1 BroadcastSignalAction_Mapping.....	140
7.7.2.3.3.2 CallBehaviorAction_Mapping .....	140
7.7.2.3.3.3 CBAFeatureTyping_Mapping.....	141
7.7.2.3.3.4 CallOperationAction_Mapping .....	142
7.7.2.3.3.5 COAOutputPinFeature_Mapping.....	143
7.7.2.3.3.6 COAOutputPinFeatureChainExpression_Mapping .....	143
7.7.2.3.3.7 COAOutputPinFeatureChainExpressionMembership_Mapping .....	144
7.7.2.3.3.8 COAOutputPinFeatureFeature_Mapping.....	145
7.7.2.3.3.9 COAOutputPinFeatureFeatureMembership_Mapping.....	145
7.7.2.3.3.10 COAOutputPinFeatureFeatureValue_Mapping .....	146
7.7.2.3.3.11 COAOutputPinFeatureMembership_Mapping.....	146
7.7.2.3.3.12 COAOutputPinFeatureReferenceExpression_Mapping.....	147
7.7.2.3.3.13 COAOutputPinFeatureReferenceExpressionMembership_Mapping.....	148
7.7.2.3.3.14 COAOutputPinParameterMembership_Mapping .....	148
7.7.2.3.3.15 COAOutputPinReferenceUsage_Mapping.....	149
7.7.2.3.3.16 COAOutputPinReferenceUsageFeatureValue_Mapping.....	149
7.7.2.3.3.17 COAPerformAction_Mapping .....	150
7.7.2.3.3.18 COAPerformActionFeatureMembership_Mapping.....	151
7.7.2.3.3.19 COAPerformActionReferenceSubsetting_Mapping .....	151
7.7.2.3.3.20 COAPerformActionFeature_Mapping .....	152
7.7.2.3.3.21 COAPerformActionFeatureChainingOperation_Mapping.....	153
7.7.2.3.3.22 COAPerformActionFeatureChainingTarget_Mapping.....	153
7.7.2.3.3.23 SendObjectAction_Mapping.....	154
7.7.2.3.3.24 SendSignalAction_Mapping.....	154
7.7.2.3.3.25 SSAFeatureMembership_Mapping .....	155
7.7.2.3.3.26 SSAParameterMembership_Mapping.....	156
7.7.2.3.3.27 SSAResourceUsage_Mapping .....	156
7.7.2.3.3.28 SSAItemParameterMembership_Mapping.....	157
7.7.2.3.3.29 SSAItemResourceUsage_Mapping.....	158
7.7.2.3.3.30 SSAItemResourceUsageFeatureValue_Mapping .....	158
7.7.2.3.3.31 SSAItemResourceUsageFeatureTyping_Mapping .....	159
7.7.2.3.3.32 SSAItemResourceUsageInvocationExpression_Mapping.....	160
7.7.2.3.3.33 SSATargetParameterMembership_Mapping .....	160
7.7.2.3.3.34 SSATargetResourceUsage_Mapping.....	161
7.7.2.3.3.35 SSATargetResourceUsageFeatureValue_Mapping .....	162
7.7.2.3.3.36 SSATargetResourceUsageFeatureValueMembership_Mapping.....	162
7.7.2.3.3.37 SSATargetResourceUsageFeatureValueExpression_Mapping .....	163
7.7.2.3.3.38 SSASendActionUsage_Mapping .....	163
7.7.2.3.3.39 StartClassifierBehaviorAction_Mapping .....	164
7.7.2.3.3.40 StartObjectBehaviorAction_Mapping.....	165
7.7.2.3.4 Link Actions .....	165
7.7.2.3.4.1 ClearAssociationAction_Mapping .....	165
7.7.2.3.4.2 CreateLinkAction_Mapping.....	165
7.7.2.3.4.3 CreateLinkObjectAction_Mapping.....	166
7.7.2.3.4.4 DestroyLinkAction_Mapping.....	167
7.7.2.3.4.5 ReadLinkAction_Mapping.....	167
7.7.2.3.4.6 ReadLinkObjectEndAction_Mapping.....	168
7.7.2.3.4.7 ReadLinkObjectEndQualifierAction_Mapping .....	169
7.7.2.3.5 Object Actions .....	169
7.7.2.3.5.1 CreateObjectAction_Mapping.....	169

7.7.2.3.3.9 COAOutputPinFeatureFeatureMembership_Mapping.....	117
7.7.2.3.3.10 COAOutputPinFeatureFeatureValue_Mapping .....	118
7.7.2.3.3.11 COAOutputPinFeatureMembership_Mapping.....	118
7.7.2.3.3.12 COAOutputPinFeatureReferenceExpression_Mapping.....	119
7.7.2.3.3.13 COAOutputPinFeatureReferenceExpressionMembership_Mapping.....	120
7.7.2.3.3.14 COAOutputPinParameterMembership_Mapping .....	120
7.7.2.3.3.15 COAOutputPinReferenceUsage_Mapping.....	121
7.7.2.3.3.16 COAOutputPinReferenceUsageFeatureValue_Mapping .....	122
7.7.2.3.3.17 COAPerformAction_Mapping .....	123
7.7.2.3.3.18 COAPerformActionFeatureMembership_Mapping .....	123
7.7.2.3.3.19 COAPerformActionReferenceSubsetting_Mapping .....	124
7.7.2.3.3.20 COAPerformActionFeature_Mapping .....	125
7.7.2.3.3.21 COAPerformActionFeatureChainingOperation_Mapping.....	125
7.7.2.3.3.22 COAPerformActionFeatureChainingTarget_Mapping .....	126
7.7.2.3.3.23 SendObjectAction_Mapping.....	127
7.7.2.3.3.24 SendSignalAction_Mapping.....	127
7.7.2.3.3.25 SSAFeatureMembership_Mapping .....	128
7.7.2.3.3.26 SSAParameterMembership_Mapping .....	129
7.7.2.3.3.27 SSAResourceUsage_Mapping .....	129
7.7.2.3.3.28 SSAItemParameterMembership_Mapping.....	130
7.7.2.3.3.29 SSAItemResourceUsage_Mapping .....	131
7.7.2.3.3.30 SSAItemResourceUsageFeatureValue_Mapping .....	131
7.7.2.3.3.31 SSAItemResourceUsageFeatureTyping_Mapping .....	132
7.7.2.3.3.32 SSAItemResourceUsageInvocationExpression_Mapping.....	133
7.7.2.3.3.33 SSATargetParameterMembership_Mapping .....	134
7.7.2.3.3.34 SSATargetResourceUsage_Mapping.....	134
7.7.2.3.3.35 SSATargetResourceUsageFeatureValue_Mapping .....	135
7.7.2.3.3.36 SSATargetResourceUsageFeatureValueMembership_Mapping.....	136
7.7.2.3.3.37 SSATargetResourceUsageFeatureValueExpression_Mapping .....	136
7.7.2.3.3.38 SSASendActionUsage_Mapping .....	137
7.7.2.3.3.39 StartClassifierBehaviorAction_Mapping .....	138
7.7.2.3.3.40 StartObjectBehaviorAction_Mapping .....	138
7.7.2.3.4 Link Actions .....	139
7.7.2.3.4.1 ClearAssociationAction_Mapping .....	139
7.7.2.3.4.2 CreateLinkAction_Mapping.....	139
7.7.2.3.4.3 CreateLinkObjectAction_Mapping .....	140
7.7.2.3.4.4 DestroyLinkAction_Mapping.....	140
7.7.2.3.4.5 ReadLinkAction_Mapping.....	141
7.7.2.3.4.6 ReadLinkObjectEndAction_Mapping.....	142
7.7.2.3.4.7 ReadLinkObjectEndQualifierAction_Mapping .....	143
7.7.2.3.5 Object Actions .....	143
7.7.2.3.5.1 CreateObjectAction_Mapping.....	143
7.7.2.3.5.2 COAInvocationExpressionFeatureTyping_Mapping .....	144
7.7.2.3.5.3 COAInvocationExpression_Mapping .....	144
7.7.2.3.5.4 COAPin_Mapping .....	145
7.7.2.3.5.5 COAPinFeatureValue_Mapping .....	146
7.7.2.3.5.6 DestroyObjectAction_Mapping .....	146
7.7.2.3.5.7 DOADestroyActionUsage_Mapping .....	147
7.7.2.3.5.8 DOADestroyActionUsageFeatureMembership_Mapping .....	148
7.7.2.3.5.9 DOADestroyActionUsageFeatureReferenceExpression_Mapping .....	149
7.7.2.3.5.10 DOADestroyActionUsageMembership_Mapping .....	149
7.7.2.3.5.11 DOADestroyActionUsageFeatureTyping_Mapping.....	150
7.7.2.3.5.12 DOADestroyActionUsageFeatureValue_Mapping.....	151
7.7.2.3.5.13 DOADestroyActionUsageResourceUsage_Mapping .....	151
7.7.2.3.5.14 DOADestroyFeatureMembership_Mapping .....	152
7.7.2.3.5.15 ReadIsClassifiedObjectAction_Mapping .....	153

7.7.2.3.5.2 COAInvocationExpressionFeatureTyping_Mapping .....	170
7.7.2.3.5.3 COAInvocationExpression_Mapping .....	170
7.7.2.3.5.4 COAPin_Mapping .....	171
7.7.2.3.5.5 COAPinFeatureValue_Mapping .....	172
7.7.2.3.5.6 DestroyObjectAction_Mapping .....	172
7.7.2.3.5.7 DOADestroyActionUsage_Mapping .....	173
7.7.2.3.5.8 DOADestroyActionUsageFeatureMembership_Mapping .....	174
7.7.2.3.5.9 DOADestroyActionUsageFeatureReferenceExpression_Mapping .....	174
7.7.2.3.5.10 DOADestroyActionUsageMembership_Mapping .....	175
7.7.2.3.5.11 DOADestroyActionUsageFeatureTyping_Mapping .....	176
7.7.2.3.5.12 DOADestroyActionUsageFeatureValue_Mapping .....	176
7.7.2.3.5.13 DOADestroyActionUsageReferenceUsage_Mapping .....	177
7.7.2.3.5.14 DOADestroyFeatureMembership_Mapping .....	178
7.7.2.3.5.15 ReadIsClassifiedObjectAction_Mapping .....	178
7.7.2.3.5.16 RICOAFeatureValue_Mapping .....	179
7.7.2.3.5.17 RICOAFeatureValueOperatorExpression_Mapping .....	180
7.7.2.3.5.18 RICOAFeatureValueOperatorExpressionFeature_Mapping .....	180
7.7.2.3.5.19 RICOAFeatureValueOperatorExpressionFeatureValue_Mapping .....	181
7.7.2.3.5.20 RICOAFeatureValueOperatorFeatureReferenceExpression_Mapping .....	182
7.7.2.3.5.21 RICOAFeatureValueOperatorMembership_Mapping .....	182
7.7.2.3.5.22 RICOAFeatureValueOperatorParameterMembership_Mapping .....	183
7.7.2.3.5.23 RICOAOutputPin_Mapping .....	183
7.7.2.3.5.24 ReadExtentAction_Mapping .....	184
7.7.2.3.5.25 REAFeatureValue_Mapping .....	185
7.7.2.3.5.26 REAFeatureValueOperatorExpression_Mapping .....	185
7.7.2.3.5.27 REAFeatureValueOperatorExpressionFeature_Mapping .....	186
7.7.2.3.5.28 REAFeatureValueOperatorExpressionFeatureTyping_Mapping .....	187
7.7.2.3.5.29 REAFeatureValueOperatorExpressionMembership_Mapping .....	187
7.7.2.3.5.30 REAOutputPin_Mapping .....	188
7.7.2.3.5.31 ReadSelfAction_Mapping .....	189
7.7.2.3.5.32 RSAFeatureValue_Mapping .....	189
7.7.2.3.5.33 RSAFeatureValueFeatureReferenceExpression_Mapping .....	190
7.7.2.3.5.34 RSAFeatureValueMembership_Mapping .....	191
7.7.2.3.5.35 RSAOutputPin_Mapping .....	191
7.7.2.3.5.36 ReclassifyObjectAction_Mapping .....	192
7.7.2.3.5.37 TestIdentityAction_Mapping .....	192
7.7.2.3.5.38 TIAOperatorExpression_Mapping .....	193
7.7.2.3.5.39 TIAResultExpressionMembership_Mapping .....	194
7.7.2.3.5.40 ValueSpecificationAction_Mapping .....	195
7.7.2.3.5.41 VSAOutputPin_Mapping .....	196
7.7.2.3.5.42 VSAOutputPinFeatureValue_Mapping .....	197
7.7.2.3.6 Other Actions .....	197
7.7.2.3.6.1 RaiseExceptionAction_Mapping .....	197
7.7.2.3.6.2 ReduceAction_Mapping .....	198
7.7.2.3.7 Structural Feature Actions .....	198
7.7.2.3.7.1 AddStructuralFeatureValueAction_Mapping .....	198
7.7.2.3.7.2 ASFVAFeatureTyping_Mapping .....	199
7.7.2.3.7.3 ASFVAObjectFeatureMembership_Mapping .....	200
7.7.2.3.7.4 ASFVAObjectReferenceUsage_Mapping .....	200
7.7.2.3.7.5 ASFVAObjectReferenceUsageFeatureTyping_Mapping .....	201
7.7.2.3.7.6 ASFVAObjectReferenceUsageRedefinition_Mapping .....	201
7.7.2.3.7.7 ASFVATargetFeatureChainExpression_Mapping .....	202
7.7.2.3.7.8 ASFVATargetFeatureMembership_Mapping .....	203
7.7.2.3.7.9 ASFVATargetFeatureValue_Mapping .....	203

7.7.2.3.5.16 RICOAFeatureValue_Mapping.....	153
7.7.2.3.5.17 RICOAFeatureValueOperatorExpression_Mapping.....	154
7.7.2.3.5.18 RICOAFeatureValueOperatorExpressionFeature_Mapping.....	155
7.7.2.3.5.19 RICOAFeatureValueOperatorExpressionFeatureValue_Mapping.....	156
7.7.2.3.5.20 RICOAFeatureValueOperatorFeatureReferenceExpression_Mapping.....	156
7.7.2.3.5.21 RICOAFeatureValueOperatorMembership_Mapping.....	157
7.7.2.3.5.22 RICOAFeatureValueOperatorParameterMembership_Mapping.....	157
7.7.2.3.5.23 RICOAOutputPin_Mapping.....	158
7.7.2.3.5.24 ReadExtentAction_Mapping.....	159
7.7.2.3.5.25 REAFeatureValue_Mapping.....	160
7.7.2.3.5.26 REAFeatureValueOperatorExpression_Mapping.....	160
7.7.2.3.5.27 REAFeatureValueOperatorExpressionFeature_Mapping.....	161
7.7.2.3.5.28 REAFeatureValueOperatorExpressionFeatureTyping_Mapping.....	162
7.7.2.3.5.29 REAFeatureValueOperatorExpressionMembership_Mapping.....	163
7.7.2.3.5.30 REAOutputPin_Mapping.....	163
7.7.2.3.5.31 ReadSelfAction_Mapping.....	164
7.7.2.3.5.32 RSAFeatureValue_Mapping.....	165
7.7.2.3.5.33 RSAFeatureValueFeatureReferenceExpression_Mapping.....	165
7.7.2.3.5.34 RSAFeatureValueMembership_Mapping.....	166
7.7.2.3.5.35 RSAOutputPin_Mapping.....	167
7.7.2.3.5.36 ReclassifyObjectAction_Mapping.....	167
7.7.2.3.5.37 TestIdentityAction_Mapping.....	168
7.7.2.3.5.38 TIAOperatorExpression_Mapping.....	169
7.7.2.3.5.39 TIAResultExpressionMembership_Mapping.....	169
7.7.2.3.5.40 ValueSpecificationAction_Mapping.....	170
7.7.2.3.5.41 VSAOutputPin_Mapping.....	171
7.7.2.3.5.42 VSAOutputPinFeatureValue_Mapping.....	172
7.7.2.3.6 Other Actions.....	173
7.7.2.3.6.1 RaiseExceptionAction_Mapping.....	173
7.7.2.3.6.2 ReduceAction_Mapping.....	173
7.7.2.3.7 Structural Feature Actions.....	174
7.7.2.3.7.1 AddStructuralFeatureValueAction_Mapping.....	174
7.7.2.3.7.2 ASFVAFeatureTyping_Mapping.....	174
7.7.2.3.7.3 ASFVAObjectFeatureMembership_Mapping.....	175
7.7.2.3.7.4 ASFVAObjectReferenceUsage_Mapping.....	176
7.7.2.3.7.5 ASFVAObjectReferenceUsageFeatureTyping_Mapping.....	176
7.7.2.3.7.6 ASFVAObjectReferenceUsageRedefinition_Mapping.....	177
7.7.2.3.7.7 ASFVATargetFeatureChainExpression_Mapping.....	178
7.7.2.3.7.8 ASFVATargetFeatureMembership_Mapping.....	179
7.7.2.3.7.9 ASFVATargetFeatureValue_Mapping.....	179
7.7.2.3.7.10 ASFVATargetParameterExpressionFeature_Mapping.....	180
7.7.2.3.7.11 ASFVATargetParameterExpressionFeatureMembership_Mapping.....	180
7.7.2.3.7.12 ASFVATargetParameterExpressionMembership_Mapping.....	181
7.7.2.3.7.13 ASFVATargetParameterFeature_Mapping.....	182
7.7.2.3.7.14 ASFVATargetParameterFeatureExpressionMembership_Mapping.....	183
7.7.2.3.7.15 ASFVATargetParameterFeatureReferenceExpression_Mapping.....	183
7.7.2.3.7.16 ASFVATargetParameterFeatureValue_Mapping.....	184
7.7.2.3.7.17 ASFVATargetParameterMembership_Mapping.....	185
7.7.2.3.7.18 ASFVATargetReferenceUsage_Mapping.....	185
7.7.2.3.7.19 ASFVATargetReferenceUsageRedefinition_Mapping.....	186
7.7.2.3.7.20 ClearStructuralFeatureAction_Mapping.....	187
7.7.2.3.7.21 ReadStructuralFeatureAction_Mapping.....	187
7.7.2.3.7.22 RSFAReferenceUsage_Mapping.....	188
7.7.2.3.7.23 RSFAReferenceUsageExpressionFeature_Mapping.....	189
7.7.2.3.7.24 RSFAReferenceUsageExpressionFeatureMembership_Mapping.....	190
7.7.2.3.7.25 RSFAReferenceUsageExpressionFeatureReferenceExpression_Mapping.....	190

7.7.2.3.7.10 ASFVATargetParameterExpressionFeature_Mapping .....	204
7.7.2.3.7.11 ASFVATargetParameterExpressionFeatureMembership_Mapping .....	204
7.7.2.3.7.12 ASFVATargetParameterExpressionMembership_Mapping .....	205
7.7.2.3.7.13 ASFVATargetParameterFeature_Mapping .....	206
7.7.2.3.7.14 ASFVATargetParameterFeatureExpressionMembership_Mapping .....	206
7.7.2.3.7.15 ASFVATargetParameterFeatureReferenceExpression_Mapping .....	207
7.7.2.3.7.16 ASFVATargetParameterFeatureValue_Mapping .....	208
7.7.2.3.7.17 ASFVATargetParameterMembership_Mapping .....	208
7.7.2.3.7.18 ASFVATargetReferenceUsage_Mapping .....	209
7.7.2.3.7.19 ASFVATargetReferenceUsageRedefinition_Mapping .....	210
7.7.2.3.7.20 ClearStructuralFeatureAction_Mapping .....	210
7.7.2.3.7.21 ReadStructuralFeatureAction_Mapping .....	211
7.7.2.3.7.22 RSFReferenceUsage_Mapping .....	212
7.7.2.3.7.23 RSFReferenceUsageExpressionFeature_Mapping .....	212
7.7.2.3.7.24 RSFReferenceUsageExpressionFeatureMembership_Mapping .....	213
7.7.2.3.7.25 RSFReferenceUsageExpressionFeatureReferenceExpression_Mapping .....	214
7.7.2.3.7.26 RSFReferenceUsageExpressionFeatureValue_Mapping .....	214
7.7.2.3.7.27 RSFReferenceUsageFeatureChainExpression_Mapping .....	215
7.7.2.3.7.28 RSFReferenceUsageFeatureChainExpressionFeature_Mapping .....	216
7.7.2.3.7.29 RSFReferenceUsageFeatureChainExpressionMembership_Mapping .....	216
7.7.2.3.7.30 RSFReferenceUsageFeatureMembership_Mapping .....	217
7.7.2.3.7.31 RSFReferenceUsageFeatureValue_Mapping .....	217
7.7.2.3.7.32 RSFReferenceUsageMembership_Mapping .....	218
7.7.2.3.7.33 RSFReferenceUsageParameterMembership_Mapping .....	218
7.7.2.3.7.34 RemoveStructuralFeatureValueAction_Mapping .....	219
7.7.2.3.8 Structured Actions .....	219
7.7.2.3.8.1 LoopNode_Mapping .....	220
7.7.2.3.8.2 SequenceNode_Mapping .....	220
7.7.2.3.8.3 StructuredActivityNode_Mapping .....	220
7.7.2.3.9 Variable Actions .....	221
7.7.2.3.9.1 AddVariableValueAction_Mapping .....	221
7.7.2.3.9.2 AVVAFeatureTyping_Mapping .....	223
7.7.2.3.9.3 AVVAFeatureValue_Mapping .....	223
7.7.2.3.9.4 AVVAIsReplaceAll_Mapping .....	224
7.7.2.3.9.5 AVVAIsReplaceAllFeatureMembership_Mapping .....	224
7.7.2.3.9.6 AVVAIsReplaceAllRedefinition_Mapping .....	225
7.7.2.3.9.7 AVVAIsReplaceAllValue_Mapping .....	226
7.7.2.3.9.8 AVVAValueExpressionMembership_Mapping .....	226
7.7.2.3.9.9 AVVAValueFeatureReferenceExpression_Mapping .....	227
7.7.2.3.9.10 AVVAVariable_Mapping .....	228
7.7.2.3.9.11 AVVAVariableFeatureMembership_Mapping .....	228
7.7.2.3.9.12 AVVAVariableRedefinition_Mapping .....	229
7.7.2.3.9.13 ClearVariableAction_Mapping .....	229
7.7.2.3.9.14 CVAFeatureMembership_Mapping .....	230
7.7.2.3.9.15 CVAReferenceUsage_Mapping .....	231
7.7.2.3.9.16 CVAReferenceUsageFeatureValue_Mapping .....	232
7.7.2.3.9.17 ReadVariableAction_Mapping .....	232
7.7.2.3.9.18 RVAFeatureMembership_Mapping .....	233
7.7.2.3.9.19 RVAReferenceUsage_Mapping .....	234
7.7.2.3.9.20 RVAReferenceUsageFeatureReferenceExpression_Mapping .....	234
7.7.2.3.9.21 RVAReferenceUsageFeatureTyping_Mapping .....	235
7.7.2.3.9.22 RVAReferenceUsageFeatureValue_Mapping .....	235
7.7.2.3.9.23 RVAReferenceUsageExpressionMembership_Mapping .....	236
7.7.2.3.9.24 RemoveVariableValueAction_Mapping .....	237

7.7.2.3.7.26 RSFReferenceUsageExpressionFeatureValue_Mapping .....	191
7.7.2.3.7.27 RSFReferenceUsageFeatureChainExpression_Mapping .....	192
7.7.2.3.7.28 RSFReferenceUsageFeatureChainExpressionFeature_Mapping .....	192
7.7.2.3.7.29 RSFReferenceUsageFeatureChainExpressionMembership_Mapping .....	193
7.7.2.3.7.30 RSFReferenceUsageFeatureMembership_Mapping .....	194
7.7.2.3.7.31 RSFReferenceUsageFeatureValue_Mapping .....	194
7.7.2.3.7.32 RSFReferenceUsageMembership_Mapping .....	195
7.7.2.3.7.33 RSFReferenceUsageParameterMembership_Mapping .....	196
7.7.2.3.7.34 RemoveStructuralFeatureValueAction_Mapping .....	196
7.7.2.3.8 Structured Actions .....	197
7.7.2.3.8.1 LoopNode_Mapping .....	197
7.7.2.3.8.2 SequenceNode_Mapping .....	197
7.7.2.3.8.3 StructuredActivityNode_Mapping .....	198
7.7.2.3.9 Variable Actions .....	199
7.7.2.3.9.1 AddVariableValueAction_Mapping .....	199
7.7.2.3.9.2 AVVAFeatureTyping_Mapping .....	200
7.7.2.3.9.3 AVVAFeatureValue_Mapping .....	200
7.7.2.3.9.4 AVVAIsReplaceAll_Mapping .....	201
7.7.2.3.9.5 AVVAIsReplaceAllFeatureMembership_Mapping .....	202
7.7.2.3.9.6 AVVAIsReplaceAllRedefinition_Mapping .....	203
7.7.2.3.9.7 AVVAIsReplaceAllValue_Mapping .....	203
7.7.2.3.9.8 AVVAValueExpressionMembership_Mapping .....	204
7.7.2.3.9.9 AVVAValueFeatureReferenceExpression_Mapping .....	205
7.7.2.3.9.10 AVVAVariable_Mapping .....	205
7.7.2.3.9.11 AVVAVariableFeatureMembership_Mapping .....	206
7.7.2.3.9.12 AVVAVariableRedefinition_Mapping .....	207
7.7.2.3.9.13 ClearVariableAction_Mapping .....	207
7.7.2.3.9.14 CVAFeatureMembership_Mapping .....	208
7.7.2.3.9.15 CVAResourceUsage_Mapping .....	209
7.7.2.3.9.16 CVAResourceUsageFeatureValue_Mapping .....	210
7.7.2.3.9.17 ReadVariableAction_Mapping .....	210
7.7.2.3.9.18 RVAFeatureMembership_Mapping .....	211
7.7.2.3.9.19 RVAResourceUsage_Mapping .....	212
7.7.2.3.9.20 RVAResourceUsageFeatureReferenceExpression_Mapping .....	212
7.7.2.3.9.21 RVAResourceUsageFeatureTyping_Mapping .....	213
7.7.2.3.9.22 RVAResourceUsageFeatureValue_Mapping .....	214
7.7.2.3.9.23 RVAResourceUsageExpressionMembership_Mapping .....	214
7.7.2.3.9.24 RemoveVariableValueAction_Mapping .....	215
7.7.2.3.9.25 RVVAFeatureTyping_Mapping .....	216
7.7.2.3.9.26 RVVAVariable_Mapping .....	217
7.7.2.3.9.27 RVVAVariableExpressionMembership_Mapping .....	217
7.7.2.3.9.28 RVVAVariableFeatureMembership_Mapping .....	218
7.7.2.3.9.29 RVVAVariableFeatureReferenceExpression_Mapping .....	219
7.7.2.3.9.30 RVVAVariableFeatureValue_Mapping .....	219
7.7.2.3.9.31 RVVAVariableRedefinition_Mapping .....	220
7.7.3 Activities .....	221
7.7.3.1 Overview .....	221
7.7.3.2 UML4SysML::Activities elements not mapped .....	221
7.7.3.3 Mapping Specifications .....	222
7.7.3.3.1 ActivityAsDefinition_Mapping .....	222
7.7.3.3.2 ActivityEdgeInitialNodeFeatureMembership_Mapping .....	223
7.7.3.3.3 ActivityEdgeMetadata_Mapping .....	223
7.7.3.3.4 ActivityEdgeMetadataFeatureMembership_Mapping .....	224
7.7.3.3.5 ActivityEdgeMetadataFeatureTyping_Mapping .....	225
7.7.3.3.6 ActivityEdgeMetadataFeatureValue_Mapping .....	226
7.7.3.3.7 ActivityEdgeMetadataOwningMembership_Mapping .....	226



7.7.2.3.9.25 RVVAFeatureTyping_Mapping.....	238
7.7.2.3.9.26 RVVAVariable_Mapping.....	238
7.7.2.3.9.27 RVVAVariableExpressionMembership_Mapping.....	239
7.7.2.3.9.28 RVVAVariableFeatureMembership_Mapping.....	239
7.7.2.3.9.29 RVVAVariableFeatureReferenceExpression_Mapping.....	240
7.7.2.3.9.30 RVVAVariableFeatureValue_Mapping.....	241
7.7.2.3.9.31 RVVAVariableRedefinition_Mapping.....	241
7.7.3 Activities.....	242
7.7.3.1 Overview.....	242
7.7.3.2 UML4SysML::Activities elements not mapped.....	243
7.7.3.3 Mapping Specifications.....	243
7.7.3.3.1 ActivityAsDefinition_Mapping.....	243
7.7.3.3.2 ActivityEdgeInitialNodeFeatureMembership_Mapping.....	244
7.7.3.3.3 ActivityEdgeMetadata_Mapping.....	245
7.7.3.3.4 ActivityEdgeMetadataFeatureMembership_Mapping.....	246
7.7.3.3.5 ActivityEdgeMetadataFeatureTyping_Mapping.....	246
7.7.3.3.6 ActivityEdgeMetadataFeatureValue_Mapping.....	247
7.7.3.3.7 ActivityEdgeMetadataOwningMembership_Mapping.....	247
7.7.3.3.8 ActivityEdgeMetadataRedefinition_Mapping.....	248
7.7.3.3.9 ActivityEdgeMetadataReferenceUsage_Mapping.....	249
7.7.3.3.10 ActivityEdgeSourceEndFeature_Mapping.....	249
7.7.3.3.11 ActivityEdgeSourceInitialNode_Mapping.....	250
7.7.3.3.12 ActivityEdgeSourceEndFeatureMembership_Mapping.....	251
7.7.3.3.13 ActivityEdgeSourceInitialNodeSubsetting_Mapping.....	251
7.7.3.3.14 ActivityEdgeSourceEndSubsetting_Mapping.....	252
7.7.3.3.15 ActivityEdgeTransitionUsageSourceMembership_Mapping.....	253
7.7.3.3.16 CentralBufferNode_Mapping.....	253
7.7.3.3.17 CommonActivityEdgeSuccessionAsUsage_Mapping.....	254
7.7.3.3.18 CommonVariable_Mapping.....	255
7.7.3.3.19 ControlFlowTransitionUsage_Mapping.....	256
7.7.3.3.20 ControlFlowFinalNodeFeatureMembership_Mapping.....	257
7.7.3.3.21 ControlFlowTargetFinalNodeSubsetting_Mapping.....	258
7.7.3.3.22 ControlFlowSuccessionAsUsage_Mapping.....	258
7.7.3.3.23 ControlFlowTargetFinalNode_Mapping.....	260
7.7.3.3.24 ControlFlowTargetEndFeature_Mapping.....	261
7.7.3.3.25 ControlFlowTargetFeatureMembership_Mapping.....	261
7.7.3.3.26 ControlFlowTargetEndSubsetting_Mapping.....	262
7.7.3.3.27 ControlFlowTransitionUsageFeatureMembership_Mapping.....	263
7.7.3.3.28 DataStoreNode_Mapping.....	263
7.7.3.3.29 DecisionNode_Mapping.....	264
7.7.3.3.30 FlowFinalNodeMembership_Mapping.....	265
7.7.3.3.31 ForkNode_Mapping.....	265
7.7.3.3.32 InitialNodeMembership_Mapping.....	266
7.7.3.3.33 JoinNode_Mapping.....	267
7.7.3.3.34 MergeNode_Mapping.....	268
7.7.3.3.35 ObjectFlow_Mapping.....	268
7.7.3.3.36 ObjectFlowFeatureMembership_Mapping.....	270
7.7.3.3.37 ObjectFlowGuardFeatureMembership_Mapping.....	270
7.7.3.3.38 ObjectFlowGuard_Mapping.....	271
7.7.3.3.39 ObjectFlowGuardSuccessionTargetEndFeature_Mapping.....	272
7.7.3.3.40 ObjectFlowGuardSuccessionTargetEndFeatureMembership_Mapping.....	273
7.7.3.3.41 ObjectFlowGuardSuccessionTargetEndSubsetting_Mapping.....	274
7.7.3.3.42 ObjectFlowItemFeature_Mapping.....	274
7.7.3.3.43 ObjectFlowItemFeatureMembership_Mapping.....	275



7.7.3.3.8 ActivityEdgeMetadataRedefinition_Mapping .....	227
7.7.3.3.9 ActivityEdgeMetadataReferenceUsage_Mapping .....	228
7.7.3.3.10 ActivityEdgeSourceEndFeature_Mapping .....	228
7.7.3.3.11 ActivityEdgeSourceInitialNode_Mapping .....	229
7.7.3.3.12 ActivityEdgeSourceEndFeatureMembership_Mapping .....	230
7.7.3.3.13 ActivityEdgeSourceInitialNodeSubsetting_Mapping .....	230
7.7.3.3.14 ActivityEdgeSourceEndSubsetting_Mapping .....	231
7.7.3.3.15 ActivityEdgeTransitionUsageSourceMembership_Mapping .....	232
7.7.3.3.16 ActivityFinalNode_Mapping .....	232
7.7.3.3.17 CentralBufferNode_Mapping .....	233
7.7.3.3.18 CommonActivityEdgeSuccessionAsUsage_Mapping .....	234
7.7.3.3.19 CommonVariable_Mapping .....	235
7.7.3.3.20 ControlFlowTransitionUsage_Mapping .....	236
7.7.3.3.21 ControlFlowFinalNodeFeatureMembership_Mapping .....	237
7.7.3.3.22 ControlFlowTargetFinalNodeSubsetting_Mapping .....	238
7.7.3.3.23 ControlFlowSuccessionAsUsage_Mapping .....	238
7.7.3.3.24 ControlFlowTargetFinalNode_Mapping .....	240
7.7.3.3.25 ControlFlowTargetEndFeature_Mapping .....	241
7.7.3.3.26 ControlFlowTargetFeatureMembership_Mapping .....	241
7.7.3.3.27 ControlFlowTargetEndSubsetting_Mapping .....	242
7.7.3.3.28 ControlFlowTransitionUsageFeatureMembership_Mapping .....	243
7.7.3.3.29 ControlNodeObjectFlowFeatureMembership_Mapping .....	243
7.7.3.3.30 ControlNodeObjectFlowFeatureValue_Mapping .....	244
7.7.3.3.31 ControlNodeObjectFlowReferenceUsage_Mapping .....	245
7.7.3.3.32 DataStoreNode_Mapping .....	246
7.7.3.3.33 DecisionNode_Mapping .....	247
7.7.3.3.34 FlowFinalNodeMembership_Mapping .....	248
7.7.3.3.35 ForkNode_Mapping .....	249
7.7.3.3.36 ForkNodeObjectFlowFeatureReferenceExpression_Mapping .....	250
7.7.3.3.37 ForkNodeObjectFlowMembership_Mapping .....	250
7.7.3.3.38 JoinMergeNodeObjectFlowFeature_Mapping .....	251
7.7.3.3.39 JoinMergeNodeObjectFlowFeatureReferenceExpression_Mapping .....	252
7.7.3.3.40 JoinMergeNodeObjectFlowFeatureValue_Mapping .....	252
7.7.3.3.41 JoinMergeNodeObjectFlowMembership_Mapping .....	253
7.7.3.3.42 JoinMergeNodeObjectFlowOperatorExpression_Mapping .....	254
7.7.3.3.43 JoinMergeNodeObjectFlowParameterMembership_Mapping .....	255
7.7.3.3.44 InitialNodeMembership_Mapping .....	255
7.7.3.3.45 JoinNode_Mapping .....	256
7.7.3.3.46 MergeNode_Mapping .....	257
7.7.3.3.47 ObjectFlow_Mapping .....	259
7.7.3.3.48 ObjectFlowFeatureMembership_Mapping .....	260
7.7.3.3.49 ObjectFlowGuardFeatureMembership_Mapping .....	261
7.7.3.3.50 ObjectFlowGuard_Mapping .....	262
7.7.3.3.51 ObjectFlowGuardSuccessionTargetEndFeature_Mapping .....	263
7.7.3.3.52 ObjectFlowGuardSuccessionTargetEndFeatureMembership_Mapping .....	264
7.7.3.3.53 ObjectFlowGuardSuccessionTargetEndSubsetting_Mapping .....	264
7.7.3.3.54 ObjectFlowItemFeature_Mapping .....	265
7.7.3.3.55 ObjectFlowItemFeatureMembership_Mapping .....	266
7.7.3.3.56 ObjectFlowItemFeatureTyping_Mapping .....	267
7.7.3.3.57 ObjectFlowItemFeatureUntyped_Mapping .....	267
7.7.3.3.58 ObjectFlowEndFeatureMembership_Mapping .....	268
7.7.3.3.59 ObjectFlowItemFlowEnd_Mapping .....	268
7.7.3.3.60 ObjectFlowItemFlowEndReferenceUsage_Mapping .....	269
7.7.3.3.61 ObjectFlowItemFlowEndFeatureMembership_Mapping .....	270
7.7.3.3.62 ObjectFlowItemFlowEndRedefinition_Mapping .....	271
7.7.3.3.63 ObjectFlowItemFlowEndSubsetting_Mapping .....	271

7.7.3.3.44	ObjectFlowItemFeatureTyping_Mapping.....	276
7.7.3.3.45	ObjectFlowItemFeatureUntyped_Mapping.....	276
7.7.3.3.46	ObjectFlowEndFeatureMembership_Mapping.....	276
7.7.3.3.47	ObjectFlowItemFlowEnd_Mapping.....	277
7.7.3.3.48	ObjectFlowItemFlowEndReferenceUsage_Mapping .....	278
7.7.3.3.49	ObjectFlowItemFlowEndFeatureMembership_Mapping .....	279
7.7.3.3.50	ObjectFlowItemFlowEndRedefinition_Mapping.....	279
7.7.3.3.51	ObjectFlowItemFlowEndSubsetting_Mapping.....	280
7.7.3.3.52	ObjectFlowTransitionUsageFeatureMembership_Mapping .....	281
7.7.3.3.53	VariableAttribute_Mapping .....	281
7.7.3.3.54	VariableFeatureTyping_Mapping .....	282
7.7.3.3.55	VariableItem_Mapping .....	283
7.7.3.3.56	VariableMembership_Mapping.....	283
7.7.4	Classification.....	284
7.7.4.1	Overview .....	284
7.7.4.2	Mapping Specifications.....	284
7.7.4.2.1	BehavioralFeature_Mapping .....	285
7.7.4.2.2	Classifier_Mapping .....	285
7.7.4.2.3	DefaultLowerBound_Mapping .....	286
7.7.4.2.4	DefaultMultiplicityBoundFeatureMembership_Mapping.....	287
7.7.4.2.5	DefaultMultiplicityElement_Mapping .....	287
7.7.4.2.6	DefaultMultiplicityLowerBoundFeatureMembership_Mapping .....	288
7.7.4.2.7	DefaultMultiplicityMembership_Mapping .....	289
7.7.4.2.8	DefaultMultiplicityUpperBoundFeatureMembership_Mapping.....	289
7.7.4.2.9	DefaultUpperBound_Mapping.....	290
7.7.4.2.10	DefaultValue_Mapping .....	290
7.7.4.2.11	ElementFeatureMembership_Mapping .....	291
7.7.4.2.12	Generalization_Mapping .....	292
7.7.4.2.13	InstanceSpecificationLink_Mapping.....	293
7.7.4.2.14	InstanceSpecification_Mapping .....	294
7.7.4.2.15	InstanceSpecificationFeatureTyping_Mapping.....	295
7.7.4.2.16	InstanceValue_Mapping.....	296
7.7.4.2.17	InstanceValueMembership_Mapping .....	296
7.7.4.2.18	LowerBoundValueFeatureMembership_Mapping.....	297
7.7.4.2.19	MultiplicityElement_Mapping .....	298
7.7.4.2.20	MultiplicityLowerBoundOwningMembership_Mapping .....	298
7.7.4.2.21	MultiplicityMembership_Mapping .....	299
7.7.4.2.22	MultiplicityUpperBoundOwningMembership_Mapping.....	300
7.7.4.2.23	Operation_Mapping.....	301
7.7.4.2.24	Parameter_Mapping .....	301
7.7.4.2.25	ParameterDefaultValue_Mapping.....	303
7.7.4.2.26	ParameterMembership_Mapping .....	303
7.7.4.2.27	ParameterSet_Mapping .....	304
7.7.4.2.28	ParameterSetMembership_Mapping.....	305
7.7.4.2.29	ParameterSetParameterFeatureMembership_Mapping.....	306
7.7.4.2.30	ParameterSetParameterReferenceUsage_Mapping .....	306
7.7.4.2.31	ParameterSetParameterReferenceUsageFeatureValue_Mapping .....	307
7.7.4.2.32	ParameterSetParameterReferenceUsageFeatureValueExpression_Mapping .....	308
7.7.4.2.33	ParameterSetParameterReferenceUsageMembership_Mapping.....	308
7.7.4.2.34	ParameterToFeatureTyping_Mapping .....	309
7.7.4.2.35	PropertyCommon_Mapping.....	310
7.7.4.2.36	PropertySubsetting_Mapping.....	311
7.7.4.2.37	PropertyTypedByClassInterface_Mapping .....	311
7.7.4.2.38	PropertyUntyped_Mapping .....	312

7.7.3.3.64	ObjectFlowTransitionUsageFeatureMembership_Mapping	272
7.7.3.3.65	VariableAttribute_Mapping	273
7.7.3.3.66	VariableFeatureTyping_Mapping	274
7.7.3.3.67	VariableItem_Mapping	274
7.7.3.3.68	VariableMembership_Mapping	275
7.7.4	Classification	275
7.7.4.1	Overview	276
7.7.4.2	Mapping Specifications	276
7.7.4.2.1	BehavioralFeature_Mapping	276
7.7.4.2.2	Classifier_Mapping	277
7.7.4.2.3	DefaultLowerBound_Mapping	277
7.7.4.2.4	DefaultMultiplicityBoundFeatureMembership_Mapping	278
7.7.4.2.5	DefaultMultiplicityElement_Mapping	279
7.7.4.2.6	DefaultMultiplicityLowerBoundFeatureMembership_Mapping	280
7.7.4.2.7	DefaultMultiplicityMembership_Mapping	280
7.7.4.2.8	DefaultMultiplicityUpperBoundFeatureMembership_Mapping	281
7.7.4.2.9	DefaultUpperBound_Mapping	282
7.7.4.2.10	DefaultValue_Mapping	282
7.7.4.2.11	ElementFeatureMembership_Mapping	283
7.7.4.2.12	Generalization_Mapping	284
7.7.4.2.13	InstanceSpecificationLink_Mapping	285
7.7.4.2.14	InstanceSpecification_Mapping	286
7.7.4.2.15	InstanceSpecificationFeatureTyping_Mapping	287
7.7.4.2.16	InstanceValue_Mapping	287
7.7.4.2.17	InstanceValueMembership_Mapping	288
7.7.4.2.18	LowerBoundValueFeatureMembership_Mapping	289
7.7.4.2.19	MultiplicityElement_Mapping	290
7.7.4.2.20	MultiplicityLowerBoundOwningMembership_Mapping	290
7.7.4.2.21	MultiplicityMembership_Mapping	291
7.7.4.2.22	MultiplicityUpperBoundOwningMembership_Mapping	292
7.7.4.2.23	Operation_Mapping	293
7.7.4.2.24	Parameter_Mapping	294
7.7.4.2.25	ParameterDefaultValue_Mapping	295
7.7.4.2.26	ParameterMembership_Mapping	296
7.7.4.2.27	ParameterSet_Mapping	296
7.7.4.2.28	ParameterSetMembership_Mapping	298
7.7.4.2.29	ParameterSetParameterFeatureMembership_Mapping	298
7.7.4.2.30	ParameterSetParameterReferenceUsage_Mapping	299
7.7.4.2.31	ParameterSetParameterReferenceUsageFeatureValue_Mapping	300
7.7.4.2.32	ParameterSetParameterReferenceUsageFeatureValueExpression_Mapping	300
7.7.4.2.33	ParameterSetParameterReferenceUsageMembership_Mapping	301
7.7.4.2.34	ParameterToFeatureTyping_Mapping	302
7.7.4.2.35	PropertyCommon_Mapping	302
7.7.4.2.36	PropertySubsetting_Mapping	303
7.7.4.2.37	PropertyTypedByClassInterface_Mapping	304
7.7.4.2.38	PropertyUntyped_Mapping	305
7.7.4.2.39	Realization_Mapping	306
7.7.4.2.40	Slot_Mapping	306
7.7.4.2.41	SlotMembership_Mapping	307
7.7.4.2.42	SlotFeatureTyping_Mapping	308
7.7.4.2.43	SlotValue_Mapping	308
7.7.4.2.44	StructuralFeature_Mapping	309
7.7.4.2.45	StructuralFeatureMembership_Mapping	310
7.7.4.2.46	StructuralFeatureToFeatureTyping_Mapping	311
7.7.4.2.47	TypedElementFeatureTyping_Mapping	311
7.7.4.2.48	UpperBoundValueFeatureMembership_Mapping	312

7.7.4.2.39	Realization_Mapping	313
7.7.4.2.40	Slot_Mapping	314
7.7.4.2.41	SlotMembership_Mapping	314
7.7.4.2.42	SlotFeatureTyping_Mapping	315
7.7.4.2.43	SlotValue_Mapping	315
7.7.4.2.44	StructuralFeature_Mapping	316
7.7.4.2.45	StructuralFeatureMembership_Mapping	317
7.7.4.2.46	StructuralFeatureToFeatureTyping_Mapping	318
7.7.4.2.47	TypedElementFeatureTyping_Mapping	318
7.7.4.2.48	UpperBoundValueFeatureMembership_Mapping	319
7.7.5	CommonBehavior	320
7.7.5.1	Overview	320
7.7.5.2	UML4SysML::CommonBehavior elements not mapped	320
7.7.5.3	Mapping Specifications	321
7.7.5.3.1	Behavior_Mapping	321
7.7.5.3.2	ChangeEvent_Mapping	322
7.7.5.3.3	OpaqueBehavior_Mapping	323
7.7.5.3.4	OpaqueBehaviorMembership_Mapping	324
7.7.5.3.5	OpaqueBehaviorSpecification_Mapping	324
7.7.5.3.6	TimeEvent_Mapping	325
7.7.5.3.7	Trigger_Mapping	326
7.7.6	CommonStructure	326
7.7.6.1	Overview	326
7.7.6.2	Mapping Specifications	326
7.7.6.2.1	Abstraction_Mapping	326
7.7.6.2.2	Comment_Mapping	327
7.7.6.2.3	CommentAnnotation_Mapping	328
7.7.6.2.4	CommentOwnership_Mapping	328
7.7.6.2.5	Constraint_Mapping	329
7.7.6.2.6	ConstrainedElementFeatureMembership_Mapping	330
7.7.6.2.7	ConstraintUsageFeatureTyping_Mapping	331
7.7.6.2.8	ConstraintUsage_Mapping	331
7.7.6.2.9	Dependency_Mapping	332
7.7.6.2.10	DirectedRelationship_Mapping	333
7.7.6.2.11	ElementMain_Mapping	334
7.7.6.2.12	ElementMembership_Mapping	334
7.7.6.2.13	ElementOwnership_Mapping	335
7.7.6.2.14	ElementOwningMembership_Mapping	336
7.7.6.2.15	NamedElementMain_Mapping	337
7.7.6.2.16	Namespace_Mapping	337
7.7.6.2.17	Relationship_Mapping	338
7.7.6.2.18	Usage_Mapping	339
7.7.7	InformationFlows	339
7.7.7.1	Overview	339
7.7.7.2	Mapping Specifications	339
7.7.7.2.1	InformationFlow_Mapping	340
7.7.7.2.2	InformationFlowConveyedFeatureMembership_Mapping	341
7.7.7.2.3	InformationFlowEnd_Mapping	342
7.7.7.2.4	InformationFlowEndFeatureMembership_Mapping	342
7.7.7.2.5	InformationFlowFeatureTyping_Mapping	343
7.7.7.2.6	InformationFlowSubclassification_Mapping	344
7.7.7.2.7	InformationItem_Mapping	344
7.7.7.2.8	InformationItemFlowConveyedItemUsage_Mapping	345
7.7.7.2.9	InformationItemFlowConveyedItemUsageFeatureTyping_Mapping	345

7.7.5 CommonBehavior .....	313
7.7.5.1 Overview .....	313
7.7.5.2 UML4SysML::CommonBehavior elements not mapped .....	313
7.7.5.3 Mapping Specifications .....	313
7.7.5.3.1 Behavior_Mapping .....	313
7.7.5.3.2 ChangeEvent_Mapping .....	314
7.7.5.3.3 ChangeEventReturnParameter_Mapping .....	315
7.7.5.3.4 ChangeEventReturnParameterMembership_Mapping .....	316
7.7.5.3.5 ChangeTriggerBindingConnector_Mapping .....	317
7.7.5.3.6 ChangeTriggerConstraintUsage_Mapping .....	317
7.7.5.3.7 ChangeTriggerEndFeatureMembership_Mapping .....	318
7.7.5.3.8 ChangeTriggerEventChainingFeature_Mapping .....	319
7.7.5.3.9 ChangeTriggerEventReturnParameterChainingFeature_Mapping .....	319
7.7.5.3.10 ChangeTriggerExpressionFeature_Mapping .....	320
7.7.5.3.11 ChangeTriggerExpressionFeatureMembership_Mapping .....	321
7.7.5.3.12 ChangeTriggerExpressionFeatureReferenceExpression_Mapping .....	322
7.7.5.3.13 ChangeTriggerExpressionFeatureTyping_Mapping .....	322
7.7.5.3.14 ChangeTriggerExpressionFeatureValue_Mapping .....	323
7.7.5.3.15 ChangeTriggerExpressionInvocationExpression_Mapping .....	324
7.7.5.3.16 ChangeTriggerExpressionParameterMembership_Mapping .....	324
7.7.5.3.17 ChangeTriggerFeature_Mapping .....	325
7.7.5.3.18 ChangeTriggerFeatureMembership_Mapping .....	326
7.7.5.3.19 ChangeTriggerFeatureValue_Mapping .....	326
7.7.5.3.20 ChangeTriggerInvocationExpression_Mapping .....	327
7.7.5.3.21 ChangeTriggerReferenceSubsetting_Mapping .....	328
7.7.5.3.22 ChangeTriggerReferenceUsage_Mapping .....	329
7.7.5.3.23 ChangeTriggerReturnEndFeatureMembership_Mapping .....	329
7.7.5.3.24 ChangeTriggerReturnParameter_Mapping .....	330
7.7.5.3.25 ChangeTriggerReturnParameterMembership_Mapping .....	331
7.7.5.3.26 ChangeTriggerReturnReferenceSubsetting_Mapping .....	332
7.7.5.3.27 ChangeTriggerReturnReferenceUsage_Mapping .....	332
7.7.5.3.28 OpaqueBehavior_Mapping .....	333
7.7.5.3.29 OpaqueBehaviorMembership_Mapping .....	334
7.7.5.3.30 OpaqueBehaviorSpecification_Mapping .....	335
7.7.5.3.31 SignalTriggerReferenceUsage_Mapping .....	335
7.7.5.3.32 SignalTriggerReferenceUsageFeatureTyping_Mapping .....	336
7.7.5.3.33 TimeEvent_Mapping .....	337
7.7.5.3.34 TimeTriggerBindingConnector_Mapping .....	338
7.7.5.3.35 TimeTriggerCalculationUsage_Mapping .....	339
7.7.5.3.36 TimeTriggerEndFeatureMembership_Mapping .....	339
7.7.5.3.37 TimeTriggerEventChainingFeature_Mapping .....	340
7.7.5.3.38 TimeTriggerEventReturnParameterChainingFeature_Mapping .....	341
7.7.5.3.39 TimeTriggerExpressionFeature_Mapping .....	341
7.7.5.3.40 TimeTriggerExpressionFeatureTyping_Mapping .....	342
7.7.5.3.41 TimeTriggerExpressionFeatureValue_Mapping .....	343
7.7.5.3.42 TimeTriggerExpressionInvocationExpression_Mapping .....	344
7.7.5.3.43 TimeTriggerExpressionParameterMembership_Mapping .....	344
7.7.5.3.44 TimeTriggerFeature_Mapping .....	345
7.7.5.3.45 TimeTriggerFeatureMembership_Mapping .....	346
7.7.5.3.46 TimeTriggerFeatureTyping_Mapping .....	346
7.7.5.3.47 TimeTriggerFeatureValue_Mapping .....	347
7.7.5.3.48 TimeTriggerInvocationExpression_Mapping .....	348
7.7.5.3.49 TimeTriggerReferenceSubsetting_Mapping .....	349
7.7.5.3.50 TimeTriggerReferenceUsage_Mapping .....	349
7.7.5.3.51 TimeTriggerReturnEndFeatureMembership_Mapping .....	350
7.7.5.3.52 TimeTriggerReturnParameter_Mapping .....	351

7.7.8 Interactions .....	346
7.7.8.1 Overview .....	346
7.7.8.2 UML4SysML::Interactions elements not mapped .....	347
7.7.8.3 Mapping Specifications .....	347
7.7.8.3.1 ActionExecutionSpecification_Mapping .....	347
7.7.8.3.2 BehaviorExecutionSpecification_Mapping .....	348
7.7.8.3.3 CombinedFragment_Mapping .....	348
7.7.8.3.4 CombinedFragmentMembership_Mapping .....	349
7.7.8.3.5 ExecutionSpecificationMembership_Mapping .....	350
7.7.8.3.6 Interaction_Mapping .....	350
7.7.8.3.7 InteractionOperand_Mapping .....	351
7.7.8.3.8 InteractionOperandMembership_Mapping .....	352
7.7.8.3.9 InteractionUse_Mapping .....	353
7.7.8.3.10 InteractionUseMembership_Mapping .....	354
7.7.8.3.11 InteractionUseFeatureTyping_Mapping .....	354
7.7.8.3.12 LifelineMembership_Mapping .....	355
7.7.8.3.13 LifelinePartUsage_Mapping .....	356
7.7.8.3.14 LifelineFeatureTyping_Mapping .....	356
7.7.8.3.15 Message_Mapping .....	357
7.7.8.3.16 MessageMembership_Mapping .....	357
7.7.8.3.17 StateInvariant_Mapping .....	358
7.7.8.3.18 StateInvariantMembership_Mapping .....	359
7.7.8.3.19 StateInvariantFeatureTyping_Mapping .....	359
7.7.9 Packages .....	360
7.7.9.1 Overview .....	360
7.7.9.2 UML4SysML::Packages elements not mapped .....	361
7.7.9.3 Mapping Specifications .....	361
7.7.9.3.1 ElementImport_Mapping .....	361
7.7.9.3.2 Model_Mapping .....	362
7.7.9.3.3 ModelViewpointMetadataUsage_Mapping .....	363
7.7.9.3.4 ModelViewpointMetadataFeatureMembership_Mapping .....	363
7.7.9.3.5 ModelViewpointMetadataReferenceUsage_Mapping .....	364
7.7.9.3.6 ModelViewpointMetadataFeatureTyping_Mapping .....	364
7.7.9.3.7 ModelViewpointMetadataMembership_Mapping .....	365
7.7.9.3.8 ModelViewpointMetadataFeatureValue_Mapping .....	365
7.7.9.3.9 ModelViewpointMetadataRedefinition_Mapping .....	366
7.7.9.3.10 ModelViewpointValue_Mapping .....	367
7.7.9.3.11 Package_Mapping .....	367
7.7.9.3.12 PackageImport_Mapping .....	368
7.7.9.3.13 PackageURIMetadataUsage_Mapping .....	369
7.7.9.3.14 PackageURIFeatureMembership_Mapping .....	370
7.7.9.3.15 PackageURIFeatureTyping_Mapping .....	370
7.7.9.3.16 PackageURIMetadataReferenceUsage_Mapping .....	371
7.7.9.3.17 PackageURIMetadataFeatureValue_Mapping .....	372
7.7.9.3.18 PackageURIMetadataMembership_Mapping .....	373
7.7.9.3.19 PackageURIRedefinition_Mapping .....	373
7.7.9.3.20 PackageURIValue_Mapping .....	374
7.7.9.3.21 Profile_Mapping .....	375
7.7.9.3.22 ProfileMetadataMembership_Mapping .....	375
7.7.9.3.23 ProfileMetadataUsage_Mapping .....	376
7.7.9.3.24 StereotypeMetadataDefinition_Mapping .....	377
7.7.9.3.25 StereotypeMetadataDefinitionMembership_Mapping .....	377
7.7.9.3.26 StereotypeOccurrenceUsage_Mapping .....	378
7.7.9.3.27 StereotypeOccurrenceUsageFeatureTyping_Mapping .....	378



7.7.5.3.53	TimeTriggerReturnParameterMembership_Mapping.....	352
7.7.5.3.54	TimeTriggerReturnReferenceSubsetting_Mapping .....	352
7.7.5.3.55	TimeTriggerReturnReferenceUsage_Mapping .....	353
7.7.5.3.56	Trigger_Mapping.....	354
7.7.5.3.57	TriggerParameterMembership_Mapping .....	354
7.7.6	CommonStructure .....	355
7.7.6.1	Overview .....	355
7.7.6.2	Mapping Specifications.....	356
7.7.6.2.1	Abstraction_Mapping.....	356
7.7.6.2.2	Comment_Mapping.....	356
7.7.6.2.3	CommentAnnotation_Mapping.....	357
7.7.6.2.4	CommentOwnership_Mapping .....	358
7.7.6.2.5	Constraint_Mapping.....	359
7.7.6.2.6	ConstrainedElementFeatureMembership_Mapping.....	360
7.7.6.2.7	ConstraintUsageFeatureTyping_Mapping .....	361
7.7.6.2.8	ConstraintUsage_Mapping.....	361
7.7.6.2.9	Dependency_Mapping.....	362
7.7.6.2.10	DirectedRelationship_Mapping.....	363
7.7.6.2.11	ElementMain_Mapping.....	363
7.7.6.2.12	ElementMembership_Mapping .....	364
7.7.6.2.13	ElementOwnership_Mapping.....	365
7.7.6.2.14	ElementOwningMembership_Mapping .....	366
7.7.6.2.15	NamedElementMain_Mapping .....	367
7.7.6.2.16	Namespace_Mapping .....	367
7.7.6.2.17	Relationship_Mapping .....	368
7.7.6.2.18	Usage_Mapping.....	369
7.7.7	InformationFlows .....	369
7.7.7.1	Overview .....	369
7.7.7.2	Mapping Specifications.....	369
7.7.7.2.1	InformationFlow_Mapping .....	369
7.7.7.2.2	InformationFlowConveyedFeatureMembership_Mapping.....	370
7.7.7.2.3	InformationFlowEnd_Mapping.....	371
7.7.7.2.4	InformationFlowEndFeatureMembership_Mapping.....	372
7.7.7.2.5	InformationFlowFeatureTyping_Mapping.....	373
7.7.7.2.6	InformationFlowSubclassification_Mapping.....	373
7.7.7.2.7	InformationItem_Mapping .....	374
7.7.7.2.8	InformationItemFlowConveyedItemUsage_Mapping .....	374
7.7.7.2.9	InformationItemFlowConveyedItemUsageFeatureTyping_Mapping.....	375
7.7.8	Interactions .....	376
7.7.8.1	Overview .....	376
7.7.8.2	UML4SysML::Interactions elements not mapped .....	376
7.7.8.3	Mapping Specifications.....	377
7.7.8.3.1	ActionExecutionSpecification_Mapping .....	377
7.7.8.3.2	BehaviorExecutionSpecification_Mapping.....	377
7.7.8.3.3	CombinedFragment_Mapping.....	378
7.7.8.3.4	CombinedFragmentMembership_Mapping .....	379
7.7.8.3.5	ExecutionSpecificationMembership_Mapping .....	380
7.7.8.3.6	Interaction_Mapping .....	380
7.7.8.3.7	InteractionOperand_Mapping .....	381
7.7.8.3.8	InteractionOperandMembership_Mapping .....	382
7.7.8.3.9	InteractionUse_Mapping .....	383
7.7.8.3.10	InteractionUseMembership_Mapping.....	384
7.7.8.3.11	InteractionUseFeatureTyping_Mapping .....	385
7.7.8.3.12	LifelineMembership_Mapping.....	385
7.7.8.3.13	LifelinePartUsage_Mapping .....	386
7.7.8.3.14	LifelineFeatureTyping_Mapping .....	387

7.7.9.3.28 StereotypeOccurrenceUsageMembership_Mapping .....	379
7.7.9.3.29 StereotypeOccurrenceUsageMultiplicityMembership_Mapping .....	379
7.7.9.3.30 StereotypeOccurrenceUsageMultiplicityRange_Mapping .....	380
7.7.9.3.31 StereotypeOccurrenceUsageMultiplicityRangeInfinity_Mapping .....	381
7.7.9.3.32 StereotypeOccurrenceUsageInfinityReturnParameter_Mapping .....	381
7.7.9.3.33 StereotypeOccurrenceUsageInfinityReturnParameterMembership_Mapping .....	382
7.7.9.3.34 StereotypeOccurrenceUsageMultiplicityRangeMembership_Mapping .....	383
7.7.10 SimpleClassifiers.....	384
7.7.10.1 Overview .....	384
7.7.10.2 Mapping Specifications.....	384
7.7.10.2.1 Attribute_Mapping .....	384
7.7.10.2.2 AttributeRedefined_Mapping.....	385
7.7.10.2.3 AttributeRedefinedRedefinition_Mapping .....	386
7.7.10.2.4 AttributeRedefinedMembership_Mapping .....	386
7.7.10.2.5 AttributeRedefinedFeatureTyping_Mapping .....	387
7.7.10.2.6 BehavioredClassifier_Mapping.....	388
7.7.10.2.7 BehavioredClassifierFeatureMembership_Mapping.....	389
7.7.10.2.8 BehavioredClassifierFeatureTyping_Mapping .....	389
7.7.10.2.9 BehavioredClassifierActionUsage_Mapping.....	390
7.7.10.2.10 DataType_Mapping.....	391
7.7.10.2.11 Enumeration_Mapping.....	391
7.7.10.2.12 EnumerationLiteral_Mapping .....	392
7.7.10.2.13 EnumerationVariantMembership_Mapping.....	393
7.7.10.2.14 Interface_Mapping .....	393
7.7.10.2.15 InterfaceConjugatedPortDefinition_Mapping.....	394
7.7.10.2.16 InterfaceConjugatedPortDefinitionMembership_Mapping.....	395
7.7.10.2.17 InterfacePortConjugation_Mapping .....	395
7.7.10.2.18 InterfaceRealization_Mapping .....	396
7.7.10.2.19 PrimitiveType_Mapping .....	397
7.7.10.2.20 Reception_Mapping .....	397
7.7.10.2.21 ReceptionFeatureTyping_Mapping.....	398
7.7.10.2.22 Signal_Mapping .....	399
7.7.11 StateMachines .....	399
7.7.11.1 Overview .....	399
7.7.11.2 Mapping Specifications.....	399
7.7.11.2.1 ConnectionPointReference_Mapping .....	399
7.7.11.2.2 FinalState_Mapping .....	400
7.7.11.2.3 PseudoState_Mapping .....	401
7.7.11.2.4 Region_Mapping .....	402
7.7.11.2.5 State_Mapping.....	402
7.7.11.2.6 StateDefinition_Mapping .....	403
7.7.11.2.7 Transition_Mapping .....	404
7.7.11.2.8 TransitionSuccession_Mapping .....	405
7.7.11.2.9 TransitionSourceToSubsetting_Mapping.....	406
7.7.11.2.10 TransitionSuccessionSource_Mapping .....	406
7.7.11.2.11 TransitionSuccessionSourceMembership_Mapping .....	407
7.7.11.2.12 TransitionSuccessionTarget_Mapping.....	408
7.7.11.2.13 TransitionSuccessionTargetMembership_Mapping.....	408
7.7.11.2.14 TransitionTargetToSubsetting_Mapping .....	409
7.7.12 StructuredClassifiers .....	410
7.7.12.1 Overview .....	410
7.7.12.2 Mapping Specifications.....	410
7.7.12.2.1 AssociationClass_Mapping .....	410
7.7.12.2.2 AssociationCommon_Mapping.....	411



7.7.8.3.15 Message_Mapping.....	387
7.7.8.3.16 MessageMembership_Mapping .....	388
7.7.8.3.17 StateInvariant_Mapping.....	389
7.7.8.3.18 StateInvariantMembership_Mapping .....	389
7.7.8.3.19 StateInvariantFeatureTyping_Mapping.....	390
7.7.9 Packages.....	391
7.7.9.1 Overview .....	391
7.7.9.2 UML4SysML::Packages elements not mapped .....	391
7.7.9.3 Mapping Specifications.....	391
7.7.9.3.1 ElementImport_Mapping .....	391
7.7.9.3.2 Model_Mapping .....	392
7.7.9.3.3 ModelViewpointMetadataUsage_Mapping .....	393
7.7.9.3.4 ModelViewpointMetadataFeatureMembership_Mapping .....	393
7.7.9.3.5 ModelViewpointMetadataReferenceUsage_Mapping .....	394
7.7.9.3.6 ModelViewpointMetadataFeatureTyping_Mapping.....	395
7.7.9.3.7 ModelViewpointMetadataMembership_Mapping .....	395
7.7.9.3.8 ModelViewpointMetadataFeatureValue_Mapping .....	396
7.7.9.3.9 ModelViewpointMetadataRedefinition_Mapping .....	397
7.7.9.3.10 ModelViewpointValue_Mapping.....	398
7.7.9.3.11 Package_Mapping .....	398
7.7.9.3.12 PackageImport_Mapping .....	399
7.7.9.3.13 PackageURIMetadataUsage_Mapping .....	400
7.7.9.3.14 PackageURIFeatureMembership_Mapping .....	401
7.7.9.3.15 PackageURIFeatureTyping_Mapping.....	401
7.7.9.3.16 PackageURIMetadataReferenceUsage_Mapping .....	402
7.7.9.3.17 PackageURIMetadataFeatureValue_Mapping.....	403
7.7.9.3.18 PackageURIMetadataMembership_Mapping .....	404
7.7.9.3.19 PackageURIRedefinition_Mapping .....	404
7.7.9.3.20 PackageURIValue_Mapping.....	405
7.7.9.3.21 Profile_Mapping.....	406
7.7.9.3.22 ProfileMetadataMembership_Mapping.....	406
7.7.9.3.23 ProfileMetadataUsage_Mapping .....	407
7.7.9.3.24 StereotypeMetadataDefinition_Mapping .....	408
7.7.9.3.25 StereotypeMetadataDefinitionMembership_Mapping.....	408
7.7.9.3.26 StereotypeOccurrenceUsage_Mapping .....	409
7.7.9.3.27 StereotypeOccurrenceUsageFeatureTyping_Mapping.....	409
7.7.9.3.28 StereotypeOccurrenceUsageMembership_Mapping .....	410
7.7.9.3.29 StereotypeOccurrenceUsageMultiplicityMembership_Mapping .....	411
7.7.9.3.30 StereotypeOccurrenceUsageMultiplicityRange_Mapping .....	412
7.7.9.3.31 StereotypeOccurrenceUsageMultiplicityRangeInfinity_Mapping .....	412
7.7.9.3.32 StereotypeOccurrenceUsageInfinityReturnParameter_Mapping .....	413
7.7.9.3.33 StereotypeOccurrenceUsageInfinityReturnParameterMembership_Mapping .....	414
7.7.9.3.34 StereotypeOccurrenceUsageMultiplicityRangeMembership_Mapping .....	414
7.7.10 SimpleClassifiers.....	415
7.7.10.1 Overview .....	415
7.7.10.2 Mapping Specifications.....	416
7.7.10.2.1 Attribute_Mapping .....	416
7.7.10.2.2 AttributeRedefined_Mapping.....	416
7.7.10.2.3 AttributeRedefinedRedefinition_Mapping.....	417
7.7.10.2.4 AttributeRedefinedMembership_Mapping .....	418
7.7.10.2.5 AttributeRedefinedFeatureTyping_Mapping .....	419
7.7.10.2.6 BehavioredClassifier_Mapping.....	419
7.7.10.2.7 BehavioredClassifierFeatureMembership_Mapping.....	420
7.7.10.2.8 BehavioredClassifierFeatureTyping_Mapping .....	421
7.7.10.2.9 BehavioredClassifierActionUsage_Mapping.....	422
7.7.10.2.10 DataType_Mapping.....	422

7.7.12.2.3	AssociationMetadataUsage_Mapping	412
7.7.12.2.4	AssociationMetadataUsageFeatureMembership_Mapping	413
7.7.12.2.5	AssociationMetadataUsageFeatureTyping_Mapping	413
7.7.12.2.6	AssociationMetadataUsageFeature_Mapping	414
7.7.12.2.7	AssociationMetadataUsageFeatureValue_Mapping	415
7.7.12.2.8	AssociationMetadataUsageMembership_Mapping	415
7.7.12.2.9	AssociationMetadataUsageRedefinition_Mapping	416
7.7.12.2.10	Class_Mapping	416
7.7.12.2.11	ConnectionEndToSubsetting_Mapping	417
7.7.12.2.12	Connector_Mapping	418
7.7.12.2.13	ConnectorEndToFeatureCommon_Mapping	419
7.7.12.2.14	ConnectorEndToMembership_Mapping	420
7.7.12.2.15	ConnectorEndToOwnedFeature_Mapping	420
7.7.12.2.16	ConnectorEndToSubsettedFeature_Mapping	421
7.7.12.2.17	ConnectorEndToSubsettedFeatureMembership_Mapping	422
7.7.12.2.18	ConnectorMultiplicityMembership_Mapping	423
7.7.12.2.19	ConnectorType_Mapping	423
7.7.12.2.20	ConnectorTypeDerived_Mapping	424
7.7.12.2.21	End_Mapping	425
7.7.12.2.22	EndMembership_Mapping	426
7.7.12.2.23	EndToSubsettedFeature_Mapping	426
7.7.12.2.24	EndToSubsettedFeatureChaining_Mapping	427
7.7.12.2.25	NonOwnedEndSubsetting_Mapping	427
7.7.12.2.26	NonOwnedEndToSubsettedFeatureMembership_Mapping	428
7.7.12.2.27	NonOwnedEnd_Mapping	429
7.7.12.2.28	NonOwnedEndMembership_Mapping	429
7.7.12.2.29	NonOwnedEndSubsettingMembership_Mapping	430
7.7.12.2.30	NonOwnedEndFeatureTyping_Mapping	431
7.7.12.2.31	OwnedEnd_Mapping	431
7.7.12.2.32	OwnedEndMembership_Mapping	432
7.7.12.2.33	Port_Mapping	433
7.7.12.2.34	PortUntyped_Mapping	434
7.7.12.2.35	PropertyToFeatureChaining_Mapping	435
7.7.12.2.36	QualifierMembership_Mapping	435
7.7.13	UseCases	436
7.7.13.1	Overview	436
7.7.13.2	UML4SysML::UseCases elements not mapped	436
7.7.13.3	Mapping Specifications	436
7.7.13.3.1	Actor_Mapping	436
7.7.13.3.2	Include_Mapping	437
7.7.13.3.3	IncludeFeatureTyping_Mapping	438
7.7.13.3.4	UseCase_Mapping	438
7.7.13.3.5	UseCaseActor_Mapping	440
7.7.13.3.6	UseCaseActorFeatureTyping_Mapping	440
7.7.13.3.7	UseCaseActorMembership_Mapping	441
7.7.13.3.8	UseCaseEmptySubjectReferenceUsage_Mapping	441
7.7.13.3.9	UseCaseObjectiveMembership_Mapping	442
7.7.13.3.10	UseCaseObjectiveRequirementUsage_Mapping	443
7.7.13.3.11	UseCaseObjectiveSubjectMembership_Mapping	443
7.7.13.3.12	UseCaseSubjectFeatureTyping_Mapping	444
7.7.13.3.13	UseCaseSubjectMembership_Mapping	444
7.7.13.3.14	UseCaseSubjectReferenceUsage_Mapping	445
7.7.14	Values	446
7.7.14.1	Overview	446

7.7.10.2.11 Enumeration_Mapping.....	423
7.7.10.2.12 EnumerationLiteral_Mapping .....	424
7.7.10.2.13 EnumerationVariantMembership_Mapping.....	424
7.7.10.2.14 Interface_Mapping .....	425
7.7.10.2.15 InterfaceConjugatedPortDefinition_Mapping.....	426
7.7.10.2.16 InterfaceConjugatedPortDefinitionMembership_Mapping.....	427
7.7.10.2.17 InterfacePortConjugation_Mapping .....	427
7.7.10.2.18 InterfaceRealization_Mapping .....	428
7.7.10.2.19 PrimitiveType_Mapping .....	429
7.7.10.2.20 Reception_Mapping .....	429
7.7.10.2.21 ReceptionFeatureTyping_Mapping.....	430
7.7.10.2.22 Signal_Mapping .....	431
7.7.11 StateMachines .....	431
7.7.11.1 Overview .....	431
7.7.11.2 Mapping Specifications.....	431
7.7.11.2.1 ChangeTriggerReferenceUsage_Mapping .....	431
7.7.11.2.2 CommonPseudostate_Mapping.....	432
7.7.11.2.3 ConnectionPointReference_Mapping .....	433
7.7.11.2.4 DoBehaviorStateSubactionMembership_Mapping.....	434
7.7.11.2.5 EntryBehaviorStateSubactionMembership_Mapping.....	435
7.7.11.2.6 ExitBehaviorStateSubactionMembership_Mapping .....	435
7.7.11.2.7 FinalState_Mapping .....	436
7.7.11.2.8 InitialState_Mapping.....	436
7.7.11.2.9 InitialStateSubactionMembership_Mapping.....	437
7.7.11.2.10 PseudoState_Mapping .....	438
7.7.11.2.11 Region_Mapping .....	439
7.7.11.2.12 State_Mapping.....	439
7.7.11.2.13 StateBehaviorPerformActionUsage_Mapping .....	441
7.7.11.2.14 StateBehaviorPerformActionUsageFeatureTyping_Mapping .....	442
7.7.11.2.15 StateBehaviorStateSubactionMembership_Mapping.....	442
7.7.11.2.16 StateDefinition_Mapping .....	443
7.7.11.2.17 TimeTriggerReferenceUsage_Mapping.....	444
7.7.11.2.18 Transition_Mapping .....	445
7.7.11.2.19 TransitionSuccession_Mapping .....	446
7.7.11.2.20 TransitionSourceToSubsetting_Mapping.....	446
7.7.11.2.21 TransitionSuccessionSource_Mapping .....	447
7.7.11.2.22 TransitionSuccessionSourceMembership_Mapping .....	448
7.7.11.2.23 TransitionSuccessionTarget_Mapping.....	448
7.7.11.2.24 TransitionSuccessionTargetMembership_Mapping.....	449
7.7.11.2.25 TransitionTargetToSubsetting_Mapping .....	450
7.7.11.2.26 TransitionTriggerFeatureMembership_Mapping.....	451
7.7.12 StructuredClassifiers .....	452
7.7.12.1 Overview .....	452
7.7.12.2 Mapping Specifications.....	452
7.7.12.2.1 AssociationClass_Mapping .....	452
7.7.12.2.2 AssociationCommon_Mapping.....	453
7.7.12.2.3 AssociationMetadataUsage_Mapping .....	454
7.7.12.2.4 AssociationMetadataUsageFeatureMembership_Mapping.....	454
7.7.12.2.5 AssociationMetadataUsageFeatureTyping_Mapping .....	455
7.7.12.2.6 AssociationMetadataUsageFeature_Mapping.....	456
7.7.12.2.7 AssociationMetadataUsageFeatureValue_Mapping .....	456
7.7.12.2.8 AssociationMetadataUsageMembership_Mapping.....	457
7.7.12.2.9 AssociationMetadataUsageRedefinition_Mapping.....	458
7.7.12.2.10 Class_Mapping .....	458
7.7.12.2.11 ConnectionDefEnd_Mapping.....	459
7.7.12.2.12 ConnectionDefEndMembership_Mapping .....	460

7.7.14.2 UML4SysML::Values elements not mapped .....	447
7.7.14.3 Mapping Specifications .....	447
7.7.14.3.1 EqualOperatorExpressionFeature_Mapping .....	447
7.7.14.3.2 EqualOperatorExpressionFeatureValue_Mapping .....	448
7.7.14.3.3 EqualOperatorExpressionOperandParameterMembership_Mapping .....	448
7.7.14.3.4 Expression_Mapping .....	449
7.7.14.3.5 ExpressionElse_Mapping .....	450
7.7.14.3.6 ExpressionElseMembership_Mapping .....	450
7.7.14.3.7 ExpressionElseSpecification_Mapping .....	451
7.7.14.3.8 LiteralBoolean_Mapping .....	452
7.7.14.3.9 LiteralInteger_Mapping .....	452
7.7.14.3.10 LiteralNull_Mapping .....	453
7.7.14.3.11 LiteralReal_Mapping .....	453
7.7.14.3.12 LiteralSpecificationCommon_Mapping .....	454
7.7.14.3.13 LiteralSpecificationFeatureTyping_Mapping .....	455
7.7.14.3.14 LiteralString_Mapping .....	455
7.7.14.3.15 LiteralUnlimitedUnbounded_Mapping .....	456
7.7.14.3.16 LiteralUnlimitedInteger_Mapping .....	456
7.7.14.3.17 OpaqueExpressionAsValue_Mapping .....	457
7.7.14.3.18 OpaqueExpression_Mapping .....	458
7.7.14.3.19 OpaqueExpressionFeature_Mapping .....	458
7.7.14.3.20 OpaqueExpressionFeatureFeature_Mapping .....	459
7.7.14.3.21 OpaqueExpressionFeatureFeatureMembership_Mapping .....	459
7.7.14.3.22 OpaqueExpressionFeatureValue_Mapping .....	460
7.7.14.3.23 OpaqueExpressionFeatureValueExpression_Mapping .....	461
7.7.14.3.24 OpaqueExpressionFeatureValueExpressionMembership_Mapping .....	461
7.7.14.3.25 OpaqueExpressionMembership_Mapping .....	462
7.7.14.3.26 OpaqueExpressionParameterMembership_Mapping .....	463
7.7.14.3.27 OpaqueExpressionReferenceUsageReturnParameterMembership_Mapping .....	463
7.7.14.3.28 OpaqueExpressionReferenceUsage_Mapping .....	464
7.7.14.3.29 OpaqueExpressionReferenceUsageFeatureTyping_Mapping .....	465
7.7.14.3.30 OpaqueExpressionReferenceUsageUntyped_Mapping .....	465
7.7.14.3.31 OpaqueExpressionSpecification_Mapping .....	466
7.7.14.3.32 TimeExpression_Mapping .....	466
7.7.14.3.33 ValueSpecification_Mapping .....	467
7.8 Mappings from SysML v1.7 stereotypes .....	468
7.8.1 Overview .....	468
7.8.2 Activities .....	468
7.8.2.1 Overview .....	468
7.8.2.2 SysML::Activities elements not mapped .....	468
7.8.2.3 Mapping Specifications .....	469
7.8.2.3.1 ProbabilityMetadataUsage_Mapping .....	469
7.8.2.3.2 ProbabilityMetadataUsageFeatureMembership_Mapping .....	470
7.8.2.3.3 ProbabilityMetadataUsageFeatureTyping_Mapping .....	470
7.8.2.3.4 ProbabilityMetadataUsageReferenceUsage_Mapping .....	471
7.8.2.3.5 ProbabilityMetadataUsageReferenceUsageFeatureValue_Mapping .....	472
7.8.2.3.6 ProbabilityMetadataUsageReferenceUsageRedefinition_Mapping .....	472
7.8.2.3.7 ProbabilityOwningMembership_Mapping .....	473
7.8.2.3.8 RateMetadataUsage_Mapping .....	474
7.8.2.3.9 RateMetadataUsageContinuousFeatureMembership_Mapping .....	475
7.8.2.3.10 RateMetadataUsageFeatureValue_Mapping .....	476
7.8.2.3.11 RateMetadataUsageContinuousReferenceUsage_Mapping .....	476
7.8.2.3.12 RateMetadataUsageContinuousReferenceUsageRedefinition_Mapping .....	477
7.8.2.3.13 RateMetadataUsageDiscreteFeatureMembership_Mapping .....	478

7.7.12.2.13	ConnectionEndToSubsetting_Mapping .....	461
7.7.12.2.14	Connector_Mapping .....	462
7.7.12.2.15	ConnectorEndToFeatureCommon_Mapping .....	463
7.7.12.2.16	ConnectorEndToMembership_Mapping .....	463
7.7.12.2.17	ConnectorEndToOwnedFeature_Mapping .....	464
7.7.12.2.18	ConnectorEndToSubsettedFeature_Mapping .....	465
7.7.12.2.19	ConnectorEndToSubsettedFeatureMembership_Mapping .....	466
7.7.12.2.20	ConnectorMultiplicityMembership_Mapping .....	466
7.7.12.2.21	ConnectorType_Mapping .....	467
7.7.12.2.22	ConnectorTypeDerived_Mapping .....	468
7.7.12.2.23	CrossSubsetting_Mapping .....	469
7.7.12.2.24	End_Mapping .....	469
7.7.12.2.25	EndMembership_Mapping .....	470
7.7.12.2.26	EndToSubsettedFeature_Mapping .....	470
7.7.12.2.27	EndToSubsettedFeatureChaining_Mapping .....	471
7.7.12.2.28	MultiplicityReferenceUsage_Mapping .....	472
7.7.12.2.29	NonOwnedEndSubsetting_Mapping .....	473
7.7.12.2.30	NonOwnedEndToSubsettedFeatureMembership_Mapping .....	473
7.7.12.2.31	NonOwnedEnd_Mapping .....	474
7.7.12.2.32	NonOwnedEndMembership_Mapping .....	475
7.7.12.2.33	NonOwnedEndSubsettingMembership_Mapping .....	475
7.7.12.2.34	NonOwnedEndFeatureTyping_Mapping .....	476
7.7.12.2.35	OwnedEnd_Mapping .....	477
7.7.12.2.36	OwnedEndMembership_Mapping .....	478
7.7.12.2.37	Port_Mapping .....	479
7.7.12.2.38	PortUntyped_Mapping .....	479
7.7.12.2.39	PropertyToFeatureChaining_Mapping .....	480
7.7.12.2.40	QualifierMembership_Mapping .....	481
7.7.13	UseCases .....	481
7.7.13.1	Overview .....	481
7.7.13.2	UML4SysML::UseCases elements not mapped .....	481
7.7.13.3	Mapping Specifications .....	482
7.7.13.3.1	Actor_Mapping .....	482
7.7.13.3.2	Include_Mapping .....	482
7.7.13.3.3	IncludeFeatureTyping_Mapping .....	483
7.7.13.3.4	UseCase_Mapping .....	484
7.7.13.3.5	UseCaseActor_Mapping .....	485
7.7.13.3.6	UseCaseActorFeatureTyping_Mapping .....	486
7.7.13.3.7	UseCaseActorMembership_Mapping .....	487
7.7.13.3.8	UseCaseEmptySubjectReferenceUsage_Mapping .....	487
7.7.13.3.9	UseCaseObjectiveMembership_Mapping .....	488
7.7.13.3.10	UseCaseObjectiveRequirementUsage_Mapping .....	488
7.7.13.3.11	UseCaseObjectiveSubjectMembership_Mapping .....	489
7.7.13.3.12	UseCaseSubjectFeatureTyping_Mapping .....	490
7.7.13.3.13	UseCaseSubjectMembership_Mapping .....	490
7.7.13.3.14	UseCaseSubjectReferenceUsage_Mapping .....	491
7.7.14	Values .....	492
7.7.14.1	Overview .....	492
7.7.14.2	UML4SysML::Values elements not mapped .....	493
7.7.14.3	Mapping Specifications .....	493
7.7.14.3.1	EqualOperatorExpressionFeature_Mapping .....	493
7.7.14.3.2	EqualOperatorExpressionFeatureValue_Mapping .....	494
7.7.14.3.3	EqualOperatorExpressionOperandParameterMembership_Mapping .....	494
7.7.14.3.4	Expression_Mapping .....	495
7.7.14.3.5	ExpressionElse_Mapping .....	496
7.7.14.3.6	ExpressionElseMembership_Mapping .....	496

7.8.2.3.14 RateMetadataUsageDiscreteReferenceUsage_Mapping .....	478
7.8.2.3.15 RateMetadataUsageDiscreteReferenceUsageRedefinition_Mapping .....	479
7.8.2.3.16 RateMetadataUsageFeatureTyping_Mapping .....	480
7.8.2.3.17 RateOwningMembership_Mapping .....	481
7.8.2.3.18 Model Libraries .....	481
7.8.2.3.18.1 ControlValues .....	481
7.8.2.3.18.1.1 ControlValueKind .....	481
7.8.3 Allocations .....	481
7.8.3.1 Overview .....	482
7.8.3.2 SysML::Allocations elements not mapped .....	482
7.8.3.3 Mapping Specifications .....	482
7.8.3.3.1 Allocation_Mapping .....	482
7.8.3.3.2 AllocationFeatureMembership_Mapping .....	483
7.8.3.3.3 AllocationFeatureTyping_Mapping .....	484
7.8.3.3.4 AllocationReferenceUsage_Mapping .....	485
7.8.3.3.5 AllocationSourceReferenceUsageRedefinition_Mapping .....	485
7.8.3.3.6 AllocationTargetFeatureMembership_Mapping .....	486
7.8.3.3.7 AllocationTargetReferenceUsage_Mapping .....	487
7.8.3.3.8 AllocationTargetReferenceUsageRedefinition_Mapping .....	487
7.8.3.3.9 AllocationUsage_Mapping .....	488
7.8.3.3.10 AllocationUsageEndFeatureMembership_Mapping .....	489
7.8.3.3.11 AllocationUsageFeature_Mapping .....	489
7.8.3.3.12 AllocationUsageFeatureChaining_Mapping .....	490
7.8.3.3.13 AllocationUsageFeatureChainingChainedFeature_Mapping .....	491
7.8.3.3.14 AllocationUsageFeatureMembership_Mapping .....	491
7.8.3.3.15 AllocationUsageFeatureSubsetting_Mapping .....	492
7.8.3.3.16 AllocationUsageFeatureSubsettingFeature_Mapping .....	492
7.8.3.3.17 AllocationUsageTargetEndFeatureMembership_Mapping .....	493
7.8.3.3.18 AllocationUsageTargetFeature_Mapping .....	494
7.8.3.3.19 AllocationUsageTargetFeatureChaining_Mapping .....	494
7.8.3.3.20 AllocationUsageTargetFeatureSubsetting_Mapping .....	495
7.8.3.3.21 AllocationUsageTargetFeatureSubsettingFeature_Mapping .....	496
7.8.4 Blocks .....	496
7.8.4.1 Overview .....	497
7.8.4.2 SysML::Blocks elements not mapped .....	498
7.8.4.3 Mapping Specifications .....	498
7.8.4.3.1 AssociationBlock_Mapping .....	498
7.8.4.3.2 BindingConnector_Mapping .....	499
7.8.4.3.3 Block_Mapping .....	500
7.8.4.3.4 EncapsulatedBlock_Mapping .....	501
7.8.4.3.5 EncapsulatedBlockMetadataMembership_Mapping .....	502
7.8.4.3.6 EncapsulatedBlockMetadata_Mapping .....	502
7.8.4.3.7 EncapsulatedBlockMetadataFeatureMembership_Mapping .....	503
7.8.4.3.8 EncapsulatedBlockMetadataFeatureTyping_Mapping .....	504
7.8.4.3.9 EncapsulatedBlockMetadataReferenceUsage_Mapping .....	504
7.8.4.3.10 EncapsulatedBlockMetadataFeatureValue_Mapping .....	505
7.8.4.3.11 EncapsulatedBlockMetadataRedefinition_Mapping .....	506
7.8.4.3.12 PartProperty_Mapping .....	506
7.8.4.3.13 Model Libraries .....	507
7.8.4.3.13.1 PrimitiveValueTypes .....	507
7.8.4.3.13.1.1 Boolean .....	507
7.8.4.3.13.1.2 Complex .....	507
7.8.4.3.13.1.3 Integer .....	507
7.8.4.3.13.1.4 Number .....	508

7.7.14.3.7 ExpressionElseSpecification_Mapping .....	497
7.7.14.3.8 LiteralBoolean_Mapping .....	498
7.7.14.3.9 LiteralInteger_Mapping .....	498
7.7.14.3.10 LiteralNull_Mapping .....	499
7.7.14.3.11 LiteralReal_Mapping .....	499
7.7.14.3.12 LiteralSpecificationCommon_Mapping .....	500
7.7.14.3.13 LiteralSpecificationFeatureTyping_Mapping .....	501
7.7.14.3.14 LiteralString_Mapping .....	501
7.7.14.3.15 LiteralUnlimitedUnbounded_Mapping .....	502
7.7.14.3.16 LiteralUnlimitedInteger_Mapping .....	502
7.7.14.3.17 OpaqueExpressionAsValue_Mapping .....	503
7.7.14.3.18 OpaqueExpression_Mapping .....	504
7.7.14.3.19 OpaqueExpressionFeature_Mapping .....	505
7.7.14.3.20 OpaqueExpressionFeatureFeature_Mapping .....	505
7.7.14.3.21 OpaqueExpressionFeatureFeatureMembership_Mapping .....	506
7.7.14.3.22 OpaqueExpressionFeatureValue_Mapping .....	507
7.7.14.3.23 OpaqueExpressionFeatureValueExpression_Mapping .....	507
7.7.14.3.24 OpaqueExpressionFeatureValueExpressionMembership_Mapping .....	508
7.7.14.3.25 OpaqueExpressionMembership_Mapping .....	509
7.7.14.3.26 OpaqueExpressionParameterMembership_Mapping .....	509
7.7.14.3.27 OpaqueExpressionReferenceUsageReturnParameterMembership_Mapping .....	510
7.7.14.3.28 OpaqueExpressionReferenceUsage_Mapping .....	511
7.7.14.3.29 OpaqueExpressionReferenceUsageFeatureTyping_Mapping .....	511
7.7.14.3.30 OpaqueExpressionReferenceUsageUntyped_Mapping .....	512
7.7.14.3.31 OpaqueExpressionSpecification_Mapping .....	512
7.7.14.3.32 TimeExpression_Mapping .....	513
7.7.14.3.33 ValueSpecification_Mapping .....	514
7.8 Mappings from SysML v1.7 stereotypes .....	515
7.8.1 Overview .....	515
7.8.2 Activities .....	515
7.8.2.1 Overview .....	515
7.8.2.2 SysML::Activities elements not mapped .....	515
7.8.2.3 Mapping Specifications .....	516
7.8.2.3.1 ProbabilityMetadataUsage_Mapping .....	516
7.8.2.3.2 ProbabilityMetadataUsageFeatureMembership_Mapping .....	517
7.8.2.3.3 ProbabilityMetadataUsageFeatureTyping_Mapping .....	517
7.8.2.3.4 ProbabilityMetadataUsageReferenceUsage_Mapping .....	518
7.8.2.3.5 ProbabilityMetadataUsageReferenceUsageFeatureValue_Mapping .....	519
7.8.2.3.6 ProbabilityMetadataUsageReferenceUsageRedefinition_Mapping .....	520
7.8.2.3.7 ProbabilityOwningMembership_Mapping .....	520
7.8.2.3.8 RateMetadataUsage_Mapping .....	521
7.8.2.3.9 RateMetadataUsageContinuousFeatureMembership_Mapping .....	522
7.8.2.3.10 RateMetadataUsageFeatureValue_Mapping .....	523
7.8.2.3.11 RateMetadataUsageContinuousReferenceUsage_Mapping .....	524
7.8.2.3.12 RateMetadataUsageContinuousReferenceUsageRedefinition_Mapping .....	524
7.8.2.3.13 RateMetadataUsageDiscreteFeatureMembership_Mapping .....	525
7.8.2.3.14 RateMetadataUsageDiscreteReferenceUsage_Mapping .....	526
7.8.2.3.15 RateMetadataUsageDiscreteReferenceUsageRedefinition_Mapping .....	527
7.8.2.3.16 RateMetadataUsageFeatureTyping_Mapping .....	527
7.8.2.3.17 RateOwningMembership_Mapping .....	528
7.8.2.3.18 Model Libraries .....	529
7.8.2.3.18.1 ControlValues .....	529
7.8.2.3.18.1.1 ControlValueKind .....	529
7.8.3 Allocations .....	529
7.8.3.1 Overview .....	529
7.8.3.2 SysML::Allocations elements not mapped .....	529



7.8.4.3.1.5 Real .....	508
7.8.4.3.1.6 String .....	508
7.8.4.3.1.2 UnitAndQuantityKind .....	508
7.8.4.3.1.2.1 QuantityKind .....	508
7.8.4.3.1.2.2 Unit .....	508
7.8.4.3.1.4 ValueType_Mapping.....	508
7.8.5 ConstraintBlocks .....	509
7.8.5.1 Overview .....	509
7.8.5.2 Mapping Specifications .....	509
7.8.5.2.1 ConstraintBlock_Mapping .....	509
7.8.5.2.2 ConstraintParameter_Mapping.....	510
7.8.6 Model Elements .....	511
7.8.6.1 Overview .....	511
7.8.6.2 SysML::ModelElements elements not mapped.....	511
7.8.6.3 Mapping Specifications .....	512
7.8.6.3.1 ProblemRationaleMetadataFeatureMembership_Mapping.....	512
7.8.6.3.2 ProblemRationaleMetadataFeatureTyping_Mapping .....	512
7.8.6.3.3 ProblemRationaleMetadataReferenceUsage_Mapping.....	513
7.8.6.3.4 ProblemRationaleMetadataFeatureValue_Mapping .....	514
7.8.6.3.5 ProblemRationaleMetadataMembership_Mapping.....	514
7.8.6.3.6 Concern_Mapping .....	515
7.8.6.3.7 ConcernDocumentation_Mapping .....	516
7.8.6.3.8 ConcernOwningMembership_Mapping.....	517
7.8.6.3.9 ConcernStakeholderMembership_Mapping.....	517
7.8.6.3.10 ConcernStakeholderPartUsage_Mapping .....	518
7.8.6.3.11 ConcernStakeholderPartUsageFeatureTyping_Mapping .....	519
7.8.6.3.12 ConcernStakeholderPartUsageOwningMembership_Mapping .....	519
7.8.6.3.13 ConcernStakeholderPartUsageFeature_Mapping .....	520
7.8.6.3.14 ElementGroup_Mapping .....	520
7.8.6.3.15 ElementGroupMetadaMembership_Mapping.....	522
7.8.6.3.16 ElementGroupMetadataFeatureMembership_Mapping.....	522
7.8.6.3.17 ElementGroupMetadataFeatureTyping_Mapping.....	523
7.8.6.3.18 ElementGroupMetadataFeatureValue_Mapping.....	523
7.8.6.3.19 ElementGroupMetadataRedefinition_Mapping .....	524
7.8.6.3.20 ElementGroupMetadataReferenceUsage_Mapping .....	525
7.8.6.3.21 ElementGroupMetadataUsage_Mapping .....	525
7.8.6.3.22 ProblemRationale_Mapping.....	526
7.8.6.3.23 ProblemRationaleMetadataRedefinition_Mapping.....	527
7.8.6.3.24 ProblemRationaleMetadataUsage_Mapping.....	528
7.8.6.3.25 Stakeholder_Mapping .....	528
7.8.6.3.26 StakeholderMetadataUsage_Mapping.....	530
7.8.6.3.27 StakeholderMetadataFeatureMembership_Mapping .....	530
7.8.6.3.28 StakeholderMetadataFeatureTyping_Mapping.....	531
7.8.6.3.29 StakeholderMetadataOwningMembership .....	532
7.8.6.3.30 StakeholderMetadataReferenceUsage_Mapping .....	532
7.8.6.3.31 StakeholderMetadataReferenceUsageFeatureValue_Mapping.....	533
7.8.6.3.32 StakeholderMetadataReferenceUsageRedefinition_Mapping .....	534
7.8.6.3.33 Viewpoint_Mapping.....	534
7.8.6.3.34 ViewpointConcernReferenceSubsetting_Mapping .....	536
7.8.6.3.35 ViewpointConcernUsage_Mapping .....	537
7.8.6.3.36 ViewpointConstraintUsage_Mapping .....	537
7.8.6.3.37 ViewpointConstraintUsageDocumentation_Mapping .....	538
7.8.6.3.38 ViewpointConstraintUsageOwningMembership_Mapping.....	539
7.8.6.3.39 ViewpointFramedConcernMembership_Mapping.....	539



7.8.3.3 Mapping Specifications .....	529
7.8.3.3.1 Allocation_Mapping.....	529
7.8.3.3.2 AllocationFeatureMembership_Mapping .....	531
7.8.3.3.3 AllocationFeatureTyping_Mapping .....	531
7.8.3.3.4 AllocationReferenceUsage_Mapping .....	532
7.8.3.3.5 AllocationSourceReferenceUsageRedefinition_Mapping .....	533
7.8.3.3.6 AllocationTargetFeatureMembership_Mapping .....	534
7.8.3.3.7 AllocationTargetReferenceUsage_Mapping .....	534
7.8.3.3.8 AllocationTargetReferenceUsageRedefinition_Mapping .....	535
7.8.3.3.9 AllocationUsage_Mapping.....	536
7.8.3.3.10 AllocationUsageEndFeatureMembership_Mapping .....	536
7.8.3.3.11 AllocationUsageFeature_Mapping.....	537
7.8.3.3.12 AllocationUsageFeatureChaining_Mapping .....	538
7.8.3.3.13 AllocationUsageFeatureChainingChainedFeature_Mapping.....	538
7.8.3.3.14 AllocationUsageFeatureMembership_Mapping .....	539
7.8.3.3.15 AllocationUsageFeatureSubsetting_Mapping .....	540
7.8.3.3.16 AllocationUsageFeatureSubsettingFeature_Mapping.....	541
7.8.3.3.17 AllocationUsageTargetEndFeatureMembership_Mapping.....	541
7.8.3.3.18 AllocationUsageTargetFeature_Mapping .....	542
7.8.3.3.19 AllocationUsageTargetFeatureChaining_Mapping.....	543
7.8.3.3.20 AllocationUsageTargetFeatureSubsetting_Mapping .....	543
7.8.3.3.21 AllocationUsageTargetFeatureSubsettingFeature_Mapping .....	544
7.8.4 Blocks.....	545
7.8.4.1 Overview .....	545
7.8.4.2 SysML::Blocks elements not mapped .....	545
7.8.4.3 Mapping Specifications .....	546
7.8.4.3.1 AssociationBlock_Mapping .....	546
7.8.4.3.2 BindingConnector_Mapping .....	546
7.8.4.3.3 Block_Mapping .....	547
7.8.4.3.4 EncapsulatedBlock_Mapping .....	548
7.8.4.3.5 EncapsulatedBlockMetadataMembership_Mapping .....	549
7.8.4.3.6 EncapsulatedBlockMetadata_Mapping.....	550
7.8.4.3.7 EncapsulatedBlockMetadataFeatureMembership_Mapping.....	551
7.8.4.3.8 EncapsulatedBlockMetadataFeatureTyping_Mapping .....	551
7.8.4.3.9 EncapsulatedBlockMetadataReferenceUsage_Mapping.....	552
7.8.4.3.10 EncapsulatedBlockMetadataFeatureValue_Mapping .....	553
7.8.4.3.11 EncapsulatedBlockMetadataRedefinition_Mapping.....	553
7.8.4.3.12 FlowPropertyPart_Mapping .....	554
7.8.4.3.13 PartProperty_Mapping .....	555
7.8.4.3.14 Model Libraries .....	556
7.8.4.3.14.1 PrimitiveValueTypes .....	556
7.8.4.3.14.1.1 Boolean.....	556
7.8.4.3.14.1.2 Complex.....	556
7.8.4.3.14.1.3 Integer .....	556
7.8.4.3.14.1.4 Number .....	556
7.8.4.3.14.1.5 Real.....	556
7.8.4.3.14.1.6 String .....	556
7.8.4.3.14.2 UnitAndQuantityKind .....	556
7.8.4.3.14.2.1 QuantityKind .....	556
7.8.4.3.14.2.2 Unit .....	556
7.8.4.3.15 ValueType_Mapping.....	556
7.8.5 ConstraintBlocks .....	557
7.8.5.1 Overview .....	557
7.8.5.2 Mapping Specifications .....	557
7.8.5.2.1 ConstraintBlock_Mapping .....	557
7.8.5.2.2 ConstraintParameter_Mapping.....	558

7.8.6.3.40	ViewpointLanguagesMetadataFeatureMembership_Mapping .....	540
7.8.6.3.41	ViewpointLanguagesMetadataFeatureValue_Mapping .....	540
7.8.6.3.42	ViewpointLanguagesMetadataRedefinition_Mapping .....	541
7.8.6.3.43	ViewpointLanguagesMetadataReferenceUsage_Mapping .....	542
7.8.6.3.44	ViewpointMetadataFeatureTyping_Mapping .....	542
7.8.6.3.45	ViewpointLanguagesMetadataOperatorExpression_Mapping .....	543
7.8.6.3.46	ViewpointMetadataOwningMembership_Mapping .....	544
7.8.6.3.47	ViewpointMetadataUsage_Mapping .....	544
7.8.6.3.48	ViewpointPresentationsMetadataFeatureMembership_Mapping .....	545
7.8.6.3.49	ViewpointPresentationsMetadataFeatureValue_Mapping .....	546
7.8.6.3.50	ViewpointPresentationsMetadataOperatorExpression_Mapping .....	546
7.8.6.3.51	ViewpointPresentationsMetadataRedefinition_Mapping .....	547
7.8.6.3.52	ViewpointPresentationsMetadataReferenceUsage_Mapping .....	548
7.8.6.3.53	ViewpointRenderingFeatureMembership_Mapping .....	548
7.8.6.3.54	ViewpointRenderingUsage_Mapping .....	549
7.8.6.3.55	ViewpointRenderingUsageActionUsage_Mapping .....	550
7.8.6.3.56	ViewpointRenderingUsageActionUsageFeatureMembership_Mapping .....	550
7.8.6.3.57	ViewpointRenderingUsageActionUsageFeatureTyping_Mapping .....	551
7.8.6.3.58	ViewpointRequirementConstraintMembership_Mapping .....	551
7.8.6.3.59	ViewpointSatisfyFeatureMembership_Mapping .....	552
7.8.6.3.60	ViewpointSatisfyRequirementUsage_Mapping .....	553
7.8.6.3.61	ViewpointSatisfyRequirementUsageReferenceSubsetting_Mapping .....	553
7.8.6.3.62	ViewpointViewpointUsage_Mapping .....	554
7.8.6.3.63	ViewpointViewpointUsageFeatureMembership_Mapping .....	555
7.8.7	PortsAndFlows .....	555
7.8.7.1	Overview .....	555
7.8.7.2	SysML::Ports&Flows elements not mapped .....	556
7.8.7.3	Mapping Specifications .....	556
7.8.7.3.1	AcceptChangeStructuralFeatureEventAction_Mapping .....	556
7.8.7.3.2	CommonFullPort_Mapping .....	557
7.8.7.3.3	FeatureDirectionKind .....	558
7.8.7.3.4	FlowDirectionKind .....	558
7.8.7.3.5	FullPort_Mapping .....	558
7.8.7.3.6	FullPortMetadata_Mapping .....	559
7.8.7.3.7	FullPortMetadataFeatureMembership_Mapping .....	559
7.8.7.3.8	FullPortMetadataFeatureTyping_Mapping .....	560
7.8.7.3.9	FullPortMetadataOwningMembership_Mapping .....	560
7.8.7.3.10	FullPortMetadataReferenceUsage_Mapping .....	561
7.8.7.3.11	FullPortMetadataReferenceUsageFeatureValue_Mapping .....	562
7.8.7.3.12	FullPortMetadataReferenceUsageRedefinition_Mapping .....	562
7.8.7.3.13	FullPortUntyped_Mapping .....	563
7.8.7.3.14	InterfaceBlock_Mapping .....	564
7.8.7.3.15	InterfaceBlockConjugated_Mapping .....	564
7.8.7.3.16	OperationDirectedFeature_Mapping .....	565
7.8.8	Requirements .....	566
7.8.8.1	Overview .....	566
7.8.8.2	SysML::Requirements elements not mapped .....	567
7.8.8.3	Mapping Specifications .....	567
7.8.8.3.1	DeriveReq_Mapping .....	567
7.8.8.3.2	DeriveReqFeatureTyping_Mapping .....	568
7.8.8.3.3	DeriveReqSourceEndFeatureMembership_Mapping .....	568
7.8.8.3.4	DeriveReqSourceFeature_Mapping .....	569
7.8.8.3.5	DeriveReqSourceFeatureReferenceSubsetting_Mapping .....	570
7.8.8.3.6	DeriveReqTargetEndFeatureMembership_Mapping .....	570

7.8.6 Model Elements .....	559
7.8.6.1 Overview .....	559
7.8.6.2 SysML::ModelElements elements not mapped .....	560
7.8.6.3 Mapping Specifications .....	560
7.8.6.3.1 ProblemRationaleMetadataFeatureMembership_Mapping .....	560
7.8.6.3.2 ProblemRationaleMetadataFeatureTyping_Mapping .....	561
7.8.6.3.3 ProblemRationaleMetadataReferenceUsage_Mapping .....	561
7.8.6.3.4 ProblemRationaleMetadataFeatureValue_Mapping .....	562
7.8.6.3.5 ProblemRationaleMetadataMembership_Mapping .....	563
7.8.6.3.6 Concern_Mapping .....	563
7.8.6.3.7 ConcernDocumentation_Mapping .....	565
7.8.6.3.8 ConcernOwningMembership_Mapping .....	565
7.8.6.3.9 ConcernStakeholderMembership_Mapping .....	566
7.8.6.3.10 ConcernStakeholderPartUsage_Mapping .....	567
7.8.6.3.11 ConcernStakeholderPartUsageFeatureTyping_Mapping .....	567
7.8.6.3.12 ConcernStakeholderPartUsageOwningMembership_Mapping .....	568
7.8.6.3.13 ConcernStakeholderPartUsageFeature_Mapping .....	569
7.8.6.3.14 ElementGroup_Mapping .....	569
7.8.6.3.15 ElementGroupMetadaMembership_Mapping .....	570
7.8.6.3.16 ElementGroupMetadataFeatureMembership_Mapping .....	571
7.8.6.3.17 ElementGroupMetadataFeatureTyping_Mapping .....	572
7.8.6.3.18 ElementGroupMetadataFeatureValue_Mapping .....	572
7.8.6.3.19 ElementGroupMetadataRedefinition_Mapping .....	573
7.8.6.3.20 ElementGroupMetadataReferenceUsage_Mapping .....	574
7.8.6.3.21 ElementGroupMetadataUsage_Mapping .....	575
7.8.6.3.22 ProblemRationale_Mapping .....	575
7.8.6.3.23 ProblemRationaleMetadataRedefinition_Mapping .....	576
7.8.6.3.24 ProblemRationaleMetadataUsage_Mapping .....	577
7.8.6.3.25 Stakeholder_Mapping .....	578
7.8.6.3.26 StakeholderMetadataUsage_Mapping .....	579
7.8.6.3.27 StakeholderMetadataFeatureMembership_Mapping .....	580
7.8.6.3.28 StakeholderMetadataFeatureTyping_Mapping .....	580
7.8.6.3.29 StakeholderMetadataOwningMembership .....	581
7.8.6.3.30 StakeholderMetadataReferenceUsage_Mapping .....	582
7.8.6.3.31 StakeholderMetadataReferenceUsageFeatureValue_Mapping .....	582
7.8.6.3.32 StakeholderMetadataReferenceUsageRedefinition_Mapping .....	583
7.8.6.3.33 Viewpoint_Mapping .....	584
7.8.6.3.34 ViewpointConcernReferenceSubsetting_Mapping .....	585
7.8.6.3.35 ViewpointConcernUsage_Mapping .....	586
7.8.6.3.36 ViewpointConstraintUsage_Mapping .....	587
7.8.6.3.37 ViewpointConstraintUsageDocumentation_Mapping .....	588
7.8.6.3.38 ViewpointConstraintUsageOwningMembership_Mapping .....	588
7.8.6.3.39 ViewpointFramedConcernMembership_Mapping .....	589
7.8.6.3.40 ViewpointLanguagesMetadataFeatureMembership_Mapping .....	590
7.8.6.3.41 ViewpointLanguagesMetadataFeatureValue_Mapping .....	590
7.8.6.3.42 ViewpointLanguagesMetadataRedefinition_Mapping .....	591
7.8.6.3.43 ViewpointLanguagesMetadataReferenceUsage_Mapping .....	592
7.8.6.3.44 ViewpointMetadataFeatureTyping_Mapping .....	592
7.8.6.3.45 ViewpointLanguagesMetadataOperatorExpression_Mapping .....	593
7.8.6.3.46 ViewpointMetadataOwningMembership_Mapping .....	594
7.8.6.3.47 ViewpointMetadataUsage_Mapping .....	594
7.8.6.3.48 ViewpointPresentationsMetadataFeatureMembership_Mapping .....	595
7.8.6.3.49 ViewpointPresentationsMetadataFeatureValue_Mapping .....	596
7.8.6.3.50 ViewpointPresentationsMetadataOperatorExpression_Mapping .....	596
7.8.6.3.51 ViewpointPresentationsMetadataRedefinition_Mapping .....	597
7.8.6.3.52 ViewpointPresentationsMetadataReferenceUsage_Mapping .....	598

7.8.8.3.7 DeriveReqTargetFeature_Mapping.....	571
7.8.8.3.8 DeriveReqTargetFeatureReferenceSubsetting_Mapping.....	572
7.8.8.3.9 Refine_Mapping.....	572
7.8.8.3.10 RefineAnnotation_Mapping.....	573
7.8.8.3.11 RefineMetadataFeatureMembership_Mapping.....	574
7.8.8.3.12 RefineMetadataReferenceUsage_Mapping.....	575
7.8.8.3.13 RefineMetadataReferenceUsageFeatureValue_Mapping.....	575
7.8.8.3.14 RefineMetadataReferenceUsageRedefinition_Mapping.....	576
7.8.8.3.15 RefineMetadataUsage_Mapping.....	576
7.8.8.3.16 RefineMetadataUsageFeatureTyping_Mapping.....	577
7.8.8.3.17 Requirement_Mapping.....	578
7.8.8.3.18 RequirementDocumentation_Mapping.....	579
7.8.8.3.19 RequirementDocumentationMembership_Mapping.....	579
7.8.8.3.20 RequirementSubject_Mapping.....	580
7.8.8.3.21 RequirementSubjectMembership_Mapping.....	581
7.8.8.3.22 Satisfy_Mapping.....	581
7.8.8.3.23 SatisfyReferenceUsage_Mapping.....	583
7.8.8.3.24 SatisfyReferenceUsageFeatureMembership_Mapping.....	583
7.8.8.3.25 SatisfySubjectReferenceUsage_Mapping.....	584
7.8.8.3.26 SatisfySubjectReferenceUsageValue_Mapping.....	585
7.8.8.3.27 SatisfySubjectReferenceUsageValueFeature_Mapping.....	585
7.8.8.3.28 SatisfySubjectReferenceUsageFeatureChaining_Mapping.....	586
7.8.8.3.29 SatisfySubjectReferenceUsageValueFeatureChainingProperty_Mapping.....	587
7.8.8.3.30 SatisfySubjectReferenceUsageFeatureValue_Mapping.....	587
7.8.8.3.31 SatisfySubjectReferenceUsageValueOwningMembership_Mapping.....	588
7.8.8.3.32 SatisfySubjectSubjectMembership_Mapping.....	589
7.8.8.3.33 SatisfyFeatureTyping_Mapping.....	589
7.8.8.3.34 SatisfyReferenceUsageFeatureTyping_Mapping.....	590
7.8.8.3.35 TestCaseActivity_Mapping.....	590
7.8.8.3.36 TestCaseActivityReturnParameterMembership_Mapping.....	592
7.8.8.3.37 TestCaseVerifyObjectiveMembership_Mapping.....	592
7.8.8.3.38 TestCaseVerifyObjectiveRequirementUsage_Mapping.....	592
7.8.8.3.39 TestCaseVerifyRequirementUsageReferenceSubsetting_Mapping.....	593
7.8.8.3.40 TestCaseVerifyRequirementUsage_Mapping.....	593
7.8.8.3.41 Trace_Mapping.....	594
7.8.8.3.42 TraceAnnotation_Mapping.....	595
7.8.8.3.43 TraceMetadataFeatureMembership_Mapping.....	596
7.8.8.3.44 TraceMetadataReferenceUsage_Mapping.....	596
7.8.8.3.45 TraceMetadataReferenceUsageFeatureValue_Mapping.....	597
7.8.8.3.46 TraceMetadataReferenceUsageRedefinition_Mapping.....	598
7.8.8.3.47 TraceMetadataUsage_Mapping.....	598
7.8.8.3.48 TraceMetadataUsageFeatureTyping_Mapping.....	599
7.8.8.3.49 Verify_Mapping.....	600
7.8.8.3.50 Model Libraries.....	600
7.8.8.3.50.1 Verdicts.....	601
7.8.8.3.50.1.1 VerdictKind.....	601

7.8.6.3.53 ViewpointRenderingFeatureMembership_Mapping.....	599
7.8.6.3.54 ViewpointRenderingUsage_Mapping.....	599
7.8.6.3.55 ViewpointRenderingUsageActionUsage_Mapping.....	600
7.8.6.3.56 ViewpointRenderingUsageActionUsageFeatureMembership_Mapping.....	601
7.8.6.3.57 ViewpointRenderingUsageActionUsageFeatureTyping_Mapping.....	601
7.8.6.3.58 ViewpointRequirementConstraintMembership_Mapping.....	602
7.8.6.3.59 ViewpointSatisfyFeatureMembership_Mapping.....	602
7.8.6.3.60 ViewpointSatisfyRequirementUsage_Mapping.....	603
7.8.6.3.61 ViewpointSatisfyRequirementUsageReferenceSubsetting_Mapping.....	604
7.8.6.3.62 ViewpointViewpointUsage_Mapping.....	605
7.8.6.3.63 ViewpointViewpointUsageFeatureMembership_Mapping.....	605
7.8.7 PortsAndFlows.....	606
7.8.7.1 Overview.....	606
7.8.7.2 SysML::Ports&Flows elements not mapped.....	607
7.8.7.3 Mapping Specifications.....	607
7.8.7.3.1 AcceptChangeStructuralFeatureEventAction_Mapping.....	607
7.8.7.3.2 CommonFullPort_Mapping.....	608
7.8.7.3.3 ConjugatedPortDefinition_Mapping.....	608
7.8.7.3.4 FlowProperty_Mapping.....	609
7.8.7.3.5 FlowPropertyAttribute_Mapping.....	610
7.8.7.3.6 FlowPropertyUntyped_Mapping.....	611
7.8.7.3.7 FullPort_Mapping.....	612
7.8.7.3.8 FullPortMetadata_Mapping.....	613
7.8.7.3.9 FullPortMetadataFeatureMembership_Mapping.....	613
7.8.7.3.10 FullPortMetadataFeatureTyping_Mapping.....	614
7.8.7.3.11 FullPortMetadataOwningMembership_Mapping.....	615
7.8.7.3.12 FullPortMetadataReferenceUsage_Mapping.....	615
7.8.7.3.13 FullPortMetadataReferenceUsageFeatureValue_Mapping.....	616
7.8.7.3.14 FullPortMetadataReferenceUsageRedefinition_Mapping.....	617
7.8.7.3.15 FullPortUntyped_Mapping.....	617
7.8.7.3.16 InterfaceBlock_Mapping.....	618
7.8.7.3.17 InterfaceBlockConjugated_Mapping.....	619
7.8.7.3.18 InterfaceBlockOwningMembership_Mapping.....	620
7.8.7.3.19 OperationDirectedFeature_Mapping.....	620
7.8.7.3.20 PortConjugation_Mapping.....	621
7.8.8 Requirements.....	622
7.8.8.1 Overview.....	622
7.8.8.2 SysML::Requirements elements not mapped.....	622
7.8.8.3 Mapping Specifications.....	622
7.8.8.3.1 DeriveReq_Mapping.....	622
7.8.8.3.2 DeriveReqFeatureTyping_Mapping.....	623
7.8.8.3.3 DeriveReqSourceEndFeatureMembership_Mapping.....	624
7.8.8.3.4 DeriveReqSourceFeature_Mapping.....	625
7.8.8.3.5 DeriveReqSourceFeatureReferenceSubsetting_Mapping.....	625
7.8.8.3.6 DeriveReqTargetEndFeatureMembership_Mapping.....	626
7.8.8.3.7 DeriveReqTargetFeature_Mapping.....	627
7.8.8.3.8 DeriveReqTargetFeatureReferenceSubsetting_Mapping.....	627
7.8.8.3.9 Refine_Mapping.....	628
7.8.8.3.10 RefineAnnotation_Mapping.....	629
7.8.8.3.11 RefineMetadataFeatureMembership_Mapping.....	630
7.8.8.3.12 RefineMetadataReferenceUsage_Mapping.....	630
7.8.8.3.13 RefineMetadataReferenceUsageFeatureValue_Mapping.....	631
7.8.8.3.14 RefineMetadataReferenceUsageRedefinition_Mapping.....	632
7.8.8.3.15 RefineMetadataUsage_Mapping.....	632
7.8.8.3.16 RefineMetadataUsageFeatureTyping_Mapping.....	633
7.8.8.3.17 Requirement_Mapping.....	634



7.8.8.3.18 RequirementDocumentation_Mapping .....	635
7.8.8.3.19 RequirementDocumentationMembership_Mapping .....	636
7.8.8.3.20 RequirementSubject_Mapping .....	636
7.8.8.3.21 RequirementSubjectMembership_Mapping .....	637
7.8.8.3.22 Satisfy_Mapping .....	638
7.8.8.3.23 SatisfyReferenceUsage_Mapping .....	639
7.8.8.3.24 SatisfyReferenceUsageFeatureMembership_Mapping .....	640
7.8.8.3.25 SatisfySubjectReferenceUsage_Mapping .....	640
7.8.8.3.26 SatisfySubjectReferenceUsageValue_Mapping .....	641
7.8.8.3.27 SatisfySubjectReferenceUsageValueFeature_Mapping .....	642
7.8.8.3.28 SatisfySubjectReferenceUsageFeatureChaining_Mapping .....	642
7.8.8.3.29 SatisfySubjectReferenceUsageValueFeatureChainingProperty_Mapping .....	643
7.8.8.3.30 SatisfySubjectReferenceUsageFeatureValue_Mapping .....	644
7.8.8.3.31 SatisfySubjectReferenceUsageValueOwningMembership_Mapping .....	644
7.8.8.3.32 SatisfySubjectSubjectMembership_Mapping .....	645
7.8.8.3.33 SatisfyFeatureTyping_Mapping .....	646
7.8.8.3.34 SatisfyReferenceUsageFeatureTyping_Mapping .....	646
7.8.8.3.35 TestCaseActivity_Mapping .....	647
7.8.8.3.36 TestCaseActivityReturnParameterMembership_Mapping .....	648
7.8.8.3.37 TestCaseVerifyObjectiveMembership_Mapping .....	649
7.8.8.3.38 TestCaseVerifyObjectiveRequirementUsage_Mapping .....	649
7.8.8.3.39 TestCaseVerifyRequirementUsageReferenceSubsetting_Mapping .....	650
7.8.8.3.40 TestCaseVerifyRequirementUsage_Mapping .....	651
7.8.8.3.41 Trace_Mapping .....	651
7.8.8.3.42 TraceAnnotation_Mapping .....	652
7.8.8.3.43 TraceMetadataFeatureMembership_Mapping .....	653
7.8.8.3.44 TraceMetadataReferenceUsage_Mapping .....	654
7.8.8.3.45 TraceMetadataReferenceUsageFeatureValue_Mapping .....	654
7.8.8.3.46 TraceMetadataReferenceUsageRedefinition_Mapping .....	655
7.8.8.3.47 TraceMetadataUsage_Mapping .....	656
7.8.8.3.48 TraceMetadataUsageFeatureTyping_Mapping .....	656
7.8.8.3.49 Verify_Mapping .....	657
7.8.8.3.50 Model Libraries .....	658
7.8.8.3.50.1 Verdicts .....	658
7.8.8.3.50.1.1 VerdictKind .....	658

# List of Tables

1. List of all mappings .....	115
2. List of SysML v1 elements not mapped of this section .....	117
3. List of all mappings .....	242
4. List of SysML v1 elements not mapped of this section .....	243
5. List of all mappings .....	284
6. List of all mappings .....	320
7. List of SysML v1 elements not mapped of this section .....	321
8. List of all mappings .....	326
9. List of all mappings .....	326
10. List of all mappings .....	339
11. List of all mappings .....	346
12. List of SysML v1 elements not mapped of this section .....	347
13. List of all mappings .....	360
14. List of SysML v1 elements not mapped of this section .....	361
15. List of all mappings .....	384
16. List of all mappings .....	399
17. List of all mappings .....	410
18. List of all mappings .....	436
19. List of SysML v1 elements not mapped of this section .....	436
20. List of all mappings .....	446
21. List of SysML v1 elements not mapped of this section .....	447
22. List of all mappings .....	468
23. List of SysML v1 elements not mapped of this section .....	468
24. List of all mappings .....	482
25. List of SysML v1 elements not mapped of this section .....	482
26. List of all mappings .....	497
27. List of SysML v1 elements not mapped of this section .....	498
28. List of all mappings .....	509
29. List of all mappings .....	511
30. List of SysML v1 elements not mapped of this section .....	511
31. List of all mappings .....	555
32. List of SysML v1 elements not mapped of this section .....	556
33. List of all mappings .....	566
34. List of SysML v1 elements not mapped of this section .....	567



# List of Tables

1. List of all mappings .....	85
2. List of SysML v1 elements not mapped of this section .....	87
3. List of all mappings .....	221
4. List of SysML v1 elements not mapped of this section .....	221
5. List of all mappings .....	276
6. List of all mappings .....	313
7. List of SysML v1 elements not mapped of this section .....	313
8. List of all mappings .....	355
9. List of all mappings .....	369
10. List of all mappings .....	376
11. List of SysML v1 elements not mapped of this section .....	377
12. List of all mappings .....	391
13. List of SysML v1 elements not mapped of this section .....	391
14. List of all mappings .....	415
15. List of all mappings .....	431
16. List of all mappings .....	452
17. List of all mappings .....	481
18. List of SysML v1 elements not mapped of this section .....	482
19. List of all mappings .....	492
20. List of SysML v1 elements not mapped of this section .....	493
21. List of all mappings .....	515
22. List of SysML v1 elements not mapped of this section .....	515
23. List of all mappings .....	529
24. List of SysML v1 elements not mapped of this section .....	529
25. List of all mappings .....	545
26. List of SysML v1 elements not mapped of this section .....	545
27. List of all mappings .....	557
28. List of all mappings .....	559
29. List of SysML v1 elements not mapped of this section .....	560
30. List of all mappings .....	606
31. List of SysML v1 elements not mapped of this section .....	607
32. List of all mappings .....	622
33. List of SysML v1 elements not mapped of this section .....	622









# 0 Preface

## OMG

Founded in 1989, the Object Management Group, Inc. (OMG) is an open membership, not-for-profit computer industry standards consortium that produces and maintains computer industry specifications for interoperable, portable, and reusable enterprise applications in distributed, heterogeneous environments. Membership includes Information Technology vendors, end users, government agencies, and academia.

OMG member companies write, adopt, and maintain its specifications following a mature, open process. OMG's specifications implement the Model Driven Architecture<sup>®</sup> (MDA<sup>®</sup>), maximizing ROI through a full-lifecycle approach to enterprise integration that covers multiple operating systems, programming languages, middleware and networking infrastructures, and software development environments. OMG's specifications include: UML<sup>®</sup> (Unified Modeling Language<sup>™</sup>); CORBA<sup>®</sup> (Common Object Request Broker Architecture); CWM<sup>™</sup> (Common Warehouse Metamodel); and industry-specific standards for dozens of vertical markets.

More information on the OMG is available at <https://www.omg.org/>.

## OMG Specifications

As noted, OMG specifications address middleware, modeling, and vertical domain frameworks. All OMG Specifications are available from the OMG website at: <https://www.omg.org/spec>

All of OMG's formal specifications may be downloaded without charge from our website. (Products implementing OMG specifications are available from individual suppliers.) Copies of specifications, available in PostScript and PDF format, may be obtained from the Specifications Catalog cited above or by contacting the Object Management Group, Inc. at:

OMG Headquarters  
9C Medway Road, PMB 274  
Milford, MA 01757  
USA  
Tel: +1-781-444-0404  
Fax: +1-781-444-0320

Email: [pubs@omg.org](mailto:pubs@omg.org)

Certain OMG specifications are also available as ISO standards. Please consult <https://www.iso.org>

## Issues

All OMG specifications are subject to continuous review and improvement. As part of this process we encourage readers to report any ambiguities, inconsistencies, or inaccuracies they may find by completing the Issue Reporting Form listed on the main web page <https://www.omg.org>, under Specifications, Report an Issue.

# 0 Preface

## OMG

Founded in 1989, the Object Management Group, Inc. (OMG) is an open membership, not-for-profit computer industry standards consortium that produces and maintains computer industry specifications for interoperable, portable, and reusable enterprise applications in distributed, heterogeneous environments. Membership includes Information Technology vendors, end users, government agencies, and academia.

OMG member companies write, adopt, and maintain its specifications following a mature, open process. OMG's specifications implement the Model Driven Architecture<sup>®</sup> (MDA<sup>®</sup>), maximizing ROI through a full-lifecycle approach to enterprise integration that covers multiple operating systems, programming languages, middleware and networking infrastructures, and software development environments. OMG's specifications include: UML<sup>®</sup> (Unified Modeling Language<sup>™</sup>); CORBA<sup>®</sup> (Common Object Request Broker Architecture); CWM<sup>™</sup> (Common Warehouse Metamodel); and industry-specific standards for dozens of vertical markets.

More information on the OMG is available at <https://www.omg.org/>.

## OMG Specifications

As noted, OMG specifications address middleware, modeling, and vertical domain frameworks. All OMG Specifications are available from the OMG website at: <https://www.omg.org/spec>

All of OMG's formal specifications may be downloaded without charge from our website. (Products implementing OMG specifications are available from individual suppliers.) Copies of specifications, available in PostScript and PDF format, may be obtained from the Specifications Catalog cited above or by contacting the Object Management Group, Inc. at:

OMG Headquarters  
9C Medway Road, PMB 274  
Milford, MA 01757  
USA  
Tel: +1-781-444-0404  
Fax: +1-781-444-0320

Email: [pubs@omg.org](mailto:pubs@omg.org)

Certain OMG specifications are also available as ISO standards. Please consult <https://www.iso.org>

## Issues

All OMG specifications are subject to continuous review and improvement. As part of this process we encourage readers to report any ambiguities, inconsistencies, or inaccuracies they may find by completing the Issue Reporting Form listed on the main web page <https://www.omg.org>, under Specifications, Report an Issue.







# 1 Scope

This specification describes a transformation for a semantic translation from SysML v1 [SysMLv1] to SysML v2 [SysMLv2] in a precise way. (In this document, "SysML v1" refers to SysML v1.7, the last version of SysML prior to v2.0, and "SysML v2" refers to SysML v2.0, or whatever version corresponds to the current version of this specification.)

The main intent is to provide the rules on which automated conversions of SysML v1 models to the SysML v2 standard can be developed. In addition, this annex can be considered an educational document that provides useful information for people who would like to compare using SysML v2 and using SysML v1.

More sophisticated applications of this transformation can also be envisaged. For instance, a SysML v1 conformant tool could use this transformation to implement a limited subset of the SysML v2 API that will provide "SysMLv2-like" read-only access to its SysMLv1 models for external applications.

# 1 Scope

This specification describes a transformation for a semantic translation from SysML v1 [SysMLv1] to SysML v2 [SysMLv2] in a precise way. (In this document, "SysML v1" refers to SysML v1.7, the last version of SysML prior to v2.0, and "SysML v2" refers to SysML v2.0, or whatever version corresponds to the current version of this specification.)

The main intent is to provide the rules on which automated conversions of SysML v1 models to the SysML v2 standard can be developed. In addition, this annex can be considered an educational document that provides useful information for people who would like to compare using SysML v2 and using SysML v1.

More sophisticated applications of this transformation can also be envisaged. For instance, a SysML v1 conformant tool could use this transformation to implement a limited subset of the SysML v2 API that will provide "SysMLv2-like" read-only access to its SysMLv1 models for external applications.





## 2 Conformance

A tool shall demonstrate *conformance* with this specification by meeting all of the following requirements.

1. The tool shall implement the UML4SysML abstract syntax and SysML v1 profile conformant with [SysMLv1]. The tool should, but is not required, to provide the ability to import a SysML v1 model using standard XMI Model Interchange format [XMI].
2. The tool shall implement the SysML v2 abstract syntax conformant with [SysML v2]. The tool should, but is not required, to provide the ability to export a SysML v2 model KerML-standard model interchange project (see [KerML], Clause 10; see also [SysML v2], Clause 2).
3. The tool shall implement a transformation from an abstract syntax representation of an input SysML v1 model to the abstract syntax representation of an output SysML v2, as specified in [view link does not exist](#) of this specification.

A tool may claim *partial conformance* with this specification by satisfying the first two requirements above, but only implementing an identified subset of the mappings specified in [view link does not exist](#) and [view link does not exist](#). (Note that care must also be taken that certain mappings depend on other mappings, and so cannot reasonably be implemented separately.)

**Note.** A tool that conforms to [SysMLv2] is not required to necessarily implement a transformation conformant with this specification, or it may implement a SysML v1 to v2 transformation that is not claimed to conform with the transformation defined in this specification.

## 2 Conformance

A tool shall demonstrate *conformance* with this specification by meeting all of the following requirements.

1. The tool shall implement the UML4SysML abstract syntax and SysML v1 profile conformant with [SysMLv1]. The tool should, but is not required, to provide the ability to import a SysML v1 model using standard XMI Model Interchange format [XMI].
2. The tool shall implement the SysML v2 abstract syntax conformant with [SysML v2]. The tool should, but is not required, to provide the ability to export a SysML v2 model KerML-standard model interchange project (see [KerML], Clause 10; see also [SysML v2], Clause 2).
3. The tool shall implement a transformation from an abstract syntax representation of an input SysML v1 model to the abstract syntax representation of an output SysML v2, as specified in 4 of this specification.

A tool may claim *partial conformance* with this specification by satisfying the first two requirements above, but only implementing an identified subset of the mappings specified in 4. (Note that care must also be taken that certain mappings depend on other mappings, and so cannot reasonably be implemented separately.)

**Note.** A tool that conforms to [SysMLv2] is not required to necessarily implement a transformation conformant with this specification, or it may implement a SysML v1 to v2 transformation that is not claimed to conform with the transformation defined in this specification.







## 3 Normative References

The following normative documents contain provisions which, through reference in this text, constitute provisions of this specification.

[KerML] *Kernel Modeling Language (KerML)*, Version 1.0  
<https://www.omg.org/spec/KerML/1.0>

[MOF] *Meta Object Facility*, Version 2.5.1  
<https://www.omg.org/spec/MOF/2.5.1>

[OCL] *Object Constraint Language*, Version 2.4  
<https://www.omg.org/spec/OCL/2.4>

[SysML v1] *OMG Systems Modeling Language (SysML)*, Version 1.7  
<https://www.omg.org/spec/SysML/1.7>

[SysML v2] *OMG Systems Modeling Language (SysML)*, Version 2.0  
<https://www.omg.org/spec/SysML/2.0>

[UML] *Unified Modeling Language (UML)*, Version 2.5.1  
<https://www.omg.org/spec/UML/2.5.1>

[XMI] *XML Metadata Interchange*, Version 2.5.1  
<https://www.omg.org/spec/XMI/2.5.1>

## 3 Normative References

The following normative documents contain provisions which, through reference in this text, constitute provisions of this specification.

[KerML] *Kernel Modeling Language (KerML)*, Version 1.0  
<https://www.omg.org/spec/KerML/1.0>

[MOF] *Meta Object Facility*, Version 2.5.1  
<https://www.omg.org/spec/MOF/2.5.1>

[OCL] *Object Constraint Language*, Version 2.4  
<https://www.omg.org/spec/OCL/2.4>

[SysML v1] *OMG Systems Modeling Language (SysML)*, Version 1.7  
<https://www.omg.org/spec/SysML/1.7>

[SysML v2] *OMG Systems Modeling Language (SysML)*, Version 2.0  
<https://www.omg.org/spec/SysML/2.0>

[UML] *Unified Modeling Language (UML)*, Version 2.5.1  
<https://www.omg.org/spec/UML/2.5.1>

[XMI] *XML Metadata Interchange*, Version 2.5.1  
<https://www.omg.org/spec/XMI/2.5.1>





## 4 Terms and Definitions

Various terms and definitions are specified throughout the body of this specification.

## 4 Terms and Definitions

Various terms and definitions are specified throughout the body of this specification.







## 5 Symbols

No special symbols are defined in this specification.

## 5 Symbols

No special symbols are defined in this specification.





# 6 Introduction

## 6.1 Mapping Approach

The SysML v1 to v2 transformation is specified by directional mappings between UML metaclasses or stereotypes that are part of the SysML v1 specification [SysMLv1] (referenced below as the "SysML v1 scope") on the one hand, and the set of the metaclasses defined in the KerML [KerML] and SysMLv2 [SysMLv2] specifications (referenced below as "SysML v2") in the other hand. Some library classes are also involved.

Each mapping is a directed relationship that reifies a semantic link between a concept belonging to the SysML v1 scope on the source side and one concept belonging to SysML v2 (or one conforming library element) on the target side. As a set, those mappings constitute a declarative specification of a formal transformation that describes how the information encoded by the SysML v1 concepts can be reliably represented using constructs of SysML v2 metaclass instances.

In this approach, a mapping is represented by a UML class that has a pair of associations. One provides the `from` end that designates the source SysML v1 concept, while the other provides the `to` end that designates the target SysML v2 metaclass.

In addition to those associations, a mapping class provides a set of operations defining how the values of non-derived properties of the target metaclass instance have to be computed based on property values reachable from the source object. The computation algorithm is provided by the body condition of those operations and expressed using OCL code.

Note that the values assigned to the properties of the target object shall be instances of SysML v2 metaclasses, coming themselves from transformations of SysMLv1 objects to SysMLv2 objects. Since the specification is declarative, the order in which the individual transformations shall happen is not imposed. It is up to a conforming implementation to deal with this. Instead, the `getMapped` static operation is provided for referring to the result of a transformation from within an OCL rule. It returns a (possibly undefined) value, that is typed by the target metaclass of the mapping class from which it is invoked.

Each mapping class enables the transformation of any object that has the type specified by the `from` role to an object of the type specified by the `to` role, as long as it is not overloaded by a more specific mapping definition. In other words, assume a mapping is specified for the class A (i.e., it has A typing its `from` property), then it applies to any instance of a class B if B is a subclass of A and if there is no specialization of that mapping class specified for B (i.e., that has B typing its `from` property).

It is possible to restrict the applicability of a mapping specification to a specific subset of objects. This is achieved by the `filter` static operation that is evaluated against each candidate object. Only objects of the appropriate type for which this `filter` operation returns `true` shall be translated according to the specifications of that mapping class. The default `filter` operation always returns `true`.

Some mapping classes have one or more qualifiers for their `to` attribute. In such a case, each of those qualifiers reflects the specific property of the source type (i.e. the type of the `from` attribute) that has the same name and the same type. For those specific mappings, it is expected to get one instance of the target class (as specified by the type of the `to` attribute") for each actual combination of value of those properties for a given instance of object of the source type, assuming they pass the applicability filter as described above.

## 6.2 Acknowledgements

The primary authors of this specification document (and also developers of a proof-of-concept implementation of it) are:

# 6 Introduction

## 6.1 Mapping Approach

The SysML v1 to v2 transformation is specified by directional mappings between UML metaclasses or stereotypes that are part of the SysML v1 specification [SysMLv1] (referenced below as the "SysML v1 scope") on the one hand, and the set of the metaclasses defined in the KerML [KerML] and SysMLv2 [SysMLv2] specifications (referenced below as "SysML v2") in the other hand. Some library classes are also involved.

Each mapping is a directed relationship that reifies a semantic link between a concept belonging to the SysML v1 scope on the source side and one concept belonging to SysML v2 (or one conforming library element) on the target side. As a set, those mappings constitute a declarative specification of a formal transformation that describes how the information encoded by the SysML v1 concepts can be reliably represented using constructs of SysML v2 metaclass instances.

In this approach, a mapping is represented by a UML class that has a pair of associations. One provides the `from` end that designates the source SysML v1 concept, while the other provides the `to` end that designates the target SysML v2 metaclass.

In addition to those associations, a mapping class provides a set of operations defining how the values of non-derived properties of the target metaclass instance have to be computed based on property values reachable from the source object. The computation algorithm is provided by the body condition of those operations and expressed using OCL code.

Note that the values assigned to the properties of the target object shall be instances of SysML v2 metaclasses, coming themselves from transformations of SysMLv1 objects to SysMLv2 objects. Since the specification is declarative, the order in which the individual transformations shall happen is not imposed. It is up to a conforming implementation to deal with this. Instead, the `getMapped` static operation is provided for referring to the result of a transformation from within an OCL rule. It returns a (possibly undefined) value, that is typed by the target metaclass of the mapping class from which it is invoked.

Each mapping class enables the transformation of any object that has the type specified by the `from` role to an object of the type specified by the `to` role, as long as it is not overloaded by a more specific mapping definition. In other words, assume a mapping is specified for the class `A` (i.e., it has `A` typing its `from` property), then it applies to any instance of a class `B` if `B` is a subclass of `A` and if there is no specialization of that mapping class specified for `B` (i.e., that has `B` typing its `from` property).

It is possible to restrict the applicability of a mapping specification to a specific subset of objects. This is achieved by the `filter` static operation that is evaluated against each candidate object. Only objects of the appropriate type for which this `filter` operation returns `true` shall be translated according to the specifications of that mapping class. The default `filter` operation always returns `true`.

Some mapping classes have one or more qualifiers for their `to` attribute. In such a case, each of those qualifiers reflects the specific property of the source type (i.e. the type of the `from` attribute) that has the same name and the same type. For those specific mappings, it is expected to get one instance of the target class (as specified by the type of the `to` attribute") for each actual combination of value of those properties for a given instance of object of the source type, assuming they pass the applicability filter as described above.

## 6.2 Acknowledgements

The primary authors of this specification document (and also developers of a proof-of-concept implementation of it) are:

- Yves Bernard, Airbus

- Yves Bernard, Airbus
- Tim Weilkiens, oose

The specification was formally submitted for standardization by the following organizations:

- 88solutions Corporation
- Dassault Systèmes
- GfSE e.V.
- IBM
- INCOSE
- Intercax LLC
- Lockheed Martin Corporation
- MITRE
- Model Driven Solutions, Inc.
- PTC
- Simula Research Laboratory AS
- Thematrix Partners LLC

However, work on the specification was also supported by over 200 people in over 80 organizations that participated in the SysML v2 Submission Team (SST), by contributing use cases, providing critical review and comment, and validating the language design. The following individuals had leadership roles in the SST:

- Manas Bajaj, Intercax LLC (API and services development lead)
- Yves Bernard, Airbus (v1 to v2 transformation co-lead)
- Bjorn Cole, Lockheed Martin Corporation (metamodel development co-lead)
- Sanford Friedenthal, SAF Consulting (SST co-lead, requirements V&V lead)
- Charles Galey, Lockheed Martin Corporation (metamodel development co-lead)
- Karen Ryan, Siemens (metamodel development co-lead)
- Ed Seidewitz, Model Driven Solutions (SST co-lead, pilot implementation lead)
- Tim Weilkiens, oose (v1 to v2 transformation co-lead)

The specification was prepared using CATIA No Magic modeling tools and the OpenMBEE system for model publication (<http://www.openmbee.org>), with the invaluable support of the following individuals:

- Tyler Anderson, No Magic/Dassault Systèmes
- Christopher Delp, Jet Propulsion Laboratory
- Ivan Gomes, Twingineer
- Doris Lam, Jet Propulsion Laboratory
- Robert Karban, Jet Propulsion Laboratory
- Christopher Klotz, No Magic/Dassault Systèmes
- John Watson, Lightstreet Consulting



- Tim Weilkiens, oose

The specification was formally submitted for standardization by the following organizations:

- 88solutions Corporation
- Dassault Systèmes
- GfSE e.V.
- IBM
- INCOSE
- Intercax LLC
- Lockheed Martin Corporation
- MITRE
- Model Driven Solutions, Inc.
- PTC
- Simula Research Laboratory AS
- Thematrix Partners LLC

However, work on the specification was also supported by over 200 people in over 80 organizations that participated in the SysML v2 Submission Team (SST), by contributing use cases, providing critical review and comment, and validating the language design. The following individuals had leadership roles in the SST:

- Manas Bajaj, Intercax LLC (API and services development lead)
- Yves Bernard, Airbus (v1 to v2 transformation co-lead)
- Bjorn Cole, Lockheed Martin Corporation (metamodel development co-lead)
- Sanford Friedenthal, SAF Consulting (SST co-lead, requirements V&V lead)
- Charles Galey, Lockheed Martin Corporation (metamodel development co-lead)
- Karen Ryan, Siemens (metamodel development co-lead)
- Ed Seidewitz, Model Driven Solutions (SST co-lead, pilot implementation lead)
- Tim Weilkiens, oose (v1 to v2 transformation co-lead)

The specification was prepared using CATIA No Magic modeling tools and the OpenMBEE system for model publication (<http://www.openmbee.org>), with the invaluable support of the following individuals:

- Tyler Anderson, No Magic/Dassault Systèmes
- Christopher Delp, Jet Propulsion Laboratory
- Ivan Gomes, Twingineer
- Doris Lam, Jet Propulsion Laboratory
- Robert Karban, Jet Propulsion Laboratory
- Christopher Klotz, No Magic/Dassault Systèmes
- John Watson, Lightstreet Consulting

# 7 Mappings

## 7.1 Overview

This Clause is organized in order to match the packages that subdivide the model of the transformation. The `Foundations` package gathers the abstract classes that represent the concepts on top of which the mapping approach is built. The next subclause presents a utility class named `Helper` that provides reusable operations that simplify the OCL statements defining the computation rules of target properties and make them more readable. Libraries play an important role in SysML v2, and a specific one has been created in order to represent semantics equivalent to those of UML/SysML concepts, where needed. It is presented in this subclause as well.

The three next subclauses are dedicated to initializers, factories and generic mappings, respectively. They do not specify mappings, strictly speaking. Instead, they factorize more or less advanced OCL code that will be reused by the actual mapping specifications that are contained in the two last subclauses. The first of them is dedicated to UML metaclass from the UML4SYSML scope, while the second deals with SysML stereotypes more specifically.

## 7.2 Foundations

### 7.2.1 Overview

The concepts defined by KerML/SysML v2 are relatively similar to those of UML/SysML v1, but the ways they are built are different. This makes the specification of the global transformation quite complex. In order to keep it manageable, specific kinds of foundational classes are provided. They represent concepts on which classical "model to model" transformation technologies rely:

- The mappings built on top of the abstract class `Mapping` shall be executed only when they are explicitly called. Each call shall produce a new target element, whatever the source element. It specifies a `from` property typed by the `UML::CommonStructure::Element` metaclass that shall be redefined by any of its subclass for specifying the convenient type of source element. Also it specifies a default (neutral) filter and a set of `getMapped` operations for various purposes: regular mapping result, qualified mapping result and mapping result for a collection of elements.
- The mappings built on top of the abstract class `UniqueMapping`, specified as a specialization of the `Mapping` class, shall produce only one target element for a given source element, whatever the number of time they are called.
- The mappings built on top of the abstract class `MainMapping`, specified as a specialization of the `UniqueMapping` class, shall be systematically executed (i.e. implicitly called) for all the elements that match both their source type and filter. There can be at most one main mapping for a given source type and only one target element shall be produced for a given source element.

The corresponding classes are located in the `Foundations` package.

Sometimes, it is necessary to be able to generate elements in the target model without having to provide an explicit link with a source element. In such a case, a mapping class is not appropriate. Instead the mapping framework provides the concept of a `Factory`.

Last, the concept of an `Initializer` allows the factorization of the specification of properties' default values that can be inherited by mappings and factories, as convenient.

In the model of the transformation that is specified here, all of the abstract classes of this `Foundations` package are subject to direct or indirect subclassing. In other words, this specification is built as a set of interrelated initializers, factories, regular, unique and main mappings, where the initializers' operation factorizes the specification of default

# 7 Mappings

## 7.1 Overview

This Clause is organized in order to match the packages that subdivide the model of the transformation. The `Foundations` package gathers the abstract classes that represent the concepts on top of which the mapping approach is built. The next subclause presents a utility class named `Helper` that provides reusable operations that simplify the OCL statements defining the computation rules of target properties and make them more readable. Libraries play an important role in SysML v2, and a specific one has been created in order to represent semantics equivalent to those of UML/SysML concepts, where needed. It is presented in this subclause as well.

The three next subclauses are dedicated to initializers, factories and generic mappings, respectively. They do not specify mappings, strictly speaking. Instead, they factorize more or less advanced OCL code that will be reused by the actual mapping specifications that are contained in the two last subclauses. The first of them is dedicated to UML metaclass from the UML4SYSML scope, while the second deals with SysML stereotypes more specifically.

## 7.2 Foundations

### 7.2.1 Overview

The concepts defined by KerML/SysML v2 are relatively similar to those of UML/SysML v1, but the ways they are built are different. This makes the specification of the global transformation quite complex. In order to keep it manageable, specific kinds of foundational classes are provided. They represent concepts on which classical "model to model" transformation technologies rely:

- The mappings built on top of the abstract class `Mapping` shall be executed only when they are explicitly called. Each call shall produce a new target element, whatever the source element. It specifies a `from` property typed by the `UML::CommonStructure::Element` metaclass that shall be redefined by any of its subclass for specifying the convenient type of source element. Also it specifies a default (neutral) filter and a set of `getMapped` operations for various purposes: regular mapping result, qualified mapping result and mapping result for a collection of elements.
- The mappings built on top of the abstract class `UniqueMapping`, specified as a specialization of the `Mapping` class, shall produce only one target element for a given source element, whatever the number of time they are called.
- The mappings built on top of the abstract class `MainMapping`, specified as a specialization of the `UniqueMapping` class, shall be systematically executed (i.e. implicitly called) for all the elements that match both their source type and filter. There can be at most one main mapping for a given source type and only one target element shall be produced for a given source element.

The corresponding classes are located in the `Foundations` package.

Sometimes, it is necessary to be able to generate elements in the target model without having to provide an explicit link with a source element. In such a case, a mapping class is not appropriate. Instead the mapping framework provides the concept of a `Factory`.

Last, the concept of an `Initializer` allows the factorization of the specification of properties' default values that can be inherited by mappings and factories, as convenient.

In the model of the transformation that is specified here, all of the abstract classes of this `Foundations` package are subject to direct or indirect subclassing. In other words, this specification is built as a set of interrelated initializers, factories, regular, unique and main mappings, where the initializers' operation factorizes the specification of default values for their target element, wherever possible. Those "default operations" are either used as-is or redefined by mappings or factories that can inherit for a specific initializer, as appropriate.

values for their target element, wherever possible. Those "default operations" are either used as-is or redefined by mappings or factories that can inherit for a specific initializer, as appropriate.

## 7.2.2 Foundational class specifications

### 7.2.2.1 UniqueMapping

#### Description

The mappings built on top of the abstract class UniqueMapping are a specific kind of Mappings that are intended to produce only one target element for a given source element, whatever the number of time they are called. If a getMapped is called several time with the same source element, the target element returned shall always be the same.

#### Generalizations

- Mapping (from Foundations)

### 7.2.2.2 Factory

#### Description

Similarly to the well-known to the homonyms software design pattern, a Factory can be used for specifying the production of a target element without any link with a source element. Factories have in common with mapping classes the operations that specify how the properties of the target element shall be computed and the "to" property that specifies the type of the target element. However factories do not define source element. Instead, they can have parameters. Those parameters, if any, shall be specified by properties with appropriate types and multiplicities. Factories are expected to provide a "create" operation with parameters matching in type and multiplicity the properties that are intended to specify them.

#### Generalizations

- Initializer (from Foundations)

### 7.2.2.3 Mapping

#### Description

This is the generic abstract class that provides the basic features of any mapping class mapping. The mappings built on top of the abstract class Mapping are intended to be executed only when explicitly called (e.g. by the rule of another mapping class). It specifies a "from" property typed by the UML::CommonStructure::Element metaclass that shall be redefined by any of its subclass for specifying the convenient type of source element. Also it specifies a default (neutral) filter and a set of getMapped operations for various purposes: regular mapping result, qualified mapping result and mapping result for a collection of elements. Each call to the getMapped operation shall produce a new target element, whatever the source element provided. Instances of Mapping class are represent a link between one source element and the target element produced by the transformation specified by that mapping class.

#### Generalizations

- Initializer (from Foundations)

#### Association Ends

- from : Element [1]

## 7.2.2 Foundational class specifications

### 7.2.2.1 UniqueMapping

#### Description

The mappings built on top of the abstract class UniqueMapping are a specific kind of Mappings that are intended to produce only one target element for a given source element, whatever the number of time they are called. If a getMapped is called several time with the same source element, the target element returned shall always be the same.

#### General Classes

- Mapping (from Foundations)

### 7.2.2.2 Factory

#### Description

Similarly to the well-known to the homonyms software design pattern, a Factory can be used for specifying the production of a target element without any link with a source element. Factories have in common with mapping classes the operations that specify how the properties of the target element shall be computed and the "to" property that specifies the type of the target element. However factories do not define source element. Instead, they can have parameters. Those parameters, if any, shall be specified by properties with appropriate types and multiplicities. Factories are expected to provide a "create" operation with parameters matching in type and multiplicity the properties that are intended to specify them.

#### General Classes

- Initializer (from Foundations)

### 7.2.2.3 Mapping

#### Description

This is the generic abstract class that provides the basic features of any mapping class mapping. The mappings built on top of the abstract class Mapping are intended to be executed only when explicitly called (e.g. by the rule of another mapping class). It specifies a "from" property typed by the UML::CommonStructure::Element metaclass that shall be redefined by any of its subclass for specifying the convenient type of source element. Also it specifies a default (neutral) filter and a set of getMapped operations for various purposes: regular mapping result, qualified mapping result and mapping result for a collection of elements. Each call to the getMapped operation shall produce a new target element, whatever the source element provided. Instances of Mapping class are represent a link between one source element and the target element produced by the transformation specified by that mapping class.

#### General Classes

- Initializer (from Foundations)

#### Association Ends

- from : Element [1]

#### Operations

- filter (in src : Element) : Boolean [1]  
returns "true" if the element provided as the actual parameter value can have a mapping to an instance of

## Operations

- `filter (in src : Element) : Boolean [1]`  
returns "true" if the element provided as the actual parameter value can have a mapping to an instance of the type specified by the "to" attribute (i.e. can be used as a value for the "from" attribute)

```
true
```

- `getMapped (in fromVar : Element) : Element [1]`

### postConditions:

```
self.filter(fromVar) and
self.to.allFeatures()->selectByKind(UML::Property)->reject(isDerived)
->forAll(p | let ops: Operation = self.allFeatures()
    ->selectByKind(UML::Operation)->any(o | o.name = p.name) in
    p = ops()) and
result = self.to
```

- `getMapped (in fromVar : Element, in qual : Element) : Element [1]`

### postConditions:

```
self.filter(fromVar) and
self.to.allFeatures()->selectByKind(UML::Property)->reject(isDerived)
->forAll(p | let ops: Operation = self.allFeatures()
    ->selectByKind(UML::Operation)->any(o | o.name = p.name) in
    if ops.ownedParameter
        ->select(p | p.direction = UML::ParameterDirectionKind::_'in')
        ->size()=1 then
            p = ops(qual)
        else if ops.ownedParameter
            ->select(p | p.direction = UML::ParameterDirectionKind::_'in')
            ->size()=0 then
                p = ops()
            else
                invalid
            endif endif) and
result = self.to
```

- `getMappedColl (in fromColl : Element) : Element [0..*]`

### postConditions:

```
result = fromColl->collect(e | self.getMapped(e))
```

## 7.2.2.4 MainMapping

### Description

The mappings built on top of the abstract class MainMapping are a specific kind of UniqueMappings class that are always implicitly called for any element in the source model that match both their source type (as specified by their

the type specified by the "to" attribute (i.e. can be used as a value for the "from" attribute)

```
true
```

- `getMapped (in fromVar : Element) : Element [1]`

**postConditions:**

```
self.filter(fromVar) and
self.to.allFeatures()->selectByKind(UML::Property)->reject(isDerived)
->forAll(p | let ops: Operation = self.allFeatures()
  ->selectByKind(UML::Operation)->any(o | o.name = p.name) in
  p = ops()) and
result = self.to
```

- `getMapped (in fromVar : Element, in qual : Element) : Element [1]`

**postConditions:**

```
self.filter(fromVar) and
self.to.allFeatures()->selectByKind(UML::Property)->reject(isDerived)
->forAll(p | let ops: Operation = self.allFeatures()
  ->selectByKind(UML::Operation)->any(o | o.name = p.name) in
  if ops.ownedParameter
    ->select(p | p.direction = UML::ParameterDirectionKind::_'in')
    ->size()=1 then
      p = ops(qual)
  else if ops.ownedParameter
    ->select(p | p.direction = UML::ParameterDirectionKind::_'in')
    ->size()=0 then
      p = ops()
  else
    invalid
  endif endif) and
result = self.to
```

- `getMappedColl (in fromColl : Element) : Element [0..*]`

**postConditions:**

```
result = fromColl->collect(e | self.getMapped(e))
```

## 7.2.2.4 MainMapping

### Description

The mappings built on top of the abstract class MainMapping are a specific kind of UniqueMappings class that are always implicitly called for any element in the source model that match both their source type (as specified by their "from" property) and their filter condition. If more than one main mapping is specified for a given source type, they shall have filters that specify mutually exclusive conditions. Also, as with any unique mapping, only one target element shall be produced for a given source element.

### General Classes

- UniqueMapping (from Foundations)

"from" property) and their filter condition. If more than one main mapping is specified for a given source type, they shall have filters that specify mutually exclusive conditions. Also, as with any unique mapping, only one target element shall be produced for a given source element.

### Generalizations

- UniqueMapping (from Foundations)

#### 7.2.2.5 Initializer

##### Description

The abstract class Initializer is the common ancestor of Mapping and Factory. It specifies a "to" property typed by the KerML::Root::Element metaclass that shall be redefined by any of its subclass for specifying the convenient type of target element. Initializers are intended to specify reusable properties' computation rules, mainly for initializing them with default values. Those rules will be inherited or redefined by the sub-classes, as appropriate.

##### Attributes

- /inputs [0..\*]

##### Association Ends

- to : Element [1]

## 7.3 Mapping Helper and Library

### 7.3.1 Helper

##### Description

The Helper class contains operations that are used by multiple mapping classes. The specification is in the bodyCondition.

##### Operations

- actionOwnedRelationship (in src : Element) : Relationship [0..\*]  
Reusable mapping rule for owned relationships of a UML4SysML::Action mapping.

```
let actionInputPin: Set(UML::Element) =
  src.ownedElement->select(e | e.ocIsTypeOf(UML::ActionInputPin)) in
let triggers: Set(UML::Element) =
  src.ownedElement->select(e | e.ocIsKindOf(UML::Trigger)) in
let toElementFMS: Set(UML::Element) =
  src.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in
let toElementOMS: Set(UML::Element) =
  (((src.ownedElement - toElementFMS) - actionInputPin) - triggers) in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
```

- activityOwnedRelationship (in src : Element) : Relationship [0..\*]  
Reusable mapping rule for owned relationships of a UML4SysML::Activity mapping.



### 7.2.2.5 Initializer

#### Description

The abstract class Initializer is the common ancestor of Mapping and Factory. It specifies a "to" property typed by the KerML::Root::Element metaclass that shall be redefined by any of its subclass for specifying the convenient type of target element. Initializers are intended to specify reusable properties' computation rules, mainly for initializing them with default values. Those rules will be inherited or redefined by the sub-classes, as appropriate.

#### Attributes

- /inputs [0..\*]

#### Association Ends

- to : Element [1]

## 7.3 Mapping Helper and Library

### 7.3.1 Helper

[SYSML2 -76](#): Transformation does not cover SysMLv1::FlowProperty

[SYSML2 -376](#): Specification of Helper::getScalarValueType() uses unknown OCL function

[SYSML2 -171](#): Helper::getScalarValueType operation is not robust enough

[SYSML2 -300](#): Weak check of input parameter in Helper::getScalarValueType

[SYSML2 -424](#): Adopted resolution SYSML2 -403 has impact on the v1 to v2 Transformation

#### Description

The Helper class contains operations that are used by multiple mapping classes. The specification is in the bodyCondition.

#### Operations

- actionOwnedRelationship (in src : Element) : Relationship [0..\*]  
Reusable mapping rule for owned relationships of a UML4SysML::Action mapping.

```
let actionInputPin: Set(UML::Element) =
  src.ownedElement->select(e | e.ocIsTypeOf(UML::ActionInputPin)) in
let triggers: Set(UML::Element) =
  src.ownedElement->select(e | e.ocIsKindOf(UML::Trigger)) in
let toElementFMS: Set(UML::Element) =
  src.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in
let toElementOMS: Set(UML::Element) =
  (((src.ownedElement - toElementFMS) - actionInputPin) - triggers) in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
```

- activityOwnedRelationship (in src : Element) : Relationship [0..\*]  
Reusable mapping rule for owned relationships of a UML4SysML::Activity mapping.

```
let initialNodes: Set(UML!Element) = src.ownedElement->select(e | e.ocIsKindOf(UML!InitialN
let flowFinalNodes: Set(UML!Element) = src.ownedElement->select(e | e.ocIsKindOf(UML!FlowFi
let elementsFMS: Set(UML!Element) = (src.ownedElement->select(e | e.ocIsKindOf(UML!ControlN
```

```

let initialNodes : Set(UML::Element) =
    src.ownedElement->select(e | e.ocIsKindOf(UML::InitialNode)) in
let flowFinalNodes : Set(UML::Element) =
    src.ownedElement->select(e | e.ocIsKindOf(UML::FlowFinalNode)) in
let ignoreActivityFinalNodes : Set(UML::Element) =
    src.ownedElement->select(e | e.ocIsKindOf(UML::ActivityFinalNode)) in
let ignoreEdgesToActivityFinalNodes : Set(UML::Element) =
    src.ownedElement->select(e | e.ocIsKindOf(UML::ActivityEdge)
    and e.ocAsType(UML::ActivityEdge).target.ocIsTypeOf(UML::ActivityFinalNode)) in
let elementsFMS : Set(UML::Element) =
    (((src.ownedElement->select(e | e.ocIsKindOf(UML::ControlNode) or
    e.ocIsKindOf(UML::Action) or e.ocIsKindOf(UML::ControlFlow) or
    e.ocIsKindOf(UML::ObjectFlow) or e.ocIsKindOf(UML::Property))
    - initialNodes) - flowFinalNodes) - ignoreActivityFinalNodes)
    - ignoreEdgesToActivityFinalNodes in
let parameters : Set(UML::Parameter) =
    src.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
let ignoreParameterNodes : Set(UML::ActivityParameterNode) =
    src.ownedElement->select(e | e.ocIsKindOf(UML::ActivityParameterNode)) in
let ignoreActivityPartition : Set(UML::ActivityPartition) =
    src.ownedElement->select(e | e.ocIsKindOf(UML::ActivityPartition)) in
let ignoreInterruptibleActivityRegion : Set(UML::InterruptibleActivityRegion) =
    src.ownedElement
    ->select(e | e.ocIsKindOf(UML::InterruptibleActivityRegion)) in
let ownedClassifier : Sequence(UML::Classifier) =
    src.ownedElement->select(e | e.ocIsKindOf(UML::Classifier)) in
let variables : Sequence(UML::Variable) =
    src.ownedElement->select(e | e.ocIsKindOf(UML::Variable)) in
let parameterSets : Set(UML::ParameterSet) =
    src.ownedElement->select(e | e.ocIsKindOf(UML::ParameterSet)) in
let elementsOMS : Set(UML::Element) =
    (((((((((((src.ownedElement-initialNodes)-flowFinalNodes)-
    ignoreActivityFinalNodes)-ignoreEdgesToActivityFinalNodes)
    -elementsFMS)-parameters)-ignoreParameterNodes)-
    ignoreActivityPartition)-ignoreInterruptibleActivityRegion)-
    ownedClassifier)-variables)-parameterSets)-
    Set{from.classifierBehavior} in
let memberships : Sequence(UML::Element) =
elementsOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(initialNodes->collect(e | InitialNodeMembership_Mapping.getMapped(e)))
->union(flowFinalNodes->collect(e | FlowFinalNodeMembership_Mapping.getMapped(e)))
->union(elementsFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(variables->collect(e | VariableMembership_Mapping.getMapped(e)))
->union(parameterSets->collect(e | ParameterSetMembership_Mapping.getMapped(e)))
->union(ownedClassifier
->collect(e | ElementOwningMembership_Mapping.getMapped(e))) in
if src.classifierBehavior.ocIsUndefined() then
    memberships
else
    memberships
    ->append(BehavoredClassifierFeatureMembership_Mapping.getMapped(src))
endif

```

- **createUUID () : String [1]**  
Creates a UUID. The specification is implementation-specific and therefore cannot provided here.
- **excludedPin (in pin : Pin) : Boolean [1]**  
Checks if a pin is excluded from the transformation, because it is already defined as a parameter in the

- `createUUID () : String [1]`  
Creates a UUID. The specification is implementation-specific and therefore cannot be provided here.
- `excludedPin (in pin : Pin) : Boolean [1]`  
Checks if a pin is excluded from the transformation, because it is already defined as a parameter in the SysMLv1Library.

- `getAppliedStereotypes (in element : Element) : Stereotype [0..*]`  
Returns the list of applied stereotypes. The specification is implementation-specific and therefore cannot provided here.
- `getEnumerationType (in t : Enumeration) : EnumerationDefinition [1]`  
Maps a given UML4SysM::Enumeration to the appropriate SysML v2 EnumerationDefinition.

Systems Modeling Language v2.0 Beta 3

SysMLv1Library.

```
if (pin.owner.ocIsTypeOf(UML::AddVariableValueAction) and
    (pin.name = 'value' or pin.name = 'insertAt')) then
    true
else if (pin.owner.ocIsTypeOf(UML::AddStructuralFeatureValueAction) and
    (pin.name = 'value' or pin.name = 'insertAt' or pin.name = 'object')) then
    true
else
    false
endif endif
```

- **getAppliedStereotypes (in element : Element) : Stereotype [0..\*]**  
Returns the list of applied stereotypes. The specification is implementation-specific and therefore cannot be provided here.
- **getEnumerationType (in t : Enumeration) : EnumerationDefinition [1]**  
Maps a given UML4SysM::Enumeration to the appropriate SysML v2 EnumerationDefinition.

```
let enum: SYSML2::EnumerationDefinition =
    Enumeration_Mapping.getMapped(t) in
if enum.ocIsKindOf(SYSML2::EnumerationDefinition) then
    enum
else if t.name = 'VerdictKind' then
    SYSML2::EnumerationDefinition.allInstances()
    ->any(e | e.qualifiedName = 'VerificationCases::VerdictKind')

else if t = UML::ParameterDirectionKind then
    KerML::FeatureDirectionKind

else if t.qualifiedName =
    'SysML::Libraries::ControlValues::ControlValueKind' then
    SYSML2::EnumerationDefinition.allInstances()
    ->any(e | e.qualifiedName =
        'SysMLv1Library::Enumerations::ControlValueKind')

else
    SYSML2::EnumerationDefinition.allInstances()
    ->any(e | e.qualifiedName =
        'SysMLv1Library::Enumerations::' + t.name)
endif
endif
endif
endif
```

- **getFlowDirectionKind (in v : EnumerationLiteral) : FeatureDirectionKind [1]**  
Maps a given SysMLv1 feature direction enumeration literal to a SysML v2 FeatureDirectionKind enumeration literal.

```
if v.enumeration.qualifiedName =
    'SysML::Ports&Flows::FlowDirectionKind' then
if v = SysML::FlowDirectionKind::_out' then
    KerML::FeatureDirectionKind::_out'
else if (v = SysML::FlowDirectionKind::_in') then
```

```

        ->any(e | e.qualifiedName =
            'SysMLv1Library::Enumerations::' + t.name)
    endif
endif
endif
endif
endif

```

- **getFlowDirectionKind (in v : EnumerationLiteral) : FeatureDirectionKind [1]**  
Maps a given SysMLv1 feature direction enumeration literal to a SysML v2 FeatureDirectionKind enumeration literal.

```

if v.enumeration.qualifiedName =
    'SysML::Ports&Flows::FlowDirectionKind' then
    if v.name = 'out' then
        KerML::FeatureDirectionKind::_out'
    else if v.name = 'in' then
        KerML::FeatureDirectionKind::_in'
    else if v.name = 'inout' then
        KerML::FeatureDirectionKind::inout
    else
        invalid
    endif endif endif
else
    invalid
endif

```

- **getID (in src : Element) : String [1]**  
Returns the identifier of a UML4SysML::Element. The specification is implementation-specific and therefore cannot be provided here.
- **getKerMLFeatureDirectionKind (in v : EnumerationLiteral) : FeatureDirectionKind [1]**  
Maps a given SysMLv1 feature direction enumeration literal to a SysML v2 FeatureDirectionKind enumeration literal.

```

if v.enumeration.qualifiedName =
    'SysML::Ports&Flows::FeatureDirectionKind' or
    v.enumeration.qualifiedName = 'SysML::Ports&Flows::FeatureDirection' then
    if v = SysML::FeatureDirectionKind::provided then
        KerML::FeatureDirectionKind::_out'
    else if (v = SysML::FeatureDirectionKind::required) then
        KerML::FeatureDirectionKind::_in'
    else if (v = SysML::FeatureDirectionKind::providedRequired) then
        KerML::FeatureDirectionKind::inout
    else
        invalid
    endif endif endif
else
    invalid
endif

```

- **getKerMLParameterDirectionKind (in v : ParameterDirectionKind) : FeatureDirectionKind [1]**  
Maps a given SysMLv1 parameter direction enumeration literal to a SysML v2 FeatureDirectionKind enumeration literal.

```

if v = UML::ParameterDirectionKind::_in' then
    KerML::FeatureDirectionKind::_in'
else if (v = UML::ParameterDirectionKind::return) then
    KerML::FeatureDirectionKind::out

```

```

        KerML::FeatureDirectionKind::_'in'
    else if (v = SysML::FlowDirectionKind::inout) then
        KerML::FeatureDirectionKind::inout
    else
        invalid
    endif endif endif
else
    invalid
endif

```

- **getID (in src : Element) : String [1]**  
Returns the identifier of a UML4SysML::Element. The specification is implementation-specific and therefore cannot be provided here.
- **getKerMLFeatureDirectionKind (in v : EnumerationLiteral) : FeatureDirectionKind [1]**  
Maps a given SysMLv1 feature direction enumeration literal to a SysML v2 FeatureDirectionKind enumeration literal.

```

if v.enumeration.qualifiedName =
    'SysML::Ports&Flows::FeatureDirectionKind' or
    v.enumeration.qualifiedName = 'SysML::Ports&Flows::FeatureDirection' then
    if v = SysML::FeatureDirectionKind::provided then
        KerML::FeatureDirectionKind::_'out'
    else if (v = SysML::FeatureDirectionKind::required) then
        KerML::FeatureDirectionKind::_'in'
    else if (v = SysML::FeatureDirectionKind::providedRequired) then
        KerML::FeatureDirectionKind::inout
    else
        invalid
    endif endif endif
else
    invalid
endif

```

- **getKerMLParameterDirectionKind (in v : ParameterDirectionKind) : FeatureDirectionKind [1]**  
Maps a given SysMLv1 parameter direction enumeration literal to a SysML v2 FeatureDirectionKind enumeration literal.

```

if v = UML::ParameterDirectionKind::_'in' then
    KerML::FeatureDirectionKind::_'in'
else if (v = UML::ParameterDirectionKind::return) then
    KerML::FeatureDirectionKind::out
else if (v = UML::ParameterDirectionKind::out) then
    KerML::FeatureDirectionKind::out
else if (v = UML::ParameterDirectionKind::inout) then
    KerML::FeatureDirectionKind::inout
else
    invalid
endif endif endif endif

```

- **getKerMLVisibilityKind (in v : VisibilityKind) : VisibilityKind [1]**  
Maps a given UML4SysML::VisibilityKind enumeration literal to a SysML v2 VisibilityKind enumeration literal.

```

else if (v = UML::ParameterDirectionKind::out) then
    KerML::FeatureDirectionKind::out
else if (v = UML::ParameterDirectionKind::inout) then
    KerML::FeatureDirectionKind::inout
else
    invalid
endif endif endif endif

```

- **getKerMLVisibilityKind (in v : VisibilityKind) : VisibilityKind [1]**  
Maps a given UML4SysML::VisibilityKind enumeration literal to a SysML v2 VisibilityKind enumeration literal.

```

if (v = UML::VisibilityKind::public) then
    KerML::VisibilityKind::public
else if (v = UML::VisibilityKind::protected) then
    KerML::VisibilityKind::protected
else if (v = UML::VisibilityKind::private) then
    KerML::VisibilityKind::private
else if (v = UML::VisibilityKind::package) then
    KerML::VisibilityKind::public
else
    invalid
endif endif endif endif

```

- **getMetadataByName (in mdName : String) : AttributeDefinition [1]**  
Returns the metadata attribute definition element for a given metadata name.

```

SYSML2::AttributeDefiniton.allInstances()->any(e | e.name = mdName)

```

- **getMultiplicityRangeByName (in name : String) : MultiplicityRange [0..1]**  
This operation retrieve a frequently used multiplicity range defiend in the KerML Base Library

```

SYSML2::DataType.allInstances()
->any(e | e.qualifiedName = 'Base::' + name)

```

- **getRequirementStereotype (in element : NamedElement) : Stereotype [0..1]**  
Returns the requirement stereotype for a given element.

```

let stereotypes: Set(UML::Stereotype) =
    Helper.getAppliedStereotypes(element) in
stereotypes->any(s | s.general->collect(g | g.qualifiedName)
->includes('SysML::Requirements::AbstractRequirement'))

```

- **getScalarValueType (in t : DataType) : DataType [1]**  
Maps a given SysMLv1 primitive type to a SysMLv2 scalar value type.

```

if t.ocIsUndefined()
or t.name = ''
or t.name.ocIsUndefined()
or t.qualifiedName.ocIsUndefined() then
    OclUndefined
else if (t.qualifiedName = 'SysML::Libraries::PrimitiveValueTypes::UnlimitedNatural')
or t.qualifiedName.indexOf('PrimitiveTypes::UnlimitedNatural') > 0 then
    SYSML2::DataType.allInstances()
->any(e | e.qualifiedName = 'ScalarValues::Natural')

```

```

    if (v = UML::VisibilityKind::public) then
        KerML::VisibilityKind::public
    else if (v = UML::VisibilityKind::protected) then
        KerML::VisibilityKind::protected
    else if (v = UML::VisibilityKind::private) then
        KerML::VisibilityKind::private
    else if (v = UML::VisibilityKind::package) then
        KerML::VisibilityKind::public
    else
        invalid
    endif endif endif endif

```

- **getMetadataByName** (in mdName : String) : AttributeDefinition [1]  
Returns the metadata attribute definition element for a given metadata name.

```

SYSML2::AttributeDefiniton.allInstances()->any(e | e.name = mdName)

```

- **getRequirementStereotype** (in element : NamedElement) : Stereotype [0..1]  
Returns the requirement stereotype for a given element.

```

let stereotypes: Set(UML::Stereotype) =
    Helper.getAppliedStereotypes(element) in
stereotypes->any(s | s.general->collect(g | g.qualifiedName)
->includes('SysML::Requirements::AbstractRequirement'))

```

- **getScalarValueType** (in t : DataType) : DataType [1]  
Maps a given SysMLv1 primitive type to a SysMLv2 scalar value type.

```

if t.name = 'UnlimitedNatural' then
    SYSML2::DataType.allInstances()
    ->any(e | e.qualifiedName = 'ScalarValues::Natural')
else
    SYSML2::DataType.allInstances()
    ->any(e | e.qualifiedName = 'ScalarValues::' + t.name)
endif

```

- **getScalarValueTypeByName** (in ptName : String) : DataType [1]  
Maps a given SysMLv1 primitive type name string to a SysMLv2 scalar value type.

```

SYSML2::DataType.allInstances()
->any(e | e.qualifiedName = 'ScalarValues::' + ptName)

```

- **getTagValue** (in element : Element, in stereotypeName : String, in tagValueName : String) [1]  
Returns the value of a stereotype property. The specification is implementation-specific and therefore cannot provided here.
- **getTagValueAsElement** (in element : Element, in stereotypeName : String, in tagValueName : String) : Element [1]  
Returns the value of a stereotype property. The specification is implementation-specific and therefore cannot provided here.
- **getTagValueAsElementColl** (in element : Element, in stereotypeName : String, in tagValueName : String) : Element [0..\*]



```

else
  SYSML2::DataType.allInstances()
  ->any(e | e.qualifiedName = 'ScalarValues::' + t.name)
endif endif

```

- **getScalarValueTypeByName** (in ptName : String) : DataType [1]  
Maps a given SysMLv1 primitive type name string to a SysMLv2 scalar value type.

```

SYSML2::DataType.allInstances()
->any(e | e.qualifiedName = 'ScalarValues::' + ptName)

```

- **getTagValue** (in element : Element, in stereotypeName : String, in tagValueName : String) [1]  
Returns the value of a stereotype property. The specification is implementation-specific and therefore cannot provided here.
- **getTagValueAsElement** (in element : Element, in stereotypeName : String, in tagValueName : String) : Element [1]  
Returns the value of a stereotype property. The specification is implementation-specific and therefore cannot provided here.
- **getTagValueAsElementColl** (in element : Element, in stereotypeName : String, in tagValueName : String) : Element [0..\*]  
Returns the value of a stereotype property as a collection. The specification is implementation-specific and therefore cannot provided here.
- **getTagValueAsString** (in element : Element, in stereotypeName : String, in tagValueName : String) : String [1]  
Returns the value of a stereotype property as a string. The specification is implementation-specific and therefore cannot provided here.
- **getTagValueAsStringColl** (in element : Element, in stereotypeName : String, in tagValueName : String) : String [0..\*]  
Returns the value of a stereotype property as a string collection. The specification is implementation-specific and therefore cannot provided here.
- **globalNamespace** () : Namespace [1]

```

KerML::Package.allInstances()->any(p | p.owningNamespace->isEmpty())

```

- **hasMainMapping** (in element : Element) : Boolean [1]
- **hasStereotypeApplied** (in element : Element, in stereotypeName : String) : Boolean [1]  
Returns true if the given stereotype is applied to the element. The specification is implementation-specific and therefore cannot provided here.
- **isConnectionDef** (in association : Association) : Boolean [1]  
Checks if a UML4SysML::Association is mapped to a SysML v2 ConnectionDefinition.

```

-- Case 1: composite association with
-- multiplicity 1..1 on owner side
let casel: Boolean = association.memberEnd
->exists(e | not e.isComposite and e.lower=1) and
association.memberEnd->exists(e | e.isComposite) in

-- Case 2: association is not composite and

```

Returns the value of a stereotype property as a collection. The specification is implementation-specific and therefore cannot be provided here.

- `getTagValueAsString (in element : Element, in stereotypeName : String, in tagValueName : String) : String [1]`  
Returns the value of a stereotype property as a string. The specification is implementation-specific and therefore cannot be provided here.
- `getTagValueAsStringColl (in element : Element, in stereotypeName : String, in tagValueName : String) : String [0..*]`  
Returns the value of a stereotype property as a string collection. The specification is implementation-specific and therefore cannot be provided here.
- `globalNamespace () : Namespace [1]`

```
KerML::Package.allInstances()->any(p | p.owningNamespace->isEmpty())
```

- `hasMainMapping (in element : Element) : Boolean [1]`
- `hasStereotypeApplied (in element : Element, in stereotypeName : String) : Boolean [1]`  
Returns true if the given stereotype is applied to the element. The specification is implementation-specific and therefore cannot be provided here.
- `isConnectionDef (in association : Association) : Boolean [1]`  
Checks if a UML4SysML::Association is mapped to a SysML v2 ConnectionDefinition.

```
-- Case 1: composite association with
-- multiplicity 1..1 on owner side
let case1: Boolean = association.memberEnd
->exists(e | not e.isComposite and e.lower=1) and
association.memberEnd->exists(e | e.isComposite) in

-- Case 2: association is not composite and
-- there is no owned end with multiplicity 0..*
let case2: Boolean = not association.memberEnd
->exists(e | e.isComposite) and
not association.ownedEnd
->exists(e | e.lower = 0 and e.upper = -1) in

association.oclIsTypeOf(UML::AssociationClass) or
case1 or
case2
```

- `isInScope (in element : Element) : Boolean [1]`  
The `isInScope` operation is intended to define the scope on which the transformation will apply. If the `isInScope` operation returns "true" for a given model element, this element shall be considered by the transformation. Especially, main mappings - if any - will apply to it. It shall be ignored otherwise.
- `isRequirement (in element : Element) : Boolean [1]`  
Checks whether the stereotype `AbstractRequirement` is applied to the given element.

```
let stereotypes: Set(UML::Stereotype) =
  Helper.getAppliedStereotypes(element) in
```

```

-- there is no owned end with multiplicity 0..*
let case2: Boolean = not association.memberEnd
->exists(e | e.isComposite) and
not association.ownedEnd
->exists(e | e.lower = 0 and e.upper = -1) in

association.oclIsTypeOf(UML::AssociationClass) or
case1 or
case2

```

- **isInScope (in element : Element) : Boolean [1]**  
The **isInScope** operation is intended to define the scope on which the transformation will apply. If the **isInScope** operation return "true" for a given model element, this element shall be consider by the transformation. Especially, main mappings - if any - will apply to it. It shall be ignored otherwise.
- **isRequirement (in element : Element) : Boolean [1]**  
Checks whether the stereotype **AbstractRequirement** is applied to the given element.

```

let stereotypes: Set(UML::Stereotype) =
  Helper.getAppliedStereotypes(element) in
stereotypes->exists(s | s.general->collect(g | g.qualifiedName)
->includes('SysML::Requirements::AbstractRequirement'))

```

- **packageOwnedRelationship (in src : Element) : Relationship [0..\*]**  
Reusable mapping rule for owned relationships of a **UML4SysML::Package** mapping.

```

let pkg: UML::Package = src.oclAsType(UML::Package) in
if pkg.oclIsUndefined() then
  Set{}
else
  let useCaseAssociations : Set(UML::Association) =
    pkg.ownedType->select(e | e.oclIsKindOf(UML::Association))
    ->select(a | a.memberEnd->exists(e | e.type.oclIsKindOf(UML::UseCase))) in
  let unmappedAssociations : Set(UML::Association) = pkg.ownedType->select(e | e.oclIsKindOf
    ->reject(a | Helper.isConnectionDef(a)) in
  let imports: Set(UML::PackageImport) = pkg.packageImport->select(pi | Helper.isInScope(pi)
  let informationFlows: Set(UML::InformationFlow) = pkg.packagedElement->select(e | e.oclIsKindOf
    ->reject(i | i.realization->isEmpty() and i.realizingConnector->isEmpty()) in
  let fromIF: Set(SysMLv2::ConnectionUsage) = informationFlows->collect(i | i.realization->collect
    ->union(informationFlows->collect(i | i.realizingConnector->collect(r | InformationFlow
  let relationships: Set(SysMLv2::Relationship) = pkg.ownedComment->reject(c | c.annotatedEL
    ->union((pkg.ownedType-useCaseAssociations)-unmappedAssociations)->collect(e | ElementC
    ->union(imports->collect(i | PackageImport_Mapping.getMapped(i))->asSet())
    ->union(pkg.ownedElement->select(e | e.oclIsKindOf(UML::Dependency)
      or e.oclIsKindOf(UML::Package)
      or (e.oclIsKindOf(UML::InstanceSpecification)
        and e.oclAsType(UML::InstanceSpecification).oclIsKindOf(UML::Package))
    ->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet())
  ->union(fromIF)->asSet() in
if pkg.URI.oclIsUndefined() or pkg.URI = '' then
  relationships
else
  relationships->including(PackageURIMetadataMembership_Mapping.getMapped(pkg))
endif endif

```

- **stateOwnedRelationship (in src : Element) : Relationship [0..\*]**  
Reusable mapping rule for owned relationships of a **UML4SysML::State** mapping.

```

stereotypes->exists(s | s.general->collect(g | g.qualifiedName)
->includes('SysML::Requirements::AbstractRequirement'))

```

- **packageOwnedRelationship** (in `src : Element`) : `Relationship [0..*]`  
Reusable mapping rule for owned relationships of a `UML4SysML::Package` mapping.

```

let useCaseAssociations : Set(UML::Association) =
    src.ownedType->select(e | e.ocIsKindOf(UML::Association))
    ->select(a | a.memberEnd->exists(e | e.type.ocIsKindOf(UML::UseCase))) in
let unmappedAssociations : Set(UML::Association) =
    src.ownedType->select(e | e.ocIsKindOf(UML::Association))
    ->reject(a | Helper.isConnectionDef(a)) in
let imports: Set(UML::PackageImport) =
    src.packageImport->select(pi | Helper.isInScope(pi.importedPackage)) in
let relationships: Set(SysMLv2::Relationship) =
    src.ownedComment->reject(c | c.annotatedElement->includes(src))->collect(c | CommentOwners
->union(((src.ownedType-useCaseAssociations)-unmappedAssociations)->collect(e | ElementOwning
->union(imports->collect(i | PackageImport_Mapping.getMapped(i))->asSet())
->union(src.ownedElement->select(e | e.ocIsKindOf(UML::Dependency) or
e.ocIsKindOf(UML::InformationFlow) or e.ocIsKindOf(UML::Package)
or (e.ocIsKindOf(UML::InstanceSpecification) and
e.ocAsType(UML::InstanceSpecification).classifier->notEmpty()))
->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()) in

if src.URI.ocIsUndefined() or src.URI = '' then
    relationships
else
    relationships->including(PackageURIMetadataMembership_Mapping.getMapped(src))
endif

```

- **stateOwnedRelationship** (in `src : Element`) : `Relationship [0..*]`  
Reusable mapping rule for owned relationships of a `UML4SysML::State` mapping.

```

let initialState : Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Pseudostate) and
    e.ocAsType(UML::Pseudostate).kind = UML::PseudostateKind::initial) in
let toElementOMS : Set(UML::Element) = from.ownedElement - initialState in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(initialState->collect(e | InitialStateMembership_Mapping.getMapped(e)))

```

### 7.3.2 SysML v1 Library

The SysML v1 library is a SysML v2 model library with metadata definitions for annotating some model elements resulting from a transformation from a SysML v1 model using the SysML v1 to SysML v2 transformation.

```

package SysMLv1Library {

    doc /*
    * The SysMLv1Library defines library elements and metadata for
    * SysML elements which cannot mapped to a SysML v2 element.
    */

    // Library elements

```

```

let initialState : Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Pseudostate) and
    e.ocIsType(UML::Pseudostate).kind = UML::PseudostateKind::initial) in
let toElementOMS : Set(UML::Element) = from.ownedElement - initialState in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(initialState->collect(e | InitialStateMembership_Mapping.getMapped(e)))

```

### 7.3.2 SysML v1 Library

The SysML v1 library is a SysML v2 model library with metadata definitions for annotating some model elements resulting from a transformation from a SysML v1 model using the SysML v1 to SysML v2 transformation.

```

package SysMLv1Library {

  doc /*
   * The SysMLv1Library defines library elements and metadata for
   * SysML elements which cannot mapped to a SysML v2 element.
   */

  // Library elements

  action def AddValueAction {
    in insertAt : ScalarValues::Natural [0..1];
    in value : ScalarValues::Integer;
    in isReplaceAll : ScalarValues::Boolean = false;
    in target;

    if not isReplaceAll {
      if insertAt == * {
        assign target := SequenceFunctions::including(target, value);
      }
      else {
        assign target :=
          SequenceFunctions::includingAt(target, value, insertAt);
      }
    } else {
      target := value;
    }
  }

  action def AddStructuralFeatureValueAction :> AddValueAction {
    in object;
  }

  action def RemoveVariableValueAction :> Actions::AssignmentAction {
    in removeAt: ScalarValues::Integer [0..1];
    in value : ScalarValues::Integer;
    in isRemoveDuplicates : ScalarValues::Boolean = false;
    in variable;

    // isRemoveDuplicates not covered yet
    if isRemoveDuplicates {
      if removeAt {
        assign variable :=
          SequenceFunctions::excludingAt(variable, value, removeAt);
      } else {
        assign variable := SequenceFunctions::excluding(variable, value);
      }
    }
  }
}

```

```

action def AddValueAction {
  in insertAt : ScalarValues::Natural [0..1];
  in value : ScalarValues::Integer;
  in isReplaceAll : ScalarValues::Boolean = false;
  in target;

  if not isReplaceAll {
    if insertAt == * {
      assign target := SequenceFunctions::including(target, value);
    }
    else {
      assign target :=
        SequenceFunctions::includingAt(target, value, insertAt);
    }
  } else {
    target := value;
  }
}

action def AddStructuralFeatureValueAction :> AddValueAction {
  in object;
}

action def RemoveVariableValueAction :> Actions::AssignmentAction {
  in removeAt: ScalarValues::Natural [0..1];
  in value : ScalarValues::Integer;
  in isRemoveDuplicates : ScalarValues::Boolean = false;
  in variable;

  // isRemoveDuplicates not covered yet

  if removeAt {
    assign variable :=
      SequenceFunctions::excludingAt(variable, value, removeAt);
  } else {
    assign variable := SequenceFunctions::excluding(variable, value);
  }
}

// Metadata

metadata def ActivityEdgeData {
  doc /* Metadata definition for UML::ActivityEdge::weight property */
  attribute weight : ScalarValues::Natural;
}

metadata def AssociationData {
  doc /* Metadata definition for
    * UML::StructuredClassifiers::Association::isDerived property mapping
    */
  attribute isDerived : ScalarValues::Boolean;
}

metadata def BlockData {
  doc /* Metadata definition for
    * SysML::Blocks::Block::isEncapsulated property
    */
  attribute isEncapsulated : ScalarValues::Boolean;
}

```

```

// Metadata

metadata def ActivityEdgeData {
    doc /* Metadata definition for UML::ActivityEdge::weight property */
    attribute weight : ScalarValues::Natural;
}

metadata def AssociationData {
    doc /* Metadata definition for
        * UML::StructuredClassifiers::Association::isDerived property mapping
        */
    attribute isDerived : ScalarValues::Boolean;
}

metadata def BlockData {
    doc /* Metadata definition for
        * SysML::Blocks::Block::isEncapsulated property
        */
    attribute isEncapsulated : ScalarValues::Boolean;
}

metadata def ElementGroupData {
    doc /* Metadata definition for the criterion
        * of a SysML::ModelElements::ElementGroup
        */
    attribute criterion : ScalarValues::String;
}

metadata def ModelData :> PackageData {
    doc /* Metadata definition for the UML::Model::viewpoint property */
    :> annotatedElement : SysML::Package;
    attribute 'viewpoint' : ScalarValues::String;
}

metadata def PackageData {
    doc /* Metadata definition for the UML::Package::URI property */
    :> annotatedElement : SysML::Package;
    attribute URI : ScalarValues::String;
}

metadata def ParameterSetData {
    doc /* Metadata definition for tagging parameters
        * mapped from a UML::ParameterSet
        */
    attribute isParameterSet : ScalarValues::Boolean;
}

metadata def PortData {
    doc /* Metadata definition for tagging SysML v2 ports
        * mapped from a SysML::Ports&Flows::FullPort element
        */
    :> annotatedElement : SysML::PartUsage;
    attribute isFullPort : ScalarValues::Boolean;
}

metadata def ProbabilityData {
    doc /* Metadata definition for SysML::Activities::Probability stereotype */
    attribute probability : ScalarValues::Real;
}

metadata def RateData {
    doc /* Metadata definition for SysML::Activities::Rate and

```

```

}

metadata def ElementGroupData {
    doc /* Metadata definition for the criterion
        * of a SysML::ModelElements::ElementGroup
        */
    attribute criterion : ScalarValues::String;
}

metadata def ModelData :> PackageData {
    doc /* Metadata definition for the UML::Model::viewpoint property */
    :> annotatedElement : SysML::Package;
    attribute 'viewpoint' : ScalarValues::String;
}

metadata def PackageData {
    doc /* Metadata definition for the UML::Package::URI property */
    :> annotatedElement : SysML::Package;
    attribute URI : ScalarValues::String;
}

    metadata def ParameterSetData {
        doc /* Metadata definition for tagging parameters
            * mapped from a UML::ParameterSet
            */
        attribute isParameterSet : ScalarValues::Boolean;
    }

metadata def PortData {
    doc /* Metadata definition for tagging SysML v2 ports
        * mapped from a SysML::Ports&Flows::FullPort element
        */
    :> annotatedElement : SysML::PartUsage;
    attribute isFullPort : ScalarValues::Boolean;
}

metadata def ProbabilityData {
    doc /* Metadata definition for SysML::Activities::Probability stereotype */
    attribute probability : ScalarValues::Real;
}

metadata def RateData {
    doc /* Metadata definition for SysML::Activities::Rate and
        * specialized Discrete and Continuous stereotypes
        */
    :> annotatedElement : SysML::PartUsage;
    part rate;
    attribute isDiscrete : ScalarValues::Boolean;
    attribute isConcrete : ScalarValues::Boolean;
}

metadata def RefineData {
    doc /* Metadata definition for tagging SysML v2 dependencies
        * mapped from a SysML::Requirements::Refine relationship
        */
    :> annotatedElement : SysML::Dependency;
    attribute isRefine : ScalarValues::Boolean;
}

metadata def StakeholderData {

```



```

        * specialized Discrete and Continuous stereotypes
        */
        :> annotatedElement : SysML::PartUsage;
        part rate;
        attribute isDiscrete : ScalarValues::Boolean;
        attribute isConcrete : ScalarValues::Boolean;
    }

    metadata def RefineData {
        doc /* Metadata definition for tagging SysML v2 dependencies
            * mapped from a SysML::Requirements::Refine relationship
            */
        :> annotatedElement : SysML::Dependency;
        attribute isRefine : ScalarValues::Boolean;
    }

    metadata def StakeholderData {
        doc /* Metadata definition for tagging SysML v2 item definitions
            * mapped from a SysML::ModelElements::Stakeholder element
            */
        :> annotatedElement : SysML::ItemDefinition;
        attribute isStakeholder : ScalarValues::Boolean;
    }

    metadata def traceData {
        doc /* Metadata definition for tagging SysML v2 dependencies
            * mapped from a SysML::Requirements::Trace relationship
            */
        :> annotatedElement : SysML::Dependency;
        attribute isTrace : ScalarValues::Boolean;
    }

    metadata def ViewpointData {
        doc /* Metadata definition for SysML::ModelElements::Viewpoint properties */
        attribute languages [0..*] : ScalarValues::String;
        attribute presentations [0..*] : ScalarValues::String;
    }

    package Enumerations {
        enum def ControlValueKind {
            doc /* The ControlValueKind enumeration is a type for
                * treating control values as data and for UML control pins.
                */
            enum disable;
            enum enable;
        }
    }
}

```

## 7.4 Initializers

### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

#### 7.4.1 Overview

The classes presented in this subclause provide set of rules that provide default values for all non-derived features of their target metaclasses. Intentionally, initializers do not specify any "source" element. This makes them easier to specialize but prevents them from being able to provide a computation algorithm for some target features. In such a case, the operation matching the feature will be specified as abstract.

#### 7.4.2 Mapping Specifications

```

        doc /* Metadata definition for tagging SysML v2 item definitions
           * mapped from a SysML::ModelElements::Stakeholder element
           */
        :> annotatedElement : SysML::ItemDefinition;
        attribute isStakeholder : ScalarValues::Boolean;
    }

    metadata def traceData {
        doc /* Metadata definition for tagging SysML v2 dependencies
           * mapped from a SysML::Requirements::Trace relationship
           */
        :> annotatedElement : SysML::Dependency;
        attribute isTrace : ScalarValues::Boolean;
    }

    metadata def ViewpointData {
        doc /* Metadata definition for SysML::ModelElements::Viewpoint properties */
        attribute languages [0..*] : ScalarValues::String;
        attribute presentations [0..*] : ScalarValues::String;
    }

    package Enumerations {
        enum def ControlValueKind {
            doc /* The ControlValueKind enumeration is a type for
               * treating control values as data and for UML control pins.
               */
            enum disable;
            enum enable;
        }
    }
}

```

## 7.4 Initializers

### 7.4.1 Overview

The classes presented in this subclause provide set of rules that provide default values for all non-derived features of their target metaclasses. Intentionally, initializers do not specify any "source" element. This makes them easier to specialize but prevents them from being able to provide a computation algorithm for some target features. In such a case, the operation matching the feature will be specified as abstract.

### 7.4.2 Mapping Specifications

#### 7.4.2.1 KerML Initializers

##### 7.4.2.1.1 AnnotatingElement\_Init

###### Description

Initializes the properties of the SysML v2 element AnnotatingElement.

###### Generalizations

- Element\_Init (from KerMLInitializers)

###### Association Ends

### 7.4.2.1 KerML Initializers

#### 7.4.2.1.1 ToAnnotatingElement\_Init

##### Description

Initializes the properties of the SysML v2 element AnnotatingElement.

##### General Classes

- ToElement\_Init (from KerMLInitializers)

##### Association Ends

- to : AnnotatingElement [1]  
{redefines: ToElement\_Init::to}

##### Operations

- annotation () : Annotation [0..\*]

Set { }

#### 7.4.2.1.2 ToAnnotation\_Init

##### Description

Initializes the properties of the SysML v2 element Annotation.

##### General Classes

- ToRelationship\_Init (from KerMLInitializers)

##### Association Ends

- to : Annotation [1]  
{redefines: ToRelationship\_Init::to}

##### Operations

- annotatedElement () : Element [1] {redefines target, abstract}
- annotatingElement () : AnnotatingElement [1] {redefines source, abstract}
- owningAnnotatedElement () : Element [0..1]

null

#### 7.4.2.1.3 ToAssociation\_Init

##### Description

Initializes the properties of the SysML v2 element Association.

##### General Classes

- ToClassifier\_Init (from KerMLInitializers)

- to : AnnotatingElement [1]  
(redefines: Element\_Init::to)

### Operations

- annotation () : Annotation [0..\*]

Set { }

#### 7.4.2.1.2 Annotation\_Init

### Description

Initializes the properties of the SysML v2 element Annotation.

### Generalizations

- Relationship\_Init (from KerMLInitializers)

### Attributes

- to : Annotation [1]

### Operations

- annotatedElement () : Element [1] {redefines target, abstract}
- annotatingElement () : AnnotatingElement [1] {redefines source, abstract}
- owningAnnotatedElement () : Element [0..1]

null

#### 7.4.2.1.3 Association\_Init

### Description

Initializes the properties of the SysML v2 element Association.

### Generalizations

- Classifier\_Init (from KerMLInitializers)
- Relationship\_Init (from KerMLInitializers)

### Attributes

- to : Association [1]

#### 7.4.2.1.4 Behavior\_Init

### Description

Initializes the properties of the SysML v2 element Behavior.

### Generalizations

- `ToRelationship_Init` (from `KerMLInitializers`)

#### Association Ends

- `to : Association [1]`  
`{redefines: ToRelationship_Init::to}`  
`{redefines: ToClassifier_Init::to}`

#### 7.4.2.1.4 `ToBehavior_Init`

##### Description

Initializes the properties of the SysML v2 element Behavior.

##### General Classes

- `ToClassifier_Init` (from `KerMLInitializers`)

#### Association Ends

- `to : Behavior [1]`  
`{redefines: ToClassifier_Init::to}`

#### 7.4.2.1.5 `ToClassifier_Init`

##### Description

Initializes the properties of the SysML v2 element Classifier.

##### General Classes

- `ToType_Init` (from `KerMLInitializers`)

#### Association Ends

- `to : Classifier [1]`  
`{redefines: ToType_Init::to}`

#### 7.4.2.1.6 `ToComment_Init`

##### Description

Initializes the properties of the SysML v2 element Comment.

##### General Classes

- `ToAnnotatingElement_Init` (from `KerMLInitializers`)

#### Association Ends

- `to : Comment [1]`  
`{redefines: ToAnnotatingElement_Init::to}`

##### Operations

- `body () : String [1]{abstract}`

- Classifier\_Init (from KerMLInitializers)

#### Attributes

- to : Behavior [1]

#### 7.4.2.1.5 Classifier\_Init

##### Description

Initializes the properties of the SysML v2 element Classifier.

#### Generalizations

- Type\_Init (from KerMLInitializers)

#### Attributes

- to : Classifier [1]

#### 7.4.2.1.6 Comment\_Init

##### Description

Initializes the properties of the SysML v2 element Comment.

#### Generalizations

- AnnotatingElement\_Init (from KerMLInitializers)

#### Association Ends

- to : Comment [1]  
(redefines: AnnotatingElement\_Init::to)

#### Operations

- body () : String [1]{abstract}
- locale () : String [1]

null

#### 7.4.2.1.7 Conjugation\_Init

##### Description

Initializes the properties of the SysML v2 element Conjugation.

#### Generalizations

- Relationship\_Init (from KerMLInitializers)

#### Attributes

- locale () : String [1]

null

#### 7.4.2.1.7 ToConjugation\_Init

##### Description

Initializes the properties of the SysML v2 element Conjugation.

##### General Classes

- ToRelationship\_Init (from KerMLInitializers)

##### Association Ends

- to : Conjugation [1]  
{redefines: ToRelationship\_Init::to}

##### Operations

- conjugatedType () : Type [1] {redefines source, abstract}
- originalType () : Type [1] {redefines target, abstract}

#### 7.4.2.1.8 ToConnector\_Init

##### Description

Initializes the properties of the SysML v2 element Connector.

##### General Classes

- ToFeature\_Init (from KerMLInitializers)
- ToRelationship\_Init (from KerMLInitializers)

##### Association Ends

- to : Connector [1]  
{redefines: ToFeature\_Init::to}  
{redefines: ToRelationship\_Init::to}

##### Operations

- isDirected () : Boolean [1]

false

#### 7.4.2.1.9 ToDocumentation\_Init

##### Description

Initializes the properties of the SysML v2 element Documentation.

##### General Classes

- to : Conjugation [1]

#### Operations

- conjugatedType () : Type [1] {redefines source, abstract}
- originalType () : Type [1] {redefines target, abstract}

#### 7.4.2.1.8 Connector\_Init

##### Description

Initializes the properties of the SysML v2 element Connector.

##### Generalizations

- Feature\_Init (from KerMLInitializers)
- Relationship\_Init (from KerMLInitializers)

##### Attributes

- to : Connector [1]

#### Operations

- isDirected () : Boolean [1]

false

#### 7.4.2.1.9 Documentation\_Init

##### Description

Initializes the properties of the SysML v2 element Documentation.

##### Generalizations

- Comment\_Init (from KerMLInitializers)

##### Attributes

- to : Documentation [1]

#### 7.4.2.1.10 Element\_Init

##### Description

This is the general abstract class to be used as an ancestor for any class mapping specification.

##### Generalizations

- Initializer (from Foundations)

#### Association Ends



- `ToComment_Init` (from `KerMLInitializers`)

#### Association Ends

- `to : Documentation [1]`  
`{redefines: ToComment_Init::to}`

#### 7.4.2.1.10 `ToElement_Init`

##### Description

This is the general abstract class to be used as an ancestor for any class mapping specification.

#### General Classes

- `Initializer` (from `Foundations`)

#### Association Ends

- `to : Element [1]`  
`{redefines: Initializer::to}`

#### Operations

- `aliasId () : String [0..*]`

`Set {}`

- `declaredName () : String [0..1]`

`null`

- `elementId () : String [1]`

`Helper.createUUID()`

- `ownedRelationship () : Relationship [0..*]`

`Set {}`

- `shortName () : String [0..1]`

`null`

#### Constraints

- `from_and_to_types`  
`from.oclIsKindOf(factory.srcType) and to.oclIsKindOf(factory.tgtType)`

#### 7.4.2.1.11 `ToEndFeatureMembership_Init`

##### Description

- to : Element [1]  
(redefines: Initializer::to)

## Operations

- aliasId () : String [0..\*]

Set{}

- declaredName () : String [0..1]

null

- elementId () : String [1]

Helper.createUUID()

- ownedRelationship () : Relationship [0..\*]

Set{}

- shortName () : String [0..1]

null

### 7.4.2.1.11 EndFeatureMembership\_Init

#### Description

Initializes the properties of the SysML v2 element EndFeatureMembership.

#### Generalizations

- FeatureMembership\_Init (from KerMLInitializers)

#### Attributes

- to : EndFeatureMembership [1]

### 7.4.2.1.12 Expression\_Init

#### Description

Initializes the properties of the SysML v2 element Expression.

#### Generalizations

- Step\_Init (from KerMLInitializers)

#### Attributes

- to : Expression [1]

Initializes the properties of the SysML v2 element EndFeatureMembership.

#### General Classes

- ToFeatureMembership\_Init (from KerMLInitializers)

#### Association Ends

- to : EndFeatureMembership [1]  
{redefines: ToFeatureMembership\_Init::to}

#### 7.4.2.1.12 ToExpression\_Init

##### Description

Initializes the properties of the SysML v2 element Expression.

#### General Classes

- ToStep\_Init (from KerMLInitializers)

#### Association Ends

- to : Expression [1]  
{redefines: ToStep\_Init::to}

#### 7.4.2.1.13 ToFeature\_Init

##### Description

Initializes the properties of the SysML v2 element Feature.

#### General Classes

- ToType\_Init (from KerMLInitializers)

#### Association Ends

- to : Feature [1]  
{redefines: ToType\_Init::to}

#### Operations

- direction () : FeatureDirectionKind [0..1]

null

- isComposite () : Boolean [1]

false

- isDerived () : Boolean [1]

false

#### 7.4.2.1.13 Feature\_Init

##### Description

Initializes the properties of the SysML v2 element Feature.

##### Generalizations

- Type\_Init (from KerMLInitializers)

##### Attributes

- to : Feature [1]

##### Operations

- direction () : FeatureDirectionKind [0..1]

null

- isComposite () : Boolean [1]

false

- isDerived () : Boolean [1]

false

- isEnd () : Boolean [1]

false

- isOrdered () : Boolean [1]

false

- isPortion () : Boolean [1]

false

- isReadOnly () : Boolean [1]

false

- isUnique () : Boolean [1]

true

- isEnd () : Boolean [1]

false

- isOrdered () : Boolean [1]

false

- isPortion () : Boolean [1]

false

- isReadOnly () : Boolean [1]

false

- isUnique () : Boolean [1]

true

#### 7.4.2.1.14 ToFeatureChainExpression\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureChainExpression.

##### General Classes

- ToOperatorExpression\_Init (from KerMLInitializers)

##### Association Ends

- to : FeatureChainExpression [1]  
{redefines: ToOperatorExpression\_Init::to}

#### 7.4.2.1.15 ToFeatureChaining\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureChaining.

##### General Classes

- ToRelationship\_Init (from KerMLInitializers)

##### Association Ends

- to : FeatureChaining [1]  
{redefines: ToRelationship\_Init::to}

##### Operations

- chainingFeature () : Feature [1] {redefines target, abstract}

#### 7.4.2.1.14 FeatureChainExpression\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureChainExpression.

##### Generalizations

- OperatorExpression\_Init (from KerMLInitializers)

##### Attributes

- to : FeatureChainExpression [1]

#### 7.4.2.1.15 FeatureChaining\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureChaining.

##### Generalizations

- Relationship\_Init (from KerMLInitializers)

##### Attributes

- to : FeatureChaining [1]

##### Operations

- chainingFeature () : Feature [1] {redefines target, abstract}

#### 7.4.2.1.16 FeatureMembership\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureMembership.

##### Generalizations

- OwningMembership\_Init (from KerMLInitializers)
- TypeFeaturing\_Init (from KerMLInitializers)

##### Attributes

- to : FeatureMembership [1]

##### Operations

- ownedMemberFeature () : Feature [1] {redefines ownedMemberElement, abstract}
- ownedRelatedElement () : Element [0..\*] {redefines ownedRelatedElement}

```
Set { self.ownedMemberFeature () }
```

#### 7.4.2.1.16 ToFeatureMembership\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureMembership.

##### General Classes

- ToOwningMembership\_Init (from KerMLInitializers)
- ToTypeFeaturing\_Init (from KerMLInitializers)

##### Association Ends

- to : FeatureMembership [1]  
{redefines: ToTypeFeaturing\_Init::to}  
{redefines: ToOwningMembership\_Init::to}

##### Operations

- ownedMemberFeature () : Feature [1] {redefines ownedMemberElement}  
  
self.upperBound
- ownedRelatedElement () : Element [0..\*] {redefines ownedRelatedElement}  
  
Set {self.ownedMemberFeature () }

#### 7.4.2.1.17 ToFeatureReferenceExpression\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureReferenceExpression.

##### General Classes

- ToExpression\_Init (from KerMLInitializers)

##### Association Ends

- to : FeatureReferenceExpression [1]  
{redefines: ToExpression\_Init::to}

#### 7.4.2.1.18 ToFeatureTyping\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureTyping.

##### General Classes

- ToSpecialization\_Init (from KerMLInitializers)

##### Association Ends

#### 7.4.2.1.17 FeatureReferenceExpression\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureReferenceExpression.

##### Generalizations

- Expression\_Init (from KerMLInitializers)

##### Attributes

- to : FeatureReferenceExpression [1]

#### 7.4.2.1.18 FeatureTyping\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureTyping.

##### Generalizations

- Specialization\_Init (from KerMLInitializers)

##### Attributes

- to : FeatureTyping [1]

##### Operations

- type () : Type [1] {redefines general, abstract}
- typedFeature () : Feature [1] {redefines specific, abstract}

#### 7.4.2.1.19 FeatureValue\_Init

##### Description

Initializes the properties of the SysML v2 element FeatureValue.

##### Generalizations

- OwningMembership\_Init (from KerMLInitializers)

##### Attributes

- to : FeatureValue [1]

##### Operations

- featureWithValue () : Feature [1] {redefines ownedMemberElement, abstract}
- isDefault () : Boolean [1]

false



- `to : FeatureTyping [1]`  
`{redefines: ToSpecialization_Init::to}`

### Operations

- `type () : Type [1]` {redefines general, abstract}
- `typedFeature () : Feature [1]` {redefines specific, abstract}

#### 7.4.2.1.19 ToFeatureValue\_Init

### Description

Initializes the properties of the SysML v2 element FeatureValue.

### General Classes

- `ToOwningMembership_Init` (from KerMLInitializers)

### Association Ends

- `to : FeatureValue [1]`  
`{redefines: ToOwningMembership_Init::to}`

### Operations

- `featureWithValue () : Feature [1]` {redefines ownedMemberElement, abstract}
- `isDefault () : Boolean [1]`

`false`

- `isInitial () : Boolean [1]`

`false`

- `ownedRelatedElement () : Element [0..*]` {redefines ownedRelatedElement}

`Set{self.value ()}`

- `value () : Expression [1]` {redefines ownedMemberElement, abstract}

#### 7.4.2.1.20 ToFlow\_Init

**[SYSML2\\_-417](#): Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"**

### Description

Initializes the properties of the SysML v2 element Flow.

### General Classes

- `ToConnector_Init` (from KerMLInitializers)

- `isInitial () : Boolean [1]`

`false`

- `ownedRelatedElement () : Element [0..*]` {redefines `ownedRelatedElement`}

`Set {self.value () }`

- `value () : Expression [1]` {redefines `ownedMemberElement`, abstract}

#### 7.4.2.1.20 Function\_Init

##### Description

Initializes the properties of the SysML v2 element Function.

##### Generalizations

- `Behavior_Init` (from `KerMLInitializers`)

##### Attributes

- `to : Function [1]`

#### 7.4.2.1.21 Import\_Init

##### Description

Initializes the properties of the SysML v2 element Import.

##### Generalizations

- `Relationship_Init` (from `KerMLInitializers`)

##### Attributes

- `to : Import [1]`

##### Operations

- `importedMemberName () : String [0..1]`

`null`

- `isImportAll () : Boolean [1]`

`false`

- `isRecursive () : Boolean [1]`

`false`

### Association Ends

- to : Flow [1]  
{redefines: ToConnector\_Init::to}

#### 7.4.2.1.21 ToFunction\_Init

##### Description

Initializes the properties of the SysML v2 element Function.

##### General Classes

- ToBehavior\_Init (from KerMLInitializers)

### Association Ends

- to : Function [1]  
{redefines: ToBehavior\_Init::to}

#### 7.4.2.1.22 ToImport\_Init

##### Description

Initializes the properties of the SysML v2 element Import.

##### General Classes

- ToRelationship\_Init (from KerMLInitializers)

### Association Ends

- to : Import [1]  
{redefines: ToRelationship\_Init::to}

##### Operations

- importedMemberName () : String [0..1]

null

- isImportAll () : Boolean [1]

false

- isRecursive () : Boolean [1]

false

- visibility () : VisibilityKind [1]

KerML::VisibilityKind::public

#### 7.4.2.1.23 ToInteraction\_Init

- `source () : Element [1] {redefines source, abstract}`
- `target () : Element [1] {redefines target, abstract}`
- `visibility () : VisibilityKind [1]`

`KerML::VisibilityKind::public`

#### 7.4.2.1.22 Interaction\_Init

##### Description

Initializes the properties of the SysML v2 element Interaction.

##### Generalizations

- Association\_Init (from KerMLInitializers)
- Behavior\_Init (from KerMLInitializers)

##### Attributes

- `to : Interaction [1]`

#### 7.4.2.1.23 InvocationExpression\_Init

##### Description

Initializes the properties of the SysML v2 element InvocationExpression.

##### Generalizations

- Expression\_Init (from KerMLInitializers)

##### Attributes

- `to : InvocationExpression [1]`

#### 7.4.2.1.24 ItemFlow\_Init

##### Description

Initializes the properties of the SysML v2 element ItemFlow.

##### Generalizations

- Connector\_Init (from KerMLInitializers)

##### Attributes

- `to : ItemFlow [1]`

#### 7.4.2.1.25 Membership\_Init

##### Description

Initializes the properties of the SysML v2 element Membership.

## Description

Initializes the properties of the SysML v2 element Interaction.

### General Classes

- `ToAssociation_Init` (from `KerMLInitializers`)
- `ToBehavior_Init` (from `KerMLInitializers`)

### Association Ends

- `to : Interaction [1]`  
`{redefines: ToAssociation_Init::to}`  
`{redefines: ToBehavior_Init::to}`

#### 7.4.2.1.24 `ToInvocationExpression_Init`

## Description

Initializes the properties of the SysML v2 element InvocationExpression.

### General Classes

- `ToExpression_Init` (from `KerMLInitializers`)

### Association Ends

- `to : InvocationExpression [1]`  
`{redefines: ToExpression_Init::to}`

#### 7.4.2.1.25 `ToMembership_Init`

## Description

Initializes the properties of the SysML v2 element Membership.

### General Classes

- `ToRelationship_Init` (from `KerMLInitializers`)

### Association Ends

- `to : Membership [1]`  
`{redefines: ToRelationship_Init::to}`

## Operations

- `memberElement () : Element [1]` {redefines target, abstract}
- `memberName () : String [0..1]`

`null`

- `memberShortName () : String [0..1]`

`null`

### Generalizations

- Relationship\_Init (from KerMLInitializers)

### Attributes

- to : Membership [1]

### Operations

- memberElement () : Element [1] {redefines target, abstract}
- memberName () : String [0..1]

null

- memberShortName () : String [0..1]

null

- membershipOwningNamespace () : Element [0..\*] {redefines source, abstract}
- visibility () : VisibilityKind [1]

KerML::VisibilityKind::public

#### 7.4.2.1.26 MembershipImport\_Init

##### Description

Initializes the properties of the SysML v2 element MembershipImport.

### Generalizations

- Import\_Init (from KerMLInitializers)

### Attributes

- to : MembershipImport [1]

### Operations

- importedMembership () : Namespace [1] {redefines target, abstract}

#### 7.4.2.1.27 Namespace\_Init

##### Description

Initializes the properties of the SysML v2 element Namespace.

### Generalizations

- Element\_Init (from KerMLInitializers)

- membershipOwningNamespace () : Element [0..\*] {redefines source, abstract}
- visibility () : VisibilityKind [1]

KerML::VisibilityKind::public

#### 7.4.2.1.26 ToMembershipImport\_Init

##### Description

Initializes the properties of the SysML v2 element MembershipImport.

##### General Classes

- ToImport\_Init (from KerMLInitializers)

##### Association Ends

- to : MembershipImport [1]  
{redefines: ToImport\_Init::to}

##### Operations

- importedMembership () : Namespace [1] {redefines target, abstract}

#### 7.4.2.1.27 ToNamespace\_Init

##### Description

Initializes the properties of the SysML v2 element Namespace.

##### General Classes

- ToElement\_Init (from KerMLInitializers)

##### Association Ends

- to : Namespace [1]  
{redefines: ToElement\_Init::to}

#### 7.4.2.1.28 ToNamespaceImport\_Init

##### Description

Initializes the properties of the SysML v2 element NamespaceImport.

##### General Classes

- ToImport\_Init (from KerMLInitializers)

##### Association Ends

- to : NamespaceImport [1]  
{redefines: ToImport\_Init::to}

## Association Ends

- to : Namespace [1]  
(redefines: Element\_Init::to)

### 7.4.2.1.28 NamespaceImport\_Init

#### Description

Initializes the properties of the SysML v2 element NamespaceImport.

#### Generalizations

- Import\_Init (from KerMLInitializers)

#### Attributes

- to : NamespaceImport [1]

#### Operations

- importedNamespace () : Namespace [1] {redefines target, abstract}

### 7.4.2.1.29 OperatorExpression\_Init

#### Description

Initializes the properties of the SysML v2 element OperatorExpression.

#### Generalizations

- Expression\_Init (from KerMLInitializers)

#### Attributes

- to : OperatorExpression [1]

#### Operations

- operator () : String [1]{abstract}

### 7.4.2.1.30 OwningMembership\_Init

#### Description

Initializes the properties of the SysML v2 element OwningMembership.

#### Generalizations

- Membership\_Init (from KerMLInitializers)

#### Attributes

- to : OwningMembership [1]



## Operations

- `importedNamespace () : Namespace [1] {redefines target, abstract}`

### 7.4.2.1.29 `ToOperatorExpression_Init`

#### Description

Initializes the properties of the SysML v2 element `OperatorExpression`.

#### General Classes

- `ToExpression_Init` (from `KerMLInitializers`)

#### Association Ends

- `to : OperatorExpression [1]`  
`{redefines: ToExpression_Init::to}`

## Operations

- `operator () : String [1]{abstract}`

### 7.4.2.1.30 `ToOwningMembership_Init`

#### Description

Initializes the properties of the SysML v2 element `OwningMembership`.

#### General Classes

- `ToMembership_Init` (from `KerMLInitializers`)

#### Association Ends

- `to : OwningMembership [1]`  
`{redefines: ToMembership_Init::to}`

## Operations

- `ownedMemberElement () : Element [1] {redefines memberElement, abstract}`
- `ownedRelatedElement () : Element [0..*] {redefines ownedRelatedElement}`

```
Set {self.ownedMemberElement () }
```

### 7.4.2.1.31 `ToPackage_Init`

#### Description

Initializes the properties of the SysML v2 element `Package`.

#### General Classes

- `ToNamespace_Init` (from `KerMLInitializers`)

## Operations

- ownedMemberElement () : Element [1] {redefines memberElement, abstract}
- ownedRelatedElement () : Element [0..\*] {redefines ownedRelatedElement}

```
Set { self.ownedMemberElement () }
```

### 7.4.2.1.31 Package\_Init

#### Description

Initializes the properties of the SysML v2 element Package.

#### Generalizations

- Namespace\_Init (from KerMLInitializers)

#### Attributes

- to : Package [1]

### 7.4.2.1.32 ParameterMembership\_Init

#### Description

Initializes the properties of the SysML v2 element ParameterMembership.

#### Generalizations

- FeatureMembership\_Init (from KerMLInitializers)

#### Attributes

- to : ParameterMembership [1]

## Operations

- ownedMemberParameter () : Feature [1] {redefines ownedMemberFeature, abstract}
- ownedRelatedElement () : Element [0..\*] {redefines ownedRelatedElement}

```
Set { self.ownedMemberParameter () }
```

### 7.4.2.1.33 Predicate\_Init

#### Description

Initializes the properties of the SysML v2 element Predicate.

#### Generalizations

- Function\_Init (from KerMLInitializers)

### Association Ends

- to : Package [1]  
{redefines: ToNamespace\_Init::to}

#### 7.4.2.1.32 ToParameterMembership\_Init

##### Description

Initializes the properties of the SysML v2 element ParameterMembership.

##### General Classes

- ToFeatureMembership\_Init (from KerMLInitializers)

### Association Ends

- to : ParameterMembership [1]  
{redefines: ToFeatureMembership\_Init::to}  
{redefines: ElementOwningMembership\_Mapping::to}

##### Operations

- ownedMemberParameter () : Feature [1] {redefines ownedMemberFeature}

null

- ownedRelatedElement () : Element [0..\*] {redefines ownedRelatedElement}

Set{self.ownedMemberParameter () }

#### 7.4.2.1.33 ToPredicate\_Init

##### Description

Initializes the properties of the SysML v2 element Predicate.

##### General Classes

- ToFunction\_Init (from KerMLInitializers)

### Association Ends

- to : Predicate [1]  
{redefines: ToFunction\_Init::to}

#### 7.4.2.1.34 ToRedefinition\_Init

##### Description

Initializes the properties of the SysML v2 element Redefinition.

##### General Classes

- ToSubsetting\_Init (from KerMLInitializers)

#### Attributes

- to : Predicate [1]

#### 7.4.2.1.34 Redefinition\_Init

##### Description

Initializes the properties of the SysML v2 element Redefinition.

#### Generalizations

- Subsetting\_Init (from KerMLInitializers)

#### Attributes

- to : Redefinition [1]

##### Operations

- redefinedFeature () : Feature [1] {redefines subsettedFeature, abstract}
- redefiningFeature () : Feature [1] {redefines subsettingFeature, abstract}

#### 7.4.2.1.35 ReferenceSubsetting\_Init

##### Description

Initializes the properties of the SysML v2 element ReferenceSubsetting.

#### Generalizations

- Subsetting\_Init (from KerMLInitializers)

#### Attributes

- to : ReferenceSubsetting [1]

##### Operations

- referencedFeature () : Feature [1] {redefines subsettedFeature, abstract}

#### 7.4.2.1.36 Relationship\_Init

##### Description

Initializes the properties of the SysML v2 element Relationship.

#### Generalizations

- Element\_Init (from KerMLInitializers)

##### Association Ends

- to : Relationship [1]  
(redefines: Element\_Init::to)

### Association Ends

- to : Redefinition [1]  
    {redefines: ToSubsetting\_Init::to}

### Operations

- redefinedFeature () : Feature [1] {redefines subsettedFeature, abstract}
- redefiningFeature () : Feature [1]{abstract}

#### 7.4.2.1.35 ToReferenceSubsetting\_Init

### Description

Initializes the properties of the SysML v2 element ReferenceSubsetting.

### General Classes

- ToSubsetting\_Init (from KerMLInitializers)

### Association Ends

- to : ReferenceSubsetting [1]  
    {redefines: ToSubsetting\_Init::to}

### Operations

- referencedFeature () : Feature [1] {redefines subsettedFeature, abstract}

#### 7.4.2.1.36 ToRelationship\_Init

### Description

Initializes the properties of the SysML v2 element Relationship.

### General Classes

- ToElement\_Init (from KerMLInitializers)

### Association Ends

- to : Relationship [1]  
    {redefines: ToElement\_Init::to}

### Operations

- ownedRelatedElement () : Element [0..\*]

Set { }

- source () : Element [0..\*]

Set { }

## Operations

- `ownedRelatedElement () : Element [0..*]`

`Set {}`

- `source () : Element [0..*]`

`Set {}`

- `target () : Element [0..*]`

`Set {}`

### 7.4.2.1.37 ReturnParameterMembership\_Init

#### Description

Initializes the properties of the SysML v2 element ReturnParameterMembership.

#### Generalizations

- ParameterMembership\_Init (from KerMLInitializers)

#### Attributes

- `to : ReturnParameterMembership [1]`

#### Operations

- `isComposite (in src : Element) : Boolean [1]`  
returns "true" if the element provided as the actual parameter value can have a mapping to an instance of the type specified by the "to" attribute (i.e. can be used as a value for the "from" attribute)

`false`

### 7.4.2.1.38 Specialization\_Init

#### Description

Initializes the properties of the SysML v2 element Specialization.

#### Generalizations

- Relationship\_Init (from KerMLInitializers)

#### Attributes

- `to : Specialization [1]`

- target () : Element [0..\*]

Set {}

#### 7.4.2.1.37 ToReturnParameterMembership\_Init

##### Description

Initializes the properties of the SysML v2 element ReturnParameterMembership.

##### General Classes

- ToParameterMembership\_Init (from KerMLInitializers)

##### Association Ends

- to : ReturnParameterMembership [1]  
{redefines: ToParameterMembership\_Init::to}

##### Operations

- isComposite (in src : Element) : Boolean [1]  
returns "true" if the element provided as the actual parameter value can have a mapping to an instance of the type specified by the "to" attribute (i.e. can be used as a value for the "from" attribute)

false

#### 7.4.2.1.38 ToSpecialization\_Init

##### Description

Initializes the properties of the SysML v2 element Specialization.

##### General Classes

- ToRelationship\_Init (from KerMLInitializers)

##### Association Ends

- to : Specialization [1]  
{redefines: ToRelationship\_Init::to}

##### Operations

- general () : Type [1] {redefines target, abstract}
- specific () : Type [1] {redefines source, abstract}

#### 7.4.2.1.39 ToStep\_Init

##### Description

Initializes the properties of the SysML v2 element Step.

##### General Classes

## Operations

- general () : Type [1] {redefines target, abstract}
- specific () : Type [1] {redefines source, abstract}

### 7.4.2.1.39 Step\_Init

#### Description

Initializes the properties of the SysML v2 element Step.

#### Generalizations

- Feature\_Init (from KerMLInitializers)

#### Attributes

- to : Step [1]

### 7.4.2.1.40 Subclassification\_Init

#### Description

Initializes the properties of the SysML v2 element Subclassification.

#### Generalizations

- Specialization\_Init (from KerMLInitializers)

#### Attributes

- to : Subclassification [1]

## Operations

- subclassifier () : Classifier [1] {abstract}
- superclassifier () : Classifier [1] {abstract}

### 7.4.2.1.41 Subsetting\_Init

#### Description

Initializes the properties of the SysML v2 element Subsetting.

#### Generalizations

- Specialization\_Init (from KerMLInitializers)

#### Attributes

- to : Subsetting [1]

## Operations

- subsettedFeature () : Feature [1] {redefines general, abstract}



- `ToFeature_Init` (from `KerMLInitializers`)

#### Association Ends

- `to : Step [1]`  
`{redefines: ToFeature_Init::to}`

#### 7.4.2.1.40 `ToSubclassification_Init`

##### Description

Initializes the properties of the SysML v2 element Subclassification.

#### General Classes

- `ToSpecialization_Init` (from `KerMLInitializers`)

#### Association Ends

- `to : Subclassification [1]`  
`{redefines: ToSpecialization_Init::to}`

##### Operations

- `subclassifier () : Classifier [1]`

`null`

- `superclassifier () : Classifier [1]`

`null`

#### 7.4.2.1.41 `ToSubsetting_Init`

##### Description

Initializes the properties of the SysML v2 element Subsetting.

#### General Classes

- `ToSpecialization_Init` (from `KerMLInitializers`)

#### Association Ends

- `to : Subsetting [1]`  
`{redefines: ToSpecialization_Init::to}`

##### Operations

- `ownedRelatedElement () : Element [0..*]` {redefines `ownedRelatedElement`}

`Set {}`

- `subsettingFeature () : Feature [1]` {redefines `general`, `abstract`}

- `subsettingFeature () : Feature [1] {redefines specific, abstract}`

#### 7.4.2.1.42 Succession\_Init

##### Description

Initializes the properties of the SysML v2 element Succession.

##### Generalizations

- `Connector_Init` (from `KerMLInitializers`)

##### Attributes

- `to : Succession [1]`

#### 7.4.2.1.43 SuccessionItemFlow\_Init

##### Description

Initializes the properties of the SysML v2 element SuccessionItemFlow.

##### Generalizations

- `ItemFlow_Init` (from `KerMLInitializers`)
- `Succession_Init` (from `KerMLInitializers`)

##### Attributes

- `to : SuccessionItemFlow [1]`

#### 7.4.2.1.44 TextualRepresentation\_Init

##### Description

Initializes the properties of the SysML v2 element TextualRepresentation.

##### Generalizations

- `AnnotatingElement_Init` (from `KerMLInitializers`)

##### Attributes

- `to : TextualRepresentation [1]`

##### Operations

- `body () : String [1]{abstract}`
- `language () : String [1]{abstract}`

#### 7.4.2.1.45 Type\_Init

##### Description

Initializes the properties of the SysML v2 element Type.

#### 7.4.2.1.42 ToSuccession\_Init

##### Description

Initializes the properties of the SysML v2 element Succession.

##### General Classes

- ToConnector\_Init (from KerMLInitializers)

##### Association Ends

- to : Succession [1]  
{redefines: ToConnector\_Init::to}

#### 7.4.2.1.43 ToSuccessionItemFlow\_Init

##### Description

Initializes the properties of the SysML v2 element SuccessionFlow.

##### General Classes

- ToItemFlow\_Init (from KerMLInitializers)
- ToSuccession\_Init (from KerMLInitializers)

##### Association Ends

- to : SuccessionFlow [1]  
{redefines: ToSuccession\_Init::to}  
{redefines: ToItemFlow\_Init::to}

#### 7.4.2.1.44 ToTextualRepresentation\_Init

##### Description

Initializes the properties of the SysML v2 element TextualRepresentation.

##### General Classes

- ToAnnotatingElement\_Init (from KerMLInitializers)

##### Association Ends

- to : TextualRepresentation [1]  
{redefines: ToAnnotatingElement\_Init::to}

##### Operations

- body () : String [1]{abstract}
- language () : String [1]{abstract}

#### 7.4.2.1.45 ToType\_Init

##### Description

Initializes the properties of the SysML v2 element Type.

### Generalizations

- Namespace\_Init (from KerMLInitializers)

### Attributes

- to : Type [1]

### Operations

- isAbstract () : Boolean [1]

false

- isSufficient () : Boolean [1]

false

#### 7.4.2.1.46 TypeFeaturing\_Init

### Description

Initializes the properties of the SysML v2 element TypeFeaturing.

### Generalizations

- Relationship\_Init (from KerMLInitializers)

### Attributes

- to : TypeFeaturing [1]

### Operations

- featureOfType () : Feature [1] {redefines source, abstract}
- featuringType () : Type [1] {redefines target, abstract}

#### 7.4.2.2 System Initializers

##### 7.4.2.2.1 ActionUsage\_Init

### Description

Initializes the properties of the SysML v2 element ActionUsage.

### Generalizations

- Step\_Init (from KerMLInitializers)
- Usage\_Init (from SystemInitializers)

### Attributes

- to : ActionUsage [1]

### General Classes

- `ToNamespace_Init` (from `KerMLInitializers`)

### Association Ends

- `to : Type [1]`  
`{redefines: ToNamespace_Init::to}`

### Operations

- `isAbstract () : Boolean [1]`

`false`

- `isSufficient () : Boolean [1]`

`false`

#### 7.4.2.1.46 `ToTypeFeaturing_Init`

### Description

Initializes the properties of the SysML v2 element `TypeFeaturing`.

### General Classes

- `ToRelationship_Init` (from `KerMLInitializers`)

### Association Ends

- `to : TypeFeaturing [1]`  
`{redefines: ToRelationship_Init::to}`

### Operations

- `featureOfType () : Feature [1]` {redefines source, abstract}
- `featuringType () : Type [1]` {redefines target, abstract}

#### 7.4.2.2 System Initializers

##### 7.4.2.2.1 `ToActionUsage_Init`

### Description

Initializes the properties of the SysML v2 element `ActionUsage`.

### General Classes

- `ToStep_Init` (from `KerMLInitializers`)
- `ToUsage_Init` (from `SystemInitializers`)

### Association Ends

## Operations

- isComposite () : Boolean [1] {redefines isComposite}

true

### 7.4.2.2.2 ActorMembership\_Init

#### Description

Initializes the properties of the SysML v2 element ActorMembership.

#### Generalizations

- ParameterMembership\_Init (from KerMLInitializers)

#### Attributes

- to : ActorMembership [1]

### 7.4.2.2.3 AssignmentActionUsage\_Init

#### Description

Initializes the properties of the SysML v2 element AssignmentActionUsage.

#### Generalizations

- ActionUsage\_Init (from SystemInitializers)

#### Attributes

- to : AssignmentActionUsage [1]

### 7.4.2.2.4 ConjugatedPortDefinition\_Init

#### Description

Initializes the properties of the SysML v2 element ConjugatedPortDefinition.

#### Generalizations

- PortDefinition\_Init (from SystemInitializers)

#### Attributes

- to : ConjugatedPortDefinition [1]

### 7.4.2.2.5 ConjugatedPortTyping\_Init

#### Description

Initializes the properties of the SysML v2 element ConjugatedPortTyping.

- `to : ActionUsage [1]`  
`{redefines: ToStep_Init::to}`  
`{redefines: ToUsage_Init::to}`

## Operations

- `isComposite () : Boolean [1] {redefines isComposite}`

`true`

### 7.4.2.2.2 ToActorMembership\_Init

#### Description

Initializes the properties of the SysML v2 element ActorMembership.

#### General Classes

- `ToParameterMembership_Init` (from KerMLInitializers)

#### Association Ends

- `to : ActorMembership [1]`  
`{redefines: ToParameterMembership_Init::to}`

### 7.4.2.2.3 ToAssignmentActionUsage\_Init

#### Description

Initializes the properties of the SysML v2 element AssignmentActionUsage.

#### General Classes

- `ToActionUsage_Init` (from SystemInitializers)

#### Association Ends

- `to : AssignmentActionUsage [1]`  
`{redefines: ToActionUsage_Init::to}`

### 7.4.2.2.4 ToBindingConnectorAsUsage\_Init

**[SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation](#)**

#### Description

Initializes the properties of the SysML v2 element BindingConnectorAsUsage.

#### General Classes

- `ToConnectionUsage_Init` (from SystemInitializers)

### Generalizations

- FeatureTyping\_Init (from KerMLInitializers)

### Attributes

- to : ConjugatedPortTyping [1]

### Operations

- conjugatedPortDefinition () : ConjugatedPortDefinition [1] {redefines type, abstract}
- portDefinition () : PortDefinition [1]{abstract}

#### 7.4.2.2.6 ConnectionUsage\_Init

##### Description

Initializes the properties of the SysML v2 element ConnectionUsage.

### Generalizations

- PartUsage\_Init (from SystemInitializers)

### Attributes

- to : ConnectionUsage [1]

#### 7.4.2.2.7 ConstraintDefinition\_Init

##### Description

Initializes the properties of the SysML v2 element ConstraintDefinition.

### Generalizations

- Definition\_Init (from SystemInitializers)

### Attributes

- to : ConstraintDefinition [1]

#### 7.4.2.2.8 ConstraintUsage\_Init

##### Description

Initializes the properties of the SysML v2 element ConstraintUsage.

### Generalizations

- Usage\_Init (from SystemInitializers)

### Attributes

- to : ConstraintUsage [1]



## Association Ends

- to : BindingConnectorAsUsage [1]  
{redefines: ToConnectionUsage\_Init::to}

### 7.4.2.2.5 ToCalculationUsage\_Init

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

## Description

Initializes the properties of the SysML v2 element CalculationUsage.

## General Classes

- ToActionUsage\_Init (from SystemInitializers)

## Association Ends

- to : CalculationUsage [1]  
{redefines: ToActionUsage\_Init::to}

### 7.4.2.2.6 ToConjugatedPortDefinition\_Init

## Description

Initializes the properties of the SysML v2 element ConjugatedPortDefinition.

## General Classes

- ToPortDefinition\_Init (from SystemInitializers)

## Association Ends

- to : ConjugatedPortDefinition [1]  
{redefines: ToPortDefinition\_Init::to}

### 7.4.2.2.7 ToConjugatedPortTyping\_Init

## Description

Initializes the properties of the SysML v2 element ConjugatedPortTyping.

## General Classes

- ToFeatureTyping\_Init (from KerMLInitializers)

## Association Ends

- to : ConjugatedPortTyping [1]  
{redefines: ToFeatureTyping\_Init::to}

## Operations

- conjugatedPortDefinition () : ConjugatedPortDefinition [1] {redefines type, abstract}

#### 7.4.2.2.9 Definition\_Init

##### Description

Initializes the properties of the SysML v2 element Definition.

##### Generalizations

- Classifier\_Init (from KerMLInitializers)

##### Attributes

- to : Definition [1]

##### Operations

- isVariation () : Boolean [1]

false

#### 7.4.2.2.10 EventOccurrenceUsage\_Init

##### Description

Initializes the properties of the SysML v2 element EventOccurrenceUsage.

##### Generalizations

- OccurrenceUsage\_Init (from SystemInitializers)

##### Attributes

- to : EventOccurrenceUsage [1]

#### 7.4.2.2.11 FlowConnectionUsage\_Init

##### Description

Initializes the properties of the SysML v2 element FlowConnectionUsage.

##### Generalizations

- ConnectionUsage\_Init (from SystemInitializers)

##### Association Ends

- to : FlowConnectionUsage [1]  
(redefines: ConnectionUsage\_Init::to)

#### 7.4.2.2.12 ItemDefinition\_Init

##### Description

Initializes the properties of the SysML v2 element ItemDefinition.

- portDefinition () : PortDefinition [1]{abstract}

#### 7.4.2.2.8 ToConnectionUsage\_Init

##### Description

Initializes the properties of the SysML v2 element ConnectionUsage.

##### General Classes

- ToPartUsage\_Init (from SystemInitializers)

##### Association Ends

- to : ConnectionUsage [1]  
{redefines: ToPartUsage\_Init::to}

#### 7.4.2.2.9 ToConstraintDefinition\_Init

##### Description

Initializes the properties of the SysML v2 element ConstraintDefinition.

##### General Classes

- ToDefinition\_Init (from SystemInitializers)

##### Association Ends

- to : ConstraintDefinition [1]  
{redefines: ToDefinition\_Init::to}  
{redefines: ToFunction\_Init::to}

#### 7.4.2.2.10 ToConstraintUsage\_Init

##### Description

Initializes the properties of the SysML v2 element ConstraintUsage.

##### General Classes

- ToUsage\_Init (from SystemInitializers)

##### Association Ends

- to : ConstraintUsage [1]  
{redefines: ToUsage\_Init::to}

#### 7.4.2.2.11 ToDefinition\_Init

##### Description

Initializes the properties of the SysML v2 element Definition.

##### General Classes

- ToClassifier\_Init (from KerMLInitializers)



### Association Ends

- to : Definition [1]  
{redefines: ToClassifier\_Init::to}

### Operations

- isVariation () : Boolean [1]

false

#### 7.4.2.2.12 ToEventOccurrenceUsage\_Init

### Description

Initializes the properties of the SysML v2 element EventOccurrenceUsage.

### General Classes

- ToOccurrenceUsage\_Init (from SystemInitializers)

### Association Ends

- to : EventOccurrenceUsage [1]  
{redefines: ToOccurrenceUsage\_Init::to}

#### 7.4.2.2.13 ToFlowUsage\_Init

**SYSML2\_-417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"**

**SYSML2\_-424: Adopted resolution SYSML2\_-403 has impact on the v1 to v2 Transformation**

### Description

Initializes the properties of the SysML v2 element FlowUsage.

### General Classes

- ToActionUsage\_Init (from SystemInitializers)
- ToConnector\_Init (from KerMLInitializers)

### Association Ends

- to : FlowUsage [1]  
{redefines: ToConnector\_Init::to}  
{redefines: ToActionUsage\_Init::to}

### Operations

- isDirected () : Boolean [1] {redefines isDirected}

true

#### 7.4.2.2.14 ToItemDefinition\_Init

### Generalizations

- Definition\_Init (from SystemInitializers)

### Attributes

- to : ItemDefinition [1]

#### 7.4.2.2.13 ItemFeature\_Init

##### Description

Initializes the properties of the SysML v2 element ItemFeature.

### Generalizations

- Feature\_Init (from KerMLInitializers)

### Association Ends

- to : ItemFeature [1]  
(redefines: Feature\_Init::to)

#### 7.4.2.2.14 MetadataUsage\_Init

##### Description

Initializes the properties of the SysML v2 element MetadataUsage.

### Generalizations

- Usage\_Init (from SystemInitializers)

### Attributes

- to : MetadataUsage [1]

#### 7.4.2.2.15 ObjectiveMembership\_Init

##### Description

Initializes the properties of the SysML v2 element ObjectiveMembership.

### Generalizations

- FeatureMembership\_Init (from KerMLInitializers)

### Attributes

- to : ObjectiveMembership [1]

#### 7.4.2.2.16 OccurrenceDefinition\_Init

##### Description

## Description

Initializes the properties of the SysML v2 element ItemDefinition.

## General Classes

- ToDefinition\_Init (from SystemInitializers)

## Association Ends

- to : ItemDefinition [1]  
{redefines: ToDefinition\_Init::to}

### 7.4.2.2.15 ToltemFeature\_Init

## Description

Initializes the properties of the SysML v2 element ItemFeature.

## General Classes

- ToFeature\_Init (from KerMLInitializers)

## Association Ends

- to : PayloadFeature [1]  
{redefines: ToFeature\_Init::to}

### 7.4.2.2.16 ToltemUsage\_Init

## Description

Generic mapping class for mappings to the SysML v2 element ItemUsage.

## General Classes

- ToOccurrenceUsage\_Init (from SystemInitializers)

## Association Ends

- to : ItemUsage [1]  
{redefines: ToOccurrenceUsage\_Init::to}

### 7.4.2.2.17 ToMetadataUsage\_Init

## Description

Initializes the properties of the SysML v2 element MetadataUsage.

## General Classes

- ToUsage\_Init (from SystemInitializers)

## Association Ends

- to : MetadataUsage [1]  
{redefines: ToUsage\_Init::to}

Initializes the properties of the SysML v2 element OccurrenceDefinition.

#### Generalizations

- Definition\_Init (from SystemInitializers)

#### Attributes

- to : OccurrenceDefinition [1]

#### Operations

- isIndividual () : Boolean [1]

false

### 7.4.2.2.17 OccurrenceUsage\_Init

#### Description

Initializes the properties of the SysML v2 element OccurrenceUsage.

#### Generalizations

- Usage\_Init (from SystemInitializers)

#### Attributes

- to : OccurrenceUsage [1]

#### Operations

- isIndividual () : Boolean [1]

false

- portionKind () : PortionKind [1] {abstract}

### 7.4.2.2.18 PartUsage\_Init

#### Description

Initializes the properties of the SysML v2 element PartUsage.

#### Generalizations

- Usage\_Init (from SystemInitializers)

#### Attributes

- to : PartUsage [1]



#### 7.4.2.2.18 ToObjectiveMembership\_Init

##### Description

Initializes the properties of the SysML v2 element ObjectiveMembership.

##### General Classes

- ToFeatureMembership\_Init (from KerMLInitializers)

##### Association Ends

- to : ObjectiveMembership [1]  
{redefines: ToFeatureMembership\_Init::to}

#### 7.4.2.2.19 ToOccurrenceDefinition\_Init

##### Description

Initializes the properties of the SysML v2 element OccurrenceDefinition.

##### General Classes

- ToDefinition\_Init (from SystemInitializers)

##### Association Ends

- to : OccurrenceDefinition [1]  
{redefines: ToDefinition\_Init::to}

##### Operations

- isIndividual () : Boolean [1]

false

#### 7.4.2.2.20 ToOccurrenceUsage\_Init

##### Description

Initializes the properties of the SysML v2 element OccurrenceUsage.

##### General Classes

- ToUsage\_Init (from SystemInitializers)

##### Association Ends

- to : OccurrenceUsage [1]  
{redefines: ToUsage\_Init::to}

##### Operations

- isIndividual () : Boolean [1]

#### 7.4.2.2.19 PortConjugation\_Init

##### Description

Initializes the properties of the SysML v2 element PortConjugation.

##### Generalizations

- Conjugation\_Init (from KerMLInitializers)

##### Attributes

- to : PortConjugation [1]

##### Operations

- originalPortDefinition () : PortDefinition [1] {redefines originalType, abstract}

#### 7.4.2.2.20 PortDefinition\_Init

##### Description

Initializes the properties of the SysML v2 element PortDefinition.

##### Generalizations

- Definition\_Init (from SystemInitializers)

##### Attributes

- to : PortDefinition [1]

#### 7.4.2.2.21 ReferenceUsage\_Init

##### Description

Provides the basic features to map to a ReferenceUsage element.

##### Generalizations

- Usage\_Init (from SystemInitializers)

##### Attributes

- to : ReferenceUsage [1]

#### 7.4.2.2.22 RequirementUsage\_Init

##### Description

Initializes the properties of the SysML v2 element RequirementUsage.

##### Generalizations

- Usage\_Init (from SystemInitializers)

false

- portionKind () : PortionKind [1]

invalid

#### 7.4.2.2.21 ToPartUsage\_Init

##### Description

Initializes the properties of the SysML v2 element PartUsage.

##### General Classes

- ToUsage\_Init (from SystemInitializers)

##### Association Ends

- to : PartUsage [1]  
{redefines: ToUsage\_Init::to}

#### 7.4.2.2.22 ToPerformActionUsage\_Init

##### Description

Initializes the properties of the SysML v2 element PerformActionUsage.

##### General Classes

- ToActionUsage\_Init (from SystemInitializers)

##### Association Ends

- to : PerformActionUsage [1]  
{redefines: ToActionUsage\_Init::to}

#### 7.4.2.2.23 ToPortConjugation\_Init

##### Description

Initializes the properties of the SysML v2 element PortConjugation.

##### General Classes

- ToConjugation\_Init (from KerMLInitializers)

##### Association Ends

- to : PortConjugation [1]  
{redefines: ToConjugation\_Init::to}

##### Operations

- originalPortDefinition () : PortDefinition [1] {redefines originalType, abstract}

#### 7.4.2.2.24 ToPortDefinition\_Init



## Description

Initializes the properties of the SysML v2 element PortDefinition.

## General Classes

- ToDefinition\_Init (from SystemInitializers)

## Association Ends

- to : PortDefinition [1]  
{redefines: ToDefinition\_Init::to}

### 7.4.2.2.25 ToReferenceUsage\_Init

## Description

Provides the basic features to map to a ReferenceUsage element.

## General Classes

- ToUsage\_Init (from SystemInitializers)

## Association Ends

- to : ReferenceUsage [1]  
{redefines: ToUsage\_Init::to}

### 7.4.2.2.26 ToRequirementUsage\_Init

## Description

Initializes the properties of the SysML v2 element RequirementUsage.

## General Classes

- ToUsage\_Init (from SystemInitializers)

## Association Ends

- to : RequirementUsage [1]  
{redefines: ToUsage\_Init::to}

### 7.4.2.2.27 ToStateSubactionMembership\_Init

## Description

Initializes the properties of the SysML v2 element StateSubactionMembership.

## General Classes

- ToFeatureMembership\_Init (from KerMLInitializers)

## Association Ends

- to : StateSubactionMembership [1]  
{redefines: ToFeatureMembership\_Init::to}

### Attributes

- to : RequirementUsage [1]

#### 7.4.2.2.23 StateUsage\_Init

### Description

Initializes the properties of the SysML v2 element StateUsage.

### Generalizations

- ActionUsage\_Init (from SystemInitializers)

### Attributes

- to : StateUsage [1]

#### 7.4.2.2.24 SubjectMembership\_Init

### Description

Initializes the properties of the SysML v2 element SubjectMembership.

### Generalizations

- ParameterMembership\_Init (from KerMLInitializers)

### Attributes

- to : SubjectMembership [1]

#### 7.4.2.2.25 Usage\_Init

### Description

Initializes the properties of the SysML v2 element Usage.

### Generalizations

- Feature\_Init (from KerMLInitializers)

### Attributes

- to : Usage [1]

### Operations

- isVariation () : Boolean [1]

false

## 7.5 Factories

#### 7.4.2.2.28 ToStateUsage\_Init

##### Description

Initializes the properties of the SysML v2 element StateUsage.

##### General Classes

- ToActionUsage\_Init (from SystemInitializers)

##### Association Ends

- to : StateUsage [1]  
{redefines: ToActionUsage\_Init::to}

#### 7.4.2.2.29 ToSubjectMembership\_Init

##### Description

Initializes the properties of the SysML v2 element SubjectMembership.

##### General Classes

- ToParameterMembership\_Init (from KerMLInitializers)

##### Association Ends

- to : SubjectMembership [1]  
{redefines: ToParameterMembership\_Init::to}

#### 7.4.2.2.30 ToTransitionUsage\_Init

##### Description

Initializes the properties of the SysML v2 element TransitionUsage.

##### General Classes

- ToActionUsage\_Init (from SystemInitializers)

##### Association Ends

- to : TransitionUsage [1]  
{redefines: ToActionUsage\_Init::to}

#### 7.4.2.2.31 ToTriggerInvocationExpression\_Init

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Initializes the properties of the SysML v2 element TriggerInvocationExpression.

##### General Classes

- ToInvocationExpression\_Init (from KerMLInitializers)

## 7.5.1 Overview

The classes presented in this subclause specify facilities for creating elements in the target model from an arbitrary set of zero to many input parameters. After the target element is created, no link between it and the value of inputs parameter (if any) will be preserved.

## 7.5.2 Mapping Specifications

### 7.5.2.1 LiteralString\_Factory

#### Description

Factory class to create a LiteralString element.

#### Generalizations

- Expression\_Init (from KerMLInitializers)
- Factory (from Foundations)

#### Association Ends

- string : String [1]
- to : LiteralString [1]  
(redefines: Expression\_Init::to)

#### Operations

- create (in string : String) : LiteralString [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{ReturnParameterFeatureMembership_Factory.create() }
```

### 7.5.2.2 StringParameterFeature\_Factory

#### Description

Factory class to create a feature element representing a string.

#### Generalizations

- Factory (from Foundations)
- Feature\_Init (from KerMLInitializers)

#### Association Ends

- string : String [1]

#### Operations

- create (in string : String) : Feature [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{StringParameterFeatureValue_Factory.create(string) }
```



### Association Ends

- to : TriggerInvocationExpression [1]  
{redefines: ToInvocationExpression\_Init::to}

### Operations

- kind () : TriggerKind [0..1] {redefines direction, abstract}

#### 7.4.2.2.32 ToUsage\_Init

### Description

Initializes the properties of the SysML v2 element Usage.

### General Classes

- ToFeature\_Init (from KerMLInitializers)

### Association Ends

- to : Usage [1]  
{redefines: ToFeature\_Init::to}

### Operations

- isVariation () : Boolean [1]

false

## 7.5 Factories

### 7.5.1 Overview

The classes presented in this subclause specify facilities for creating elements in the target model form an arbitrary set of zero to many input parameters. After the target element is created, no link between it and an the value of inputs parameter (if any) will be preserved.

### 7.5.2 Mapping Specifications

#### 7.5.2.1 LiteralString\_Factory

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

Factory class to create a LiteralString element.

### General Classes

- Factory (from Foundations)
- ToExpression\_Init (from KerMLInitializers)

### Association Ends

- string : String [1]

### 7.5.2.3 StringParameterFeatureValue\_Factory

#### Description

Factory class to create a string feature value relationship for a feature element.

#### Generalizations

- Factory (from Foundations)
- FeatureValue\_Init (from KerMLInitializers)

#### Association Ends

- string : String [1]

#### Operations

- create (in string : String) : FeatureValue [1]
- value () : Expression [1] {redefines value}

```
LiteralString_Factory.create(string)
```

### 7.5.2.4 StringParameterMembership\_Factory

#### Description

Factory class to create a parameter membership relationship for a feature element representing a string.

#### Generalizations

- Factory (from Foundations)
- ParameterMembership\_Init (from KerMLInitializers)

#### Association Ends

- string : String [1]

#### Operations

- create (in string : String) : ParameterMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

```
StringParameterFeature_Factory.create(string)
```

### 7.5.2.5 SubjectMembership\_Factory

#### Description

Factory class to create a subject membership relationship for a given subject.

#### Generalizations

- Factory (from Foundations)

- to : LiteralString [1]  
    {redefines: ToExpression\_Init::to}

### Operations

- create (in string : String) : LiteralString [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{ReturnParameterFeatureMembership_Factory.create() }
```

### 7.5.2.2 StringParameterFeature\_Factory

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Factory class to create a feature element representing a string.

#### General Classes

- Factory (from Foundations)
- ToFeature\_Init (from KerMLInitializers)

#### Association Ends

- string : String [1]

### Operations

- create (in string : String) : Feature [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{StringParameterFeatureValue_Factory.create(string) }
```

### 7.5.2.3 StringParameterFeatureValue\_Factory

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Factory class to create a string feature value relationship for a feature element.

#### General Classes

- Factory (from Foundations)
- ToFeatureValue\_Init (from KerMLInitializers)

#### Association Ends

- string : String [1]

### Operations

- create (in string : String) : FeatureValue [1]

- SubjectMembership\_Init (from SystemInitializers)

#### Association Ends

- subject : Type [1]

#### Operations

- create (in subject : Type) : SubjectMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

subject

### 7.5.2.6 AssignmentActionUsage\_Factory

#### Description

Factory to create an assignment action usage.

#### Generalizations

- AssignmentActionUsage\_Init (from SystemInitializers)
- Factory (from Foundations)

#### Operations

- create () : AssignmentActionUsage [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{AssignmentActionUsageParameterMembership_Factory.create(),
DirectedReferenceUsageParameterMembership_Factory.create(KerML::FeatureDirectionKind::_'in')}
```

### 7.5.2.7 AssignmentActionUsageFeatureMembership2\_Factory

#### Description

Factory class to create a feature membership relationship for a feature element created by the factory class AssignmentActionUsageTargetReferenceUsageIn2\_Factory.

#### Generalizations

- Factory (from Foundations)
- FeatureMembership\_Init (from KerMLInitializers)

#### Operations

- create () : FeatureMembership [1]
- ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}

```
AssignmentActionUsageTargetReferenceUsageIn2_Factory.create()
```

- `value () : Expression [1] {redefines value}`

```
LiteralString_Factory.create(string)
```

#### 7.5.2.4 StringParameterMembership\_Factory

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Factory class to create a parameter membership relationship for a feature element representing a string.

##### General Classes

- Factory (from Foundations)
- [ToParameterMembership\\_Init](#) (from KerMLInitializers)

##### Association Ends

- `string : String [1]`

##### Operations

- `create (in string : String) : ParameterMembership [1]`
- `ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}`

```
StringParameterFeature_Factory.create(string)
```

#### 7.5.2.5 SubjectMembership\_Factory

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Factory class to create a subject membership relationship for a given subject.

##### General Classes

- Factory (from Foundations)
- [ToSubjectMembership\\_Init](#) (from SystemInitializers)

##### Association Ends

- `subject : Type [1]`

##### Operations

- `create (in subject : Type) : SubjectMembership [1]`
- `ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}`

```
subject
```

### 7.5.2.8 AssignmentActionUsageFeatureMembership3\_Factory

#### Description

Factory class to create a feature membership relationship for a feature element created by the factory class AssignmentActionUsageTargetReferenceUsageIn3\_Factory.

#### Generalizations

- Factory (from Foundations)
- FeatureMembership\_Init (from KerMLInitializers)

#### Operations

- create () : FeatureMembership [1]
- ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}

```
AssignmentActionUsageTargetReferenceUsageIn3_Factory.create()
```

### 7.5.2.9 AssignmentActionUsageOwningMembership\_Factory

#### Description

Factory class to create a owning membership relationship for an element created by the factory class AssignmentActionUsage\_Factory.

#### Generalizations

- Factory (from Foundations)
- OwningMembership\_Init (from KerMLInitializers)

#### Operations

- create () : OwningMembership [1]
- ownedMemberElement () : Element [1] {redefines ownedMemberElement}

```
AssignmentActionUsage_Factory.create()
```

### 7.5.2.10 AssignmentActionUsageParameterMembership\_Factory

#### Description

Factory class to create a parameter membership relationship for a feature element created by the factory class AssignmentActionUsageReferenceUsageIn1\_Factory.

#### Generalizations

- Factory (from Foundations)
- ParameterMembership\_Init (from KerMLInitializers)

#### Operations

- create () : ParameterMembership [1]

### 7.5.2.6 AssignmentActionUsage\_Factory

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Factory to create an assignment action usage.

#### General Classes

- Factory (from Foundations)
- ToAssignmentActionUsage\_Init (from SystemInitializers)

#### Operations

- create () : AssignmentActionUsage [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set { AssignmentActionUsageParameterMembership_Factory.create () ,  
DirectedReferenceUsageParameterMembership_Factory.create (KerML::FeatureDirectionKind::_in') }
```

### 7.5.2.7 AssignmentActionUsageFeatureMembership2\_Factory

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Factory class to create a feature membership relationship for a feature element created by the factory class AssignmentActionUsageTargetReferenceUsageIn2\_Factory.

#### General Classes

- Factory (from Foundations)
- ToFeatureMembership\_Init (from KerMLInitializers)

#### Operations

- create () : FeatureMembership [1]
- ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}

```
AssignmentActionUsageTargetReferenceUsageIn2_Factory.create ()
```

### 7.5.2.8 AssignmentActionUsageFeatureMembership3\_Factory

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Factory class to create a feature membership relationship for a feature element created by the factory class AssignmentActionUsageTargetReferenceUsageIn3\_Factory.

#### General Classes

- Factory (from Foundations)
- ToFeatureMembership\_Init (from KerMLInitializers)

- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

```
AssignmentActionUsageReferenceUsageIn1_Factory.create()
```

#### 7.5.2.11 AssignmentActionUsageReferenceUsageIn1\_Factory

##### Description

Factory class creating a reference usage element with direction "in" as parameter of an assignment action usage.

##### Generalizations

- Factory (from Foundations)
- ReferenceUsage\_Init (from SystemInitializers)

##### Operations

- create () : ReferenceUsage [1]
- direction () : FeatureDirectionKind [0..1] {redefines direction}

```
KerML::FeatureDirectionKind::_in'
```

- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{AssignmentActionUsageFeatureMembership2_Factory.create() }
```

#### 7.5.2.12 AssignmentActionUsageTargetReferenceUsageIn2\_Factory

##### Description

Factory class creating a reference usage element as an owned feature of the reference usage of an assignment action usage.

##### Generalizations

- Factory (from Foundations)
- ReferenceUsage\_Init (from SystemInitializers)

##### Operations

- create () : ReferenceUsage [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{AssignmentActionUsageFeatureMembership3_Factory.create() }
```

#### 7.5.2.13 AssignmentActionUsageTargetReferenceUsageIn3\_Factory

##### Description

Factory class creating a reference usage element as an owned feature of the reference usage of an assignment action usage.



## Operations

- `create () : FeatureMembership [1]`
- `ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}`

```
AssignmentActionUsageTargetReferenceUsageIn3_Factory.create()
```

### 7.5.2.9 AssignmentActionUsageOwningMembership\_Factory

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Factory class to create a owning membership relationship for an element created by the factory class `AssignmentActionUsage_Factory`.

#### General Classes

- `Factory` (from `Foundations`)
- `ToOwningMembership_Init` (from `KerMLInitializers`)

## Operations

- `create () : OwningMembership [1]`
- `ownedMemberElement () : Element [1] {redefines ownedMemberElement}`

```
AssignmentActionUsage_Factory.create()
```

### 7.5.2.10 AssignmentActionUsageParameterMembership\_Factory

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Factory class to create a parameter membership relationship for a feature element created by the factory class `AssignmentActionUsageReferenceUsageIn1_Factory`.

#### General Classes

- `Factory` (from `Foundations`)
- `ToParameterMembership_Init` (from `KerMLInitializers`)

## Operations

- `create () : ParameterMembership [1]`
- `ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}`

```
AssignmentActionUsageReferenceUsageIn1_Factory.create()
```

### 7.5.2.11 AssignmentActionUsageReferenceUsageIn1\_Factory

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

## Generalizations

- Factory (from Foundations)
- ReferenceUsage\_Init (from SystemInitializers)

## Operations

- create () : ReferenceUsage [1]

### 7.5.2.14 DirectedReferenceUsage\_Factory

## Description

Factory class creating a reference usage element with a given direction and without owned relationships.

## Generalizations

- Factory (from Foundations)
- ReferenceUsage\_Init (from SystemInitializers)

## Association Ends

- featureDirectionKind : FeatureDirectionKind [1]

## Operations

- create (in featureDirectionKind : FeatureDirectionKind) : ReferenceUsage [1]
- direction () : FeatureDirectionKind [0..1] {redefines direction}

```
featureDirectionKind
```

### 7.5.2.15 DirectedReferenceUsageParameterMembership\_Factory

## Description

Factory class to create a parameter membership relationship for a feature element created by the factory class DirectedReferenceUsage\_Factory.

## Generalizations

- Factory (from Foundations)
- ParameterMembership\_Init (from KerMLInitializers)

## Association Ends

- featureDirectionKind : FeatureDirectionKind [1]

## Operations

- create (in featureDirectionKind : FeatureDirectionKind) : ParameterMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

```
DirectedReferenceUsage_Factory.create(featureDirectionKind)
```

Factory class creating a reference usage element with direction "in" as parameter of an assignment action usage.

#### General Classes

- Factory (from Foundations)
- [ToReferenceUsage\\_Init](#) (from SystemInitializers)

#### Operations

- `create ()` : ReferenceUsage [1]
- `direction ()` : FeatureDirectionKind [0..1] {redefines direction}

```
KerML::FeatureDirectionKind::_in'
```

- `ownedRelationship ()` : Relationship [0..\*] {redefines ownedRelationship}

```
Set{AssignmentActionUsageFeatureMembership2_Factory.create() }
```

#### 7.5.2.12 AssignmentActionUsageTargetReferenceUsageIn2\_Factory

##### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

#### Description

Factory class creating a reference usage element as an owned feature of the reference usage of an assignment action usage.

#### General Classes

- Factory (from Foundations)
- [ToReferenceUsage\\_Init](#) (from SystemInitializers)

#### Operations

- `create ()` : ReferenceUsage [1]
- `ownedRelationship ()` : Relationship [0..\*] {redefines ownedRelationship}

```
Set{AssignmentActionUsageFeatureMembership3_Factory.create() }
```

#### 7.5.2.13 AssignmentActionUsageTargetReferenceUsageIn3\_Factory

##### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

#### Description

Factory class creating a reference usage element as an owned feature of the reference usage of an assignment action usage.

#### General Classes

- Factory (from Foundations)
- [ToReferenceUsage\\_Init](#) (from SystemInitializers)



## Operations

- create () : ReferenceUsage [1]

### 7.5.2.14 DirectedReferenceUsage\_Factory

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

## Description

Factory class creating a reference usage element with a given direction and without owned relationships.

## General Classes

- Factory (from Foundations)
- ToReferenceUsage\_Init (from SystemInitializers)

## Association Ends

- featureDirectionKind : FeatureDirectionKind [1]

## Operations

- create (in featureDirectionKind : FeatureDirectionKind) : ReferenceUsage [1]
- direction () : FeatureDirectionKind [0..1] {redefines direction}

```
featureDirectionKind
```

### 7.5.2.15 DirectedReferenceUsageParameterMembership\_Factory

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

## Description

Factory class to create a parameter membership relationship for a feature element created by the factory class DirectedReferenceUsage\_Factory.

## General Classes

- Factory (from Foundations)
- ToParameterMembership\_Init (from KerMLInitializers)

## Association Ends

- featureDirectionKind : FeatureDirectionKind [1]

## Operations

- create (in featureDirectionKind : FeatureDirectionKind) : ParameterMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

```
DirectedReferenceUsage_Factory.create(featureDirectionKind)
```

### 7.5.2.16 EmptyObjectiveMembership\_Factory

#### Description

Factory class to create an objective membership without a source in the SysML v1 model.

#### Generalizations

- Factory (from Foundations)
- ObjectiveMembership\_Init (from SystemInitializers)

#### Operations

- create () : ObjectiveMembership [1]
- ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}

```
EmptyRequirementUsage_Factory.create()
```

### 7.5.2.17 EmptyRequirementUsage\_Factory

#### Description

Factory class to create a requirement usage without a source in the SysML v1 model.

#### Generalizations

- Factory (from Foundations)
- RequirementUsage\_Init (from SystemInitializers)

#### Operations

- create () : RequirementUsage [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{  
  EmptySubjectMembership_Factory.create(),  
  ReturnParameterFeatureMembership_Factory.create() }
```

### 7.5.2.18 EmptySubject\_Factory

#### Description

Factory class to create a reference usage representing a subject without a source in the SysML v1 model.

#### Generalizations

- Factory (from Foundations)
- ReferenceUsage\_Init (from SystemInitializers)

#### Operations

- create () : ReferenceUsage [1]
- direction () : FeatureDirectionKind [0..1] {redefines direction}

### 7.5.2.16 EmptyObjectiveMembership\_Factory

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Factory class to create an objective membership without a source in the SysML v1 model.

#### General Classes

- Factory (from Foundations)
- [ToObjectiveMembership\\_Init](#) (from SystemInitializers)

#### Operations

- create () : ObjectiveMembership [1]
- ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}

```
EmptyRequirementUsage_Factory.create()
```

### 7.5.2.17 EmptyRequirementUsage\_Factory

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Factory class to create a requirement usage without a source in the SysML v1 model.

#### General Classes

- Factory (from Foundations)
- [ToRequirementUsage\\_Init](#) (from SystemInitializers)

#### Operations

- create () : RequirementUsage [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{  
  EmptySubjectMembership_Factory.create(),  
  ReturnParameterFeatureMembership_Factory.create() }
```

### 7.5.2.18 EmptySubject\_Factory

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Factory class to create a reference usage representing a subject without a source in the SysML v1 model.

#### General Classes

- Factory (from Foundations)
- [ToReferenceUsage\\_Init](#) (from SystemInitializers)

```
KerML::FeatureDirectionKind::_in'
```

### 7.5.2.19 EmptySubjectMembership\_Factory

#### Description

Factory class to create a membership relationship for a reference usage representing a subject without a source in the SysML v1 model.

#### Generalizations

- Factory (from Foundations)
- SubjectMembership\_Init (from SystemInitializers)

#### Operations

- create () : SubjectMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

```
EmptySubject_Factory.create()
```

### 7.5.2.20 FeatureTyping\_Factory

#### Description

Factory class to create a FeatureTyping relationship. The create parameter is set as the type.

#### Generalizations

- Factory (from Foundations)
- FeatureTyping\_Init (from KerMLInitializers)

#### Association Ends

- type : NamedElement [1]

#### Operations

- create (in type : NamedElement) : FeatureTyping [1]
- type () : Type [1] {redefines type}

```
type
```

### 7.5.2.21 FlowConnectionUsage\_Factory

#### Description

Factory class to create a **FlowConnectionUsage** as a target element for a UML4SysML::InformationFlow that is realized by a UML4SysML::Connector. The factory class only supports UML4SysML::InformationFlows which have exactly one source and one target element, which is implicitly assured since connectors in SysML may only ever have two ends.

#### Generalizations



## Operations

- create () : ReferenceUsage [1]
- direction () : FeatureDirectionKind [0..1] {redefines direction}

```
KerML::FeatureDirectionKind::_in'
```

### 7.5.2.19 EmptySubjectMembership\_Factory

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Factory class to create a membership relationship for a reference usage representing a subject without a source in the SysML v1 model.

#### General Classes

- Factory (from Foundations)
- ToSubjectMembership\_Init (from SystemInitializers)

## Operations

- create () : SubjectMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

```
EmptySubject_Factory.create()
```

### 7.5.2.20 FeatureTyping\_Factory

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Factory class to create a FeatureTyping relationship. The create parameter is set as the type.

#### General Classes

- Factory (from Foundations)
- ToFeatureTyping\_Init (from KerMLInitializers)

#### Association Ends

- type : NamedElement [1]

## Operations

- create (in type : NamedElement) : FeatureTyping [1]
- type () : Type [1] {redefines type}

```
type
```

- Factory (from Foundations)
- **FlowConnectionUsage\_Init** (from SystemInitializers)

#### Association Ends

- informationFlow : InformationFlow [1]

#### Operations

- create (in informationFlow : InformationFlow) : **FlowConnectionUsage** [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```

let relationships : Set(KerML::Relationship) =
    informationFlow.realizingConnector->collect(c|Subsetting_Factory.create(c))
->including (FeatureTyping_Factory.create(informationFlow))
->including (FlowEndParameterMembership_Factory.create(
    informationFlow,informationFlow.source.get(0)))
->including (FlowEndParameterMembership_Factory.create(
    informationFlow,informationFlow.target.get(0))) in
let itemProperty : UML::Property =
    if Helper.hasStereotypeApplied(informationFlow, 'SysML::Ports&Flows::ItemFlow') then
        Helper.getTagValueAsElement(informationFlow, 'SysML::Ports&Flows::ItemFlow', 'itemPro
    else
        invalid
    endif in

if itemProperty.oclIsUndefined() then
    relationships->union(informationFlow.conveyed->flatten()
        ->collect(i | FlowItemFeatureMembership_Factory.create(i)))
else
    relationships->including(
        FlowItemFeatureMembership_Factory.create(itemProperty))
endif

```

#### 7.5.2.22 **FlowConnectionUsageFeatureMembership\_Factory**

##### Description

Factory class to create a FeatureMembership relationship for a **FlowConnectionUsage** as a target element for a UML4SysML::InformationFlow that is realized by a UML4SysML::Connector.

##### Generalizations

- Factory (from Foundations)
- FeatureMembership\_Init (from KerMLInitializers)

#### Association Ends

- informationFlow : InformationFlow [1]

#### Operations

- create (in informationFlow : InformationFlow) : FeatureMembership [1]

### 7.5.2.21 FlowEndParameterMembership\_Factory

**SYSML2 -417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"**  
**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Factory class to create a ParameterMembership relationship for an end of a FlowUsage as a target element for a UML4SysML::InformationFlow that is realized by a UML4SysML::Connector.

#### General Classes

- Factory (from Foundations)
- ToParameterMembership\_Init (from KerMLInitializers)

#### Association Ends

- end : NamedElement [1]
- informationFlow : InformationFlow [1]

#### Operations

- create (in informationFlow : InformationFlow, in end : NamedElement) : ParameterMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

```
InformationFlowEventOccurrenceUsage_Factory.create(informationFlow, end)
```

### 7.5.2.22 FlowItem\_Factory

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Factory class to create a ItemFeature element as a target element for the flowing entity specified by an UML4SysML::InformationFlow.

#### General Classes

- Factory (from Foundations)
- ToItemFeature\_Init (from SystemInitializers)

#### Association Ends

- item : NamedElement [1]

#### Operations

- create (in item : NamedElement) : PayloadFeature [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
if item.ocIsKindOf(UML::Classifier) then
  Set{FeatureTyping_Factory.create(item)}
else if item.ocIsKindOf(UML::Property) then
```



```

        Set{ReferenceSubsetting_Factory.create(item)}
    else
        Set{}
    endif
endif

```

### 7.5.2.23 FlowItemFeatureMembership\_Factory

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

##### **Description**

Factory class to create a FeatureMembership relationship for an ItemFeature as a target element for the flowing entity specified by an UML4SysML::InformationFlow.

##### **General Classes**

- Factory (from Foundations)
- ToFeatureMembership\_Init (from KerMLInitializers)

##### **Association Ends**

- item : NamedElement [1]

##### **Operations**

- create (in item : NamedElement) : FeatureMembership [1]
- ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}

```
FlowItem_Factory.create(item)
```

### 7.5.2.24 FlowUsage\_Factory

#### **SYSML2 -417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"** **SYSML2 -220: Replace Generic mapping classes by Initializers**

##### **Description**

Factory class to create a FlowUsage as a target element for a UML4SysML::InformationFlow that is realized by a UML4SysML::Connector. The factory class only supports UML4SysML::InformationFlows which have exactly one source and one target element, which is implicitly assured since connectors in SysML may only ever have two ends.

##### **General Classes**

- Factory (from Foundations)
- ToFlowUsage\_Init (from SystemInitializers)

##### **Association Ends**

- informationFlow : InformationFlow [1]

##### **Operations**

- create (in informationFlow : InformationFlow) : FlowUsage [1]



- `ownedRelationship () : Relationship [0..*]` {redefines `ownedRelationship`}

```

let relationships : Set(KerML::Relationship) =
    informationFlow.realizingConnector->collect(c|Subsetting_Factory.create(c))
->including(FeatureTyping_Factory.create(informationFlow))
->including(FlowEndParameterMembership_Factory.create(
    informationFlow,informationFlow.source.get(0)))
->including(FlowEndParameterMembership_Factory.create(
    informationFlow,informationFlow.target.get(0))) in
let itemProperty : UML::Property =
    if Helper.hasStereotypeApplied(informationFlow, 'SysML::Ports&Flows::ItemFlow') then
        Helper.getTagValueAsElement(informationFlow, 'SysML::Ports&Flows::ItemFlow', 'itemPro
    else
        invalid
    endif in

if itemProperty.oclIsUndefined() then
    relationships->union(informationFlow.conveyed->flatten()
        ->collect(i | FlowItemFeatureMembership_Factory.create(i)))
else
    relationships->including(
        FlowItemFeatureMembership_Factory.create(itemProperty))
endif

```

### 7.5.2.25 FlowUsageFeatureMembership\_Factory

**[SYSML2 -417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"](#)**  
**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

#### Description

Factory class to create a FeatureMembership relationship for a `FlowUsage` as a target element for a `UML4SysML::InformationFlow` that is realized by a `UML4SysML::Connector`.

#### General Classes

- Factory (from Foundations)
- `ToFeatureMembership_Init` (from `KerMLInitializers`)

#### Association Ends

- `informationFlow : InformationFlow [1]`

#### Operations

- `create (in informationFlow : InformationFlow) : FeatureMembership [1]`
- `ownedMemberFeature () : Feature [1]` {redefines `ownedMemberFeature`}

```
FlowUsage_Factory.create(informationFlow)
```

### 7.5.2.26 InformationFlowEventOccurrenceUsage\_Factory

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

- ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}

```
FlowConnectionUsage_Factory.create(informationFlow)
```

### 7.5.2.23 FlowEndParameterMembership\_Factory

#### Description

Factory class to create a ParameterMembership relationship for an end of a FlowConnectionUsage as a target element for a UML4SysML::InformationFlow that is realized by a UML4SysML::Connector.

#### Generalizations

- Factory (from Foundations)
- ParameterMembership\_Init (from KerMLInitializers)

#### Association Ends

- end : NamedElement [1]
- informationFlow : InformationFlow [1]

#### Operations

- create (in informationFlow : InformationFlow, in end : NamedElement) : ParameterMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

```
InformationFlowEventOccurrenceUsage_Factory.create(informationFlow, end)
```

### 7.5.2.24 FlowItem\_Factory

#### Description

Factory class to create a ItemFeature element as a target element for the flowing entity specified by an UML4SysML::InformationFlow.

#### Generalizations

- Factory (from Foundations)
- ItemFeature\_Init (from SystemInitializers)

#### Association Ends

- item : NamedElement [1]

#### Operations

- create (in item : NamedElement) : ItemFeature [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
if item.ocIsKindOf(UML::Classifier) then
    Set{FeatureTyping_Factory.create(item)}
else if item.ocIsKindOf(UML::Property) then
```



## Description

### General Classes

- Factory (from Foundations)
- [ToEventOccurrenceUsage\\_Init](#) (from SystemInitializers)

### Association Ends

- end : NamedElement [1]
- informationFlow : InformationFlow [1]

### Operations

- create (in informationFlow : InformationFlow, in end : NamedElement) : EventOccurrenceUsage [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{InformationFlowReferenceSubsetting_Factory.create(informationFlow, end)}
```

## 7.5.2.27 InformationFlowReferenceSubsetting\_Factory

**[SYSML2 -417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"](#)**

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

## Description

Factory class to create a ReferenceSubsetting relationship for an end of a [FlowUsage](#) subsetting the target element of an end element of an UML4SysML::InformationFlow.

### General Classes

- Factory (from Foundations)
- [ToReferenceSubsetting\\_Init](#) (from KerMLInitializers)

### Association Ends

- end : NamedElement [1]
- informationFlow : InformationFlow [1]

### Operations

- create (in informationFlow : InformationFlow, in end : NamedElement) : ReferenceSubsetting [1]
- referencedFeature () : Feature [1] {redefines referencedFeature}

```
InformationFlowEnd_Mapping.getMapped(informationFlow, end)
```

## 7.5.2.28 LiteralBoolean\_Factory

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

## Description

Factory class to create a LiteralBoolean element.

```

        Set{ReferenceSubsetting_Factory.create(item)}
    else
        Set{}
    endif
endif

```

#### 7.5.2.25 FlowItemFeatureMembership\_Factory

##### Description

Factory class to create a FeatureMembership relationship for an ItemFeature as a target element for the flowing entity specified by an UML4SysML::InformationFlow.

##### Generalizations

- Factory (from Foundations)
- FeatureMembership\_Init (from KerMLInitializers)

##### Association Ends

- item : NamedElement [1]

##### Operations

- create (in item : NamedElement) : FeatureMembership [1]
- ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}

```
FlowItem_Factory.create(item)
```

#### 7.5.2.26 InformationFlowEventOccurrenceUsage\_Factory

##### Description

##### Generalizations

- EventOccurrenceUsage\_Init (from SystemInitializers)
- Factory (from Foundations)

##### Association Ends

- end : NamedElement [1]
- informationFlow : InformationFlow [1]

##### Operations

- create (in informationFlow : InformationFlow, in end : NamedElement) : EventOccurrenceUsage [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{InformationFlowReferenceSubsetting_Factory.create(informationFlow, end)}
```

#### 7.5.2.27 InformationFlowReferenceSubsetting\_Factory

##### Description



Factory class to create a ReferenceSubsetting relationship for an end of a **FlowConnectionUsage** subsetting the target element of an end element of an UML4SysML::InformationFlow.

#### Generalizations

- Factory (from Foundations)
- ReferenceSubsetting\_Init (from KerMLInitializers)

#### Association Ends

- end : NamedElement [1]
- informationFlow : InformationFlow [1]

#### Operations

- create (in informationFlow : InformationFlow, in end : NamedElement) : ReferenceSubsetting [1]
- referencedFeature () : Feature [1] {redefines referencedFeature}

```
InformationFlowEnd_Mapping.getMapped(informationFlow, end)
```

### 7.5.2.28 LiteralBoolean\_Factory

#### Description

Factory class to create a LiteralBoolean element.

#### Generalizations

- Expression\_Init (from KerMLInitializers)
- Factory (from Foundations)

#### Association Ends

- boolean : Boolean [1]
- to : LiteralBoolean [1]  
(redefines: Expression\_Init::to)

#### Operations

- create (in boolean : Boolean) : LiteralBoolean [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set {ReturnParameterFeatureMembership_Factory.create () }
```

### 7.5.2.29 LiteralNull\_Factory

#### Description

Factory class to create a LiteralNull element.

#### Generalizations

- Expression\_Init (from KerMLInitializers)

## General Classes

- Factory (from Foundations)
- ToExpression\_Init (from KerMLInitializers)

## Association Ends

- boolean : Boolean [1]
- to : LiteralBoolean [1]  
{redefines: ToExpression\_Init::to}

## Operations

- create (in boolean : Boolean) : LiteralBoolean [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{ReturnParameterFeatureMembership_Factory.create() }
```

### 7.5.2.29 LiteralNull\_Factory

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Factory class to create a LiteralNull element.

## General Classes

- Factory (from Foundations)
- ToExpression\_Init (from KerMLInitializers)

## Association Ends

- to : NullExpression [1]  
{redefines: ToExpression\_Init::to}

## Operations

- create () : NullExpression [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set{ReturnParameterFeatureMembership_Factory.create() }
```

### 7.5.2.30 LiteralRational\_Factory

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Factory class to create a LiteralRational element.

## General Classes

- Factory (from Foundations)
- ToExpression\_Init (from KerMLInitializers)

- Factory (from Foundations)

#### Association Ends

- to : NullExpression [1]  
(redefines: Expression\_Init::to)

#### Operations

- create () : NullExpression [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set {ReturnParameterFeatureMembership_Factory.create () }
```

### 7.5.2.30 LiteralRational\_Factory

#### Description

Factory class to create a LiteralRational element.

#### Generalizations

- Expression\_Init (from KerMLInitializers)
- Factory (from Foundations)

#### Association Ends

- real : Real [1]
- to : LiteralRational [1]  
(redefines: Expression\_Init::to)

#### Operations

- create (in real : Real) : LiteralReal [1]
- ownedRelationship () : Relationship [0..\*] {redefines ownedRelationship}

```
Set {ReturnParameterFeatureMembership_Factory.create () }
```

### 7.5.2.31 ObjectFlowItemFlowEndRedefinition\_Factory

#### Description

#### Generalizations

- Factory (from Foundations)
- Redefinition\_Init (from KerMLInitializers)

#### Association Ends

- feature : Feature [1]

## Association Ends

- `real : Real [1]`
- `to : LiteralRational [1]`  
`{redefines: ToExpression_Init::to}`

## Operations

- `create (in real : Real) : LiteralReal [1]`
- `ownedRelationship () : Relationship [0..*]` {redefines ownedRelationship}

```
Set{ReturnParameterFeatureMembership_Factory.create() }
```

### 7.5.2.31 LowerBound\_Factory

**[SYSML2 -498](#): The approved Issue KERML\_-18 requires the transformation specification to be adjusted**

## Description

### General Classes

- `Factory` (from Foundations)

## Association Ends

- `multiplicityLowerBoundMembership : MultiplicityLowerBoundMembership_Factory [1]`
- `to : LiteralInteger [1]`  
`{redefines: Initializer::to}`

## Operations

- `create (in lowerValue : Integer) : LiteralInteger [1]`
- `ownedRelationship () : Relationship [0..*]`

```
Set{ReturnParameterFeatureMembership_Factory.create() }
```

- `value () : Integer [1]`

```
lowerValue
```

### 7.5.2.32 MultiplicityElement\_Factory

**[SYSML2 -498](#): The approved Issue KERML\_-18 requires the transformation specification to be adjusted**

## Description

### General Classes

- `Factory` (from Foundations)
- `ToFeature_Init` (from KerMLInitializers)

## Association Ends

- `lowerValue : Integer [1]`

## Operations

- create (in feature : Feature) : Redefinition [1]
- redefinedFeature () : Feature [1] {redefines redefinedFeature}

feature

### 7.5.2.32 ReferenceSubsetting\_Factory

#### Description

Factory class to create a ReferenceSubsetting relationship. The create parameter is set as the referenced feature.

#### Generalizations

- Factory (from Foundations)
- ReferenceSubsetting\_Init (from KerMLInitializers)

#### Association Ends

- property : Property [1]

## Operations

- create (in property : Property) : ReferenceSubsetting [1]
- referencedFeature () : Feature [1] {redefines referencedFeature}

property

### 7.5.2.33 ReturnParameterFeature\_Factory

#### Description

Factory class to create a feature element with direction 'out' representing a return parameter.

#### Generalizations

- Factory (from Foundations)
- Feature\_Init (from KerMLInitializers)

## Operations

- create () : Feature [1]
- direction () : FeatureDirectionKind [0..1] {redefines direction}

KerML::FeatureDirectionKind::\_'out'

### 7.5.2.34 ReturnParameterFeatureMembership\_Factory

#### Description

Factory class to create a feature membership relationship for a feature element with direction 'out' representing a return parameter.



- `multiplicityLowerBoundMembership : MultiplicityLowerBoundMembership_Factory [1]`
- `multiplicityUpperBoundMembership : MultiplicityUpperBoundMembership_Factory [1]`
- `upperValue : Integer [1]`

#### Operations

- `create (in lowerValue : Integer, in upperValue : Integer) : Feature [1]`
- `ownedRelationship () : Relationship [0..*] {redefines ownedRelationship}`

```
Set{self.multiplicityLowerBoundMembership, self.multiplicityUpperBoundMembership}
```

### 7.5.2.33 MultiplicityLowerBoundMembership\_Factory

**[SYSML2\\_-498](#): The approved Issue KERML\_-18 requires the transformation specification to be adjusted**

#### Description

##### General Classes

- `Factory` (from `Foundations`)
- `ToFeatureMembership_Init` (from `KerMLInitializers`)

##### Association Ends

- `lowerBound : LowerBound_Factory [1]`
- `multiplicityElement : MultiplicityElement_Factory [1]`

#### Operations

- `create () : FeatureMembership [1]`
- `ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}`

```
self.lowerBound
```

### 7.5.2.34 MultiplicityMembership\_Factory

**[SYSML2\\_-498](#): The approved Issue KERML\_-18 requires the transformation specification to be adjusted**

#### Description

##### General Classes

- `Factory` (from `Foundations`)
- `ToFeatureMembership_Init` (from `KerMLInitializers`)

##### Association Ends

- `lowerValue : Integer [1]`
- `upperValue : Integer [1]`

#### Operations

- `create (in lowerValue : Integer, in upperValue : Integer) : FeatureMembership [1]`
- `ownedMemberFeature () : Feature [1] {redefines ownedMemberFeature}`



```

if upperValue = 1 then
  if lowerValue = 0 then
    Helpers.getMultiplicityRangeByName('zeroOrOne')
  else if lowerValue = 1 then
    Helpers.getMultiplicityRangeByName('exactlyOne')
  else
    MultiplicityElement.create(lowerValue, upperValue)
  endif endif
else if upperValue = -1 then
  if lowerValue = 0 then
    Helpers.getMultiplicityRangeByName('zeroToMany')
  else if lowerValue = 1 then
    Helpers.getMultiplicityRangeByName('oneToMany')
  else
    MultiplicityElement.create(lowerValue, upperValue)
  endif endif
else
  MultiplicityElement.create(lowerValue, upperValue)
endif endif

```

### 7.5.2.35 MultiplicityUpperBoundMembership\_Factory

**SYSML2\_-498: The approved Issue KERML\_-18 requires the transformation specification to be adjusted**

#### Description

##### General Classes

- Factory (from Foundations)
- ToFeatureMembership\_Init (from KerMLInitializers)

##### Association Ends

- multiplicityElement : MultiplicityElement\_Factory [1]
- upperBound : UpperBound\_Factory [1]

##### Operations

- create (in upperValue : Integer) : FeatureMembership [1]

### 7.5.2.36 ObjectFlowItemFlowEndRedefinition\_Factory

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

##### General Classes

- Factory (from Foundations)
- ToRedefinition\_Init (from KerMLInitializers)

##### Association Ends

- feature : Feature [1]

##### Operations

- create (in feature : Feature) : Redefinition [1]



- redefinedFeature () : Feature [1] {redefines redefinedFeature}

feature

### 7.5.2.37 ParameterMembership\_Factory

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Factory class to create a ParameterMembership relationship.

#### General Classes

- Factory (from Foundations)
- ToParameterMembership\_Init (from KerMLInitializers)

#### Operations

- create () : ParameterMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

ReferenceUsage\_Factory.create()

### 7.5.2.38 ReferenceSubsetting\_Factory

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Factory class to create a ReferenceSubsetting relationship. The create parameter is set as the referenced feature.

#### General Classes

- Factory (from Foundations)
- ToReferenceSubsetting\_Init (from KerMLInitializers)

#### Association Ends

- property : Property [1]

#### Operations

- create (in property : Property) : ReferenceSubsetting [1]
- referencedFeature () : Feature [1] {redefines referencedFeature}

property

### 7.5.2.39 ReferenceUsage\_Factory

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

### Generalizations

- Factory (from Foundations)
- ReturnParameterMembership\_Init (from KerMLInitializers)

### Operations

- create () : ReturnParameterMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}

```
ReturnParameterFeature_Factory.create()
```

### 7.5.2.35 Subsetting\_Factory

#### Description

Factory class to create a Subsetting relationship. The create parameter is set as the subsetting feature.

### Generalizations

- Factory (from Foundations)
- Subsetting\_Init (from KerMLInitializers)

### Association Ends

- subsetting : NamedElement [1]

### Operations

- create (in subsetting : NamedElement) : Subsetting [1]
- subsettingFeature () : Feature [1] {redefines subsettingFeature}

```
subsetting
```

## 7.6 Generic Mappings

### 7.6.1 Overview

Generic mappings are partial definitions of transformation rules that are intended to factorize reusable algorithms for making the global specification more compact and easier to read and maintain. Basically, they provide a default value for all the non-derived attributes of their target metaclass wherever possible, or declare an abstract operation for them otherwise. They are similar to initializers, except that they have a source element defined. The operations provided by the generic mappings can be redefined by their specialization, as appropriate according to the source type specified by the redefinition of their `from` attribute.

All of these generic mappings are abstract.

### 7.6.2 Common Mappings

#### 7.6.2.1 CommonFeatureReferenceExpression\_Mapping

#### Description

## Description

Factory class to create a ReferenceUsage element with direction 'in'.

## General Classes

- Factory (from Foundations)
- ToReferenceUsage\_Init (from SystemInitializers)

## Operations

- create () : ReferenceUsage [1]
- direction () : FeatureDirectionKind [0..1] {redefines direction}

```
KerML::FeatureDirectionKind::_in'
```

### 7.5.2.40 ReturnParameterFeature\_Factory

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Factory class to create a feature element with direction 'out' representing a return parameter.

## General Classes

- Factory (from Foundations)
- ToFeature\_Init (from KerMLInitializers)

## Operations

- create () : Feature [1]
- direction () : FeatureDirectionKind [0..1] {redefines direction}

```
KerML::FeatureDirectionKind::_out'
```

### 7.5.2.41 ReturnParameterFeatureMembership\_Factory

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Factory class to create a feature membership relationship for a feature element with direction 'out' representing a return parameter.

## General Classes

- Factory (from Foundations)
- ToReturnParameterMembership\_Init (from KerMLInitializers)

## Operations

- create () : ReturnParameterMembership [1]
- ownedMemberParameter () : Feature [1] {redefines ownedMemberParameter}





```
ReturnParameterFeature_Factory.create()
```

### 7.5.2.42 Subsetting\_Factory

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

Factory class to create a Subsetting relationship. The create parameter is set as the subsetting feature.

##### **General Classes**

- Factory (from Foundations)
- ToSubsetting\_Init (from KerMLInitializers)

##### **Association Ends**

- subsetting : NamedElement [1]

##### **Operations**

- create (in subsetting : NamedElement) : Subsetting [1]
- subsettingFeature () : Feature [1] {redefines subsettingFeature}

```
subsetting
```

### 7.5.2.43 UpperBound\_Factory

#### **SYSML2\_-498: The approved Issue KERML\_-18 requires the transformation specification to be adjusted**

##### **Description**

##### **General Classes**

- Factory (from Foundations)

##### **Attributes**

- multiplicityLowerBoundMembership : MultiplicityLowerBoundMembership\_Factory [1]
- multiplicityUpperBoundMembership : MultiplicityUpperBoundMembership\_Factory [1]

##### **Association Ends**

- multiplicityUpperBoundMembership : MultiplicityUpperBoundMembership\_Factory [1]
- to : LiteralInteger [1]  
{redefines: Initializer::to}

##### **Operations**

- create (in upperValue : Integer) : LiteralInteger [1]
- ownedRelationship () : Relationship [0..\*]

```
Set {ReturnParameterFeatureMembership_Factory.create() }
```

Common mapping class for a feature reference expression.

### General Mappings

**Generic**ToFeatureReferenceExpression\_Mapping

### Mapping Source

TypedElement

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set { CommonMembership_Mapping.getMapped (from) ,  
CommonReturnParameterFeatureMembership_Mapping.getMapped (from) }
```

## 7.6.2.2 CommonMembership\_Mapping

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

**Generic**ToMembership\_Mapping

### Mapping Source

TypedElement

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

- `value () : Integer [1]`

`upperValue`

## 7.6 Generic Mappings

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### 7.6.1 Overview

Generic mappings are partial definitions of transformation rules that are intended to factorize reusable algorithms for making the global specification more compact and easier to read and maintain. Basically, they provide a default value for all the non-derived attributes of their target metaclass wherever possible, or declare an abstract operation for them otherwise. They are similar to initializers, except that they have a source element defined. The operations provided by the generic mappings can be redefined by their specialization, as appropriate according to the source type specified by the redefinition of their `from` attribute.

All of these generic mappings are abstract.

### 7.6.2 Common Mappings

#### 7.6.2.1 CommonFeatureReferenceExpression\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Common mapping class for a feature reference expression.

##### General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

##### Mapping Source

TypedElement

##### Mapping Target

FeatureReferenceExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
from

#### 7.6.2.3 CommonParameterReferenceUsageInMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToParameterMembership\_Mapping

##### Mapping Source

Element

##### Mapping Target

ParameterMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
if not from.ocIsKindOf(UML::TypedElement) then  
CommonParameterReferenceUsageIn\_Mapping.getMapped(from)  
else if from.ocIsType(UML::TypedElement).type.ocIsUndefined() then  
CommonParameterReferenceUsageIn\_Mapping.getMapped(from)  
else  
CommonParameterReferenceUsageInUntyped\_Mapping.getMapped(from)  
endif  
endif

#### 7.6.2.4 CommonParameterReferenceUsageIn\_Mapping

##### Description

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`  
`Set { CommonMembership_Mapping.getMapped (from) ,`  
`CommonReturnParameterFeatureMembership_Mapping.getMapped (from) }`

### 7.6.2.2 CommonMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToMembership\_Init  
Mapping

##### Mapping Source

TypedElement

##### Mapping Target

Membership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`  
`from`

### 7.6.2.3 CommonParameterReferenceUsageInMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

Common mapping class that creates a parameter reference usage element with direction 'in' and with a type.

### General Mappings

CommonParameterReferenceUsageInUntyped\_Mapping

### Mapping Source

Element

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
if from.ocIsKindOf(UML::TypedElement) then
Set{CommonParameterReferenceUsageInFeatureTyping_Mapping.getMapped(from)}
else Set{} endif
```

## 7.6.2.5 CommonParameterReferenceUsageInFeatureTyping\_Mapping

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

GenericToFeatureTyping\_Mapping

### Mapping Source

Element

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

[ToParameterMembership\\_Init](#)  
Mapping

### Mapping Source

Element

### Mapping Target

ParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ParameterMembership::ownedMemberParameter () : Feature [1]`

```
if not from.ocIsKindOf(UML::TypedElement) then
    CommonParameterReferenceUsageIn_Mapping.getMapped(from)
else if from.ocIsType(UML::TypedElement).type.ocIsUndefined() then
    CommonParameterReferenceUsageIn_Mapping.getMapped(from)
else
    CommonParameterReferenceUsageInUntyped_Mapping.getMapped(from)
endif
endif
```

#### 7.6.2.4 CommonParameterReferenceUsageIn\_Mapping

##### Description

Common mapping class that creates a parameter reference usage element with direction 'in' and with a type.

##### General Mappings

[CommonParameterReferenceUsageInUntyped\\_Mapping](#)  
[Mapping](#)

### Mapping Source

Element

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
if from.ocIsKindOf (UML::TypedElement)
then
if from.ocAsType (UML::TypedElement) .type.ocIsKindOf (UML::PrimitiveType) then
    Helper.getScalarValueType (from.ocAsType (UML::TypedElement) .type)
else
    from.ocAsType (UML::TypedElement) .type
endif
else invalid endif
```

#### 7.6.2.6 CommonParameterReferenceUsageInUntyped\_Mapping

##### Description

Common mapping class that creates a parameter reference usage element with direction 'in' and without a type.

##### General Mappings

GenericToReferenceUsage\_Mapping

##### Mapping Source

Element

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

```
KerML::FeatureDirectionKind::_in'
```

#### 7.6.2.7 CommonReturnParameterFeature\_Mapping

##### Description



## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
if from.ocIsKindOf(UML::TypedElement) then
Set{CommonParameterReferenceUsageInFeatureTyping_Mapping.getMapped(from)}
else Set{} endif
```

### 7.6.2.5 CommonParameterReferenceUsageInFeatureTyping\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

Element

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
if from.ocIsKindOf(UML::TypedElement)
then
if from.ocAsType(UML::TypedElement).type.ocIsKindOf(UML::PrimitiveType) then
Helper.getScalarValueType(from.ocAsType(UML::TypedElement).type)
else
from.ocAsType(UML::TypedElement).type
```

Common mapping class that creates a parameter feature element with a type.

### General Mappings

CommonReturnParameterFeatureUntyped\_Mapping

### Mapping Source

Element

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  

```
if from.ocIsKindOf(UML::Property) then
    Set{CommonReturnParameterFeatureTyping_Mapping.getMapped(from) }
else
    Set{}
endif
```

## 7.6.2.8 CommonReturnParameterFeatureTyping\_Mapping

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

GenericToFeatureTyping\_Mapping

### Mapping Source

Element

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

```
endif
else invalid endif
```

### 7.6.2.6 CommonParameterReferenceUsageInUntyped\_Mapping

**[SYSML2 -220](#): Replace Generic mapping classes by Initializers**

#### Description

Common mapping class that creates a parameter reference usage element with direction 'in' and without a type.

#### General Mappings

ToReferenceUsage\_Init  
Mapping

#### Mapping Source

Element

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]  
KerML::FeatureDirectionKind::\_in'

### 7.6.2.7 CommonReturnParameterFeature\_Mapping

**[SYSML2 -220](#): Replace Generic mapping classes by Initializers**

#### Description

Common mapping class that creates a parameter feature element with a type.

#### General Mappings

CommonReturnParameterFeatureUntyped\_Mapping  
Mapping

#### Mapping Source

Element

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
if from.ocIsKindOf (UML::Property)
then
if from.ocAsType (UML::TypedElement) .type.ocIsKindOf (UML::PrimitiveType) then
    Helper.getScalarValueType (from.ocAsType (UML::TypedElement) .type)
else
    from.ocAsType (UML::TypedElement) .type
endif
else invalid endif
```

### 7.6.2.9 CommonReturnParameterFeatureUntyped\_Mapping

#### Description

Common mapping class that creates a parameter feature element without a type.

#### General Mappings

GenericToFeature\_Mapping

#### Mapping Source

Element

#### Mapping Target

Feature

#### Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::direction () : FeatureDirectionKind [0..1]

```
KerML::FeatureDirectionKind::_out'
```

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  

```
if from.ocIsKindOf(UML::Property) then
    Set{CommonReturnParameterFeatureTyping_Mapping.getMapped(from)}
else
    Set{}
endif
```

### 7.6.2.8 CommonReturnParameterFeatureTyping\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

Element

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules



In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```

if from.ocIsKindOf (UML::Property)
then
if from.ocAsType (UML::TypedElement) .type.ocIsKindOf (UML::PrimitiveType) then
    Helper.getScalarValueType (from.ocAsType (UML::TypedElement) .type)
else
    from.ocAsType (UML::TypedElement) .type
endif
else invalid endif

```

### 7.6.2.9 CommonReturnParameterFeatureUntyped\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Common mapping class that creates a parameter feature element without a type.

#### General Mappings

ToFeature\_**Init**  
Mapping

#### Mapping Source

Element

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::direction () : FeatureDirectionKind [0..1]

```
KerML::FeatureDirectionKind::_out'
```

### 7.6.2.10 CommonReturnParameterFeatureMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

### 7.6.2.10 CommonReturnParameterFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToReturnParameterMembership\_Mapping

#### Mapping Source

Element

#### Mapping Target

ReturnParameterMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReturnParameterMembership::ownedMemberParameter () : Feature [1]

```
if not from.ocliIsKindOf(UML::TypedElement) then
    CommonReturnParameterFeatureUntyped_Mapping.getMapped(from)
else if from.oclAsType(UML::TypedElement).type.ocliIsUndefined() then
    CommonReturnParameterFeatureUntyped_Mapping.getMapped(from)
else
    CommonReturnParameterFeatureUntyped_Mapping.getMapped(from)
endif
endif
```

### 7.6.2.11 CommonReturnParameterReferenceUsageMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

**Generic**ToReturnParameterMembership\_Mapping

#### Mapping Source

Element



Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToReturnParameterMembership\_Init  
Mapping

### Mapping Source

Element

### Mapping Target

ReturnParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReturnParameterMembership::ownedMemberParameter () : Feature [1]

```
if not from.ocIsKindOf(UML::TypedElement) then
    CommonReturnParameterFeatureUntyped_Mapping.getMapped(from)
else if from.ocIsType(UML::TypedElement).type.ocIsUndefined() then
    CommonReturnParameterFeatureUntyped_Mapping.getMapped(from)
else
    CommonReturnParameterFeatureUntyped_Mapping.getMapped(from)
endif
endif
```

#### 7.6.2.11 CommonReturnParameterReferenceUsageMembership\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToReturnParameterMembership\_Init  
Mapping

### Mapping Source

Element

### Mapping Target

## Mapping Target

ReturnParameterMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReturnParameterMembership::ownedMemberParameter () : Feature [0..1]

```
if not from.ocIsKindOf(UML::TypedElement) then
    CommonReturnParameterReferenceUsageUntyped_Mapping.getMapped(from)
else if from.ocIsType(UML::TypedElement).type.ocIsUndefined() then
    CommonReturnParameterReferenceUsageUntyped_Mapping.getMapped(from)
else
    CommonReturnParameterReferenceUsageUntyped_Mapping.getMapped(from)
endif
endif
```

### 7.6.2.12 CommonReturnParameterReferenceUsage\_Mapping

#### Description

Creates a reference usage.

#### General Mappings

CommonReturnParameterReferenceUsageUntyped\_Mapping

#### Mapping Source

Element

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

ReturnParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReturnParameterMembership::ownedMemberParameter () : Feature [0..1]

```
if not from.ocIsKindOf(UML::TypedElement) then
    CommonReturnParameterReferenceUsageUntyped_Mapping.getMapped(from)
else if from.ocIsType(UML::TypedElement).type.ocIsUndefined() then
    CommonReturnParameterReferenceUsageUntyped_Mapping.getMapped(from)
else
    CommonReturnParameterReferenceUsageUntyped_Mapping.getMapped(from)
endif
endif
```

## 7.6.2.12 CommonReturnParameterReferenceUsage\_Mapping

### Description

Creates a reference usage.

### General Mappings

CommonReturnParameterReferenceUsageUntyped\_Mapping  
Mapping

### Mapping Source

Element

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
if from.oclIsKindOf(UML::TypedElement) then
Set{CommonReturnParameterReferenceUsageFeatureTyping_Mapping.getMapped(from)}
else Set{} endif
```

### 7.6.2.13 CommonReturnParameterReferenceUsageFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**Generic**ToFeatureTyping\_Mapping

#### Mapping Source

Element

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
if from.oclIsKindOf(UML::TypedElement)
then
if from.oclAsType(UML::TypedElement).type.oclIsKindOf(UML::PrimitiveType) then
Helper.getScalarValueType(from.oclAsType(UML::TypedElement).type)
else
from.oclAsType(UML::TypedElement).type
endif
else invalid endif
```

### 7.6.2.14 CommonReturnParameterReferenceUsageUntyped\_Mapping

#### Description

Creates a reference usage.

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
if from.ocIsKindOf(UML::TypedElement) then
Set{CommonReturnParameterReferenceUsageFeatureTyping_Mapping.getMapped(from)}
else Set{} endif
```

#### 7.6.2.13 CommonReturnParameterReferenceUsageFeatureTyping\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

###### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

###### General Mappings

ToFeatureTyping\_Init  
Mapping

###### Mapping Source

Element

###### Mapping Target

FeatureTyping

###### Owned Mappings

(none)

###### Applicable filters

(none)

###### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
if from.ocIsKindOf(UML::TypedElement)
then
if from.ocAsType(UML::TypedElement).type.ocIsKindOf(UML::PrimitiveType) then
Helper.getScalarValueType(from.ocAsType(UML::TypedElement).type)
else
from.ocAsType(UML::TypedElement).type
endif
else invalid endif
```

#### 7.6.2.14 CommonReturnParameterReferenceUsageUntyped\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## General Mappings

**Generic**ToReferenceUsage\_Mapping

## Mapping Source

Element

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

`KerML::FeatureDirectionKind::_out'`

### 7.6.2.15 CommonReferenceUsageIn\_Mapping

## Description

Common mapping class that creates a reference usage element with direction 'in'.

## General Mappings

CommonReferenceUsageInUntyped\_Mapping

## Mapping Source

TypedElement

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

### Description

Creates a reference usage.

### General Mappings

ToReferenceUsage\_Init  
Mapping

### Mapping Source

Element

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]  
`KerML::FeatureDirectionKind::_out'`

## 7.6.2.15 CommonReferenceUsageIn\_Mapping

### Description

Common mapping class that creates a reference usage element with direction 'in'.

### General Mappings

CommonReferenceUsageInUntyped\_Mapping  
Mapping

### Mapping Source

TypedElement

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

Common mapping class that creates a reference usage element with direction 'in'.

```
Set { CommonReferenceUsageInFeatureTyping_Mapping.getMapped (from) }
```

#### 7.6.2.16 CommonReferenceUsageInFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

`GenericToFeatureMembership_Mapping`

##### Mapping Source

`TypedElement`

##### Mapping Target

`FeatureMembership`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
if from.type.oclIsUndefined() then
    CommonReferenceUsageInUntyped_Mapping.getMapped (from)
else
    CommonReferenceUsageIn_Mapping.getMapped (from)
endif
```

#### 7.6.2.17 CommonReferenceUsageInFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings



## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

Common mapping class that creates a reference usage element with direction 'in'.

```
Set{CommonReferenceUsageInFeatureTyping_Mapping.getMapped(from) }
```

### 7.6.2.16 CommonReferenceUsageInFeatureMembership\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

TypedElement

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
if from.type.oclIsUndefined() then
    CommonReferenceUsageInUntyped_Mapping.getMapped(from)
else
    CommonReferenceUsageIn_Mapping.getMapped(from)
endif
```

## GenericToFeatureTyping\_Mapping

### Mapping Source

TypedElement

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
if from.type.ocliIsKindOf(UML::PrimitiveType) then
    Helper.getScalarValueType(from.type)
else
    from.type
endif
```

## 7.6.2.18 CommonReferenceUsageInUntyped\_Mapping

### Description

Common mapping class that creates an untyped reference usage element with direction 'in'.

### General Mappings

## GenericToReferenceUsage\_Mapping

### Mapping Source

TypedElement

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

### 7.6.2.17 CommonReferenceUsagelnFeatureTyping\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

ToFeatureTyping\_Init  
Mapping

#### Mapping Source

TypedElement

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
if from.type.ocIsKindOf(UML::PrimitiveType) then
  Helper.getScalarValueType(from.type)
else
  from.type
endif
```

### 7.6.2.18 CommonReferenceUsagelnUntyped\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Common mapping class that creates an untyped reference usage element with direction 'in'.

#### General Mappings

ToReferenceUsage\_Init  
Mapping

#### Mapping Source

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_'in'`
- `ReferenceUsage::declaredName () : String [0..1]`  
`from.name`

## 7.6.3 Generic Mappings To KerML

### 7.6.3.1 GenericToAnnotatingElement\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *AnnotatingElement*.

#### General Mappings

GenericToElement\_Mapping

#### Mapping Source

Element

#### Mapping Target

AnnotatingElement

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `AnnotatingElement::annotation () : Annotation [0..*]`  
`Set {}`

### 7.6.3.2 GenericToAnnotation\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Annotation*.

TypedElement

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::declaredName () : String [0..1]`  
`from.name`
- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_in'`

## 7.7 Mappings from UML4SysML metaclasses

### 7.7.1 Overview

UML4SysML is the subset of UML containing all model elements that are reused by SysML. The complete list of model elements is defined in [SysMLv1], subclause 4.1.

### 7.7.2 Actions

#### 7.7.2.1 Overview

**SYSML2\_-329: Mapping overview tables are wrong**

Table 1. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
AcceptCallAction	AcceptActionUsage
AcceptEventAction	AcceptActionUsage
ActionInputPin	ReferenceUsage
AddStructuralFeatureValueAction	ActionUsage
AddVariableValueAction	ActionUsage
BroadcastSignalAction	ActionUsage
CallBehaviorAction	ActionUsage
CallOperationAction	ActionUsage
Clause	not mapped; see next section

## General Mappings

GenericToRelationship\_Mapping

## Mapping Source

Element

## Mapping Target

Annotation

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Annotation::annotatedElement () : Element [1]  
*abstract rule*
- Annotation::owningAnnotatedElement () : Element [0..1]  
*null*
- Annotation::annotatingElement () : AnnotatingElement [1]  
*abstract rule*

### 7.6.3.3 GenericToAssociation\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Association*.

#### General Mappings

GenericToRelationship\_Mapping

GenericToClassifier\_Mapping

#### Mapping Source

Element

#### Mapping Target

Association

#### Owned Mappings

(none)

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
ClearAssociationAction	ActionUsage
ClearStructuralFeatureAction	ActionUsage
ClearVariableAction	ActionUsage
ConditionalNode	Namespace ActionUsage
CreateLinkAction	ActionUsage
CreateLinkObjectAction	ActionUsage
CreateObjectAction	ActionUsage
DestroyLinkAction	ActionUsage
DestroyObjectAction	ActionUsage
InputPin	ReferenceUsage
LinkEndCreationData	not mapped; see next section
LinkEndData	not mapped; see next section
LinkEndDestructionData	not mapped; see next section
LoopNode	Namespace ActionUsage
OpaqueAction	ActionUsage
OutputPin	ReferenceUsage
RaiseExceptionAction	ActionUsage
ReadExtentAction	ActionUsage
ReadIsClassifiedObjectAction	ActionUsage
ReadLinkAction	ActionUsage
ReadLinkObjectEndAction	ActionUsage
ReadSelfAction	ActionUsage
ReadStructuralFeatureAction	ActionUsage
ReadVariableAction	ActionUsage
ReclassifyObjectAction	ActionUsage
ReduceAction	ActionUsage
RemoveStructuralFeatureValueAction	ActionUsage
RemoveVariableValueAction	ActionUsage
ReplyAction	ActionUsage
SendObjectAction	ActionUsage
SendSignalAction	ActionUsage
SequenceNode	Namespace ActionUsage
StartClassifierBehaviorAction	ActionUsage

#### 7.6.3.4 GenericToBehavior\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *Behavior*.

##### General Mappings

GenericToClassifier\_Mapping

##### Mapping Source

Element

##### Mapping Target

Behavior

##### Owned Mappings

(none)

#### 7.6.3.5 GenericToClassifier\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *Classifier*.

##### General Mappings

GenericToType\_Mapping

##### Mapping Source

Element

##### Mapping Target

Classifier

##### Owned Mappings

(none)

#### 7.6.3.6 GenericToComment\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *Comment*.

##### General Mappings

GenericToAnnotatingElement\_Mapping

##### Mapping Source



SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
StartObjectBehaviorAction	ActionUsage
StructuredActivityNode	Namespace ActionUsage
TestIdentityAction	CalculationUsage
UnmarshallAction	ActionUsage
ValuePin	ReferenceUsage
ValueSpecificationAction	ActionUsage

### 7.7.2.2 UML4SysML::Actions elements not mapped

**Table 2. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
AcceptCallAction	Since the CallEvent is not supported by SysML v2, the AcceptCallAction is also not covered. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.
ActionInputPin	The UML4SysML::ActionInputPin concept is not covered by SysML v2. The model element is mapped as a input or output pin, but without the special action input pin semantics.
Clause	Mapping is not specified yet.
ConditionalNode	Mapping is not specified yet.
LinkEndCreationData	Mapping is not specified yet.
LinkEndData	Mapping is not specified yet.
LinkEndDestructionData	Mapping is not specified yet.
ReclassifyObjectAction	The UML4SysML::ReclassifyObjectAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.
ReplyAction	The UML4SysML::ReplyAction is only used with UML4SysML::AcceptCallAction. Since we have no mapping of AcceptCallAction to SysML v2, there is also no mapping for ReplyAction. However, it is mapped to an empty action usage to keep the connections within the activity respectively action definition.
StartClassifierBehaviorAction	The UML4SysML::StartClassifierBehaviorAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.
StartObjectBehaviorAction	The UML4SysML::StartObjectBehaviorAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.

Element

**Mapping Target**

Comment

**Owned Mappings**

(none)

**Applicable filters**

(none)

**Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Comment::locale () : String [1]  
    null
- Comment::body () : String [1]  
    abstract rule

### 7.6.3.7 GenericToConjugation\_Mapping

**Description**

Generic mapping class for mappings to the SysML v2 element *Conjugation*.

**General Mappings**

GenericToRelationship\_Mapping

**Mapping Source**

Element

**Mapping Target**

Conjugation

**Owned Mappings**

(none)

**Applicable filters**

(none)

**Mapping rules**

SysML v1 Concept	Rationale
UnmarshallAction	Mapping is not specified yet.

### 7.7.2.3 Mapping Specifications

#### 7.7.2.3.1 Accept Event Actions

##### 7.7.2.3.1.1 AcceptCallAction\_Mapping

###### Description

Since the CallEvent is not supported by SysML v2, the AcceptCallAction is also not covered. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.

###### General Mappings

AcceptEventAction\_Mapping

###### Mapping Source

AcceptCallAction

###### Mapping Target

AcceptActionUsage

###### Owned Mappings

(none)

###### Applicable filters

(none)

##### 7.7.2.3.1.2 AcceptEventAction\_Mapping

###### Description

The UML4SysML::AcceptEventAction is mapped to a AcceptActionUsage element.

If the trigger is a signal, it is mapped to an accept parameter typed by the signal.

SysMLv2 does not support more than one trigger. Therefore only the first specified trigger of the action is transformed. All further triggers are ignored.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action acceptEventActionSignalEvent1 accept : SysMLv1Signal via sysMLv1Port;
action acceptEventActionChangeEvent1 accept when when changeExpression.result {
    calc changeExpression {
        return : ScalarValues::Boolean;
        language "OCL"
        /*
         * x > 0
         */
    }
}

```

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Conjugation::conjugatedType () : Type [1]`  
*abstract rule*
- `Conjugation::originalType () : Type [1]`  
*abstract rule*

### 7.6.3.8 GenericToConnector\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Connector*.

#### General Mappings

GenericToFeature\_Mapping

GenericToRelationship\_Mapping

#### Mapping Source

Element

#### Mapping Target

Connector

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Connector::isDirected () : Boolean [1]`  
*false*

### 7.6.3.9 GenericToDocumentation\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Documentation*.

#### General Mappings

GenericToComment\_Mapping

#### Mapping Source



Element

**Mapping Target**

Documentation

**Owned Mappings**

(none)

### 7.6.3.10 GenericToElement\_Mapping

**Description**

This is the general abstract class to be used as an ancestor for any class mapping specification.

**General Mappings**

Mapping

**Mapping Source**

Element

**Mapping Target**

Element

**Owned Mappings**

(none)

**Applicable filters**

(none)

**Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Element::ownedRelationship () : Relationship [0..*]`  
`Set {}`
- `Element::aliasId () : String [0..*]`  
`Set {}`
- `Element::shortName () : String [0..1]`  
`null`
- `Element::declaredName () : String [0..1]`  
`null`



- `Element::elementId () : String [1]`

`Helper.createUUID()`

### 7.6.3.11 GenericToEndFeatureMembership\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *EndFeatureMembership*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

Element

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

### 7.6.3.12 GenericToExpression\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Expression*.

#### General Mappings

GenericToStep\_Mapping

#### Mapping Source

Element

#### Mapping Target

Expression

#### Owned Mappings

(none)

### 7.6.3.13 GenericToFeature\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Feature*.

#### General Mappings





GenericToType\_Mapping

## Mapping Source

Element

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isComposite () : Boolean [1]  
false
- Feature::isOrdered () : Boolean [1]  
false
- Feature::isEnd () : Boolean [1]  
false
- Feature::isReadOnly () : Boolean [1]  
false
- Feature::direction () : FeatureDirectionKind [0..1]  
null
- Feature::isDerived () : Boolean [1]  
false
- Feature::isPortion () : Boolean [1]  
false
- Feature::isUnique () : Boolean [1]  
true

### 7.6.3.14 GenericToFeatureChainExpression\_Mapping

#### Description



Generic mapping class for mappings to the SysML v2 element *FeatureChainExpression*.

#### General Mappings

GenericToOperatorExpression\_Mapping

#### Mapping Source

Element

#### Mapping Target

FeatureChainExpression

#### Owned Mappings

(none)

### 7.6.3.15 GenericToFeatureChaining\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *FeatureChaining*.

#### General Mappings

GenericToRelationship\_Mapping

#### Mapping Source

Element

#### Mapping Target

FeatureChaining

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]  
*abstract rule*

### 7.6.3.16 GenericToFeatureMembership\_Mapping

#### Description



Generic mapping class for mappings to the SysML v2 element *FeatureMembership*.

### General Mappings

GenericToOwningMembership\_Mapping

GenericToTypeFeaturing\_Mapping

### Mapping Source

Element

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
*abstract rule*
- FeatureMembership::ownedRelatedElement () : Element [0..\*]

```
Set{self.ownedMemberFeature() }
```

### 7.6.3.17 GenericToFeatureReferenceExpression\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *FeatureReferenceExpression*.

### General Mappings

GenericToExpression\_Mapping

### Mapping Source

Element

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)



### 7.6.3.18 GenericToFeatureTyping\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *FeatureTyping*.

#### General Mappings

GenericToSpecialization\_Mapping

#### Mapping Source

Element

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::typedFeature () : Feature [1]  
*abstract rule*
- FeatureTyping::type () : Type [1]  
*abstract rule*

### 7.6.3.19 GenericToFeatureValue\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *FeatureValue*.

#### General Mappings

GenericToOwningMembership\_Mapping

#### Mapping Source

Element

#### Mapping Target

FeatureValue

#### Owned Mappings





(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::featureWithValue () : Feature [1]  
*abstract rule*
- FeatureValue::value () : Expression [1]  
*abstract rule*
- FeatureValue::isDefault () : Boolean [1]  
  
false
- FeatureValue::ownedRelatedElement () : Element [0..\*]  
  
Set{self.value () }
- FeatureValue::isInitial () : Boolean [1]  
  
false

### 7.6.3.20 GenericToFunction\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Function*.

#### General Mappings

GenericToBehavior\_Mapping

#### Mapping Source

Element

#### Mapping Target

Function

#### Owned Mappings

(none)

### 7.6.3.21 GenericToImport\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Import*.

#### General Mappings



## GenericToRelationship\_Mapping

### Mapping Source

Element

### Mapping Target

Import

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Import::isImportAll () : Boolean [1]`  
`false`
- `Import::isRecursive () : Boolean [1]`  
`false`
- `Import::importedMemberName () : String [0..1]`  
`null`
- `Import::visibility () : VisibilityKind [1]`  
`KerML::VisibilityKind::public`

## 7.6.3.22 GenericToInvocationExpression\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *InvocationExpression*.

### General Mappings

GenericToExpression\_Mapping

### Mapping Source

Element

### Mapping Target

InvocationExpression



## Owned Mappings

(none)

### 7.6.3.23 GenericToInteraction\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Interaction*.

#### General Mappings

GenericToBehavior\_Mapping

GenericToAssociation\_Mapping

#### Mapping Source

Element

#### Mapping Target

Interaction

## Owned Mappings

(none)

### 7.6.3.24 GenericToItemFlow\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *ItemFlow*.

#### General Mappings

GenericToConnector\_Mapping

#### Mapping Source

Element

#### Mapping Target

ItemFlow

## Owned Mappings

(none)

### 7.6.3.25 GenericToMembership\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Membership*.

#### General Mappings



GenericToRelationship\_Mapping

### Mapping Source

Element

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberShortName () : String [0..1]  
null
- Membership::membershipOwningNamespace () : Element [0..\*]  
abstract rule
- Membership::visibility () : VisibilityKind [1]  
KerML::VisibilityKind::public
- Membership::memberElement () : Element [1]  
abstract rule
- Membership::memberName () : String [0..1]  
null

### 7.6.3.26 GenericToMembershipImport\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *MembershipImport*.

#### General Mappings

GenericToImport\_Mapping

### Mapping Source

Element

### Mapping Target

MembershipImport





## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MembershipImport::importedMembership () : Namespace [1]  
*abstract rule*

### 7.6.3.27 GenericToNamespace\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Namespace*.

#### General Mappings

GenericToElement\_Mapping

#### Mapping Source

Element

#### Mapping Target

Namespace

#### Owned Mappings

(none)

### 7.6.3.28 GenericToNamespaceImport\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *NamespaceImport*.

#### General Mappings

GenericToImport\_Mapping

#### Mapping Source

Element

#### Mapping Target

NamespaceImport



## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `NamespaceImport::importedNamespace () : Namespace [1]`  
*abstract rule*

### 7.6.3.29 GenericToOperatorExpression\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *OperatorExpression*.

#### General Mappings

GenericToExpression\_Mapping

#### Mapping Source

Element

#### Mapping Target

OperatorExpression

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OperatorExpression::operator () : String [1]`  
*abstract rule*

### 7.6.3.30 GenericToOwningMembership\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *OwningMembership*.



## General Mappings

GenericToMembership\_Mapping

## Mapping Source

Element

## Mapping Target

OwningMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
*abstract rule*
- OwningMembership::ownedRelatedElement () : Element [0..\*]  

```
Set { self.ownedMemberElement () }
```

### 7.6.3.31 GenericToPackage\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Package*.

## General Mappings

GenericToNamespace\_Mapping

## Mapping Source

Element

## Mapping Target

Package

## Owned Mappings

(none)

### 7.6.3.32 GenericToParameterMembership\_Mapping

#### Description



Generic mapping class for mappings to the SysML v2 element *ParameterMembership*.

### General Mappings

GenericToFeatureMembership\_Mapping

### Mapping Source

Element

### Mapping Target

ParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ParameterMembership::ownedRelatedElement () : Element [0..*]`  
`Set{self.ownedMemberParameter () }`
- `ParameterMembership::ownedMemberParameter () : Feature [1]`  
`null`

## 7.6.3.33 GenericToPredicate\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *Predicate*.

### General Mappings

GenericToFunction\_Mapping

### Mapping Source

Element

### Mapping Target

Predicate

### Owned Mappings

(none)





### 7.6.3.34 GenericToRedefinition\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Redefinition*.

#### General Mappings

GenericToSubsetting\_Mapping

#### Mapping Source

Element

#### Mapping Target

Redefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefiningFeature () : Feature [1]`  
*abstract rule*
- `Redefinition::redefinedFeature () : Feature [1]`  
*abstract rule*

### 7.6.3.35 GenericToReferenceSubsetting\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *ReferenceSubsetting*.

#### General Mappings

GenericToSubsetting\_Mapping

#### Mapping Source

Element

#### Mapping Target

ReferenceSubsetting

#### Owned Mappings



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceSubsetting::referencedFeature () : Feature [1]`  
*abstract rule*

### 7.6.3.36 GenericToRelationship\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Relationship*.

#### General Mappings

GenericToElement\_Mapping

#### Mapping Source

Element

#### Mapping Target

Relationship

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Relationship::target () : Element [0..*]`  
`Set {}`
- `Relationship::ownedRelatedElement () : Element [0..*]`  
`Set {}`
- `Relationship::source () : Element [0..*]`  
`Set {}`



### 7.6.3.37 GenericToReturnParameterMembership\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *ReturnParameterMembership*.

#### General Mappings

GenericToParameterMembership\_Mapping

#### Mapping Source

Element

#### Mapping Target

ReturnParameterMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReturnParameterMembership::isComposite (in src : Element) : Boolean [1]

returns "true" if the element provided as the actual parameter value can have a mapping to an instance of the type specified by the "to" attribute (i.e. can be used as a value for the "from" attribute)

false

### 7.6.3.38 GenericToSpecialization\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Specialization*.

#### General Mappings

GenericToRelationship\_Mapping

#### Mapping Source

Element

#### Mapping Target

Specialization



### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Specialization::general () : Type [1]  
*abstract rule*
- Specialization::specific () : Type [1]  
*abstract rule*

### 7.6.3.39 GenericToStep\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Step*.

#### General Mappings

GenericToFeature\_Mapping

#### Mapping Source

Element

#### Mapping Target

Step

#### Owned Mappings

(none)

### 7.6.3.40 GenericToSubclassification\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Subclassification*.

#### General Mappings

GenericToSpecialization\_Mapping

#### Mapping Source

Element

#### Mapping Target





Subclassification

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subclassification::subclassifier () : Classifier [1]  
null
- Subclassification::superclassifier () : Classifier [1]  
null

## 7.6.3.41 GenericToSubsetting\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *Subsetting*.

### General Mappings

GenericToSpecialization\_Mapping

### Mapping Source

Element

### Mapping Target

Subsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subsetting::ownedRelatedElement () : Element [0..\*]



Set{}

- Subsetting::subsettingFeature () : Feature [1]  
*abstract rule*
- Subsetting::subsettingFeature () : Feature [1]

from

#### 7.6.3.42 GenericToSuccession\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *Succession*.

##### General Mappings

GenericToConnector\_Mapping

##### Mapping Source

Element

##### Mapping Target

Succession

##### Owned Mappings

(none)

#### 7.6.3.43 GenericToSuccessionItemFlow\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *SuccessionItemFlow*.

##### General Mappings

GenericToSuccession\_Mapping

GenericToItemFlow\_Mapping

##### Mapping Source

Element

##### Mapping Target

SuccessionItemFlow

##### Owned Mappings

(none)

#### 7.6.3.44 GenericToTextualRepresentation\_Mapping

##### Description



Generic mapping class for mappings to the SysML v2 element *TextualRepresentation*.

### General Mappings

GenericToAnnotatingElement\_Mapping

### Mapping Source

Element

### Mapping Target

TextualRepresentation

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TextualRepresentation::language () : String [1]  
*abstract rule*
- TextualRepresentation::body () : String [1]  
*abstract rule*

### 7.6.3.45 GenericToType\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *Type*.

### General Mappings

GenericToNamespace\_Mapping

### Mapping Source

Element

### Mapping Target

Type

### Owned Mappings

(none)

### Applicable filters



(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Type::isAbstract () : Boolean [1]`  
`false`
- `Type::isSufficient () : Boolean [1]`  
`false`

### 7.6.3.46 GenericToTypeFeaturing\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *TypeFeaturing*.

#### General Mappings

GenericToRelationship\_Mapping

#### Mapping Source

Element

#### Mapping Target

TypeFeaturing

#### Owned Mappings

(none)

#### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TypeFeaturing::featuringType () : Type [1]`  
*abstract rule*
- `TypeFeaturing::featureOfType () : Feature [1]`  
*abstract rule*

## 7.6.4 Generic Mappings to Systems

### 7.6.4.1 GenericToActionUsage\_Mapping

#### Description





Generic mapping class for mappings to the SysML v2 element *ActionUsage*.

### General Mappings

GenericToUsage\_Mapping

GenericToStep\_Mapping

### Mapping Source

Element

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::isComposite () : Boolean [1]

true

## 7.6.4.2 GenericToActorMembership\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *ActorMembership*.

### General Mappings

GenericToParameterMembership\_Mapping

### Mapping Source

Element

### Mapping Target

ActorMembership

### Owned Mappings

(none)



### 7.6.4.3 GenericToAssignmentActionUsage\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *AssignmentActionUsage*.

#### General Mappings

GenericToActionUsage\_Mapping

#### Mapping Source

Element

#### Mapping Target

AssignmentActionUsage

#### Owned Mappings

(none)

### 7.6.4.4 GenericToConnectionUsage\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *ConnectionUsage*.

#### General Mappings

GenericToPartUsage\_Mapping

#### Mapping Source

Element

#### Mapping Target

ConnectionUsage

#### Owned Mappings

(none)

### 7.6.4.5 GenericToConjugatedPortDefinition\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *ConjugatedPortDefinition*.

#### General Mappings

GenericToPortDefinition\_Mapping

#### Mapping Source



Element

### Mapping Target

ConjugatedPortDefinition

### Owned Mappings

(none)

## 7.6.4.6 GenericToConjugatedPortTyping\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *ConjugatedPortTyping*.

### General Mappings

GenericToFeatureTyping\_Mapping

### Mapping Source

Element

### Mapping Target

ConjugatedPortTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConjugatedPortTyping::conjugatedPortDefinition () : ConjugatedPortDefinition [1]  
*abstract rule*
- ConjugatedPortTyping::portDefinition () : PortDefinition [1]  
*abstract rule*

## 7.6.4.7 GenericToConstraintDefinition\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *ConstraintDefinition*.

### General Mappings

GenericToDefinition\_Mapping



### Mapping Source

Element

### Mapping Target

ConstraintDefinition

### Owned Mappings

(none)

## 7.6.4.8 GenericToConstraintUsage\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *ConstraintUsage*.

### General Mappings

GenericToUsage\_Mapping

### Mapping Source

Element

### Mapping Target

ConstraintUsage

### Owned Mappings

(none)

## 7.6.4.9 GenericToDefinition\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *Definition*.

### General Mappings

GenericToClassifier\_Mapping

### Mapping Source

Element

### Mapping Target

Definition

### Owned Mappings

(none)





### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Definition::isVariation () : Boolean [1]  
`false`

#### 7.6.4.10 GenericToEventOccurrenceUsage\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *EventOccurrenceUsage*.

##### General Mappings

GenericToOccurrenceUsage\_Mapping

##### Mapping Source

Element

##### Mapping Target

EventOccurrenceUsage

##### Owned Mappings

(none)

#### 7.6.4.11 GenericToItemDefinition\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *ItemDefinition*.

##### General Mappings

GenericToDefinition\_Mapping

##### Mapping Source

Element

##### Mapping Target

ItemDefinition

##### Owned Mappings

(none)



#### 7.6.4.12 GenericToItemUsage

##### Description

Generic mapping class for mappings to the SysML v2 element *ItemUsage*.

##### General Mappings

GenericToOccurrenceUsage\_Mapping

##### Mapping Source

Element

##### Mapping Target

ItemUsage

##### Owned Mappings

(none)

#### 7.6.4.13 GenericToMetadataUsage\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *MetadataUsage*.

##### General Mappings

GenericToUsage\_Mapping

##### Mapping Source

Element

##### Mapping Target

MetadataUsage

##### Owned Mappings

(none)

#### 7.6.4.14 GenericToObjectiveMembership\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *ObjectiveMembership*.

##### General Mappings

GenericToFeatureMembership\_Mapping

##### Mapping Source



Element

### Mapping Target

ObjectiveMembership

### Owned Mappings

(none)

## 7.6.4.15 GenericToOccurrenceDefinition\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *OccurrenceDefinition*.

### General Mappings

GenericToDefinition\_Mapping

### Mapping Source

Element

### Mapping Target

OccurrenceDefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OccurrenceDefinition::isIndividual () : Boolean [1]`  
`false`

## 7.6.4.16 GenericToOccurrenceUsage\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *OccurrenceUsage*.

### General Mappings

GenericToUsage\_Mapping

### Mapping Source



Element

### Mapping Target

OccurrenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OccurrenceUsage::isIndividual () : Boolean [1]  
false
- OccurrenceUsage::portionKind () : PortionKind [1]  
invalid

## 7.6.4.17 GenericToPartUsage\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *PartUsage*.

### General Mappings

GenericToUsage\_Mapping

### Mapping Source

Element

### Mapping Target

PartUsage

### Owned Mappings

(none)

## 7.6.4.18 GenericToPortConjugation\_Mapping

### Description

Generic mapping class for mappings to the SysML v2 element *PortConjugation*.

### General Mappings





GenericToConjugation\_Mapping

#### Mapping Source

Element

#### Mapping Target

PortConjugation

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PortConjugation::originalPortDefinition () : PortDefinition [1]  
*abstract rule*

### 7.6.4.19 GenericToPortDefinition\_Mapping

#### Description

Generic mapping class for mappings to the SysML v2 element *PortDefinition*.

#### General Mappings

GenericToDefinition\_Mapping

#### Mapping Source

Element

#### Mapping Target

PortDefinition

#### Owned Mappings

(none)

### 7.6.4.20 GenericToReferenceUsage\_Mapping

#### Description

Provides the basic features to map to a ReferenceUsage element.

#### General Mappings



GenericToUsage\_Mapping

**Mapping Source**

Element

**Mapping Target**

ReferenceUsage

**Owned Mappings**

(none)

**7.6.4.21 GenericToRequirementUsage\_Mapping**

**Description**

Generic mapping class for mappings to the SysML v2 element *RequirementUsage*.

**General Mappings**

GenericToUsage\_Mapping

**Mapping Source**

Element

**Mapping Target**

RequirementUsage

**Owned Mappings**

(none)

**7.6.4.22 GenericToStateUsage\_Mapping**

**Description**

Generic mapping class for mappings to the SysML v2 element *StateUsage*.

**General Mappings**

GenericToActionUsage\_Mapping

**Mapping Source**

Element

**Mapping Target**

StateUsage

**Owned Mappings**



(none)

#### 7.6.4.23 GenericToSubjectMembership\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *SubjectMembership*.

##### General Mappings

GenericToParameterMembership\_Mapping

##### Mapping Source

Element

##### Mapping Target

SubjectMembership

##### Owned Mappings

(none)

#### 7.6.4.24 GenericToTransitionUsage\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *TransitionUsage*.

##### General Mappings

GenericToActionUsage\_Mapping

##### Mapping Source

Element

##### Mapping Target

TransitionUsage

##### Owned Mappings

(none)

#### 7.6.4.25 GenericToUsage\_Mapping

##### Description

Generic mapping class for mappings to the SysML v2 element *Usage*.

##### General Mappings

GenericToFeature\_Mapping



## Mapping Source

Element

## Mapping Target

Usage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Usage::isVariation () : Boolean [1]

false

## 7.7 Mappings from UML4SysML metaclasses

### 7.7.1 Overview

UML4SysML is the subset of UML containing all model elements that are reused by SysML. The complete list of model elements is defined in [SysMLv1], subclause 4.1.

### 7.7.2 Actions

This chapter lists all mapping specifications of UML4SysML::Actions model elements.

#### 7.7.2.1 Overview

Table 1. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
AcceptCallAction	AcceptActionUsage
AcceptEventAction	AcceptActionUsage
ActionInputPin	ReferenceUsage
AddStructuralFeatureValueAction	ActionUsage
AddVariableValueAction	ActionUsage
BroadcastSignalAction	ActionUsage
CallBehaviorAction	ActionUsage
CallOperationAction	ActionUsage
Clause	not mapped; see next section





SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
ClearAssociationAction	ActionUsage
ClearStructuralFeatureAction	ActionUsage
ClearVariableAction	ActionUsage
ConditionalNode	not mapped; see next section
CreateLinkAction	ActionUsage
CreateLinkObjectAction	ActionUsage
CreateObjectAction	ActionUsage
DestroyLinkAction	ActionUsage
DestroyObjectAction	ActionUsage
InputPin	not mapped; see next section
LinkEndCreationData	not mapped; see next section
LinkEndData	not mapped; see next section
LinkEndDestructionData	not mapped; see next section
LoopNode	ActionUsage
OpaqueAction	ActionUsage
OutputPin	ReferenceUsage
RaiseExceptionAction	ActionUsage
ReadExtentAction	ActionUsage
ReadIsClassifiedObjectAction	ActionUsage
ReadLinkAction	ActionUsage
ReadLinkObjectEndAction	ActionUsage
ReadSelfAction	ActionUsage
ReadStructuralFeatureAction	ActionUsage
ReadVariableAction	ActionUsage
ReclassifyObjectAction	ActionUsage
ReduceAction	ActionUsage
RemoveStructuralFeatureValueAction	ActionUsage
RemoveVariableValueAction	ActionUsage
ReplyAction	ActionUsage
SendObjectAction	ActionUsage
SendSignalAction	ActionUsage
SequenceNode	ActionUsage
StartClassifierBehaviorAction	ActionUsage



SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
StartObjectBehaviorAction	ActionUsage
StructuredActivityNode	ActionUsage
TestIdentityAction	CalculationUsage
UnmarshallAction	ActionUsage
ValuePin	ReferenceUsage
ValueSpecificationAction	ActionUsage

The following table gives an overview of which SysML v2 elements the UML4SysML::Actions elements are transformed with which mapping class. The mapping details are in [7.7.2.3](#).

The justifications for the elements without mapping are given in [7.7.2.2](#).

### 7.7.2.2 UML4SysML::Actions elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 2. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
AcceptCallAction	Since the CallEvent is not supported by SysML v2, the AcceptCallAction is also not covered. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.
ActionInputPin	The UML4SysML::ActionInputPin concept is not covered by SysML v2. The model element is mapped as a input or output pin, but without the special action input pin semantics.
Clause	Mapping is not specified yet.
ConditionalNode	Mapping is not specified yet.
LinkEndCreationData	Mapping is not specified yet.
LinkEndData	Mapping is not specified yet.
LinkEndDestructionData	Mapping is not specified yet.
ReclassifyObjectAction	The UML4SysML::ReclassifyObjectAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.
ReplyAction	The UML4SysML::ReplyAction is only used with UML4SysML::AcceptCallAction. Since we have no mapping of AcceptCallAction to SysML v2, there is also no mapping for ReplyAction. However, it is mapped to an empty action usage to keep the connections within the activity respectively action definition.



<b>SysML v1 Concept</b>	<b>Rationale</b>
StartClassifierBehaviorAction	The UML4SysML::StartClassifierBehaviorAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.
StartObjectBehaviorAction	The UML4SysML::StartObjectBehaviorAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.
UnmarshallAction	Mapping is not specified yet.

### 7.7.2.3 Mapping Specifications

#### 7.7.2.3.1 Accept Event Actions

##### 7.7.2.3.1.1 AcceptCallAction\_Mapping

###### Description

Since the CallEvent is not supported by SysML v2, the AcceptCallAction is also not covered. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.

###### General Mappings

AcceptEventAction\_Mapping

###### Mapping Source

AcceptCallAction

###### Mapping Target

AcceptActionUsage

###### Owned Mappings

(none)

##### 7.7.2.3.1.2 AcceptEventAction\_Mapping

###### Description

The UML4SysML::AcceptEventAction is mapped to a AcceptActionUsage element.

If the trigger is a signal, it is mapped to an accept parameter typed by the signal.

SysMLv2 does not support more than one trigger. Therefore only the first specified trigger of the action is transformed. All further triggers are ignored.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action acceptEventActionSignalEvent1 accept : SysMLv1Signal via sysMLv1Port;
action acceptEventActionChangeEvent1 accept when when changeExpression.result {
    calc changeExpression {

```



```

        return : ScalarValues::Boolean;
        language "OCL"
            /*
             * x > 0
             */
        }
    }
}

```

## General Mappings

CommonAction\_Mapping

## Mapping Source

AcceptEventAction

## Mapping Target

AcceptActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- AcceptActionUsage::ownedRelationship () : Relationship [0..\*]

```

let relationships : Set(KerML::Relationship) = Helper.actionOwnedRelationship(from)
->including(AEAReceiverParameterMembership_Mapping.getMapped(from)) in
let relationshipsWithParameter : Set(KerML::Relationship) =
if (from.trigger.get(0).event.ocIsTypeOf(UML::SignalEvent) or
    from.trigger.get(0).event.ocIsTypeOf(UML::ChangeEvent)) then
    relationships->including(AEAParameterMembership_Mapping.getMapped(from))
else
    relationships
endif in
if from.trigger.get(0).event.ocIsTypeOf(UML::ChangeEvent) then
    relationshipsWithParameter
    ->including(ElementFeatureMembership_Mapping.getMapped(
        from.trigger.get(0).event.ocAsType(UML::ChangeEvent).changeExpression))
else relationshipsWithParameter
endif

```

### 7.7.2.3.1.3 AEChangeExpressionMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.



## General Mappings

CommonAction\_Mapping

## Mapping Source

AcceptEventAction

## Mapping Target

AcceptActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- AcceptActionUsage::ownedRelationship () : Relationship [0..\*]

```
let relationships : Set(KerML::Relationship) = Helper.actionOwnedRelationship(from)
->including(AEAReceiverParameterMembership_Mapping.getMapped(from)) in
let relationshipsWithParameter : Set(KerML::Relationship) =
if (from.trigger.get(0).event.ocIsTypeOf(UML::SignalEvent) or
    from.trigger.get(0).event.ocIsTypeOf(UML::ChangeEvent)) then
    relationships->including(AEAParameterMembership_Mapping.getMapped(from))
else
    relationships
endif in
if from.trigger.get(0).event.ocIsTypeOf(UML::ChangeEvent) then
    relationshipsWithParameter
    ->including(ElementFeatureMembership_Mapping.getMapped(
        from.trigger.get(0).event.ocAsType(UML::ChangeEvent).changeExpression))
else relationshipsWithParameter
endif
```

### 7.7.2.3.1.3 AEChangeExpressionMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## General Mappings

GenericToFeatureMembership\_Mapping

### Mapping Source

AcceptEventAction

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`from.trigger.get(0).event.oclassType(UML::ChangeEvent).changeExpression`

#### 7.7.2.3.1.4 AEChangeParameter\_Mapping

### Description

The mapping class transforms the change event specified at the AcceptEventAction.

## General Mappings

GenericToReferenceUsage\_Mapping

### Mapping Source

AcceptEventAction

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

**Mapping Source**

AcceptEventAction

**Mapping Target**

FeatureMembership

**Owned Mappings**

(none)

**Applicable filters**

(none)

**Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`from.trigger.get(0).event.oclassType(UML::ChangeEvent).changeExpression`

**7.7.2.3.1.4 AEChangeParameter\_Mapping****[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)****Description**

The mapping class transforms the change event specified at the AcceptEventAction.

**General Mappings**

ToReferenceUsage\_Init  
Mapping

**Mapping Source**

AcceptEventAction

**Mapping Target**

ReferenceUsage

**Owned Mappings**

(none)

**Applicable filters**

(none)

**Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

`KerML::FeatureDirectionKind::_in'`

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

`Set{AEChangeParameterFeatureValue_Mapping.getMapped(from)}`

#### 7.7.2.3.1.5 AEChangeParameterFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

`AEChangeParameterTrigger_Mapping.getMapped(from)`

#### 7.7.2.3.1.6 AEChangeParameterTrigger\_Mapping

##### Description

The mapping class creates a TriggerInvocationExpression from the change event specified at the AcceptEventAction.

##### General Mappings

**Generic**ToInvocationExpression\_Mapping

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_in'`
- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{AEChangeParameterFeatureValue_Mapping.getMapped(from) }`

#### 7.7.2.3.1.5 AEChangeParameterFeatureValue\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

###### Description

Creates a feature value relationship.

###### General Mappings

ToFeatureValue\_Init  
Mapping

###### Mapping Source

AcceptEventAction

###### Mapping Target

FeatureValue

###### Owned Mappings

(none)

###### Applicable filters

(none)

###### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`AEChangeParameterTrigger_Mapping.getMapped(from)`

#### 7.7.2.3.1.6 AEChangeParameterTrigger\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

###### Description

The mapping class creates a TriggerInvocationExpression from the change event specified at the AcceptEventAction.

### Mapping Source

AcceptEventAction

### Mapping Target

TriggerInvocationExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TriggerInvocationExpression::ownedRelationship () : Relationship [0..\*]  
`Set { AEChangeParameterFeatureMembership_Mapping.getMapped (from) }`

#### 7.7.2.3.1.7 AEChangeParameterTriggerExpression\_Mapping

### Description

The mapping class creates the trigger expression element for the change parameter of the SysML v2 AcceptActionUsage element.

### General Mappings

GenericToExpression\_Mapping

### Mapping Source

AcceptEventAction

### Mapping Target

Expression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

## General Mappings

ToInvocationExpression\_Init  
Mapping

## Mapping Source

AcceptEventAction

## Mapping Target

TriggerInvocationExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TriggerInvocationExpression::ownedRelationship () : Relationship [0..\*]  
`Set{AEChangeParameterFeatureMembership_Mapping.getMapped(from) }`

### 7.7.2.3.1.7 AEChangeParameterTriggerExpression\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

## Description

The mapping class creates the trigger expression element for the change parameter of the SysML v2 AcceptActionUsage element.

## General Mappings

ToExpression\_Init  
Mapping

## Mapping Source

AcceptEventAction

## Mapping Target

Expression

## Owned Mappings

(none)

## Applicable filters

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Expression::ownedRelationship () : Relationship [0..*]`

```
Set{AEChangeParameterResultExpressionMembership_Mapping.getMapped(from)}
```

#### 7.7.2.3.1.8 AEChangeParameterResultExpressionMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

ResultExpressionMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ResultExpressionMembership::ownedMemberFeature () : Feature [1]`

```
AEChangeParameterFeatureChainExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.1.9 AEChangeParameterFeatureChainExpression\_Mapping

##### Description

The mapping class creates the feature chain expression element for the change parameter of the SysML v2 `AcceptActionUsage` element.

##### General Mappings

**Generic**ToInvocationExpression\_Mapping

##### Mapping Source

AcceptEventAction



(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Expression::ownedRelationship () : Relationship [0..\*]

```
Set{AEChangeParameterResultExpressionMembership_Mapping.getMapped(from) }
```

#### 7.7.2.3.1.8 AEChangeParameterResultExpressionMembership\_Mapping

### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

AcceptEventAction

#### Mapping Target

ResultExpressionMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ResultExpressionMembership::ownedMemberFeature () : Feature [1]

```
AEChangeParameterFeatureChainExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.1.9 AEChangeParameterFeatureChainExpression\_Mapping

### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

#### Description

The mapping class creates the feature chain expression element for the change parameter of the SysML v2 AcceptActionUsage element.

## Mapping Target

FeatureChainExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChainExpression::ownedRelationship () : Relationship [0..\*]

```
Set { AEChangeParameterParameterMembership_Mapping.getMapped (from) }
```

### 7.7.2.3.1.10 AEChangeParameterFeature\_Mapping

#### Description

The mapping class creates the feature for the feature chain expression element for the change parameter of the SysML v2 AcceptActionUsage element.

#### General Mappings

**Generic**ToFeature\_Mapping

#### Mapping Source

AcceptEventAction

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
Set { AEChangeParameterExpressionFeatureValue_Mapping.getMapped (from) }
```

## General Mappings

ToInvocationExpression\_Init  
Mapping

## Mapping Source

AcceptEventAction

## Mapping Target

FeatureChainExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChainExpression::ownedRelationship () : Relationship [0..\*]  
`Set{AEChangeParameterParameterMembership_Mapping.getMapped(from) }`

### 7.7.2.3.1.10 AEChangeParameterFeatureMembership\_Mapping

**SYSML2 -370: Mapping class description AEChangeParameterFeatureMembership\_Mapping is missing**

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

AcceptEventAction

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

#### 7.7.2.3.1.11 AEChangeParameterExpressionFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

GenericToFeatureValue\_Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
AEChangeParameterFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.1.12 AEChangeParameterFeatureReferenceExpression\_Mapping

##### Description

The mapping class creates the feature reference expression for the feature chain expression element for the change parameter of the SysML v2 AcceptActionUsage element.

##### General Mappings

GenericToFeatureReferenceExpression\_Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

FeatureReferenceExpression

##### Owned Mappings

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`AEChangeParameterTriggerExpression_Mapping.getMapped(from)`

#### 7.7.2.3.1.11 AEChangeParameterFeature\_Mapping

### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

The mapping class creates the feature for the feature chain expression element for the change parameter of the SysML v2 AcceptActionUsage element.

#### General Mappings

ToFeature `_Init`  
Mapping

#### Mapping Source

AcceptEventAction

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set{AEChangeParameterExpressionFeatureValue_Mapping.getMapped(from) }`

#### 7.7.2.3.1.12 AEChangeParameterExpressionFeatureValue\_Mapping

### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature value relationship.



## General Mappings

ToFeatureValue\_Init  
Mapping

## Mapping Source

AcceptEventAction

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

`AEChangeParameterFeatureReferenceExpression_Mapping.getMapped(from)`

### 7.7.2.3.1.13 AEChangeParameterFeatureReferenceExpression\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

## Description

The mapping class creates the feature reference expression for the feature chain expression element for the change parameter of the SysML v2 AcceptActionUsage element.

## General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

## Mapping Source

AcceptEventAction

## Mapping Target

FeatureReferenceExpression

## Owned Mappings

(none)

## Applicable filters

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`  
`Set { AEChangeParameterMembership_Mapping.getMapped (from) }`

#### 7.7.2.3.1.13 AEChangeParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToMembership\_Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

Membership

##### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`  
`from.trigger.get (0) .event.oclassType (UML::ChangeEvent) .changeExpression`

#### 7.7.2.3.1.14 AEChangeParameterParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings



(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`  
`Set{AEChangeParameterMembership_Mapping.getMapped(from) }`

#### 7.7.2.3.1.14 AEChangeParameterMembership\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

AcceptEventAction

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`  
`from.trigger.get(0).event.oclassType(UML::ChangeEvent).changeExpression`

#### 7.7.2.3.1.15 AEChangeParameterParameterMembership\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a membership relationship for *memberElement()*.

GenericToParameterMembership\_Mapping

#### Mapping Source

AcceptEventAction

#### Mapping Target

ParameterMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`AEChangeParameterFeature_Mapping.getMapped (from)`

### 7.7.2.3.1.15 AEAReceiverParameter\_Mapping

#### Description

The mapping class creates the reference usage element for the receiver parameter of the SysML v2 AcceptActionUsage element.

#### General Mappings

GenericToReferenceUsage\_Mapping

#### Mapping Source

AcceptEventAction

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

## General Mappings

ToParameterMembership\_Init  
Mapping

### Mapping Source

AcceptEventAction

### Mapping Target

ParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`AEChangeParameterFeature_Mapping.getMapped (from)`

#### 7.7.2.3.1.16 AEARReceiverParameter\_Mapping

### **SysML2 -220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the reference usage element for the receiver parameter of the SysML v2 AcceptActionUsage element.

## General Mappings

ToReferenceUsage\_Init  
Mapping

### Mapping Source

AcceptEventAction

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`

```
KerML::FeatureDirectionKind:: '_in'
```

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
if from.trigger.get(0).port->size() > 0
then Set{AEARReceiverFeatureValue_Mapping.getMapped(from)}
else Set{}
endif
```

#### 7.7.2.3.1.16 AEARReceiverParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

`GenericToParameterMembership_Mapping`

##### Mapping Source

AcceptEventAction

##### Mapping Target

ParameterMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ParameterMembership::ownedMemberParameter () : Feature [1]`

```
AEARReceiverParameter_Mapping.getMapped(from)
```

#### 7.7.2.3.1.17 AEARReceiverFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
if from.trigger.get(0).port->size() > 0
then Set{AEARceiverFeatureValue_Mapping.getMapped(from)}
else Set{}
endif
```

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`

```
KerML::FeatureDirectionKind::_in'
```

#### 7.7.2.3.1.17 AEAReceiverParameterMembership\_Mapping

### **SysML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToParameterMembership\_**Init**  
Mapping

#### Mapping Source

AcceptEventAction

#### Mapping Target

ParameterMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ParameterMembership::ownedMemberParameter () : Feature [1]`

```
AEARceiverParameter_Mapping.getMapped(from)
```

## GenericToFeatureValue\_Mapping

### Mapping Source

AcceptEventAction

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
AEARceiverFeatureReferenceExpression_Mapping.getMapped(from)
```

## 7.7.2.3.1.18 AEASignalParameter\_Mapping

### Description

The mapping class creates the reference usage element for the signal parameter of the SysML v2 AcceptActionUsage element.

### General Mappings

## GenericToReferenceUsage\_Mapping

### Mapping Source

AcceptEventAction

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

#### 7.7.2.3.1.18 AEAReceiverFeatureValue\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature value relationship.

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
AEAReceiverFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.1.19 AEASignalParameter\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates the reference usage element for the signal parameter of the SysML v2 AcceptActionUsage element.

##### General Mappings

ToReferenceUsage\_Init  
Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_in'`
- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{AEASignalParameterFeatureTyping_Mapping.getMapped(from) }`

#### 7.7.2.3.1.19 AEASignalParameterFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

`GenericToFeatureTyping_Mapping`

##### Mapping Source

`AcceptEventAction`

##### Mapping Target

`FeatureTyping`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  

```

let event : UML::Event = from.trigger.get(0).event in
if event.ocIsTypeOf(UML::SignalEvent) then
    event.ocAsType(UML::SignalEvent).signal
else invalid endif

```

#### 7.7.2.3.1.20 AEAParameterMembership\_Mapping

##### Description

The mapping class creates the parameter membership relationship for the element that can be received by the accept action. The source of the element is the trigger of the `UML4SysML::AcceptEventAction`.

Currently, more than one trigger is not supported by the transformation.



ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
`Set{AEASignalParameterFeatureTyping_Mapping.getMapped(from) }`
- ReferenceUsage::direction () : FeatureDirectionKind [0..1]  
`KerML::FeatureDirectionKind::_in'`

#### 7.7.2.3.1.20 AEASignalParameterFeatureTyping\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

AcceptEventAction

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

## General Mappings

GenericToParameterMembership\_Mapping

## Mapping Source

AcceptEventAction

## Mapping Target

ParameterMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  

```
if from.trigger.get(0).event.ocIsTypeOf(UML::SignalEvent) then
    AEASignalParameter_Mapping.getMapped(from)
else if from.trigger.get(0).event.ocIsTypeOf(UML::ChangeEvent) then
    AEASignalParameter_Mapping.getMapped(from)
else
    invalid
endif endif
```

### 7.7.2.3.1.21 AEASignalParameter\_Mapping

#### Description

The mapping class creates the feature reference expression for the reference usage element for the receiver parameter of the SysML v2 AcceptActionUsage element.

## General Mappings

GenericToFeatureReferenceExpression\_Mapping

## Mapping Source

AcceptEventAction

## Mapping Target

FeatureReferenceExpression

## Owned Mappings

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
let event : UML::Event = from.trigger.get(0).event in
if event.ocIsTypeOf(UML::SignalEvent) then
    event.ocAsType(UML::SignalEvent).signal
else invalid endif
```

#### 7.7.2.3.1.21 AEAPParameterMembership\_Mapping

##### **SYSML2 -220: Replace Generic mapping classes by Initializers**

###### **Description**

The mapping class creates the parameter membership relationship for the element that can be received by the accept action. The source of the element is the trigger of the UML4SysML::AcceptEventAction.

Currently, more than one trigger is not supported by the transformation.

###### **General Mappings**

ToParameterMembership\_Init  
Mapping

###### **Mapping Source**

AcceptEventAction

###### **Mapping Target**

ParameterMembership

###### **Owned Mappings**

(none)

###### **Applicable filters**

(none)

###### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]

```
if from.trigger.get(0).event.ocIsTypeOf(UML::SignalEvent) then
    AEASignalParameter_Mapping.getMapped(from)
else if from.trigger.get(0).event.ocIsTypeOf(UML::ChangeEvent) then
    AEASignalParameter_Mapping.getMapped(from)
else
    invalid
endif endif
```

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set { AEAReceiverFeatureReferenceExpressionMembership_Mapping.getMapped (from) ,  
ReturnParameterFeatureMembership_Factory.create () }
```

#### 7.7.2.3.1.22 AEAReceiverFeatureReferenceExpressionMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic**ToMembership\_Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

Membership

##### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`

```
if from.trigger.get (0) .port->size () > 0 then  
    from.trigger.get (0) .port.get (0)  
else  
    invalid  
endif
```

#### 7.7.2.3.1.22 AEAReceiverFeatureReferenceExpression\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

##### Description

The mapping class creates the feature reference expression for the reference usage element for the receiver parameter of the SysML v2 AcceptActionUsage element.

##### General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

FeatureReferenceExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{AEAReceiverFeatureReferenceExpressionMembership_Mapping.getMapped(from) ,  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.1.23 AEAReceiverFeatureReferenceExpressionMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToMembership\_Init  
Mapping

##### Mapping Source

AcceptEventAction

#### 7.7.2.3.1.23 ReplyAction\_Mapping

##### Description

The UML4SysML::ReplyAction is only used with UML4SysML::AcceptCallAction. Since we have no mapping of AcceptCallAction to SysML v2, there is also no mapping for ReplyAction. However, it is mapped to an empty action usage to keep the connections within the activity respectively action definition.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

ReplyAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

#### 7.7.2.3.1.24 UnmarshallAction\_Mapping

##### Description

The mapping of UML4SysML::UnmarshallAction is not specified yet. It is currently mapped to an empty action usage to keep the connections within the activity respectively action definition.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

UnmarshallAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

#### 7.7.2.3.2 Actions

##### 7.7.2.3.2.1 CommonAction\_Mapping

##### Description

Base mapping class for model elements of kind UML4SysML::Action. The target element is a SysML v2 ActionUsage.

##### General Mappings

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  

```
if from.trigger.get(0).port->size() > 0 then
    from.trigger.get(0).port.get(0)
else
    invalid
endif
```

#### 7.7.2.3.1.24 ReplyAction\_Mapping

##### Description

The UML4SysML::ReplyAction is only used with UML4SysML::AcceptCallAction. Since we have no mapping of AcceptCallAction to SysML v2, there is also no mapping for ReplyAction. However, it is mapped to an empty action usage to keep the connections within the activity respectively action definition.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

ReplyAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.2.3.1.25 UnmarshallAction\_Mapping

##### Description

## GenericToActionUsage\_Mapping

### NamedElementMain\_Mapping

#### Mapping Source

Action

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
let actionInputPin: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsTypeOf(UML::ActionInputPin)) in
let triggers: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Trigger)) in
let toElementFMS: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - actionInputPin) - triggers) - from.ownedElement in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(self.ocAsType(ElementMain_Mapping).ownedRelationship())
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())
```

- ActionUsage::isComposite () : Boolean [1]

```
true
```

#### 7.7.2.3.2.2 OpaqueAction\_Mapping

##### Description

The UML4SysML::OpaqueAction is mapped to a SysML v2 ActionUsage with a textual representation.

The following shows an example of the expected SysMLv2 textual syntax of a UML4SysML::OpaqueAction.

```
action thisIsAOpaqueAction {
    in x : ScalarValues::Integer;
    in y : ScalarValues::Integer;
    out result : ScalarValues::Boolean;

    language "OCL"
```



The mapping of UML4SysML::UnmarshallAction is not specified yet. It is currently mapped to an empty action usage to keep the connections within the activity respectively action definition.

### General Mappings

CommonAction\_Mapping

### Mapping Source

UnmarshallAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

## 7.7.2.3.2 Actions

### 7.7.2.3.2.1 CommonAction\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Base mapping class for model elements of kind UML4SysML::Action. The target element is a SysML v2 ActionUsage.

### General Mappings

ToActionUsage\_Init  
NamedElementMain\_Mapping

### Mapping Source

Action

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

```

/*
 * x = y + 1;
 */
}

```

## General Mappings

CommonAction\_Mapping

## Mapping Source

OpaqueAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```

if from.body->size() > 0 then
  Helper.actionOwnedRelationship(from)->append(OABodyMembership_Mapping.getMapped(from))
else
  Helper.actionOwnedRelationship(from)
endif

```

### 7.7.2.3.2.3 OABody\_Mapping

#### Description

The languages and bodies of a UML4SysML::OpaqueAction are mapped to SysMLv2 TextualRepresentations.

## General Mappings

GenericToAnnotatingElement\_Mapping

## Mapping Source

OpaqueAction

## Mapping Target

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionUsage::ownedRelationship () : Relationship [0..*]`

```
let actionInputPin: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsTypeOf(UML::ActionInputPin)) in
let triggers: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Trigger)) in
let toElementFMS: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - actionInputPin) - triggers) - from.ownedElement in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(self.ocIsType(ElementMain_Mapping).ownedRelationship())
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())
```

- `ActionUsage::isComposite () : Boolean [1]`

```
true
```

#### 7.7.2.3.2.2 OpaqueAction\_Mapping

##### Description

The `UML4SysML::OpaqueAction` is mapped to a SysML v2 `ActionUsage` with a textual representation.

The following shows an example of the expected SysMLv2 textual syntax of a `UML4SysML::OpaqueAction`.

```
action thisIsAOpaqueAction {
    in x : ScalarValues::Integer;
    in y : ScalarValues::Integer;
    out result : ScalarValues::Boolean;

    language "OCL"
    /*
    * x = y + 1;
    */
}
```

##### General Mappings

`CommonAction_Mapping`

##### Mapping Source

`OpaqueAction`

##### Mapping Target

`ActionUsage`

##### Owned Mappings

(none)

##### Applicable filters

TextualRepresentation

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TextualRepresentation::body () : String [1]`  
`if from.body.notEmpty() then from.body.first() else invalid endif`
- `TextualRepresentation::language () : String [1]`  
`if from.language.notEmpty() then from.language.first() else invalid endif`

#### 7.7.2.3.2.4 OABodyMembership\_Mapping

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

`GenericToOwningMembership_Mapping`

### Mapping Source

OpaqueAction

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
if from.body->size() > 0 then
  Helper.actionOwnedRelationship(from)->append(OABodyMembership_Mapping.getMapped(from))
else
  Helper.actionOwnedRelationship(from)
endif
```

#### 7.7.2.3.2.3 OABody\_Mapping

### **SysML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

The languages and bodies of a UML4SysML::OpaqueAction are mapped to SysMLv2 TextualRepresentations.

#### General Mappings

ToAnnotatingElement\_Init  
Mapping

#### Mapping Source

OpaqueAction

#### Mapping Target

TextualRepresentation

#### Owned Mappings

(none)

#### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TextualRepresentation::language () : String [1]

```
if from.language.notEmpty() then from.language.first() else invalid endif
```

- TextualRepresentation::body () : String [1]

```
if from.body.notEmpty() then from.body.first() else invalid endif
```

```
OABody_Mapping.getMapped(from)
```

#### 7.7.2.3.2.5 Pin\_Mapping

##### Description

Mapping class for model elements of kind UML4SysML::Pin. The operation `ownedRelationship()` makes a distinction between typed and untyped pins. The target element is a SysMLv2 `ReferenceUsage`.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1Action {  
        in sysMLv1InputPin : ScalarValues::Integer;  
        out sysMLv1UntypedOutputPin;  
    }  
}
```

##### General Mappings

GenericToReferenceUsage\_Mapping

NamedElementMain\_Mapping

##### Mapping Source

Pin

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not Helper.excludedPin(src)
```

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
self.oclAsType (ElementMain_Mapping).ownedRelationship ()  
->including (MultiplicityMembership_Mapping.getMapped (from))
```
- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

#### 7.7.2.3.2.4 OABodyMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToOwningMembership\_Init  
Mapping

##### Mapping Source

OpaqueAction

##### Mapping Target

OwningMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

```
OABody_Mapping.getMapped (from)
```

#### 7.7.2.3.2.5 Pin\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Mapping class for model elements of kind UML4SysML::Pin. The operation ownedRelationship() makes a distinction between typed and untyped pins. The target element is a SysMLv2 ReferenceUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1Action {  
        in sysMLv1InputPin : ScalarValues::Integer;  
        out sysMLv1UntypedOutputPin;  
    }  
}
```

```

    if from.ocIsTypeOf(UML::InputPin) then
        KerML::FeatureDirectionKind::_in'
    else if from.ocIsTypeOf(UML::OutputPin) then
        KerML::FeatureDirectionKind::_out'
    else
        invalid
    endif endif

```

#### 7.7.2.3.2.6 ValuePin\_Mapping

##### Description

A UML4SysML::ValuePin is mapped to a SysML v2 ReferenceUsage with assigned value.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action sysMLv1Action {
    in sysMLv1ValuePin1 : ScalarValues::Integer = 42;
    in sysMLv1ValuePin2 = {
        return result;
        language "English"
        /*
         * this is a opaque expression
         */
    }.result;
}

```

##### General Mappings

No general mappings.

##### Mapping Source

ValuePin

##### Mapping Target

No target element.

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ownedRelationship () : Relationship [0..\*]



## General Mappings

ToReferenceUsage\_Init  
NamedElementMain\_Mapping

## Mapping Source

Pin

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not Helper.excludedPin(src)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

```
if from.ocIsTypeOf(UML::InputPin) then
  KerML::FeatureDirectionKind::_in'
else if from.ocIsTypeOf(UML::OutputPin) then
  KerML::FeatureDirectionKind::_out'
else
  invalid
endif endif
```

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
self.ocIsType(ElementMain_Mapping).ownedRelationship()
->including(MultiplicityMembership_Mapping.getMapped(from))
```

### 7.7.2.3.2.6 ValuePin\_Mapping

#### **SYSML2\_-372: ValuePin\_Mapping is not correctly specified**

## Description

A UML4SysML::ValuePin is mapped to a SysML v2 ReferenceUsage with assigned value.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action sysMLv1Action {
  in sysMLv1ValuePin1 : ScalarValues::Integer = 42;
```

```
Set{PinFeatureTyping_Mapping.getMapped(from),
ValuePinFeatureValue_Mapping.getMapped(from),
MultiplicityMembership_Mapping.getMapped(from)}
```

#### 7.7.2.3.2.7 ValuePinFeatureValue\_Mapping

##### Description

The mapping class creates the value expression for the reference usage element.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

##### Mapping Source

ValuePin

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  

```
if from.value.oclIsUndefined() then invalid else from.value endif
```

#### 7.7.2.3.2.8 ValuePinUntyped\_Mapping

##### Description

Same as ValuePin\_Mapping, but for UML4SysML::ValuePins without a specified type.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action sysMLv1Action {
    in sysMLv1ValuePin1 = 42;
}
```

##### General Mappings

Pin\_Mapping

```

        in sysMLv1ValuePin2 = {
            return result;
            language "English"
            /*
             * this is a opaque expression
             */
        }.result;
    }

```

## General Mappings

### Pin\_Mapping

#### Mapping Source

ValuePin

#### Mapping Target

### ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not Helper.excludedPin(src) and not src.type.ocliIsUndefined()
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **ReferenceUsage::ownedRelationship () : Relationship [0..\*]**  

```
Set{PinFeatureTyping_Mapping.getMapped(from),
ValuePinFeatureValue_Mapping.getMapped(from),
MultiplicityMembership_Mapping.getMapped(from)}
```

### 7.7.2.3.2.7 ValuePinFeatureValue\_Mapping

## **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the value expression for the reference usage element.

## General Mappings

ToFeatureValue\_**Init**  
Mapping

#### Mapping Source

## Mapping Source

ValuePin

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(Pin_Mapping).ownedRelationship()->including(ValuePinFeatureValue_Mapping.getM
```

### 7.7.2.3.3 Invocation Actions

#### 7.7.2.3.3.1 BroadcastSignalAction\_Mapping

##### Description

The UML4SysML::BroadcastSignalAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

BroadcastSignalAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

#### 7.7.2.3.3.2 CallBehaviorAction\_Mapping

##### Description

A UML4SysML::CallBehaviorAction is mapped to a SysML v2 ActionUsage.

ValuePin

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  

```
if from.value.oclIsUndefined() then invalid else from.value endif
```

#### 7.7.2.3.2.8 ValuePinUntyped\_Mapping

**SYSML2\_-372: ValuePin\_Mapping is not correctly specified**

### Description

Same as ValuePin\_Mapping, but for UML4SysML::ValuePins without a specified type.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action sysMLv1Action {  
    in sysMLv1ValuePin1 = 42;  
}
```

### General Mappings

Pin\_Mapping

### Mapping Source

ValuePin

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity1 {  
    action sysMLv1CallBehaviorAction : SysMLv1Activity2;  
}  
action def SysMLv1Activity2;
```

## General Mappings

CommonAction\_Mapping

## Mapping Source

CallBehaviorAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  

```
Helper.actionOwnedRelationship(from)  
->append(CBAFeatureTyping_Mapping.getMapped(from))
```

### 7.7.2.3.3 CBAFeatureTyping\_Mapping

## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

**Generic**ToFeatureTyping\_Mapping

## Mapping Source

CallBehaviorAction

## Mapping Target

FeatureTyping

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not Helper.excludedPin(src) and src.type.ocIsUndefined()
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(Pin_Mapping).ownedRelationship()->including(ValuePinFeatureValue_Mapping.getM
```

### 7.7.2.3.3 Invocation Actions

#### 7.7.2.3.3.1 BroadcastSignalAction\_Mapping

##### Description

The UML4SysML::BroadcastSignalAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

BroadcastSignalAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.2.3.3.2 CallBehaviorAction\_Mapping

##### Description

A UML4SysML::CallBehaviorAction is mapped to a SysML v2 ActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity1 {  
    action sysMLv1CallBehaviorAction : SysMLv1Activity2;  
}  
action def SysMLv1Activity2;
```

##### General Mappings

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`from.behavior`

### 7.7.2.3.3.4 CallOperationAction\_Mapping

#### Description

A `UML4SysML::CallOperationAction` is mapped to a SysML v2 `ActionUsage` which calls the operation.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action sysMLv1CallOperationAction {  
  in paramIn;  
  in target : ThisIsABlock;  
  out paramReturn = target.sysMLv1Operation;  
}
```

## General Mappings

`CommonAction_Mapping`

## Mapping Source

`CallOperationAction`

## Mapping Target

`ActionUsage`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules



CommonAction\_Mapping

#### Mapping Source

CallBehaviorAction

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  

```
Helper.actionOwnedRelationship (from)  
->append (CBAFeatureTyping_Mapping.getMapped (from) )
```

#### 7.7.2.3.3 CBAFeatureTyping\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

ToFeatureTyping\_Init  
Mapping

#### Mapping Source

CallBehaviorAction

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
Helper.actionOwnedRelationship (from)
->including (COAPerformActionFeatureMembership_Mapping.getMapped (from))
```

#### 7.7.2.3.3.5 COAOutputPinFeature\_Mapping

##### Description

The mapping class creates the feature element for the output parameter.

##### General Mappings

**Generic**ToFeature\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
Set { COAOutputPinFeatureFeatureValue_Mapping.getMapped (from) ,
COAOutputPinFeatureFeatureMembership_Mapping.getMapped (from) }
```

- Feature::direction () : FeatureDirectionKind [0..1]

```
KerML::FeatureDirectionKind::_in'
```

#### 7.7.2.3.3.6 COAOutputPinFeatureChainExpression\_Mapping

##### Description

The mapping class creates the feature chain expression for the output parameter feature value.

##### General Mappings

**Generic**ToInvocationExpression\_Mapping

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`from.behavior`

### 7.7.2.3.3.4 CallOperationAction\_Mapping

#### Description

A `UML4SysML::CallOperationAction` is mapped to a SysML v2 `ActionUsage` which calls the operation.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action sysMLv1CallOperationAction {  
  in paramIn;  
  in target : ThisIsABlock;  
  out paramReturn = target.sysMLv1Operation;  
}
```

#### General Mappings

`CommonAction_Mapping`

#### Mapping Source

`CallOperationAction`

#### Mapping Target

`ActionUsage`

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionUsage::ownedRelationship () : Relationship [0..*]`  
`Helper.actionOwnedRelationship(from)`  
`->including(COAPerformActionFeatureMembership_Mapping.getMapped(from))`

### 7.7.2.3.3.5 COAOutputPinFeature\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Mapping Source

OutputPin

## Mapping Target

FeatureChainExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChainExpression::ownedRelationship () : Relationship [0..\*]  

```
Set { COAOutputPinParameterMembership_Mapping.getMapped (from) ,  
COAOutputPinFeatureChainExpressionMembership_Mapping.getMapped (from) ,  
ReturnParameterFeatureMembership_Factory.create () }
```

### 7.7.2.3.3.7 COAOutputPinFeatureChainExpressionMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToMembership\_Mapping

## Mapping Source

OutputPin

## Mapping Target

Membership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

## Description

The mapping class creates the feature element for the output parameter.

## General Mappings

ToFeature\_Init  
Mapping

## Mapping Source

OutputPin

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  

```
Set { COAOutputPinFeatureFeatureValue_Mapping.getMapped (from) ,  
      COAOutputPinFeatureFeatureMembership_Mapping.getMapped (from) }
```
- Feature::direction () : FeatureDirectionKind [0..1]  

```
KerML::FeatureDirectionKind::_in'
```

### 7.7.2.3.3.6 COAOutputPinFeatureChainExpression\_Mapping

#### SYSML2\_-220: Replace Generic mapping classes by Initializers

## Description

The mapping class creates the feature chain expression for the output parameter feature value.

## General Mappings

ToInvocationExpression\_Init  
Mapping

## Mapping Source

OutputPin

## Mapping Target

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

```
from.owner.oclAsType(UML::CallOperationAction).operation
```

#### 7.7.2.3.3.8 COAOutputPinFeatureFeature\_Mapping

##### Description

Creates a feature element for the UML4SysML::CallOperationAction mapping.

##### General Mappings

GenericToFeature\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

Feature

##### Owned Mappings

(none)

#### 7.7.2.3.3.9 COAOutputPinFeatureFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

GenericToFeatureMembership\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

FeatureChainExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChainExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{COAOutputPinParameterMembership_Mapping.getMapped(from) ,  
COAOutputPinFeatureChainExpressionMembership_Mapping.getMapped(from) ,  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.3.7 COAOutputPinFeatureChainExpressionMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

OutputPin

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]





```
from.owner.oclAsType(UML::CallOperationAction).operation
```

#### 7.7.2.3.3.8 COAOutputPinFeatureFeature\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature element for the UML4SysML::CallOperationAction mapping.

##### General Mappings

ToFeature\_Init  
Mapping

##### Mapping Source

OutputPin

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.2.3.3.9 COAOutputPinFeatureFeatureMembership\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

OutputPin

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`COAOutputPinFeatureFeature_Mapping.getMapped(from)`

#### 7.7.2.3.3.10 COAOutputPinFeatureFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

`GenericToFeatureValue_Mapping`

##### Mapping Source

`OutputPin`

##### Mapping Target

`FeatureValue`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`COAOutputPinFeatureReferenceExpression_Mapping.getMapped(from)`

#### 7.7.2.3.3.11 COAOutputPinFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

`GenericToFeatureMembership_Mapping`

##### Mapping Source

`OutputPin`

##### Mapping Target

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`COAOutputPinFeatureFeature_Mapping.getMapped (from)`

#### 7.7.2.3.3.10 COAOutputPinFeatureFeatureValue\_Mapping

### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature value relationship.

#### General Mappings

ToFeatureValue\_Init  
Mapping

#### Mapping Source

OutputPin

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`COAOutputPinFeatureReferenceExpression_Mapping.getMapped (from)`

#### 7.7.2.3.3.11 COAOutputPinFeatureMembership\_Mapping

### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`COAOutputPinReferenceUsage_Mapping.getMapped(from)`

#### 7.7.2.3.3.12 COAOutputPinFeatureReferenceExpression\_Mapping

### Description

The mapping class creates the feature reference expression for the output parameter.

### General Mappings

**Generic**ToFeatureReferenceExpression\_Mapping

### Mapping Source

OutputPin

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  
`Set { COAOutputPinFeatureReferenceExpressionMembership_Mapping.getMapped(from) ,  
ReturnParameterFeatureMembership_Factory.create() }`

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

OutputPin

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`COAOutputPinReferenceUsage_Mapping.getMapped (from)`

### 7.7.2.3.3.12 COAOutputPinFeatureReferenceExpression\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

The mapping class creates the feature reference expression for the output parameter.

## General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

## Mapping Source

OutputPin

## Mapping Target

FeatureReferenceExpression

## Owned Mappings

(none)

## Applicable filters

#### 7.7.2.3.3.13 COAOutputPinFeatureReferenceExpressionMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToMembership\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

Membership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
`from.owner.oclAsType(UML::CallOperationAction).target`

#### 7.7.2.3.3.14 COAOutputPinParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToParameterMembership\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

ParameterMembership

##### Owned Mappings

(none)

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set{COAOutputPinFeatureReferenceExpressionMembership_Mapping.getMapped(from) ,  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.3.13 COAOutputPinFeatureReferenceExpressionMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

OutputPin

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`

```
from.owner.oclAsType(UML::CallOperationAction).target
```

#### 7.7.2.3.3.14 COAOutputPinParameterMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a membership relationship for *memberElement()*.

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::visibility () : VisibilityKind [1]  
`KerML::VisibilityKind::private`
- ParameterMembership::ownedMemberParameter () : Feature [1]  
`COAOutputPinFeature_Mapping.getMapped(from)`

### 7.7.2.3.3.15 COAOutputPinReferenceUsage\_Mapping

#### Description

Creates a reference usage.

#### General Mappings

**Generic**ToReferenceUsage\_Mapping

#### Mapping Source

OutputPin

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
`Set{COAOutputPinReferenceUsageFeatureValue_Mapping.getMapped(from)}`

### 7.7.2.3.3.16 COAOutputPinReferenceUsageFeatureValue\_Mapping

#### Description

Creates a feature value relationship.



## General Mappings

ToParameterMembership\_Init  
Mapping

## Mapping Source

OutputPin

## Mapping Target

ParameterMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::visibility () : VisibilityKind [1]  
`KerML::VisibilityKind::private`
- ParameterMembership::ownedMemberParameter () : Feature [1]  
`COAOutputPinFeature_Mapping.getMapped(from)`

### 7.7.2.3.3.15 COAOutputPinReferenceUsage\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a reference usage.

## General Mappings

ToReferenceUsage\_Init  
Mapping

## Mapping Source

OutputPin

## Mapping Target

ReferenceUsage

## Owned Mappings

## General Mappings

GenericToFeatureValue\_Mapping

## Mapping Source

OutputPin

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
COAOutputPinFeatureChainExpression_Mapping.getMapped(from)
```

### 7.7.2.3.3.17 COAPerformAction\_Mapping

## Description

The mapping class creates the PerformActionUsage element.

## General Mappings

GenericToActionUsage\_Mapping

## Mapping Source

CallOperationAction

## Mapping Target

PerformActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{COAOutputPinReferenceUsageFeatureValue_Mapping.getMapped(from) }
```

#### 7.7.2.3.3.16 COAOutputPinReferenceUsageFeatureValue\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_Init  
Mapping

### Mapping Source

OutputPin

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
COAOutputPinFeatureChainExpression_Mapping.getMapped(from)
```

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PerformActionUsage::ownedRelationship () : Relationship [0..*]`

```
Set { COAPerformActionReferenceSubsetting_Mapping.getMapped (from) }
```

#### 7.7.2.3.3.18 COAPerformActionFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToEndFeatureMembership\_Mapping

##### Mapping Source

CallOperationAction

##### Mapping Target

EndFeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`

```
COAPerformAction_Mapping.getMapped (from)
```

#### 7.7.2.3.3.19 COAPerformActionReferenceSubsetting\_Mapping

##### Description

Creates a subsetting relationship.

##### General Mappings

**Generic**ToReferenceSubsetting\_Mapping

##### Mapping Source

CallOperationAction

##### Mapping Target

#### 7.7.2.3.3.17 COAPerformAction\_Mapping

**[SYSML2 -136: Transformation of UML4SysML::State does not consider entry, do, and exit behavior](#)**

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates the PerformActionUsage element.

##### General Mappings

ToPerformActionUsage\_Init  
Mapping

##### Mapping Source

CallOperationAction

##### Mapping Target

PerformActionUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PerformActionUsage::ownedRelationship () : Relationship [0..\*]  
`Set{COAPerformActionReferenceSubsetting_Mapping.getMapped(from)}`

#### 7.7.2.3.3.18 COAPerformActionFeatureMembership\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToEndFeatureMembership\_Init  
Mapping

##### Mapping Source

CallOperationAction

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::ownedRelatedElement () : Element [0..\*]  
`Set { COAPerformActionFeature_Mapping.getMapped (from) }`

#### 7.7.2.3.3.20 COAPerformActionFeature\_Mapping

### Description

The mapping class creates the feature element for the perform action usage.

### General Mappings

**Generic**ToFeature\_Mapping

### Mapping Source

CallOperationAction

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  
`Set { COAPerformActionFeatureChainingTarget_Mapping.getMapped (from) ,  
COAPerformActionFeatureChainingOperation_Mapping.getMapped (from) }`

### Mapping Target

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`COAPerformAction_Mapping.getMapped (from)`

#### 7.7.2.3.3.19 COAPerformActionReferenceSubsetting\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a subsetting relationship.

### General Mappings

ToReferenceSubsetting\_Init  
Mapping

### Mapping Source

CallOperationAction

### Mapping Target

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::ownedRelatedElement () : Element [0..\*]

#### 7.7.2.3.3.21 COAPPerformActionFeatureChainingOperation\_Mapping

##### Description

The mapping class creates the feature chaining element for the operation of the perform action usage.

##### General Mappings

GenericToFeatureChaining\_Mapping

##### Mapping Source

CallOperationAction

##### Mapping Target

FeatureChaining

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]

from.operation

#### 7.7.2.3.3.22 COAPPerformActionFeatureChainingTarget\_Mapping

##### Description

The mapping class creates the feature chaining element for the target element of the perform action usage.

##### General Mappings

GenericToFeatureChaining\_Mapping

##### Mapping Source

CallOperationAction

##### Mapping Target

FeatureChaining

##### Owned Mappings

(none)



```
Set{COAPerformActionFeature_Mapping.getMapped(from) }
```

#### 7.7.2.3.3.20 COAPerformActionFeature\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

###### Description

The mapping class creates the feature element for the perform action usage.

###### General Mappings

ToFeature\_Init  
Mapping

###### Mapping Source

CallOperationAction

###### Mapping Target

Feature

###### Owned Mappings

(none)

###### Applicable filters

(none)

###### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
Set{COAPerformActionFeatureChainingTarget_Mapping.getMapped(from),  
COAPerformActionFeatureChainingOperation_Mapping.getMapped(from) }
```

#### 7.7.2.3.3.21 COAPerformActionFeatureChainingOperation\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

###### Description

The mapping class creates the feature chaining element for the operation of the perform action usage.

###### General Mappings

ToFeatureChaining\_Init  
Mapping

###### Mapping Source

CallOperationAction

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]  
`from.target`

### 7.7.2.3.3.23 SendObjectAction\_Mapping

#### Description

A UML4SysML::SendObjectAction is mapped to a SysMLv2 ActionUsage that includes a SendActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action sysMLv1SendObjectAction {  
    in target : SysMLv1Block;  
    send SysMLv1Object1() to target;  
}  
part def SysMLv1Block;  
item def SysMLv1Object;
```

## General Mappings

SendSignalAction\_Mapping

### Mapping Source

SendObjectAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### 7.7.2.3.3.24 SendSignalAction\_Mapping

#### Description

A UML4SysML::SendSignalAction is mapped to a SysMLv2 ActionUsage that includes a SendActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action sysMLv1SendSignalAction {  
    in target : SysMLv1Block;
```

### Mapping Target

FeatureChaining

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]  
`from.operation`

#### 7.7.2.3.3.22 COAPerformActionFeatureChainingTarget\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the feature chaining element for the target element of the perform action usage.

### General Mappings

ToFeatureChaining\_Init  
Mapping

### Mapping Source

CallOperationAction

### Mapping Target

FeatureChaining

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]

```

        send SysMLv1Signal() to target;
    }
    part def SysMLv1Block;
    item def SysMLv1Signal;

```

## General Mappings

CommonAction\_Mapping

## Mapping Source

SendSignalAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```

    Helper.actionOwnedRelationship(from)
    ->including(SSAFeatureMembership_Mapping.getMapped(from))

```

### 7.7.2.3.3.25 SSAFeatureMembership\_Mapping

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

**Generic**ToFeatureMembership\_Mapping

## Mapping Source

InvocationAction

## Mapping Target

FeatureMembership

## Owned Mappings

from.target

#### 7.7.2.3.3.23 SendObjectAction\_Mapping

##### Description

A UML4SysML::SendObjectAction is mapped to a SysMLv2 ActionUsage that includes a SendActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action sysMLv1SendObjectAction {
    in target : SysMLv1Block;
    send SysMLv1Object1() to target;
}
part def SysMLv1Block;
item def SysMLv1Object;
```

##### General Mappings

SendSignalAction\_Mapping

##### Mapping Source

SendObjectAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.2.3.3.24 SendSignalAction\_Mapping

##### Description

A UML4SysML::SendSignalAction is mapped to a SysMLv2 ActionUsage that includes a SendActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action sysMLv1SendSignalAction {
    in target : SysMLv1Block;
    send SysMLv1Signal() to target;
}
part def SysMLv1Block;
item def SysMLv1Signal;
```

##### General Mappings

CommonAction\_Mapping

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`SSASendActionUsage_Mapping.getMapped(from)`

#### 7.7.2.3.3.26 SSAParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToParameterMembership\_Mapping

##### Mapping Source

InvocationAction

##### Mapping Target

ParameterMembership

##### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`SSAReferenceUsage_Mapping.getMapped(from)`

#### 7.7.2.3.3.27 SSAReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

### Mapping Source

SendSignalAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  

```
Helper.actionOwnedRelationship (from)  
->including (SSAFeatureMembership_Mapping.getMapped (from) )
```

#### 7.7.2.3.3.25 SSAFeatureMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

InvocationAction

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules





In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`SSASendActionUsage_Mapping.getMapped (from)`

#### 7.7.2.3.3.26 SSAParameterMembership\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a membership relationship for *memberElement()*.

###### **General Mappings**

`ToParameterMembership_Init`  
`Mapping`

###### **Mapping Source**

`InvocationAction`

###### **Mapping Target**

`ParameterMembership`

###### **Owned Mappings**

(none)

###### **Applicable filters**

(none)

###### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ParameterMembership::ownedMemberParameter () : Feature [1]`  
`SSAReferenceUsage_Mapping.getMapped (from)`

#### 7.7.2.3.3.27 SSAReferenceUsage\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a reference usage.

###### **General Mappings**

`ToReferenceUsage_Init`  
`Mapping`

## GenericToReferenceUsage\_Mapping

### Mapping Source

InvocationAction

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

`KerML::FeatureDirectionKind::_in'`

## 7.7.2.3.3.28 SSAltItemParameterMembership\_Mapping

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

## GenericToParameterMembership\_Mapping

### Mapping Source

InvocationAction

### Mapping Target

ParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

### Mapping Source

InvocationAction

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

KerML::FeatureDirectionKind::\_in'

#### 7.7.2.3.3.28 SSALtemParameterMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToParameterMembership\_Init  
Mapping

### Mapping Source

InvocationAction

### Mapping Target

ParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]

```
SSAItemReferenceUsage_Mapping.getMapped(from)
```

#### 7.7.2.3.3.29 SSAItemReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

**Generic**ToReferenceUsage\_Mapping

##### Mapping Source

InvocationAction

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

```
KerML::FeatureDirectionKind::_in'
```

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set{SSAItemReferenceUsageFeatureValue_Mapping.getMapped(from)}
```

#### 7.7.2.3.3.30 SSAItemReferenceUsageFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

##### Mapping Source

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ParameterMembership::ownedMemberParameter () : Feature [1]`  
`SSAItemReferenceUsage_Mapping.getMapped (from)`

#### 7.7.2.3.3.29 SSAItemReferenceUsage\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a reference usage.

###### **General Mappings**

ToReferenceUsage\_Init  
Mapping

###### **Mapping Source**

InvocationAction

###### **Mapping Target**

ReferenceUsage

###### **Owned Mappings**

(none)

###### **Applicable filters**

(none)

###### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_in'`
- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set {SSAItemReferenceUsageFeatureValue_Mapping.getMapped (from) }`

#### 7.7.2.3.3.30 SSAItemReferenceUsageFeatureValue\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a feature value relationship.

InvocationAction

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  
`SSAItemReferenceUsageInvocationExpression_Mapping.getMapped (from)`

#### 7.7.2.3.3.31 SSAItemReferenceUsageFeatureTyping\_Mapping

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

**Generic**ToFeatureTyping\_Mapping

### Mapping Source

InvocationAction

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

## General Mappings

ToFeatureValue\_Init  
Mapping

## Mapping Source

InvocationAction

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
SSAItemReferenceUsageInvocationExpression_Mapping.getMapped(from)
```

### 7.7.2.3.3.31 SSAItemReferenceUsageFeatureTyping\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

InvocationAction

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

```

    if from.ocIsTypeOf(UML::SendSignalAction) then
        from.signal
    else if from.ocIsTypeOf(UML::SendObjectAction) then
        from.request
    else
        invalid
    endif endif

```

#### 7.7.2.3.3.32 SSItemReferenceUsageInvocationExpression\_Mapping

##### Description

The mapping class creates the invocation expression for the SysML v2 SendActionUsage.

##### General Mappings

GenericToInvocationExpression\_Mapping

##### Mapping Source

InvocationAction

##### Mapping Target

InvocationExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- InvocationExpression::ownedRelationship () : Relationship [0..\*]  

```

Set { SSItemReferenceUsageFeatureTyping_Mapping.getMapped (from) ,
ReturnParameterFeatureMembership_Factory.create () }

```

#### 7.7.2.3.3.33 SSATargetParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToParameterMembership\_Mapping

##### Mapping Source

InvocationAction



(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
if from.ocIsTypeOf(UML::SendSignalAction) then
    from.signal
else if from.ocIsTypeOf(UML::SendObjectAction) then
    from.request
else
    invalid
endif endif
```

### 7.7.2.3.32 SSItemReferenceUsageInvocationExpression\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

The mapping class creates the invocation expression for the SysML v2 SendActionUsage.

## General Mappings

ToInvocationExpression\_Init  
Mapping

## Mapping Source

InvocationAction

## Mapping Target

InvocationExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `InvocationExpression::ownedRelationship () : Relationship [0..*]`

```
Set{SSAItemReferenceUsageFeatureTyping_Mapping.getMapped(from),
ReturnParameterFeatureMembership_Factory.create() }
```

## Mapping Target

ParameterMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`SSATargetReferenceUsage_Mapping.getMapped(from)`

### 7.7.2.3.3.34 SSATargetReferenceUsage\_Mapping

## Description

Creates a reference usage.

## General Mappings

**Generic**ToReferenceUsage\_Mapping

## Mapping Source

InvocationAction

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]  
`KerML::FeatureDirectionKind::_in'`

#### 7.7.2.3.3.33 SSATargetParameterMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToParameterMembership\_Init  
Mapping

##### Mapping Source

InvocationAction

##### Mapping Target

ParameterMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`SSATargetReferenceUsage_Mapping.getMapped(from)`

#### 7.7.2.3.3.34 SSATargetReferenceUsage\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a reference usage.

##### General Mappings

ToReferenceUsage\_Init  
Mapping

##### Mapping Source

InvocationAction

##### Mapping Target

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set { SSATargetReferenceUsageFeatureValue_Mapping.getMapped (from) }
```

#### 7.7.2.3.3.35 SSATargetReferenceUsageFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

`GenericToFeatureValue_Mapping`

##### Mapping Source

InvocationAction

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
SSATargetReferenceUsageFeatureValueExpression_Mapping.getMapped (from)
```

#### 7.7.2.3.3.36 SSATargetReferenceUsageFeatureValueMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

`GenericToMembership_Mapping`

##### Mapping Source

InvocationAction

##### Mapping Target

Membership

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{SSATargetReferenceUsageFeatureValue_Mapping.getMapped (from) }`
- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_in'`

#### 7.7.2.3.3.35 SSATargetReferenceUsageFeatureValue\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_Init  
Mapping

### Mapping Source

InvocationAction

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

`from.target`

### 7.7.2.3.3.37 SSATargetReferenceUsageFeatureValueExpression\_Mapping

#### Description

The mapping class creates the feature reference expression for the target reference usage element of the SysML v2 SendActionUsage.

#### General Mappings

GenericToFeatureReferenceExpression\_Mapping

#### Mapping Source

InvocationAction

#### Mapping Target

FeatureReferenceExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]

`Set { SSATargetReferenceUsageFeatureValueMembership_Mapping.getMapped (from) ,  
ReturnParameterFeatureMembership_Factory.create () }`

### 7.7.2.3.3.38 SSASendActionUsage\_Mapping

#### Description

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

`SSATargetReferenceUsageFeatureValueExpression_Mapping.getMapped (from)`

#### 7.7.2.3.36 SSATargetReferenceUsageFeatureValueMembership\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

###### Description

Creates a membership relationship for *memberElement()*.

###### General Mappings

ToMembership\_Init  
Mapping

###### Mapping Source

InvocationAction

###### Mapping Target

Membership

###### Owned Mappings

(none)

###### Applicable filters

(none)

###### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`

`from.target`

#### 7.7.2.3.37 SSATargetReferenceUsageFeatureValueExpression\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

###### Description

The mapping class creates the feature reference expression for the target reference usage element of the SysML v2 `SendActionUsage`.

###### General Mappings

The mapping class creates the SysML v2 element SendActionUsage for the UML4SysML::SendSignalAction mapping.

### General Mappings

GenericToActionUsage\_Mapping

### Mapping Source

InvocationAction

### Mapping Target

SendActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SendActionUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { SSAItemParameterMembership_Mapping.getMapped (from) ,  
      SSAParameterMembership_Mapping.getMapped (from) ,  
      SSATargetParameterMembership_Mapping.getMapped (from) }
```

#### 7.7.2.3.39 StartClassifierBehaviorAction\_Mapping

### Description

The UML4SysML::StartClassifierBehaviorAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.

### General Mappings

CommonAction\_Mapping

### Mapping Source

StartClassifierBehaviorAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)



ToFeatureReferenceExpression\_Init  
Mapping

### Mapping Source

InvocationAction

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set { SSATargetReferenceUsageFeatureValueMembership_Mapping.getMapped (from) ,  
ReturnParameterFeatureMembership_Factory.create () }
```

#### 7.7.2.3.3.38 SSASendActionUsage\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the SysML v2 element SendActionUsage for the UML4SysML::SendSignalAction mapping.

### General Mappings

ToActionUsage\_Init  
Mapping

### Mapping Source

InvocationAction

### Mapping Target

SendActionUsage

### Owned Mappings

(none)

### Applicable filters

#### **7.7.2.3.3.40 StartObjectBehaviorAction\_Mapping**

##### **Description**

The UML4SysML::StartObjectBehaviorAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.

##### **General Mappings**

CommonAction\_Mapping

##### **Mapping Source**

StartObjectBehaviorAction

##### **Mapping Target**

ActionUsage

##### **Owned Mappings**

(none)

#### **7.7.2.3.4 Link Actions**

##### **7.7.2.3.4.1 ClearAssociationAction\_Mapping**

##### **Description**

The UML4SysML::ClearAssociationAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### **General Mappings**

CommonAction\_Mapping

##### **Mapping Source**

ClearAssociationAction

##### **Mapping Target**

ActionUsage

##### **Owned Mappings**

(none)

##### **7.7.2.3.4.2 CreateLinkAction\_Mapping**

##### **Description**

The UML4SysML::CreateLinkAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not completely defined yet.

##### **General Mappings**

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `SendActionUsage::ownedRelationship () : Relationship [0..*]`  
`Set { SSAItemParameterMembership_Mapping.getMapped (from) ,  
SSAParameterMembership_Mapping.getMapped (from) ,  
SSATargetParameterMembership_Mapping.getMapped (from) }`

### 7.7.2.3.39 StartClassifierBehaviorAction\_Mapping

#### Description

The UML4SysML::StartClassifierBehaviorAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.

#### General Mappings

CommonAction\_Mapping

#### Mapping Source

StartClassifierBehaviorAction

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.2.3.40 StartObjectBehaviorAction\_Mapping

#### Description

The UML4SysML::StartObjectBehaviorAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.

#### General Mappings

CommonAction\_Mapping

#### Mapping Source

StartObjectBehaviorAction

#### Mapping Target

ActionUsage

CommonAction\_Mapping

#### Mapping Source

CreateLinkAction

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
let linkEndCreationData : Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsTypeOf(UML::LinkEndCreationData)) in
let actionInputPin: Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsTypeOf(UML::ActionInputPin)) in
let triggers: Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Trigger)) in
let toElementFMS: Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in
let toElementOMS: Set(UML::Element) =
  (((from.ownedElement - toElementFMS) - actionInputPin)
   - triggers) - linkEndCreationData in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
```

#### 7.7.2.3.4.3 CreateLinkObjectAction\_Mapping

##### Description

A UML4SysML::CreateLinkObjectAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CreateLinkAction\_Mapping

#### Mapping Source

CreateLinkObjectAction

#### Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

### 7.7.2.3.4 Link Actions

#### 7.7.2.3.4.1 ClearAssociationAction\_Mapping

##### Description

The UML4SysML::ClearAssociationAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

ClearAssociationAction

##### Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

#### 7.7.2.3.4.2 CreateLinkAction\_Mapping

##### Description

The UML4SysML::CreateLinkAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not completely defined yet.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

CreateLinkAction

##### Mapping Target

ActionUsage

## Owned Mappings

## Owned Mappings

(none)

### 7.7.2.3.4.4 DestroyLinkAction\_Mapping

#### Description

The UML4SysML::DestroyLinkAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not completely defined yet.

#### General Mappings

CommonAction\_Mapping

#### Mapping Source

DestroyLinkAction

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  

```
let actionInputPin: Set(UML::Element) =  
    from.ownedElement->select(e | e.ocIsTypeOf(UML::ActionInputPin)) in  
let triggers: Set(UML::Element) =  
    from.ownedElement->select(e | e.ocIsKindOf(UML::Trigger)) in  
let linkData: Set(UML::Element) =  
    from.ownedElement->select( e | e.ocIsKindOf(UML::LinkEndData) or  
    e.ocIsKindOf(UML::LinkEndDestructionData)) in  
let toElementFMS: Set(UML::Element) =  
    from.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in  
let toElementOMS: Set(UML::Element) =  
    (((from.ownedElement - toElementFMS) - actionInputPin)  
    - triggers) - linkData) in  
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))  
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
```

### 7.7.2.3.4.5 ReadLinkAction\_Mapping

#### Description

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
let linkEndCreationData : Set(UML::Element) =
    from.ownedElement->select(e | e.oclcIsTypeOf(UML::LinkEndCreationData)) in
let actionInputPin: Set(UML::Element) =
    from.ownedElement->select(e | e.oclcIsTypeOf(UML::ActionInputPin)) in
let triggers: Set(UML::Element) =
    from.ownedElement->select(e | e.oclcIsKindOf(UML::Trigger)) in
let toElementFMS: Set(UML::Element) =
    from.ownedElement->select(e | e.oclcIsKindOf(UML::Pin)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - actionInputPin)
     - triggers) - linkEndCreationData in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
```

#### 7.7.2.3.4.3 CreateLinkObjectAction\_Mapping

##### Description

A UML4SysML::CreateLinkObjectAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CreateLinkAction\_Mapping

##### Mapping Source

CreateLinkObjectAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

### Applicable filters

(none)

#### 7.7.2.3.4.4 DestroyLinkAction\_Mapping

##### Description

The UML4SysML::ReadLinkAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not completely defined yet.

### General Mappings

CommonAction\_Mapping

### Mapping Source

ReadLinkAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
let actionInputPin: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsTypeOf(UML::ActionInputPin)) in
let triggers: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Trigger)) in
let linkData: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::LinkEndData)) in
let toElementFMS: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - actionInputPin)
    - triggers) - linkData) in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
```

#### 7.7.2.3.4.6 ReadLinkObjectEndAction\_Mapping

### Description

The UML4SysML::ReadLinkObjectEndAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

### General Mappings

CommonAction\_Mapping

### Mapping Source



The UML4SysML::DestroyLinkAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not completely defined yet.

### General Mappings

CommonAction\_Mapping

### Mapping Source

DestroyLinkAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
let actionInputPin: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsTypeOf(UML::ActionInputPin)) in
let triggers: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Trigger)) in
let linkData: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::LinkEndData) or
    e.ocIsKindOf(UML::LinkEndDestructionData)) in
let toElementFMS: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - actionInputPin)
    - triggers) - linkData in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
```

#### 7.7.2.3.4.5 ReadLinkAction\_Mapping

### Description

The UML4SysML::ReadLinkAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not completely defined yet.

### General Mappings

CommonAction\_Mapping

### Mapping Source

ReadLinkAction



## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
let actionInputPin: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsTypeOf(UML::ActionInputPin)) in
let triggers: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Trigger)) in
let linkData: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::LinkEndData)) in
let toElementFMS: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - actionInputPin)
     - triggers) - linkData) in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
```

### 7.7.2.3.4.6 ReadLinkObjectEndAction\_Mapping

#### Description

The UML4SysML::ReadLinkObjectEndAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

#### General Mappings

CommonAction\_Mapping

#### Mapping Source

ReadLinkObjectEndAction

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

ReadLinkObjectEndAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

#### 7.7.2.3.4.7 ReadLinkObjectEndQualifierAction\_Mapping

### Description

The UML4SysML::ReadLinkObjectEndQualifierAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

### General Mappings

CommonAction\_Mapping

### Mapping Source

ReadLinkObjectEndQualifierAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

#### 7.7.2.3.5 Object Actions

##### 7.7.2.3.5.1 CreateObjectAction\_Mapping

### Description

A UML4SysML::CreateObjectAction is mapped to a SysML v2 ActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1CreateObjectAction {  
        out result : SysMLv1Block = SysMLv1Block();  
    }  
}  
part def SysMLv1Block;
```

### General Mappings

CommonAction\_Mapping

### Mapping Source

(none)

#### 7.7.2.3.4.7 ReadLinkObjectEndQualifierAction\_Mapping

##### Description

The UML4SysML::ReadLinkObjectEndQualifierAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

ReadLinkObjectEndQualifierAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

#### Applicable filters

(none)

#### 7.7.2.3.5 Object Actions

##### 7.7.2.3.5.1 CreateObjectAction\_Mapping

##### Description

A UML4SysML::CreateObjectAction is mapped to a SysML v2 ActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1CreateObjectAction {  
        out result : SysMLv1Block = SysMLv1Block();  
    }  
}  
part def SysMLv1Block;
```

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

CreateObjectAction

##### Mapping Target

CreateObjectAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

#### 7.7.2.3.5.2 COAInvocationExpressionFeatureTyping\_Mapping

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

GenericToFeatureTyping\_Mapping

### Mapping Source

CreateObjectAction

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`from.classifier`

#### 7.7.2.3.5.3 COAInvocationExpression\_Mapping

### Description

The mapping class creates the invocation expression to create the object.

### General Mappings

GenericToInvocationExpression\_Mapping

### Mapping Source

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

#### 7.7.2.3.5.2 COAInvocationExpressionFeatureTyping\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

CreateObjectAction

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`from.classifier`

#### 7.7.2.3.5.3 COAInvocationExpression\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

### Description

The mapping class creates the invocation expression to create the object.

### General Mappings

CreateObjectAction

### Mapping Target

InvocationExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- InvocationExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{COAInvocationExpressionFeatureTyping_Mapping.getMapped(from),  
CommonReturnParameterFeatureMembership_Mapping.getMapped(from,result)}
```

#### 7.7.2.3.5.4 COAPin\_Mapping

### Description

The mapping class creates the output parameter of the ActionUsage for the mapping of UML4SysML::CreateObjectAction.

### General Mappings

No general mappings.

### Mapping Source

OutputPin

### Mapping Target

No target element.

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.oclIsTypeOf(UML::CreateObjectAction)
```

### Mapping rules



ToInvocationExpression\_Init  
Mapping

#### Mapping Source

CreateObjectAction

#### Mapping Target

InvocationExpression

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- InvocationExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{COAInvocationExpressionFeatureTyping_Mapping.getMapped(from),  
CommonReturnParameterFeatureMembership_Mapping.getMapped(from,result)}
```

#### 7.7.2.3.5.4 COAPin\_Mapping

**SYSML2 -374: COAPin\_Mapping is not correctly specified**

#### Description

The mapping class creates the output parameter of the ActionUsage for the mapping of UML4SysML::CreateObjectAction.

#### General Mappings

Pin\_Mapping

#### Mapping Source

OutputPin

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ownedRelationship () : Relationship [0..*]`

```
Set{PinFeatureTyping_Mapping.getMapped(from),  
COAPinFeatureValue_Mapping.getMapped(from)}
```

#### 7.7.2.3.5.5 COAPinFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic** ToFeatureValue\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
COAInvocationExpression_Mapping.getMapped(from.owner)
```

#### 7.7.2.3.5.6 DestroyObjectAction\_Mapping

##### Description

The UML4SysML::DestroyObjectAction is conceptually mapped to the SysML v2 library function OccurrenceFunctions::destroy.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1DestroyObjectAction {  
        in target : SysMLv1Block;  
        action : OccurrenceFunctions::destroy {
```

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.ocIsTypeOf(UML::CreateObjectAction)
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{PinFeatureTyping_Mapping.getMapped(from),`  
`COAPinFeatureValue_Mapping.getMapped(from)}`

#### 7.7.2.3.5.5 COAPinFeatureValue\_Mapping

### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature value relationship.

#### General Mappings

ToFeatureValue\_Init  
Mapping

#### Mapping Source

OutputPin

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`COAInvocationExpression_Mapping.getMapped(from.owner)`

#### 7.7.2.3.5.6 DestroyObjectAction\_Mapping

#### Description

```

        in occ = target;
    }
}
part def SysMLv1Block;

```

## General Mappings

CommonAction\_Mapping

## Mapping Source

DestroyObjectAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```

    Helper.actionOwnedRelationship (from)
    ->including (DOADestroyFeatureMembership_Mapping.getMapped (from))

```

### 7.7.2.3.5.7 DOADestroyActionUsage\_Mapping

## Description

The mapping class creates the action usage for the destroy function.

## General Mappings

GenericToActionUsage\_Mapping

## Mapping Source

DestroyObjectAction

## Mapping Target

ActionUsage

## Owned Mappings

The UML4SysML::DestroyObjectAction is conceptually mapped to the SysML v2 library function OccurrenceFunctions::destroy.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
    action sysMLv1DestroyObjectAction {
        in target : SysMLv1Block;
        action : OccurrenceFunctions::destroy {
            in occ = target;
        }
    }
}
part def SysMLv1Block;
```

## General Mappings

CommonAction\_Mapping

## Mapping Source

DestroyObjectAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
Helper.actionOwnedRelationship(from)
->including(DOADestroyFeatureMembership_Mapping.getMapped(from))
```

### 7.7.2.3.5.7 DOADestroyActionUsage\_Mapping

## **SysML2 -220: Replace Generic mapping classes by Initializers**

## Description

The mapping class creates the action usage for the destroy function.

## General Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionUsage::ownedRelationship () : Relationship [0..*]`

```
Set { DOADestroyActionUsageFeatureTyping_Mapping.getMapped (from) ,  
      DOADestroyActionUsageFeatureMembership_Mapping.getMapped (from) }
```

#### 7.7.2.3.5.8 DOADestroyActionUsageFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic** ToFeatureMembership\_Mapping

##### Mapping Source

DestroyObjectAction

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
DOADestroyActionUsageReferenceUsage_Mapping.getMapped (from)
```

#### 7.7.2.3.5.9 DOADestroyActionUsageFeatureReferenceExpression\_Mapping

##### Description

The mapping class creates the feature reference expression for the UML4SysML::DestroyObjectAction mapping.

ToActionUsage\_Init  
Mapping

#### Mapping Source

DestroyObjectAction

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{DOADestroyActionUsageFeatureTyping_Mapping.getMapped(from) ,  
DOADestroyActionUsageFeatureMembership_Mapping.getMapped(from) }
```

#### 7.7.2.3.5.8 DOADestroyActionUsageFeatureMembership\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

DestroyObjectAction

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

## General Mappings

GenericToFeatureReferenceExpression\_Mapping

## Mapping Source

DestroyObjectAction

## Mapping Target

FeatureReferenceExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{DOADestroyActionUsageMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

### 7.7.2.3.5.10 DOADestroyActionUsageMembership\_Mapping

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

GenericToMembership\_Mapping

## Mapping Source

DestroyObjectAction

## Mapping Target

Membership

## Owned Mappings

(none)

## Applicable filters

(none)



## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
DOADestroyActionUsageReferenceUsage_Mapping.getMapped(from)
```

### 7.7.2.3.5.9 DOADestroyActionUsageFeatureReferenceExpression\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

The mapping class creates the feature reference expression for the `UML4SysML::DestroyObjectAction` mapping.

## General Mappings

`ToFeatureReferenceExpression_Init`  
Mapping

## Mapping Source

`DestroyObjectAction`

## Mapping Target

`FeatureReferenceExpression`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set{DOADestroyActionUsageMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

### 7.7.2.3.5.10 DOADestroyActionUsageMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

```
from.target
```

### 7.7.2.3.5.11 DOADestroyActionUsageFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**Generic**ToFeatureTyping\_Mapping

#### Mapping Source

DestroyObjectAction

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
SysMLv2::Function.allInstances(  
)->any(e | e.qualifiedName = 'OccurrenceFunctions::destroy')
```

### 7.7.2.3.5.12 DOADestroyActionUsageFeatureValue\_Mapping

#### Description

Creates a feature value relationship.

#### General Mappings

**Generic**ToFeatureValue\_Mapping

#### Mapping Source

ToMembership\_Init  
Mapping

#### Mapping Source

DestroyObjectAction

#### Mapping Target

Membership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
`from.target`

#### 7.7.2.3.5.11 DOADestroyActionUsageFeatureTyping\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

ToFeatureTyping\_Init  
Mapping

#### Mapping Source

DestroyObjectAction

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

DestroyObjectAction

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
DOADestroyActionUsageFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.5.13 DOADestroyActionUsageReferenceUsage\_Mapping

### Description

Creates a reference usage.

### General Mappings

GenericToReferenceUsage\_Mapping

### Mapping Source

DestroyObjectAction

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SysMLv2::Function.allInstances(  
  )->any(e | e.qualifiedName = 'OccurrenceFunctions::destroy')
```

### 7.7.2.3.5.12 DOADestroyActionUsageFeatureValue\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature value relationship.

##### General Mappings

ToFeatureValue [\\_Init](#)  
Mapping

##### Mapping Source

DestroyObjectAction

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
DOADestroyActionUsageFeatureReferenceExpression_Mapping.getMapped(from)
```

### 7.7.2.3.5.13 DOADestroyActionUsageReferenceUsage\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a reference usage.

##### General Mappings

```
Set{DOADestroyActionUsageFeatureValue_Mapping.getMapped(from)}
```

#### 7.7.2.3.5.14 DOADestroyFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

DestroyObjectAction

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
DOADestroyActionUsage_Mapping.getMapped(from)
```

#### 7.7.2.3.5.15 ReadIsClassifiedObjectAction\_Mapping

##### Description

The UML4SysML::ReadIsClassifiedObjectAction is conceptually mapped to a SysML v2 ActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
    action sysMLv1ReadIsClassifiedObjectActionDirect {
        in object;
        out result : ScalarValues::Boolean =
            object istype ThisIsABlock;
    }

    action sysMLv1ReadIsClassifiedObjectActionNonDirect {
        in object;
        out result : ScalarValues::Boolean =
            object hastype ThisIsABlock;
    }
}
```

ToReferenceUsage\_Init  
Mapping

#### Mapping Source

DestroyObjectAction

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
`Set{DOADestroyActionUsageFeatureValue_Mapping.getMapped(from) }`

#### 7.7.2.3.5.14 DOADestroyFeatureMembership\_Mapping

### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

DestroyObjectAction

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

```
}  
}
```

### General Mappings

CommonAction\_Mapping

### Mapping Source

ReadIsClassifiedObjectAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

#### 7.7.2.3.5.16 RICOAFeatureValue\_Mapping

### Description

Creates a feature value relationship.

### General Mappings

GenericToFeatureValue\_Mapping

### Mapping Source

ReadIsClassifiedObjectAction

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
RICOAFeatureValueOperatorExpression_Mapping.getMapped (from)
```



## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`DOADestroyActionUsage_Mapping.getMapped(from)`

### 7.7.2.3.5.15 ReadIsClassifiedObjectAction\_Mapping

#### Description

The `UML4SysML::ReadIsClassifiedObjectAction` is conceptually mapped to a SysML v2 `ActionUsage`.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
  action sysMLv1ReadIsClassifiedObjectActionDirect {
    in object;
    out result : ScalarValues::Boolean =
      object istype ThisIsABlock;
  }

  action sysMLv1ReadIsClassifiedObjectActionNonDirect {
    in object;
    out result : ScalarValues::Boolean =
      object hastype ThisIsABlock;
  }
}
```

#### General Mappings

`CommonAction_Mapping`

#### Mapping Source

`ReadIsClassifiedObjectAction`

#### Mapping Target

`ActionUsage`

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.2.3.5.16 RICOAFeatureValue\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

#### 7.7.2.3.5.17 RICOAFeatureValueOperatorExpression\_Mapping

##### Description

The mapping class creates the operator expression for the UML4SysML::ReadIsClassifiedObjectAction mapping.

##### General Mappings

GenericToOperatorExpression\_Mapping

##### Mapping Source

ReadIsClassifiedObjectAction

##### Mapping Target

OperatorExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OperatorExpression::ownedRelationship () : Relationship [0..\*]  
`Set { RICOAFeatureValueOperatorParameterMembership_Mapping.getMapped (from) }`
- OperatorExpression::operator () : String [1]  
`if from.isDirect then 'istype' else 'hastype' endif`

#### 7.7.2.3.5.18 RICOAFeatureValueOperatorExpressionFeature\_Mapping

##### Description

The mapping class creates the feature for the operator expression of the UML4SysML::ReadIsClassifiedObjectAction mapping.

##### General Mappings

GenericToFeature\_Mapping

##### Mapping Source

ReadIsClassifiedObjectAction

##### Mapping Target

Feature

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_Init  
Mapping

### Mapping Source

ReadIsClassifiedObjectAction

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
RICOAFeatureValueOperatorExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.5.17 RICOAFeatureValueOperatorExpression\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the operator expression for the UML4SysML::ReadIsClassifiedObjectAction mapping.

### General Mappings

ToOperatorExpression\_Init  
Mapping

### Mapping Source

ReadIsClassifiedObjectAction

### Mapping Target

OperatorExpression

### Owned Mappings

(none)

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set{RICOAFeatureValueOperatorExpressionFeatureValue_Mapping.getMapped(from) }`
- `Feature::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_in'`

### 7.7.2.3.5.19 RICOAFeatureValueOperatorExpressionFeatureValue\_Mapping

#### Description

Creates a feature value relationship.

#### General Mappings

`GenericToFeatureValue_Mapping`

#### Mapping Source

`ReadIsClassifiedObjectAction`

#### Mapping Target

`FeatureValue`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`RICOAFeatureValueOperatorFeatureReferenceExpression_Mapping.getMapped(from)`

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OperatorExpression::operator () : String [1]`  
`if from.isDirect then 'istype' else 'hastype' endif`
- `OperatorExpression::ownedRelationship () : Relationship [0..*]`  
`Set{RICOAFeatureValueOperatorParameterMembership_Mapping.getMapped(from) }`

### 7.7.2.3.5.18 RICOAFeatureValueOperatorExpressionFeature\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

## Description

The mapping class creates the feature for the operator expression of the UML4SysML::ReadIsClassifiedObjectAction mapping.

## General Mappings

ToFeature Init  
Mapping

## Mapping Source

ReadIsClassifiedObjectAction

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_' in'`
- `Feature::ownedRelationship () : Relationship [0..*]`

#### 7.7.2.3.5.20 RICOAFeatureValueOperatorFeatureReferenceExpression\_Mapping

##### Description

The mapping class creates the feature reference expression for the UML4SysML::ReadIsClassifiedObjectAction mapping.

##### General Mappings

**Generic**ToFeatureReferenceExpression\_Mapping

##### Mapping Source

ReadIsClassifiedObjectAction

##### Mapping Target

FeatureReferenceExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]

```
Set { RICOAFeatureValueOperatorMembership_Mapping.getMapped (from) ,  
CommonReturnParameterFeatureMembership_Mapping.getMapped (from) }
```

#### 7.7.2.3.5.21 RICOAFeatureValueOperatorMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic**ToMembership\_Mapping

##### Mapping Source

ReadIsClassifiedObjectAction

##### Mapping Target

Membership

##### Owned Mappings

```
Set{RICOAFeatureValueOperatorExpressionFeatureValue_Mapping.getMapped(from)}
```

#### 7.7.2.3.5.19 RICOAFeatureValueOperatorExpressionFeatureValue\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a feature value relationship.

###### **General Mappings**

ToFeatureValue\_Init  
Mapping

###### **Mapping Source**

ReadIsClassifiedObjectAction

###### **Mapping Target**

FeatureValue

###### **Owned Mappings**

(none)

###### **Applicable filters**

(none)

###### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
RICOAFeatureValueOperatorFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.5.20 RICOAFeatureValueOperatorFeatureReferenceExpression\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

The mapping class creates the feature reference expression for the UML4SysML::ReadIsClassifiedObjectAction mapping.

###### **General Mappings**

ToFeatureReferenceExpression\_Init  
Mapping

###### **Mapping Source**

ReadIsClassifiedObjectAction

(none)

#### 7.7.2.3.5.22 RICOAFeatureValueOperatorParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToParameterMembership\_Mapping

##### Mapping Source

ReadIsClassifiedObjectAction

##### Mapping Target

ParameterMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`RICOAFeatureValueOperatorExpressionFeature_Mapping.getMapped(from)`
- ParameterMembership::visibility () : VisibilityKind [1]  
`KerML::VisibilityKind::private`

#### 7.7.2.3.5.23 RICOAOutputPin\_Mapping

##### Description

The mapping class creates the output parameter of the ActionUsage element for the UML4SysML::ReadIsClassifiedObjectAction mapping.

##### General Mappings

No general mappings.

##### Mapping Source

OutputPin

##### Mapping Target



### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{RICOAFeatureValueOperatorMembership_Mapping.getMapped(from) ,  
CommonReturnParameterFeatureMembership_Mapping.getMapped(from) }
```

#### 7.7.2.3.5.21 RICOAFeatureValueOperatorMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

ReadIsClassifiedObjectAction

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

#### 7.7.2.3.5.22 RICOAFeatureValueOperatorParameterMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description



Creates a membership relationship for *memberElement()*.

### General Mappings

ToParameterMembership\_Init  
Mapping

### Mapping Source

ReadIsClassifiedObjectAction

### Mapping Target

ParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`RICOAFeatureValueOperatorExpressionFeature_Mapping.getMapped(from)`
- ParameterMembership::visibility () : VisibilityKind [1]  
`KerML::VisibilityKind::private`

#### 7.7.2.3.5.23 RICOAOutputPin\_Mapping

**[SYSML2 -385: The operation RICOAOutputPin\\_Mapping::filter\(\) should redefine Pin\\_Mapping::filter\(\)](#)**

**[SYSML2 -249: RICOAOutputPin\\_Mapping should specialized Pin\\_Mapping](#)**

### Description

The mapping class creates the output parameter of the ActionUsage element for the UML4SysML::ReadIsClassifiedObjectAction mapping.

### General Mappings

Pin\_Mapping

### Mapping Source

OutputPin

### Mapping Target

No target element.

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.oclIsTypeOf(UML::ReadIsClassifiedObjectAction)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ownedRelationship () : Relationship [0..\*]

```
Set{PinFeatureTyping_Mapping.getMapped(from),  
RICOAFeatureValue_Mapping.getMapped(from.owner),  
MultiplicityMembership_Mapping.getMapped(from)}
```

### 7.7.2.3.5.24 ReadExtentAction\_Mapping

#### Description

A UML4SysML::ReadExtentAction is mapped to a SysML v2 ActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1ReadExtentAction {  
        out thisIsTheOutputPin : SysMLv1Block =  
            all SysMLv1Block;  
    }  
}  
part def SysMLv1Block;
```

## General Mappings

CommonAction\_Mapping

## Mapping Source

ReadExtentAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.oclIsTypeOf(UML::ReadIsClassifiedObjectAction)
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **ReferenceUsage::ownedRelationship () : Relationship [0..\*]**  

```
Set{TypedElementFeatureTyping_Mapping.getMapped(from),  
RICOAFeatureValue_Mapping.getMapped(from.owner),  
MultiplicityMembership_Mapping.getMapped(from)}
```

#### 7.7.2.3.5.24 ReadExtentAction\_Mapping

##### Description

A UML4SysML::ReadExtentAction is mapped to a SysML v2 ActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1ReadExtentAction {  
        out thisIsTheOutputPin : SysMLv1Block =  
            all SysMLv1Block;  
    }  
}  
part def SysMLv1Block;
```

### General Mappings

CommonAction\_Mapping

### Mapping Source

ReadExtentAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

`Helper.actionOwnedRelationship (from)`

#### 7.7.2.3.5.25 REAFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

GenericToFeatureValue\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

`REAFeatureValueOperatorExpression_Mapping.getMapped (from)`

#### 7.7.2.3.5.26 REAFeatureValueOperatorExpression\_Mapping

##### Description

The mapping class creates the operator expression for the UML4SysML::ReadExtentAction mapping.

##### General Mappings

GenericToOperatorExpression\_Mapping

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

`Helper.actionOwnedRelationship (from)`

#### 7.7.2.3.5.25 REAFeatureValue\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_Init  
Mapping

### Mapping Source

OutputPin

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

`REAFeatureValueOperatorExpression_Mapping.getMapped (from)`

#### 7.7.2.3.5.26 REAFeatureValueOperatorExpression\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

## Mapping Source

OutputPin

## Mapping Target

OperatorExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OperatorExpression::operator () : String [1]  
`'all'`
- OperatorExpression::ownedRelationship () : Relationship [0..\*]  
`Set { REAFeatureValueOperatorExpressionMembership_Mapping.getMapped (from) ,  
CommonReturnParameterFeatureMembership_Mapping.getMapped (from) }`

### 7.7.2.3.5.27 REAFeatureValueOperatorExpressionFeature\_Mapping

#### Description

The mapping class creates the feature for the operator expression for the UML4SysML::ReadExtentAction mapping.

#### General Mappings

**Generic**ToFeature\_Mapping

#### Mapping Source

OutputPin

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)



The mapping class creates the operator expression for the UML4SysML::ReadExtentAction mapping.

### General Mappings

ToOperatorExpression\_Init  
Mapping

### Mapping Source

OutputPin

### Mapping Target

OperatorExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OperatorExpression::operator () : String [1]  
  
    'all'
- OperatorExpression::ownedRelationship () : Relationship [0..\*]  
  
    Set{REAFeatureValueOperatorExpressionMembership\_Mapping.getMapped(from),  
    CommonReturnParameterFeatureMembership\_Mapping.getMapped(from) }

#### 7.7.2.3.5.27 REAFeatureValueOperatorExpressionFeature\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the feature for the operator expression for the UML4SysML::ReadExtentAction mapping.

### General Mappings

ToFeature\_Init  
Mapping

### Mapping Source

OutputPin

### Mapping Target

Feature

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set { REAFeatureValueOperatorExpressionFeatureTyping_Mapping.getMapped (from) }
```

### 7.7.2.3.5.28 REAFeatureValueOperatorExpressionFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

`GenericToFeatureTyping_Mapping`

#### Mapping Source

OutputPin

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
from.owner.classifier
```

### 7.7.2.3.5.29 REAFeatureValueOperatorExpressionMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

`GenericToFeatureMembership_Mapping`

#### Mapping Source

OutputPin

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set{REAFeatureValueOperatorExpressionFeatureTyping_Mapping.getMapped(from) }
```

### 7.7.2.3.5.28 REAFeatureValueOperatorExpressionFeatureTyping\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

OutputPin

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
from.owner.classifier
```

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
REAFeatureValueOperatorExpressionFeature_Mapping.getMapped(from)
```

#### 7.7.2.3.5.30 REAOutputPin\_Mapping

### Description

The mapping class creates the output parameter of the ActionUsage for the mapping of UML4SysML::ReadExtentAction.

### General Mappings

Pin\_Mapping

### Mapping Source

OutputPin

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.ocIsTypeOf(UML::ReadExtentAction)
```

### Mapping rules

#### 7.7.2.3.5.29 REAFeatureValueOperatorExpressionMembership\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a membership relationship for *memberElement()*.

###### **General Mappings**

ToFeatureMembership\_Init  
Mapping

###### **Mapping Source**

OutputPin

###### **Mapping Target**

FeatureMembership

###### **Owned Mappings**

(none)

###### **Applicable filters**

(none)

###### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`REAFeatureValueOperatorExpressionFeature_Mapping.getMapped(from)`

#### 7.7.2.3.5.30 REAOutputPin\_Mapping

###### **Description**

The mapping class creates the output parameter of the ActionUsage for the mapping of UML4SysML::ReadExtentAction.

###### **General Mappings**

Pin\_Mapping

###### **Mapping Source**

OutputPin

###### **Mapping Target**

ReferenceUsage

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  

```
Set {TypedElementFeatureTyping_Mapping.getMapped(from),  
    REAFeatureValue_Mapping.getMapped(from)}  
->union(self.oclassType(Pin_Mapping).ownedRelationship())
```

#### 7.7.2.3.5.31 ReadSelfAction\_Mapping

##### Description

A `UML4SysML::ReadSelfAction` is mapped to a SysML v2 `ActionUsage`.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1ReadSelfAction {  
        out : Base::Anything = this;  
    }  
}
```

##### General Mappings

`CommonAction_Mapping`

##### Mapping Source

`ReadSelfAction`

##### Mapping Target

`ActionUsage`

##### Owned Mappings

(none)

#### 7.7.2.3.5.32 RSAFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

`GenericToFeatureValue_Mapping`

##### Mapping Source

`OutputPin`

##### Mapping Target

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.oclIsTypeOf(UML::ReadExtentAction)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
Set {TypedElementFeatureTyping_Mapping.getMapped(from),  
    REAFeatureValue_Mapping.getMapped(from)}  
->union(self.oclAsType(Pin_Mapping).ownedRelationship())
```

### 7.7.2.3.5.31 ReadSelfAction\_Mapping

#### Description

A UML4SysML::ReadSelfAction is mapped to a SysML v2 ActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1ReadSelfAction {  
        out : Base::Anything = this;  
    }  
}
```

## General Mappings

CommonAction\_Mapping

## Mapping Source

ReadSelfAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
RSAFeatureValueFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.5.33 RSAFeatureValueFeatureReferenceExpression\_Mapping

### Description

The mapping class creates the feature reference expression for the mapping of UML4SysML::ReadSelfAction.

### General Mappings

**Generic**ToFeatureReferenceExpression\_Mapping

### Mapping Source

OutputPin

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]

```
Set{RSAFeatureValueMembership_Mapping.getMapped(from),  
CommonReturnParameterFeatureMembership_Mapping.getMapped(from) }
```



#### 7.7.2.3.5.32 RSAFeatureValue\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature value relationship.

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

OutputPin

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
RSAFeatureValueFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.5.33 RSAFeatureValueFeatureReferenceExpression\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates the feature reference expression for the mapping of UML4SysML::ReadSelfAction.

##### General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

##### Mapping Source

OutputPin

##### Mapping Target

#### 7.7.2.3.5.34 RSAFeatureValueMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToMembership\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

Membership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  

```
SysML2::Feature.allInstances()  
->any(e | e.qualifiedName = 'Occurrences::Occurrence::this')
```

#### 7.7.2.3.5.35 RSAOutputPin\_Mapping

##### Description

The mapping class creates the output parameter of the ActionUsage for the mapping of UML4SysML::ReadSelfAction.

##### General Mappings

Pin\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

ReferenceUsage

##### Owned Mappings

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{RSAFeatureValueMembership_Mapping.getMapped(from),  
CommonReturnParameterFeatureMembership_Mapping.getMapped(from)}
```

#### 7.7.2.3.5.34 RSAFeatureValueMembership\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

OutputPin

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.oclIsKindOf(UML::ReadSelfAction)
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **ReferenceUsage::isUnique () : Boolean [1]**

**false**

- **ReferenceUsage::isAbstract () : Boolean [1]**

**true**

- **ReferenceUsage::ownedRelationship () : Relationship [0..\*]**

```
Set{TypedElementFeatureTyping_Mapping.getMapped(from),  
RSAFeatureValue_Mapping.getMapped(from)}  
->union(self.oclAsType(Pin_Mapping).ownedRelationship())
```

#### 7.7.2.3.5.36 ReclassifyObjectAction\_Mapping

##### Description

The UML4SysML::ReclassifyObjectAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

ReclassifyObjectAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

#### 7.7.2.3.5.37 TestIdentityAction\_Mapping

##### Description

A UML4SysML::TestIdentityAction is mapped to a SysML v2 ActionUsage.

```

SYSML2::Feature.allInstances()
->any(e | e.qualifiedName = 'Occurrences::Occurrence::this')

```

#### 7.7.2.3.5.35 RSAOutputPin\_Mapping

##### Description

The mapping class creates the output parameter of the ActionUsage for the mapping of UML4SysML::ReadSelfAction.

##### General Mappings

Pin\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.oclIsKindOf(UML::ReadSelfAction)
```

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{TypedElementFeatureTyping_Mapping.getMapped(from),
RSAFeatureValue_Mapping.getMapped(from)}
->union(self.oclAsType(Pin_Mapping).ownedRelationship())
```
- ReferenceUsage::isAbstract () : Boolean [1]  

```
true
```
- ReferenceUsage::isUnique () : Boolean [1]  

```
false
```

#### 7.7.2.3.5.36 ReclassifyObjectAction\_Mapping

##### Description

The UML4SysML::ReclassifyObjectAction is not supported by SysML v2. It is mapped to an empty action usage to keep the connections within the activity respectively action definition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
    action sysMLv1TestIdentityAction {
        in firstParameter;
        in secondParameter;
        out result : ScalarValues::Boolean =
            firstParameter == secondParameter;
    }
}
```

## General Mappings

CommonAction\_Mapping

### Mapping Source

TestIdentityAction

### Mapping Target

CalculationUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- CalculationUsage::ownedRelationship () : Relationship [0..\*]  

```
Helper.actionOwnedRelationship(from)
->including(TIAResultExpressionMembership_Mapping.getMapped(from))
```

#### 7.7.2.3.5.38 TIAOperatorExpression\_Mapping

### Description

The mapping class creates the operator expression for the UML4SysML::TestIdentityAction mapping.

## General Mappings

GenericToOperatorExpression\_Mapping

### Mapping Source

TestIdentityAction

## General Mappings

CommonAction\_Mapping

## Mapping Source

ReclassifyObjectAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

### 7.7.2.3.5.37 TestIdentityAction\_Mapping

#### Description

A UML4SysML::TestIdentityAction is mapped to a SysML v2 ActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1TestIdentityAction {  
        in firstParameter;  
        in secondParameter;  
        out result : ScalarValues::Boolean =  
            firstParameter == secondParameter;  
    }  
}
```

## General Mappings

CommonAction\_Mapping

## Mapping Source

TestIdentityAction

## Mapping Target

CalculationUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping Target

OperatorExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OperatorExpression::operator () : String [1]`  
`'=='`
- `OperatorExpression::ownedRelationship () : Relationship [0..*]`  

```
Set {EqualOperatorExpressionOperandParameterMembership_Mapping.getMapped(from.first),  
EqualOperatorExpressionOperandParameterMembership_Mapping.getMapped(from.second),  
CommonReturnParameterFeatureMembership_Mapping.getMapped(from.result)}
```

### 7.7.2.3.5.39 TIAResultExpressionMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

`GenericToFeatureMembership_Mapping`

#### Mapping Source

TestIdentityAction

#### Mapping Target

ResultExpressionMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules



## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- CalculationUsage::ownedRelationship () : Relationship [0..\*]

```
Helper.actionOwnedRelationship (from)
->including (TIAResultExpressionMembership_Mapping.getMapped (from))
```

### 7.7.2.3.5.38 TIAOperatorExpression\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

The mapping class creates the operator expression for the UML4SysML::TestIdentityAction mapping.

## General Mappings

ToOperatorExpression\_Init  
Mapping

## Mapping Source

TestIdentityAction

## Mapping Target

OperatorExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OperatorExpression::ownedRelationship () : Relationship [0..\*]

```
Set {EqualOperatorExpressionOperandParameterMembership_Mapping.getMapped (from.first),
EqualOperatorExpressionOperandParameterMembership_Mapping.getMapped (from.second),
CommonReturnParameterFeatureMembership_Mapping.getMapped (from.result) }
```

- OperatorExpression::operator () : String [1]

```
'=='
```

### 7.7.2.3.5.39 TIAResultExpressionMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ResultExpressionMembership::ownedMemberFeature () : Feature [0..1]

`TIAOperatorExpression_Mapping.getMapped(from)`

#### 7.7.2.3.5.40 ValueSpecificationAction\_Mapping

##### Description

A UML4SysML::ValueSpecificationAction is mapped to a SysML v2 ActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Acticity {
  action sysMLv1ValueSpecificationAction1 {
    out result : ScalarValues::Integer = 42;
  }

  action sysMLv1ValueSpecificationAction2 {
    out result = sysMLv1OpaqueExpression.result;
    calc sysMLv1OpaqueExpression {
      language "Math"
      /*
      * 42 + 23
      */
    }
  }
}
```

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

ValueSpecificationAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

TestIdentityAction

## Mapping Target

ResultExpressionMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ResultExpressionMembership::ownedMemberFeature () : Feature [0..1]  
`TIAOperatorExpression_Mapping.getMapped(from)`

### 7.7.2.3.5.40 ValueSpecificationAction\_Mapping

## Description

A UML4SysML::ValueSpecificationAction is mapped to a SysML v2 ActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Acticity {
  action sysMLv1ValueSpecificationAction1 {
    out result : ScalarValues::Integer = 42;
  }

  action sysMLv1ValueSpecificationAction2 {
    out result = sysMLv1OpaqueExpression.result;
    calc sysMLv1OpaqueExpression {
      language "Math"
      /*
      * 42 + 23
      */
    }
  }
}
```

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionUsage::ownedRelationship () : Relationship [0..*]`

```
let toElementFMS: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in
let toElementOMS: Set(UML::Element) =
    (from.ownedElement - toElementFMS) - Set{from.value} in
toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))
->union(toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e)))
```

#### 7.7.2.3.5.41 VSAOutputPin\_Mapping

##### Description

The mapping class creates the output parameter of the ActionUsage for the mapping of UML4SysML::ValueSpecificationAction.

##### General Mappings

Pin\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.ocIsKindOf(UML::ValueSpecificationAction)
```

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
let relationships : Set(KerML::Relationship) = self.ocIsType(Pin_Mapping).ownedRelationship
->including(VSAOutputPinFeatureValue_Mapping.getMapped(from)) in
if from.type.ocIsUndefined() then
    relationships
else
    relationships->including(TypedElementFeatureTyping_Mapping.getMapped(from))
endif
```

## General Mappings

CommonAction\_Mapping

## Mapping Source

ValueSpecificationAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  

```
let toElementFMS: Set(UML::Element) =  
    from.ownedElement->select(e | e.ocIsKindOf(UML::Pin)) in  
let toElementOMS: Set(UML::Element) =  
    (from.ownedElement - toElementFMS) - Set{from.value} in  
toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))  
->union(toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e)))
```

### 7.7.2.3.5.41 VSAOutputPin\_Mapping

#### Description

The mapping class creates the output parameter of the ActionUsage for the mapping of UML4SysML::ValueSpecificationAction.

## General Mappings

Pin\_Mapping

## Mapping Source

OutputPin

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

#### 7.7.2.3.5.42 VSAOutputPinFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

##### Mapping Source

OutputPin

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  

```
if from.owner.value.ocIsTypeOf(UML::OpaqueExpression) then
    OpaqueExpressionAsValue_Mapping.getMapped(from.owner.value)
else
    from.owner.value
endif
```

#### 7.7.2.3.6 Other Actions

##### 7.7.2.3.6.1 RaiseExceptionAction\_Mapping

##### Description

The UML4SysML::RaiseExceptionAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

RaiseExceptionAction

##### Mapping Target

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.oclIsKindOf(UML::ValueSpecificationAction)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
let relationships : Set(KerML::Relationship) = self.oclAsType(Pin_Mapping).ownedRelationship
->including(VSAOutputPinFeatureValue_Mapping.getMapped(from)) in
if from.type.oclIsUndefined() then
relationships
else
relationships->including(TypedElementFeatureTyping_Mapping.getMapped(from))
endif
```

### 7.7.2.3.5.42 VSAOutputPinFeatureValue\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a feature value relationship.

## General Mappings

ToFeatureValue Init  
Mapping

## Mapping Source

OutputPin

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

ActionUsage

### Owned Mappings

(none)

#### 7.7.2.3.6.2 ReduceAction\_Mapping

##### Description

The UML4SysML::ReduceAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

ReduceAction

##### Mapping Target

ActionUsage

### Owned Mappings

(none)

#### 7.7.2.3.7 Structural Feature Actions

##### 7.7.2.3.7.1 AddStructuralFeatureValueAction\_Mapping

##### Description

A UML4SysML::AddStructuralFeatureValueAction is mapped to a SysML v2 ActionUsage defined by the SysML v1 library action definition SysMLv1Library::AddStructuralFeatureValueAction.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action thisIsAAddStructuralFeatureValueAction : SysMLv1Library::AddStructuralFeatureValueAction {
    :>> target := object.thisIsAnAttribute;
    :>> object : ThisIsABlock;
}
part def SysMLv1Block {
    attribute sysMLv1Property;
}
```

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

AddStructuralFeatureValueAction



```

if from.owner.value.ocIsTypeOf(UML::OpaqueExpression) then
    OpaqueExpressionAsValue_Mapping.getMapped(from.owner.value)
else
    from.owner.value
endif

```

### 7.7.2.3.6 Other Actions

#### 7.7.2.3.6.1 RaiseExceptionAction\_Mapping

##### Description

The UML4SysML::RaiseExceptionAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

RaiseExceptionAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.2.3.6.2 ReduceAction\_Mapping

##### Description

The UML4SysML::ReduceAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

ReduceAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  

```
Set {ASFVAFeatureTyping_Mapping.getMapped(from),  
    ASFVATargetFeatureMembership_Mapping.getMapped(from),  
    ASFVAObjectFeatureMembership_Mapping.getMapped(from)}
```

### 7.7.2.3.7.2 ASFVAFeatureTyping\_Mapping

## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

GenericToFeatureTyping\_Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

## Applicable filters

(none)

### 7.7.2.3.7 Structural Feature Actions

#### 7.7.2.3.7.1 AddStructuralFeatureValueAction\_Mapping

##### Description

A UML4SysML::AddStructuralFeatureValueAction is mapped to a SysML v2 ActionUsage defined by the SysML v1 library action definition SysMLv1Library::AddStructuralFeatureValueAction.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action thisIsAAddStructuralFeatureValueAction : SysMLv1Library::AddStructuralFeatureValueAction {
    :>> target := object.thisIsAnAttribute;
    :>> object : ThisIsABlock;
}
part def SysMLv1Block {
    attribute sysMLv1Property;
}
```

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

AddStructuralFeatureValueAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ASFVAFeatureTyping_Mapping.getMapped(from),
ASFVATargetFeatureMembership_Mapping.getMapped(from),
ASFVAObjectFeatureMembership_Mapping.getMapped(from)}
```

#### 7.7.2.3.7.2 ASFVAFeatureTyping\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

```
SysML2::ActionDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AddStructuralFeatureValueAction')
```

#### 7.7.2.3.7.3 ASFVAObjectFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

AddStructuralFeatureValueAction

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
ASFVAObjectReferenceUsage_Mapping.getMapped(from)
```

#### 7.7.2.3.7.4 ASFVAObjectReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

UniqueMapping

**Generic**ToReferenceUsage\_Mapping

##### Mapping Source

AddStructuralFeatureValueAction

##### Mapping Target

ReferenceUsage

## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
SYSML2::ActionDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AddStructuralFeatureValueAction')
```

### 7.7.2.3.7.3 ASFVAObjectFeatureMembership\_Mapping

#### SYSML2\_-220: Replace Generic mapping classes by Initializers

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

FeatureMembership

## Owned Mappings

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{ASFVAObjectReferenceUsageRedefinition_Mapping.getMapped(from) ,  
ASFVAObjectReferenceUsageFeatureTyping_Mapping.getMapped(from) }
```

### 7.7.2.3.7.5 ASFVAObjectReferenceUsageFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**Generic**ToFeatureTyping\_Mapping

#### Mapping Source

AddStructuralFeatureValueAction

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
from.structuralFeature.owner
```

### 7.7.2.3.7.6 ASFVAObjectReferenceUsageRedefinition\_Mapping

#### Description

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`ASFVAObjectReferenceUsage_Mapping.getMapped(from)`

#### 7.7.2.3.7.4 ASFVAObjectReferenceUsage\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a reference usage.

#### General Mappings

UniqueMapping  
ToReferenceUsage\_Init

#### Mapping Source

AddStructuralFeatureValueAction

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
`Set{ASFVAObjectReferenceUsageRedefinition_Mapping.getMapped(from) ,  
ASFVAObjectReferenceUsageFeatureTyping_Mapping.getMapped(from) }`

#### 7.7.2.3.7.5 ASFVAObjectReferenceUsageFeatureTyping\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

**Generic**ToRedefinition\_Mapping

### Mapping Source

AddStructuralFeatureValueAction

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]

```
SysML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AddStructuralFeatureValueAction::object')
```

#### 7.7.2.3.7.7 ASFVATargetFeatureChainExpression\_Mapping

### Description

The mapping class creates the feature chain expression element for the target element of the UML4SysML::AddStructuralFeatureValueAction mapping.

### General Mappings

**Generic**ToFeatureChainExpression\_Mapping

### Mapping Source

AddStructuralFeatureValueAction

### Mapping Target

FeatureChainExpression

### Owned Mappings

(none)

### Applicable filters



## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`from.structuralFeature.owner`

### 7.7.2.3.7.6 ASFVAObjectReferenceUsageRedefinition\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

## General Mappings

ToRedefinition\_Init  
Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

Redefinition

## Owned Mappings

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChainExpression::ownedRelationship () : Relationship [0..*]`  

```
Set {ASFVATargetParameterMembership_Mapping.getMapped(from) ,  
ASFVATargetParameterFeatureExpressionMembership_Mapping.getMapped(from) ,  
ReturnParameterFeatureMembership_Factory.create() }
```

### 7.7.2.3.7.8 ASFVATargetFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

`GenericToFeatureMembership_Mapping`

#### Mapping Source

`AddStructuralFeatureValueAction`

#### Mapping Target

`FeatureMembership`

#### Owned Mappings

(none)

#### Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  

```
ASFVATargetReferenceUsage_Mapping.getMapped(from)
```

### 7.7.2.3.7.9 ASFVATargetFeatureValue\_Mapping

#### Description

Creates a feature value relationship.

#### General Mappings

`GenericToFeatureValue_Mapping`

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  

```
SYXML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AddStructuralFeatureValueAction::object')
```

#### 7.7.2.3.7.7 ASFVATargetFeatureChainExpression\_Mapping

#### SYXML2\_-220: Replace Generic mapping classes by Initializers

#### Description

The mapping class creates the feature chain expression element for the target element of the UML4SysML::AddStructuralFeatureValueAction mapping.

#### General Mappings

ToFeatureChainExpression\_Init  
Mapping

#### Mapping Source

AddStructuralFeatureValueAction

#### Mapping Target

FeatureChainExpression

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChainExpression::ownedRelationship () : Relationship [0..*]`  

```
Set{ASFVATargetParameterMembership_Mapping.getMapped(from),  
ASFVATargetParameterFeatureExpressionMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  
`ASFVATargetFeatureChainExpression_Mapping.getMapped(from)`
- FeatureValue::isInitial () : Boolean [1]  
`true`

### 7.7.2.3.7.10 ASFVATargetParameterExpressionFeature\_Mapping

#### Description

The mapping class creates the feature element of the feature reference expression for the target element of the UML4SysML::AddStructuralFeatureValueAction mapping.

#### General Mappings

**Generic**ToFeature\_Mapping

#### Mapping Source

AddStructuralFeatureValueAction

#### Mapping Target

Feature

#### Owned Mappings

(none)

### 7.7.2.3.7.11 ASFVATargetParameterExpressionFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### 7.7.2.3.7.8 ASFVATargetFeatureMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

AddStructuralFeatureValueAction

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`ASFVATargetReferenceUsage_Mapping.getMapped(from)`

#### 7.7.2.3.7.9 ASFVATargetFeatureValue\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature value relationship.

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

AddStructuralFeatureValueAction

##### Mapping Target



FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  
`ASFVATargetFeatureChainExpression_Mapping.getMapped (from)`
- FeatureValue::isInitial () : Boolean [1]  
`true`

#### 7.7.2.3.7.10 ASFVATargetParameterExpressionFeature\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the feature element of the feature reference expression for the target element of the UML4SysML::AddStructuralFeatureValueAction mapping.

### General Mappings

ToFeature\_Init  
Mapping

### Mapping Source

AddStructuralFeatureValueAction

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

#### 7.7.2.3.7.11 ASFVATargetParameterExpressionFeatureMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## General Mappings

GenericToFeatureMembership\_Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`ASFVATargetParameterExpressionFeature_Mapping.getMapped(from)`

### 7.7.2.3.7.12 ASFVATargetParameterExpressionMembership\_Mapping

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

GenericToMembership\_Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

Membership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules



## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`ASFVATargetParameterExpressionFeature_Mapping.getMapped(from)`

### 7.7.2.3.7.12 ASFVATargetParameterExpressionMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToMembership\_Init  
Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

Membership

## Owned Mappings

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

```
ASFVAObjectReferenceUsage_Mapping.getMapped(from)
```

#### 7.7.2.3.7.13 ASFVATargetParameterFeature\_Mapping

##### Description

The mapping class creates the feature element for the target element of the UML4SysML::AddStructuralFeatureValueAction mapping.

##### General Mappings

GenericToFeature\_Mapping

##### Mapping Source

AddStructuralFeatureValueAction

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
Set { ASFVATargetParameterFeatureValue_Mapping.getMapped(from) ,  
ASFVATargetParameterExpressionFeatureMembership_Mapping.getMapped(from) }
```

- Feature::direction () : FeatureDirectionKind [0..1]

```
KerML::FeatureDirectionKind::_in'
```

#### 7.7.2.3.7.14 ASFVATargetParameterFeatureExpressionMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToMembership\_Mapping

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
`ASFVAObjectReferenceUsage_Mapping.getMapped(from)`

#### 7.7.2.3.7.13 ASFVATargetParameterFeature\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates the feature element for the target element of the UML4SysML::AddStructuralFeatureValueAction mapping.

#### General Mappings

ToFeature\_Init  
Mapping

#### Mapping Source

AddStructuralFeatureValueAction

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::direction () : FeatureDirectionKind [0..1]  
`KerML::FeatureDirectionKind::_in'`
- Feature::ownedRelationship () : Relationship [0..\*]

### Mapping Source

AddStructuralFeatureValueAction

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
`from. structuralFeature`

#### 7.7.2.3.7.15 ASFVATargetParameterFeatureReferenceExpression\_Mapping

### Description

The mapping class creates the feature reference expression element for the target element of the UML4SysML::AddStructuralFeatureValueAction mapping.

### General Mappings

**Generic**ToFeatureReferenceExpression\_Mapping

### Mapping Source

AddStructuralFeatureValueAction

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

```
Set{ASFVATargetParameterFeatureValue_Mapping.getMapped(from),
ASFVATargetParameterExpressionFeatureMembership_Mapping.getMapped(from)}
```

#### 7.7.2.3.7.14 ASFVATargetParameterFeatureExpressionMembership\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToMembership\_Init  
Mapping

##### Mapping Source

AddStructuralFeatureValueAction

##### Mapping Target

Membership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
  
from.structuralFeature

#### 7.7.2.3.7.15 ASFVATargetParameterFeatureReferenceExpression\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates the feature reference expression element for the target element of the UML4SysML::AddStructuralFeatureValueAction mapping.

##### General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

##### Mapping Source

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set {ASFVATargetParameterExpressionMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.7.16 ASFVATargetParameterFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

`GenericToFeatureValue_Mapping`

##### Mapping Source

`AddStructuralFeatureValueAction`

##### Mapping Target

`FeatureValue`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
ASFVATargetParameterFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.7.17 ASFVATargetParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

`GenericToParameterMembership_Mapping`

##### Mapping Source

`AddStructuralFeatureValueAction`

AddStructuralFeatureValueAction

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{ASFVATargetParameterExpressionMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.7.16 ASFVATargetParameterFeatureValue\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_Init  
Mapping

### Mapping Source

AddStructuralFeatureValueAction

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

### Mapping Target

ParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::visibility () : VisibilityKind [1]  
`KerML::VisibilityKind::private`
- ParameterMembership::ownedMemberParameter () : Feature [1]  
`ASFVATargetParameterFeature_Mapping.getMapped(from)`

#### 7.7.2.3.7.18 ASFVATargetReferenceUsage\_Mapping

### Description

Creates a reference usage.

### General Mappings

**Generic**ToReferenceUsage\_Mapping

### Mapping Source

AddStructuralFeatureValueAction

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules



In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

`ASFVATargetParameterFeatureReferenceExpression_Mapping.getMapped (from)`

#### 7.7.2.3.7.17 ASFVATargetParameterMembership\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

###### Description

Creates a membership relationship for *memberElement()*.

###### General Mappings

ToParameterMembership\_Init  
Mapping

###### Mapping Source

AddStructuralFeatureValueAction

###### Mapping Target

ParameterMembership

###### Owned Mappings

(none)

###### Applicable filters

(none)

###### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ParameterMembership::visibility () : VisibilityKind [1]`

`KerML::VisibilityKind::private`

- `ParameterMembership::ownedMemberParameter () : Feature [1]`

`ASFVATargetParameterFeature_Mapping.getMapped (from)`

#### 7.7.2.3.7.18 ASFVATargetReferenceUsage\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

###### Description

Creates a reference usage.

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{ASFVATargetReferenceUsageRedefinition_Mapping.getMapped(from),
ASFVATargetFeatureValue_Mapping.getMapped(from),
AssignmentActionUsageOwningMembership_Factory.create() }
```

#### 7.7.2.3.7.19 ASFVATargetReferenceUsageRedefinition\_Mapping

##### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

##### General Mappings

GenericToRedefinition\_Mapping

##### Mapping Source

AddStructuralFeatureValueAction

##### Mapping Target

Redefinition

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::ReferenceUsage.allInstances()
->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction::target')
```

#### 7.7.2.3.7.20 ClearStructuralFeatureAction\_Mapping

##### Description

The UML4SysML::ClearStructuralFeatureAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

## General Mappings

ToReferenceUsage\_**Init**  
Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ASFVATargetReferenceUsageRedefinition_Mapping.getMapped(from) ,  
ASFVATargetFeatureValue_Mapping.getMapped(from) ,  
AssignmentActionUsageOwningMembership_Factory.create() }
```

### 7.7.2.3.7.19 ASFVATargetReferenceUsageRedefinition\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

## General Mappings

ToRedefinition\_**Init**  
Mapping

## Mapping Source

AddStructuralFeatureValueAction

## Mapping Target

Redefinition

## Owned Mappings

(none)

ClearStructuralFeatureAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

#### 7.7.2.3.7.21 ReadStructuralFeatureAction\_Mapping

### Description

A UML4SysML::ReadStructuralFeatureAction is mapped to a SysML v2 ActionUsage that returns the value of the specified structural feature of the given object.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    action sysMLv1ReadStructuralFeatureAction {  
        in object : SysMLv1Block;  
        out result = object.sysMLv1Property;  
    }  
}  
part def SysMLv1Block {  
    attribute sysMLv1Property;  
}
```

### General Mappings

CommonAction\_Mapping

### Mapping Source

ReadStructuralFeatureAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  
`SysML2::ReferenceUsage.allInstances()`  
`->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction::target')`

### 7.7.2.3.7.20 ClearStructuralFeatureAction\_Mapping

#### Description

The UML4SysML::ClearStructuralFeatureAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

#### General Mappings

CommonAction\_Mapping

#### Mapping Source

ClearStructuralFeatureAction

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

## Applicable filters

(none)

### 7.7.2.3.7.21 ReadStructuralFeatureAction\_Mapping

#### Description

A UML4SysML::ReadStructuralFeatureAction is mapped to a SysML v2 ActionUsage that returns the value of the specified structural feature of the given object.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
    action sysMLv1ReadStructuralFeatureAction {
        in object : SysMLv1Block;
        out result = object.sysMLv1Property;
    }
}
part def SysMLv1Block {
```

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionUsage::ownedRelationship () : Relationship [0..*]`

```
Helper.actionOwnedRelationship (from)
->including (RSFAReferenceUsageFeatureMembership_Mapping.getMapped (from) )
```

#### 7.7.2.3.7.22 RSFAReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

`GenericToReferenceUsage_Mapping`

##### Mapping Source

`ReadStructuralFeatureAction`

##### Mapping Target

`ReferenceUsage`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`

```
KerML::FeatureDirectionKind::_out'
```

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set { RSFAReferenceUsageFeatureValue_Mapping.getMapped (from) }
```

#### 7.7.2.3.7.23 RSFAReferenceUsageExpressionFeature\_Mapping

##### Description

The mapping class creates the feature of the feature chain expression for the reference usage of the `UML4SysML::ReadStructuralFeatureValueAction` mapping.

##### General Mappings

`GenericToFeature_Mapping`

```

        attribute sysMLv1Property;
    }

```

## General Mappings

CommonAction\_Mapping

## Mapping Source

ReadStructuralFeatureAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```

Helper.actionOwnedRelationship (from)
->including (RSFAReferenceUsageFeatureMembership_Mapping.getMapped (from) )

```

### 7.7.2.3.7.22 RSFAReferenceUsage\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Creates a reference usage.

## General Mappings

ToReferenceUsage\_Init  
Mapping

## Mapping Source

ReadStructuralFeatureAction

## Mapping Target

ReferenceUsage

## Owned Mappings

### Mapping Source

ReadStructuralFeatureAction

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
Set { RSFAReferenceUsageExpressionFeatureValue_Mapping.getMapped (from) ,  
      RSFAReferenceUsageExpressionFeatureMembership_Mapping.getMapped (from) }
```

#### 7.7.2.3.7.24 RSFAReferenceUsageExpressionFeatureMembership\_Mapping

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

GenericToFeatureMembership\_Mapping

### Mapping Source

ReadStructuralFeatureAction

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{RSFAReferenceUsageFeatureValue_Mapping.getMapped(from) }`
- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_out'`

#### 7.7.2.3.7.23 RSFAReferenceUsageExpressionFeature\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates the feature of the feature chain expression for the reference usage of the UML4SysML::ReadStructuralFeatureValueAction mapping.

#### General Mappings

ToFeature\_**Init**  
Mapping

#### Mapping Source

ReadStructuralFeatureAction

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
RSFAReferenceUsageFeatureChainExpressionFeature_Mapping.getMapped(from)
```

#### 7.7.2.3.7.25 RSFAReferenceUsageExpressionFeatureReferenceExpression\_Mapping

##### Description

The mapping class creates the feature reference expression element for the UML4SysML::RemoveStructuralFeatureValueAction mapping.

##### General Mappings

**Generic**ToFeatureReferenceExpression\_Mapping

##### Mapping Source

ReadStructuralFeatureAction

##### Mapping Target

FeatureReferenceExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]

```
Set { RSFAReferenceUsageExpressionFeatureMembership_Mapping.getMapped(from) ,  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.7.26 RSFAReferenceUsageExpressionFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

##### Mapping Source

ReadStructuralFeatureAction

```
Set{RSFAReferenceUsageExpressionFeatureValue_Mapping.getMapped(from),
RSFAReferenceUsageExpressionFeatureMembership_Mapping.getMapped(from)}
```

#### 7.7.2.3.7.24 RSFAReferenceUsageExpressionFeatureMembership\_Mapping

##### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

ReadStructuralFeatureAction

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
RSFAReferenceUsageFeatureChainExpressionFeature_Mapping.getMapped(from)
```

#### 7.7.2.3.7.25 RSFAReferenceUsageExpressionFeatureReferenceExpression\_Mapping

##### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class creates the feature reference expression element for the UML4SysML::RemoveStructuralFeatureValueAction mapping.

##### General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

##### Mapping Source

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
RSFReferenceUsageExpressionFeatureReferenceExpression_Mapping.getMapped(from)
```

### 7.7.2.3.7.27 RSFReferenceUsageFeatureChainExpression\_Mapping

#### Description

The mapping class creates the feature chain expression element for the reference usage of the UML4SysML::ReadStructuralFeatureValueAction mapping.

#### General Mappings

**Generic**ToFeatureChainExpression\_Mapping

#### Mapping Source

ReadStructuralFeatureAction

#### Mapping Target

FeatureChainExpression

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChainExpression::ownedRelationship () : Relationship [0..\*]

ReadStructuralFeatureAction

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set { RSFAResourceUsageExpressionFeatureMembership_Mapping.getMapped (from) ,  
ReturnParameterFeatureMembership_Factory.create () }
```

#### 7.7.2.3.7.26 RSFAResourceUsageExpressionFeatureValue\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_Init  
Mapping

### Mapping Source

ReadStructuralFeatureAction

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

```

Set { RSFAReferenceUsageParameterMembership_Mapping.getMapped(from) ,
RSFAReferenceUsageMembership_Mapping.getMapped(from) ,
ReturnParameterFeatureMembership_Factory.create() }

```

#### 7.7.2.3.7.28 RSFAReferenceUsageFeatureChainExpressionFeature\_Mapping

##### Description

The mapping class creates the feature element for the feature chain expression for the UML4SysML::RemoveStructuralFeatureValueAction mapping.

##### General Mappings

**Generic**ToFeature\_Mapping

##### Mapping Source

ReadStructuralFeatureAction

##### Mapping Target

Feature

##### Owned Mappings

(none)

#### 7.7.2.3.7.29 RSFAReferenceUsageFeatureChainExpressionMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic**ToMembership\_Mapping

##### Mapping Source

ReadStructuralFeatureAction

##### Mapping Target

Membership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
RSFAReferenceUsageExpressionFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.7.27 RSFAReferenceUsageFeatureChainExpression\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class creates the feature chain expression element for the reference usage of the UML4SysML::ReadStructuralFeatureValueAction mapping.

##### General Mappings

ToFeatureChainExpression\_Init  
Mapping

##### Mapping Source

ReadStructuralFeatureAction

##### Mapping Target

FeatureChainExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChainExpression::ownedRelationship () : Relationship [0..*]`

```
Set{RSFAReferenceUsageParameterMembership_Mapping.getMapped(from),  
RSFAReferenceUsageMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.7.28 RSFAReferenceUsageFeatureChainExpressionFeature\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class creates the feature element for the feature chain expression for the UML4SysML::RemoveStructuralFeatureValueAction mapping.

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

`from.structuralFeature`

#### 7.7.2.3.7.30 RSFAReferenceUsageFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

ReadStructuralFeatureAction

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

`RSFAReferenceUsageFeatureValue_Mapping.getMapped(from)`

#### 7.7.2.3.7.31 RSFAReferenceUsageFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

##### Mapping Source

ReadStructuralFeatureAction

##### Mapping Target



## General Mappings

ToFeature\_Init  
Mapping

## Mapping Source

ReadStructuralFeatureAction

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

### 7.7.2.3.7.29 RSFReferenceUsageFeatureChainExpressionMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToMembership\_Init  
Mapping

## Mapping Source

ReadStructuralFeatureAction

## Mapping Target

Membership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]



```
from.structuralFeature
```

#### 7.7.2.3.7.30 RSFAReferenceUsageFeatureMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

ReadStructuralFeatureAction

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
RSFAReferenceUsageFeatureValue_Mapping.getMapped(from)
```

#### 7.7.2.3.7.31 RSFAReferenceUsageFeatureValue\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature value relationship.

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

ReadStructuralFeatureAction

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
RSFAReferenceUsageFeatureChainExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.7.32 RSFAReferenceUsageMembership\_Mapping

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

GenericToMembership\_Mapping

### Mapping Source

ReadStructuralFeatureAction

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

```
from.object
```

#### 7.7.2.3.7.33 RSFAReferenceUsageParameterMembership\_Mapping

### Description

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

`RSFAReferenceUsageFeatureChainExpression_Mapping.getMapped(from)`

### 7.7.2.3.7.32 RSFAReferenceUsageMembership\_Mapping

### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

ReadStructuralFeatureAction

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

Creates a membership relationship for *memberElement()*.

### General Mappings

**Generic**ToParameterMembership\_Mapping

### Mapping Source

ReadStructuralFeatureAction

### Mapping Target

ParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`RSFReferenceUsageExpressionFeature_Mapping.getMapped (from)`

#### 7.7.2.3.7.34 RemoveStructuralFeatureValueAction\_Mapping

### Description

The UML4SysML::RemoveStructuralFeatureValueAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

### General Mappings

CommonAction\_Mapping

### Mapping Source

RemoveStructuralFeatureValueAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

#### 7.7.2.3.8 Structured Actions

`from.object`

#### 7.7.2.3.7.33 RSFAReferenceUsageParameterMembership\_Mapping

##### SYSML2\_-220: Replace Generic mapping classes by Initializers

###### Description

Creates a membership relationship for *memberElement()*.

###### General Mappings

ToParameterMembership\_Init  
Mapping

###### Mapping Source

ReadStructuralFeatureAction

###### Mapping Target

ParameterMembership

###### Owned Mappings

(none)

###### Applicable filters

(none)

###### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`RSFAReferenceUsageExpressionFeature_Mapping.getMapped(from)`

#### 7.7.2.3.7.34 RemoveStructuralFeatureValueAction\_Mapping

###### Description

The UML4SysML::RemoveStructuralFeatureValueAction is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

###### General Mappings

CommonAction\_Mapping

###### Mapping Source

RemoveStructuralFeatureValueAction

###### Mapping Target

#### **7.7.2.3.8.1 LoopNode\_Mapping**

##### **Description**

The UML4SysML::LoopNode is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### **General Mappings**

StructuredActivityNode\_Mapping

##### **Mapping Source**

LoopNode

##### **Mapping Target**

ActionUsage

##### **Owned Mappings**

(none)

#### **7.7.2.3.8.2 SequenceNode\_Mapping**

##### **Description**

The UML4SysML::SequenceNode is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### **General Mappings**

CommonAction\_Mapping

StructuredActivityNode\_Mapping

##### **Mapping Source**

SequenceNode

##### **Mapping Target**

ActionUsage

##### **Owned Mappings**

(none)

#### **7.7.2.3.8.3 StructuredActivityNode\_Mapping**

##### **Description**

The UML4SysML::StructuredActivityNode is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### **General Mappings**



ActionUsage

#### **Owned Mappings**

(none)

#### **Applicable filters**

(none)

### **7.7.2.3.8 Structured Actions**

#### **7.7.2.3.8.1 LoopNode\_Mapping**

##### **Description**

The UML4SysML::LoopNode is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### **General Mappings**

StructuredActivityNode\_Mapping

##### **Mapping Source**

LoopNode

##### **Mapping Target**

ActionUsage

##### **Owned Mappings**

(none)

#### **Applicable filters**

(none)

#### **7.7.2.3.8.2 SequenceNode\_Mapping**

##### **Description**

The UML4SysML::SequenceNode is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

##### **General Mappings**

CommonAction\_Mapping

StructuredActivityNode\_Mapping

##### **Mapping Source**

SequenceNode

##### **Mapping Target**

ActionUsage

CommonAction\_Mapping

## Mapping Source

StructuredActivityNode

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
let initialNodes : Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::InitialNode)) in
let finalNodes : Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::FinalNode)) in
let objectFlowsWithGuard : Set(UML::ObjectFlow) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::ObjectFlow)
    and not e.ocIsType(UML::ObjectFlow).guard.ocIsUndefined()) in
let objectFlows : Set(UML::ObjectFlow) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::ObjectFlow)) in
let ignoreInterruptibleActivityRegion: Set(UML::InterruptibleActivityRegion) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::InterruptibleActivityRegion)) in
let elementsFMS : Set(UML::Element) =
  ((from.ownedElement->select(e | e.ocIsKindOf(UML::ControlNode) or
    e.ocIsKindOf(UML::Action) or (e.ocIsKindOf(UML::ControlFlow) or
    e.ocIsKindOf(UML::Pin))) - initialNodes) - finalNodes) in
let elementsOMS: Set(UML::Element) =
  ((((((from.ownedElement-initialNodes)-finalNodes)-objectFlowsWithGuard)
    -objectFlows)-elementsFMS)-ignoreInterruptibleActivityRegion) in
elementsOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(elementsFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(initialNodes->collect(e | InitialNodeMembership_Mapping.getMapped(e)))
->union(finalNodes->collect(e | FlowFinalNodeMembership_Mapping.getMapped(e)))
->union(objectFlowsWithGuard
  ->collect(e | ObjectFlowGuardFeatureMembership_Mapping.getMapped(e)))
->union(objectFlows->collect(e | ObjectFlowFeatureMembership_Mapping.getMapped(e)))
```

### 7.7.2.3.9 Variable Actions

#### 7.7.2.3.9.1 AddVariableValueAction\_Mapping

##### Description

## Owned Mappings

(none)

## Applicable filters

(none)

### 7.7.2.3.8.3 StructuredActivityNode\_Mapping

#### Description

The UML4SysML::StructuredActivityNode is mapped to a SysML v2 ActionUsage. The details of the mapping are not defined yet.

#### General Mappings

CommonAction\_Mapping

#### Mapping Source

StructuredActivityNode

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

## Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```
let initialNodes : Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::InitialNode)) in
let finalNodes : Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::FinalNode)) in
let objectFlowsWithGuard : Set(UML::ObjectFlow) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::ObjectFlow)
    and not e.ocIsType(UML::ObjectFlow).guard.ocIsUndefined()) in
let objectFlows : Set(UML::ObjectFlow) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::ObjectFlow)) in
let ignoreInterruptibleActivityRegion: Set(UML::InterruptibleActivityRegion) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::InterruptibleActivityRegion)) in
let elementsFMS : Set(UML::Element) =
  (((from.ownedElement->select(e | e.ocIsKindOf(UML::ControlNode) or
    e.ocIsKindOf(UML::Action) or (e.ocIsKindOf(UML::ControlFlow) or
    e.ocIsKindOf(UML::Pin))) - initialNodes) - finalNodes) in
let elementsOMS: Set(UML::Element) =
  ((((((from.ownedElement-initialNodes)-finalNodes)-objectFlowsWithGuard)
```

A UML4SysML::AddVariableValueAction is mapped to a SysML v2 ActionUsage defined by the SysML v1 library action definition SysMLv1Library::AddValueAction. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action def SysMLv1Activity {
  private attribute sysMLv1Variable1 : ScalarValues::Integer;
  private attribute sysMLv1Variable2 [0..*] : ScalarValues::Integer;

  action sysMLv1AddVariableValueAction1 : SysMLv1Library::AddValueAction {
    :>> target := sysMLv1Variable1;
  }

  action sysMLv1AddVariableValueAction1 : SysMLv1Library::AddValueAction {
    :>> target := thisIsAVariable;
    :>> isReplaceAll := true;
  }
}

```

## General Mappings

CommonAction\_Mapping

### Mapping Source

AddVariableValueAction

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```

let relationships : Set(KerML::Relationship) =
Set{AVVAFeatureTyping_Mapping.getMapped(from)}
->including(AVVAVariableFeatureMembership_Mapping.getMapped(from)) in
if from.isReplaceAll then
  relationships->including(AVVAIsReplaceAllFeatureMembership_Mapping.getMapped(from))
else
  relationships
endif

```

```

        -objectFlows)-elementsFMS)-ignoreInterruptibleActivityRegion) in
elementsOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(elementsFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(initialNodes->collect(e | InitialNodeMembership_Mapping.getMapped(e)))
->union(finalNodes->collect(e | FlowFinalNodeMembership_Mapping.getMapped(e)))
->union(objectFlowsWithGuard
    ->collect(e | ObjectFlowGuardFeatureMembership_Mapping.getMapped(e)))
->union(objectFlows->collect(e | ObjectFlowFeatureMembership_Mapping.getMapped(e)))

```

### 7.7.2.3.9 Variable Actions

#### 7.7.2.3.9.1 AddVariableValueAction\_Mapping

##### Description

A UML4SysML::AddVariableValueAction is mapped to a SysML v2 ActionUsage defined by the SysML v1 library action definition SysMLv1Library::AddValueAction. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action def SysMLv1Activity {
    private attribute sysMLv1Variable1 : ScalarValues::Integer;
    private attribute sysMLv1Variable2 [0..*] : ScalarValues::Integer;

    action sysMLv1AddVariableValueAction1 : SysMLv1Library::AddValueAction {
        :>> target := sysMLv1Variable1;
    }

    action sysMLv1AddVariableValueAction1 : SysMLv1Library::AddValueAction {
        :>> target := thisIsAVariable;
        :>> isReplaceAll := true;
    }
}

```

##### General Mappings

CommonAction\_Mapping

##### Mapping Source

AddVariableValueAction

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

#### 7.7.2.3.9.2 AVVAFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

**Generic**ToFeatureTyping\_Mapping

##### Mapping Source

AddVariableValueAction

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
SysML2::ActionDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction')
```

#### 7.7.2.3.9.3 AVVAFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

##### Mapping Source

AddVariableValueAction

##### Mapping Target

FeatureValue

##### Owned Mappings

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionUsage::ownedRelationship () : Relationship [0..*]`

```
let relationships : Set(KerML::Relationship) =
  Set{AVVAFeatureTyping_Mapping.getMapped(from)}
->including(AVVAVariableFeatureMembership_Mapping.getMapped(from)) in
if from.isReplaceAll then
  relationships->including(AVVAIsReplaceAllFeatureMembership_Mapping.getMapped(from))
else
  relationships
endif
```

#### 7.7.2.3.9.2 AVVAFeatureTyping\_Mapping

##### SYSML2 -220: Replace Generic mapping classes by Initializers

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

ToFeatureTyping\_Init  
Mapping

##### Mapping Source

AddVariableValueAction

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SYSML2::ActionDefinition.allInstances()
->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction')
```

#### 7.7.2.3.9.3 AVVAFeatureValue\_Mapping

##### SYSML2 -220: Replace Generic mapping classes by Initializers

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
AVVAValueFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.9.4 AVVAIsReplaceAll\_Mapping

##### Description

The mapping class creates a reference usage element as mapping target for the `AddVariableValueAction::isReplaceAll` property.

##### General Mappings

`GenericToReferenceUsage_Mapping`

##### Mapping Source

`AddVariableValueAction`

##### Mapping Target

`ReferenceUsage`

##### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{AVVAIsReplaceAllRedefinition_Mapping.getMapped(from),  
AVVAIsReplaceAllValue_Mapping.getMapped(from),  
AssignmentActionUsageOwningMembership_Factory.create() }
```

#### 7.7.2.3.9.5 AVVAIsReplaceAllFeatureMembership\_Mapping

##### Description



## Description

Creates a feature value relationship.

## General Mappings

ToFeatureValue\_Init  
Mapping

## Mapping Source

AddVariableValueAction

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
AVVAValueFeatureReferenceExpression_Mapping.getMapped (from)
```

### 7.7.2.3.9.4 AVVAIsReplaceAll\_Mapping

## **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

The mapping class creates a reference usage element as mapping target for the AddVariableValueAction::isReplaceAll property.

## General Mappings

ToReferenceUsage\_Init  
Mapping

## Mapping Source

AddVariableValueAction

## Mapping Target

ReferenceUsage

## Owned Mappings

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

**Generic**ToFeatureMembership\_Mapping

### Mapping Source

AddVariableValueAction

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`AVVAIsReplaceAll_Mapping.getMapped(from)`

### 7.7.2.3.9.6 AVVAIsReplaceAllRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

**Generic**ToRedefinition\_Mapping

### Mapping Source

AddVariableValueAction

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  

```
Set{AVVAIsReplaceAllRedefinition_Mapping.getMapped(from),  
AVVAIsReplaceAllValue_Mapping.getMapped(from),  
AssignmentActionUsageOwningMembership_Factory.create() }
```

#### 7.7.2.3.9.5 AVVAIsReplaceAllFeatureMembership\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

AddVariableValueAction

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  

```
AVVAIsReplaceAll_Mapping.getMapped(from)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction::isReplaceAll')
```

### 7.7.2.3.9.7 AVVAIsReplaceAllValue\_Mapping

#### Description

The mapping class maps the value of the `AddVariableValueAction::isReplaceAll` property.

#### General Mappings

**GenericToFeatureValue\_Mapping**

#### Mapping Source

`AddVariableValueAction`

#### Mapping Target

`FeatureValue`

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
LiteralBoolean_Factory.create(from.isReplaceAll)
```

### 7.7.2.3.9.8 AVVAValueExpressionMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

**GenericToMembership\_Mapping**

#### Mapping Source

#### 7.7.2.3.9.6 AVVAIsReplaceAllRedefinition\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

ToRedefinition\_Init  
Mapping

#### Mapping Source

AddVariableValueAction

#### Mapping Target

Redefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]  
  

```
SYSML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction::isReplaceAll')
```

#### 7.7.2.3.9.7 AVVAIsReplaceAllValue\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

The mapping class maps the value of the AddVariableValueAction::isReplaceAll property.

#### General Mappings

ToFeatureValue\_Init  
Mapping

#### Mapping Source

AddVariableValueAction

#### Mapping Target

AddVariableValueAction

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

from.variable

#### 7.7.2.3.9.9 AVVAValueFeatureReferenceExpression\_Mapping

### Description

The mapping class creates the feature reference expression element for the UML4SysML::AddStructuralFeatureValueAction mapping.

### General Mappings

GenericToFeatureReferenceExpression\_Mapping

### Mapping Source

AddVariableValueAction

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  
`LiteralBoolean_Factory.create(from.isReplaceAll)`

#### 7.7.2.3.9.8 AVVAValueExpressionMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

AddVariableValueAction

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
`from.variable`

```
Set{AVVAValueExpressionMembership_Mapping.getMapped(from) ,
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.9.10 AVVAVariable\_Mapping

##### Description

The mapping class creates a reference usage element for the UML4SysML::AddVariableValueAction mapping.

##### General Mappings

**Generic**ToReferenceUsage\_Mapping

##### Mapping Source

AddVariableValueAction

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set{AVVAVariableRedefinition_Mapping.getMapped(from) ,
AVVAFeatureValue_Mapping.getMapped(from) ,
AssignmentActionUsageOwningMembership_Factory.create() }
```

#### 7.7.2.3.9.11 AVVAVariableFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

AddVariableValueAction

##### Mapping Target

FeatureMembership



#### 7.7.2.3.9.9 AVVAValueFeatureReferenceExpression\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

##### Description

The mapping class creates the feature reference expression element for the UML4SysML::AddStructuralFeatureValueAction mapping.

##### General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

##### Mapping Source

AddVariableValueAction

##### Mapping Target

FeatureReferenceExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{AVVAValueExpressionMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.9.10 AVVAVariable\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

##### Description

The mapping class creates a reference usage element for the UML4SysML::AddVariableValueAction mapping.

##### General Mappings

ToReferenceUsage\_Init  
Mapping

##### Mapping Source

AddVariableValueAction

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
AVVAVariable_Mapping.getMapped(from)
```

### 7.7.2.3.9.12 AVVAVariableRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

`GenericToRedefinition_Mapping`

#### Mapping Source

`AddVariableValueAction`

#### Mapping Target

`Redefinition`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction::target')
```

### 7.7.2.3.9.13 ClearVariableAction\_Mapping

#### Description

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  

```
Set{AVVAVariableRedefinition_Mapping.getMapped(from),  
AVVAFeatureValue_Mapping.getMapped(from),  
AssignmentActionUsageOwningMembership_Factory.create() }
```

### 7.7.2.3.9.11 AVVAVariableFeatureMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

AddVariableValueAction

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

The UML4SysML::ClearVariableAction is mapped to a SysML v2 ActionUsage that sets the attribute usage representing the variable to null.

The expected SysML v2 textual notation of a SysMLv1::ClearVariableAction is as follows

```
action def SysMLv1Activity {  
    private attribute sysMLv1Variable : ScalarValues::Integer;  
  
    action sysMLv1ClearVariableAction {  
        sysMLv1Variable := null;  
    }  
}
```

## General Mappings

CommonAction\_Mapping

## Mapping Source

ClearVariableAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  
  
    Helper.actionOwnedRelationship (from)  
    ->including (CVAFeatureMembership\_Mapping.getMapped (from) )

### 7.7.2.3.9.14 CVAFeatureMembership\_Mapping

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

GenericToFeatureMembership\_Mapping

## Mapping Source

ClearVariableAction

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
AVVAVariable_Mapping.getMapped(from)
```

#### 7.7.2.3.9.12 AVVAVariableRedefinition\_Mapping

### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### **Description**

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### **General Mappings**

ToRedefinition\_Init  
Mapping

#### **Mapping Source**

AddVariableValueAction

#### **Mapping Target**

Redefinition

#### **Owned Mappings**

(none)

#### **Applicable filters**

(none)

#### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]

```
SYSML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction::target')
```

#### 7.7.2.3.9.13 ClearVariableAction\_Mapping

#### **Description**

The UML4SysML::ClearVariableAction is mapped to a SysML v2 ActionUsage that sets the attribute usage representing the variable to null.

The expected SysML v2 textual notation of a SysMLv1::ClearVariableAction is as follows

```
action def SysMLv1Activity {  
    private attribute sysMLv1Variable : ScalarValues::Integer;
```

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`CVAReferenceUsage_Mapping.getMapped(from)`

#### 7.7.2.3.9.15 CVAReferenceUsage\_Mapping

### Description

Creates a reference usage.

### General Mappings

**Generic**ToReferenceUsage\_Mapping

### Mapping Source

ClearVariableAction

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::declaredName () : String [0..1]  
`from.variable.name`

```

        action sysMLv1ClearVariableAction {
            sysMLv1Variable := null;
        }
    }

```

## General Mappings

CommonAction\_Mapping

## Mapping Source

ClearVariableAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

```

Helper.actionOwnedRelationship (from)
->including (CVAFeatureMembership_Mapping.getMapped (from) )

```

### 7.7.2.3.9.14 CVAFeatureMembership\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

ClearVariableAction

## Mapping Target

FeatureMembership

## Owned Mappings

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set { CVAReferenceUsageFeatureValue_Mapping.getMapped(from),
AssignmentActionUsageOwningMembership_Factory.create() }
```

#### 7.7.2.3.9.16 CVAReferenceUsageFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic** ToFeatureValue\_Mapping

##### Mapping Source

ClearVariableAction

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
LiteralNull_Factory.create()
```

#### 7.7.2.3.9.17 ReadVariableAction\_Mapping

##### Description

A `UML4SysML::ReadVariableValueAction` is mapped to a SysML v2 `ActionUsage` with an out parameter that returns the value of the attribute usage that is the transformation target of the `UML4SysML::Variable`.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
  private attribute sysMLv1Variable : ScalarValues::Integer;

  action sysMLv1ReadVariableAction {
    out result : ScalarValues::Integer = sysMLv1Variable;
  }
}
```



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
CVAReferenceUsage_Mapping.getMapped(from)
```

#### 7.7.2.3.9.15 CVAReferenceUsage\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a reference usage.

#### General Mappings

ToReferenceUsage\_Init  
Mapping

#### Mapping Source

ClearVariableAction

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{CVAReferenceUsageFeatureValue_Mapping.getMapped(from),  
AssignmentActionUsageOwningMembership_Factory.create() }
```

- `ReferenceUsage::declaredName () : String [0..1]`

```
from.variable.name
```



#### 7.7.2.3.9.16 CVAReferenceUsageFeatureValue\_Mapping

##### **SysML2\_-220: Replace Generic mapping classes by Initializers**

#### **Description**

Creates a feature value relationship.

#### **General Mappings**

ToFeatureValue\_Init  
Mapping

#### **Mapping Source**

ClearVariableAction

#### **Mapping Target**

FeatureValue

#### **Owned Mappings**

(none)

#### **Applicable filters**

(none)

#### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
LiteralNull_Factory.create()
```

#### 7.7.2.3.9.17 ReadVariableAction\_Mapping

#### **Description**

A UML4SysML::ReadVariableValueAction is mapped to a SysML v2 ActionUsage with an out parameter that returns the value of the attribute usage that is the transformation target of the UML4SysML::Variable.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    private attribute sysMLv1Variable : ScalarValues::Integer;  
  
    action sysMLv1ReadVariableAction {  
        out result : ScalarValues::Integer = sysMLv1Variable;  
    }  
}
```

#### **General Mappings**

## General Mappings

CommonAction\_Mapping

## Mapping Source

ReadVariableAction

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  
`Set{RVAFeatureMembership_Mapping.getMapped(from)}`

### 7.7.2.3.9.18 RVAFeatureMembership\_Mapping

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

GenericToFeatureMembership\_Mapping

## Mapping Source

ReadVariableAction

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

CommonAction\_Mapping

#### Mapping Source

ReadVariableAction

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  
`Set{RVAFeatureMembership_Mapping.getMapped(from) }`

#### 7.7.2.3.9.18 RVAFeatureMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

ReadVariableAction

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
RVReferenceUsage_Mapping.getMapped(from.result)
```

### 7.7.2.3.9.19 RVReferenceUsage\_Mapping

#### Description

Creates a reference usage.

#### General Mappings

**Generic**ToReferenceUsage\_Mapping

#### Mapping Source

Pin

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
let featureTyping : Set(KerML::FeatureTyping) =  
  if from.type.ocIsUndefined() then  
    Set{}  
  else  
    Set{RVReferenceUsageFeatureTyping_Mapping.getMapped(from)}  
  endif in  
featureTyping  
->including(RVReferenceUsageFeatureValue_Mapping.getMapped(from))
```

### 7.7.2.3.9.20 RVReferenceUsageFeatureReferenceExpression\_Mapping

#### Description

The mapping class creates the feature reference expression element for the UML4SysML::ReadVariableAction mapping.

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`RVAReferenceUsage_Mapping.getMapped(from.result)`

#### 7.7.2.3.9.19 RVAReferenceUsage\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a reference usage.

###### **General Mappings**

ToReferenceUsage\_Init  
Mapping

###### **Mapping Source**

Pin

###### **Mapping Target**

ReferenceUsage

###### **Owned Mappings**

(none)

###### **Applicable filters**

(none)

###### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  

```
let featureTyping : Set(KerML::FeatureTyping) =
  if from.type.oclIsUndefined() then
    Set{}
  else
    Set{RVAReferenceUsageFeatureTyping_Mapping.getMapped(from)}
  endif in
featureTyping
->including(RVAReferenceUsageFeatureValue_Mapping.getMapped(from))
```

#### 7.7.2.3.9.20 RVAReferenceUsageFeatureReferenceExpression\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

## General Mappings

**Generic**ToFeatureReferenceExpression\_Mapping

### Mapping Source

Pin

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]

```
Set{RVAResourceUsageExpressionMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.9.21 RVAResourceUsageFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

TypedElementFeatureTyping\_Mapping

##### Mapping Source

Pin

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

#### 7.7.2.3.9.22 RVAResourceUsageFeatureValue\_Mapping

##### Description



The mapping class creates the feature reference expression element for the UML4SysML::ReadVariableAction mapping.

### General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

### Mapping Source

Pin

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]

```
Set {RVReferenceUsageExpressionMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.9.21 RVReferenceUsageFeatureTyping\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

TypedElementFeatureTyping\_Mapping

### Mapping Source

Pin

### Mapping Target

FeatureTyping

### Owned Mappings

Creates a feature value relationship.

### General Mappings

**Generic**ToFeatureValue\_Mapping

### Mapping Source

Pin

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
RVAReferenceUsageFeatureReferenceExpression_Mapping.getMapped(from)
```

### 7.7.2.3.9.23 RVAReferenceUsageExpressionMembership\_Mapping

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

**Generic**ToMembership\_Mapping

### Mapping Source

Pin

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

(none)

#### Applicable filters

(none)

#### 7.7.2.3.9.22 RVAReferenceUsageFeatureValue\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature value relationship.

#### General Mappings

ToFeatureValue\_Init  
Mapping

#### Mapping Source

Pin

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
RVAReferenceUsageFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.9.23 RVAReferenceUsageExpressionMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToMembership\_Init  
Mapping

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
`from.owner.oclAsType(UML::ReadVariableAction).variable`

### 7.7.2.3.9.24 RemoveVariableValueAction\_Mapping

#### Description

A UML4SysML::RemoveVariableValueAction is mapped to a SysML v2 ActionUsage defined by the SysML v1 library action definition SysMLv1Library::RemoveVariableValueAction.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    private sysMLv1Variable : ScalarValues::Integer;  
  
    action sysMLv1RemoveVariableValueAction  
        : SysMLv1Library::RemoveVariableValueAction {  
        :>> variable := sysMLv1Variable;  
    }  
}
```

#### General Mappings

CommonAction\_Mapping

#### Mapping Source

RemoveVariableValueAction

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]

## Mapping Source

Pin

## Mapping Target

Membership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
`from.owner.oclAsType (UML::ReadVariableAction).variable`

### 7.7.2.3.9.24 RemoveVariableValueAction\_Mapping

#### Description

A UML4SysML::RemoveVariableValueAction is mapped to a SysML v2 ActionUsage defined by the SysML v1 library action definition SysMLv1Library::RemoveVariableValueAction.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    private sysMLv1Variable : ScalarValues::Integer;  
  
    action sysMLv1RemoveVariableValueAction  
        : SysMLv1Library::RemoveVariableValueAction {  
        :>> variable := sysMLv1Variable;  
    }  
}
```

## General Mappings

CommonAction\_Mapping

## Mapping Source

RemoveVariableValueAction

## Mapping Target

ActionUsage

## Owned Mappings

```

    Helper.actionOwnedRelationship(from)
->including(RVVAFeatureTyping_Mapping.getMapped(from))
->including(RVVAVariableFeatureMembership_Mapping.getMapped(from))

```

#### 7.7.2.3.9.25 RVVAFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

**Generic**ToFeatureTyping\_Mapping

##### Mapping Source

RemoveVariableValueAction

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type() : Type [1]
 

```

SYSML2::ActionDefinition.allInstances()
->any(m | m.qualifiedName = 'SysMLv1Library::RemoveVariableValueAction')

```

#### 7.7.2.3.9.26 RVVAVariable\_Mapping

##### Description

The mapping class creates a reference usage element for the UML4SysML::RemoveVariableValueAction mapping.

##### General Mappings

**Generic**ToReferenceUsage\_Mapping

##### Mapping Source

RemoveVariableValueAction

##### Mapping Target

ReferenceUsage

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionUsage::ownedRelationship () : Relationship [0..*]`  
`Helper.actionOwnedRelationship (from)`  
`->including (RVVAFeatureTyping_Mapping.getMapped (from))`  
`->including (RVVAVariableFeatureMembership_Mapping.getMapped (from))`

#### 7.7.2.3.9.25 RVVAFeatureTyping\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

ToFeatureTyping\_Init  
Mapping

#### Mapping Source

RemoveVariableValueAction

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`SYSML2::ActionDefinition.allInstances()`  
`->any (m | m.qualifiedName = 'SysMLv1Library::RemoveVariableValueAction')`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{RVVAVariableRedefinition_Mapping.getMapped(from),  
RVVAVariableFeatureValue_Mapping.getMapped(from),  
AssignmentActionUsageOwningMembership_Factory.create() }
```

### 7.7.2.3.9.27 RVVAVariableExpressionMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

`GenericToMembership_Mapping`

#### Mapping Source

`RemoveVariableValueAction`

#### Mapping Target

`Membership`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`

```
from.variable
```

### 7.7.2.3.9.28 RVVAVariableFeatureMembership\_Mapping

#### Description



#### 7.7.2.3.9.26 RVVAVariable\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates a reference usage element for the UML4SysML::RemoveVariableValueAction mapping.

##### General Mappings

ToReferenceUsage\_Init  
Mapping

##### Mapping Source

RemoveVariableValueAction

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{RVVAVariableRedefinition_Mapping.getMapped(from),  
RVVAVariableFeatureValue_Mapping.getMapped(from),  
AssignmentActionUsageOwningMembership_Factory.create() }
```

#### 7.7.2.3.9.27 RVVAVariableExpressionMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToMembership\_Init  
Mapping

##### Mapping Source

RemoveVariableValueAction

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

**Generic**ToFeatureMembership\_Mapping

### Mapping Source

RemoveVariableValueAction

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`RVVVariable_Mapping.getMapped(from)`

### 7.7.2.3.9.29 RVVVariableFeatureReferenceExpression\_Mapping

#### Description

The mapping class creates the feature reference expression element for the UML4SysML::RemoveVariableValueAction mapping.

### General Mappings

**Generic**ToFeatureReferenceExpression\_Mapping

### Mapping Source

RemoveVariableValueAction

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
`from.variable`

#### 7.7.2.3.9.28 RVVAVariableFeatureMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

RemoveVariableValueAction

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set{RVVAVariableExpressionMembership_Mapping.getMapped(from) ,  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.9.30 RVVAVariableFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

`GenericToFeatureValue_Mapping`

##### Mapping Source

`RemoveVariableValueAction`

##### Mapping Target

`FeatureValue`

##### Owned Mappings

(none)

##### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
RVVAVariableFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.2.3.9.31 RVVAVariableRedefinition\_Mapping

##### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

##### General Mappings

`GenericToRedefinition_Mapping`

```
RVVAVariable_Mapping.getMapped(from)
```

#### 7.7.2.3.9.29 RVVAVariableFeatureReferenceExpression\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

The mapping class creates the feature reference expression element for the UML4SysML::RemoveVariableValueAction mapping.

##### General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

##### Mapping Source

RemoveVariableValueAction

##### Mapping Target

FeatureReferenceExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]

```
Set{RVVAVariableExpressionMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.2.3.9.30 RVVAVariableFeatureValue\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

Creates a feature value relationship.

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

## Mapping Source

RemoveVariableValueAction

## Mapping Target

Redefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  

```
SysML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::RemoveVariableValueAction::variable')
```

## 7.7.3 Activities

This chapter lists all mapping specifications of UML4SysML::Activities model elements.

### 7.7.3.1 Overview

Table 3. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Activity	ViewDefinition ActionDefinition RequirementUsage
ActivityFinalNode	not mapped; see next section
ActivityParameterNode	not mapped; see next section
ActivityPartition	not mapped; see next section
CentralBufferNode	ActionUsage
ControlFlow	TransitionUsage SuccessionAsUsage
DataStoreNode	ActionUsage
DecisionNode	DecisionNode
ExceptionHandler	not mapped; see next section
FlowFinalNode	not mapped; see next section
ForkNode	ForkNode

RemoveVariableValueAction

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

`RVVAVariableFeatureReferenceExpression_Mapping.getMapped (from)`

#### 7.7.2.3.9.31 RVVAVariableRedefinition\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

ToRedefinition\_Init  
Mapping

### Mapping Source

RemoveVariableValueAction

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
InitialNode	not mapped; see next section
InterruptibleActivityRegion	not mapped; see next section
JoinNode	JoinNode
MergeNode	MergeNode
ObjectFlow	TransitionUsage SuccessionFlowConnectionUsage
Variable	not mapped; see next section

The following table gives an overview of which SysML v2 elements the UML4SysML::Activities elements are transformed with which mapping class. The mapping details are in [7.7.3.3](#).

The justifications for the elements without mapping are given in [7.7.3.2](#).

### 7.7.3.2 UML4SysML::Activities elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 4. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
ActivityFinalNode	Mapping is not specified yet.
ActivityParameterNode	The parameter of the activity is mapped from SysML v1 to SysML v2. The additional concept of the activity parameter node is necessary for the token semantic of SysML v1 activities, which is not part of SysML v2. Therefore, the additional concept of the activity parameter node is not mapped to SysML v2.
ActivityPartition	Mapping is not specified yet.
ExceptionHandler	Mapping is not specified yet.
InterruptibleActivityRegion	Mapping is not specified yet.

### 7.7.3.3 Mapping Specifications

#### 7.7.3.3.1 ActivityAsDefinition\_Mapping

##### Description

A UML4SysML::Activity is mapped to a SysMLv2 ActionDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action def SysMLv1Activity {
  in parIn : SysMLv1Block;
  out parOut;
  out parReturn;
}

```



In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::ReferenceUsage.allInstances()
->any(m | m.qualifiedName = 'SysMLv1Library::RemoveVariableValueAction::variable')
```

## 7.7.3 Activities

### 7.7.3.1 Overview

**SysML2 -417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"**

**SysML2 -44: Transformation of UML4SysML::ActivityFinalNode is not specified yet**

**SysML2 -329: Mapping overview tables are wrong**

Table 3. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Activity	ActionDefinition
ActivityFinalNode	TerminateActionUsage
ActivityParameterNode	not mapped; see next section
ActivityPartition	not mapped; see next section
CentralBufferNode	ActionUsage
ControlFlow	SuccessionAsUsage TransitionUsage
DataStoreNode	ActionUsage
DecisionNode	DecisionNode
ExceptionHandler	not mapped; see next section
FlowFinalNode	not mapped; see next section
ForkNode	ForkNode
InitialNode	not mapped; see next section
InterruptibleActivityRegion	not mapped; see next section
JoinNode	JoinNode
MergeNode	MergeNode
ObjectFlow	TransitionUsage SuccessionFlowUsage
Variable	AttributeUsage ItemUsage

### 7.7.3.2 UML4SysML::Activities elements not mapped

Table 4. List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
ActivityFinalNode	Mapping is not specified yet.

```

}
part def SysMLv1Block;

```

## General Mappings

Behavior\_Mapping

## Mapping Source

Activity

## Mapping Target

ActionDefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionDefinition::ownedRelationship () : Relationship [0..\*]  

```

let relationships : Set(KerML::Relationship) =
    Helper.activityOwnedRelationship(from) in
let parameters : Set(UML::Paramter) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
relationships->union(parameters
    ->collect(p | ParameterMembership_Mapping.getMapped(p))
)

```

### 7.7.3.3.2 ActivityEdgeInitialNodeFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToEndFeatureMembership\_Mapping

#### Mapping Source

InitialNode

#### Mapping Target

EndFeatureMembership

SysML v1 Concept	Rationale
ActivityParameterNode	The parameter of the activity is mapped from SysML v1 to SysML v2. The additional concept of the activity parameter node is necessary for the token semantic of SysML v1 activities, which is not part of SysML v2. Therefore, the additional concept of the activity parameter node is not mapped to SysML v2.
ActivityPartition	Mapping is not specified yet.
ExceptionHandler	Mapping is not specified yet.
InterruptibleActivityRegion	Mapping is not specified yet.

### 7.7.3.3 Mapping Specifications

#### 7.7.3.3.1 ActivityAsDefinition\_Mapping

##### Description

A UML4SysML::Activity is mapped to a SysMLv2 ActionDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action def SysMLv1Activity {
  in parIn : SysMLv1Block;
  out parOut;
  out parReturn;
}
part def SysMLv1Block;

```

##### General Mappings

Behavior\_Mapping

##### Mapping Source

Activity

##### Mapping Target

ActionDefinition

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`ActivityEdgeSourceInitialNode_Mapping.getMapped(from)`

### 7.7.3.3.3 ActivityEdgeMetadata\_Mapping

#### Description

Adds metadata to the transformation target elements of UML4SysML::ControlFlow and UML::ObjectFlow to map the UML4SysML::ActivityEdge::weight property which has no direct target in SysML v2.

## General Mappings

GenericToMetadataUsage\_Mapping

## Mapping Source

ActivityEdge

## Mapping Target

MetadataUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::declaredName () : String [0..1]  
`'weight'`
- MetadataUsage::ownedRelationship () : Relationship [0..\*]

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionDefinition::ownedRelationship () : Relationship [0..*]`  

```

let relationships : Set(KerML::Relationship) =
    Helper.activityOwnedRelationship(from) in
let parameters : Set(UML::Paramter) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
relationships->union(parameters
    ->collect(p | ParameterMembership_Mapping.getMapped(p))
)

```

### 7.7.3.3.2 ActivityEdgeInitialNodeFeatureMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToEndFeatureMembership\_Init  
Mapping

#### Mapping Source

InitialNode

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  

```

ActivityEdgeSourceInitialNode_Mapping.getMapped(from)

```

### 7.7.3.3.3 ActivityEdgeMetadata\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

```
Set{ActivityEdgeMetadataFeatureTyping_Mapping.getMapped(from),  
ActivityEdgeMetadataFeatureMembership_Mapping.getMapped(from)}
```

#### 7.7.3.3.4 ActivityEdgeMetadataFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

ActivityEdge

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
ActivityEdgeMetadataReferenceUsage_Mapping.getMapped(from)
```

#### 7.7.3.3.5 ActivityEdgeMetadataFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

**Generic**ToFeatureTyping\_Mapping

##### Mapping Source

ActivityEdge

##### Mapping Target

FeatureTyping

Adds metadata to the transformation target elements of UML4SysML::ControlFlow and UML::ObjectFlow to map the UML4SysML::ActivityEdge::weight property which has no direct target in SysML v2.

### General Mappings

ToMetadataUsage\_Init  
Mapping

### Mapping Source

ActivityEdge

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::declaredName () : String [0..1]  
`'weight'`
- MetadataUsage::ownedRelationship () : Relationship [0..\*]  
`Set{ActivityEdgeMetadataFeatureTyping_Mapping.getMapped(from) ,  
ActivityEdgeMetadataFeatureMembership_Mapping.getMapped(from) }`

#### 7.7.3.3.4 ActivityEdgeMetadataFeatureMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

ActivityEdge

### Mapping Target

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ActivityEdgeData')
```

### 7.7.3.3.6 ActivityEdgeMetadataFeatureValue\_Mapping

#### Description

Creates a feature value relationship.

#### General Mappings

`GenericToFeatureValue_Mapping`

#### Mapping Source

`ActivityEdge`

#### Mapping Target

`FeatureValue`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
from.weight
```

### 7.7.3.3.7 ActivityEdgeMetadataOwningMembership\_Mapping

#### Description



FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`ActivityEdgeMetadataReferenceUsage_Mapping.getMapped(from)`

#### 7.7.3.3.5 ActivityEdgeMetadataFeatureTyping\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

ActivityEdge

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`SYSML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ActivityEdgeData')`

Creates a owning membership relationship for *ownedMemberElement()*.

### General Mappings

**Generic**ToOwningMembership\_Mapping

### Mapping Source

ActivityEdge

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

`ActivityEdgeMetadata_Mapping.getMapped(from)`

### 7.7.3.3.8 ActivityEdgeMetadataRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

**Generic**ToRedefinition\_Mapping

### Mapping Source

ActivityEdge

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

#### 7.7.3.3.6 ActivityEdgeMetadataFeatureValue\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature value relationship.

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

ActivityEdge

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

`from.weight`

#### 7.7.3.3.7 ActivityEdgeMetadataOwningMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a owning membership relationship for *ownedMemberElement()*.

##### General Mappings

ToOwningMembership\_Init  
Mapping

##### Mapping Source

ActivityEdge

##### Mapping Target

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ActivityEdgeData::weight')
```

### 7.7.3.3.9 ActivityEdgeMetadataReferenceUsage\_Mapping

#### Description

Creates a reference usage.

#### General Mappings

**Generic**ToReferenceUsage\_Mapping

#### Mapping Source

ActivityEdge

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{ActivityEdgeMetadataRedefinition_Mapping.getMapped(from) ,  
ActivityEdgeMetadataFeatureValue_Mapping.getMapped(from) }
```

### 7.7.3.3.10 ActivityEdgeSourceEndFeature\_Mapping

#### Description

Creates a SysML v2 feature for the source activity node of the SysML v1 activity edge which subsets the SysML v2 target element of the source activity node.

#### General Mappings

**Generic**ToFeature\_Mapping

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ActivityEdgeMetadata_Mapping.getMapped(from)`

### 7.7.3.3.8 ActivityEdgeMetadataRedefinition\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

ToRedefinition\_Init  
Mapping

### Mapping Source

ActivityEdge

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]  
`SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ActivityEdgeData::weight')`



#### 7.7.3.3.9 ActivityEdgeMetadataReferenceUsage\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

Creates a reference usage.

##### General Mappings

ToReferenceUsage\_Init  
Mapping

##### Mapping Source

ActivityEdge

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{ActivityEdgeMetadataRedefinition_Mapping.getMapped(from),  
ActivityEdgeMetadataFeatureValue_Mapping.getMapped(from)}
```

#### 7.7.3.3.10 ActivityEdgeSourceEndFeature\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

Creates a SysML v2 feature for the source activity node of the SysML v1 activity edge which subsets the SysML v2 target element of the source activity node.

##### General Mappings

ToFeature\_Init  
Mapping

##### Mapping Source

Element

## Mapping Source

## Element

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]  
`true`
- Feature::ownedRelationship () : Relationship [0..\*]  
`Set{ActivityEdgeSourceEndSubsetting_Mapping.getMapped(from) }`

### 7.7.3.3.11 ActivityEdgeSourceInitialNode\_Mapping

## Description

The UML4SysML::InitialNode is mapped to a subsetted feature of the SysML v2 library element Actions::start.

## General Mappings

## GenericToFeature\_Mapping

## Mapping Source

InitialNode

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules



## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]  
`true`
- Feature::ownedRelationship () : Relationship [0..\*]  
`Set{ActivityEdgeSourceEndSubsetting_Mapping.getMapped(from) }`

### 7.7.3.3.11 ActivityEdgeSourceInitialNode\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

## Description

The UML4SysML::InitialNode is mapped to a subsetted feature of the SysML v2 library element Actions::start.

## General Mappings

ToFeature\_[Init](#)  
Mapping

## Mapping Source

InitialNode

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::isEnd () : Boolean [1]`

`true`

- `Feature::ownedRelationship () : Relationship [0..*]`

`Set{ActivityEdgeSourceInitialNodeSubsetting_Mapping.getMapped(from) }`

#### 7.7.3.3.12 ActivityEdgeSourceEndFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

`GenericToEndFeatureMembership_Mapping`

##### Mapping Source

Element

##### Mapping Target

EndFeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`

`ActivityEdgeSourceEndFeature_Mapping.getMapped(from)`

#### 7.7.3.3.13 ActivityEdgeSourceInitialNodeSubsetting\_Mapping

##### Description

Creates a subsetting relationship.

##### General Mappings

`GenericToReferenceSubsetting_Mapping`

##### Mapping Source

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set{ActivityEdgeSourceInitialNodeSubsetting_Mapping.getMapped (from) }`
- `Feature::isEnd () : Boolean [1]`  
`true`

#### 7.7.3.3.12 ActivityEdgeSourceEndFeatureMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToEndFeatureMembership\_Init  
Mapping

##### Mapping Source

Element

##### Mapping Target

EndFeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  
`ActivityEdgeSourceEndFeature_Mapping.getMapped (from)`

#### 7.7.3.3.13 ActivityEdgeSourceInitialNodeSubsetting\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

Creates a subsetting relationship.

InitialNode

### Mapping Target

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  

```
SysML2::ActionUsage.allInstances()  
->any(m | m.qualifiedName = 'Actions::Action::start')
```

## 7.7.3.3.14 ActivityEdgeSourceEndSubsetting\_Mapping

### Description

Creates a subsetting relationship.

### General Mappings

**Generic**ToReferenceSubsetting\_Mapping

### Mapping Source

Element

### Mapping Target

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]

## General Mappings

ToReferenceSubsetting\_Init  
Mapping

## Mapping Source

InitialNode

## Mapping Target

ReferenceSubsetting

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  
  

```
SYSML2::ActionUsage.allInstances()  
->any(m | m.qualifiedName = 'Actions::Action::start')
```

### 7.7.3.3.14 ActivityEdgeSourceEndSubsetting\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a subsetting relationship.

## General Mappings

ToReferenceSubsetting\_Init  
Mapping

## Mapping Source

Element

## Mapping Target

ReferenceSubsetting

## Owned Mappings

(none)

## Applicable filters

from

### 7.7.3.3.15 ActivityEdgeTransitionUsageSourceMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToMembership\_Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

Membership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  

```
if from.ocIsTypeOf(UML::ActivityParameterNode) then
    from.parameter
else
    from
endif
```

### 7.7.3.3.16 CentralBufferNode\_Mapping

#### Description

The mapping of the UML4SysML::CentralBufferNode is not defined in detail yet. It will be an action usage which contains the behavior of a central buffer node.

#### General Mappings

GenericToActionUsage\_Mapping  
NamedElementMain\_Mapping

#### Mapping Source

CentralBufferNode

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]

from

#### 7.7.3.3.15 ActivityEdgeTransitionUsageSourceMembership\_Mapping

[SYSML2 -220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

ActivityNode

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  

```
if from.ocIsTypeOf(UML::ActivityParameterNode) then
    from.parameter
else
    from
endif
```

#### 7.7.3.3.16 ActivityFinalNode\_Mapping

[SYSML2 -44: Transformation of UML4SysML::ActivityFinalNode is not specified yet](#)

[SYSML2 -220: Replace Generic mapping classes by Initializers](#)





## Description

A UML4SysML::ActivityFinalNode is mapped to SysML v2 TerminateAction.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
  first start;  
  then action action1;  
  then termine;  
}
```

## General Mappings

NamedElementMain\_Mapping  
ToActionUsage\_Init

## Mapping Source

ActivityFinalNode

## Mapping Target

TerminateActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

### 7.7.3.3.17 CentralBufferNode\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

## Description

The mapping of the UML4SysML::CentralBufferNode is not defined in detail yet. It will be an action usage which contains the behavior of a central buffer node.

## General Mappings

ToActionUsage\_Init  
NamedElementMain\_Mapping

## Mapping Source

CentralBufferNode

## Mapping Target

ActionUsage

## Mapping Target

### ActionUsage

## Owned Mappings

(none)

### 7.7.3.3.17 CommonActivityEdgeSuccessionAsUsage\_Mapping

## Description

The mapping class provides a common mapping of a UML4SysML::ActivityEdge to a SysMLv2 SuccessionAsUsage. The mapping is used for UML4SysML::ControlFlows and UML4SysML::ObjectFlows.

## General Mappings

### GenericToConnector\_Mapping

## Mapping Source

ActivityEdge

## Mapping Target

SuccessionAsUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SuccessionAsUsage::ownedRelationship () : Relationship [0..\*]  

```
let relationships : Set(KerML::Relationship) = Set{
if from.source.ocIsKindOf(UML::InitialNode) then
    ActivityEdgeInitialNodeFeatureMembership_Mapping.getMapped(from.source)
else if from.source.ocIsKindOf(UML::ActivityParameterNode) then
    ActivityEdgeSourceEndFeatureMembership_Mapping.getMapped(from.source.parameter)
else
    ActivityEdgeSourceEndFeatureMembership_Mapping.getMapped(from.source)
endif
endif,
if from.ocIsKindOf(UML::ObjectFlow) then
    ObjectFlowGuardSuccessionTargetEndFeatureMembership_Mapping.getMapped(from)
else if from.target.ocIsKindOf(UML::FinalNode) then
    ControlFlowFinalNodeFeatureMembership_Mapping.getMapped(from.target)
else
    ControlFlowTargetFeatureMembership_Mapping.getMapped(from.target)
end}
```

## Owned Mappings

(none)

## Applicable filters

(none)

### 7.7.3.3.18 CommonActivityEdgeSuccessionAsUsage\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

## Description

The mapping class provides a common mapping of a UML4SysML::ActivityEdge to a SysMLv2 SuccessionAsUsage. The mapping is used for UML4SysML::ControlFlows and UML4SysML::ObjectFlows.

## General Mappings

ToConnector\_Init  
Mapping

## Mapping Source

ActivityEdge

## Mapping Target

SuccessionAsUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SuccessionAsUsage::ownedRelationship () : Relationship [0..\*]  

```
let relationships : Set(KerML::Relationship) = Set{
  if from.source.ocIsKindOf(UML::InitialNode) then
    ActivityEdgeInitialNodeFeatureMembership_Mapping.getMapped(from.source)
  else if from.source.ocIsKindOf(UML::ActivityParameterNode) then
    ActivityEdgeSourceEndFeatureMembership_Mapping.getMapped(from.source.parameter)
  else
    ActivityEdgeSourceEndFeatureMembership_Mapping.getMapped(from.source)
  endif
endif,
if from.ocIsKindOf(UML::ObjectFlow) then
  ObjectFlowGuardSuccessionTargetEndFeatureMembership_Mapping.getMapped(from)
else if from.target.ocIsKindOf(UML::FinalNode) then
  ControlFlowFinalNodeFeatureMembership_Mapping.getMapped(from.target)
```

```

        endif
    endif} in
    if from.guard.oclIsUndefined() then
        relationships
    else
        relationships
        ->including (ElementFeatureMembership_Mapping.getMapped(from.guard))
    endif

```

### 7.7.3.3.18 CommonVariable\_Mapping

#### Description

Abstract mapping class for UML4SysML::Variable which is defined in the context of UML4SysML::Activity. A UML4SysML::Variable is mapped to a SysMLv2 AttributeUsage or SysMLv2 ItemUsage. See specialized mapping classes for the specific mapping rules.

#### General Mappings

PropertyCommon\_Mapping

#### Mapping Source

Variable

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]  
false
- Feature::isComposite () : Boolean [1]  
false
- Feature::ownedRelationship () : Relationship [0..\*]

```

let typing: KerML::FeatureTyping =
    VariableFeatureTyping_Mapping.getMapped(from) in
if typing.oclIsUndefined() then
    Set{MultiplicityMembership_Mapping.getMapped(from)}

```

```

        else
            ControlFlowTargetFeatureMembership_Mapping.getMapped(from.target)
        endif
    endif} in
    if from.guard.oclIsUndefined() then
        relationships
    else
        relationships
        ->including (ElementFeatureMembership_Mapping.getMapped(from.guard))
    endif

```

### 7.7.3.3.19 CommonVariable\_Mapping

#### Description

Abstract mapping class for UML4SysML::Variable which is defined in the context of UML4SysML::Activity. A UML4SysML::Variable is mapped to a SysMLv2 AttributeUsage or SysMLv2 ItemUsage. See specialized mapping classes for the specific mapping rules.

#### General Mappings

PropertyCommon\_Mapping

#### Mapping Source

Variable

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```

let typing: KerML::FeatureTyping =
    VariableFeatureTyping_Mapping.getMapped(from) in
if typing.oclIsUndefined() then
    Set{MultiplicityMembership_Mapping.getMapped(from)}
else
    Set{MultiplicityMembership_Mapping.getMapped(from), typing}
endif

```

- Feature::isComposite () : Boolean [1]

```
false
```

```

else
    Set{MultiplicityMembership_Mapping.getMapped(from), typing}
endif

```

- Feature::isDerived () : Boolean [1]

```

false

```

### 7.7.3.3.19 ControlFlowTransitionUsage\_Mapping

#### Description

A UML4SysML::ControlFlow with a guard condition is mapped to a SysMLv2 TransitionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action def SysMLv1Activity {
    action sysMLv1Action1;
    succession sysMLv1ControlFlow first sysMLv1Action1
        if guardCondition.result then sysMLv1Action2 {
            calc guardCondition {
                return : ScalarValues::Boolean;
                language "English"
            }
            /*
             * thisIsAGuard
             */
        }
    }
    action sysMLv1Action2;
}

```

#### General Mappings

##### GenericToTransitionUsage\_Mapping

##### NamedElementMain\_Mapping

#### Mapping Source

ControlFlow

#### Mapping Target

TransitionUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```

not src.guard.oclIsUndefined()

```

- `Feature::isDerived () : Boolean [1]`

`false`

- `Feature::isEnd () : Boolean [1]`

`false`

### 7.7.3.3.20 ControlFlowTransitionUsage\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

##### **Description**

A UML4SysML::ControlFlow with a guard condition is mapped to a SysMLv2 TransitionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
  action sysMLv1Action1;
  succession sysMLv1ControlFlow first sysMLv1Action1
    if guardCondition.result then sysMLv1Action2 {
      calc guardCondition {
        return : ScalarValues::Boolean;
        language "English"
      }
      /*
       * thisIsAGuard
       */
    }
  }
  action sysMLv1Action2;
}
```

##### **General Mappings**

ToTransitionUsage `Init`  
NamedElementMain\_Mapping

##### **Mapping Source**

ControlFlow

##### **Mapping Target**

TransitionUsage

##### **Owned Mappings**

(none)

##### **Applicable filters**

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not src.guard.oclIsUndefined()
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TransitionUsage::ownedRelationship () : Relationship [0..*]`

```
let relationships : Set(KerML::Relationship) = self.oclAsType(ElementMain_Mapping).ownedRelationships
->union(Set{ActivityEdgeTransitionUsageSourceMembership_Mapping.getMapped(from.source)
,CommonParameterReferenceUsageInMembership_Mapping.getMapped(from.source)
,ControlFlowTransitionUsageFeatureMembership_Mapping.getMapped(from)
,CommonActivityEdgeSuccessionAsUsage_Mapping.getMapped(from)
,CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)}) in
let relationshipsWithGuard : Set(KerML::Relationship) =
if from.guard.oclIsTypeOf(UML::OpaqueExpression) then
relationships
->including(ElementFeatureMembership_Mapping.getMapped(from.guard))
else
relationships
endif in
let relationshipsConsideringWeight : Set(KerML::Relationship) =
if from.weight.oclIsUndefined() then
relationshipsWithGuard
else
relationshipsConsideringWeight
->including(ActivityEdgeMetadataOwningMembership_Mapping.getMapped(from))
endif in
if Helper.hasStereotypeApplied(from, 'SysML::Activities::Probability') then
relationshipsConsideringWeight
->including(ProbabilityOwningMembership_Mapping.getMapped(from))
else
relationshipsConsideringWeight
endif
```

### 7.7.3.3.20 ControlFlowFinalNodeFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToEndFeatureMembership\_Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters



## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TransitionUsage::ownedRelationship () : Relationship [0..*]`

```
let relationships : Set(KerML::Relationship) = self.oclAsType(ElementMain_Mapping).ownedRelationships
->union(Set{ActivityEdgeTransitionUsageSourceMembership_Mapping.getMapped(from.source)
,CommonParameterReferenceUsageInMembership_Mapping.getMapped(from.source)
,ControlFlowTransitionUsageFeatureMembership_Mapping.getMapped(from)
,CommonActivityEdgeSuccessionAsUsage_Mapping.getMapped(from)
,CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)}) in
let relationshipsWithGuard : Set(KerML::Relationship) =
if from.guard.oclIsTypeOf(UML::OpaqueExpression) then
    relationships
->including(ElementFeatureMembership_Mapping.getMapped(from.guard))
else
    relationships
endif in
let relationshipsConsideringWeight : Set(KerML::Relationship) =
if from.weight.oclIsUndefined() then
    relationshipsWithGuard
else
    relationshipsWithGuard
->including(ActivityEdgeMetadataOwningMembership_Mapping.getMapped(from))
endif in
if Helper.hasStereotypeApplied(from, 'SysML::Activities::Probability') then
    relationshipsConsideringWeight
->including(ProbabilityOwningMembership_Mapping.getMapped(from))
else
    relationshipsConsideringWeight
endif
```

### 7.7.3.3.21 ControlFlowFinalNodeFeatureMembership\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToEndFeatureMembership\_Init  
Mapping

##### Mapping Source

ActivityNode

##### Mapping Target

EndFeatureMembership

##### Owned Mappings

(none)

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`ControlFlowTargetFinalNode_Mapping.getMapped(from)`

#### 7.7.3.3.21 ControlFlowTargetFinalNodeSubsetting\_Mapping

##### Description

Creates a subsetting relationship.

##### General Mappings

`GenericToReferenceSubsetting_Mapping`

##### Mapping Source

FinalNode

##### Mapping Target

ReferenceSubsetting

##### Owned Mappings

(none)

##### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  
`SysML2::ActionUsage.allInstances()  
->any(m | m.qualifiedName = 'Actions::Action::done')`

#### 7.7.3.3.22 ControlFlowSuccessionAsUsage\_Mapping

##### Description

A UML4SysML::ControlFlow without a guard condition is mapped to a SysMLv2 SuccessionAsUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`ControlFlowTargetFinalNode_Mapping.getMapped(from)`

#### 7.7.3.3.22 ControlFlowTargetFinalNodeSubsetting\_Mapping

### **SysML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a subsetting relationship.

### General Mappings

ToReferenceSubsetting\_Init  
Mapping

### Mapping Source

FinalNode

### Mapping Target

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  
`SysML2::ActionUsage.allInstances()  
->any(m | m.qualifiedName = 'Actions::Action::done')`

#### 7.7.3.3.23 ControlFlowSuccessionAsUsage\_Mapping

### Description

A UML4SysML::ControlFlow without a guard condition is mapped to a SysMLv2 SuccessionAsUsage.

```

action def SysMLv1Activity {
    action sysMLv1Action1;
    succession sysMLv1ControlFlow
        first sysMLv1Action1 then sysMLv1Action2;
    action sysMLv1Action2;
}

```

## General Mappings

NamedElementMain\_Mapping  
CommonActivityEdgeSuccessionAsUsage\_Mapping

## Mapping Source

ControlFlow

## Mapping Target

SuccessionAsUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.guard.oclIsUndefined()
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SuccessionAsUsage::ownedRelationship () : Relationship [0..\*]  

```

let relationships : Set(KerML::Relationship) = Set{
if from.source.oclIsKindOf(UML::InitialNode) then
    ActivityEdgeInitialNodeFeatureMembership_Mapping.getMapped(from.source)
else
    ActivityEdgeSourceEndFeatureMembership_Mapping.getMapped(from.source)
endif,
if from.oclIsKindOf(UML::ObjectFlow) then
    ObjectFlowGuardSuccessionTargetEndFeatureMembership_Mapping.getMapped(from)
else if from.target.oclIsKindOf(UML::FinalNode) then
    ControlFlowFinalNodeFeatureMembership_Mapping.getMapped(from.target)
else
    ControlFlowTargetFeatureMembership_Mapping.getMapped(from.target)
endif
endif} in
let relationshipsWithGuard : Set(KerML::Relationship) =
if from.guard.oclIsUndefined() then
    relationships
else

```

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
    action sysMLv1Action1;
    succession sysMLv1ControlFlow
        first sysMLv1Action1 then sysMLv1Action2;
    action sysMLv1Action2;
}
```

## General Mappings

NamedElementMain\_Mapping  
CommonActivityEdgeSuccessionAsUsage\_Mapping

## Mapping Source

ControlFlow

## Mapping Target

SuccessionAsUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.guard.oclIsUndefined()
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SuccessionAsUsage::ownedRelationship () : Relationship [0..\*]  

```
let relationships : Set(KerML::Relationship) = Set{
if from.source.oclIsKindOf(UML::InitialNode) then
    ActivityEdgeInitialNodeFeatureMembership_Mapping.getMapped(from.source)
else
    ActivityEdgeSourceEndFeatureMembership_Mapping.getMapped(from.source)
endif,
if from.oclIsKindOf(UML::ObjectFlow) then
    ObjectFlowGuardSuccessionTargetEndFeatureMembership_Mapping.getMapped(from)
else if from.target.oclIsKindOf(UML::FinalNode) then
    ControlFlowFinalNodeFeatureMembership_Mapping.getMapped(from.target)
else
    ControlFlowTargetFeatureMembership_Mapping.getMapped(from.target)
endif
endif} in
let relationshipsWithGuard : Set(KerML::Relationship) =
if from.guard.oclIsUndefined() then
    relationships
```

```

        relationships
        ->including (ElementFeatureMembership_Mapping.getMapped(from.guard))
    endif in
    let relationshipsConsideringWeight : Set(KerML::Relationship) =
    if from.weight.oclIsUndefined() then
        relationshipsWithGuard
    else
        relationshipsWithGuard
        ->including (ActivityEdgeMetadataOwningMembership_Mapping.getMapped(from))
    endif in

    (if Helper.hasStereotypeApplied(from, 'SysML::Activities::Probability') then
        relationshipsConsideringWeight
        ->including (ProbabilityOwningMembership_Mapping.getMapped(from))
    else
        relationshipsConsideringWeight
    endif) ->union (self.oclAsType (ElementMain_Mapping).ownedRelationship())

```

### 7.7.3.3.23 ControlFlowTargetFinalNode\_Mapping

#### Description

The mapping class maps a UML4SysML::FinalNode to a Feature which will be subsetted by Actions::Action::done. The subsetting is created by the mapping class ControlFlowTargetFinalNodeSubsetting\_Mapping.

#### General Mappings

GenericToFeature\_Mapping

#### Mapping Source

FinalNode

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]
 

```

true

```
- Feature::ownedRelationship () : Relationship [0..\*]
 

```

Set {ControlFlowTargetFinalNodeSubsetting_Mapping.getMapped(from)}

```

```

else
    relationships
    ->including (ElementFeatureMembership_Mapping.getMapped(from.guard))
endif in
let relationshipsConsideringWeight : Set(KerML::Relationship) =
if from.weight.oclIsUndefined() then
    relationshipsWithGuard
else
    relationshipsWithGuard
    ->including (ActivityEdgeMetadataOwningMembership_Mapping.getMapped(from))
endif in

(if Helper.hasStereotypeApplied(from, 'SysML::Activities::Probability') then
    relationshipsConsideringWeight
    ->including (ProbabilityOwningMembership_Mapping.getMapped(from))
else
    relationshipsConsideringWeight
endif)->union (self.oclAsType (ElementMain_Mapping).ownedRelationship())

```

### 7.7.3.3.24 ControlFlowTargetFinalNode\_Mapping

#### SYSML2 -220: Replace Generic mapping classes by Initializers

##### Description

The mapping class maps a UML4SysML::FinalNode to a Feature which will be subsetted by Actions::Action::done. The subsetting is created by the mapping class ControlFlowTargetFinalNodeSubsetting\_Mapping.

##### General Mappings

ToFeature Init  
Mapping

##### Mapping Source

FinalNode

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]  
true
- Feature::ownedRelationship () : Relationship [0..\*]

### 7.7.3.3.24 ControlFlowTargetEndFeature\_Mapping

#### Description

The mapping class maps the UML4SysML::ActivityNode to a Feature which is subsetted by the mapping target of the UML4SysML::ActivityNode. The subsetting is created by the mapping class ControlFlowTargetEndSubsetting\_Mapping.

#### General Mappings

GenericToFeature\_Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]  
`true`
- Feature::ownedRelationship () : Relationship [0..\*]  
`Set{ControlFlowTargetEndSubsetting_Mapping.getMapped(from)}`

### 7.7.3.3.25 ControlFlowTargetFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

GenericToEndFeatureMembership\_Mapping

#### Mapping Source

ActivityNode

#### Mapping Target



```
Set{ControlFlowTargetFinalNodeSubsetting_Mapping.getMapped(from) }
```

#### 7.7.3.3.25 ControlFlowTargetEndFeature\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

The mapping class maps the UML4SysML::ActivityNode to a Feature which is subsetting by the mapping target of the UML4SysML::ActivityNode. The subsetting is created by the mapping class ControlFlowTargetEndSubsetting\_Mapping.

##### General Mappings

ToFeature\_Init  
Mapping

##### Mapping Source

ActivityNode

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
Set{ControlFlowTargetEndSubsetting_Mapping.getMapped(from) }
```

- Feature::isEnd () : Boolean [1]

```
true
```

#### 7.7.3.3.26 ControlFlowTargetFeatureMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`ControlFlowTargetEndFeature_Mapping.getMapped(from)`

### 7.7.3.3.26 ControlFlowTargetEndSubsetting\_Mapping

#### Description

Creates a subsetting relationship.

#### General Mappings

**Generic**ToReferenceSubsetting\_Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  
`from`

ToEndFeatureMembership\_Init  
Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`ControlFlowTargetEndFeature_Mapping.getMapped(from)`

### 7.7.3.3.27 ControlFlowTargetEndSubsetting\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a subsetting relationship.

#### General Mappings

ToReferenceSubsetting\_Init  
Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

ReferenceSubsetting

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.3.3.27 ControlFlowTransitionUsageFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

ControlFlow

#### Mapping Target

TransitionFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TransitionFeatureMembership::kind () : TransitionFeatureKind [1]  

```
KerML::TransitionFeatureKind::guard
```
- TransitionFeatureMembership::ownedMemberFeature () : Feature [1]  

```
if from.guard.ocIsKindOf(UML::OpaqueExpression) then
  OpaqueExpressionAsValue_Mapping.getMapped(from.guard)
else
  from.guard
endif
```

### 7.7.3.3.28 DataStoreNode\_Mapping

#### Description

The mapping of the UML4SysML::DataStoreNode is not defined in detail yet. It will an action usage which contains the behavior of a data store node.

#### General Mappings

CentralBufferNode\_Mapping

#### Mapping Source

**DataStoreNode**

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceSubsetting::referencedFeature () : Feature [1]`

`from`

### 7.7.3.3.28 ControlFlowTransitionUsageFeatureMembership\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

ControlFlow

## Mapping Target

TransitionFeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TransitionFeatureMembership::kind () : TransitionFeatureKind [1]`

`KerML::TransitionFeatureKind::guard`

- `TransitionFeatureMembership::ownedMemberFeature () : Feature [1]`

```
if from.guard.ocIsKindOf(UML::OpaqueExpression) then
  OpaqueExpressionAsValue_Mapping.getMapped(from.guard)
else
  from.guard
endif
```

### 7.7.3.3.29 ControlNodeObjectFlowFeatureMembership\_Mapping

#### [SYSML2 -111: Mapping of ObjectFlows with ForkNodes](#)

## Mapping Target

ActionUsage

## Owned Mappings

(none)

### 7.7.3.3.29 DecisionNode\_Mapping

#### Description

The UML4SysML::DecisionNode is mapped to a SysMLv2 DecisionNode.

There is no suitable element in SysML v2 for the else condition of an outgoing UML4SysML::ActivityEdge. Therefore, it is mapped to a TextualRepresentation with language "SysML v1" and body "else" (see ExpressionElse\_Mapping class).

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
    action sysMLv1Action1;
    succession sysMLv1ControlFlow1 first sysMLv1Action1 then sysMLv1DecisionNode;
    decide sysMLv1DecisionNode;
    succession sysMLv1ControlFlow2 first sysMLv1DecisionNode if {
        return : ScalarValues::Boolean;
        // guard expression, for example, opaque expression
    }.result then sysMLv1Action2;
    succession flow2 first sysMLv1DecisionNode if {
        return : ScalarValues::Boolean;
        language "SysMLv1"
        /*
         * else
         */
    }.result then sysMLv1Action2;
    action sysMLv1Action2;
}
```

## General Mappings

GenericToUsage\_Mapping

NamedElementMain\_Mapping

## Mapping Source

DecisionNode

## Mapping Target

DecisionNode

## Owned Mappings

(none)

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init  
UniqueMapping

### Mapping Source

ObjectFlow

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`ControlNodeObjectFlowReferenceUsage_Mapping.getMapped (from)`

### 7.7.3.3.30 ControlNodeObjectFlowFeatureValue\_Mapping

#### **SYSML2 -111: Mapping of ObjectFlows with ForkNodes**

### Description

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_Init  
UniqueMapping

### Mapping Source

ObjectFlow

### Mapping Target

FeatureValue

### Owned Mappings





(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
if from.source.ocIsTypeOf(UML::ForkNode) then
  ForkNodeObjectFlowFeatureReferenceExpression_Mapping.getMapped(from)
else if from.source.ocIsTypeOf(UML::JoinNode)
  or from.source.ocIsTypeOf(UML::MergeNode) then
  JoinMergeNodeObjectFlowOperatorExpression_Mapping.getMapped(from)
else
  OclUndefined
endif endif
```

#### 7.7.3.3.31 ControlNodeObjectFlowReferenceUsage\_Mapping

##### **SYSML2 -111: Mapping of ObjectFlows with ForkNodes**

#### Description

Creates a reference usage.

#### General Mappings

ToReferenceUsage\_Init  
UniqueMapping

#### Mapping Source

ObjectFlow

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::declaredName () : String [0..1]



```

if from.target.ocIsTypeOf (UML::ForkNode)
or from.target.ocIsTypeOf (UML::JoinNode)
or from.target.ocIsTypeOf (UML::MergeNode) then
'inputObject' + from.target.incoming->indexOf(from).toString()
else if from.source.ocIsTypeOf (UML::ForkNode)
or from.source.ocIsTypeOf (UML::JoinNode)
or from.target.ocIsTypeOf (UML::MergeNode) then
'outputObject' + from.source.outgoing->indexOf(from).toString()
else
OclUndefined
endif endif

```

- **ReferenceUsage::ownedRelationship () : Relationship [0..\*]**

```

if from.source.ocIsTypeOf (UML::ForkNode)
or from.source.ocIsTypeOf (UML::JoinNode)
or from.source.ocIsTypeOf (UML::MergeNode) then
Set{ControlNodeObjectFlowFeatureValue_Mapping.getMapped(from)}
else
Set{}
endif

```

- **ReferenceUsage::direction () : FeatureDirectionKind [0..1]**

```

if from.target.ocIsTypeOf (UML::ForkNode)
or from.target.ocIsTypeOf (UML::JoinNode)
or from.target.ocIsTypeOf (UML::MergeNode) then
KerML::FeatureDirectionKind::_in'
else if from.source.ocIsTypeOf (UML::ForkNode)
or from.target.ocIsTypeOf (UML::JoinNode)
or from.target.ocIsTypeOf (UML::MergeNode) then
KerML::FeatureDirectionKind::_out'
else
OclUndefined
endif endif

```

- **ReferenceUsage::isUnique () : Boolean [1]**

```

if from.source.ocIsTypeOf (UML::JoinNode) then
if from.source.ocAsType (UML::JoinNode).isCombineDuplicate then
true
else
false
endif
else
true
endif

```

### 7.7.3.3.32 DataStoreNode\_Mapping

#### Description

The mapping of the UML4SysML::DataStoreNode is not defined in detail yet. It will be an action usage which contains the behavior of a data store node.

#### General Mappings

CentralBufferNode\_Mapping

#### Mapping Source



`DataStoreNode`

## Mapping Target

ActionUsage

## Owned Mappings

(none)

## Applicable filters

(none)

### 7.7.3.3.33 DecisionNode\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

The UML4SysML::DecisionNode is mapped to a SysMLv2 DecisionNode.

There is no suitable element in SysML v2 for the else condition of an outgoing UML4SysML::ActivityEdge. Therefore, it is mapped to a TextualRepresentation with language "SysML v1" and body "else" (see ExpressionElse\_Mapping class).

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
  action sysMLv1Action1;
  succession sysMLv1ControlFlow1 first sysMLv1Action1 then sysMLv1DecisionNode;
  decide sysMLv1DecisionNode;
  succession sysMLv1ControlFlow2 first sysMLv1DecisionNode if {
    return : ScalarValues::Boolean;
    // guard expression, for example, opaque expression
  }.result then sysMLv1Action2;
  succession flow2 first sysMLv1DecisionNode if {
    return : ScalarValues::Boolean;
    language "SysMLv1"
    /*
     * else
     */
  }.result then sysMLv1Action2;
  action sysMLv1Action2;
}
```

## General Mappings

`ToUsage_Init`

NamedElementMain\_Mapping

## Mapping Source

DecisionNode

## Mapping Target

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `DecisionNode::isComposite () : Boolean [1]`

`true`

### 7.7.3.3.30 FlowFinalNodeMembership\_Mapping

#### Description

The mapping class creates a membership relationship to the action usage library element `Actions::Action::done`.

#### General Mappings

`GenericToMembership_Mapping`

#### Mapping Source

`FlowFinalNode`

#### Mapping Target

`Membership`

#### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`

```
SysMLv2::ActionUsage.allInstances()  
->any(e | e.qualifiedName = 'Actions::Action::done')
```

### 7.7.3.3.31 ForkNode\_Mapping

#### Description

The `UML4SysML::ForkNode` is mapped to a SysMLv2 `ForkNode`.

DecisionNode

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- DecisionNode::isComposite () : Boolean [1]  
true

### 7.7.3.3.34 FlowFinalNodeMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates a membership relationship to the action usage library element Actions::Action::done.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

FlowFinalNode

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  

```
SysMLv2::ActionUsage.allInstances()  
->any(e | e.qualifiedName = 'Actions::Action::done')
```

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    first start;  
    action sysMLv1Action1;  
  
    then fork sysMLv1ForkNode;  
  
    then sysMLv1Action2;  
    then sysMLv1Action3;  
    action sysMLv1Action2;  
    then sysMLv1JoinNode;  
    action sysMLv1Action3;  
    then sysMLv1JoinNode;  
  
    join sysMLv1JoinNode;  
  
    then done;  
}
```

## General Mappings

GenericToUsage\_Mapping  
NamedElementMain\_Mapping

## Mapping Source

ForkNode

## Mapping Target

ForkNode

## Owned Mappings

(none)

### 7.7.3.3.32 InitialNodeMembership\_Mapping

## Description

The mapping class creates a membership relationship to the action usage library element Actions::Action::start.

## General Mappings

GenericToMembership\_Mapping

## Mapping Source

InitialNode

## Mapping Target

Membership



### 7.7.3.3.35 ForkNode\_Mapping

**SysML2 -111: Mapping of ObjectFlows with ForkNodes**

**SysML2 -220: Replace Generic mapping classes by Initializers**

#### Description

A UML4SysML::ForkNode is mapped to a SysMLv2 ForkNode. If object flows are connected with the UML4SysML::ForkNode, corresponding input and output parameters are created to transfer the objects through the ForkNode.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
  succession cf1 first sysMLv1Action1 then sysMLv1ForkNodeA;
  succession cf2 first sysMLv1Action2 then sysMLv1ForkNodeA;
  succession cf3 first sysMLv1ForkNodeA then sysMLv1Action4;

  succession flow of1 from sysMLv1Action1.result to sysMLv1ForkNodeB.inputObject1;
  succession flow of2 from sysMLv1ForkNodeB.outputObject1 to sysMLv1Action2.inputValue;
  succession flow of3 from sysMLv1ForkNodeB.outputObject2 to sysMLv1Action3.inputValue;

  fork sysMLv1ForkNodeA;
  fork sysMLv1ForkNodeB {
    in ref inputObject1;
    out ref outputObject1 = inputObject1;
    out ref outputObject2 = inputObject1;
  }
  action sysMLv1Action1 {
    out item result;
  }
  action sysMLv1Action2 {
    in item inputValue;
  }
  action sysMLv1Action3 {
    in item inputValue;
  }
  action sysMLv1Action4;
}
```

#### General Mappings

**CommonAction\_Mapping**

#### Mapping Source

ForkNode

#### Mapping Target

ForkNode

#### Owned Mappings

(none)

#### Applicable filters

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberName () : String [0..1]  

```
if from.name = '' then null else from.name endif
```
- Membership::memberElement () : Element [1]  

```
SysMLv2::ActionUsage.allInstances()  
->any(e | e.qualifiedName = 'Actions::Action::start')
```

### 7.7.3.33 JoinNode\_Mapping

#### Description

The UML4SysML::JoinNode is mapped to a SysMLv2JoinNode.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    first start;  
    action sysMLv1Action1;  
  
    then fork sysMLv1ForkNode;  
  
    then sysMLv1Action2;  
    then sysMLv1Action3;  
    action sysMLv1Action2;  
    then sysMLv1JoinNode;  
    action sysMLv1Action3;  
    then sysMLv1JoinNode;  
  
    join sysMLv1JoinNode;  
  
    then done;  
}
```

## General Mappings

GenericToUsage\_Mapping

NamedElementMain\_Mapping

## Mapping Source

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ForkNode::ownedRelationship () : Relationship [0..*]`

```
if not (src.incoming->forAll(e | e.ocIsTypeOf(UML::ControlFlow))
and src.outgoing->forAll(e | e.ocIsTypeOf(UML::ControlFlow))) then
  from.ownedElement->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
  ->union(from.incoming->collect(i | ControlNodeObjectFlowFeatureMembership_Mapping.getMapped(i))
  ->union(from.outgoing->collect(i | ControlNodeObjectFlowFeatureMembership_Mapping.getMapped(i)))
else
  Set{}
endif
```

#### 7.7.3.3.36 ForkNodeObjectFlowFeatureReferenceExpression\_Mapping

##### Description

Creates a feature reference expression.

##### General Mappings

UniqueMapping  
ToFeatureReferenceExpression\_Init

##### Mapping Source

ObjectFlow

##### Mapping Target

FeatureReferenceExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set{ForkNodeObjectFlowMembership_Mapping.getMapped(from)}
->including(ReturnParameterFeatureMembership_Factory.create())
```

#### 7.7.3.3.37 ForkNodeObjectFlowMembership\_Mapping

##### Description



Creates a membership relationship for *memberElement()*.

#### General Mappings

ToMembership\_Init  
UniqueMapping

#### Mapping Source

ObjectFlow

#### Mapping Target

Membership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

```
ControlNodeObjectFlowReferenceUsage_Mapping.getMapped(  
    from.source.oclAsType(UML::ForkNode).incoming  
    ->asOrderedSet() ->first())
```

#### 7.7.3.38 JoinMergeNodeObjectFlowFeature\_Mapping

##### Description

Creates a feature for the operator expression created by JoinMergeNodeObjectFlowOperatorExpression\_Mapping.

##### General Mappings

ToFeature\_Init  
UniqueMapping

##### Mapping Source

ObjectFlow

##### Mapping Target

Feature

##### Owned Mappings

(none)



### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set{JoinMergeNodeObjectFlowFeatureValue_Mapping.getMapped(from)}
```

#### 7.7.3.3.39 JoinMergeNodeObjectFlowFeatureReferenceExpression\_Mapping

#### [SYSML2 -111: Mapping of ObjectFlows with ForkNodes](#)

### Description

Creates a feature reference expression.

### General Mappings

ToFeatureReferenceExpression\_Init  
UniqueMapping

### Mapping Source

ObjectFlow

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set{JoinMergeNodeObjectFlowMembership_Mapping.getMapped(from)}  
->including(ReturnParameterFeatureMembership_Factory.create())
```

#### 7.7.3.3.40 JoinMergeNodeObjectFlowFeatureValue\_Mapping

#### [SYSML2 -111: Mapping of ObjectFlows with ForkNodes](#)

### Description





Creates a feature value relationship.

### General Mappings

UniqueMapping  
ToFeatureValue\_Init

### Mapping Source

ObjectFlow

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

`JoinMergeNodeObjectFlowFeatureReferenceExpression_Mapping.getMapped(from)`

### 7.7.3.3.41 JoinMergeNodeObjectFlowMembership\_Mapping

#### [SYSML2\\_-111: Mapping of ObjectFlows with ForkNodes](#)

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
UniqueMapping

### Mapping Source

ObjectFlow

### Mapping Target

Membership

### Owned Mappings

(none)



## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
`ControlNodeObjectFlowReferenceUsage_Mapping.getMapped(from)`

### 7.7.3.3.42 JoinMergeNodeObjectFlowOperatorExpression\_Mapping

#### [SYSML2 -111](#): Mapping of ObjectFlows with ForkNodes

## Description

Creates an operator expression to combine the input objects.

## General Mappings

ToOperatorExpression\_Init  
UniqueMapping

## Mapping Source

ObjectFlow

## Mapping Target

OperatorExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OperatorExpression::ownedRelationship () : Relationship [0..\*]  

```
if from.source.ocIsKindOf(UML::ControlNode) then
  from.source.ocAsType(UML::ControlNode).incoming
->collect(o | JoinMergeNodeObjectFlowParameterMembership_Mapping.getMapped(o))
->including(ReturnParameterFeatureMembership_Factory.create())
else
  Set{}
endif
```
- OperatorExpression::operator () : String [1]



### 7.7.3.3.43 JoinMergeNodeObjectFlowParameterMembership\_Mapping

#### [SYSML2\\_-111: Mapping of ObjectFlows with ForkNodes](#)

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToParameterMembership\_Init  
UniqueMapping

##### Mapping Source

ObjectFlow

##### Mapping Target

ParameterMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`JoinMergeNodeObjectFlowFeature_Mapping.getMapped(from)`

### 7.7.3.3.44 InitialNodeMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class creates a membership relationship to the action usage library element Actions::Action::start.

##### General Mappings

ToMembership\_Init  
Mapping

##### Mapping Source

InitialNode



## Mapping Target

### Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberName () : String [0..1]  
  
if from.name = '' then null else from.name endif
- Membership::memberElement () : Element [1]  
  
SysMLv2::ActionUsage.allInstances()  
->any(e | e.qualifiedName = 'Actions::Action::start')

#### 7.7.3.3.45 JoinNode\_Mapping

##### [SYSML2 -111: Mapping of ObjectFlows with ForkNodes](#)

##### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

### Description

A UML4SysML::JoinNode is mapped to a SysMLv2 JoinNode. If object flows are connected with the UML4SysML::JoinNode, corresponding input and output parameters are created to transfer the objects through the JoinNode.

The output object is specified as follows if UML4SysML::JoinNode::isCombineDuplicate is false:

```
out ref outputObject1 nonunique = (inputObject1, inputObject2)
```

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
  succession cf1 first sysMLv1Action1 then sysMLv1JoinNodeA;  
  succession cf2 first sysMLv1Action2 then sysMLv1JoinNodeA;  
  
  succession flow of1 from sysMLv1Action2.result to sysMLv1JoinNodeB.inputObject1;  
  succession flow of2 from sysMLv1Action3.result to sysMLv1JoinNodeB.inputObject2;  
  succession flow of3 from sysMLv1JoinNodeB.outputObject1 to sysMLv1Action4.inputValue;  
  
  join sysMLv1JoinNodeA;  
  join sysMLv1JoinNodeB {  
    in ref inputObject1;  
    in ref inputObject2;  
    out ref outputObject1 = (inputObject1, inputObject2);  
  }  
  action sysMLv1Action1;  
}
```





```

    action sysMLv1Action2 {
        out item result;
    }
    action sysMLv1Action3 {
        out item result;
    }
    action sysMLv1Action4 {
        in item inputValue;
    }
}

```

## General Mappings

### CommonAction\_Mapping

#### Mapping Source

JoinNode

#### Mapping Target

JoinNode

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- JoinNode::ownedRelationship () : Relationship [0..\*]

```

if not (src.incoming->forall(e | e.ocIsTypeOf(UML::ControlFlow))
and src.outgoing->forall(e | e.ocIsTypeOf(UML::ControlFlow))) then
    from.ownedElement->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(from.incoming->collect(i | ControlNodeObjectFlowFeatureMembership_Mapping.getMapped(i))
->union(from.outgoing->collect(i | ControlNodeObjectFlowFeatureMembership_Mapping.getMapped(i)))
else
    Set{}
endif

```

### 7.7.3.3.46 MergeNode\_Mapping

**SysML2 -111: Mapping of ObjectFlows with ForkNodes**

**SysML2 -220: Replace Generic mapping classes by Initializers**

#### Description

A UML4SysML::MergeNode is mapped to a SysMLv2 MergeNode. If object flows are connected with the UML4SysML::MergeNode, corresponding input and output parameters are created to transfer the objects through the MergeNode.

JoinNode

### Mapping Target

JoinNode

### Owned Mappings

(none)

## 7.7.3.3.34 MergeNode\_Mapping

### Description

The UML4SysML::MergeNode is mapped to a SysMLv2 MergeNode.

### General Mappings

GenericToUsage\_Mapping

NamedElementMain\_Mapping

### Mapping Source

MergeNode

### Mapping Target

MergeNode

### Owned Mappings

(none)

## 7.7.3.3.35 ObjectFlow\_Mapping

### Description

A UML4SysML::ObjectFlowFlow without a guard condition is mapped to a SysMLv2SuccessionFlowConnectionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Acticity {
  action sysMLv1Action1 {
    out outputValue;
  }
  succession flow sysMLv1ObjectFlow of ScalarValues::String
    from sysMLv1Action1.outputValue to sysMLv1Action1.inputValue;
  action sysMLv1Action2 {
    out inputValue;
  }
}
```

### General Mappings

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
  succession cf1 first sysMLv1Action1 then sysMLv1MergeNodeA;
  succession cf2 first sysMLv1Action2 then sysMLv1MergeNodeA;

  succession flow of1 from sysMLv1Action2.result to sysMLv1MergeNodeB.inputObject1;
  succession flow of2 from sysMLv1Action3.result to sysMLv1MergeNodeB.inputObject2;
  succession flow of3 from sysMLv1MergeNodeB.outputObject1 to sysMLv1Action4.inputValue;

  merge sysMLv1MergeNodeA;
  merge sysMLv1MergeNodeB {
    in ref inputObject1;
    in ref inputObject2;
    out ref outputObject1 = (inputObject1, inputObject2);
  }
  action sysMLv1Action1;
  action sysMLv1Action2 {
    out item result;
  }
  action sysMLv1Action3 {
    out item result;
  }
  action sysMLv1Action4 {
    in item inputValue;
  }
}
```

## General Mappings

### CommonAction\_Mapping

#### Mapping Source

MergeNode

#### Mapping Target

MergeNode

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MergeNode::ownedRelationship () : Relationship [0..\*]

```
if not (src.incoming->forAll(e | e.ocIsTypeOf(UML::ControlFlow))
and src.outgoing->forAll(e | e.ocIsTypeOf(UML::ControlFlow))) then
  from.ownedElement->collect(e | ElementOwningMembership_Mapping.getMapped(e)) ->asSet()
```

GenericToConnector\_Mapping  
NamedElementMain\_Mapping

## Mapping Source

ObjectFlow

## Mapping Target

SuccessionFlowConnectionUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.guard.oclIsUndefined()  
and (not src.target.oclIsTypeOf(UML::ActivityFinalNode))
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SuccessionFlowConnectionUsage::ownedRelationship () : Relationship [0..\*]

```
let relationships : Set(KerML::Relationship) =  
let sourceFeatureMembership : KerML::FeatureMembership = ObjectFlowEndFeatureMembership_Mapping.getMapped(from)  
let targetFeatureMembership : KerML::FeatureMembership = ObjectFlowEndFeatureMembership_Mapping.getMapped(to)  
if from.source.oclIsKindOf(UML::ObjectNode) then  
    Set{ObjectFlowItemFeatureMembership_Mapping.getMapped(from),  
        sourceFeatureMembership, targetFeatureMembership}  
else  
    Set{sourceFeatureMembership, targetFeatureMembership}  
endif in  
  
let relationshipsConsideringWeight : Set(KerML::Relationship) =  
if from.weight.oclIsUndefined() then  
    relationships  
else  
    relationships  
    ->including(ActivityEdgeMetadataOwningMembership_Mapping.getMapped(from))  
endif in  
  
let relationshipsConsideringRate : Set(KerML::Relationship) =  
if (Helper.hasStereotypeApplied(from, 'SysML::Activities::Rate') or  
    Helper.hasStereotypeApplied(from, 'SysML::Activities::Discrete') or  
    Helper.hasStereotypeApplied(from, 'SysML::Activities::Continuous')) then  
  
    relationshipsConsideringWeight  
    ->including(RateOwningMembership_Mapping.getMapped(from))  
else  
    relationshipsConsideringWeight  
endif in
```

```

->union(from.incoming->collect(i | ControlNodeObjectFlowFeatureMembership_Mapping.getMapped
->union(from.outgoing->collect(i | ControlNodeObjectFlowFeatureMembership_Mapping.getMapped
else
  Set{}
endif

```

### 7.7.3.3.47 ObjectFlow\_Mapping

**SYSML2 -417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"**

**SYSML2 -424: Adopted resolution SYSML2 -403 has impact on the v1 to v2 Transformation**

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

A UML4SysML::ObjectFlowFlow without a guard condition is mapped to a SysMLv2 SuccessionFlowUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action def SysMLv1Acticity {
  action sysMLv1Action1 {
    out outputValue;
  }
  succession flow sysMLv1ObjectFlow of ScalarValues::String
    from sysMLv1Action1.outputValue to sysMLv1Action1.inputValue;
  action sysMLv1Action2 {
    out inputValue;
  }
}

```

#### General Mappings

ToConnector\_Init  
 NamedElementMain\_Mapping  
 ToFlowUsage\_Init

#### Mapping Source

ObjectFlow

#### Mapping Target

SuccessionFlowUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```

src.guard.oclIsUndefined()
and (not src.target.oclIsTypeOf(UML::ActivityFinalNode))

```

```

self.oclassType(ElementMain_Mapping).ownedRelationship()->union(
  if Helper.hasStereotypeApplied(from, 'SysML::Activities::Probability') then
    relationshipsConsideringRate
    ->including(ProbabilityOwningMembership_Mapping.getMapped(from))
  else
    relationshipsConsideringRate
  endif
)

```

### 7.7.3.3.36 ObjectFlowFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

ObjectFlow

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
ObjectFlow_Mapping.getMapped(from)
```

### 7.7.3.3.37 ObjectFlowGuardFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SuccessionFlowUsage::ownedRelationship () : Relationship [0..\*]

```
let relationships : Set(KerML::Relationship) =
let sourceFeatureMembership : KerML::FeatureMembership = ObjectFlowEndFeatureMembership_Mapping
let targetFeatureMembership : KerML::FeatureMembership = ObjectFlowEndFeatureMembership_Mapping
if from.source.ocIsKindOf(UML::ObjectNode) then
    Set{ObjectFlowItemFeatureMembership_Mapping.getMapped(from),
        sourceFeatureMembership, targetFeatureMembership}
else
    Set{sourceFeatureMembership, targetFeatureMembership}
endif in

let relationshipsConsideringWeight : Set(KerML::Relationship) =
if from.weight.ocIsUndefined() then
    relationships
else
    relationships
    ->including(ActivityEdgeMetadataOwningMembership_Mapping.getMapped(from))
endif in

let relationshipsConsideringRate : Set(KerML::Relationship) =
if (Helper.hasStereotypeApplied(from, 'SysML::Activities::Rate') or
    Helper.hasStereotypeApplied(from, 'SysML::Activities::Discrete') or
    Helper.hasStereotypeApplied(from, 'SysML::Activities::Continuous')) then

    relationshipsConsideringWeight
    ->including(RateOwningMembership_Mapping.getMapped(from))
else
    relationshipsConsideringWeight
endif in

self.ocAsType(ElementMain_Mapping).ownedRelationship()->union(
    if Helper.hasStereotypeApplied(from, 'SysML::Activities::Probability') then
        relationshipsConsideringRate
        ->including(ProbabilityOwningMembership_Mapping.getMapped(from))
    else
        relationshipsConsideringRate
    endif
)
```

### 7.7.3.3.48 ObjectFlowFeatureMembership\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

ObjectFlow

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`ObjectFlowGuard_Mapping.getMapped(from)`

### 7.7.3.3.38 ObjectFlowGuard\_Mapping

#### Description

A UML4SysML::ObjectFlowFlow with a guard condition is mapped to a combined SysMLv2 TransitionUsage and SysMLv2 SuccessionFlowConnectionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
  action sysMLv1Action1 {
    out outputValue;
  }

  first sysMLv1Action1 if guardCondition.result then sysMLv1ObjectFlow {
    calc guardCondition {
      return : ScalarValues::Boolean;
      language "English"
    }
    /*
     * guard says ok
     */
  }
}

succession flow sysMLv1ObjectFlow of SysMLv1Block from
  sysMLv1Action1.outputValue to sysMLv1Action2.inputValue;

action sysMLv1Action2 {
  out inputValue;
}
}
```

## General Mappings



ObjectFlow

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

`ObjectFlow_Mapping.getMapped(from)`

## 7.7.3.3.49 ObjectFlowGuardFeatureMembership\_Mapping

### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

ObjectFlow

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

**GenericToTransitionUsage\_Mapping**  
NamedElementMain\_Mapping

#### Mapping Source

ObjectFlow

#### Mapping Target

TransitionUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(not src.guard.oclIsUndefined())  
and (not src.target.oclIsTypeOf(UML::ActivityFinalNode))
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TransitionUsage::ownedRelationship () : Relationship [0..\*]

```
Set{  
  ActivityEdgeTransitionUsageSourceMembership_Mapping.getMapped(from.source),  
  CommonParameterReferenceUsageInMembership_Mapping.getMapped(from.source),  
  ObjectFlowTransitionUsageFeatureMembership_Mapping.getMapped(from),  
  ObjectFlowGuardSuccessionTargetEndFeatureMembership_Mapping.getMapped(from),  
  CommonActivityEdgeSuccessionAsUsage_Mapping.getMapped(from),  
  CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)  
}->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
```

### 7.7.3.3.39 ObjectFlowGuardSuccessionTargetEndFeature\_Mapping

#### Description

Creates a feature element for the UML4SysML::ObjectFlow mapping.

#### General Mappings

**GenericToFeature\_Mapping**

#### Mapping Source

ObjectFlow

#### Mapping Target

Feature

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

ObjectFlowGuard\_Mapping.getMapped(from)

### 7.7.3.3.50 ObjectFlowGuard\_Mapping

**SYSML2\_-417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"**

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

A UML4SysML::ObjectFlowFlow with a guard condition is mapped to a combined SysMLv2 TransitionUsage and SysMLv2 SuccessionFlowUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
  action sysMLv1Action1 {
    out outputValue;
  }

  first sysMLv1Action1 if guardCondition.result then sysMLv1ObjectFlow {
    calc guardCondition {
      return : ScalarValues::Boolean;
      language "English"
      /*
       * guard says ok
       */
    }
  }
  succession flow sysMLv1ObjectFlow of SysMLv1Block from
    sysMLv1Action1.outputValue to sysMLv1Action2.inputValue;

  action sysMLv1Action2 {
    out inputValue;
  }
}
```

#### General Mappings

ToTransitionUsage\_Init

NamedElementMain\_Mapping

#### Mapping Source

ObjectFlow

#### Mapping Target

TransitionUsage

#### Owned Mappings

## Owned Mappings

- `objectFlowGuardSuccessionTargetEndSubsetting :`  
`ObjectFlowGuardSuccessionTargetEndSubsetting_Mapping`

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::isEnd () : Boolean [1]`  
`true`
- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set {objectFlowGuardSuccessionTargetEndSubsetting.to}`

### 7.7.3.3.40 ObjectFlowGuardSuccessionTargetEndFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

`GenericToEndFeatureMembership_Mapping`

#### Mapping Source

`ObjectFlow`

#### Mapping Target

`EndFeatureMembership`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  
`ObjectFlowGuardSuccessionTargetEndFeature_Mapping.getMapped(from)`

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(not src.guard.oclIsUndefined())  
and (not src.target.oclIsTypeOf(UML::ActivityFinalNode))
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TransitionUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{  
  ActivityEdgeTransitionUsageSourceMembership_Mapping.getMapped(from.source),  
  CommonParameterReferenceUsageInMembership_Mapping.getMapped(from.source),  
  ObjectFlowTransitionUsageFeatureMembership_Mapping.getMapped(from),  
  ObjectFlowGuardSuccessionTargetEndFeatureMembership_Mapping.getMapped(from),  
  CommonActivityEdgeSuccessionAsUsage_Mapping.getMapped(from),  
  CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)  
}->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
```

#### 7.7.3.3.51 ObjectFlowGuardSuccessionTargetEndFeature\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature element for the UML4SysML::ObjectFlow mapping.

### General Mappings

ToFeature\_Init  
Mapping

### Mapping Source

ObjectFlow

### Mapping Target

Feature

### Owned Mappings

- objectFlowGuardSuccessionTargetEndSubsetting :  
ObjectFlowGuardSuccessionTargetEndSubsetting\_Mapping

### Applicable filters

(none)

### Mapping rules

### 7.7.3.3.41 ObjectFlowGuardSuccessionTargetEndSubsetting\_Mapping

#### Description

Creates a subsetting relationship.

#### General Mappings

`GenericToSubsetting_Mapping`

#### Mapping Source

ObjectFlow

#### Mapping Target

Subsetting

#### Owned Mappings

- `objectFlowGuardSuccessionTargetEndFeature : ObjectFlowGuardSuccessionTargetEndFeature_Mapping`

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Subsetting::subsettingFeature () : Feature [1]`  
`objectFlowGuardSuccessionTargetEndFeature.to`
- `Subsetting::subsettingFeature () : Feature [1]`  
`ObjectFlow_Mapping.getMapped(from)`

### 7.7.3.3.42 ObjectFlowItemFeature\_Mapping

#### Description

The mapping class maps the source UML4SysML::ObjectNode to a ItemFeature which is typed by the UML4SysML::ObjectNode type.

#### General Mappings

ObjectFlowItemFeatureUntyped\_Mapping

#### Mapping Source

ObjectNode

#### Mapping Target

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::isEnd () : Boolean [1]`  
`true`
- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set{objectFlowGuardSuccessionTargetEndSubsetting.to}`

### 7.7.3.3.52 ObjectFlowGuardSuccessionTargetEndFeatureMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToEndFeatureMembership\_Init  
Mapping

#### Mapping Source

ObjectFlow

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  
`ObjectFlowGuardSuccessionTargetEndFeature_Mapping.getMapped(from)`

### 7.7.3.3.53 ObjectFlowGuardSuccessionTargetEndSubsetting\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a subsetting relationship.





## General Mappings

ToSubsetting\_Init  
Mapping

## Mapping Source

ObjectFlow

## Mapping Target

Subsetting

## Owned Mappings

- objectFlowGuardSuccessionTargetEndFeature : ObjectFlowGuardSuccessionTargetEndFeature\_Mapping

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subsetting::subsettingFeature () : Feature [1]  
`ObjectFlow_Mapping.getMapped(from)`
- Subsetting::subsettingFeature () : Feature [1]  
`objectFlowGuardSuccessionTargetEndFeature.to`

### 7.7.3.3.54 ObjectFlowItemFeature\_Mapping

#### Description

The mapping class maps the source UML4SysML::ObjectNode to a ItemFeature which is typed by the UML4SysML::ObjectNode type.

## General Mappings

ObjectFlowItemFeatureUntyped\_Mapping

## Mapping Source

ObjectNode

## Mapping Target

PayloadFeature

## Owned Mappings

(none)

ItemFeature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ItemFeature::ownedRelationship () : Relationship [0..\*]  
`Set {ObjectFlowItemFeatureTyping_Mapping.getMapped(from) }`

### 7.7.3.3.43 ObjectFlowItemFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

ObjectFlow

#### Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  

```
if from.source.type.oclIsUndefined() then
    ObjectFlowItemFeatureUntyped_Mapping.getMapped(from.source)
else
```

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PayloadFeature::ownedRelationship () : Relationship [0..*]`  
`Set{ObjectFlowItemFeatureTyping_Mapping.getMapped(from) }`

### 7.7.3.3.55 ObjectFlowItemFeatureMembership\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

ObjectFlow

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  

```
if from.source.type.ocIsUndefined() then
    ObjectFlowItemFeatureUntyped_Mapping.getMapped(from.source)
else
    ObjectFlowItemFeature_Mapping.getMapped(from.source)
endif
```

```
        ObjectFlowItemFeature_Mapping.getMapped(from.source)
    endif
```

#### 7.7.3.3.44 ObjectFlowItemFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

TypedElementFeatureTyping\_Mapping

##### Mapping Source

ObjectNode

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

#### 7.7.3.3.45 ObjectFlowItemFeatureUntyped\_Mapping

##### Description

The mapping class maps the source UML4SysML::ObjectNode to a ItemFeature without a type.

##### General Mappings

GenericToFeature\_Mapping

##### Mapping Source

ObjectNode

##### Mapping Target

ItemFeature

##### Owned Mappings

(none)

#### 7.7.3.3.46 ObjectFlowEndFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

GenericToEndFeatureMembership\_Mapping

### 7.7.3.3.56 ObjectFlowItemFeatureTyping\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

TypedElementFeatureTyping\_Mapping

#### Mapping Source

ObjectNode

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.3.3.57 ObjectFlowItemFeatureUntyped\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

The mapping class maps the source UML4SysML::ObjectNode to a ItemFeature without a type.

#### General Mappings

ToFeature\_[Init](#)

#### Mapping Source

ObjectNode

#### Mapping Target

[PayloadFeature](#)

#### Owned Mappings

(none)

#### Applicable filters

(none)

## Mapping Source

ActivityNode

## Mapping Target

EndFeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]

`ObjectFlowItemFlowEnd_Mapping.getMapped (from)`

### 7.7.3.3.47 ObjectFlowItemFlowEnd\_Mapping

#### Description

The mapping class maps a UML4SysML::ActivityNode to a ItemFlowEnd which is subsetted by the transformation target of the UML4SysML::ActivityNode.

#### General Mappings

GenericToFeature\_Mapping

## Mapping Source

ActivityNode

## Mapping Target

ItemFlowEnd

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

### 7.7.3.3.58 ObjectFlowEndFeatureMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToEndFeatureMembership\_**Init**  
Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`ObjectFlowItemFlowEnd_Mapping.getMapped(from)`

### 7.7.3.3.59 ObjectFlowItemFlowEnd\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

The mapping class maps a UML4SysML::ActivityNode to a ItemFlowEnd which is subsetted by the transformation target of the UML4SysML::ActivityNode.

#### General Mappings

ToFeature\_**Init**  
Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **ItemFlowEnd::ownedRelationship ()** : Relationship [0..\*]  

```
Set{ObjectFlowItemFlowEndSubsetting_Mapping.getMapped(from) ,
ObjectFlowItemFlowEndFeatureMembership_Mapping.getMapped(from) }
```
- **ItemFlowEnd::isEnd ()** : Boolean [1]  

```
true
```

### 7.7.3.3.48 ObjectFlowItemFlowEndReferenceUsage\_Mapping

#### Description

Creates a feature element for the UML4SysML::ObjectFlow mapping.

#### General Mappings

**GenericToReferenceUsage\_Mapping**

#### Mapping Source

ActivityNode

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **ReferenceUsage::ownedRelationship ()** : Relationship [0..\*]  

```
let redefinition : KerML::Redefinition =
if from.owner.ocliIsTypeOf(UML::AddVariableValueAction) or
from.owner.ocliIsTypeOf(UML::AddStructuralFeatureValueAction) then
if from.name = 'value' then
ObjectFlowItemFlowEndRedefinition_Factory.create(SYSML2::ReferenceUsage.allInstances
->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction::value'))
else if from.name = 'insertAt' then
ObjectFlowItemFlowEndRedefinition_Factory.create(SYSML2::ReferenceUsage.allInstances
->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction::insertAt'))
else if from.owner.ocliIsTypeOf(UML::AddStructuralFeatureValueAction) and (from.name = 'ob
ObjectFlowItemFlowEndRedefinition_Factory.create(SYSML2::ReferenceUsage.allInstances
->any(m | m.qualifiedName = 'SysMLv1Library::AddStructuralFeatureValueAction::obj
```



FlowEnd

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FlowEnd::ownedRelationship () : Relationship [0..\*]  

```
Set{ObjectFlowItemFlowEndSubsetting_Mapping.getMapped(from) ,  
ObjectFlowItemFlowEndFeatureMembership_Mapping.getMapped(from) }
```
- FlowEnd::isEnd () : Boolean [1]  

```
true
```

### 7.7.3.3.60 ObjectFlowItemFlowEndReferenceUsage\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature element for the UML4SysML::ObjectFlow mapping.

#### General Mappings

ToReferenceUsage\_Init  
Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

```

        else
            ObjectFlowItemFlowEndRedefinition_Factory.create(ElementMain_Mapping.getMapped(from))
        endif endif endif
    else
        if from.ocllsTypeOf(UML::ActivityParameterNode) then
            ObjectFlowItemFlowEndRedefinition_Factory.create(
                ElementMain_Mapping.getMapped(from.oclAsType(UML::ActivityParameterNode)).parameter
            )
        else if from.ocllsTypeOf(UML::FlowFinalNode) then
            ObjectFlowItemFlowEndRedefinition_Factory.create(ElementMain_Mapping.getMapped(
                SysMLv2::ActionUsage.allInstances()->any(e | e.qualifiedName = 'Actions::Action::done')
            ))
        else
            ObjectFlowItemFlowEndRedefinition_Factory.create(ElementMain_Mapping.getMapped(from))
        endif endif
    endif in
    Set{redefinition}

```

### 7.7.3.3.49 ObjectFlowItemFlowEndFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
ObjectFlowItemFlowEndReferenceUsage_Mapping.getMapped(from)
```

### 7.7.3.3.50 ObjectFlowItemFlowEndRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
let redefinition : KerML::Redefinition =
if from.owner.ocIsTypeOf(UML::AddVariableValueAction) or
  from.owner.ocIsTypeOf(UML::AddStructuralFeatureValueAction) then
  if from.name = 'value' then
    ObjectFlowItemFlowEndRedefinition_Factory.create(SYSML2::ReferenceUsage.allInstances()
      ->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction::value'))
  else if from.name = 'insertAt' then
    ObjectFlowItemFlowEndRedefinition_Factory.create(SYSML2::ReferenceUsage.allInstances()
      ->any(m | m.qualifiedName = 'SysMLv1Library::AddValueAction::insertAt'))
  else if from.owner.ocIsTypeOf(UML::AddStructuralFeatureValueAction) and (from.name = 'ob
    ObjectFlowItemFlowEndRedefinition_Factory.create(SYSML2::ReferenceUsage.allInstances()
      ->any(m | m.qualifiedName = 'SysMLv1Library::AddStructuralFeatureValueAction::obj
  else
    ObjectFlowItemFlowEndRedefinition_Factory.create(ElementMain_Mapping.getMapped(from))
  endif endif endif
endif
else
  if from.ocIsTypeOf(UML::ActivityParameterNode) then
    ObjectFlowItemFlowEndRedefinition_Factory.create(
      ElementMain_Mapping.getMapped(from.ocAsType(UML::ActivityParameterNode).parameter
  else if from.ocIsTypeOf(UML::FlowFinalNode) then
    ObjectFlowItemFlowEndRedefinition_Factory.create(ElementMain_Mapping.getMapped(
      SysMLv2::ActionUsage.allInstances()->any(e | e.qualifiedName = 'Actions::Action::dor
  else
    ObjectFlowItemFlowEndRedefinition_Factory.create(ElementMain_Mapping.getMapped(from))
  endif endif
endif in
Set{redefinition}
```

### 7.7.3.3.61 ObjectFlowItemFlowEndFeatureMembership\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

ActivityNode

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

## General Mappings

**Generic**ToRedefinition\_Mapping

## Mapping Source

ActivityNode

## Mapping Target

Redefinition

## Owned Mappings

(none)

### 7.7.3.3.51 ObjectFlowItemFlowEndSubsetting\_Mapping

## Description

Creates a subsetting relationship.

## General Mappings

**Generic**ToReferenceSubsetting\_Mapping

## Mapping Source

ActivityNode

## Mapping Target

ReferenceSubsetting

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  

```
if from.ocIsKindOf(UML::ActivityParameterNode) then
    Parameter_Mapping.getMapped(from.parameter)
else if from.ocIsKindOf(UML::Pin) then
    CommonAction_Mapping.getMapped(from.owner)
else if from.ocIsKindOf(UML::InitialNode) then
    SysMLv2::ActionUsage.allInstances()
    ->any(e | e.qualifiedName = 'Actions::Action::start')
```

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

`ObjectFlowItemFlowEndReferenceUsage_Mapping.getMapped(from)`

### 7.7.3.3.62 ObjectFlowItemFlowEndRedefinition\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

ToRedefinition\_Init  
Mapping

#### Mapping Source

ActivityNode

#### Mapping Target

Redefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.3.3.63 ObjectFlowItemFlowEndSubsetting\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a subsetting relationship.

#### General Mappings

ToReferenceSubsetting\_Init  
Mapping

#### Mapping Source

ActivityNode

```

        else if from.ocIsKindOf(UML::FinalNode) then
            SysMLv2::ActionUsage.allInstances()
            ->any(e | e.qualifiedName = 'Actions::Action::done')
        else
            from
        endif
    endif
endif
endif

```

### 7.7.3.3.52 ObjectFlowTransitionUsageFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

ObjectFlow

#### Mapping Target

TransitionFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TransitionFeatureMembership::ownedMemberFeature () : Feature [1]
 

```

            if from.guard.ocIsKindOf(UML::OpaqueExpression) then
                OpaqueExpressionAsValue_Mapping.getMapped(from.guard)
            else
                from.guard
            endif
            
```
- TransitionFeatureMembership::kind () : TransitionFeatureKind [1]
 

```

            KerML::TransitionFeatureKind::guard
            
```

### 7.7.3.3.53 VariableAttribute\_Mapping

#### Description

## Mapping Target

ReferenceSubsetting

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]

```
if from.ocIsKindOf(UML::ActivityParameterNode) then
    Parameter_Mapping.getMapped(from.parameter)
else if from.ocIsKindOf(UML::Pin) then
    CommonAction_Mapping.getMapped(from.owner)
else if from.ocIsKindOf(UML::InitialNode) then
    SysMLv2::ActionUsage.allInstances()
    ->any(e | e.qualifiedName = 'Actions::Action::start')
else if from.ocIsKindOf(UML::FinalNode) then
    SysMLv2::ActionUsage.allInstances()
    ->any(e | e.qualifiedName = 'Actions::Action::done')
else
    from
endif
endif
endif
endif
```

### 7.7.3.3.64 ObjectFlowTransitionUsageFeatureMembership\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

ObjectFlow

## Mapping Target

TransitionFeatureMembership

## Owned Mappings

A UML4SysML::Variable is mapped to a SysML v2 AttributeUsage if the type of the variable is of kind UML4SysML::DataType.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    private attribute sysmlv1Variable : ScalarValues::Integer;  
}
```

## General Mappings

NamedElementMain\_Mapping  
CommonVariable\_Mapping

## Mapping Source

Variable

## Mapping Target

AttributeUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.type.ocIsKindOf(UML::DataType)
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.3.3.54 VariableFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

TypedElementFeatureTyping\_Mapping

#### Mapping Source

Variable

#### Mapping Target

FeatureTyping



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TransitionFeatureMembership::ownedMemberFeature () : Feature [1]`  

```
if from.guard.oclIsKindOf(UML::OpaqueExpression) then
    OpaqueExpressionAsValue_Mapping.getMapped(from.guard)
else
    from.guard
endif
```
- `TransitionFeatureMembership::kind () : TransitionFeatureKind [1]`  

```
KerML::TransitionFeatureKind::guard
```

### 7.7.3.3.65 VariableAttribute\_Mapping

#### Description

A `UML4SysML::Variable` is mapped to a SysML v2 `AttributeUsage` if the type of the variable is of kind `UML4SysML::DataType`.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
  private attribute sysmlv1Variable : ScalarValues::Integer;
}
```

#### General Mappings

`NamedElementMain_Mapping`  
`CommonVariable_Mapping`

#### Mapping Source

`Variable`

#### Mapping Target

`AttributeUsage`

#### Owned Mappings

(none)

#### Applicable filters

## Owned Mappings

(none)

### 7.7.3.3.55 VariableItem\_Mapping

#### Description

A UML4SysML::Variable is mapped to a SysML v2 ItemUsage if the type of the variable is not of kind UML4SysML::DataType.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    private item sysmlv1Variable : SysMLv1Block;  
}  
part def SysMLv1Block;
```

## General Mappings

NamedElementMain\_Mapping  
CommonVariable\_Mapping

## Mapping Source

Variable

## Mapping Target

ItemUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not src.type.ocIsKindOf(UML::DataType)
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.3.3.56 VariableMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

## General Mappings

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.type.ocIsKindOf(UML::DataType)
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

#### 7.7.3.3.66 VariableFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

TypedElementFeatureTyping\_Mapping

##### Mapping Source

Variable

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.3.3.67 VariableItem\_Mapping

##### Description

A UML4SysML::Variable is mapped to a SysML v2 ItemUsage if the type of the variable is not of kind UML4SysML::DataType.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
  private item sysmlv1Variable : SysMLv1Block;  
}  
part def SysMLv1Block;
```

##### General Mappings

NamedElementMain\_Mapping

CommonVariable\_Mapping

##### Mapping Source

ElementFeatureMembership\_Mapping

### Mapping Source

Variable

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::visibility () : VisibilityKind [1]

KerML::VisibilityKind::private

## 7.7.4 Classification

### 7.7.4.1 Overview

Table 5. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Generalization	Subclassification
GeneralizationSet	not mapped; see next section
InstanceSpecification	ConnectionUsage
InstanceValue	FeatureReferenceExpression
Operation	PerformActionUsage
Parameter	ReferenceUsage
ParameterSet	not mapped; see next section
Property	AttributeUsage
Slot	Feature
Substitution	SatisfyRequirementUsage AllocationDefinition

The following table gives an overview of which SysML v2 elements the UML4SysML::Classification elements are transformed with which mapping class. The mapping details are in [7.7.4.2](#).

### 7.7.4.2 Mapping Specifications

Variable

### Mapping Target

ItemUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not src.type.ocIsKindOf(UML::DataType)
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

## 7.7.3.3.68 VariableMembership\_Mapping

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ElementFeatureMembership\_Mapping

### Mapping Source

Variable

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::visibility () : VisibilityKind [1]

```
KerML::VisibilityKind::private
```

## 7.7.4 Classification

#### 7.7.4.2.1 BehavioralFeature\_Mapping

##### Description

The mapping class is the abstract base class for UML4SysML::BehavioralFeature mappings.

##### General Mappings

GenericToUsage\_Mapping

Namespace\_Mapping

##### Mapping Source

BehavioralFeature

##### Mapping Target

Usage

##### Owned Mappings

(none)

#### 7.7.4.2.2 Classifier\_Mapping

##### Description

The mapping class is the abstract base class for all mapping classes that map specializations of UML4SysML::Classifier elements.

##### General Mappings

GenericToClassifier\_Mapping

Namespace\_Mapping

##### Mapping Source

Classifier

##### Mapping Target

Classifier

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

### 7.7.4.1 Overview

**[SYSML2\\_-329: Mapping overview tables are wrong](#)**

**Table 5. List of all mappings**

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Generalization	Subclassification
GeneralizationSet	not mapped; see next section
InstanceSpecification	PartUsage ConnectionUsage
InstanceValue	FeatureReferenceExpression
Operation	PerformActionUsage
Parameter	ReferenceUsage
ParameterSet	not mapped; see next section
Property	AttributeUsage OccurrenceUsage Feature ReferenceUsage
Slot	Feature
Substitution	Dependency

### 7.7.4.2 Mapping Specifications

#### 7.7.4.2.1 BehavioralFeature\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

The mapping class is the abstract base class for UML4SysML::BehavioralFeature mappings.

#### General Mappings

ToUsage\_Init

Namespace\_Mapping

#### Mapping Source

BehavioralFeature

#### Mapping Target

Usage

#### Owned Mappings

(none)

#### Applicable filters

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Classifier::isAbstract () : Boolean [1]`

```
from.isAbstract
```

- `Classifier::ownedRelationship () : Relationship [0..*]`

```
let generalizations : Set(UML::Generalization) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Generalization))->asSet() in
let toElementFMS: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Feature))->asSet() in
let toElementOMS: Set(UML::Element) =
    ((from.ownedElement - toElementFMS) - generalizations) - from.ownedComment in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e))->asSet())
->union(self.ocAsType(ElementMain_Mapping).ownedRelationship())
```

#### 7.7.4.2.3 DefaultLowerBound\_Mapping

##### Description

The mapping class creates the default lower bound of a multiplicity element.

##### General Mappings

`GenericToExpression_Mapping`

##### Mapping Source

Element

##### Mapping Target

LiteralInteger

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `LiteralInteger::ownedRelationship () : Relationship [0..*]`

```
Set { CommonReturnParameterFeatureMembership_Mapping.getMapped(from) }
```

- `LiteralInteger::value () : Integer [1]`



(none)

#### 7.7.4.2.2 Classifier\_Mapping

**SysML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

The mapping class is the abstract base class for all mapping classes that map specializations of UML4SysML::Classifier elements.

##### General Mappings

ToClassifier\_Init  
Namespace\_Mapping

##### Mapping Source

Classifier

##### Mapping Target

Classifier

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Classifier::ownedRelationship () : Relationship [0..\*]

```
let generalizations : Set(UML::Generalization) =  
    from.ownedElement->select(e | e.ocIsKindOf(UML::Generalization))->asSet() in  
let toElementFMS: Set(UML::Element) =  
    from.ownedElement->select(e | e.ocIsKindOf(UML::Feature))->asSet() in  
let toElementOMS: Set(UML::Element) =  
    ((from.ownedElement - toElementFMS) - generalizations) - from.ownedComment in  
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()  
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())  
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e))->asSet())  
->union(self.ocIsType(ElementMain_Mapping).ownedRelationship())
```

- Classifier::isAbstract () : Boolean [1]

```
from.isAbstract
```

#### 7.7.4.2.3 DefaultLowerBound\_Mapping

**SysML2\_-220: Replace Generic mapping classes by Initializers**

#### 7.7.4.2.4 DefaultMultiplicityBoundFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

GenericToFeatureMembership\_Mapping

##### Mapping Source

Element

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::isComposite () : Boolean [1]

true

#### 7.7.4.2.5 DefaultMultiplicityElement\_Mapping

##### Description

The mapping class creates a feature element representing the default multiplicity.

##### General Mappings

GenericToFeature\_Mapping

##### Mapping Source

Element

##### Mapping Target

MultiplicityRange

##### Owned Mappings

## Description

The mapping class creates the default lower bound of a multiplicity element.

## General Mappings

ToExpression\_Init  
Mapping

## Mapping Source

Element

## Mapping Target

LiteralInteger

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralInteger::ownedRelationship () : Relationship [0..\*]  
`Set { CommonReturnParameterFeatureMembership_Mapping.getMapped (from) }`
- LiteralInteger::value () : Integer [1]  
1

### 7.7.4.2.4 DefaultMultiplicityBoundFeatureMembership\_Mapping

#### [SYSML2\\_-220](#): Replace Generic mapping classes by Initializers

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

Element

## Mapping Target

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MultiplicityRange::declaredName () : String [0..1]  
`'defaultMultiplicity'`
- MultiplicityRange::isUnique () : Boolean [1]  
`true`
- MultiplicityRange::ownedRelationship () : Relationship [0..\*]  
`OrderedSet{DefaultMultiplicityLowerBoundFeatureMembership_Mapping.getMapped(from),  
DefaultMultiplicityUpperBoundFeatureMembership_Mapping.getMapped(from)}`

#### 7.7.4.2.6 DefaultMultiplicityLowerBoundFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

DefaultMultiplicityBoundFeatureMembership\_Mapping

##### Mapping Source

Element

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : MultiplicityRange [1]

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::isComposite () : Boolean [1]  
`true`

#### 7.7.4.2.5 DefaultMultiplicityElement\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates a feature element representing the default multiplicity.

### General Mappings

ToFeature\_Init  
Mapping

### Mapping Source

Element

### Mapping Target

MultiplicityRange

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MultiplicityRange::declaredName () : String [0..1]  
`'defaultMultiplicity'`

`DefaultLowerBound_Mapping.getMapped(from)`

#### 7.7.4.2.7 DefaultMultiplicityMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

`GenericToOwningMembership_Mapping`

##### Mapping Source

Element

##### Mapping Target

OwningMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`

`DefaultMultiplicityElement_Mapping.getMapped(from)`

#### 7.7.4.2.8 DefaultMultiplicityUpperBoundFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

`DefaultMultiplicityBoundFeatureMembership_Mapping`

##### Mapping Source

Element

##### Mapping Target

FeatureMembership

##### Owned Mappings

- `MultiplicityRange::ownedRelationship () : Relationship [0..*]`

```
OrderedSet(DefaultMultiplicityLowerBoundFeatureMembership_Mapping.getMapped(from),
DefaultMultiplicityUpperBoundFeatureMembership_Mapping.getMapped(from))
```

- `MultiplicityRange::isUnique () : Boolean [1]`

```
true
```

#### 7.7.4.2.6 DefaultMultiplicityLowerBoundFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

DefaultMultiplicityBoundFeatureMembership\_Mapping

##### Mapping Source

Element

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : MultiplicityRange [1]`

```
DefaultLowerBound_Mapping.getMapped(from)
```

#### 7.7.4.2.7 DefaultMultiplicityMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

Mapping

ToOwningMembership\_Init

##### Mapping Source

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : MultiplicityRange [1]`

`DefaultUpperBound_Mapping.getMapped(from)`

### 7.7.4.2.9 DefaultUpperBound\_Mapping

#### Description

The mapping class creates the default upper bound of a multiplicity element.

#### General Mappings

`GenericToExpression_Mapping`

#### Mapping Source

Element

#### Mapping Target

LiteralInteger

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `LiteralInteger::value () : Integer [1]`

`1`

- `LiteralInteger::ownedRelationship () : Relationship [0..*]`

`Set { CommonReturnParameterFeatureMembership_Mapping.getMapped(from) }`

### 7.7.4.2.10 DefaultValue\_Mapping

#### Description



Element

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`DefaultMultiplicityElement_Mapping.getMapped(from)`

## 7.7.4.2.8 DefaultMultiplicityUpperBoundFeatureMembership\_Mapping

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

DefaultMultiplicityBoundFeatureMembership\_Mapping

### Mapping Source

Element

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : MultiplicityRange [1]  
`DefaultUpperBound_Mapping.getMapped(from)`

The expected SysML v2 textual syntax of a mapped SysML v2 default value is as follows:

```
attribute sysMLv1Property : ScalarValues::String default := "default value";
```

## General Mappings

**Generic**ToFeatureValue\_Mapping

### Mapping Source

Property

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **FeatureValue::isDefault () : Boolean [1]**

**true**

- **FeatureValue::value () : Expression [1]**

**from.defaultValue**

## 7.7.4.2.11 ElementFeatureMembership\_Mapping

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

**Generic**ToFeatureMembership\_Mapping

### Mapping Source

Element

### Mapping Target

FeatureMembership

#### 7.7.4.2.9 DefaultUpperBound\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class creates the default upper bound of a multiplicity element.

##### General Mappings

ToExpression\_Init  
Mapping

##### Mapping Source

Element

##### Mapping Target

LiteralInteger

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralInteger::value () : Integer [1]  
1
- LiteralInteger::ownedRelationship () : Relationship [0..\*]  
Set{CommonReturnParameterFeatureMembership\_Mapping.getMapped(from) }

#### 7.7.4.2.10 DefaultValue\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The expected SysML v2 textual syntax of a mapped SysML v2 default value is as follows:

```
attribute sysMLv1Property : ScalarValues::String default := "default value";
```

##### General Mappings

ToFeatureValue\_Init  
Mapping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`NamedElementMain_Mapping.getMapped (from)`
- `FeatureMembership::visibility () : VisibilityKind [1]`  
`if from.ocIsKindOf (UML::NamedElement) then`  
`Helper.getKerMLVisibilityKind (from.ocAsType (UML::NamedElement).visibility)`  
`else KerML::VisibilityKind::public endif`

### 7.7.4.2.12 Generalization\_Mapping

#### Description

A `UML4SysML::Generalization` relationship is mapped to a `SysML v2 Subclassification`.

The following shows an example of what the textual `SysML v2` syntax of the result of the transformation may look like.

```
part def SysMLv1BlockGeneral;  
part def SysMLv1BlockSpecial :> SysMLv1BlockGeneral;
```

## General Mappings

`GenericToSpecialization_Mapping`  
`ElementMain_Mapping`

## Mapping Source

`Generalization`

## Mapping Target

`Subclassification`

## Owned Mappings

(none)

## Applicable filters

(none)

### Mapping Source

Property

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`from.defaultValue`
- `FeatureValue::isDefault () : Boolean [1]`  
`true`

#### 7.7.4.2.11 ElementFeatureMembership\_Mapping

##### **SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

Element

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)



## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`NamedElementMain_Mapping.getMapped(from)`
- `FeatureMembership::visibility () : VisibilityKind [1]`  
`if from.ooclIsKindOf(UML::NamedElement) then`  
`Helper.getKerMLVisibilityKind(from.ooclAsType(UML::NamedElement).visibility)`  
`else KerML::VisibilityKind::public endif`

### 7.7.4.2.12 Generalization\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

##### Description

A `UML4SysML::Generalization` relationship is mapped to a SysML v2 Subclassification.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1BlockGeneral;  
part def SysMLv1BlockSpecial :> SysMLv1BlockGeneral;
```

##### General Mappings

`ToSpecialization_Init`  
`ElementMain_Mapping`

##### Mapping Source

Generalization

##### Mapping Target

Subclassification

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Subclassification::subclassifier () : Classifier [1]`

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subclassification::superclassifier () : Classifier [1]

```
if from.general.oclIsTypeOf(UML::PrimitiveType)
    and not (Helper.getScalarValueType(from.general)
        = invalid) then
    Helper.getScalarValueType(from.general)
else
    Classifier_Mapping.getMapped(from.general)
endif
```

- Subclassification::subclassifier () : Classifier [1]

```
Classifier_Mapping.getMapped(from.specific)
```

### 7.7.4.2.13 InstanceSpecificationLink\_Mapping

#### Description

The UML4SysML::InstanceSpecification that is a link is mapped to a SysMLv2 ConnectionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1;
part def SysMLv1Block2;
connection def SysMLv1Association {
    end : SysMLv1Block1[1];
    end : SysMLv1Block2[1];
}
part sysMLv1InstanceSpecification1 : SysMLv1Block1;
part sysMLv1InstanceSpecification2 : SysMLv1Block2;
connection sysMLv1Link : SysMLv1Association
    connect sysMLv1InstanceSpecification1 to sysMLv1InstanceSpecification2;
```

#### General Mappings

NamedElementMain\_Mapping

GenericToConnectionUsage\_Mapping

#### Mapping Source

InstanceSpecification

#### Mapping Target

ConnectionUsage

#### Owned Mappings

(none)



```
Classifier_Mapping.getMapped(from.specific)
```

- Subclassification::superclassifier () : Classifier [1]

```
if from.general.oclIsTypeOf(UML::PrimitiveType)
    and not (Helper.getScalarValueType(from.general)
            = invalid) then
    Helper.getScalarValueType(from.general)
else
    Classifier_Mapping.getMapped(from.general)
endif
```

#### 7.7.4.2.13 InstanceSpecificationLink\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

The UML4SysML::InstanceSpecification that is a link is mapped to a SysMLv2 ConnectionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1;
part def SysMLv1Block2;
connection def SysMLv1Association {
    end : SysMLv1Block1[1];
    end : SysMLv1Block2[1];
}
part sysMLv1InstanceSpecification1 : SysMLv1Block1;
part sysMLv1InstanceSpecification2 : SysMLv1Block2;
connection sysMLv1Link : SysMLv1Association
    connect sysMLv1InstanceSpecification1 to sysMLv1InstanceSpecification2;
```

##### General Mappings

NamedElementMain\_Mapping  
ToConnectionUsage\_Init

##### Mapping Source

InstanceSpecification

##### Mapping Target

ConnectionUsage

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.classifier->select( c | c.oclIsTypeOf(UML::Association))->size() > 0
```

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.classifier->select( c | c.ocIsTypeOf(UML::Association))->size() > 0
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConnectionUsage::ownedRelationship() : Relationship [0..*]`

```
self.ocIsType(ElementMain_Mapping).ownedRelationship()  
->union(SlotMembership_Mapping.getMappedColl(from.slot)->asSet())  
->union(from.classifier  
    ->collect(g | InstanceSpecificationFeatureTyping_Mapping.getMapped(from, g))->asSet())  
->asSet()
```

### 7.7.4.2.14 InstanceSpecification\_Mapping

#### Description

The UML4SysML::InstanceSpecification that is not a link is mapped to a SysMLv2 PartDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {  
    attribute sysMLv1ValueProperty : ScalarValues::String;  
}  
  
part sysMLv1InstanceSpecification : SysMLv1Block {  
    redefines sysMLv1ValueProperty = "Hello InstanceSpecification";  
}
```

#### General Mappings

NamedElementMain\_Mapping

GenericToPartUsage\_Mapping

#### Mapping Source

InstanceSpecification

#### Mapping Target

PartUsage

#### Owned Mappings

(none)

#### Applicable filters

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConnectionUsage::ownedRelationship () : Relationship [0..*]`

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()  
->union(SlotMembership_Mapping.getMappedColl(from.slot)->asSet())  
->union(from.classifier  
    ->collect(g | InstanceSpecificationFeatureTyping_Mapping.getMapped(from, g))->asSet())  
->asSet()
```

### 7.7.4.2.14 InstanceSpecification\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

The UML4SysML::InstanceSpecification that is not a link is mapped to a SysMLv2 PartDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {  
    attribute sysMLv1ValueProperty : ScalarValues::String;  
}  
  
part sysMLv1InstanceSpecification : SysMLv1Block {  
    redefines sysMLv1ValueProperty = "Hello InstanceSpecification";  
}
```

##### General Mappings

NamedElementMain\_Mapping  
ToPartUsage\_Init

##### Mapping Source

InstanceSpecification

##### Mapping Target

PartUsage

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.classifier->select( c | c.oclIsTypeOf(UML::Association))->size() = 0
```

##### Mapping rules

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.classifier->select( c | c.ocIsTypeOf(UML::Association))->size() = 0
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **PartUsage::ownedRelationship () : Relationship [0..\*]**

```
SlotMembership_Mapping.getMappedColl(from.slot)->asSet()
->union(from.classifier
    ->collect(g | InstanceSpecificationFeatureTyping_Mapping.getMapped(from, g))->asSet())
->union(self.ocIsType(ElementMain_Mapping).ownedRelationship())
->asSet()
```

- **PartUsage::ownedFeatureMembership () : FeatureMembership [0..\*]**

```
from.classifier
->collect(c | InstanceSpecificationToGeneralization_Mapping.getMapped(from, c))
```

### 7.7.4.2.15 InstanceSpecificationFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**GenericToFeatureTyping\_Mapping**

#### Mapping Source

InstanceSpecification

#### Mapping Target

FeatureTyping with qualifier: classifier:Classifier

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **FeatureTyping::type (in classifier : Classifier) : Type [1]**

```
Classifier_Mapping.getMapped(classifier)
```

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PartUsage::ownedFeatureMembership () : FeatureMembership [0..*]`

```
from.classifier
->collect(c | InstanceSpecificationToGeneralization_Mapping.getMapped(from, c))
```

- `PartUsage::ownedRelationship () : Relationship [0..*]`

```
SlotMembership_Mapping.getMappedColl(from, slot) -> asSet()
-> union(from.classifier
    -> collect(g | InstanceSpecificationFeatureTyping_Mapping.getMapped(from, g)) -> asSet())
-> union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
-> asSet()
```

#### 7.7.4.2.15 InstanceSpecificationFeatureTyping\_Mapping

##### SYSML2 -220: Replace Generic mapping classes by Initializers

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

ToFeatureTyping\_Init  
Mapping

##### Mapping Source

InstanceSpecification

##### Mapping Target

FeatureTyping with qualifier: classifier:Classifier

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type (in classifier : Classifier) : Type [1]`

```
Classifier_Mapping.getMapped(classifier)
```

#### 7.7.4.2.16 InstanceValue\_Mapping

##### Description

#### 7.7.4.2.16 InstanceValue\_Mapping

##### Description

The UML4SysML::InstanceValue is mapped to a SysMLv2 FeatureReferenceExpression.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1;
part sysMLv1InstanceSpecification : SysMLv1Block1;
part def SysMLv1Block2 {
    part sysMLv1PartProperty : SysMLv1Block1
        = sysMLv1InstanceSpecification;
}
```

##### General Mappings

ValueSpecification\_Mapping

##### Mapping Source

InstanceValue

##### Mapping Target

FeatureReferenceExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType (ElementMain_Mapping).ownedRelationship ()
->including (InstanceValueMembership_Mapping.getMapped (from.instance))
->including (ReturnParameterFeatureMembership_Factory.create ())
```

#### 7.7.4.2.17 InstanceValueMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToMembership\_Mapping

The UML4SysML::InstanceValue is mapped to a SysMLv2 FeatureReferenceExpression.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1;
part sysMLv1InstanceSpecification : SysMLv1Block1;
part def SysMLv1Block2 {
    part sysMLv1PartProperty : SysMLv1Block1
        = sysMLv1InstanceSpecification;
}
```

## General Mappings

ValueSpecification\_Mapping

### Mapping Source

InstanceValue

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()
->including(InstanceValueMembership_Mapping.getMapped(from.instance))
->including(ReturnParameterFeatureMembership_Factory.create())
```

#### 7.7.4.2.17 InstanceValueMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

### Mapping Source

InstanceSpecification

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
from

## 7.7.4.2.18 LowerBoundValueFeatureMembership\_Mapping

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

GenericToFeatureMembership\_Mapping

### Mapping Source

MultiplicityElement

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules



InstanceSpecification

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

from

#### 7.7.4.2.18 LowerBoundValueFeatureMembership\_Mapping

[SYSML2 -220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init

### Mapping Source

MultiplicityElement

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`  
`LiteralInteger_Mapping.getMapped(from.lowerValue)`

#### 7.7.4.2.19 MultiplicityElement\_Mapping

##### Description

A `UML4SysML::MultiplicityElement` is mapped to a SysML v2 `MultiplicityRange`.

##### General Mappings

`GenericToFeature_Mapping`

##### Mapping Source

`MultiplicityElement`

##### Mapping Target

`MultiplicityRange`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `MultiplicityRange::declaredName () : String [0..1]`  
`'multiplicity'`
- `MultiplicityRange::ownedRelationship () : Relationship [0..*]`  
`OrderedSet{MultiplicityLowerBoundOwningMembership_Mapping.getMapped(from),  
MultiplicityUpperBoundOwningMembership_Mapping.getMapped(from) }`
- `MultiplicityRange::isUnique () : Boolean [1]`  
`from.isUnique`

#### 7.7.4.2.20 MultiplicityLowerBoundOwningMembership\_Mapping

##### Description

Creates a owning membership relationship for `ownedMemberElement()`.

```
LiteralInteger_Mapping.getMapped(from.lowerValue)
```

#### 7.7.4.2.19 MultiplicityElement\_Mapping

**SysML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

A UML4SysML::MultiplicityElement is mapped to a SysML v2 MultiplicityRange.

##### General Mappings

ToFeature\_Init  
Mapping

##### Mapping Source

MultiplicityElement

##### Mapping Target

MultiplicityRange

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MultiplicityRange::declaredName () : String [0..1]  
`'multiplicity'`
- MultiplicityRange::isUnique () : Boolean [1]  
`from.isUnique`
- MultiplicityRange::ownedRelationship () : Relationship [0..\*]  
`OrderedSet{MultiplicityLowerBoundOwningMembership_Mapping.getMapped(from),  
MultiplicityUpperBoundOwningMembership_Mapping.getMapped(from)}`

#### 7.7.4.2.20 MultiplicityLowerBoundOwningMembership\_Mapping

**SysML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

Creates a owning membership relationship for *ownedMemberElement()*.

##### General Mappings

## General Mappings

GenericToOwningMembership\_Mapping

### Mapping Source

MultiplicityElement

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

```
if from.lowerValue.ocIsUndefined() then
    DefaultLowerBound_Mapping.getMapped(from)
else
    from.lowerValue
endif
```

- OwningMembership::memberName () : String [0..1]

```
'lowerBound'
```

#### 7.7.4.2.21 MultiplicityMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToOwningMembership\_Mapping

##### Mapping Source

MultiplicityElement

##### Mapping Target

OwningMembership

##### Owned Mappings

ToOwningMembership\_Init  
Mapping

### Mapping Source

MultiplicityElement

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::memberName () : String [0..1]  
`'lowerBound'`
- OwningMembership::ownedMemberElement () : Element [1]  

```
if from.lowerValue.oclIsUndefined() then
    DefaultLowerBound_Mapping.getMapped(from)
else
    from.lowerValue
endif
```

#### 7.7.4.2.21 MultiplicityMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToOwningMembership\_Init  
Mapping

### Mapping Source

MultiplicityElement

### Mapping Target

OwningMembership

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`MultiplicityElement_Mapping.getMapped(from)`

### 7.7.4.2.22 MultiplicityUpperBoundOwningMembership\_Mapping

#### Description

Creates a owning membership relationship for *ownedMemberElement()*.

#### General Mappings

GenericToOwningMembership\_Mapping

#### Mapping Source

MultiplicityElement

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  

```
if from.upperValue.oclIsUndefined() then
    DefaultUpperBound_Mapping.getMapped(from)
else
    from.upperValue
endif
```
- `OwningMembership::memberName () : String [0..1]`  
`'upperBound'`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`MultiplicityElement_Mapping.getMapped(from)`

### 7.7.4.2.22 MultiplicityUpperBoundOwningMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Creates a owning membership relationship for *ownedMemberElement()*.

## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

MultiplicityElement

## Mapping Target

OwningMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  

```
if from.upperValue.oclIsUndefined() then
    DefaultUpperBound_Mapping.getMapped(from)
else
```

### 7.7.4.2.23 Operation\_Mapping

#### Description

A UML4SysML::Operation is mapped to a SysML v2 PerformActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {
    perform action sysMLv1Operation {
        in parIn : ScalarValues::Boolean;
        out result : ScalarValues::Integer;
    }
}
```

#### General Mappings

BehavioralFeature\_Mapping

GenericToActionUsage\_Mapping

#### Mapping Source

Operation

#### Mapping Target

PerformActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PerformActionUsage::ownedRelationship () : Relationship [0..\*]

```
let parameters: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
let parameterSets: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::ParameterSet)) in
self.ocAsType(ElementMain_Mapping).ownedRelationship()
->union(parameters->collect(e | ParameterMembership_Mapping.getMapped(e))->asSet())
->union(parameterSets->collect(e | ParameterSetMembership_Mapping.getMapped(e))->asSet())
```

### 7.7.4.2.24 Parameter\_Mapping

#### Description



```

        from.upperValue
    endif

```

- OwningMembership::memberName () : String [0..1]

```

    'upperBound'

```

#### 7.7.4.2.23 Operation\_Mapping

**[SYSML2 -136: Transformation of UML4SysML::State does not consider entry, do, and exit behavior](#)**

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

A UML4SysML::Operation is mapped to a SysML v2 PerformActionUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

part def SysMLv1Block {
    perform action sysMLv1Operation {
        in parIn : ScalarValues::Boolean;
        out result : ScalarValues::Integer;
    }
}

```

##### General Mappings

BehavioralFeature\_Mapping  
ToPerformActionUsage\_Init

##### Mapping Source

Operation

##### Mapping Target

PerformActionUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PerformActionUsage::ownedRelationship () : Relationship [0..\*]

```

let parameters: Set(UML::Element) =

```

A UML4SysML::Parameter is mapped to a SysML v2 ReferenceUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {  
    in parIn : ScalarValues::Boolean;  
}
```

## General Mappings

GenericToReferenceUsage\_Mapping  
NamedElementMain\_Mapping

## Mapping Source

Parameter

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]  
    Helper.getKerMLParameterDirectionKind(from.direction)
- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
let typings: Set(KerML::FeatureTyping) =  
    if from.type.ocIsUndefined() then  
        Set{}  
    else  
        Set{ParameterToFeatureTyping_Mapping.getMapped(from)}  
    endif in  
let multiplicities: Set(KerML::Relationship) =  
    Set{MultiplicityMembership_Mapping.getMapped(from)} in  
let defaultValues: Set(KerML::Relationship) =  
    if from.defaultValue.ocIsUndefined() then  
        Set{}  
    else  
        Set{ParameterDefaultValue_Mapping.getMapped(from)}  
    endif in
```

```

    from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
let parameterSets: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::ParameterSet)) in
self.ocAsType(ElementMain_Mapping).ownedRelationship()
->union(parameters->collect(e | ParameterMembership_Mapping.getMapped(e))->asSet())
->union(parameterSets->collect(e | ParameterSetMembership_Mapping.getMapped(e))->asSet())

```

#### 7.7.4.2.24 Parameter\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

##### Description

A UML4SysML::Parameter is mapped to a SysML v2 ReferenceUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action def SysMLv1Activity {
    in parIn : ScalarValues::Boolean;
}

```

##### General Mappings

ToReferenceUsage\_**Init**  
NamedElementMain\_Mapping

##### Mapping Source

Parameter

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```

let typings: Set(KerML::FeatureTyping) =
    if from.type.ocIsUndefined() then
        Set{}
    else
        Set{ParameterToFeatureTyping_Mapping.getMapped(from)}
    endif in

```

```

self.oclAsType(ElementMain_Mapping).ownedRelationship()
->union(typings)
->union(multiplicities)
->union(defaultValues)

```

- ReferenceUsage::declaredName () : String [0..1]

```

if from.direction = UML::ParameterDirectionKind::return then 'result' else from.name endif

```

#### 7.7.4.2.25 ParameterDefaultValue\_Mapping

##### Description

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

attribute value : ScalarValues::String default := "default value";

```

##### General Mappings

GenericToFeatureValue\_Mapping

##### Mapping Source

Parameter

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```

from.defaultValue

```

- FeatureValue::isDefault () : Boolean [1]

```

true

```

#### 7.7.4.2.26 ParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

```

let multiplicities: Set(KerML::Relationship) =
  Set{MultiplicityMembership_Mapping.getMapped(from)} in
let defaultValues: Set(KerML::Relationship) =
  if from.defaultValue.oclIsUndefined() then
    Set{}
  else
    Set{ParameterDefaultValue_Mapping.getMapped(from)}
  endif in
self.oclAsType(ElementMain_Mapping).ownedRelationship()
->union(typings)
->union(multiplicities)
->union(defaultValues)

```

- ReferenceUsage::declaredName () : String [0..1]

```

if from.direction = UML::ParameterDirectionKind::return then 'result' else from.name endif

```

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

```

Helper.getKerMLParameterDirectionKind(from.direction)

```

#### 7.7.4.2.25 ParameterDefaultValue\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

##### Description

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

attribute value : ScalarValues::String default := "default value";

```

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

Parameter

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

## General Mappings

**Generic**ToParameterMembership\_Mapping

### Mapping Source

Parameter

### Mapping Target

ParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]

```
Parameter_Mapping.getMapped(from)
```

## 7.7.4.2.27 ParameterSet\_Mapping

### Description

A UML4SysML::ParameterSet is mapped to a SysML v2 ReferenceUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
  in parIn [0..1];
  inout parInOut [0..1];
  out parOut [0..1];
  out parReturn [0..1];

  sysMLv1ParameterSet1 [1] {
    ref parIn = SysMLv1Activity::parIn;
    assert constraint sysMLv1ParameterSet1Condition {
      language "English"
    /*
     * opaque expression parameter set 1
     */
    }
  }
  sysMLv1ParameterSet2 [1] {
    ref parInOut = SysMLv1Activity::parInOut;
    ref parOut = SysMLv1Activity::parOut;
    ref parReturn = SysMLv1Activity::parReturn;
  }
}
```

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::isDefault () : Boolean [1]`

`true`

- `FeatureValue::value () : Expression [1]`

`from.defaultValue`

#### 7.7.4.2.26 ParameterMembership\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a membership relationship for *memberElement()*.

###### **General Mappings**

ToParameterMembership\_Init  
Mapping

###### **Mapping Source**

Parameter

###### **Mapping Target**

ParameterMembership

###### **Owned Mappings**

(none)

###### **Applicable filters**

(none)

###### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ParameterMembership::ownedMemberParameter () : Feature [1]`

`Parameter_Mapping.getMapped (from)`

#### 7.7.4.2.27 ParameterSet\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

A UML4SysML::ParameterSet is mapped to a SysML v2 ReferenceUsage.

```
}  
}
```

## General Mappings

**Generic**ToReferenceUsage\_Mapping

## Mapping Source

ParameterSet

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
from.parameter  
->collect (p | ParameterSetParameterFeatureMembership_Mapping.getMapped (from, p))  
->asSet ()
```
- ReferenceUsage::declaredName () : String [0..1]  

```
from.name
```

### 7.7.4.2.28 ParameterSetMembership\_Mapping

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

**Generic**ToFeatureMembership\_Mapping

## Mapping Source

ParameterSet

## Mapping Target

FeatureMembership



The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action def SysMLv1Activity {
  in parIn [0..1];
  inout parInOut [0..1];
  out parOut [0..1];
  out parReturn [0..1];

  sysMLv1ParameterSet1 [1] {
    ref parIn = SysMLv1Activity::parIn;
    assert constraint sysMLv1ParameterSet1Condition {
      language "English"
      /*
       * opaque expression parameter set 1
       */
    }
  }
  sysMLv1ParameterSet2 [1] {
    ref parInOut = SysMLv1Activity::parInOut;
    ref parOut = SysMLv1Activity::parOut;
    ref parReturn = SysMLv1Activity::parReturn;
  }
}

```

## General Mappings

ToReferenceUsage [Init](#)  
Mapping

### Mapping Source

ParameterSet

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```

from.parameter
->collect(p | ParameterSetParameterFeatureMembership_Mapping.getMapped(from, p))
->asSet()

```

- ReferenceUsage::declaredName () : String [0..1]

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

`ParameterSet_Mapping.getMapped(from)`

### 7.7.4.2.29 ParameterSetParameterFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

`GenericToFeatureMembership_Mapping`

#### Mapping Source

`ParameterSet`

#### Mapping Target

`FeatureMembership` with qualifier: `parameter:Parameter`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature (in parameter : Parameter) : Feature [1]`

`ParameterSetParameterReferenceUsage_Mapping.getMapped(parameter)`

### 7.7.4.2.30 ParameterSetParameterReferenceUsage\_Mapping

#### Description

`from.name`

#### 7.7.4.2.28 ParameterSetMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

ParameterSet

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

`ParameterSet_Mapping.getMapped(from)`

#### 7.7.4.2.29 ParameterSetParameterFeatureMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

ParameterSet

The mapping class creates the reference usage element for the UML4SysML::ParameterSet mapping.

### General Mappings

**Generic**ToReferenceUsage\_Mapping

### Mapping Source

Parameter

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set { ParameterSetParameterReferenceUsageFeatureValue_Mapping.getMapped(from) ,  
MultiplicityMembership_Mapping.getMapped(from) }
```

#### 7.7.4.2.31 ParameterSetParameterReferenceUsageFeatureValue\_Mapping

### Description

The mapping class creates the feature reference expression for the reference usage element of the UML4SysML::ParameterSet mapping.

### General Mappings

**Generic**ToFeatureValue\_Mapping

### Mapping Source

Parameter

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

### Mapping Target

FeatureMembership with qualifier: parameter:Parameter

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature (in parameter : Parameter) : Feature [1]  
`ParameterSetParameterReferenceUsage_Mapping.getMapped(parameter)`

#### 7.7.4.2.30 ParameterSetParameterReferenceUsage\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the reference usage element for the UML4SysML::ParameterSet mapping.

### General Mappings

ToReferenceUsage\_Init  
Mapping

### Mapping Source

Parameter

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
ParameterSetParameterReferenceUsageFeatureValueExpression_Mapping.getMapped(from)
```

#### 7.7.4.2.32 ParameterSetParameterReferenceUsageFeatureValueExpression\_Mapping

##### Description

The mapping class creates the feature reference expression for the UML4SysML::ParameterSet mapping.

##### General Mappings

`GenericToFeatureReferenceExpression_Mapping`

##### Mapping Source

Parameter

##### Mapping Target

FeatureReferenceExpression

##### Owned Mappings

(none)

##### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set { ParameterSetParameterReferenceUsageMembership_Mapping.getMapped(from) ,  
CommonReturnParameterFeatureMembership_Mapping.getMapped(from) }
```

#### 7.7.4.2.33 ParameterSetParameterReferenceUsageMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

`GenericToMembership_Mapping`

```
Set{ParameterSetParameterReferenceUsageFeatureValue_Mapping.getMapped(from),  
MultiplicityMembership_Mapping.getMapped(from)}
```

#### 7.7.4.2.31 ParameterSetParameterReferenceUsageFeatureValue\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates the feature reference expression for the reference usage element of the UML4SysML::ParameterSet mapping.

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

Parameter

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
ParameterSetParameterReferenceUsageFeatureValueExpression_Mapping.getMapped(from)
```

#### 7.7.4.2.32 ParameterSetParameterReferenceUsageFeatureValueExpression\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates the feature reference expression for the UML4SysML::ParameterSet mapping.

##### General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

##### Mapping Source

### Mapping Source

Parameter

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  
from

## 7.7.4.2.34 ParameterToFeatureTyping\_Mapping

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

TypedElementFeatureTyping\_Mapping

### Mapping Source

Parameter

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules



Parameter

### Mapping Target

FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set { ParameterSetParameterReferenceUsageMembership_Mapping.getMapped (from) ,  
CommonReturnParameterFeatureMembership_Mapping.getMapped (from) }
```

#### 7.7.4.2.33 ParameterSetParameterReferenceUsageMembership\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

Parameter

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::typedFeature () : Feature [1]

```
parameter.to
```

#### 7.7.4.2.35 PropertyCommon\_Mapping

##### Description

The mapping class is the abstract base class for UML4SysML::Property mappings.

##### General Mappings

StructuralFeature\_Mapping

##### Mapping Source

Property

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]

```
if from.association.oclIsUndefined() then
  false
else
  from.association.ownedEnd->includes(from)
endif
```

- Feature::isComposite () : Boolean [1]

```
from.isComposite
```

- Feature::ownedRelationship () : Relationship [0..\*]

```
let typings: Set(KerML::FeatureTyping) = if from.type.oclIsUndefined() then
  Set{}
else
  Set{StructuralFeatureToFeatureTyping_Mapping.getMapped(from) }
```

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

from

#### 7.7.4.2.34 ParameterToFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

TypedElementFeatureTyping\_Mapping  
Mapping

##### Mapping Source

Parameter

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::typedFeature () : Feature [1]

parameter.to

#### 7.7.4.2.35 PropertyCommon\_Mapping

##### Description

The mapping class is the abstract base class for UML4SysML::Property mappings.

##### General Mappings

StructuralFeature\_Mapping  
Mapping

##### Mapping Source

Property

```

endif in
let subsettings: Set(KerML::Subsetting) = from.subsettedProperty
->collect(p | PropertySubsetting_Mapping.getMapped(from, p))->asSet() in
let defaultValue: Set(KerML::OwningMembership) =
  if from.defaultValue.oclIsUndefined() then
    Set{}
  else
    Set{DefaultValue_Mapping.getMapped(from)}
  endif in
typings->union(subsettings)->union(defaultValue)
->including(MultiplicityMembership_Mapping.getMapped(from))->asSet()

```

- Feature::isDerived () : Boolean [1]

from.isDerived

#### 7.7.4.2.36 PropertySubsetting\_Mapping

##### Description

Creates a subsetting relationship.

##### General Mappings

GenericToSubsetting\_Mapping

##### Mapping Source

Property

##### Mapping Target

Subsetting with qualifier: subsettedProperty:Property

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subsetting::subsettedFeature (in subsettedProperty : Property) : Feature [1]

Property\_Mapping.getMapped(subsettedProperty)

- Subsetting::subsettingFeature () : Feature [1]

Property\_Mapping.getMapped(from)

#### 7.7.4.2.37 PropertyTypedByClassInterface\_Mapping

##### Description

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isComposite () : Boolean [1]

```
from.isComposite
```

- Feature::isDerived () : Boolean [1]

```
from.isDerived
```

- Feature::ownedRelationship () : Relationship [0..\*]

```
let typings: Set(KerML::FeatureTyping) = if from.type.ocIsUndefined() then
  Set{}
else
  Set{StructuralFeatureToFeatureTyping_Mapping.getMapped(from)}
endif in
let subsettings: Set(KerML::Subsetting) = from.subsettedProperty
->collect(p | PropertySubsetting_Mapping.getMapped(from, p))->asSet() in
let defaultValue: Set(KerML::OwningMembership) =
  if from.defaultValue.ocIsUndefined() then
    Set{}
  else
    Set{DefaultValue_Mapping.getMapped(from)}
  endif in
typings->union(subsettings)->union(defaultValue)
->including(MultiplicityMembership_Mapping.getMapped(from))->asSet()
```

- Feature::isEnd () : Boolean [1]

```
if from.association.ocIsUndefined() then
  false
else
  from.association.ownedEnd->includes(from)
endif
```

### 7.7.4.2.36 PropertySubsetting\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

## Description

Creates a subsetting relationship.

A UML4SysML::Property typed by a UML4SysML::Class or UML4SysML::Interface is mapped to a SysML v2 OccurrenceUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {
    occurrence sysMLv1Property1 [0..1] : SysMLv1Class;
    ref occurrence sysMLv1ReferencedProperty [0..1] : SysMLv1Class;
    occurrence sysMLv1Property2 [0..1] : SysMLv1Interface;
}
```

## General Mappings

PropertyCommon\_Mapping  
NamedElementMain\_Mapping

## Mapping Source

Property

## Mapping Target

OccurrenceUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.oclIsTypeOf(UML::Property) then
    let p: UML::Property = src.oclAsType(UML::Property) in
        if p.type.oclIsUndefined() then
            false
        else
            (p.type.oclIsTypeOf(UML::Class) or
             p.type.oclIsTypeOf(UML::Interface)) and
            not (p.name.indexOf('base_') > 0) and
            (p.association.oclIsUndefined() or p.association.ownedEnd->excludes(p))
        endif
    else
        false
    endif
endif
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.4.2.38 PropertyUntyped\_Mapping

#### Description

## General Mappings

ToSubsetting\_Init  
Mapping

## Mapping Source

Property

## Mapping Target

Subsetting with qualifier: subsettedProperty:Property

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subsetting::subsettedFeature (in subsettedProperty : Property) : Feature [1]  
`Property_Mapping.getMapped(subsettedProperty)`
- Subsetting::subsettingFeature () : Feature [1]  
`Property_Mapping.getMapped(from)`

### 7.7.4.2.37 PropertyTypedByClassInterface\_Mapping

#### Description

A UML4SysML::Property typed by a UML4SysML::Class or UML4SysML::Interface is mapped to a SysML v2 OccurrenceUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {  
    occurrence sysMLv1Property1 [0..1] : SysMLv1Class;  
    ref occurrence sysMLv1ReferencedProperty [0..1] : SysMLv1Class;  
    occurrence sysMLv1Property2 [0..1] : SysMLv1Interface;  
}
```

## General Mappings

PropertyCommon\_Mapping  
NamedElementMain\_Mapping

## Mapping Source

A UML4SysML::Property is mapped to a SysML v2 Feature. The mapping class maps properties without a type.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {  
    attribute sysMLv1Property;  
}
```

## General Mappings

PropertyCommon\_Mapping  
GenericToReferenceUsage\_Mapping  
NamedElementMain\_Mapping

## Mapping Source

Property

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.type.oclIsUndefined() and not  
Helper.hasStereotypeApplied(src.owner, 'SysML::ConstraintBlocks::ConstraintBlock')
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.4.2.39 Realization\_Mapping

#### Description

A UML4SysML::Realization relationship is mapped to a SysML v2 Dependency.

## General Mappings

Abstraction\_Mapping

## Mapping Source

Realization

## Mapping Target



Property

### Mapping Target

OccurrenceUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.ocIsTypeOf(UML::Property) then
    let p: UML::Property = src.ocAsType(UML::Property) in
    if p.type.ocIsUndefined() then
        false
    else
        (p.type.ocIsTypeOf(UML::Class) or
         p.type.ocIsTypeOf(UML::Interface)) and
        not (p.name.indexOf('base_') > 0) and
        (p.association.ocIsUndefined() or p.association.ownedEnd->excludes(p))
    endif
else
    false
endif
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

#### 7.7.4.2.38 PropertyUntyped\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

A UML4SysML::Property is mapped to a SysML v2 Feature. The mapping class maps properties without a type.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {
    attribute sysMLv1Property;
}
```

##### General Mappings

PropertyCommon\_Mapping  
ToReferenceUsage\_Init  
NamedElementMain\_Mapping

##### Mapping Source

Property

Dependency

#### Owned Mappings

(none)

#### 7.7.4.2.40 Slot\_Mapping

##### Description

A UML4SysML::Slot is mapped to a SysML v2 Feature.

#### General Mappings

GenericToFeature\_Mapping  
ElementMain\_Mapping

#### Mapping Source

Slot

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### 7.7.4.2.41 SlotMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

Slot

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.type.oclIsUndefined() and not  
Helper.hasStereotypeApplied(src.owner, 'SysML::ConstraintBlocks::ConstraintBlock')
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.4.2.39 Realization\_Mapping

#### Description

A UML4SysML::Realization relationship is mapped to a SysML v2 Dependency.

#### General Mappings

Abstraction\_Mapping

#### Mapping Source

Realization

#### Mapping Target

Dependency

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.4.2.40 Slot\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

A UML4SysML::Slot is mapped to a SysML v2 Feature.

#### General Mappings

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::memberName () : String [0..1]`  
`from.definingFeature.name`
- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`from`
- `FeatureMembership::isReadOnly () : Boolean [1]`  
`from.isReadOnly`

### 7.7.4.2.42 SlotFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

`GenericToFeatureTyping_Mapping`

#### Mapping Source

Slot

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`ElementMain_Mapping.getMapped(from)`

### 7.7.4.2.43 SlotValue\_Mapping

#### Description

ToFeature\_Init  
ElementMain\_Mapping

#### Mapping Source

Slot

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### 7.7.4.2.41 SlotMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

Slot

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::memberName () : String [0..1]

`from.definingFeature.name`

Issue here since a KerML feature cannot have more than one FeatureValue while a UML4SysML::Slot can. How to manage collection of values?

## General Mappings

GenericToFeatureValue\_Mapping

### Mapping Source

ValueSpecification

### Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.oclIsKindOf(UML::Slot)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::featureWithValue () : Feature [1]

```
Slot_Mapping.getMapped(from.owner)
```

- FeatureValue::value () : Expression [1]

```
from
```

### 7.7.4.2.44 StructuralFeature\_Mapping

#### Description

The mapping class is the abstract base class for all UML4SysML::StructuralFeature mappings.

## General Mappings

GenericToFeature\_Mapping

### Mapping Source

StructuralFeature

### Mapping Target

Feature

- FeatureMembership::ownedMemberFeature () : Feature [1]  
from
- FeatureMembership::isReadOnly () : Boolean [1]  
from.isReadOnly

#### 7.7.4.2.42 SlotFeatureTyping\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

ToFeatureTyping\_Init  
Mapping

##### Mapping Source

Slot

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
ElementMain\_Mapping.getMapped(from)

#### 7.7.4.2.43 SlotValue\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Issue here since a KerML feature cannot have more than one FeatureValue while a UML4SysML::Slot can. How to manage collection of values?

##### General Mappings





ToFeatureValue\_Init  
Mapping

#### Mapping Source

ValueSpecification

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.oclIsKindOf(UML::Slot)
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::featureWithValue () : Feature [1]  
`Slot_Mapping.getMapped(from.owner)`
- FeatureValue::value () : Expression [1]  
`from`

#### 7.7.4.2.44 StructuralFeature\_Mapping

##### **SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class is the abstract base class for all UML4SysML::StructuralFeature mappings.

#### General Mappings

ToFeature\_Init  
Mapping

#### Mapping Source

StructuralFeature

#### Mapping Target

Feature

#### Owned Mappings

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::isUnique () : Boolean [1]`  
`from.isUnique`
- `Feature::isAbstract () : Boolean [1]`  
`false`
- `Feature::ownedRelationship () : Relationship [0..*]`  

```
let typing: KerML::FeatureTyping =  
    StructuralFeatureToFeatureTyping_Mapping.getMapped(from) in  
if typing.oclIsUndefined() then  
    Set{MultiplicityMembership_Mapping.getMapped(from)}  
else  
    Set{MultiplicityMembership_Mapping.getMapped(from), typing}  
endif
```
- `Feature::isOrdered () : Boolean [1]`  
`from.isOrdered`
- `Feature::isReadOnly () : Boolean [1]`  
`abstract rule`

### 7.7.4.2.45 StructuralFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

`GenericToFeatureMembership_Mapping`

#### Mapping Source

StructuralFeature

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::isUnique () : Boolean [1]`  
`from.isUnique`
- `Feature::isAbstract () : Boolean [1]`  
`false`
- `Feature::isReadOnly () : Boolean [1]`  
*abstract rule*
- `Feature::isOrdered () : Boolean [1]`  
`from.isOrdered`
- `Feature::ownedRelationship () : Relationship [0..*]`  

```
let typing: KerML::FeatureTyping =  
  StructuralFeatureToFeatureTyping_Mapping.getMapped(from) in  
if typing.oclIsUndefined() then  
  Set{MultiplicityMembership_Mapping.getMapped(from)}  
else  
  Set{MultiplicityMembership_Mapping.getMapped(from), typing}  
endif
```

#### 7.7.4.2.45 StructuralFeatureMembership\_Mapping

##### **SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

StructuralFeature

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::visibility () : VisibilityKind [1]  

```
if (from.ocIsKindOf(UML::NamedElement)) then
    Helper.getKerMLVisibilityKind(from.ocAsType(UML::NamedElement).visibility)
else
    KerML::VisibilityKind::public
endif
```
- FeatureMembership::ownedMemberFeature () : Feature [0..1]  

```
NamedElementMain_Mapping.getMapped(from)
```

#### 7.7.4.2.46 StructuralFeatureToFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

TypedElementFeatureTyping\_Mapping

##### Mapping Source

StructuralFeature

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

#### 7.7.4.2.47 TypedElementFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

GenericToFeatureTyping\_Mapping

##### Mapping Source

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::visibility () : VisibilityKind [1]  

```
if (from.ocIsKindOf(UML::NamedElement)) then
    Helper.getKerMLVisibilityKind(from.ocAsType(UML::NamedElement).visibility)
else
    KerML::VisibilityKind::public
endif
```
- FeatureMembership::ownedMemberFeature () : Feature [0..1]  

```
NamedElementMain_Mapping.getMapped(from)
```

#### 7.7.4.2.46 StructuralFeatureToFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

TypedElementFeatureTyping\_Mapping

##### Mapping Source

StructuralFeature

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

#### Applicable filters

(none)

#### 7.7.4.2.47 TypedElementFeatureTyping\_Mapping

[SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

TypedElement

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not src.type.ocIsUndefined()
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
if from.type.ocIsKindOf(UML::PrimitiveType) then
    Helper.getScalarValueType(from.type)
else if from.type.ocIsKindOf(UML::Enumeration) then
    Helper.getEnumerationType(from.type)
else
    Classifier_Mapping.getMapped(from.type)
endif endif
```

#### 7.7.4.2.48 UpperBoundValueFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

GenericToFeatureMembership\_Mapping

##### Mapping Source

MultiplicityElement

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

ToFeatureTyping\_Init  
Mapping

#### Mapping Source

TypedElement

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not src.type.ocIsUndefined()
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
if from.type.ocIsKindOf(UML::PrimitiveType) then
    Helper.getScalarValueType(from.type)
else if from.type.ocIsKindOf(UML::Enumeration) then
    Helper.getEnumerationType(from.type)
else
    Classifier_Mapping.getMapped(from.type)
endif endif
```

#### 7.7.4.2.48 UpperBoundValueFeatureMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init

#### Mapping Source

MultiplicityElement

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`

```
if from.upper <> -1 then
    LiteralUnlimitedToInteger_Mapping.getMapped(from.upperValue)
else
    LiteralUnlimitedToUnbounded_Mapping.getMapped(from.upperValue)
endif
```

This chapter lists all mapping specifications of UML4SysML::Classification model elements.

## 7.7.5 CommonBehavior

This chapter lists all mapping specifications of UML4SysML::CommonBehavior model elements.

### 7.7.5.1 Overview

Table 6. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
AnyReceiveEvent	not mapped; see next section
CallEvent	not mapped; see next section
ChangeEvent	TextualRepresentation
FunctionBehavior	ViewDefinition RequirementUsage
OpaqueBehavior	ViewDefinition ActionDefinition RequirementUsage
SignalEvent	not mapped; see next section
TimeEvent	TextualRepresentation
Trigger	AcceptActionUsage

The following table gives an overview of which SysML v2 elements the UML4SysML::CommonBehavior elements are transformed with which mapping class. The mapping details are in [7.7.5.3](#).

The justifications for the elements without mapping are given in [7.7.5.2](#).

### 7.7.5.2 UML4SysML::CommonBehavior elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]  

```
if from.upper <> -1 then
    LiteralUnlimitedToInteger_Mapping.getMapped(from.upperValue)
else
    LiteralUnlimitedToUnbounded_Mapping.getMapped(from.upperValue)
endif
```

## 7.7.5 CommonBehavior

### 7.7.5.1 Overview

[SYSML2\\_-329: Mapping overview tables are wrong](#)

Table 6. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
AnyReceiveEvent	not mapped; see next section
CallEvent	not mapped; see next section
ChangeEvent	<a href="#">CalculationUsage</a>
FunctionBehavior	<a href="#">ActionDefinition</a>
OpaqueBehavior	ActionDefinition
SignalEvent	not mapped; see next section
TimeEvent	<a href="#">CalculationUsage</a>
Trigger	AcceptActionUsage

### 7.7.5.2 UML4SysML::CommonBehavior elements not mapped

Table 7. List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
CallEvent	The concept of a CallEvent is not supported by SysML v2.

### 7.7.5.3 Mapping Specifications

#### 7.7.5.3.1 Behavior\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

**Table 7. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
CallEvent	The concept of a CallEvent is not supported by SysML v2.

### 7.7.5.3 Mapping Specifications

#### 7.7.5.3.1 Behavior\_Mapping

##### Description

The mapping class is the abstract base class for all UML4SysML::Behavior mappings.

##### General Mappings

##### GenericToBehavior\_Mapping

Class\_Mapping

##### Mapping Source

Behavior

##### Mapping Target

Behavior

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Behavior::ownedRelationship () : Relationship [0..\*]

```

let parameters: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
let parameterSets: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::ParameterSet)) in
let features: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Property)) in
let elementsOMS: Set(UML::Element) =
    (((from.ownedElement - parameters) parameterSets) - features) in
elementsOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(features->collect(e | PropertyMembership_Mapping.getMapped(e)))
->union(parameters->collect(e | ParameterMembership_Mapping.getMapped(e)))
->union(parameterSets->collect(e | ParameterSetMembership_Mapping.getMapped(e)))

```

The mapping class is the abstract base class for all UML4SysML::Behavior mappings.

## General Mappings

ToBehavior **Init**  
Class\_Mapping

## Mapping Source

Behavior

## Mapping Target

Behavior

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Behavior::ownedRelationship () : Relationship [0..\*]

```
let parameters: Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
let parameterSets: Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::ParameterSet)) in
let features: Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Property)) in
let elementsOMS: Set(UML::Element) =
  (((from.ownedElement - parameters) parameterSets) - features) in
elementsOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(features->collect(e | PropertyMembership_Mapping.getMapped(e)))
->union(parameters->collect(e | ParameterMembership_Mapping.getMapped(e)))
->union(parameterSets->collect(e | ParameterSetMembership_Mapping.getMapped(e)))
```

### 7.7.5.3.2 ChangeEvent\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

Main mapping class for the mapping of UML4SysML::ChangeEvent.

```
calc sysMLv1ChangeEvent1 {
  language "language"
  /* change expression */
}
```

### 7.7.5.3.2 ChangeEvent\_Mapping

#### Description

T#3 meeting, 2022-12-14: Do not use automatic rules! Events are not single elements in SysML v2. Consider it in the transformation for AcceptEventAction, Transition

#### General Mappings

GenericToTextualRepresentation\_Mapping

NamedElementMain\_Mapping

#### Mapping Source

ChangeEvent

#### Mapping Target

TextualRepresentation

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TextualRepresentation::body () : String [1]

```
if from.changeExpression.ocIsKindOf (UML::OpaqueExpression) then
  if from.changeExpression.
    ocIsType (UML::OpaqueExpression) .body.ocIsUndefined() then
    invalid
  else
    from.changeExpression.ocIsType (UML::OpaqueExpression) .body.get (0)
  endif
else
  invalid
endif
```

- TextualRepresentation::language () : String [1]

```
if from.changeExpression.ocIsKindOf (UML::OpaqueExpression) then
  if from.changeExpression.
    ocIsType (UML::OpaqueExpression) .language->size() = 0 then
    invalid
  else
    from.changeExpression.ocIsType (UML::OpaqueExpression) .language.get (0)
  endif
else
  invalid
endif
```

## General Mappings

NamedElementMain\_Mapping  
ToCalculationUsage\_Init

## Mapping Source

ChangeEvent

## Mapping Target

CalculationUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- CalculationUsage::ownedRelationship () : Relationship [0..\*]

```
from.ownedComment->reject (c | c.annotatedElement->includes (from)) ->collect (c | CommentOwnership  
->including (ElementOwningMembership_Mapping.getMapped (from.changeExpression))
```

### 7.7.5.3.3 ChangeEventReturnParameter\_Mapping

**[SYSML2 -131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

## Description

Creates the reference usage for the return parameter of the calculation usage which is the target of the UML4SysML::ChangeEvent mapping.

## General Mappings

UniqueMapping  
ToReferenceUsage\_Init

## Mapping Source

ChangeEvent

## Mapping Target

ReferenceUsage

## Owned Mappings

```
invalid
endif
```

### 7.7.5.3.3 OpaqueBehavior\_Mapping

#### Description

A UML4SysML::OpaqueBehavior is mapped to a SysML v2 ActionDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1OpaqueBehavior {
    language "Built-in Math"
    /*
     * result = 42 + 23;
     */
}
```

#### General Mappings

Behavior\_Mapping

#### Mapping Source

OpaqueBehavior

#### Mapping Target

ActionDefinition

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.ocIsKindOf(UML::Package)
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionDefinition::ownedRelationship () : Relationship [0..\*]

```
let parameters : Set(UML::Parameter) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
let parameterSets : Set(UML::ParameterSet) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::ParameterSet)) in
let features : Set(UML::Property) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Property)) in
```

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`

`KerML::FeatureDirectionKind::_out'`

#### 7.7.5.3.4 ChangeEventReturnParameterMembership\_Mapping

**SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

UniqueMapping

ToReturnParameterMembership\_Init

#### Mapping Source

ChangeEvent

#### Mapping Target

ReturnParameterMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReturnParameterMembership::ownedMemberParameter () : Feature [1]`

`ChangeEventReturnParameter_Mapping.getMapped (from)`

```

let elementsOMS: Set(UML::Element) =
  (((from.ownedElement - parameters) - parameterSets) - features) in
elementsOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(features->collect(e | PropertyMembership_Mapping.getMapped(e)))
->union(parameters->collect(e | ParameterMembership_Mapping.getMapped(e)))
->union(parameterSets->collect(e | ParameterSetMembership_Mapping.getMapped(e)))
->union(from.language
  ->collect(1 | OpaqueBehaviorMembership_Mapping.getMapped(from, 1)))

```

#### 7.7.5.3.4 OpaqueBehaviorMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic**ToOwningMembership\_Mapping

##### Mapping Source

OpaqueBehavior

##### Mapping Target

OwningMembership with qualifier: language:String

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement (in language : String) : Element [1]

```
OpaqueBehaviorSpecification_Mapping.getMapped(from, language)
```

#### 7.7.5.3.5 OpaqueBehaviorSpecification\_Mapping

##### Description

The mapping class creates the SysML v2 TextualRepresentation elements from the languages and bodies properties of the given UML4SysML::OpaqueBehavior.

##### General Mappings

**Generic**ToTextualRepresentation\_Mapping

##### Mapping Source



#### 7.7.5.3.5 ChangeTriggerBindingConnector\_Mapping

**SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates the binding connector between the result of the trigger calculation usage and the result of the time event calculation usage.

##### General Mappings

ToBindingConnectorAsUsage\_Init  
UniqueMapping

##### Mapping Source

Trigger

##### Mapping Target

BindingConnectorAsUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- BindingConnectorAsUsage::ownedRelationship () : Relationship [0..\*]  
`Set{ChangeTriggerReturnEndFeatureMembership_Mapping.getMapped(from) }`  
`->including(ChangeTriggerEndFeatureMembership_Mapping.getMapped(from) )`

#### 7.7.5.3.6 ChangeTriggerConstraintUsage\_Mapping

**SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates the constraint usage of the target of the mapping of a UML4SysML::Trigger referencing a UML4SysML::ChangeEvent.

##### General Mappings

ToConstraintUsage\_Init  
UniqueMapping

OpaqueBehavior

### Mapping Target

TextualRepresentation with qualifier: language:String

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TextualRepresentation::body () : String [1]  

```
let index:Integer = from.language->indexOf(language) in  
from._'body'->at(index)
```
- TextualRepresentation::language () : String [1]  

```
language
```

## 7.7.5.3.6 TimeEvent\_Mapping

### Description

T#3 meeting, 2022-12-14: Do not use automatic rules! Events are not single elements in SysML v2. Consider it in the transformation for AcceptEventAction, Transition

### General Mappings

NamedElementMain\_Mapping

GenericToTextualRepresentation\_Mapping

### Mapping Source

TimeEvent

### Mapping Target

TextualRepresentation

### Owned Mappings

(none)

### Applicable filters

(none)

## Mapping Source

Trigger

## Mapping Target

ConstraintUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConstraintUsage::ownedRelationship () : Relationship [0..*]`  
`Set{ChangeTriggerFeatureMembership_Mapping.getMapped(from) }`  
`->including (ChangeTriggerReturnParameterMembership_Mapping.getMapped(from) )`

### 7.7.5.3.7 ChangeTriggerEndFeatureMembership\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToEndFeatureMembership\_Init  
UniqueMapping

## Mapping Source

Trigger

## Mapping Target

EndFeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TextualRepresentation::body () : String [1]

'tbd timeevent'

### 7.7.5.3.7 Trigger\_Mapping

## 7.7.6 CommonStructure

This chapter lists all mapping specifications of UML4SysML::CommonStructure model elements.

### 7.7.6.1 Overview

Table 9. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Abstraction	SatisfyRequirementUsage AllocationDefinition
Comment	Package
Constraint	ConstraintDefinition
Dependency	Dependency
ElementImport	MembershipImport
PackageImport	NamespaceImport
Realization	Dependency
Usage	Dependency

The following table gives an overview of which SysML v2 elements the UML4SysML::CommonStructure elements are transformed with which mapping class. The mapping details are in [7.7.6.2](#).

### 7.7.6.2 Mapping Specifications

#### 7.7.6.2.1 Abstraction\_Mapping

##### Description

A UML4SysML::Abstraction relationship is mapped to a SysML v2 Dependency relationship.

##### General Mappings

Dependency\_Mapping

##### Mapping Source

Abstraction

##### Mapping Target

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  
`ChangeTriggerReferenceUsage_Mapping.getMapped(from)`

### 7.7.5.3.8 ChangeTriggerEventChainingFeature\_Mapping

**[SYSML2 -131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates the chaining feature for the event for the mapping of a `UML4SysML::Trigger` referencing a `UML4SysML::ChangeEvent`.

#### General Mappings

`UniqueMapping`  
`ToFeatureChaining_Init`

#### Mapping Source

`Trigger`

#### Mapping Target

`FeatureChaining`

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChaining::chainingFeature () : Feature [1]`  
`from.event`

### 7.7.5.3.9 ChangeTriggerEventReturnParameterChainingFeature\_Mapping

**[SYSML2 -131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Dependency

## Owned Mappings

(none)

### 7.7.6.2.2 Comment\_Mapping

#### Description

A UML4SysML::Comment is mapped to a SysML v2 Comment.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1;
part def SysMLv1Block2;
action def SysMLv1Activity {
    comment about SysMLv1Activity, SysMLv1Block1
        /* comment body */
}
comment about SysMLv1Block1, SysMLv1Block /* comment body */
```

#### General Mappings

ElementMain\_Mapping

GenericToAnnotatingElement\_Mapping

#### Mapping Source

Comment

#### Mapping Target

Comment

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not Helper.hasStereotypeApplied(src, 'SysML::ModelElements::ElementGroup')
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Comment::ownedRelationship () : Relationship [0..\*]  

```
self.oclAsType (ElementMain_Mapping).ownedRelationship()  
->union (self.annotation () ->asSet ())
```

Creates the chaining feature for the return parameter for the mapping of a UML4SysML::Trigger referencing a UML4SysML::ChangeEvent.

#### General Mappings

ToFeatureChaining\_Init  
UniqueMapping

#### Mapping Source

Trigger

#### Mapping Target

FeatureChaining

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]  
`ChangeEventReturnParameter_Mapping.getMapped(from.event)`

#### 7.7.5.3.10 ChangeTriggerExpressionFeature\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates the feature for the trigger invocation expression of the target of the mapping of a UML4SysML::Trigger referencing a UML4SysML::ChangeEvent.

#### General Mappings

ToFeature\_Init  
UniqueMapping

#### Mapping Source

Trigger

#### Mapping Target

Feature

#### Owned Mappings

- `Comment::body () : String [1]`  
`if from.body->isEmpty() then '' else from.body endif`
- `Comment::annotation () : Annotation [0..*]`  
`from.annotatedElement`  
`->collect(e | CommentAnnotation_Mapping.getMapped(from, e))`

### 7.7.6.2.3 CommentAnnotation\_Mapping

#### Description

The mapping class creates the annotation relationship for the UML4SysML::Comment mapping.

#### General Mappings

`GenericToAnnotation_Mapping`

#### Mapping Source

Comment

#### Mapping Target

Annotation with qualifier: `annotatedElement:Element`

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Annotation::annotatedElement (in annotatedElement : Element) : Element [1]`  
`ElementMain_Mapping.getMapped(annotatedElement)`
- `Annotation::annotatingElement () : AnnotatingElement [1]`  
`Comment_Mapping.getMapped(from)`
- `Annotation::owningAnnotatedElement () : Element [0..1]`  
`null`

### 7.7.6.2.4 CommentOwnership\_Mapping

#### Description



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set { ChangeTriggerExpressionFeatureValue_Mapping.getMapped (from) }
```

#### 7.7.5.3.11 ChangeTriggerExpressionFeatureMembership\_Mapping

**SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

UniqueMapping

ToFeatureMembership\_Init

#### Mapping Source

Trigger

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
ChangeTriggerExpressionInvocationExpression_Mapping.getMapped (from)
```

That mapping class creates an ownership relation that is convenient for a Comment. In SysMLv1/UML can be owned by any kind of element, including some that are not translated to SysMLv2 Namespaces.

## General Mappings

GenericToAnnotation\_Mapping  
UniqueMapping

## Mapping Source

Comment

## Mapping Target

Annotation

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Annotation::annotatedElement () : Element [1]  
`ElementMain_Mapping.getMapped(from.owner)`
- Annotation::annotatingElement () : AnnotatingElement [1]  
`Comment_Mapping.getMapped(from)`
- Annotation::ownedRelatedElement () : Element [0..\*]  
`Set{self.annotatingElement () }`

### 7.7.6.2.5 Constraint\_Mapping

#### Description

A UML4SysML::Constraint is mapped to a SysML v2 ConstraintDefinition and AssertConstraintUsages for the constrained elements.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {  
    constraint def SysMLv1Constraint {  
        calc sysMLv1Constraint {  
            language "English"  
            /*  
            * constraint specification
```

### 7.7.5.3.12 ChangeTriggerExpressionFeatureReferenceExpression\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates the feature reference expression for the feature value in the trigger invocation expression of the target of the mapping of a UML4SysML::Trigger referencing a UML4SysML::ChangeEvent.

#### General Mappings

UniqueMapping  
ToFeatureReferenceExpression\_Init

#### Mapping Source

Trigger

#### Mapping Target

FeatureReferenceExpression

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{ChangeTriggerExpressionFeatureMembership_Mapping.getMapped(from)}  
->including(ReturnParameterFeatureMembership_Factory.create())
```

### 7.7.5.3.13 ChangeTriggerExpressionFeatureTyping\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

ToFeatureTyping\_Init  
UniqueMapping

#### Mapping Source

```

        */
    }
}
assert constraint assert_sysMLv1Constraint : SysMLv1Constraint;
}

```

## General Mappings

GenericToConstraintDefinition\_Mapping  
NamedElementMain\_Mapping

## Mapping Source

Constraint

## Mapping Target

ConstraintDefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConstraintDefinition::ownedRelationship () : Relationship [0..\*]

```

self.oclAsType (ElementMain_Mapping).ownedRelationship ()
->union (Set {ElementFeatureMembership_Mapping.getMapped (from.specification),
CommonReturnParameterReferenceUsageMembership_Mapping.getMapped (from.specification)})

```

### 7.7.6.2.6 ConstrainedElementFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

GenericToFeatureMembership\_Mapping

## Mapping Source

Constraint

## Mapping Target

FeatureMembership

Trigger

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`TransitionChangeTriggerConstraintUsage_Mapping.getMapped (from)`

#### 7.7.5.3.14 ChangeTriggerExpressionFeatureValue\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates a feature value relationship.

#### General Mappings

UniqueMapping  
ToFeatureValue\_Init

#### Mapping Source

Trigger

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

`ConstraintUsage_Mapping.getMapped (from)`

### 7.7.6.2.7 ConstraintUsageFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

`GenericToFeatureTyping_Mapping`

#### Mapping Source

Constraint

#### Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

`from`

### 7.7.6.2.8 ConstraintUsage\_Mapping

#### Description

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
ChangeTriggerExpressionFeatureReferenceExpression_Mapping.getMapped(from)
```

#### 7.7.5.3.15 ChangeTriggerExpressionInvocationExpression\_Mapping

**[SYSML2\\_-131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates the invocation expression for the trigger invocation expression of the target of the mapping of a `UML4SysML::Trigger` referencing a `UML4SysML::ChangeEvent`.

##### General Mappings

`ToInvocationExpression_Init`  
`UniqueMapping`

##### Mapping Source

`Trigger`

##### Mapping Target

`InvocationExpression`

##### Owned Mappings

`(none)`

##### Applicable filters

`(none)`

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `InvocationExpression::ownedRelationship () : Relationship [0..*]`

```
Set{ChangeTriggerExpressionFeatureTyping_Mapping.getMapped(from)}
```

```
->including(ReturnParameterFeatureMembership_Factory.create())
```

#### 7.7.5.3.16 ChangeTriggerExpressionParameterMembership\_Mapping

**[SYSML2\\_-131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates a membership relationship for `memberElement()`.





## General Mappings

ToParameterMembership\_Init  
UniqueMapping

## Mapping Source

Trigger

## Mapping Target

ParameterMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`ChangeTriggerExpressionFeature_Mapping.getMapped(from)`

### 7.7.5.3.17 ChangeTriggerFeature\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

## Description

Creates the feature for the mapping of a UML4SysML::Trigger referencing a UML4SysML::ChangeEvent.

## General Mappings

ToFeature\_Init  
UniqueMapping

## Mapping Source

Trigger

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters



(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set{ChangeTriggerEventChainingFeature_Mapping.getMapped(from) }`  
`->including(ChangeTriggerEventReturnParameterChainingFeature_Mapping.getMapped(from))`

### 7.7.5.3.18 ChangeTriggerFeatureMembership\_Mapping

**[SYSML2 -131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

UniqueMapping  
ToFeatureMembership\_Init

#### Mapping Source

Trigger

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`ChangeTriggerBindingConnector_Mapping.getMapped(from)`

### 7.7.5.3.19 ChangeTriggerFeatureValue\_Mapping

**[SYSML2 -131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**



### Description

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_Init  
UniqueMapping

### Mapping Source

Trigger

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  
`ChangeTriggerInvocationExpression_Mapping.getMapped (from)`

### 7.7.5.3.20 ChangeTriggerInvocationExpression\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

### Description

Creates the trigger invocation expression of the target of the mapping of a UML4SysML::Trigger referencing a UML4SysML::ChangeEvent.

### General Mappings

ToTriggerInvocationExpression\_Init  
UniqueMapping

### Mapping Source

Trigger

### Mapping Target

TriggerInvocationExpression



## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TriggerInvocationExpression::kind () : TriggerKind [0..1]`  
`SysML::Systems::Actions::TriggerKind::when`
- `TriggerInvocationExpression::ownedRelationship () : Relationship [0..*]`  
`Set{ChangeTriggerExpressionParameterMembership_Mapping.getMapped(from) }`  
`->including(ReturnParameterFeatureMembership_Factory.create())`

### 7.7.5.3.21 ChangeTriggerReferenceSubsetting\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

## Description

Creates a subsetting relationship.

## General Mappings

UniqueMapping  
ToReferenceSubsetting\_Init

## Mapping Source

Trigger

## Mapping Target

ReferenceSubsetting

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules





In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceSubsetting::referencedFeature () : Feature [1]`  
`ChangeTriggerFeature_Mapping.getMapped(from)`
- `ReferenceSubsetting::ownedRelatedElement () : Element [0..*]`  
`Set{ChangeTriggerFeature_Mapping.getMapped(from)}`

#### 7.7.5.3.22 ChangeTriggerReferenceUsage\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates a reference usage.

##### General Mappings

UniqueMapping  
ToReferenceUsage\_Init

##### Mapping Source

Trigger

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_in'`
- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{ChangeTriggerFeatureValue_Mapping.getMapped(from)}`

#### 7.7.5.3.23 ChangeTriggerReturnEndFeatureMembership\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**



### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

UniqueMapping

ToEndFeatureMembership\_Init

### Mapping Source

Trigger

### Mapping Target

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`ChangeTriggerReturnReferenceUsage_Mapping.getMapped(from)`

### 7.7.5.3.24 ChangeTriggerReturnParameter\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

### Description

Creates the return parameter feature for the mapping of a UML4SysML::Trigger referencing a UML4SysML::ChangeEvent.

### General Mappings

UniqueMapping

ToReferenceUsage\_Init

### Mapping Source

Trigger

### Mapping Target

ReferenceUsage



## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_out'`

### 7.7.5.3.25 ChangeTriggerReturnParameterMembership\_Mapping

**[SYSML2\\_-131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToReturnParameterMembership\_Init  
UniqueMapping

## Mapping Source

Trigger

## Mapping Target

ReturnParameterMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReturnParameterMembership::ownedMemberParameter () : Feature [1]`  
`ChangeTriggerReturnParameter_Mapping.getMapped(from)`



#### 7.7.5.3.26 ChangeTriggerReturnReferenceSubsetting\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates a subsetting relationship.

##### General Mappings

ToReferenceSubsetting\_Init  
UniqueMapping

##### Mapping Source

Trigger

##### Mapping Target

ReferenceSubsetting

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  
`ChangeTriggerReturnParameter_Mapping.getMapped(from)`

#### 7.7.5.3.27 ChangeTriggerReturnReferenceUsage\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates a reference usage.

##### General Mappings

UniqueMapping  
ToReferenceUsage\_Init

##### Mapping Source

Trigger





## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
`Set{ChangeTriggerReturnReferenceSubsetting_Mapping.getMapped(from)}`
- ReferenceUsage::isEnd () : Boolean [1]  
`true`

### 7.7.5.3.28 OpaqueBehavior\_Mapping

#### Description

A UML4SysML::OpaqueBehavior is mapped to a SysML v2 ActionDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1OpaqueBehavior {  
    language "Built-in Math"  
    /*  
    * result = 42 + 23;  
    */  
}
```

#### General Mappings

Behavior\_Mapping

#### Mapping Source

OpaqueBehavior

#### Mapping Target

ActionDefinition

#### Owned Mappings

(none)



## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.owner.ocIsKindOf(UML::Package)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionDefinition::ownedRelationship () : Relationship [0..*]`

```
let parameters : Set(UML::Parameter) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
let parameterSets : Set(UML::ParameterSet) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::ParameterSet)) in
let features : Set(UML::Property) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Property)) in
let elementsOMS : Set(UML::Element) =
  (((from.ownedElement - parameters) - parameterSets) - features) in
elementsOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(features->collect(e | PropertyMembership_Mapping.getMapped(e)))
->union(parameters->collect(e | ParameterMembership_Mapping.getMapped(e)))
->union(parameterSets->collect(e | ParameterSetMembership_Mapping.getMapped(e)))
->union(from.language
  ->collect(1 | OpaqueBehaviorMembership_Mapping.getMapped(from, 1)))
```

### 7.7.5.3.29 OpaqueBehaviorMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

OpaqueBehavior

## Mapping Target

OwningMembership with qualifier: language:String

## Owned Mappings

(none)

## Applicable filters

(none)



## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement (in language : String) : Element [1]`

```
OpaqueBehaviorSpecification_Mapping.getMapped(from, language)
```

### 7.7.5.3.30 OpaqueBehaviorSpecification\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

The mapping class creates the SysML v2 TextualRepresentation elements from the languages and bodies properties of the given UML4SysML::OpaqueBehavior.

##### General Mappings

ToTextualRepresentation\_Init  
Mapping

##### Mapping Source

OpaqueBehavior

##### Mapping Target

TextualRepresentation with qualifier: language:String

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TextualRepresentation::language () : String [1]`

```
language
```

- `TextualRepresentation::body () : String [1]`

```
let index:Integer = from.language->indexOf(language) in  
from._'body'->at(index)
```

### 7.7.5.3.31 SignalTriggerReferenceUsage\_Mapping

#### **SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**



### Description

Creates a reference usage.

### General Mappings

UniqueMapping  
ToReferenceUsage\_Init

### Mapping Source

Trigger

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_in'`
- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{SignalTriggerReferenceUsageFeatureTyping_Mapping.getMapped(from)}`

#### 7.7.5.3.32 SignalTriggerReferenceUsageFeatureTyping\_Mapping

**[SYSML2\\_-131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

UniqueMapping  
ToFeatureTyping\_Init

### Mapping Source

Trigger

### Mapping Target





FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`from.event.oclAsType(UML::SignalEvent).signal`

### 7.7.5.3.33 TimeEvent\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Main mapping class for the mapping of UML4SysML::TimeEvent.

```
calc sysMLv1TimeEvent1 {  
  language "language"  
  /* duration */  
}
```

## General Mappings

NamedElementMain\_Mapping  
ToCalculationUsage\_Init

## Mapping Source

TimeEvent

## Mapping Target

CalculationUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules



In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `CalculationUsage::ownedRelationship () : Relationship [0..*]`  
`from.ownedComment`  
`->reject (c | c.annotatedElement->includes (from))`  
`->collect (c| CommentOwnership_Mapping.getMapped(c))->asSet ()`  
`->including (OpaqueExpressionMembership_Mapping.getMapped (from.when.expr))`

#### 7.7.5.3.34 TimeTriggerBindingConnector\_Mapping

**[SYSML2 -131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates the binding connector between the result of the trigger calculation usage and the result of the time event calculation usage.

##### General Mappings

UniqueMapping  
ToBindingConnectorAsUsage\_Init

##### Mapping Source

Trigger

##### Mapping Target

BindingConnectorAsUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `BindingConnectorAsUsage::ownedRelationship () : Relationship [0..*]`  
`Set {TimeTriggerReturnEndFeatureMembership_Mapping.getMapped (from) }`  
`->including (TimeTriggerEndFeatureMembership_Mapping.getMapped (from))`



### 7.7.5.3.35 TimeTriggerCalculationUsage\_Mapping

**SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates the calculation usage of the target of the mapping of a UML4SysML::Trigger referencing a UML4SysML::TimeEvent.

#### General Mappings

UniqueMapping  
ToCalculationUsage\_Init

#### Mapping Source

Trigger

#### Mapping Target

CalculationUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- CalculationUsage::ownedRelationship () : Relationship [0..\*]  
`Set{TimeTriggerReturnParameterMembership_Mapping.getMapped(from) }`  
`->including(TimeTriggerFeatureMembership_Mapping.getMapped(from))`
- CalculationUsage::declaredName () : String [0..1]  
`from.name`

### 7.7.5.3.36 TimeTriggerEndFeatureMembership\_Mapping

**SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings



ToEndFeatureMembership\_Init  
UniqueMapping

#### Mapping Source

Trigger

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
TimeTriggerReferenceUsage\_Mapping.getMapped(from)

### 7.7.5.3.37 TimeTriggerEventChainingFeature\_Mapping

**[SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation](#)**

#### Description

Creates the chaining feature for the event for the mapping of a UML4SysML::Trigger referencing a UML4SysML::TimeEvent.

#### General Mappings

ToFeatureChaining\_Init  
UniqueMapping

#### Mapping Source

Trigger

#### Mapping Target

FeatureChaining

#### Owned Mappings

(none)

#### Applicable filters





(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChaining::chainingFeature () : Feature [1]`  
`from.event`

### 7.7.5.3.38 TimeTriggerEventReturnParameterChainingFeature\_Mapping

**SysML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates the chaining feature for the return parameter for the mapping of a UML4SysML::Trigger referencing a UML4SysML::TimeEvent.

#### General Mappings

UniqueMapping  
ToFeatureChaining\_Init

#### Mapping Source

Trigger

#### Mapping Target

FeatureChaining

#### Owned Mappings

(none)

#### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChaining::chainingFeature () : Feature [1]`  
`TimeTriggerReturnParameter_Mapping.getMapped(from)`

### 7.7.5.3.39 TimeTriggerExpressionFeature\_Mapping

**SysML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description



Creates the feature for the trigger invocation expression of the target of the mapping of a UML4SysML::Trigger referencing a UML4SysML::TimeEvent.

### General Mappings

UniqueMapping  
ToFeature\_Init

### Mapping Source

Trigger

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  
`Set{TimeTriggerExpressionFeatureValue_Mapping.getMapped(from)}`

### 7.7.5.3.40 TimeTriggerExpressionFeatureTyping\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
UniqueMapping

### Mapping Source

Trigger

### Mapping Target

FeatureTyping

### Owned Mappings



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`TransitionTimeTriggerCalculationUsage_Mapping.getMapped (from)`

### 7.7.5.3.41 TimeTriggerExpressionFeatureValue\_Mapping

**SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates a feature value relationship.

#### General Mappings

ToFeatureValue\_Init  
UniqueMapping

#### Mapping Source

Trigger

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`TimeTriggerExpressionInvocationExpression_Mapping.getMapped (from)`



### 7.7.5.3.42 TimeTriggerExpressionInvocationExpression\_Mapping

**SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates the invocation expression for the trigger invocation expression of the target of the mapping of a UML4SysML::Trigger referencing a UML4SysML::TimeEvent.

#### General Mappings

UniqueMapping  
ToInvocationExpression\_Init

#### Mapping Source

Trigger

#### Mapping Target

InvocationExpression

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `InvocationExpression::ownedRelationship () : Relationship [0..*]`  

```
Set{TimeTriggerExpressionFeatureTyping_Mapping.getMapped(from) }  
->including (ReturnParameterFeatureMembership_Factory.create())
```

### 7.7.5.3.43 TimeTriggerExpressionParameterMembership\_Mapping

**SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

UniqueMapping  
ToParameterMembership\_Init

#### Mapping Source





Trigger

#### Mapping Target

ParameterMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`TimeTriggerExpressionFeature_Mapping.getMapped (from)`

#### 7.7.5.3.44 TimeTriggerFeature\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates the feature for the mapping of a UML4SysML::Trigger referencing a UML4SysML::TimeEvent.

#### General Mappings

UniqueMapping  
ToFeature\_Init

#### Mapping Source

Trigger

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules



In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set{TimeTriggerEventChainingFeature_Mapping.getMapped(from) }`  
`->including (TimeTriggerEventReturnParameterChainingFeature_Mapping.getMapped(from) )`

#### 7.7.5.3.45 TimeTriggerFeatureMembership\_Mapping

**[SYSML2\\_-131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
UniqueMapping

##### Mapping Source

Trigger

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`TimeTriggerBindingConnector_Mapping.getMapped(from)`

#### 7.7.5.3.46 TimeTriggerFeatureTyping\_Mapping

**[SYSML2\\_-131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

The mapping class creates the SysML v2 AssertConstraintUsage elements for the constrained elements of the UML4SysML::Constraint mapping.

### General Mappings

GenericToUsage\_Mapping

### Mapping Source

Constraint

### Mapping Target

AssertConstraintUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- AssertConstraintUsage::declaredName () : String [0..1]  
`'assert_' + from.name`
- AssertConstraintUsage::ownedRelationship () : Relationship [0..\*]  
`from.ownedComment->reject(c | c.annotatedElement->includes(from))->collect(c| CommentOwnership->union(Set{ConstraintUsageFeatureTyping_Mapping.getMapped(from), CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)}))`

### 7.7.6.2.9 Dependency\_Mapping

#### Description

A UML4SysML::Dependency relationship is mapped to a SysML v2 Dependency relationship.

### General Mappings

DirectedRelationship\_Mapping

### Mapping Source

Dependency

### Mapping Target

Dependency

## General Mappings

UniqueMapping  
ToFeatureTyping\_Init

## Mapping Source

Trigger

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
if from.event.oclAsType(UML::TimeEvent).isRelative then
  SYSML2::AttributeDefinition.allInstances()
  ->any(m | m.qualifiedName = 'ISQ::DurationValue')
else
  SYSML2::AttributeDefinition.allInstances()
  ->any(m | m.qualifiedName = 'Time::TimeInstantValue')
endif
```

### 7.7.5.3.47 TimeTriggerFeatureValue\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

## Description

Creates a feature value relationship.

## General Mappings

ToFeatureValue\_Init  
UniqueMapping

## Mapping Source

Trigger

## Mapping Target

FeatureValue



## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`TimeTriggerInvocationExpression_Mapping.getMapped(from)`

### 7.7.5.3.48 TimeTriggerInvocationExpression\_Mapping

**`SYSML2_-131`: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

## Description

Creates the trigger invocation expression of the target of the mapping of a `UML4SysML::Trigger` referencing a `UML4SysML::TimeEvent`.

## General Mappings

`ToTriggerInvocationExpression_Init`  
`UniqueMapping`

## Mapping Source

`Trigger`

## Mapping Target

`TriggerInvocationExpression`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TriggerInvocationExpression::kind () : TriggerKind [0..1]`  
`if from.event.oclAsType(UML::TimeEvent).isRelative then`  
`SysML::Systems::Actions::TriggerKind::after`





```

else
  SysML::Systems::Actions::TriggerKind::at
endif

```

- `TriggerInvocationExpression::ownedRelationship () : Relationship [0..*]`

```

Set{TimeTriggerExpressionParameterMembership_Mapping.getMapped(from)}

```

#### 7.7.5.3.49 TimeTriggerReferenceSubsetting\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates a subsetting relationship.

##### General Mappings

```

ToReferenceSubsetting_Init
UniqueMapping

```

##### Mapping Source

```

Trigger

```

##### Mapping Target

```

ReferenceSubsetting

```

##### Owned Mappings

```

(none)

```

##### Applicable filters

```

(none)

```

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceSubsetting::ownedRelatedElement () : Element [0..*]`

```

Set{TimeTriggerFeature_Mapping.getMapped(from)}

```

- `ReferenceSubsetting::referencedFeature () : Feature [1]`

```

TimeTriggerFeature_Mapping.getMapped(from)

```

#### 7.7.5.3.50 TimeTriggerReferenceUsage\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description



Creates a reference usage.

### General Mappings

ToReferenceUsage\_Init  
UniqueMapping

### Mapping Source

Trigger

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]  
KerML::FeatureDirectionKind::\_in'
- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
Set{TimeTriggerFeatureValue\_Mapping.getMapped(from) }

#### 7.7.5.3.51 TimeTriggerReturnEndFeatureMembership\_Mapping

**[SYSML2 -131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToEndFeatureMembership\_Init  
UniqueMapping

### Mapping Source

Trigger

### Mapping Target

EndFeatureMembership



## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  
`TimeTriggerReturnReferenceUsage_Mapping.getMapped(from)`

### 7.7.5.3.52 TimeTriggerReturnParameter\_Mapping

**[SYSML2\\_-131](#): ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

## Description

Creates the return parameter feature for the mapping of a `UML4SysML::Trigger` referencing a `UML4SysML::TimeEvent`.

## General Mappings

`UniqueMapping`  
`ToReferenceUsage_Init`

## Mapping Source

`Trigger`

## Mapping Target

`ReferenceUsage`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{TimeTriggerFeatureTyping_Mapping.getMapped(from)}`



#### 7.7.5.3.53 TimeTriggerReturnParameterMembership\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

UniqueMapping  
ToReturnParameterMembership\_Init

##### Mapping Source

Trigger

##### Mapping Target

ReturnParameterMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReturnParameterMembership::ownedMemberParameter () : Feature [1]  
`TimeTriggerReturnParameter_Mapping.getMapped(from)`

#### 7.7.5.3.54 TimeTriggerReturnReferenceSubsetting\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates a subsetting relationship.

##### General Mappings

UniqueMapping  
ToReferenceSubsetting\_Init

##### Mapping Source

Trigger





## Mapping Target

ReferenceSubsetting

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  
`TimeTriggerReturnParameter_Mapping.getMapped (from)`

### 7.7.5.3.55 TimeTriggerReturnReferenceUsage\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

## Description

Creates a reference usage.

## General Mappings

UniqueMapping  
ToReferenceUsage\_Init

## Mapping Source

Trigger

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::isEnd () : Boolean [1]



true

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{TimeTriggerReturnReferenceSubsetting_Mapping.getMapped(from)}
```

### 7.7.5.3.56 Trigger\_Mapping

[SYSML2\\_-382](#): Subclause 7.7.5.3.7 Trigger\_Mapping is empty

#### Description

A `UML4SysML::Trigger` is mapped to a SysML v2 `AcceptActionUsage`.

#### General Mappings

`NamedElementMain_Mapping`  
`ToActionUsage_Init`

#### Mapping Source

`Trigger`

#### Mapping Target

`AcceptActionUsage`

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `AcceptActionUsage::ownedRelationship () : Relationship [0..*]`  

```
from.ownedComment  
->reject(c | c.annotatedElement->includes(from))  
->collect(c| CommentOwnership_Mapping.getMapped(c))->asSet()  
->including(TriggerParameterMembership_Mapping.getMapped(from))  
->including(ParameterMembership_Factory.create())
```

### 7.7.5.3.57 TriggerParameterMembership\_Mapping

[SYSML2\\_-131](#): `ChangeEvent` should be mapped to an accept action instead of `TextualRepresentation`

#### Description



Creates a membership relationship for *memberElement()*.

## General Mappings

UniqueMapping  
ToParameterMembership\_Init

## Mapping Source

Trigger

## Mapping Target

ParameterMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  

```
if from.event.ocIsKindOf(UML::SignalEvent) then
  SignalTriggerReferenceUsage_Mapping.getMapped(from)
else if from.event.ocIsKindOf(UML::TimeEvent) then
  TimeTriggerReferenceUsage_Mapping.getMapped(from)
else if from.event.ocIsKindOf(UML::ChangeEvent) then
  ChangeTriggerReferenceUsage_Mapping.getMapped(from)
else
  OclUndefined
endif endif endif
```

## 7.7.6 CommonStructure

### 7.7.6.1 Overview

[SYSML2\\_-329: Mapping overview tables are wrong](#)

Table 8. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Abstraction	Dependency
Comment	Comment
Constraint	ConstraintDefinition
Dependency	Dependency
ElementImport	MembershipImport



SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
PackageImport	NamespaceImport
Realization	Dependency
Usage	Dependency

## 7.7.6.2 Mapping Specifications

### 7.7.6.2.1 Abstraction\_Mapping

#### Description

A UML4SysML::Abstraction relationship is mapped to a SysML v2 Dependency relationship.

#### General Mappings

Dependency\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

Dependency

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.6.2.2 Comment\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

#### Description

A UML4SysML::Comment is mapped to a SysML v2 Comment.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1;
part def SysMLv1Block2;
action def SysMLv1Activitiy {
    comment about SysMLv1Activity, SysMLv1Block1
        /* comment body */
}
comment about SysMLv1Block1, SysMLv1Block /* comment body */
```

#### General Mappings





ElementMain\_Mapping  
ToAnnotatingElement\_Init

### Mapping Source

Comment

### Mapping Target

Comment

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not Helper.hasStereotypeApplied(src, 'SysML::ModelElements::ElementGroup')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Comment::annotation () : Annotation [0..*]`  

```
from.annotatedElement  
->collect (e | CommentAnnotation_Mapping.getMapped(from, e))
```
- `Comment::body () : String [1]`  

```
if from.body->isEmpty() then '' else from.body endif
```
- `Comment::ownedRelationship () : Relationship [0..*]`  

```
self.oclAsType (ElementMain_Mapping).ownedRelationship()  
->union (self.annotation () ->asSet ())
```

### 7.7.6.2.3 CommentAnnotation\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the annotation relationship for the UML4SysML::Comment mapping.

### General Mappings

ToAnnotation\_Init  
Mapping

### Mapping Source

Comment



### Mapping Target

Annotation with qualifier: annotatedElement:Element

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Annotation::annotatedElement (in annotatedElement : Element) : Element [1]  
`ElementMain_Mapping.getMapped(annotatedElement)`
- Annotation::owningAnnotatedElement () : Element [0..1]  
`null`
- Annotation::annotatingElement () : AnnotatingElement [1]  
`Comment_Mapping.getMapped(from)`

#### 7.7.6.2.4 CommentOwnership\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

That mapping class creates an ownership relation that is convenient for a Comment. In SysMLv1/UML can be owned by any kind of element, including some that are not translated to SysMLv2 Namespaces.

### General Mappings

ToAnnotation `Init`  
UniqueMapping

### Mapping Source

Comment

### Mapping Target

Annotation

### Owned Mappings

(none)

### Applicable filters



(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Annotation::annotatedElement () : Element [1]`  
`ElementMain_Mapping.getMapped(from.owner)`
- `Annotation::ownedRelatedElement () : Element [0..*]`  
`Set{self.annotatingElement () }`
- `Annotation::annotatingElement () : AnnotatingElement [1]`  
`Comment_Mapping.getMapped(from)`

### 7.7.6.2.5 Constraint\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

A `UML4SysML::Constraint` is mapped to a SysML v2 `ConstraintDefinition` and `AssertConstraintUsages` for the constrained elements.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {
  constraint def SysMLv1Constraint {
    calc sysMLv1Constraint {
      language "English"
      /*
      * constraint specification
      */
    }
  }
  assert constraint assert_sysMLv1Constraint : SysMLv1Constraint;
}
```

## General Mappings

`ToConstraintDefinition_Init`  
`NamedElementMain_Mapping`

## Mapping Source

`Constraint`

## Mapping Target

`ConstraintDefinition`

## Owned Mappings



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConstraintDefinition::ownedRelationship () : Relationship [0..*]`  

```
self.oclAsType (ElementMain_Mapping).ownedRelationship()  
->union (Set {ElementFeatureMembership_Mapping.getMapped (from.specification),  
CommonReturnParameterReferenceUsageMembership_Mapping.getMapped (from.specification)})
```

### 7.7.6.2.6 ConstrainedElementFeatureMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

Constraint

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  

```
ConstraintUsage_Mapping.getMapped (from)
```





#### 7.7.6.2.7 ConstraintUsageFeatureTyping\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

ToFeatureTyping\_Init  
Mapping

##### Mapping Source

Constraint

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
from

#### 7.7.6.2.8 ConstraintUsage\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates the SysML v2 AssertConstraintUsage elements for the constrained elements of the UML4SysML::Constraint mapping.

##### General Mappings

ToUsage\_Init  
Mapping

##### Mapping Source

Constraint

##### Mapping Target

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Dependency::client () : Element [0..*]`

```
from.source->collect(e | ElementMain_Mapping.getMapped(e))
```

- `Dependency::declaredName () : String [0..1]`

```
from.name
```

- `Dependency::supplier () : Element [0..*]`

```
from.target->collect(e | ElementMain_Mapping.getMapped(e))
```

### 7.7.6.2.10 DirectedRelationship\_Mapping

#### Description

The mapping class is the abstract base class for all UML4SysML::DirectedRelationship mappings.

#### General Mappings

Relationship\_Mapping

#### Mapping Source

DirectedRelationship

#### Mapping Target

Relationship

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

AssertConstraintUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- AssertConstraintUsage::ownedRelationship () : Relationship [0..\*]

```
from.ownedComment->reject(c | c.annotatedElement->includes(from))->collect(c| CommentOwnershipMapping.getMapped(from),  
->union(Set{ConstraintUsageFeatureTyping_Mapping.getMapped(from),  
CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)}))
```

- AssertConstraintUsage::declaredName () : String [0..1]

```
'assert_' + from.name
```

## 7.7.6.2.9 Dependency\_Mapping

### Description

A UML4SysML::Dependency relationship is mapped to a SysML v2 Dependency relationship.

### General Mappings

DirectedRelationship\_Mapping

### Mapping Source

Dependency

### Mapping Target

Dependency

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Dependency::declaredName () : String [0..1]

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Relationship::target () : Element [0..\*]  

```
from.target->collect(e | ElementMain_Mapping.getMapped(e))
```
- Relationship::source () : Element [0..\*]  

```
from.source->collect(e | ElementMain_Mapping.getMapped(e))
```

#### 7.7.6.2.11 ElementMain\_Mapping

##### Description

This is the general abstract class to be used as an ancestor for any class mapping specification.

##### General Mappings

GenericToElement\_Mapping  
MainMapping

##### Mapping Source

Element

##### Mapping Target

Element

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Element::ownedRelationship () : Relationship [0..\*]  

```
from.ownedComment->reject(c | c.annotatedElement->includes(from))->collect(c | CommentOwnership)
```
- Element::elementId () : String [1]  

```
Helper.getID(from)
```

#### 7.7.6.2.12 ElementMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

```
from.name
```

- `Dependency::supplier () : Element [0..*]`

```
from.target->collect (e | ElementMain_Mapping.getMapped (e) )
```

- `Dependency::client () : Element [0..*]`

```
from.source->collect (e | ElementMain_Mapping.getMapped (e) )
```

#### 7.7.6.2.10 DirectedRelationship\_Mapping

##### Description

The mapping class is the abstract base class for all UML4SysML::DirectedRelationship mappings.

##### General Mappings

Relationship\_Mapping

##### Mapping Source

DirectedRelationship

##### Mapping Target

Relationship

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Relationship::source () : Element [0..*]`

```
from.source->collect (e | ElementMain_Mapping.getMapped (e) )
```

- `Relationship::target () : Element [0..*]`

```
from.target->collect (e | ElementMain_Mapping.getMapped (e) )
```

#### 7.7.6.2.11 ElementMain\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

This is the general abstract class to be used as an ancestor for any class mapping specification.

##### General Mappings

## General Mappings

`GenericToMembership_Mapping`

## Mapping Source

Element

## Mapping Target

Membership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::visibility () : VisibilityKind [1]`

```
if (from.ocIsKindOf(UML::NamedElement)) then
    from.ocAsType(UML::NamedElement).visibility
else
    KerML::VisibilityKind::public
endif
```
- `Membership::membershipOwningNamespace () : Element [0..*]`

```
Set{ElementMain_Mapping(from)}
-- will not be used since corresponding attribute is derived,
-- but required for redefinition
```
- `Membership::memberElement () : Element [1]`

```
ElementMain_Mapping.getMapped(from)
```

### 7.7.6.2.13 ElementOwnership\_Mapping

#### Description

The mapping class is the abstract base class for mappings that target ownership relationships.

## General Mappings

`GenericToRelationship_Mapping`

UniqueMapping

## Mapping Source

Element

ToElement\_Init  
MainMapping

### Mapping Source

Element

### Mapping Target

Element

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Element::elementId () : String [1]

```
Helper.getID(from)
```

- Element::ownedRelationship () : Relationship [0..\*]

```
from.ownedComment->reject(c | c.annotatedElement->includes(from))->collect(c| CommentOwnership)
```

#### 7.7.6.2.12 ElementMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

Element

### Mapping Target

Membership

### Owned Mappings

(none)

## Mapping Target

Relationship

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Relationship::target () : Element [0..\*]  
`OrderedSet{ElementMain_Mapping.getMapped(from) }`
- Relationship::source () : Element [0..\*]  
`OrderedSet{ElementMain_Mapping.getMapped(from.owner) }`
- Relationship::ownedRelatedElement () : Element [0..\*]  
`self.target()`

### 7.7.6.2.14 ElementOwningMembership\_Mapping

#### Description

Creates a owning membership relationship for *ownedMemberElement()*.

#### General Mappings

ElementMembership\_Mapping  
ElementOwnership\_Mapping

#### Mapping Source

Element

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)



## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::visibility () : VisibilityKind [1]  

```
if (from.ocIsKindOf(UML::NamedElement)) then
    from.ocAsType(UML::NamedElement).visibility
else
    KerML::VisibilityKind::public
endif
```
- Membership::memberElement () : Element [1]  

```
ElementMain_Mapping.getMapped(from)
```
- Membership::membershipOwningNamespace () : Element [0..\*]  

```
Set{ElementMain_Mapping(from)}
-- will not be used since corresponding attribute is derived,
-- but required for redefinition
```

### 7.7.6.2.13 ElementOwnership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

The mapping class is the abstract base class for mappings that target ownership relationships.

## General Mappings

ToRelationship\_Init  
UniqueMapping

## Mapping Source

Element

## Mapping Target

Relationship

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedRelatedElement () : Element [0..*]`  
`Set { self.ownedMemberElement () }`
- `OwningMembership::membershipOwningNamespace () : Element [0..*]`  
`Set { ElementMain_Mapping (from) }`  
`-- will not be used since corresponding attribute is derived,`  
`-- but required for redefinition`
- `OwningMembership::ownedMemberElement () : Element [1]`  
`ElementMain_Mapping.getMapped (from)`

### 7.7.6.2.15 NamedElementMain\_Mapping

#### Description

The mapping class is the abstract base class for mappings of UML4SysML::NamedElements.

#### General Mappings

ElementMain\_Mapping

#### Mapping Source

NamedElement

#### Mapping Target

Element

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Element::declaredName () : String [0..1]`  
`from.name`

### 7.7.6.2.16 Namespace\_Mapping

#### Description

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Relationship::ownedRelatedElement () : Element [0..\*]  
`self.target()`
- Relationship::source () : Element [0..\*]  
`OrderedSet {ElementMain_Mapping.getMapped (from,owner) }`
- Relationship::target () : Element [0..\*]  
`OrderedSet {ElementMain_Mapping.getMapped (from) }`

#### 7.7.6.2.14 ElementOwningMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

Creates a owning membership relationship for *ownedMemberElement()*.

##### **General Mappings**

ElementMembership\_Mapping  
 ElementOwnership\_Mapping

##### **Mapping Source**

Element

##### **Mapping Target**

OwningMembership

##### **Owned Mappings**

(none)

##### **Applicable filters**

(none)

##### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::membershipOwningNamespace () : Element [0..\*]  
`Set {ElementMain_Mapping (from) }`  
`-- will not be used since corresponding attribute is derived,`  
`-- but required for redefinition`
- OwningMembership::ownedMemberElement () : Element [1]  
`ElementMain_Mapping.getMapped (from)`

The mapping class is the abstract base class for UML4SysML::Namespace mappings.

### General Mappings

GenericToNamespace\_Mapping  
NamedElementMain\_Mapping

### Mapping Source

Namespace

### Mapping Target

Namespace

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Namespace::ownedImport () : Import [0..\*]  
Set { }

## 7.7.6.2.17 Relationship\_Mapping

### Description

The mapping class is the abstract base class for UML4SysML::Relationship mappings.

### General Mappings

GenericToRelationship\_Mapping  
ElementMain\_Mapping

### Mapping Source

Relationship

### Mapping Target

Relationship

### Owned Mappings

(none)

### Applicable filters

- `OwningMembership::ownedRelatedElement () : Element [0..*]`

```
Set{self.ownedMemberElement () }
```

#### 7.7.6.2.15 NamedElementMain\_Mapping

##### Description

The mapping class is the abstract base class for mappings of `UML4SysML::NamedElements`.

##### General Mappings

`ElementMain_Mapping`

##### Mapping Source

`NamedElement`

##### Mapping Target

`Element`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Element::declaredName () : String [0..1]`

```
from.name
```

#### 7.7.6.2.16 Namespace\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class is the abstract base class for `UML4SysML::Namespace` mappings.

##### General Mappings

`ToNamespace_Init`

`NamedElementMain_Mapping`

##### Mapping Source

`Namespace`

##### Mapping Target



Namespace

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Namespace::ownedImport () : Import [0..*]`  
`Set { }`

## 7.7.6.2.17 Relationship\_Mapping

### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

The mapping class is the abstract base class for UML4SysML::Relationship mappings.

#### General Mappings

`ToRelationship_Init`  
`ElementMain_Mapping`

#### Mapping Source

Relationship

#### Mapping Target

Relationship

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Relationship::owningRelatedElement () : Element [0..1]`  
`ElementMain_Mapping.getMapped (from.owner)`

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Relationship::ownedRelatedElement () : Element [0..\*]  

```
from.relatedElement->select(e | from.ownedElement->includes(e))  
->collect(e | ElementMain_Mapping.getMapped(e))
```
- Relationship::owningRelatedElement () : Element [0..1]  

```
ElementMain_Mapping.getMapped(from.owner)
```

### 7.7.6.2.18 Usage\_Mapping

#### Description

A UML4SysML::Usage relationship is mapped to a SysML v2 Dependency relationship.

#### General Mappings

Dependency\_Mapping

#### Mapping Source

Usage

#### Mapping Target

Dependency

#### Owned Mappings

(none)

## 7.7.7 InformationFlows

This chapter lists all mapping specifications of UML4SysML::InformationFlows model elements.

### 7.7.7.1 Overview

Table 10. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
InformationFlow	FlowConnectionDefinition
InformationItem	ItemDefinition

The following table gives an overview of which SysML v2 elements the UML4SysML::InformationFlows elements are transformed with which mapping class. The mapping details are in [7.7.7.2](#).

### 7.7.7.2 Mapping Specifications



- Relationship::ownedRelatedElement () : Element [0..\*]

```
from.relatedElement->select(e | from.ownedElement->includes(e))
->collect(e | ElementMain_Mapping.getMapped(e))
```

### 7.7.6.2.18 Usage\_Mapping

#### Description

A UML4SysML::Usage relationship is mapped to a SysML v2 Dependency relationship.

#### General Mappings

Dependency\_Mapping

#### Mapping Source

Usage

#### Mapping Target

Dependency

#### Owned Mappings

(none)

#### Applicable filters

(none)

## 7.7.7 InformationFlows

### 7.7.7.1 Overview

**[SYSML2\\_-329](#): Mapping overview tables are wrong**

Table 9. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
InformationFlow	not mapped; see next section
InformationItem	ItemDefinition

### 7.7.7.2 Mapping Specifications

#### 7.7.7.2.1 InformationFlow\_Mapping

**[SYSML2\\_-496](#): Resolution SYSML2\_-424 uses invalid operation call of base mapping class**

**[SYSML2\\_-417](#): Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"**

**[SYSML2\\_-424](#): Adopted resolution SYSML2\_-403 has impact on the v1 to v2 Transformation**

#### Description

### 7.7.7.2.1 InformationFlow\_Mapping

#### Description

A UML4SysML::InformationFlow is mapped to a FlowConnectionDefinition. If the UML4SysML::InformationFlow has defined realizingConnectors an additional FlowConnectionUsage element is created. The transformation rule is specified in the BehavedClassifier::ownedRelationship operation. Then transformation also considers SysMLv1::ItemFlows which is handled by the factory class FlowConnectionUsage\_Factory.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {
    part partA : SysMLv1BlockA;
    part partB : SysMLv1BlockB;
    part itemC : SysMLv1BlockC;

    connection sysMLv1Connector connect partA to partB;
    message : SysMLv1InformationFlowB :> sysMLv1Connector of itemC from partA to partB;
}

part def SysMLv1BlockA;
part def SysMLv1BlockB;
part def SysMLv1BlockC;
part def SysMLv1BlockD;

connection def SysMLv1Association {
    end : SysMLv1BlockA;
    end : SysMLv1BlockB;
}

flow def SysMLv1InformationFlowA :> SysMLv1Association {
    item : SysMLv1BlockC;
    item : SysMLv1BlockD;
}

flow def SysMLv1InformationFlowB {
    end partA : SysMLv1BlockA;
    end partB : SysMLv1BlockB;
}
```

#### General Mappings

Relationship\_Mapping

#### Mapping Source

InformationFlow

#### Mapping Target

FlowConnectionDefinition

#### Owned Mappings

(none)

A UML4SysML::InformationFlow is mapped to a FlowDefinition, if the UML4SysML::InformationFlow has defined realizing connectors or if it is realized by an association. If the information flow has more than one realizing connector, a FlowDefinition element is created for each of them.

## General Mappings

ToConnectionUsage\_Init  
UniqueMapping

## Mapping Source

InformationFlow

## Mapping Target

FlowDefinition with qualifier: realization:NamedElement

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.ocIsKindOf(UML::InformationFlow) and
(src.ocAsType(UML::InformationFlow).realizingConnector->notEmpty())
or src.ocAsType(UML::InformationFlow).realization->notEmpty()
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FlowDefinition::ownedRelationship () : Relationship [0..\*]

```
from.informationSource
->collect(s | InformationFlowEndFeatureMembership_Mapping.getMapped(from, s))->asSet()
->union(from.informationTarget
->collect(t | InformationFlowEndFeatureMembership_Mapping.getMapped(from, t))->asSet())
->union(from.conveyed
->collect(i | InformationFlowConveyedFeatureMembership_Mapping.getMapped(i))->asSet())
->union(from.realization->select(a | a.ocIsKindOf(UML::Association))
->collect(r | InformationFlowSubclassification_Mapping.getMapped(from, r))->asSet())
->asOrderedSet()
```

### 7.7.7.2.2 InformationFlowConveyedFeatureMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FlowConnectionDefinition::ownedRelationship () : Relationship [0..\*]

```
from.source
->collect(s | InformationFlowEndFeatureMembership_Mapping.getMapped(from, s))->asSet()
->union(from.target
->collect(t | InformationFlowEndFeatureMembership_Mapping.getMapped(from, t))->asSet())
->union(from.conveyed
->collect(i | InformationFlowConveyedFeatureMembership_Mapping.getMapped(i))->asSet())
->union(from.realization->select( a | a.ocIsKindOf(UML::Association))
->collect(r | InformationFlowSubclassification_Mapping.getMapped(from, r))->asSet())
->union(self.ocAsType(ElementMain_Mapping).ownedRelationship())
->asOrderedSet()
```

### 7.7.7.2.2 InformationFlowConveyedFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

Classifier

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
InformationItemFlowConveyedItemUsage_Mapping.getMapped(from)
```

ToFeatureMembership\_Init  
Mapping

### Mapping Source

Classifier

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`InformationItemFlowConveyedItemUsage_Mapping.getMapped (from)`

### 7.7.7.2.3 InformationFlowEnd\_Mapping

**SYSML2 -417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"**  
**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the source feature of the FlowDefinition for the mapping of UML4SysML::InformationFlow.

### General Mappings

ToFeature\_Init  
UniqueMapping

### Mapping Source

InformationFlow

### Mapping Target

Feature with qualifier: end:NamedElement

### Owned Mappings

(none)

### Applicable filters

### 7.7.7.2.3 InformationFlowEnd\_Mapping

#### Description

The mapping class creates the source feature of the FlowConnectionDefinition for the mapping of UML4SysML::InformationFlow.

#### General Mappings

GenericToFeature\_Mapping

UniqueMapping

#### Mapping Source

InformationFlow

#### Mapping Target

Feature with qualifier: end:NamedElement

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]  
`true`
- Feature::ownedRelationship () : Relationship [0..\*]  
`Set{InformationFlowFeatureTyping_Mapping.getMapped(from, end)}`

### 7.7.7.2.4 InformationFlowEndFeatureMembership\_Mapping

#### Description

The mapping class creates the source and the target membership relationships of theFlowConnectionDefinition for the UML4SysML::InformationFlow mapping.

#### General Mappings

GenericToFeatureMembership\_Mapping

UniqueMapping

#### Mapping Source

InformationFlow

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]  
`true`
- Feature::ownedRelationship () : Relationship [0..\*]  
`Set{InformationFlowFeatureTyping_Mapping.getMapped(from, end) }`

#### 7.7.7.2.4 InformationFlowEndFeatureMembership\_Mapping

**[SYSML2 -417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"](#)**  
**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

### Description

The mapping class creates the source and the target membership relationships of the `FlowDefinition` for the `UML4SysML::InformationFlow` mapping.

### General Mappings

`ToFeatureMembership_Init`  
`UniqueMapping`

### Mapping Source

`InformationFlow`

### Mapping Target

`FeatureMembership` with qualifier: `end:NamedElement`

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature (in end : NamedElement) : Feature [1]`  
`InformationFlowEnd_Mapping.getMapped(from, end)`

## Mapping Target

FeatureMembership with qualifier: end:NamedElement

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature (in end : NamedElement) : Feature [1]  
`InformationFlowEnd_Mapping.getMapped(from, end)`

### 7.7.7.2.5 InformationFlowFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

GenericToFeatureTyping\_Mapping  
UniqueMapping

#### Mapping Source

InformationFlow

#### Mapping Target

FeatureTyping with qualifier: element:NamedElement

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type (in source : NamedElement) : Type [1]  
`ElementMain_Mapping.getMapped(element)`



#### 7.7.7.2.5 InformationFlowFeatureTyping\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

ToFeatureTyping\_Init  
UniqueMapping

##### Mapping Source

InformationFlow

##### Mapping Target

FeatureTyping with qualifier: element:NamedElement

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type (in source : NamedElement) : Type [1]  
`ElementMain_Mapping.getMapped(element)`

#### 7.7.7.2.6 InformationFlowSubclassification\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a Subclassification relationship between the target element of the UML4SysML::InformationFlow mapping and the target element of the UML4SysML::Association which realizes the flow.

##### General Mappings

ToSubclassification\_Init  
Mapping

##### Mapping Source

InformationFlow

##### Mapping Target

#### 7.7.7.2.6 InformationFlowSubclassification\_Mapping

##### Description

Creates a Subclassification relationship between the target element of the UML4SysML::InformationFlow mapping and the target element of the UML4SysML::Association which realizes the flow.

##### General Mappings

`GenericToSubclassification_Mapping`

##### Mapping Source

InformationFlow

##### Mapping Target

Subclassification with qualifier: element:Relationship

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subclassification::subclassifier () : Classifier [1]  
`from`
- Subclassification::superclassifier () : Classifier [1]  
`element`

#### 7.7.7.2.7 InformationItem\_Mapping

##### Description

A UML4SysML::InformationItem is mapped to a SysML v2 ItemDefinition.

##### General Mappings

Classifier\_Mapping

##### Mapping Source

InformationItem

##### Mapping Target

Subclassification with qualifier: element:Relationship

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subclassification::superclassifier () : Classifier [1]  
element
- Subclassification::subclassifier () : Classifier [1]  
from

#### 7.7.7.2.7 InformationItem\_Mapping

##### Description

A UML4SysML::InformationItem is mapped to a SysML v2 ItemDefinition.

##### General Mappings

Classifier\_Mapping

##### Mapping Source

InformationItem

##### Mapping Target

ItemDefinition

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.7.2.8 InformationItemFlowConveyedItemUsage\_Mapping

[SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates an ItemUsage element representing the conveyed classifier of an UML4SysML::InformationFlow.

ItemDefinition

### Owned Mappings

(none)

#### 7.7.7.2.8 InformationItemFlowConveyedItemUsage\_Mapping

##### Description

Creates an ItemUsage element representing the conveyed classifier of an UML4SysML::InformationFlow.

##### General Mappings

GenericToItemUsage

##### Mapping Source

Classifier

##### Mapping Target

ItemUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ItemUsage::ownedRelationship () : Relationship [0..\*]

```
Set { InformationItemFlowConveyedItemUsageFeatureTyping_Mapping.getMapped (from) }
```

#### 7.7.7.2.9 InformationItemFlowConveyedItemUsageFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

GenericToFeatureTyping\_Mapping

##### Mapping Source

Classifier

##### Mapping Target

## General Mappings

ToItemUsage\_Init  
Mapping

### Mapping Source

Classifier

### Mapping Target

ItemUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ItemUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ InformationItemFlowConveyedItemUsageFeatureTyping_Mapping.getMapped(from) }
```

#### 7.7.7.2.9 InformationItemFlowConveyedItemUsageFeatureTyping\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

Classifier

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

from

## 7.7.8 Interactions

This chapter lists all mapping specifications of UML4SysML::Interactions model elements.

### 7.7.8.1 Overview

Table 11. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
ActionExecutionSpecification	ActionUsage
BehaviorExecutionSpecification	ActionUsage
CombinedFragment	Interaction
ConsiderIgnoreFragment	not mapped; see next section
Continuation	not mapped; see next section
DestructionOccurrenceSpecification	not mapped; see next section
ExecutionOccurrenceSpecification	not mapped; see next section
Gate	not mapped; see next section
GeneralOrdering	not mapped; see next section
Interaction	ViewDefinition Interaction RequirementUsage
InteractionConstraint	not mapped; see next section
InteractionOperand	Interaction
InteractionUse	Step
Lifeline	PartUsage
Message	ItemFlow
MessageOccurrenceSpecification	not mapped; see next section

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

from

## 7.7.8 Interactions

### 7.7.8.1 Overview

**[SYSML2\\_-417](#): Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"**  
**[SYSML2\\_-329](#): Mapping overview tables are wrong**

**Table 10.** List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
ActionExecutionSpecification	ActionUsage
BehaviorExecutionSpecification	ActionUsage
CombinedFragment	Interaction
ConsiderIgnoreFragment	Interaction
Continuation	not mapped; see next section
DestructionOccurrenceSpecification	not mapped; see next section
ExecutionOccurrenceSpecification	not mapped; see next section
Gate	not mapped; see next section
GeneralOrdering	not mapped; see next section
Interaction	Behavior Interaction
InteractionConstraint	ConstraintDefinition
InteractionOperand	Namespace Interaction
InteractionUse	Step
Lifeline	PartUsage
Message	Flow
MessageOccurrenceSpecification	not mapped; see next section
OccurrenceSpecification	not mapped; see next section
PartDecomposition	Step
StateInvariant	Invariant

### 7.7.8.2 UML4SysML::Interactions elements not mapped

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
OccurrenceSpecification	not mapped; see next section
PartDecomposition	not mapped; see next section
StateInvariant	Invariant

The following table gives an overview of which SysML v2 elements the UML4SysML::Interactions elements are transformed with which mapping class. The mapping details are in [7.7.8.3](#).

The justifications for the elements without mapping are given in [7.7.8.2](#).

### 7.7.8.2 UML4SysML::Interactions elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 12. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
ConsiderIgnoreFragment	Mapping is not specified yet.
Continuation	Mapping is not specified yet.
DestructionOccurrenceSpecification	Mapping is not specified yet.
ExecutionOccurrenceSpecification	Mapping is not specified yet.
Gate	Mapping is not specified yet.
GeneralOrdering	Mapping is not specified yet.
InteractionConstraint	Mapping is not specified yet.
MessageOccurrenceSpecification	Mapping is not specified yet.
OccurrenceSpecification	Mapping is not specified yet.
PartDecomposition	Mapping is not specified yet.

### 7.7.8.3 Mapping Specifications

#### 7.7.8.3.1 ActionExecutionSpecification\_Mapping

##### Description

A UML4SysML::ActionExecutionSpecification is mapped to a SysML v2 ActionUsage.

##### General Mappings

GenericToActionUsage\_Mapping

NamedElementMain\_Mapping

##### Mapping Source

ActionExecutionSpecification

##### Mapping Target



**Table 11. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
ConsiderIgnoreFragment	Mapping is not specified yet.
Continuation	Mapping is not specified yet.
DestructionOccurrenceSpecification	Mapping is not specified yet.
ExecutionOccurrenceSpecification	Mapping is not specified yet.
Gate	Mapping is not specified yet.
GeneralOrdering	Mapping is not specified yet.
InteractionConstraint	Mapping is not specified yet.
MessageOccurrenceSpecification	Mapping is not specified yet.
OccurrenceSpecification	Mapping is not specified yet.
PartDecomposition	Mapping is not specified yet.

### 7.7.8.3 Mapping Specifications

#### 7.7.8.3.1 ActionExecutionSpecification\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

A UML4SysML::ActionExecutionSpecification is mapped to a SysML v2 ActionUsage.

##### General Mappings

ToActionUsage\_Init  
NamedElementMain\_Mapping

##### Mapping Source

ActionExecutionSpecification

##### Mapping Target

ActionUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.8.3.2 BehaviorExecutionSpecification\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

ActionUsage

#### **Owned Mappings**

(none)

### **7.7.8.3.2 BehaviorExecutionSpecification\_Mapping**

#### **Description**

A UML4SysML::BehaviorExecutionSpecification is mapped to a SysML v2 ActionUsage.

#### **General Mappings**

GenericToActionUsage\_Mapping

NamedElementMain\_Mapping

#### **Mapping Source**

BehaviorExecutionSpecification

#### **Mapping Target**

ActionUsage

#### **Owned Mappings**

(none)

### **7.7.8.3.3 CombinedFragment\_Mapping**

#### **Description**

A UML4SysML::CombinedFragment is mapped to a SysMLv2 Interaction.

#### **General Mappings**

NamedElementMain\_Mapping

GenericToInteraction\_Mapping

#### **Mapping Source**

CombinedFragment

#### **Mapping Target**

Interaction

#### **Owned Mappings**

(none)

#### **Applicable filters**

(none)

A UML4SysML::BehaviorExecutionSpecification is mapped to a SysML v2 ActionUsage.

#### General Mappings

ToActionUsage\_Init  
NamedElementMain\_Mapping

#### Mapping Source

BehaviorExecutionSpecification

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### 7.7.8.3.3 CombinedFragment\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

A UML4SysML::CombinedFragment is mapped to a SysMLv2 Interaction.

#### General Mappings

NamedElementMain\_Mapping  
ToInteraction\_Init

#### Mapping Source

CombinedFragment

#### Mapping Target

Interaction

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Interaction::ownedRelationship () : Relationship [0..*]`

```
let operands: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::InteractionOperand)) in
let occurrencesSpecs: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::OccurrenceSpecification)) in
let elements: Set(UML::Element) =
    (from.ownedElement - operands) - occurrencesSpecs in
elements->collect(e | ElementOwningMembership_Mapping.getMapped(e)) ->asSet()
->union(operands->collect(e | InteractionOperandMembership_Mapping.getMapped(e)) ->asSet())
->union(self.ocAsType(ElementMain_Mapping).ownedRelationship())
```

### 7.7.8.3.4 CombinedFragmentMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

`GenericToFeatureMembership_Mapping`

#### Mapping Source

CombinedFragment

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`  
`self.memberFeature ()`
- `FeatureMembership::memberFeature () : Feature [1]`  
`ElementMain_Mapping.getMapped(from)`

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Interaction::ownedRelationship () : Relationship [0..*]`

```
let operands: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::InteractionOperand)) in
let occurrencesSpecs: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::OccurrenceSpecification)) in
let elements: Set(UML::Element) =
    (from.ownedElement - operands) - occurrencesSpecs in
elements->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(operands->collect(e | InteractionOperandMembership_Mapping.getMapped(e))->asSet())
->union(self.ocAsType(ElementMain_Mapping).ownedRelationship())
```

#### 7.7.8.3.4 CombinedFragmentMembership\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

Creates a membership relationship for *memberElement()*.

##### **General Mappings**

ToFeatureMembership\_Init  
Mapping

##### **Mapping Source**

CombinedFragment

##### **Mapping Target**

FeatureMembership

##### **Owned Mappings**

(none)

##### **Applicable filters**

(none)

##### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::memberFeature () : Feature [1]`  
`ElementMain_Mapping.getMapped(from)`
- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`  
`self.memberFeature()`

### 7.7.8.3.5 ExecutionSpecificationMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToEndFeatureMembership\_Mapping

#### Mapping Source

ExecutionSpecification

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::memberFeature () : Feature [1]  
`ElementMain_Mapping.getMapped(from)`
- EndFeatureMembership::ownedMemberFeature () : Feature [0..1]  
`self.memberFeature()`

### 7.7.8.3.6 Interaction\_Mapping

#### Description

A UML4SysML::Interaction is mapped to a SysMLv2 Interaction.

#### General Mappings

Namespace\_Mapping

GenericToInteraction\_Mapping

#### Mapping Source

Interaction

#### Mapping Target

### 7.7.8.3.5 ExecutionSpecificationMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToEndFeatureMembership\_[Init](#)  
Mapping

#### Mapping Source

ExecutionSpecification

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::memberFeature () : Feature [1]  
`ElementMain_Mapping.getMapped(from)`
- EndFeatureMembership::ownedMemberFeature () : Feature [0..1]  
`self.memberFeature()`

### 7.7.8.3.6 Interaction\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

A UML4SysML::Interaction is mapped to a SysMLv2 Interaction.

#### General Mappings

Namespace\_Mapping  
ToInteraction\_[Init](#)

#### Mapping Source

Interaction

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Interaction::ownedRelationship () : Relationship [0..\*]

```
let lifelines: Set(UML::Element) = from.lifeline in
let messageOccurrences: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::MessageOccurrenceSpecification)) in
let executionOccurrences: Set(UML::Element) =
    from.fragment->select(e | e.ocIsKindOf(UML::ExecutionSpecification)) in
let occurrencesSpecs: Set(UML::Element) =
    from.fragment->select(e | e.ocIsKindOf(UML::OccurrenceSpecification)) in
let messages: Set(UML::Element) = from.message in
let invariants: Set(UML::Element) =
    from.fragment->select(e | e.ocIsKindOf(UML::StateInvariant)) in
let interactionUsages: Set(UML::Element) =
    from.fragment->select(e | e.ocIsKindOf(UML::InteractionUse)) in
let combinedFragments: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::CombinedFragment)) in
let continuations: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Continuation)) in
let elements: Set(UML::Element) =
    (((((((from.ownedElement - lifelines) - messageOccurrences)
    - executionOccurrences) - occurrencesSpecs) - messages) -
    combinedFragments) - invariants) -
    interactionUsages) - continuations) - from.ownedComment in

elements->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(lifelines->collect(e | LifelineMembership_Mapping.getMapped(e))->asSet())
->union(executionOccurrences
    ->collect(e | ExecutionSpecificationMembership_Mapping.getMapped(e))->asSet())
->union(messages->collect(e | MessageMembership_Mapping.getMapped(e))->asSet())
->union(combinedFragments
    ->collect(e | CombinedFragmentMembership_Mapping.getMapped(e))->asSet())
->union(invariants
    ->collect(e | StateInvariantMembership_Mapping.getMapped(e))->asSet())
->union(interactionUsages
    ->collect(e | InteractionUseMembership_Mapping.getMapped(e))->asSet())
->union(self.ocIsType(ElementMain_Mapping).ownedRelationship())
```

### 7.7.8.3.7 InteractionOperand\_Mapping

#### Description

A UML4SysML::InteractionOperand is mapped to a SysML v2 Interaction.



## Interaction

### Mapping Target

Interaction

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Interaction::ownedRelationship () : Relationship [0..\*]

```
let lifelines: Set(UML::Element) = from.lifeline in
let messageOccurrences: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::MessageOccurrenceSpecification)) in
let executionOccurrences: Set(UML::Element) =
    from.fragment->select(e | e.ocIsKindOf(UML::ExecutionSpecification)) in
let occurrencesSpecs: Set(UML::Element) =
    from.fragment->select(e | e.ocIsKindOf(UML::OccurrenceSpecification)) in
let messages: Set(UML::Element) = from.message in
let invariants: Set(UML::Element) =
    from.fragment->select(e | e.ocIsKindOf(UML::StateInvariant)) in
let interactionUsages: Set(UML::Element) =
    from.fragment->select(e | e.ocIsKindOf(UML::InteractionUse)) in
let combinedFragments: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::CombinedFragment)) in
let continuations: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Continuation)) in
let elements: Set(UML::Element) =
    (((((((from.ownedElement - lifelines) - messageOccurrences)
    - executionOccurrences) - occurrencesSpecs) - messages) -
    combinedFragments) - invariants) -
    interactionUsages) - continuations) - from.ownedComment in

elements->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(lifelines->collect(e | LifelineMembership_Mapping.getMapped(e))->asSet())
->union(executionOccurrences
    ->collect(e | ExecutionSpecificationMembership_Mapping.getMapped(e))->asSet())
->union(messages->collect(e | MessageMembership_Mapping.getMapped(e))->asSet())
->union(combinedFragments
    ->collect(e | CombinedFragmentMembership_Mapping.getMapped(e))->asSet())
->union(invariants
    ->collect(e | StateInvariantMembership_Mapping.getMapped(e))->asSet())
->union(interactionUsages
    ->collect(e | InteractionUseMembership_Mapping.getMapped(e))->asSet())
->union(self.ocIsType(ElementMain_Mapping).ownedRelationship())
```

#### 7.7.8.3.7 InteractionOperand\_Mapping

### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## General Mappings

NamedElementMain\_Mapping  
**GenericToInteraction\_Mapping**

## Mapping Source

InteractionOperand

## Mapping Target

Interaction

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Interaction::ownedRelationship () : Relationship [0..\*]

```
let executionOccurrences: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::ExecutionSpecification)) in
let occurrencesSpecs: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::OccurrenceSpecification)) in
let continuations: Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Continuation)) in
let elements: Set(UML::Element) =
    (((from.ownedElement - executionOccurrences) - occurrencesSpecs) -
    continuations) - from.ownedComment in
elements->collect(e | ElementOwningMembership_Mapping.getMapped(e)) ->asSet()
->union(self.ocAsType(ElementMain_Mapping).ownedRelationship())
->union(executionOccurrences
    ->collect(e | ExecutionSpecificationMembership_Mapping.getMapped(e)) ->asSet())
```

### 7.7.8.3.8 InteractionOperandMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

**GenericToFeatureMembership\_Mapping**

#### Mapping Source

InteractionOperand

## Description

A UML4SysML::InteractionOperand is mapped to a SysML v2 Interaction.

## General Mappings

NamedElementMain\_Mapping  
ToInteraction\_Init

## Mapping Source

InteractionOperand

## Mapping Target

Interaction

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Interaction::ownedRelationship () : Relationship [0..\*]

```
let executionOccurrences: Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::ExecutionSpecification)) in
let occurrencesSpecs: Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::OccurrenceSpecification)) in
let continuations: Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Continuation)) in
let elements: Set(UML::Element) =
  (((from.ownedElement - executionOccurrences) - occurrencesSpecs) -
  continuations) - from.ownedComment in
elements->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(self.ocAsType(ElementMain_Mapping).ownedRelationship())
->union(executionOccurrences
  ->collect(e | ExecutionSpecificationMembership_Mapping.getMapped(e))->asSet())
```

### 7.7.8.3.8 InteractionOperandMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]

```
self.memberFeature()
```

- FeatureMembership::memberFeature () : Feature [1]

```
ElementMain_Mapping.getMapped(from)
```

### 7.7.8.3.9 InteractionUse\_Mapping

#### Description

A UML4SysML::InteractionUse is mapped to a SysML v2 Step.

#### General Mappings

GenericToStep\_Mapping

Namespace\_Mapping

#### Mapping Source

InteractionUse

#### Mapping Target

Step

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

ToFeatureMembership\_Init  
Mapping

### Mapping Source

InteractionOperand

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]  
`self.memberFeature()`
- FeatureMembership::memberFeature () : Feature [1]  
`ElementMain_Mapping.getMapped(from)`

### 7.7.8.3.9 InteractionUse\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

A UML4SysML::InteractionUse is mapped to a SysML v2 Step.

### General Mappings

ToStep\_Init  
Namespace\_Mapping

### Mapping Source

InteractionUse

### Mapping Target

Step

### Owned Mappings

(none)

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Step::ownedRelationship () : Relationship [0..*]`

```
self.oclassType (ElementMain_Mapping).ownedRelationship () ->including (InteractionUseFeatureTyping_Mapping)
```

#### 7.7.8.3.10 InteractionUseMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

InteractionUse

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::memberFeature () : Feature [1]`

```
ElementMain_Mapping.getMapped (from)
```

- **FeatureMembership::ownedMemberFeature () : Feature [0..1]**

```
self.memberFeature ()
```

#### 7.7.8.3.11 InteractionUseFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

**Generic**ToFeatureTyping\_Mapping

##### Mapping Source

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Step::ownedRelationship () : Relationship [0..*]`

```
self.oclAsType (ElementMain_Mapping).ownedRelationship ()->including (InteractionUseFeatureTypin
```

### 7.7.8.3.10 InteractionUseMembership\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

InteractionUse

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`

```
self.memberFeature()
```

- `FeatureMembership::memberFeature () : Feature [1]`

```
ElementMain_Mapping.getMapped (from)
```

InteractionUse

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`ElementMain_Mapping.getMapped(from.refersTo)`

## 7.7.8.3.12 LifelineMembership\_Mapping

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

`GenericToFeatureMembership_Mapping`

### Mapping Source

Lifeline

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`



### 7.7.8.3.11 InteractionUseFeatureTyping\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

ToFeatureTyping\_Init  
Mapping

#### Mapping Source

InteractionUse

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`ElementMain_Mapping.getMapped(from.refersTo)`

### 7.7.8.3.12 LifelineMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

Lifeline

#### Mapping Target

```
self.memberFeature()
```

- FeatureMembership::memberFeature() : Feature [1]

```
ElementMain_Mapping.getMapped(from)
```

### 7.7.8.3.13 LifelinePartUsage\_Mapping

#### Description

A UML4SysML::Lifeline is mapped to a SysML v2 PartUsage.

#### General Mappings

GenericToPartUsage\_Mapping

NamedElementMain\_Mapping

#### Mapping Source

Lifeline

#### Mapping Target

PartUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PartUsage::ownedRelationship() : Relationship [0..\*]

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()->including(LifelineFeatureTyping_Map
```

### 7.7.8.3.14 LifelineFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

GenericToFeatureTyping\_Mapping

#### Mapping Source

Lifeline

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::memberFeature () : Feature [1]  
`ElementMain_Mapping.getMapped (from)`
- FeatureMembership::ownedMemberFeature () : Feature [0..1]  
`self.memberFeature ()`

#### 7.7.8.3.13 LifelinePartUsage\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

A UML4SysML::Lifeline is mapped to a SysML v2 PartUsage.

### General Mappings

ToPartUsage\_Init  
NamedElementMain\_Mapping

### Mapping Source

Lifeline

### Mapping Target

PartUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`ElementMain_Mapping.getMapped(from.represents.type)`

### 7.7.8.3.15 Message\_Mapping

#### Description

A `UML4SysML::Message` is mapped to a SysML v2 `ItemFlow`.

#### General Mappings

`GenericToItemFlow_Mapping`  
`NamedElementMain_Mapping`

#### Mapping Source

Message

#### Mapping Target

`ItemFlow`

#### Owned Mappings

(none)

### 7.7.8.3.16 MessageMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

`GenericToFeatureMembership_Mapping`

#### Mapping Source

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PartUsage::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType (ElementMain_Mapping).ownedRelationship () ->including (LifelineFeatureTyping_Map
```

#### 7.7.8.3.14 LifelineFeatureTyping\_Mapping

##### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

ToFeatureTyping\_Init  
Mapping

##### Mapping Source

Lifeline

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
ElementMain_Mapping.getMapped (from.represents.type)
```

#### 7.7.8.3.15 Message\_Mapping

##### [SYSML2 -417: Remove "Connection" from the names "FlowConnectionDefinition", "FlowConnectionUsage", and "SuccessionFlowConnectionUsage"](#)

##### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

A UML4SysML::Message is mapped to a SysML v2 ItemFlow.

##### General Mappings

Message

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`  
`self.memberFeature ()`
- `FeatureMembership::memberFeature () : Feature [1]`  
`ElementMain_Mapping.getMapped (from)`

### 7.7.8.3.17 StateInvariant\_Mapping

#### Description

A UML4SysML::StateInvariant is mapped to a SysML v2 Invariant.

#### General Mappings

`GenericToExpression_Mapping`  
`Namespace_Mapping`

#### Mapping Source

StateInvariant

#### Mapping Target

Invariant

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

ToItemFlow\_Init  
NamedElementMain\_Mapping

#### Mapping Source

Message

#### Mapping Target

Flow

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.8.3.16 MessageMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToFeatureMembership\_Init

#### Mapping Source

Message

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::memberFeature () : Feature [1]  
ElementMain\_Mapping.getMapped(from)
- FeatureMembership::ownedMemberFeature () : Feature [0..1]

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Invariant::ownedRelationship () : Relationship [0..*]`

```
self.oclAsType (ElementMain_Mapping).ownedRelationship()  
->including (StateInvariantFeatureTyping_Mapping.getMapped (from))
```

#### 7.7.8.3.18 StateInvariantMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

`GenericToFeatureMembership_Mapping`

##### Mapping Source

StateInvariant

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`

```
self.memberFeature()
```

- `FeatureMembership::memberFeature () : Feature [1]`

```
ElementMain_Mapping.getMapped (from)
```

#### 7.7.8.3.19 StateInvariantFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

`GenericToFeatureTyping_Mapping`



```
self.memberFeature()
```

### 7.7.8.3.17 StateInvariant\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

A UML4SysML::StateInvariant is mapped to a SysML v2 Invariant.

#### General Mappings

ToExpression\_Init  
Namespace\_Mapping

#### Mapping Source

StateInvariant

#### Mapping Target

Invariant

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Invariant::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()  
->including(StateInvariantFeatureTyping_Mapping.getMapped(from))
```

### 7.7.8.3.18 StateInvariantMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

## Mapping Source

StateInvariant

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`ElementMain_Mapping.getMapped(from.invariant)`

## 7.7.9 Packages

This chapter lists all mapping specifications of UML4SysML::Packages model elements.

### 7.7.9.1 Overview

Table 13. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Extension	not mapped; see next section
ExtensionEnd	not mapped; see next section
Image	not mapped; see next section
Model	Package
Package	Package
PackageMerge	not mapped; see next section
Profile	Package
ProfileApplication	not mapped; see next section
Stereotype	MetadataDefinition

The following table gives an overview of which SysML v2 elements the UML4SysML::Packages elements are transformed with which mapping class. The mapping details are in [7.7.9.3](#).

The justifications for the elements without mapping are given in [7.7.9.2](#).

StateInvariant

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::memberFeature () : Feature [1]`  
`ElementMain_Mapping.getMapped (from)`
- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`  
`self.memberFeature ()`

#### 7.7.8.3.19 StateInvariantFeatureTyping\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

StateInvariant

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

### 7.7.9.2 UML4SysML::Packages elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 14. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
Extension	The mapping of the extension relationship is performed in the context of Stereotype_Mapping.
ExtensionEnd	The mapping of the extension end property is performed in the context of Stereotype_Mapping.
Image	Mapping is not specified yet.
PackageMerge	The concept of the PackageMerge relationship is not supported by SysML v2.

### 7.7.9.3 Mapping Specifications

#### 7.7.9.3.1 ElementImport\_Mapping

##### Description

A UML4SysML::ElementImport is mapped to a SysMLv2 MembershipImport. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
package SysMLv1Package1 {
    import SysMLv1Package2::SysMLv1Block;
    import SysMLv1Package2::SysMLv1ValueType;
}
package SysMLv1Package2 {
    part def SysMLv1Block;
    attribute def SysMLv1ValueType;
}
```

##### General Mappings

GenericToMembershipImport\_Mapping  
NamedElementMain\_Mapping

##### Mapping Source

ElementImport

##### Mapping Target

MembershipImport

##### Owned Mappings

(none)

##### Applicable filters

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`ElementMain_Mapping.getMapped(from.invariant)`

## 7.7.9 Packages

### 7.7.9.1 Overview

**SYSML2 -329: Mapping overview tables are wrong**

**Table 12. List of all mappings**

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Extension	ConnectionDefinition
ExtensionEnd	AttributeUsage OccurrenceUsage Feature ReferenceUsage
Image	not mapped; see next section
Model	Package
Package	Package
PackageMerge	not mapped; see next section
Profile	Package
ProfileApplication	not mapped; see next section
Stereotype	MetadataDefinition

### 7.7.9.2 UML4SysML::Packages elements not mapped

**Table 13. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
Extension	The mapping of the extension relationship is performed in the context of Stereotype_Mapping.
ExtensionEnd	The mapping of the extension end property is performed in the context of Stereotype_Mapping.
Image	Mapping is not specified yet.
PackageMerge	The concept of the PackageMerge relationship is not supported by SysML v2.

### 7.7.9.3 Mapping Specifications

#### 7.7.9.3.1 ElementImport\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.oclIsKindOf(UML::ElementImport) then
    Helper.hasMainMapping(src.oclAsType(UML::ElementImport).importedElement)
else
    false
endif
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **MembershipImport::importedMemberName () : String [0..1]**  
`from.alias`
- **MembershipImport::visibility () : VisibilityKind [1]**  
`Helper.getKerMLVisibilityKind(from.visibility)`
- **MembershipImport::importedMembership () : Namespace [1]**  
`ElementOwningMembership_Mapping.getMapped(from.importedElement)`

### 7.7.9.3.2 Model\_Mapping

#### Description

SysMLv2 has no explicit model element for a model. The UML4SysML::Model element is mapped to a SysMLv2 Package. The property "viewpoint" is mapped to a metadata defined in the SysML v1 library. The expected SysML v2 textual notation of a UML4SysML::Model with URI and viewpoint is as follows. If URI or viewpoint are not set in the source model, the metadata is not generated.

```
package SysMLv1Model {
    @SysMLv1Library::PackageData {URI="https://omg.org";}
    @SysMLv1Library::ModelData {'viewpoint'="The viewpoint of the model element.";}
}
```

#### General Mappings

Package\_Mapping

#### Mapping Source

Model

#### Mapping Target

Package

#### Owned Mappings

(none)

A UML4SysML::ElementImport is mapped to a SysMLv2 MembershipImport. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
package SysMLv1Package1 {
    import SysMLv1Package2::SysMLv1Block;
    import SysMLv1Package2::SysMLv1ValueType;
}
package SysMLv1Package2 {
    part def SysMLv1Block;
    attribute def SysMLv1ValueType;
}
```

## General Mappings

ToMembershipImport\_Init  
NamedElementMain\_Mapping

### Mapping Source

ElementImport

### Mapping Target

MembershipImport

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.oclIsKindOf(UML::ElementImport) then
    Helper.hasMainMapping(src.oclAsType(UML::ElementImport).importedElement)
else
    false
endif
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MembershipImport::visibility () : VisibilityKind [1]  
Helper.getKerMLVisibilityKind(from.visibility)
- MembershipImport::importedMembership () : Namespace [1]  
ElementOwningMembership\_Mapping.getMapped(from.importedElement)
- MembershipImport::importedMemberName () : String [0..1]  
from.alias

#### 7.7.9.3.2 Model\_Mapping

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Package::ownedRelationship () : Relationship [0..\*]  

```
let relationships : Set(KerML::Relationship) =  
    self.oclAsType(Package_Mapping).ownedRelationship() in  
if from.viewpoint.oclIsUndefined() or from.viewpoint = '' then  
    relationships  
else  
    relationships  
->including (ModelViewpointMetadataMembership_Mapping.getMapped(from))  
endif
```

#### 7.7.9.3.3 ModelViewpointMetadataUsage\_Mapping

#### 7.7.9.3.4 ModelViewpointMetadataFeatureMembership\_Mapping

##### Description

The mapping class creates the feature membership relationship for the metadata feature to store the UML4SysML::Model::viewpoint property.

##### General Mappings

GenericToFeatureMembership\_Mapping

##### Mapping Source

Model

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]  

```
ModelViewpointMetadataReferenceUsage_Mapping.getMapped(from)
```



## Description

SysMLv2 has no explicit model element for a model. The UML4SysML::Model element is mapped to a SysMLv2 Package. The property "viewpoint" is mapped to a metadata defined in the SysML v1 library. The expected SysML v2 textual notation of a UML4SysML::Model with URI and viewpoint is as follows. If URI or viewpoint are not set in the source model, the metadata is not generated.

```
package SysMLv1Model {
  @SysMLv1Library::PackageData {URI="https://omg.org";}
  @SysMLv1Library::ModelData {'viewpoint'="The viewpoint of the model element.";}
}
```

## General Mappings

Package\_Mapping

### Mapping Source

Model

### Mapping Target

Package

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Package::ownedRelationship () : Relationship [0..\*]  

```
let relationships : Set(KerML::Relationship) =
  self.oclAsType(Package_Mapping).ownedRelationship() in
if from.viewpoint.oclIsUndefined() or from.viewpoint = '' then
  relationships
else
  relationships
  ->including (ModelViewpointMetadataMembership_Mapping.getMapped(from))
endif
```

#### 7.7.9.3.3 ModelViewpointMetadataUsage\_Mapping

#### 7.7.9.3.4 ModelViewpointMetadataFeatureMembership\_Mapping

### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

### 7.7.9.3.5 ModelViewpointMetadataReferenceUsage\_Mapping

#### Description

The mapping class creates the MetadataFeature for the mapping of the property UML4SysML::Model::viewpoint.

#### General Mappings

GenericToReferenceUsage\_Mapping

#### Mapping Source

Model

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set { ModelViewpointMetadataRedefinition_Mapping.getMapped (from) ,  
      ModelViewpointMetadataFeatureValue_Mapping.getMapped (from) }
```

### 7.7.9.3.6 ModelViewpointMetadataFeatureTyping\_Mapping

#### Description

The mapping class creates the FeatureTyping relationship for the AnnotatingFeature for the metadata to store the UML4SysML::Model::viewpoint property.

#### General Mappings

GenericToFeatureTyping\_Mapping

#### Mapping Source

Model

#### Mapping Target

FeatureTyping

#### Owned Mappings

The mapping class creates the feature membership relationship for the metadata feature to store the UML4SysML::Model::viewpoint property.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

Model

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]  
`ModelViewpointMetadataReferenceUsage_Mapping.getMapped (from)`

### 7.7.9.3.5 ModelViewpointMetadataReferenceUsage\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the MetadataFeature for the mapping of the property UML4SysML::Model::viewpoint.

### General Mappings

ToReferenceUsage\_Init  
Mapping

### Mapping Source

Model

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SysMLv2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ModelData')
```

### 7.7.9.3.7 ModelViewpointMetadataMembership\_Mapping

#### Description

The mapping class creates a membership relationship for the metadata feature value for the UML4SysML::Model::viewpoint property.

#### General Mappings

**Generic**ToOwningMembership\_Mapping

#### Mapping Source

Model

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`

```
ModelViewpointMetadataUsage_Mapping.getMapped(from)
```

### 7.7.9.3.8 ModelViewpointMetadataFeatureValue\_Mapping

#### Description

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ModelViewpointMetadataRedefinition_Mapping.getMapped(from),  
ModelViewpointMetadataFeatureValue_Mapping.getMapped(from)}
```

### 7.7.9.3.6 ModelViewpointMetadataFeatureTyping\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

## Description

The mapping class creates the FeatureTyping relationship for the AnnotatingFeature for the metadata to store the UML4SysML::Model::viewpoint property.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

Model

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
SysMLv2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ModelData')
```

### 7.7.9.3.7 ModelViewpointMetadataMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

The mapping class maps the value of the property UML4SysML::Model::viewpoint.

### General Mappings

GenericToFeatureValue\_Mapping

### Mapping Source

Model

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  
`ModelViewpointValue_Mapping.getMapped(from)`

### 7.7.9.3.9 ModelViewpointMetadataRedefinition\_Mapping

### Description

The mapping class creates the redefinition of the attribute for the metadata UML4SysML::Model::viewpoint.

### General Mappings

GenericToRedefinition\_Mapping

### Mapping Source

Model

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

## Description

The mapping class creates a membership relationship for the metadata feature value for the UML4SysML::Model::viewpoint property.

## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

Model

## Mapping Target

OwningMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ModelViewpointMetadataUsage_Mapping.getMapped(from)`

### 7.7.9.3.8 ModelViewpointMetadataFeatureValue\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

The mapping class maps the value of the property UML4SysML::Model::viewpoint.

## General Mappings

ToFeatureValue\_Init  
Mapping

## Mapping Source

Model

## Mapping Target

FeatureValue

## Owned Mappings

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
let m : SYSML2::Membership =
  SYSML2::AttributeUsage.allInstances()
->collect(dt | dt.owningRelationship)
->select(r | r.ocIsKindOf(SYSML2::Membership))
->any(m | m.memberName = 'viewpoint') in
if (m.ocIsUndefined()) then
  invalid
else
  m.memberElement
endif
```

### 7.7.9.3.10 ModelViewpointValue\_Mapping

#### Description

The mapping class maps the value expression of the property `UML4SysML::Model::viewpoint`.

#### General Mappings

`GenericToExpression_Mapping`

#### Mapping Source

Model

#### Mapping Target

LiteralString

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `LiteralString::value () : String [1]`

```
LiteralString_Factory.create(from.viewpoint)
```

### 7.7.9.3.11 Package\_Mapping

#### Description



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`ModelViewpointValue_Mapping.getMapped(from)`

### 7.7.9.3.9 ModelViewpointMetadataRedefinition\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates the redefinition of the attribute for the metadata `UML4SysML::Model::viewpoint`.

#### General Mappings

ToRedefinition\_Init  
Mapping

#### Mapping Source

Model

#### Mapping Target

Redefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  

```
let m : SYSML2::Membership =
  SYSML2::AttributeUsage.allInstances()
->collect(dt | dt.owningRelationship)
->select(r | r.ocIsKindOf(SYSML2::Membership))
->any(m | m.memberName = 'viewpoint') in
if (m.ocIsUndefined()) then
  invalid
```

A UML4SysML::Package is mapped to a SysML v2 Package. The property "URI" is mapped to a metadata if it has a value. The expected SysML v2 textual notation of a UML4SysML::Package is as follows:

```
package ThisIsAPackageWithURI {  
  metadata SysMLv1Library::PackageData {URI="https://omg.org";} }  
}
```

## General Mappings

Namespace\_Mapping

## Mapping Source

Package

## Mapping Target

Package

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Package::ownedRelationship () : Relationship [0..\*]

```
Helper.packageOwnedRelationship(from)
```

### 7.7.9.3.12 PackageImport\_Mapping

## Description

A UML4SysML::PackageImport is mapped to a SysML v2 NamespaceImport. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
import SysMLv1Package::*;
```

## General Mappings

GenericToNamespaceImport\_Mapping

ElementMain\_Mapping

## Mapping Source

PackageImport

```

else
    m.memberElement
endif

```

### 7.7.9.3.10 ModelViewpointValue\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

The mapping class maps the value expression of the property UML4SysML::Model::viewpoint.

##### **General Mappings**

ToExpression\_Init  
Mapping

##### **Mapping Source**

Model

##### **Mapping Target**

LiteralString

##### **Owned Mappings**

(none)

##### **Applicable filters**

(none)

##### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralString::value () : String [1]  
  
LiteralString\_Factory.create(from.viewpoint)

### 7.7.9.3.11 Package\_Mapping

##### **Description**

A UML4SysML::Package is mapped to a SysML v2 Package. The property "URI" is mapped to a metadata if it has a value. The expected SysML v2 textual notation of a UML4SysML::Package is as follows:

```

package ThisIsAPackageWithURI {
    metadata SysMLv1Library::PackageData {URI="https://omg.org";}
}

```

##### **General Mappings**

Namespace\_Mapping

## Mapping Target

NamespaceImport

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.oclIsKindOf(UML::PackageImport) then
    Helper.isInScope(src.oclAsType(UML::PackageImport).importedPackage)
else
    false
endif
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `NamespaceImport::visibility () : VisibilityKind [0..1]`  
`Helper.getKerMLVisibilityKind(from.visibility)`
- `NamespaceImport::importedNamespace () : Namespace [1]`  
`Namespace_Mapping.getMapped(from.importedPackage)`

### 7.7.9.3.13 PackageURIMetadataUsage\_Mapping

#### Description

The mapping class creates the annotating feature to annotate the generated Package element with metadata to store the UML4SysML::Package::URI property.

#### General Mappings

`GenericToMetadataUsage_Mapping`

#### Mapping Source

Package

#### Mapping Target

MetadataUsage

#### Owned Mappings

(none)

#### Applicable filters

### Mapping Source

Package

### Mapping Target

Package

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Package::ownedRelationship () : Relationship [0..\*]  
`Helper.packageOwnedRelationship (from)`

### 7.7.9.3.12 PackageImport\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

### Description

A UML4SysML::PackageImport is mapped to a SysML v2 NamespaceImport. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
import SysMLv1Package::*;
```

### General Mappings

ToNamespaceImport\_Init  
ElementMain\_Mapping

### Mapping Source

PackageImport

### Mapping Target

NamespaceImport

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { PackageURIFeatureTyping_Mapping.getMapped (from) ,  
PackageURIFeatureMembership_Mapping.getMapped (from) }
```
- MetadataUsage::declaredName () : String [0..1]  

```
'URI '
```

#### 7.7.9.3.14 PackageURIFeatureMembership\_Mapping

##### Description

The mapping class creates the feature membership relationship for the metadata feature to store the UML4SysML::Package::URI property.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

Package

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  

```
PackageURIMetadataReferenceUsage_Mapping.getMapped (from)
```

#### 7.7.9.3.15 PackageURIFeatureTyping\_Mapping

##### Description

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.oclIsKindOf(UML::PackageImport) then
    Helper.isInScope(src.oclAsType(UML::PackageImport).importedPackage)
else
    false
endif
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- NamespaceImport::importedNamespace () : Namespace [1]  
`Namespace_Mapping.getMapped(from.importedPackage)`
- NamespaceImport::visibility () : VisibilityKind [0..1]  
`Helper.getKerMLVisibilityKind(from.visibility)`

#### 7.7.9.3.13 PackageURIMetadataUsage\_Mapping

##### SYSML2\_-220: Replace Generic mapping classes by Initializers

### Description

The mapping class creates the annotating feature to annotate the generated Package element with metadata to store the UML4SysML::Package::URI property.

### General Mappings

ToMetadataUsage\_Init  
Mapping

### Mapping Source

Package

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

The mapping class creates the FeatureTyping relationship for the AnnotatingFeature for the metadata to store the UML4SysML::Package::URI property.

### General Mappings

GenericToFeatureTyping\_Mapping

### Mapping Source

Package

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
let m: SysMLv2::Membership = SysMLv2::AttributeDefinition.allInstances()
->collect(dt | dt.owningRelationship)
->select(r | r.ocIsKindOf(SysMLv2::Membership))
->any(m | m.memberName = 'PackageData' ) in

if (m.ocIsUndefined()) then
    invalid
else
    m.memberElement
endif
```

### 7.7.9.3.16 PackageURIMetadataReferenceUsage\_Mapping

#### Description

The mapping class creates the MetadataFeature for the mapping of the property UML4SysML::Package::URI.

### General Mappings

GenericToReferenceUsage\_Mapping

### Mapping Source

Package

### Mapping Target



```
Set{PackageURIFeatureTyping_Mapping.getMapped(from),
PackageURIFeatureMembership_Mapping.getMapped(from)}
```

- MetadataUsage::declaredName () : String [0..1]

'URI '

### 7.7.9.3.14 PackageURIFeatureMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

The mapping class creates the feature membership relationship for the metadata feature to store the UML4SysML::Package::URI property.

##### **General Mappings**

ToFeatureMembership\_Init  
Mapping

##### **Mapping Source**

Package

##### **Mapping Target**

FeatureMembership

##### **Owned Mappings**

(none)

##### **Applicable filters**

(none)

##### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
PackageURIMetadataReferenceUsage_Mapping.getMapped(from)
```

### 7.7.9.3.15 PackageURIFeatureTyping\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

The mapping class creates the FeatureTyping relationship for the AnnotatingFeature for the metadata to store the UML4SysML::Package::URI property.

##### **General Mappings**



[ToFeatureTyping\\_Init](#)  
Mapping

#### Mapping Source

Package

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
let m: SysMLv2::Membership = SysMLv2::AttributeDefinition.allInstances()
->collect(dt | dt.owningRelationship)
->select(r | r.ocIsKindOf(SysMLv2::Membership))
->any(m | m.memberName = 'PackageData' ) in

if (m.ocIsUndefined()) then
    invalid
else
    m.memberElement
endif
```

#### 7.7.9.3.16 PackageURIMetadataReferenceUsage\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

The mapping class creates the MetadataFeature for the mapping of the property UML4SysML::Package::URI.

#### General Mappings

[ToReferenceUsage\\_Init](#)  
Mapping

#### Mapping Source

Package

#### Mapping Target

[ReferenceUsage](#)

## ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set { PackageURIRedefinition_Mapping.getMapped (from) ,  
      PackageURIMetadataFeatureValue_Mapping.getMapped (from) }
```

### 7.7.9.3.17 PackageURIMetadataFeatureValue\_Mapping

#### Description

The mapping class maps the value of the property UML4SysML::Package::URI.

#### General Mappings

#### GenericToFeatureValue\_Mapping

#### Mapping Source

Package

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::featureWithValue () : Feature [1]  

```
packageURIMetadataReferenceUsage.to
```
- FeatureValue::value () : Expression [1]

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set { PackageURIRedefinition_Mapping.getMapped (from) ,  
PackageURIMetadataFeatureValue_Mapping.getMapped (from) }`

### 7.7.9.3.17 PackageURIMetadataFeatureValue\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

The mapping class maps the value of the property `UML4SysML::Package::URI`.

## General Mappings

`ToFeatureValue_Init`  
`Mapping`

## Mapping Source

`Package`

## Mapping Target

`FeatureValue`

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::featureWithValue () : Feature [1]`  
`packageURIMetadataReferenceUsage.to`
- `FeatureValue::value () : Expression [1]`

```
PackageURIValue_Mapping.getMapped(from)
```

### 7.7.9.3.18 PackageURIMetadataMembership\_Mapping

#### Description

The mapping class creates a membership relationship for the metadata feature value for the UML4SysML::Package::URI property.

#### General Mappings

GenericToOwningMembership\_Mapping

#### Mapping Source

Package

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

```
PackageURIMetadataUsage_Mapping.getMapped(from)
```

### 7.7.9.3.19 PackageURIRedefinition\_Mapping

#### Description

The mapping class creates the redefinition of the attribute for the metadata UML4SysML::Package::URI.

#### General Mappings

GenericToRedefinition\_Mapping

#### Mapping Source

Package

#### Mapping Target

Redefinition

```
PackageURIValue_Mapping.getMapped(from)
```

### 7.7.9.3.18 PackageURIMetadataMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates a membership relationship for the metadata feature value for the UML4SysML::Package::URI property.

#### General Mappings

ToOwningMembership\_Init  
Mapping

#### Mapping Source

Package

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

```
PackageURIMetadataUsage_Mapping.getMapped(from)
```

### 7.7.9.3.19 PackageURIRedefinition\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates the redefinition of the attribute for the metadata UML4SysML::Package::URI.

#### General Mappings

ToRedefinition\_Init  
Mapping

#### Mapping Source

Package

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
let m : SysMLv2::Membership =
  SysMLv2::AttributeUsage.allInstances()
  ->collect(dt | dt.owningRelationship)
  ->select(r | r.ocIsKindOf(SYSML2::Membership))
  ->any(m | m.memberName = 'URI') in
if (m.ocIsUndefined()) then
  invalid
else
  m.memberElement
endif
```

### 7.7.9.3.20 PackageURIValue\_Mapping

#### Description

The mapping class maps the value expression of the property `UML4SysML::Package::URI`.

#### General Mappings

**Generic**ToExpression\_Mapping

#### Mapping Source

Package

#### Mapping Target

LiteralString

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules



## Mapping Target

### Redefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
let m : SysMLv2::Membership =
  SysMLv2::AttributeUsage.allInstances()
->collect(dt | dt.owningRelationship)
->select(r | r.ocIsKindOf(SYSML2::Membership))
->any(m | m.memberName = 'URI') in
if (m.ocIsUndefined()) then
  invalid
else
  m.memberElement
endif
```

### 7.7.9.3.20 PackageURIValue\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

The mapping class maps the value expression of the property `UML4SysML::Package::URI`.

## General Mappings

ToExpression\_Init  
Mapping

## Mapping Source

Package

## Mapping Target

LiteralString

## Owned Mappings

(none)

## Applicable filters

(none)

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `LiteralString::value () : String [1]`

`from.URI`

### 7.7.9.3.21 Profile\_Mapping

#### Description

A `UML4SysML::Profile` is mapped to a SysML v2 Package.

#### General Mappings

`Package_Mapping`

#### Mapping Source

`Profile`

#### Mapping Target

`Package`

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Package::ownedRelationship () : Relationship [0..*]`

```
self.oclAsType (Package_Mapping) .ownedRelationship ()  
->including (ProfileMetadataMembership_Mapping.getMapped (from) )
```

### 7.7.9.3.22 ProfileMetadataMembership\_Mapping

#### Description

The mapping class creates a membership relationship for the metadata feature value for the `UML4SysML::Model::viewpoint` property.

#### General Mappings

`GenericToOwningMembership_Mapping`

#### Mapping Source

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `LiteralString::value () : String [1]`

`from.URI`

### 7.7.9.3.21 Profile\_Mapping

#### Description

A `UML4SysML::Profile` is mapped to a SysML v2 Package.

#### General Mappings

`Package_Mapping`

#### Mapping Source

`Profile`

#### Mapping Target

`Package`

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Package::ownedRelationship () : Relationship [0..*]`

```
self.oclAsType(Package_Mapping).ownedRelationship()  
->including(ProfileMetadataMembership_Mapping.getMapped(from))
```

### 7.7.9.3.22 ProfileMetadataMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

The mapping class creates a membership relationship for the metadata feature value for the `UML4SysML::Model::viewpoint` property.

#### General Mappings

Profile

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

`ProfileMetadataUsage_Mapping.getMapped(from)`

## 7.7.9.3.23 ProfileMetadataUsage\_Mapping

### Description

The mapping class creates the annotating feature to annotate the generated Package element with metadata to store the UML4SysML::Model::viewpoint property.

### General Mappings

GenericToMetadataUsage\_Mapping

### Mapping Source

Profile

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::declaredName () : String [0..1]

ToOwningMembership\_Init  
Mapping

#### Mapping Source

Profile

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ProfileMetadataUsage_Mapping.getMapped (from)`

### 7.7.9.3.23 ProfileMetadataUsage\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates the annotating feature to annotate the generated Package element with metadata to store the UML4SysML::Model::viewpoint property.

#### General Mappings

ToMetadataUsage\_Init  
Mapping

#### Mapping Source

Profile

#### Mapping Target

MetadataUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

'Profile'

#### 7.7.9.3.24 StereotypeMetadataDefinition\_Mapping

##### Description

A UML4SysML::Stereotype is mapped to a SysML v2 MetadataDefinition.

##### General Mappings

Class\_Mapping

##### Mapping Source

Stereotype

##### Mapping Target

MetadataDefinition

##### Owned Mappings

(none)

#### 7.7.9.3.25 StereotypeMetadataDefinitionMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ElementOwningMembership\_Mapping

##### Mapping Source

Stereotype

##### Mapping Target

OwningMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [0..1]

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::declaredName () : String [0..1]  
'Profile'

### 7.7.9.3.24 StereotypeMetadataDefinition\_Mapping

#### Description

A UML4SysML::Stereotype is mapped to a SysML v2 MetadataDefinition.

#### General Mappings

Class\_Mapping

#### Mapping Source

Stereotype

#### Mapping Target

MetadataDefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.9.3.25 StereotypeMetadataDefinitionMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ElementOwningMembership\_Mapping

#### Mapping Source

Stereotype

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

```
ElementMain_Mapping.getMapped(from)
```

### 7.7.9.3.26 StereotypeOccurrenceUsage\_Mapping

#### Description

The mapping class maps the usage of a stereotype to a SysML v2 OccurrenceUsage.

#### General Mappings

**Generic**ToOccurrenceUsage\_Mapping

#### Mapping Source

Stereotype

#### Mapping Target

OccurrenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OccurrenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set { StereotypeOccurrenceUsageFeatureTyping_Mapping.getMapped(from),  
StereotypeOccurrenceUsageMultiplicityMembership_Mapping.getMapped(from) }
```

### 7.7.9.3.27 StereotypeOccurrenceUsageFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**Generic**ToFeatureTyping\_Mapping

#### Mapping Source

Stereotype

#### Mapping Target

FeatureTyping



### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [0..1]`

```
ElementMain_Mapping.getMapped(from)
```

### 7.7.9.3.26 StereotypeOccurenceUsage\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class maps the usage of a stereotype to a SysML v2 OccurrenceUsage.

#### General Mappings

ToOccurrenceUsage\_Init  
Mapping

#### Mapping Source

Stereotype

#### Mapping Target

OccurrenceUsage

#### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OccurrenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{StereotypeOccurenceUsageFeatureTyping_Mapping.getMapped(from),  
StereotypeOccurenceUsageMultiplicityMembership_Mapping.getMapped(from)}
```

### 7.7.9.3.27 StereotypeOccurenceUsageFeatureTyping\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

`StereotypeOccurenceDefinition_Mapping.getMapped(from)`

### 7.7.9.3.28 StereotypeOccurenceUsageMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

`GenericToMembership_Mapping`

#### Mapping Source

Stereotype

#### Mapping Target

Membership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`

`StereotypeOccurenceUsage_Mapping.getMapped(from)`

### 7.7.9.3.29 StereotypeOccurenceUsageMultiplicityMembership\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

Stereotype

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`StereotypeOccurrenceDefinition_Mapping.getMapped(from)`

### 7.7.9.3.28 StereotypeOccurrenceUsageMembership\_Mapping

[SYSML2 -220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

Stereotype

### Mapping Target

Membership

### Owned Mappings

(none)

Creates a membership relationship for *memberElement()*.

### General Mappings

**Generic**ToMembership\_Mapping

### Mapping Source

Stereotype

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::ownedMemberElement () : Element [0..1]  
`StereotypeOccurenceUsageMultiplicityRange_Mapping.getMapped(from)`
- **Membership::memberElement () : Element [1]**  
`self.ownedMemberElement ()`

### 7.7.9.3.30 StereotypeOccurenceUsageMultiplicityRange\_Mapping

#### Description

The mapping class creates the multiplicity range element for the UML4SysML::Stereotype mapping.

### General Mappings

**Generic**ToFeature\_Mapping

### Mapping Source

Stereotype

### Mapping Target

MultiplicityRange

### Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`  
`StereotypeOccurenceUsage_Mapping.getMapped(from)`

### 7.7.9.3.29 StereotypeOccurenceUsageMultiplicityMembership\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToMembership\_Init  
Mapping

## Mapping Source

Stereotype

## Mapping Target

Membership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::memberElement () : Element [1]`  
`self.ownedMemberElement ()`
- `Membership::ownedMemberElement () : Element [0..1]`  
`StereotypeOccurenceUsageMultiplicityRange_Mapping.getMapped(from)`

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MultiplicityRange::ownedRelationship () : Relationship [0..\*]

```
Set { StereotypeOccurenceUsageMultiplicityRangeMembership_Mapping.getMapped (from) }
```

#### 7.7.9.3.31 StereotypeOccurenceUsageMultiplicityRangeInfinity\_Mapping

##### Description

The mapping class creates the literal infinity element for the multiplicity range element for the UML4SysML::Stereotype mapping.

##### General Mappings

**Generic**ToExpression\_Mapping

##### Mapping Source

Stereotype

##### Mapping Target

LiteralInfinity

##### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralInfinity::ownedRelationship () : Relationship [0..\*]

```
Set { StereotypeOccurenceUsageInfinityReturnParameterMembership_Mapping.getMapped (from) }
```

#### 7.7.9.3.32 StereotypeOccurenceUsageInfinityReturnParameter\_Mapping

##### Description

The mapping class creates the return parameter relationship for the literal infinity element for the multiplicity range element for the UML4SysML::Stereotype mapping.

### 7.7.9.3.30 StereotypeOccurenceUsageMultiplicityRange\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

The mapping class creates the multiplicity range element for the UML4SysML::Stereotype mapping.

#### General Mappings

ToFeature\_[Init](#)  
Mapping

#### Mapping Source

Stereotype

#### Mapping Target

MultiplicityRange

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MultiplicityRange::ownedRelationship () : Relationship [0..\*]  
`Set{StereotypeOccurenceUsageMultiplicityRangeMembership_Mapping.getMapped(from) }`

### 7.7.9.3.31 StereotypeOccurenceUsageMultiplicityRangeInfinity\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

The mapping class creates the literal infinity element for the multiplicity range element for the UML4SysML::Stereotype mapping.

#### General Mappings

ToExpression\_[Init](#)  
Mapping

#### Mapping Source

Stereotype

#### Mapping Target

## General Mappings

**Generic**ToFeature\_Mapping

## Mapping Source

Stereotype

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::direction () : FeatureDirectionKind [0..1]

SysMLv2::FeatureDirectionKind::out

### 7.7.9.3.33 StereotypeOccurenceUsagelInfinityReturnParameterMembership\_Mapping

## Description

## General Mappings

**Generic**ToReturnParameterMembership\_Mapping

## Mapping Source

Stereotype

## Mapping Target

ReturnParameterMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules



LiteralInfinity

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralInfinity::ownedRelationship () : Relationship [0..\*]  
`Set{StereotypeOccurrenceUsageInfinityReturnParameterMembership_Mapping.getMapped(from) }`

### 7.7.9.3.32 StereotypeOccurrenceUsageInfinityReturnParameter\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the return parameter relationship for the literal infinity element for the multiplicity range element for the UML4SysML::Stereotype mapping.

### General Mappings

ToFeature\_Init  
Mapping

### Mapping Source

Stereotype

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::direction () : FeatureDirectionKind [0..1]  
`SysMLv2::FeatureDirectionKind::out`

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReturnParameterMembership::ownedMemberParameter () : Feature [0..1]`  
`StereotypeOccurenceUsageInfinityReturnParameter_Mapping.getMapped(from)`
- `ReturnParameterMembership::ownedRelatedElement () : Element [0..*]`  

```

let member: KerML::Element = self.ownedMemberParameter() in
if member.oclIsUndefined() then
  Set{}
else
  Set{self.ownedMemberParameter()}
endif

```
- `ReturnParameterMembership::memberParameter () : Feature [1]`  
`self.ownedMemberParameter()`

### 7.7.9.3.34 StereotypeOccurenceUsageMultiplicityRangeMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToMembership\_Mapping

#### Mapping Source

Stereotype

#### Mapping Target

Membership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Membership::ownedMemberElement () : Element [0..1]`  
`StereotypeOccurenceUsageMultiplicityRangeInfinity_Mapping.getMapped(from)`
- `Membership::memberElement () : Element [1]`

### 7.7.9.3.33 StereotypeOccurenceUsageInfinityReturnParameterMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

#### General Mappings

ToReturnParameterMembership\_Init  
Mapping

#### Mapping Source

Stereotype

#### Mapping Target

ReturnParameterMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReturnParameterMembership::ownedMemberParameter () : Feature [0..1]  
`StereotypeOccurenceUsageInfinityReturnParameter_Mapping.getMapped(from)`
- ReturnParameterMembership::ownedRelatedElement () : Element [0..\*]  

```
let member: KerML::Element = self.ownedMemberParameter() in
if member.ocIsUndefined() then
  Set{}
else
  Set{self.ownedMemberParameter()}
endif
```
- ReturnParameterMembership::memberParameter () : Feature [1]  
`self.ownedMemberParameter()`

### 7.7.9.3.34 StereotypeOccurenceUsageMultiplicityRangeMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a membership relationship for *memberElement()*.

```
self.ownedMemberElement()
```

## 7.7.10 SimpleClassifiers

This chapter lists all mapping specifications of UML4SysML::SimpleClassifiers model elements.

### 7.7.10.1 Overview

**Table 15.** List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
DataType	AttributeDefinition
Enumeration	EnumerationDefinition
EnumerationLiteral	EnumerationUsage
Interface	PortDefinition
InterfaceRealization	SatisfyRequirementUsage AllocationDefinition
PrimitiveType	AttributeDefinition
Reception	ItemUsage
Signal	ItemDefinition

The following table gives an overview of which SysML v2 elements the UML4SysML::SimpleClassifiers elements are transformed with which mapping class. The mapping details are in [7.7.10.2](#).

### 7.7.10.2 Mapping Specifications

#### 7.7.10.2.1 Attribute\_Mapping

##### Description

An UML4SysML::Property is mapped to a SysMLv2 AttributeUsage.

##### General Mappings

PropertyCommon\_Mapping  
NamedElementMain\_Mapping

##### Mapping Source

Property

##### Mapping Target

AttributeUsage

##### Owned Mappings

(none)

##### Applicable filters

## General Mappings

ToMembership\_Init  
Mapping

## Mapping Source

Stereotype

## Mapping Target

Membership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::ownedMemberElement () : Element [0..1]  
`StereotypeOccurenceUsageMultiplicityRangeInfinity_Mapping.getMapped (from)`
- Membership::memberElement () : Element [1]  
`self.ownedMemberElement ()`

## 7.7.10 SimpleClassifiers

### 7.7.10.1 Overview

[SYSML2\\_-329: Mapping overview tables are wrong](#)

Table 14. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
DataType	AttributeDefinition
Enumeration	EnumerationDefinition
EnumerationLiteral	EnumerationUsage ConnectionUsage
Interface	PortDefinition
InterfaceRealization	Dependency
PrimitiveType	AttributeDefinition
Reception	ItemUsage
Signal	ItemDefinition

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.ocIsKindOf(UML::Property) and not
    Helper.hasStereotypeApplied(src.owner,
        'SysML::ConstraintBlocks::ConstraintBlock') then
    let p: UML::Property = src.ocAsType(UML::Property) in
    if p.type.ocIsUndefined() then
        false
    else
        p.type.ocIsKindOf(UML::DataType) and
        (p.association.ocIsUndefined() or p.association.ownedEnd->excludes(p))
    endif
else
    false
endif
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

#### 7.7.10.2.2 AttributeRedefined\_Mapping

##### Description

An UML4SysML::SimpleClassifiers::Property is mapped to a SysML v2 AttributeUsage.

##### General Mappings

PropertyCommon\_Mapping

##### Mapping Source

Property

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
let typing: KerML::FeatureTyping =
    AssociationToFeatureTyping_Mapping.getMapped(from) in
```

## 7.7.10.2 Mapping Specifications

### 7.7.10.2.1 Attribute\_Mapping

#### Description

An UML4SysML::Property is mapped to a SysMLv2 AttributeUsage.

#### General Mappings

PropertyCommon\_Mapping  
NamedElementMain\_Mapping

#### Mapping Source

Property

#### Mapping Target

AttributeUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.ocIsKindOf(UML::Property) and not
    Helper.hasStereotypeApplied(src.owner,
        'SysML::ConstraintBlocks::ConstraintBlock') then
    let p: UML::Property = src.ocAsType(UML::Property) in
    if p.type.ocIsUndefined() then
        false
    else
        p.type.ocIsKindOf(UML::DataType) and
        (p.association.ocIsUndefined() or p.association.ownedEnd->excludes(p))
    endif
else
    false
endif
```

#### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.10.2.2 AttributeRedefined\_Mapping

#### Description

An UML4SysML::SimpleClassifiers::Property is mapped to a SysML v2 AttributeUsage.

#### General Mappings

PropertyCommon\_Mapping

#### Mapping Source

```

let subsetting: Set(KerML::Subsetting) =
  from.subsettedProperty
  ->collect(p | PropertySubsetting_Mapping.getMapped(from, p))->asSet() in
let subsettingMultiplicityTyping: Set(KerML::Relationship) =
  subsetting
  ->union(Set{AttributeRedefinedRedefinition_Mapping.getMapped(from)}->union(
    if typing.ocIsUndefined() then
      Set{MultiplicityMembership_Mapping.getMapped(from)}
    else
      Set{MultiplicityMembership_Mapping.getMapped(from), typing}
    endif)->asSet() in
if from.defaultValue.ocIsUndefined() then
  subsettingMultiplicityTyping
else
  subsettingMultiplicityTyping
  ->including(PropertyDefaultValue_Mapping.getMapped(from))
endif

```

### 7.7.10.2.3 AttributeRedefinedRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

**Generic**ToRedefinition\_Mapping

#### Mapping Source

Property

#### Mapping Target

Redefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]

```
from.redefinedProperty.get(0)
```

### 7.7.10.2.4 AttributeRedefinedMembership\_Mapping

#### Description



Property

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
let typing: KerML::FeatureTyping =
  AssociationToFeatureTyping_Mapping.getMapped(from) in
let subsetting: Set(KerML::Subsetting) =
  from.subsettedProperty
  ->collect(p | PropertySubsetting_Mapping.getMapped(from, p))->asSet() in
let subsettingMultiplicityTyping: Set(KerML::Relationship) =
  subsetting
  ->union(Set{AttributeRedefinedRedefinition_Mapping.getMapped(from)}->union(
    if typing.ocIsUndefined() then
      Set{MultiplicityMembership_Mapping.getMapped(from)}
    else
      Set{MultiplicityMembership_Mapping.getMapped(from), typing}
    endif)->asSet() in
if from.defaultValue.ocIsUndefined() then
  subsettingMultiplicityTyping
else
  subsettingMultiplicityTyping
  ->including(PropertyDefaultValue_Mapping.getMapped(from))
endif
```

#### 7.7.10.2.3 AttributeRedefinedRedefinition\_Mapping

##### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

##### General Mappings

ToRedefinition\_Init  
Mapping

##### Mapping Source

Property

##### Mapping Target

Creates a membership relationship for *memberElement()*.

### General Mappings

ElementFeatureMembership\_Mapping

### Mapping Source

Element

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.ocIsKindOf(UML::Property)
and (src.ocAsType(UML::Property).redefinedElement->size() > 0)
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]  
`AttributeRedefined_Mapping.getMapped(from)`

## 7.7.10.2.5 AttributeRedefinedFeatureTyping\_Mapping

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

StructuralFeatureToFeatureTyping\_Mapping

### Mapping Source

StructuralFeature

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  
`from.redefinedProperty.get (0)`

#### 7.7.10.2.4 AttributeRedefinedMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ElementFeatureMembership\_Mapping

##### Mapping Source

Element

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.ocIsKindOf (UML::Property)
and (src.ocAsType (UML::Property).redefinedElement->size () > 0)
```

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`  
`AttributeRedefined_Mapping.getMapped (from)`

### 7.7.10.2.6 BehavioredClassifier\_Mapping

#### Description

The abstract mapping class maps the abstract metaclass UML4SysML::BehavioredClassifiers to a SysMLv2 Classifier. The mapping class is used by concrete mapping classes, for example, Block\_Mapping.

#### General Mappings

Classifier\_Mapping

#### Mapping Source

BehavioredClassifier

#### Mapping Target

Classifier

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Classifier::ownedRelationship () : Relationship [0..\*]

```
let toElementFMS: Set(UML::Element) =
    from.ownedElement->select(e | (e.ocIsKindOf(UML::Property) and
        (e.ocIsType(UML::Property).redefinedProperty->size() = 0)) or
        e.ocIsKindOf(UML::Operation) or e.ocIsKindOf(UML::Connector)) in
let redefinedAttributes: Set(UML::Element) =
    from.ownedElement->select(e | from.ocIsKindOf(UML::DataType) and
        (e.ocIsType(UML::Property).redefinedProperty->size() > 0)) in
let generalizations : Set(UML::Generalization) =
    from.ownedElement
    ->select(e | e.ocIsKindOf(UML::Generalization)) in
let constraints : Set(UML::Constraint) =
    UML::Constraint.allInstances()
    ->select( c | c.constrainedElement->includes(from)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - redefinedAttributes) -
        generalizations) - from.ownedComment in
let relationships: Sequence(KerML::Relationship) =
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e)) ->asSet()
->union(toElementFMS->collect(e |
    ElementFeatureMembership_Mapping.getMapped(e)) ->asSet())
->union(constraints->collect(e |
    ConstrainedElementFeatureMembership_Mapping.getMapped(e)) ->asSet())
```

#### 7.7.10.2.5 AttributeRedefinedFeatureTyping\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

StructuralFeatureToFeatureTyping\_Mapping

##### Mapping Source

StructuralFeature

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.10.2.6 BehavioeredClassifier\_Mapping

##### Description

The abstract mapping class maps the abstract metaclass UML4SysML::BehavioeredClassifiers to a SysMLv2 Classifier. The mapping class is used by concrete mapping classes, for example, Block\_Mapping.

##### General Mappings

Classifier\_Mapping

##### Mapping Source

BehavioeredClassifier

##### Mapping Target

Classifier

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

```

->union(redefinedAttributes->collect(e |
    AttributeRedefinedMembership_Mapping.getMapped(e))->asSet())
->union(generalizations->collect(e |
    Generalization_Mapping.getMapped(e))->asSet())
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship()) in
if from.classifierBehavior.oclIsUndefined() then
    relationships
else
    relationships
->including(BehavioredClassifierFeatureMembership_Mapping.getMapped(from))
endif

```

### 7.7.10.2.7 BehavioredClassifierFeatureMembership\_Mapping

#### Description

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

BehavioredClassifier

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]  
 BehavioredClassifierActionUsage\_Mapping.getMapped(from)

### 7.7.10.2.8 BehavioredClassifierFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**Generic**ToFeatureTyping\_Mapping

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Classifier::ownedRelationship () : Relationship [0..\*]

```
let toElementFMS: Set(UML::Element) =
    from.ownedElement->select(e | (e.ocIsKindOf(UML::Property) and
        (e.ocIsType(UML::Property).redefinedProperty->size() = 0)) or
        e.ocIsKindOf(UML::Operation) or e.ocIsKindOf(UML::Connector)) in
let redefinedAttributes: Set(UML::Element) =
    from.ownedElement->select(e | from.ocIsKindOf(UML::DataType) and
        (e.ocIsType(UML::Property).redefinedProperty->size() > 0)) in
let generalizations : Set(UML::Generalization) =
    from.ownedElement
    ->select(e | e.ocIsKindOf(UML::Generalization)) in
let constraints : Set(UML::Constraint) =
    UML::Constraint.allInstances()
    ->select( c | c.constrainedElement->includes(from)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - redefinedAttributes) -
        generalizations) - from.ownedComment in
let relationships: Sequence(KerML::Relationship) =
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(toElementFMS->collect(e |
    ElementFeatureMembership_Mapping.getMapped(e))->asSet())
->union(constraints->collect(e |
    ConstrainedElementFeatureMembership_Mapping.getMapped(e))->asSet())
->union(redefinedAttributes->collect(e |
    AttributeRedefinedMembership_Mapping.getMapped(e))->asSet())
->union(generalizations->collect(e |
    Generalization_Mapping.getMapped(e))->asSet())
->union(self.ocIsType(ElementMain_Mapping).ownedRelationship()) in
if from.classifierBehavior.ocIsUndefined() then
    relationships
else
    relationships
    ->including(BehavedClassifierFeatureMembership_Mapping.getMapped(from))
endif
```

#### 7.7.10.2.7 BehavedClassifierFeatureMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

BehavedClassifier

##### Mapping Target

FeatureMembership

### Mapping Source

BehavioredClassifier

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

from

## 7.7.10.2.9 BehavioredClassifierActionUsage\_Mapping

### Description

The BehavioredClassifierToPerformActionUsage\_Mapping class creates a PerformActionUsage element to call the transformed SysML v1 classifier behavior.

### General Mappings

GenericToActionUsage\_Mapping

### Mapping Source

BehavioredClassifier

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules



## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`  
`BehavioredClassifierActionUsage_Mapping.getMapped(from)`

### 7.7.10.2.8 BehavioredClassifierFeatureTyping\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

BehavioredClassifier

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`from`

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionUsage::declaredName () : String [0..1]`  
`'classifierBehavior'`
- `ActionUsage::ownedRelationship () : Relationship [0..*]`  
`Set{BehavioredClassifierFeatureTyping_Mapping.getMapped(from) }`

#### 7.7.10.2.10 DataType\_Mapping

##### Description

A `UML4SysML::SimpleClassifiers::DataType` is mapped to a SysML v2 `AttributeDefinition`. The mapping also cover the transformation of `UML4SysML::PrimitiveType` elements.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {
    attribute sysMLv1Property : ScalarValues::Integer;
}
```

##### General Mappings

Classifier\_Mapping

##### Mapping Source

DataType

##### Mapping Target

AttributeDefinition

##### Owned Mappings

(none)

#### 7.7.10.2.11 Enumeration\_Mapping

##### Description

A `UML4SysML::Enumeration` is mapped to a SysML v2 `EnumerationDefinition`.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
enum def SysMLv1Enumeration {
    enum sysMLv1Literal1;
    enum sysMLv1Literal2;
}
```

#### 7.7.10.2.9 BehavioredClassifierActionUsage\_Mapping

##### SysML2\_-220: Replace Generic mapping classes by Initializers

#### Description

The BehavioredClassifierToPerformActionUsage\_Mapping class creates a PerformActionUsage element to call the transformed SysML v1 classifier behavior.

#### General Mappings

ToActionUsage\_Init  
Mapping

#### Mapping Source

BehavioredClassifier

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::declaredName () : String [0..1]  
`'classifierBehavior'`
- ActionUsage::ownedRelationship () : Relationship [0..\*]  
`Set{BehavioredClassifierFeatureTyping_Mapping.getMapped(from) }`

#### 7.7.10.2.10 DataType\_Mapping

#### Description

A UML4SysML::SimpleClassifiers::DataType is mapped to a SysML v2 AttributeDefinition. The mapping also cover the transformation of UML4SysML::PrimitiveType elements.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block {  
    attribute sysMLv1Property : ScalarValues::Integer;  
}
```

## General Mappings

DataType\_Mapping

## Mapping Source

Enumeration

## Mapping Target

EnumerationDefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EnumerationDefinition::isVariation () : Boolean [1]

true

- EnumerationDefinition::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(Classifier_Mapping).ownedRelationship()  
->union(from.ownedLiteral->collect(e | EnumerationVariantMembership_Mapping.getMapped(e)) ->as
```

### 7.7.10.2.12 EnumerationLiteral\_Mapping

#### Description

A UML4SysML::EnumerationLiteral is mapped to a SysML v2 EnumerationUsage.

## General Mappings

GenericToFeature\_Mapping

InstanceSpecification\_Mapping

## Mapping Source

EnumerationLiteral

## Mapping Target

EnumerationUsage

## Owned Mappings

## General Mappings

Classifier\_Mapping

## Mapping Source

DataType

## Mapping Target

AttributeDefinition

## Owned Mappings

(none)

## Applicable filters

(none)

### 7.7.10.2.11 Enumeration\_Mapping

#### Description

A UML4SysML::Enumeration is mapped to a SysML v2 EnumerationDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
enum def SysMLv1Enumeration {  
    enum sysMLv1Literal1;  
    enum sysMLv1Literal2;  
}
```

## General Mappings

DataType\_Mapping

## Mapping Source

Enumeration

## Mapping Target

EnumerationDefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

(none)

#### 7.7.10.2.13 EnumerationVariantMembership\_Mapping

##### Description

The EnumerationVariantMembership\_Mapping class creates the variant membership relationship between the enumeration definition and a enumeration usage.

##### General Mappings

**Generic** ToOwningMembership\_Mapping

##### Mapping Source

EnumerationLiteral

##### Mapping Target

VariantMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- VariantMembership::ownedMemberElement () : Element [1]  
from

#### 7.7.10.2.14 Interface\_Mapping

##### Description

A UML4SysML::Interface is mapped to a SysMLv2 PortDefinition. The mapping also includes the generation of an appropriate ConjugatedPortDefinition. That mappings is performed by the mapping classes InterfaceConjugatedPortDefinitionMembership\_Mapping, InterfacePortConjugation\_Mapping, and InterfaceConjugatedPortDefinition\_Mapping.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
port def SysMLv1Interface {  
    attribute sysMLv1Property;  
}
```

##### General Mappings

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EnumerationDefinition::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(Classifier_Mapping).ownedRelationship()  
->union(from.ownedLiteral->collect(e | EnumerationVariantMembership_Mapping.getMapped(e)) ->as
```

- EnumerationDefinition::isVariation () : Boolean [1]

```
true
```

#### 7.7.10.2.12 EnumerationLiteral\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

A UML4SysML::EnumerationLiteral is mapped to a SysML v2 EnumerationUsage.

##### General Mappings

ToFeature\_Init  
InstanceSpecification\_Mapping

##### Mapping Source

EnumerationLiteral

##### Mapping Target

EnumerationUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.10.2.13 EnumerationVariantMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The EnumerationVariantMembership\_Mapping class creates the variant membership relationship between the enumeration definition and a enumeration usage.

##### General Mappings

ToOwningMembership\_Init  
Mapping

##### Mapping Source

**GenericToPortDefinition\_Mapping**  
Classifier\_Mapping

### Mapping Source

Interface

### Mapping Target

PortDefinition

### Owned Mappings

- conjugatedPortDefinitionMembership : InterfaceConjugatedPortDefinitionMembership\_Mapping

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PortDefinition::ownedRelationship () : Relationship [0..\*]  

```
self.oclAsType(Classifier_Mapping).ownedRelationship()  
->including(conjugatedPortDefinitionMembership)
```

## 7.7.10.2.15 InterfaceConjugatedPortDefinition\_Mapping

### Description

As part of the mapping from a UML4SysML::Interface to a SysMLv2 PortDefinition, this mapping class is used to create the appropriate ConjugatedPortDefinition.

### General Mappings

**GenericToPortDefinition\_Mapping**

### Mapping Source

Interface

### Mapping Target

ConjugatedPortDefinition

### Owned Mappings

(none)

### Applicable filters

(none)



EnumerationLiteral

### Mapping Target

VariantMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- VariantMembership::ownedMemberElement () : Element [1]  
from

#### 7.7.10.2.14 Interface\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

A UML4SysML::Interface is mapped to a SysMLv2 PortDefinition. The mapping also includes the generation of an appropriate ConjugatedPortDefinition. That mappings is performed by the mapping classes InterfaceConjugatedPortDefinitionMembership\_Mapping, InterfacePortConjugation\_Mapping, and InterfaceConjugatedPortDefinition\_Mapping.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
port def SysMLv1Interface {  
    attribute sysMLv1Property;  
}
```

##### General Mappings

ToPortDefinition\_Init  
Classifier\_Mapping

##### Mapping Source

Interface

##### Mapping Target

PortDefinition

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConjugatedPortDefinition::declaredName () : String [0..1]`  
`'~'+from.name`
- `ConjugatedPortDefinition::ownedRelationship () : Relationship [0..*]`  
`Set { InterfacePortConjugation_Mapping.getMapped (from) }`

### 7.7.10.2.16 InterfaceConjugatedPortDefinitionMembership\_Mapping

#### Description

As part of the mapping from a UML4SysML::Interface to a SysML v2 PortDefinition, this mapping class is used to create the membership relationship for the ConjugatedPortDefinition.

#### General Mappings

**Generic**ToOwningMembership\_Mapping

#### Mapping Source

Interface

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`InterfaceConjugatedPortDefinition_Mapping.getMapped (from)`

### 7.7.10.2.17 InterfacePortConjugation\_Mapping

#### Description

As part of the mapping from a UML4SysML::Interface to a SysML v2 PortDefinition, this mapping class is used to create the appropriate PortConjugation relationship.

#### General Mappings

## Owned Mappings

- conjugatedPortDefinitionMembership : InterfaceConjugatedPortDefinitionMembership\_Mapping

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PortDefinition::ownedRelationship () : Relationship [0..\*]  

```
self.oclAsType(Classifier_Mapping).ownedRelationship()  
->including(conjugatedPortDefinitionMembership)
```

### 7.7.10.2.15 InterfaceConjugatedPortDefinition\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

As part of the mapping from a UML4SysML::Interface to a SysMLv2 PortDefinition, this mapping class is used to create the appropriate ConjugatedPortDefinition.

## General Mappings

ToPortDefinition\_Init  
Mapping

## Mapping Source

Interface

## Mapping Target

ConjugatedPortDefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConjugatedPortDefinition::declaredName () : String [0..1]  

```
'~'+from.name
```



- ConjugatedPortDefinition::ownedRelationship () : Relationship [0..\*]

```
Set{InterfacePortConjugation_Mapping.getMapped(from) }
```

#### 7.7.10.2.16 InterfaceConjugatedPortDefinitionMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

As part of the mapping from a UML4SysML::Interface to a SysML v2 PortDefinition, this mapping class is used to create the membership relationship for the ConjugatedPortDefinition.

##### General Mappings

ToOwningMembership\_Init  
Mapping

##### Mapping Source

Interface

##### Mapping Target

OwningMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

```
InterfaceConjugatedPortDefinition_Mapping.getMapped(from)
```

#### 7.7.10.2.17 InterfacePortConjugation\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

As part of the mapping from a UML4SysML::Interface to a SysML v2 PortDefinition, this mapping class is used to create the appropriate PortConjugation relationship.

##### General Mappings

ToRelationship\_Init  
Mapping

## GenericToRelationship\_Mapping

### Mapping Source

Interface

### Mapping Target

PortConjugation

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PortConjugation::conjugatedType () : Type [1]`  

```
SysMLv2::ConjugatedPortDefinition.allInstances()  
->collect(cpd | cpd.owningRelationship)  
->select(r | r.ocIsKindOf(SysMLv2::Membership))  
->any(m | m.memberName = from.name)
```
- `PortConjugation::originalPortDefinition () : PortDefinition [1]`  
`from`

## 7.7.10.2.18 InterfaceRealization\_Mapping

### Description

A UML4SysML::InterfaceRealization is mapped to a SysMLv2 Subclassification relationship.

### General Mappings

## GenericToSpecialization\_Mapping

### Mapping Source

InterfaceRealization

### Mapping Target

Subclassification

### Owned Mappings

(none)

## Mapping Source

Interface

## Mapping Target

PortConjugation

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PortConjugation::originalPortDefinition () : PortDefinition [1]`  
`from`
- `PortConjugation::conjugatedType () : Type [1]`  

```
SysMLv2::ConjugatedPortDefinition.allInstances()  
->collect(cpd | cpd.owningRelationship)  
->select(r | r.ocIsKindOf(SysMLv2::Membership))  
->any(m | m.memberName = from.name)
```

### 7.7.10.2.18 InterfaceRealization\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

## Description

A UML4SysML::InterfaceRealization is mapped to a SysMLv2 Subclassification relationship.

## General Mappings

ToSpecialization\_Init  
Mapping

## Mapping Source

InterfaceRealization

## Mapping Target

Subclassification

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subclassification::subclassifier () : Type [1]  
`Classifier_Mapping.getMapped(from.specific)`
- Subclassification::superclassifier () : Type [1]  
`Classifier_Mapping.getMapped(from.general)`

### 7.7.10.2.19 PrimitiveType\_Mapping

#### Description

The PrimitiveType\_Mapping class maps a UML4SysML::PrimitiveType to a SysML v2 AttributeDefinition.

#### General Mappings

DataType\_Mapping

#### Mapping Source

PrimitiveType

#### Mapping Target

AttributeDefinition

#### Owned Mappings

(none)

### 7.7.10.2.20 Reception\_Mapping

#### Description

A UML4SysML::Reception is mapped to a SysML v2 AttributeUsage with feature direction "in".

#### General Mappings

BehavioralFeature\_Mapping

#### Mapping Source

Reception

#### Mapping Target

ItemUsage



## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subclassification::superclassifier () : Type [1]  
`Classifier_Mapping.getMapped(from.general)`
- Subclassification::subclassifier () : Type [1]  
`Classifier_Mapping.getMapped(from.specific)`

### 7.7.10.2.19 PrimitiveType\_Mapping

#### Description

The PrimitiveType\_Mapping class maps a UML4SysML::PrimitiveType to a SysML v2 AttributeDefinition.

#### General Mappings

DataType\_Mapping

#### Mapping Source

PrimitiveType

#### Mapping Target

AttributeDefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.10.2.20 Reception\_Mapping

#### Description

A UML4SysML::Reception is mapped to a SysML v2 AttributeUsage with feature direction "in".

#### General Mappings

BehavioralFeature\_Mapping

#### Mapping Source

Reception

#### Mapping Target

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ItemUsage::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType (ElementMain_Mapping) .ownedRelationship () ->including (ReceptionFeatureTyping_Ma
```

- ItemUsage::direction () : FeatureDirectionKind [0..1]

```
SysMLv2::FeatureDirectionKind::in
```

### 7.7.10.2.21 ReceptionFeatureTyping\_Mapping

#### Description

A UML4SysML::Reception is mapped to SysML v2 AttributeUsage. The ReceptionToFeatureTyping\_Mapping class creates the type of the AttributeUsage which is the Signal of the Reception.

#### General Mappings

TypedElementFeatureTyping\_Mapping

#### Mapping Source

Reception

#### Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
Classifier_Mapping.getMapped (from.signal)
```

## ItemUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ItemUsage::ownedRelationship () : Relationship [0..\*]  
`self.oclAsType (ElementMain_Mapping) .ownedRelationship () ->including (ReceptionFeatureTyping_Mapping)`
- ItemUsage::direction () : FeatureDirectionKind [0..1]  
`SysMLv2::FeatureDirectionKind::in`

#### 7.7.10.2.21 ReceptionFeatureTyping\_Mapping

### Description

A UML4SysML::Reception is mapped to SysML v2 AttributeUsage. The ReceptionToFeatureTyping\_Mapping class creates the type of the AttributeUsage which is the Signal of the Reception.

### General Mappings

TypedElementFeatureTyping\_Mapping

### Mapping Source

Reception

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`Classifier_Mapping.getMapped (from.signal)`

#### 7.7.10.2.22 Signal\_Mapping

##### Description

A UML4SysML::Signal is mapped to a SysML v2 [AttributeDefinition](#).

##### General Mappings

Classifier\_Mapping

##### Mapping Source

Signal

##### Mapping Target

ItemDefinition

##### Owned Mappings

(none)

### 7.7.11 StateMachines

#### 7.7.11.1 Overview

Table 16. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
ConnectionPointReference	StateUsage
FinalState	StateUsage
Pseudostate	StateUsage
Region	StateUsage
State	StateUsage
StateMachine	<a href="#">ViewDefinition</a> <a href="#">StateDefinition</a> <a href="#">RequirementUsage</a>
Transition	TransitionUsage

The following table gives an overview of which SysML v2 elements the UML4SysML::StateMachines elements are transformed with which mapping class. The mapping details are in [7.7.11.2](#).

#### 7.7.11.2 Mapping Specifications

##### 7.7.11.2.1 ConnectionPointReference\_Mapping

##### Description

A UML4SysML::ConnectionPointReference element is mapped to a SysML v2 StateUsage.

##### General Mappings

### 7.7.10.2.22 Signal\_Mapping

**[SYSML2\\_-490](#): Signal\_Mapping maps to ItemDefinition but description says AttributeDefinition**

#### Description

A UML4SysML::Signal is mapped to a SysML v2 [ItemDefinition](#).

#### General Mappings

Classifier\_Mapping

#### Mapping Source

Signal

#### Mapping Target

ItemDefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

## 7.7.11 StateMachines

### 7.7.11.1 Overview

**[SYSML2\\_-329](#): Mapping overview tables are wrong**

Table 15. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
ConnectionPointReference	StateUsage
FinalState	StateUsage
Pseudostate	<a href="#">ActionUsage</a> StateUsage
Region	StateUsage
State	StateUsage
StateMachine	StateDefinition
Transition	TransitionUsage

### 7.7.11.2 Mapping Specifications

#### 7.7.11.2.1 [ChangeTriggerReferenceUsage\\_Mapping](#)

**[SYSML2\\_-131](#): ChangeEvent should be mapped to an accept action instead of [TextualRepresentation](#)**



### Description

Creates a reference usage.

### General Mappings

UniqueMapping  
ToReferenceUsage\_Init

### Mapping Source

Trigger

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::isEnd () : Boolean [1]  
`true`
- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
`Set{ChangeTriggerReferenceSubsetting_Mapping.getMapped(from)}`

#### 7.7.11.2.2 CommonPseudostate\_Mapping

**SYSML2\_-203: InitialState is mapped to StateUsage, but should be an empty ActionUsage**

### Description

Abstract mapping class for common rules for pseudostates mappings.

### General Mappings

Namespace\_Mapping

### Mapping Source

Pseudostate

### Mapping Target

Namespace\_Mapping  
**GenericToStateUsage\_Mapping**

### Mapping Source

ConnectionPointReference

### Mapping Target

StateUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **StateUsage::isComposite () : Boolean [1]**  
**false**
- **StateUsage::ownedRelationship () : Relationship [0..\*]**  

```
let toFeatureMS : Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Region)) in
let toElementOMS : Set(UML::Element) =
    (from.ownedElement - toFeatureMS) - from.ownedComment in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(toFeatureMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())
->union(self.ocIsType(ElementMain_Mapping).ownedRelationship())
```

## 7.7.11.2.2 FinalState\_Mapping

### Description

A UML4SysML::FinalState is mapped to a SysML v2 StateUsage. The details of the mapping are not defined yet.

### General Mappings

State\_Mapping

### Mapping Source

FinalState

### Mapping Target

StateUsage



Namespace

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Namespace::ownedRelationship () : Relationship [0..*]`

```
let toFeatureMS : Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Region))->asSet() in
let toElementOMS : Set(UML::Element) =
    from.ownedElement - toFeatureMS in
toElementOMS
->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(toFeatureMS
->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())
->union(self.ocAsType(ElementMain_Mapping).ownedRelationship())
```

### 7.7.11.2.3 ConnectionPointReference\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

A UML4SysML::ConnectionPointReference element is mapped to a SysML v2 StateUsage.

## General Mappings

Namespace\_Mapping  
ToStateUsage\_Init

## Mapping Source

ConnectionPointReference

## Mapping Target

StateUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules



In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `StateUsage::ownedRelationship () : Relationship [0..*]`

```
let toFeatureMS : Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Region)) in
let toElementOMS : Set(UML::Element) =
    (from.ownedElement - toFeatureMS) - from.ownedComment in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(toFeatureMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())
->union(self.ocAsType(ElementMain_Mapping).ownedRelationship())
```

- `StateUsage::isComposite () : Boolean [1]`

```
false
```

#### 7.7.11.2.4 DoBehaviorStateSubactionMembership\_Mapping

**SysML2\_-136: Transformation of UML4SysML::State does not consider entry, do, and exit behavior**

##### Description

Creates a state subaction membership relationship for *memberFeature()*.

##### General Mappings

StateBehaviorStateSubactionMembership\_Mapping

##### Mapping Source

Behavior

##### Mapping Target

StateSubactionMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `StateSubactionMembership::kind () : StateSubactionKind [1]`

```
SysMLv2::SubactionKind::do
```

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.ocIsTypeOf(UML::FinalState)
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.11.2.3 PseudoState\_Mapping

#### Description

A UML4SysML::PseudoState is mapped to a SysML v2 StateUsage.

## General Mappings

Namespace\_Mapping

GenericToStateUsage\_Mapping

## Mapping Source

Pseudostate

## Mapping Target

StateUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- StateUsage::ownedRelationship () : Relationship [0..\*]

```
let toFeatureMS : Set(UML::Element) =  
    from.ownedElement->select(e | e.ocIsKindOf(UML::Region)) ->asSet() in  
let toElementOMS : Set(UML::Element) =  
    from.ownedElement - toFeatureMS in  
toElementOMS  
->collect(e | ElementOwningMembership_Mapping.getMapped(e)) ->asSet()  
->union(toFeatureMS)
```

#### 7.7.11.2.5 EntryBehaviorStateSubactionMembership\_Mapping

**SysML2 -136: Transformation of UML4SysML::State does not consider entry, do, and exit behavior**

##### Description

Creates a state subaction membership relationship for *memberFeature()*.

##### General Mappings

StateBehaviorStateSubactionMembership\_Mapping

##### Mapping Source

Behavior

##### Mapping Target

StateSubactionMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- StateSubactionMembership::kind () : StateSubactionKind [1]  
SysMLv2::SubactionKind::entry

#### 7.7.11.2.6 ExitBehaviorStateSubactionMembership\_Mapping

**SysML2 -136: Transformation of UML4SysML::State does not consider entry, do, and exit behavior**

##### Description

Creates a state subaction membership relationship for *memberFeature()*.

##### General Mappings

StateBehaviorStateSubactionMembership\_Mapping

##### Mapping Source

Behavior

##### Mapping Target



StateSubactionMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- StateSubactionMembership::kind () : StateSubactionKind [1]  
SysMLv2::SubactionKind::exit

#### 7.7.11.2.7 FinalState\_Mapping

##### Description

A UML4SysML::FinalState is mapped to a SysML v2 StateUsage. The details of the mapping are not defined yet.

##### General Mappings

State\_Mapping

##### Mapping Source

FinalState

##### Mapping Target

StateUsage

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.ocIsTypeOf(UML::FinalState)
```

##### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

#### 7.7.11.2.8 InitialState\_Mapping

**SYSML2\_-203: InitialState is mapped to StateUsage, but should be an empty ActionUsage**

##### Description





The mapping class maps a Pseudostate with kind = initial to a SysML v2 ActionUsage.

### General Mappings

CommonPseudostate\_Mapping

### Mapping Source

Pseudostate

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(src.kind = PseudostateKind::initial)
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.11.2.9 InitialStateSubactionMembership\_Mapping

**[SYSML2 -136](#): Transformation of UML4SysML::State does not consider entry, do, and exit behavior**

**[SYSML2 -203](#): InitialState is mapped to StateUsage, but should be an empty ActionUsage**

**[SYSML2 -220](#): Replace Generic mapping classes by Initializers**

### Description

Creates a StateSubactionMembership relationship.

### General Mappings

ToStateSubactionMembership\_Init  
Mapping

### Mapping Source

Pseudostate

### Mapping Target

StateSubactionMembership

### Owned Mappings



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `StateSubactionMembership::ownedMemberFeature () : Feature [1]`  
`InitialState_Mapping.getMapped (from)`
- `StateSubactionMembership::kind () : StateSubactionKind [1]`  
`SysMLv2::SubactionKind::entry`

#### 7.7.11.2.10 PseudoState\_Mapping

**SYSML2\_-203: InitialState is mapped to StateUsage, but should be an empty ActionUsage**  
**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

A UML4SysML::PseudoState is mapped to a SysML v2 StateUsage.

#### General Mappings

CommonPseudostate\_Mapping  
ToStateUsage\_Init

#### Mapping Source

Pseudostate

#### Mapping Target

StateUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation `filter(src : Element) : Boolean` is verified:

```
(src.kind <> PseudostateKind::initial)
```

#### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

```
->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet()
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
```

#### 7.7.11.2.4 Region\_Mapping

##### Description

A UML4SysML::Region is mapped to SysML v2 StateUsage.

##### General Mappings

Namespace\_Mapping

GenericToStateUsage\_Mapping

##### Mapping Source

Region

##### Mapping Target

StateUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- StateUsage::ownedRelationship () : Relationship [0..\*]

```
let toFeatureMS : Set(UML::Element) =
  from.ownedElement
  ->select(e | e.oclIsKindOf(UML::State) or e.oclIsKindOf(UML::Transition)) in
let toElementOMS : Set(UML::Element) =
  (from.ownedElement - toFeatureMS) - from.ownedComment in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(toFeatureMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
```

#### 7.7.11.2.5 State\_Mapping

##### Description

A UML4SysML::State is mapped to a SysML v2 StateUsage.

##### General Mappings

### 7.7.11.2.11 Region\_Mapping

**SYSML2\_-203: InitialState is mapped to StateUsage, but should be an empty ActionUsage**

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

A UML4SysML::Region is mapped to SysML v2 StateUsage.

#### General Mappings

Namespace\_Mapping

ToStateUsage\_Init

#### Mapping Source

Region

#### Mapping Target

StateUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- StateUsage::ownedRelationship () : Relationship [0..\*]

```
let initialState : Set(UML::Pseudostate) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Pseudostate)
        and e.ocIsType(UML::Pseudostate).kind = PseudostateKind::initial)->asSet() in
let toFeatureMS : Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Region))->asSet() in
let toElementOMS : Set(UML::Element) =
    ((from.ownedElement - initialState) - toFeatureMS) - from.ownedComment in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()
->union(toFeatureMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())
->union(initialState->collect(e | InitialStateMembership_Mapping.getMapped(e))->asSet())
->union(self.ocIsType(ElementMain_Mapping).ownedRelationship())
```

### 7.7.11.2.12 State\_Mapping

**SYSML2\_-214: Mapping of State does not consider orthogonal states**

**SYSML2\_-136: Transformation of UML4SysML::State does not consider entry, do, and exit behavior**

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Namespace\_Mapping  
**GenericToStateUsage\_Mapping**

### Mapping Source

State

### Mapping Target

StateUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- StateUsage::ownedRelationship () : Relationship [0..\*]  

```
let toFeatureMS : Set(UML::Element) =  
    from.ownedElement->select(e | e.ocIsKindOf(UML::Region))->asSet() in  
let toElementOMS : Set(UML::Element) =  
    (from.ownedElement - toFeatureMS) - from.ownedComment in  
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()  
->union(toFeatureMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())  
->union(self.ocAsType(ElementMain_Mapping).ownedRelationship())
```

## 7.7.11.2.6 StateDefinition\_Mapping

### Description

A UML4SysML::StateMachine is mapped to a SysML v2 StateDefinition.

### General Mappings

Behavior\_Mapping

### Mapping Source

StateMachine

### Mapping Target

StateDefinition

### Owned Mappings

(none)

A UML4SysML::State is mapped to a SysMLv2 StateUsage. If it is a composite state, it is mapped to a parallel state.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
state SysMLv1State parallel {  
    entry; then SysMLv1StateA;  
    state SysMLv1StateA;  
}
```

## General Mappings

Namespace\_Mapping  
ToStateUsage\_Init

## Mapping Source

State

## Mapping Target

StateUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- StateUsage::isParallel () : Boolean [1]

```
from.isComposite
```

- StateUsage::ownedRelationship () : Relationship [0..\*]

```
let toFeatureMS : Set(UML::Element) =  
    from.ownedElement->select(e | e.ocIsKindOf(UML::Region))->asSet() in  
let toElementOMS : Set(UML::Element) =  
    (from.ownedElement - toFeatureMS) - from.ownedComment in  
let relationships : Set(KerML::Relationship) =  
    toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))->asSet()  
->union(toFeatureMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e))->asSet())  
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship()) in  
  
let consideredEntry : Set(KerML::Relationship) =  
if (from.entry.ocIsUndefined()) then  
    relationships  
else
```

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `StateDefinition::ownedRelationship () : Relationship [0..*]`

```
let initialState : Set(UML::Element) =
  from.ownedElement
  ->select(e | e.ocIsKindOf(UML::Pseudostate) and
    e.ocIsType(UML::Pseudostate).kind = UML::PseudostateKind::initial) in
let toParameterMS : Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
let parameterSets : Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::ParameterSet)) in
let toFeatureMS : Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Region) ) in
let toElementOMS : Set(UML::Element) =
  ((from.ownedElement - toFeatureMS) - toParameterMS) - initialState in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toFeatureMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(toParameterMS->collect(e | ParameterMembership_Mapping.getMapped(e)))
->union(parameterSets->collect(e | ParameterSetMembership_Mapping.getMapped(e)))
->union(initialState->collect(e | InitialStateMembership_Mapping.getMapped(e)))
```

- `StateDefinition::isParallel () : Boolean [1]`

```
from.region->size() > 1
```

### 7.7.11.2.7 Transition\_Mapping

#### Description

A UML4SysML::Transition is mapped to a SysML v2 TransitionUsage.

#### General Mappings

Namespace\_Mapping

GenericToTransitionUsage\_Mapping

#### Mapping Source

Transition

#### Mapping Target

TransitionUsage

#### Owned Mappings

(none)

## Applicable filters



```

        relationships->including(EntryBehaviorStateSubactionMembership_Mapping.getMapped(from.entry))
    endif in

    let consideredDo : Set(KerML::Relationship) =
    if (from.doActivity.ocllsUndefined()) then
        consideredEntry
    else
        consideredEntry->including(DoBehaviorStateSubactionMembership_Mapping.getMapped(from.doActi
    endif in
    if (from.exit.ocllsUndefined()) then
        consideredDo
    else
        consideredDo->including(ExitBehaviorStateSubactionMembership_Mapping.getMapped(from.exit))
    endif

```

### 7.7.11.2.13 StateBehaviorPerformActionUsage\_Mapping

**SYSML2 -136: Transformation of UML4SysML::State does not consider entry, do, and exit behavior**

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates a perform action usage typed by the target element of the mapping of the source behavior element.

#### General Mappings

ToPerformActionUsage\_Init  
Mapping

#### Mapping Source

Behavior

#### Mapping Target

PerformActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PerformActionUsage::ownedRelationship () : Relationship [0..\*]  
Set{StateBehaviorPerformActionUsageFeatureTyping\_Mapping.getMapped(from) }



#### 7.7.11.2.14 StateBehaviorPerformActionUsageFeatureTyping\_Mapping

[SYSML2 -136](#): Transformation of UML4SysML::State does not consider entry, do, and exit behavior

[SYSML2 -220](#): Replace Generic mapping classes by Initializers

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

ToFeatureTyping\_Init  
Mapping

##### Mapping Source

Behavior

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

from

#### 7.7.11.2.15 StateBehaviorStateSubactionMembership\_Mapping

[SYSML2 -136](#): Transformation of UML4SysML::State does not consider entry, do, and exit behavior

[SYSML2 -220](#): Replace Generic mapping classes by Initializers

##### Description

Abstract mapping class for mapping classes for state behavior mappings (enty, do and exit).

##### General Mappings

ToStateSubactionMembership\_Init  
Mapping

##### Mapping Source



Behavior

### Mapping Target

StateSubactionMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `StateSubactionMembership::ownedMemberFeature () : Feature [1]`  
`StateBehaviorPerformActionUsage_Mapping.getMapped (from)`

## 7.7.11.2.16 StateDefinition\_Mapping

### Description

A UML4SysML::StateMachine is mapped to a SysML v2 StateDefinition.

### General Mappings

Behavior\_Mapping

### Mapping Source

StateMachine

### Mapping Target

StateDefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `StateDefinition::isParallel () : Boolean [1]`  
`from.region->size () > 1`



- `StateDefinition::ownedRelationship () : Relationship [0..*]`

```

let initialState : Set(UML::Element) =
    from.ownedElement
    ->select(e | e.ocIsKindOf(UML::Pseudostate) and
        e.ocIsType(UML::Pseudostate).kind = UML::PseudostateKind::initial) in
let toParameterMS : Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter)) in
let parameterSets : Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::ParameterSet)) in
let toFeatureMS : Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Region) or e.ocIsKindOf(UML::ChangeEvent)) in
let rejectedElements : Set(UML::Element) = from.ownedElement->select(e | e.ocIsKindOf(UML::Stereotype)) in
let toElementOMS : Set(UML::Element) =
    ((from.ownedElement - toFeatureMS) - toParameterMS) - initialState in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toFeatureMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(toParameterMS->collect(e | ParameterMembership_Mapping.getMapped(e)))
->union(parameterSets->collect(e | ParameterSetMembership_Mapping.getMapped(e)))
->union(initialState->collect(e | InitialStateMembership_Mapping.getMapped(e)))

```

### 7.7.11.2.17 TimeTriggerReferenceUsage\_Mapping

**SYSML2\_-131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

#### Description

Creates a reference usage.

#### General Mappings

ToReferenceUsage\_Init  
UniqueMapping

#### Mapping Source

Trigger

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::isEnd () : Boolean [1]`

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TransitionUsage::target () : ActionUsage [1]

from.target

- TransitionUsage::ownedRelationship () : Relationship [0..\*]

```
self.oclassType(ElementMain_Mapping).ownedRelationship()  
->union((from.ownedElement - from.ownedComment)->collect(e | ElementOwningMembership_Mapping.  
->including(TransitionSuccession_Mapping.getMapped(from))
```

- TransitionUsage::source () : ActionUsage [1]

from.source

### 7.7.11.2.8 TransitionSuccession\_Mapping

#### Description

The mapping class creates the source Feature element of the Succession that is part of the TransitionUsage that is the target element of the UML4SysML::Transition mapping.

#### General Mappings

GenericToConnector\_Mapping

GenericToMembership\_Mapping

#### Mapping Source

Transition

#### Mapping Target

Succession

#### Owned Mappings

(none)

#### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Succession::ownedRelationship () : Relationship [0..\*]



true

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set{TimeTriggerReferenceSubsetting_Mapping.getMapped(from)}
```

### 7.7.11.2.18 Transition\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

A UML4SysML::Transition is mapped to a SysML v2 TransitionUsage.

##### **General Mappings**

Namespace\_Mapping  
ToTransitionUsage\_Init

##### **Mapping Source**

Transition

##### **Mapping Target**

TransitionUsage

##### **Owned Mappings**

(none)

##### **Applicable filters**

(none)

##### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TransitionUsage::source () : ActionUsage [1]

```
from.source
```

- TransitionUsage::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()  
->union((from.ownedElement - from.ownedComment)  
->collect(e | ElementOwningMembership_Mapping.getMapped(e)) ->asSet())  
->union(from.trigger->select(t | t.event.oclIsKindOf(UML::ChangeEvent) or t.event.oclIsKindOf  
->collect(e | TransitionTriggerFeatureMembership_Mapping.getMapped(e)) ->asSet())  
->including(TransitionSuccession_Mapping.getMapped(from))
```

- TransitionUsage::target () : ActionUsage [1]

```
from.target
```

```
OrderedSet{TransitionSuccessionSourceMembership_Mapping.getMapped(from),  
TransitionSuccessionTargetMembership_Mapping.getMapped(from) }
```

#### 7.7.11.2.9 TransitionSourceToSubsetting\_Mapping

##### Description

Creates a subsetting relationship.

##### General Mappings

GenericToSubsetting\_Mapping

##### Mapping Source

Transition

##### Mapping Target

Subsetting

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subsetting::subsettingFeature () : Feature [1]

```
TransitionSuccessionSource_Mapping.getMapped(from)
```

- Subsetting::subsettingFeature () : Feature [1]

```
ElementMain_Mapping.getMapped(from.source)
```

#### 7.7.11.2.10 TransitionSuccessionSource\_Mapping

##### Description

The mapping class creates the Succession element that is part of the TransitionUsage that is the target element of the UML4SysML::Transition mapping.

##### General Mappings

GenericToFeature\_Mapping

##### Mapping Source

Transition

### 7.7.11.2.19 TransitionSuccession\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates the source Feature element of the Succession that is part of the TransitionUsage that is the target element of the UML4SysML::Transition mapping.

#### General Mappings

ToConnector\_Init  
ToMembership\_Init  
Mapping

#### Mapping Source

Transition

#### Mapping Target

Succession

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Succession::ownedRelationship () : Relationship [0..\*]  
  
`OrderedSet{TransitionSuccessionSourceMembership_Mapping.getMapped(from) ,  
TransitionSuccessionTargetMembership_Mapping.getMapped(from) }`

### 7.7.11.2.20 TransitionSourceToSubsetting\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates a subsetting relationship.

#### General Mappings

ToSubsetting\_Init  
Mapping

#### Mapping Source

Transition



## Mapping Target

Subsetting

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subsetting::subsettingFeature () : Feature [1]  
`TransitionSuccessionSource_Mapping.getMapped(from)`
- Subsetting::subsettedFeature () : Feature [1]  
`ElementMain_Mapping.getMapped(from.source)`

### 7.7.11.2.21 TransitionSuccessionSource\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

The mapping class creates the Succession element that is part of the TransitionUsage that is the target element of the UML4SysML::Transition mapping.

## General Mappings

ToFeature\_Init  
Mapping

## Mapping Source

Transition

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set { TransitionSourceToSubsetting_Mapping.getMapped (from) }`
- `Feature::declaredName () : String [0..1]`  
`'source'`
- `Feature::isEnd () : Boolean [1]`  
`true`

### 7.7.11.2.11 TransitionSuccessionSourceMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToEndFeatureMembership\_Mapping

#### Mapping Source

Transition

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]  
`true`
- Feature::declaredName () : String [0..1]  
`'source'`
- Feature::ownedRelationship () : Relationship [0..\*]  
`Set { TransitionSourceToSubsetting_Mapping.getMapped (from) }`

#### 7.7.11.2.22 TransitionSuccessionSourceMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToEndFeatureMembership\_Init  
Mapping

##### Mapping Source

Transition

##### Mapping Target

EndFeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`TransitionSuccessionSource_Mapping.getMapped (from)`

#### 7.7.11.2.23 TransitionSuccessionTarget\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  
`TransitionSuccessionSource_Mapping.getMapped(from)`

#### 7.7.11.2.12 TransitionSuccessionTarget\_Mapping

##### Description

The mapping class creates the target Feature element of the Succession that is part of the TransitionUsage that is the target element of the UML4SysML::Transition mapping.

##### General Mappings

GenericToFeature\_Mapping

##### Mapping Source

Transition

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::isEnd () : Boolean [1]`  
`true`
- `Feature::declaredName () : String [0..1]`  
`'target'`
- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set { TransitionTargetToSubsetting_Mapping.getMapped(from) }`

#### 7.7.11.2.13 TransitionSuccessionTargetMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.





## General Mappings

GenericToEndFeatureMembership\_Mapping

## Mapping Source

Transition

## Mapping Target

EndFeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`TransitionSuccessionTarget_Mapping.getMapped (from)`

### 7.7.11.2.14 TransitionTargetToSubsetting\_Mapping

## Description

Creates a subsetting relationship.

## General Mappings

GenericToSubsetting\_Mapping

## Mapping Source

Transition

## Mapping Target

Subsetting

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

The mapping class creates the target Feature element of the Succession that is part of the TransitionUsage that is the target element of the UML4SysML::Transition mapping.

### General Mappings

ToFeature\_Init  
Mapping

### Mapping Source

Transition

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::declaredName () : String [0..1]  
`'target'`
- Feature::isEnd () : Boolean [1]  
`true`
- Feature::ownedRelationship () : Relationship [0..\*]  
`Set{TransitionTargetToSubsetting_Mapping.getMapped(from)}`

#### 7.7.11.2.24 TransitionSuccessionTargetMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToEndFeatureMembership\_Init  
Mapping

### Mapping Source

Transition



## Mapping Target

EndFeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  
`TransitionSuccessionTarget_Mapping.getMapped (from)`

### 7.7.11.2.25 TransitionTargetToSubsetting\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a subsetting relationship.

## General Mappings

ToSubsetting\_Init  
Mapping

## Mapping Source

Transition

## Mapping Target

Subsetting

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Subsetting::subsettingFeature () : Feature [1]`

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Subsetting::subsettingFeature () : Feature [1]`  
`TransitionSuccessionTarget_Mapping.getMapped (from)`
- `Subsetting::subsettingFeature () : Feature [1]`  
`ElementMain_Mapping.getMapped (from, target)`

This chapter lists all mapping specifications of UML4SysML::StateMachines model elements.

## 7.7.12 StructuredClassifiers

This chapter lists all mapping specifications of UML4SysML::StructuredClassifiers model elements.

### 7.7.12.1 Overview

**Table 17. List of all mappings**

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Association	not mapped; see next section
AssociationClass	ConnectionDefinition
Class	ViewDefinition RequirementUsage
Connector	ConnectionUsage
ConnectorEnd	not mapped; see next section
Port	PartUsage

The following table gives an overview of which SysML v2 elements the UML4SysML::StructuredClassifiers elements are transformed with which mapping class. The mapping details are in [7.7.12.2](#).

### 7.7.12.2 Mapping Specifications

#### 7.7.12.2.1 AssociationClass\_Mapping

##### Description

A UML4SysML::AssociationClass is mapped to a SysML v2 ConnectionDefinition. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1;
part def SysMLv1Block2;
connection def SysMLv1AssociationBlock {
    end : SysMLv1Block1;
    end : SysMLv1Block2;
}
```

##### General Mappings

AssociationCommon\_Mapping

```
ElementMain_Mapping.getMapped(from.target)
```

- Subsetting::subsettingFeature () : Feature [1]

```
TransitionSuccessionTarget_Mapping.getMapped(from)
```

#### 7.7.11.2.26 TransitionTriggerFeatureMembership\_Mapping

**SYSML2 -131: ChangeEvent should be mapped to an accept action instead of TextualRepresentation**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
UniqueMapping

##### Mapping Source

Trigger

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
if from.event.ocIsKindOf(UML::TimeEvent) then
    TimeTriggerCalculationUsage_Mapping.getMapped(from)
else if from.event.ocIsKindOf(UML::ChangeEvent) then
    ChangeTriggerConstraintUsage_Mapping.getMapped(from)
else
    OclUndefined
endif endif
```

## Mapping Source

AssociationClass

## Mapping Target

ConnectionDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not Helper.hasStereotypeApplied(src, 'SysML::Blocks::Block')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConnectionDefinition::ownedRelationship () : Relationship [0..\*]

```
let nonOwnedEnds: OrderedSet(UML::Property) =  
    (from.memberEnd-from.ownedEnd)->asOrderedSet() in  
let generalizations : Set(UML::Generalization) =  
    from.ownedElement->select(e | e.ocIsKindOf(UML::Generalization)) in  
let others: OrderedSet(UML::Element) =  
    ((from.ownedElement-from.memberEnd)-generalizations)->asOrderedSet() in  
nonOwnedEnds->collect(e | NonOwnedEndMembership_Mapping.getMapped(e))  
->union(from.ownedEnd->collect(e | OwnedEndMembership_Mapping.getMapped(e)))  
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e)))  
->union(others->collect(e | ElementOwningMembership_Mapping.getMapped(e)))  
->asOrderedSet()
```

### 7.7.12.2 AssociationCommon\_Mapping

#### Description

A UML4SysML::Association is mapped to a SysML v2 ConnectionDefinition. This is the abstract base class of all concrete association mapping classes.

#### General Mappings

Classifier\_Mapping  
Relationship\_Mapping

#### Mapping Source

Association

#### Mapping Target



## 7.7.12 StructuredClassifiers

### 7.7.12.1 Overview

[SYSML2\\_-329](#): Mapping overview tables are wrong

Table 16. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Association	ConnectionDefinition
AssociationClass	ConnectionDefinition OccurrenceDefinition
Class	OccurrenceDefinition
Connector	ConnectionUsage
ConnectorEnd	Feature
Port	AttributeUsage OccurrenceUsage PortUsage Feature

### 7.7.12.2 Mapping Specifications

#### 7.7.12.2.1 AssociationClass\_Mapping

##### Description

A UML4SysML::AssociationClass is mapped to a SysML v2 ConnectionDefinition. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1;  
part def SysMLv1Block2;  
connection def SysMLv1AssociationBlock {  
    end : SysMLv1Block1;  
    end : SysMLv1Block2;  
}
```

##### General Mappings

AssociationCommon\_Mapping

##### Mapping Source

AssociationClass

##### Mapping Target

ConnectionDefinition

##### Owned Mappings

(none)

##### Applicable filters

Association

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.memberEnd->select( m | m.type.ocIsKindOf(UML::UseCase))->isEmpty()
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Association::ownedRelationship() : Relationship [0..\*]

```
let nonOwnedEnds: OrderedSet(UML::Property) =  
    (from.memberEnd-from.ownedEnd)->asOrderedSet() in  
nonOwnedEnds->collect(e | NonOwnedEndMembership_Mapping.getMapped(e))->asOrderedSet()  
->union(self.oclAsType(Classifier_Mapping).ownedRelationship()->asOrderedSet())  
->asOrderedSet()
```

#### 7.7.12.2.3 AssociationMetadataUsage\_Mapping

### Description

The mapping class creates the MetadataUsage element to annotate a ConnectionDefinition that its mapping source element is a derived association.

### General Mappings

**Generic**ToMetadataUsage\_Mapping

### Mapping Source

Association

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not Helper.hasStereotypeApplied(src, 'SysML::Blocks::Block')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **ConnectionDefinition::ownedRelationship () : Relationship [0..\*]**

```
let nonOwnedEnds: OrderedSet(UML::Property) =
    (from.memberEnd-from.ownedEnd)->asOrderedSet() in
let generalizations : Set(UML::Generalization) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Generalization)) in
let others: OrderedSet(UML::Element) =
    ((from.ownedElement-from.memberEnd)-generalizations)->asOrderedSet() in
nonOwnedEnds->collect(e | NonOwnedEndMembership_Mapping.getMapped(e))
->union(from.ownedEnd->collect(e | OwnedEndMembership_Mapping.getMapped(e)))
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e)))
->union(others->collect(e | ElementOwningMembership_Mapping.getMapped(e)))
->asOrderedSet()
```

### 7.7.12.2.2 AssociationCommon\_Mapping

#### Description

A UML4SysML::Association is mapped to a SysML v2 ConnectionDefinition. This is the abstract base class of all concrete association mapping classes.

#### General Mappings

Classifier\_Mapping  
Relationship\_Mapping

#### Mapping Source

Association

#### Mapping Target

Association

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.memberEnd->select( m | m.type.ocIsKindOf(UML::UseCase))->isEmpty()
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `MetadataUsage::ownedRelationship () : Relationship [0..*]`

```
Set{AssociationToFeatureTyping_Mapping.getMapped(from) ,  
AssociationMetadataUsageFeatureMembership_Mapping.getMapped(from) }
```

#### 7.7.12.2.4 AssociationMetadataUsageFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

`GenericToFeatureMembership_Mapping`

##### Mapping Source

Association

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
AssociationMetadataUsageFeature_Mapping.getMapped(from)
```

#### 7.7.12.2.5 AssociationMetadataUsageFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

`GenericToFeatureTyping_Mapping`

##### Mapping Source

Association

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Association::ownedRelationship () : Relationship [0..\*]

```
let nonOwnedEnds: OrderedSet(UML::Property) =
    (from.memberEnd-from.ownedEnd)->asOrderedSet() in
nonOwnedEnds->collect(e | NonOwnedEndMembership_Mapping.getMapped(e))->asOrderedSet()
->union(self.oclAsType(Classifier_Mapping).ownedRelationship()->asOrderedSet())
->asOrderedSet()
```

### 7.7.12.2.3 AssociationMetadataUsage\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class creates the MetadataUsage element to annotate a ConnectionDefinition that its mapping source element is a derived association.

##### General Mappings

ToMetadataUsage\_Init  
Mapping

##### Mapping Source

Association

##### Mapping Target

MetadataUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

```
Set{AssociationToFeatureTyping_Mapping.getMapped(from),
AssociationMetadataUsageFeatureMembership_Mapping.getMapped(from)}
```

### 7.7.12.2.4 AssociationMetadataUsageFeatureMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
SYSMML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AssociationData')
```

## 7.7.12.2.6 AssociationMetadataUsageFeature\_Mapping

### Description

The mapping class creates the feature of the MetadataUsage.

### General Mappings

GenericToFeature\_Mapping

### Mapping Source

Association

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

Association

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`AssociationMetadataUsageFeature_Mapping.getMapped(from)`

## 7.7.12.2.5 AssociationMetadataUsageFeatureTyping\_Mapping

### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

Association

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

```
Set{AssociationMetadataUsageRedefinition_Mapping.getMapped(from),
AssociationMetadataUsageFeatureValue_Mapping.getMapped(from)}
```

#### 7.7.12.2.7 AssociationMetadataUsageFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

##### Mapping Source

Association

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
LiteralBoolean_Factory.create(from.isDerived)
```

#### 7.7.12.2.8 AssociationMetadataUsageMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic**ToOwningMembership\_Mapping

##### Mapping Source

Association

##### Mapping Target

OwningMembership



## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::AssociationData')
```

### 7.7.12.2.6 AssociationMetadataUsageFeature\_Mapping

**SysML2\_-220: Replace Generic mapping classes by Initializers**

## Description

The mapping class creates the feature of the MetadataUsage.

## General Mappings

ToFeature\_Init  
Mapping

## Mapping Source

Association

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set{AssociationMetadataUsageRedefinition_Mapping.getMapped(from),  
AssociationMetadataUsageFeatureValue_Mapping.getMapped(from) }
```

### 7.7.12.2.7 AssociationMetadataUsageFeatureValue\_Mapping

**SysML2\_-220: Replace Generic mapping classes by Initializers**



## Description

Creates a feature value relationship.

## General Mappings

ToFeatureValue\_Init  
Mapping

## Mapping Source

Association

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  
`LiteralBoolean_Factory.create(from.isDerived)`

### 7.7.12.2.8 AssociationMetadataUsageMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

Association

## Mapping Target

OwningMembership

## Owned Mappings

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`AssociationMetadataUsage_Mapping.getMapped(from)`

### 7.7.12.2.9 AssociationMetadataUsageRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

GenericToRedefinition\_Mapping

#### Mapping Source

Association

#### Mapping Target

Redefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  
`SysML2::AttributeUsage.allInstances()`  
`->any(m | m.qualifiedName = 'SysMLv1Library::AssociationData::isDerived')`

### 7.7.12.2.10 Class\_Mapping

#### Description

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`AssociationMetadataUsage_Mapping.getMapped(from)`

### 7.7.12.2.9 AssociationMetadataUsageRedefinition\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

ToRedefinition\_Init  
Mapping

#### Mapping Source

Association

#### Mapping Target

Redefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  
`SysML2::AttributeUsage.allInstances()`  
`->any(m | m.qualifiedName = 'SysMLv1Library::AssociationData::isDerived')`

### 7.7.12.2.10 Class\_Mapping

#### Description

A UML4SysML::Class is mapped to a SysML v2 OccurrenceDefinition. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
occurrence def UML4SysMLClass;
```

### General Mappings

BehavioeredClassifier\_Mapping

### Mapping Source

Class

### Mapping Target

OccurrenceDefinition

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not Helper.isRequirement(src) and not src.oclIsTypeOf(UML::AssociationClass)
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

## 7.7.12.2.11 ConnectionEndToSubsetting\_Mapping

### Description

Creates a subsetting relationship.

### General Mappings

GenericToSubsetting\_Mapping

### Mapping Source

ConnectorEnd

### Mapping Target

Subsetting

### Owned Mappings

(none)

### Applicable filters

A UML4SysML::Class is mapped to a SysML v2 OccurrenceDefinition. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
occurrence def UML4SysMLClass;
```

## General Mappings

BehavioeredClassifier\_Mapping

## Mapping Source

Class

## Mapping Target

OccurrenceDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not Helper.isRequirement(src) and not src.oclIsTypeOf(UML::AssociationClass)
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.12.2.11 ConnectionDefEnd\_Mapping

**SYSML2\_-498: The approved Issue KERML\_-18 requires the transformation specification to be adjusted**

## Description

\*\*\* not specified yet \*\*\*

## General Mappings

UniqueMapping  
End\_Mapping

## Mapping Source

Property

## Mapping Target

Feature

## Owned Mappings

(none)





## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
let crossFMultiplicity: Set(SysML2::ReferenceUsage) =
  if from.association.ownedEnd->includes(from) and
    not ((from.opposite.isComposite and from.lower = 0) or
      (from.lower = 0 and from.upper = -1)) then
    Set {MultiplicityReferenceUsage_Mapping.getMapped(from)}
  else
    Set{}
  endif in
let typings: Set(KerML::FeatureTyping) = if from.type.oclIsUndefined() then
  Set{}
else
  Set{StructuralFeatureToFeatureTyping_Mapping.getMapped(from)}
endif in
let subsettings: Set(KerML::CrossSubsetting) =
  if from.association.ownedEnd->excludes(from) and from.opposite.lower = 0 and
    not (from.isComposite or from.opposite.upper = -1) then
    Set{CrossSubsetting_Mapping.getMapped(from)}
  else
    Set{}
  endif in
let defaultValue: Set(KerML::OwningMembership) =
  if from.defaultValue.oclIsUndefined() then
    Set{}
  else
    Set{DefaultValue_Mapping.getMapped(from)}
  endif in
crossFMultiplicity->union (typings)
->union (subsettings)->union (defaultValue)
->including (MultiplicityMembership_Factory.create(1,1))->asSet()
```

### 7.7.12.2.12 ConnectionDefEndMembership\_Mapping

**SYSML2\_-498: The approved Issue KERML\_-18 requires the transformation specification to be adjusted**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

UniqueMapping  
ToFeatureMembership\_Init

#### Mapping Source

Property

#### Mapping Target



FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`ConnectionDefEnd_Mapping.getMapped (from)`

### 7.7.12.2.13 ConnectionEndToSubsetting\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a subsetting relationship.

### General Mappings

ToSubsetting\_Init  
Mapping

### Mapping Source

ConnectorEnd

### Mapping Target

Subsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Subsetting::subsettingFeature () : Feature [1]`  
`let propertyPath: OrderedSet (UML::Property) =`  
`Helper.getTagValueAsElementColl`

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subsetting::ownedRelationship () : Relationship [0..\*]

```
let propertyPath: OrderedSet(UML::Property) =
  Helper.getTagValueAsElementColl
    (from, 'SysML::Blocks::NestedConnectorEnd', 'propertyPath')
  ->asOrderedSet() in
if propertyPath->notEmpty() then
  OrderedSet{ConnectorEndToSubsettedFeatureMembership_Mapping.getMapped(from)}
else
  OrderedSet{}
endif
```

- Subsetting::subsettedFeature () : Feature [1]

```
let propertyPath: OrderedSet(UML::Property) =
  Helper.getTagValueAsElementColl
    (src, 'SysML::Blocks::NestedConnectorEnd', 'propertyPath')
  ->asOrderedSet() in
if propertyPath->isEmpty() then
  ElementMain_Mapping.getMapped(from.role)
else
  ConnectorEndToSubsettedFeature_Mapping.getMapped(from)
endif
```

- Subsetting::subsettingFeature () : Feature [1]

```
ConnectorEndToOwnedFeature_Mapping.getMapped(from)
```

### 7.7.12.2.12 Connector\_Mapping

#### Description

A UML4SysML::Connector is mapped to a SysMLv2 ConnectionUsage. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block3 {
  part sysMLv1PartProperty1 : SysMLv1Block1;
  part sysMLv1PartProperty2 : SysMLv1Block2;
  connection sysMLv1Connector connect sysMLv1PartProperty1 to sysMLv1PartProperty2;
}
part def SysMLv1Block1;
part def SysMLv1Block2;
```

#### General Mappings

NamedElementMain\_Mapping  
GenericToConnector\_Mapping

#### Mapping Source

```

        (src, 'SysML::Blocks::NestedConnectorEnd', 'propertyPath')
        ->asOrderedSet() in
    if propertyPath->isEmpty() then
        ElementMain_Mapping.getMapped(from.role)
    else
        ConnectorEndToSubsettedFeature_Mapping.getMapped(from)
    endif

```

- Subsetting::ownedRelationship () : Relationship [0..\*]

```

let propertyPath: OrderedSet(UML::Property) =
    Helper.getTagValueAsElementColl
        (from, 'SysML::Blocks::NestedConnectorEnd', 'propertyPath')
    ->asOrderedSet() in
if propertyPath->notEmpty() then
    OrderedSet{ConnectorEndToSubsettedFeatureMembership_Mapping.getMapped(from)}
else
    OrderedSet{}
endif

```

- Subsetting::subsettingFeature () : Feature [1]

```

ConnectorEndToOwnedFeature_Mapping.getMapped(from)

```

### 7.7.12.2.14 Connector\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

A UML4SysML::Connector is mapped to a SysMLv2 ConnectionUsage. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

part def SysMLv1Block3 {
    part sysMLv1PartProperty1 : SysMLv1Block1;
    part sysMLv1PartProperty2 : SysMLv1Block2;
    connection sysMLv1Connector connect sysMLv1PartProperty1 to sysMLv1PartProperty2;
}
part def SysMLv1Block1;
part def SysMLv1Block2;

```

##### **General Mappings**

NamedElementMain\_Mapping  
ToConnector\_Init

##### **Mapping Source**

Connector

##### **Mapping Target**

ConnectionUsage

##### **Owned Mappings**

(none)

##### **Applicable filters**

Connector

### Mapping Target

ConnectionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConnectionUsage::ownedRelationship () : Relationship [0..*]`  

```
from.end->collect (e | ConnectorEndToMembership_Mapping.getMapped (e)) ->asSet ()  
->including (ConnectorMultiplicityMembership_Mapping.getMapped (from))  
->union (self.oclAsType (ElementMain_Mapping).ownedRelationship ())
```

## 7.7.12.2.13 ConnectorEndToFeatureCommon\_Mapping

### Description

The mapping class is the abstract base class for UML4SysML::ConnectorEnd mapping classes.

### General Mappings

GenericToFeature\_Mapping

### Mapping Source

ConnectorEnd

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConnectionUsage::ownedRelationship () : Relationship [0..*]`

```
from.end->collect(e | ConnectorEndToMembership_Mapping.getMapped(e))->asSet()  
->including(ConnectorMultiplicityMembership_Mapping.getMapped(from))  
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
```

### 7.7.12.2.15 ConnectorEndToFeatureCommon\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

#### Description

The mapping class is the abstract base class for UML4SysML::ConnectorEnd mapping classes.

#### General Mappings

ToFeature\_[Init](#)  
Mapping

#### Mapping Source

ConnectorEnd

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::isOrdered () : Boolean [1]`

```
from.isOrdered
```

### 7.7.12.2.16 ConnectorEndToMembership\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

#### Description

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isOrdered () : Boolean [1]

`from.isOrdered`

#### 7.7.12.2.14 ConnectorEndToMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

GenericToFeatureMembership\_Mapping

##### Mapping Source

ConnectorEnd

##### Mapping Target

EndFeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]

`ConnectorEndToOwnedFeature_Mapping.getMapped(from)`

#### 7.7.12.2.15 ConnectorEndToOwnedFeature\_Mapping

##### Description

The mapping class creates the SysML v2 Feature element for the UML4SysML::ConnectorEnd mapping.

##### General Mappings

ConnectorEndToFeatureCommon\_Mapping

ElementMain\_Mapping

##### Mapping Source

ConnectorEnd



Creates a membership relationship for *memberElement()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

ConnectorEnd

### Mapping Target

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`ConnectorEndToOwnedFeature_Mapping.getMapped(from)`

## 7.7.12.2.17 ConnectorEndToOwnedFeature\_Mapping

### Description

The mapping class creates the SysML v2 Feature element for the UML4SysML::ConnectorEnd mapping.

### General Mappings

ConnectorEndToFeatureCommon\_Mapping  
ElementMain\_Mapping

### Mapping Source

ConnectorEnd

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  

```
let subsetting: KerML::Subsetting =  
    ConnectionEndToSubsetting_Mapping.getMapped(from) in  
if subsetting.oclIsUndefined() then  
    OrderedSet{MultiplicityMembership_Mapping.getMapped(from)}  
else  
    OrderedSet{MultiplicityMembership_Mapping.getMapped(from), subsetting}  
endif
```

### 7.7.12.2.16 ConnectorEndToSubsettedFeature\_Mapping

#### Description

The mapping class maps UML4SysML::ConnectorEnd that are part of a SysML::Ports&Flows::NestedConnectorEnd.

#### General Mappings

ConnectorEndToFeatureCommon\_Mapping

#### Mapping Source

ConnectorEnd

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
let subsetting: KerML::Subsetting =
  ConnectionEndToSubsetting_Mapping.getMapped(from) in
if subsetting.oclIsUndefined() then
  OrderedSet{MultiplicityMembership_Mapping.getMapped(from)}
else
  OrderedSet{MultiplicityMembership_Mapping.getMapped(from), subsetting}
endif
```

### 7.7.12.2.18 ConnectorEndToSubsettedFeature\_Mapping

#### Description

The mapping class maps UML4SysML::ConnectorEnd that are part of a SysML::Ports&Flows::NestedConnectorEnd.

#### General Mappings

ConnectorEndToFeatureCommon\_Mapping

#### Mapping Source

ConnectorEnd

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
let propertyPath: OrderedSet(UML::Property) =
  Helper.getTagValueAsElementColl(src, 'SysML::Blocks::NestedConnectorEnd', 'propertyPath')
->asOrderedSet() in
propertyPath->notEmpty()
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::declaredName () : String [0..1]  
  
    'featureChain'

```
let propertyPath: OrderedSet(UML::Property) =
  Helper.getTagValueAsElementColl(src, 'SysML::Blocks::NestedConnectorEnd', 'propertyPath')
->asOrderedSet() in
propertyPath->notEmpty()
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::declaredName () : String [0..1]

```
'featureChain'
```

- Feature::ownedRelationship () : Relationship [0..\*]

```
let propertyPath: OrderedSet(UML::Property) =
  Helper.getTagValueAsElementColl
    (from, 'SysML::Blocks::NestedConnectorEnd', 'propertyPath')
->asOrderedSet() in
let chain: OrderedSet(KerML::FeatureChaining) =
  propertyPath->collect(p | PropertyToFeatureChaining_Mapping.getMapped(p))
->asOrderedSet()
->including(PropertyToFeatureChaining_Mapping.getMapped(from.role)) in
chain->union(OrderedSet{MultiplicityMembership_Mapping.getMapped(from)})
```

### 7.7.12.2.17 ConnectorEndToSubsettedFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

ConnectorEnd

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

- `Feature::ownedRelationship () : Relationship [0..*]`

```
let propertyPath: OrderedSet(UML::Property) =
  Helper.getTagValueAsElementColl
    (from, 'SysML::Blocks::NestedConnectorEnd', 'propertyPath')
  ->asOrderedSet() in
let chain: OrderedSet(KerML::FeatureChaining) =
  propertyPath->collect(p | PropertyToFeatureChaining_Mapping.getMapped(p))
  ->asOrderedSet()
  ->including(PropertyToFeatureChaining_Mapping.getMapped(from.role)) in
chain->union(OrderedSet{MultiplicityMembership_Mapping.getMapped(from)})
```

### 7.7.12.2.19 ConnectorEndToSubsettedFeatureMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

Creates a feature membership relationship for *ownedMemberFeature()*.

##### **General Mappings**

ToFeatureMembership\_Init  
Mapping

##### **Mapping Source**

ConnectorEnd

##### **Mapping Target**

EndFeatureMembership

##### **Owned Mappings**

(none)

##### **Applicable filters**

(none)

##### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  
`ConnectorEndToSubsettedFeature_Mapping.getMapped(from)`

### 7.7.12.2.20 ConnectorMultiplicityMembership\_Mapping

##### **DescriptionGeneral Mappings**

No general mappings.

##### **Mapping Source**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  
`ConnectorEndToSubsettedFeature_Mapping.getMapped(from)`

#### 7.7.12.2.18 ConnectorMultiplicityMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

`DefaultMultiplicityMembership_Mapping`

##### Mapping Source

Connector

##### Mapping Target

`OwningMembership`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::memberName () : String [0..1]`  
`from.name+'_Connector_multiplicity'`

#### 7.7.12.2.19 ConnectorType\_Mapping

##### Description

A `UML4SysML::Association` is mapped to a `SysML v2 ConnectionDefinition`.

##### General Mappings

`AssociationCommon_Mapping`

##### Mapping Source

Association

Connector

### Mapping Target

No target element.

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `memberName () : String [0..1]`  
`from.name+'_Connector_multiplicity'`

## 7.7.12.2.21 ConnectorType\_Mapping

### Description

A UML4SysML::Association is mapped to a SysML v2 ConnectionDefinition.

### General Mappings

AssociationCommon\_Mapping

### Mapping Source

Association

### Mapping Target

ConnectionDefinition

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
let this: UML::Association = src.oclAsType(UML::Association) in
if this.oclIsUndefined() then
  false
else
  not src.memberEnd->exists( m | m.type.oclIsKindOf(UML::UseCase)) and
  not src.isDerived and
  not src.oclIsTypeOf(UML::AssociationClass) and
```

## Mapping Target

ConnectionDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
let this: UML::Association = src.oclAsType(UML::Association) in
if this.oclIsUndefined() then
    false
else
    not src.memberEnd->exists( m | m.type.oclIsKindOf(UML::UseCase)) and
    not src.isDerived and
    not src.oclIsTypeOf(UML::AssociationClass) and
    Helper.isConnectionDef(src)
endif
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.12.2.20 ConnectorTypeDerived\_Mapping

#### Description

The mapping class is a concrete mapping class of the abstract AssociationCommon\_Mapping class for mappings of derived associations. The UML4SysML::Association::isDerived property is not supported in SysML v2. To preserve the information, it is stored in a metadata annotation.

#### General Mappings

AssociationCommon\_Mapping

#### Mapping Source

Association

#### Mapping Target

ConnectionDefinition

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:



```

        Helper.isConnectionDef(src)
    endif

```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConnectionDefinition::ownedRelationship () : Relationship [0..*]`

```

from.memberEnd->collect (e | ConnectionDefEndMembership_Mapping.getMapped(e)) ->asOrderedSet ()

```

### 7.7.12.2.22 ConnectorTypeDerived\_Mapping

#### Description

The mapping class is a concrete mapping class of the abstract `AssociationCommon_Mapping` class for mappings of derived associations. The `UML4SysML::Association::isDerived` property is not supported in SysML v2. To preserve the information, it is stored in a metadata annotation.

#### General Mappings

`AssociationCommon_Mapping`

#### Mapping Source

`Association`

#### Mapping Target

`ConnectionDefinition`

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```

(src.memberEnd->select ( m | m.type.ocIsKindOf (UML::UseCase)) ->isEmpty()) and
(let this: UML::Association = src.ocAsType (UML::Association) in
if this.ocIsUndefined() then
    false
else
    this.isDerived and
    not this.ocIsTypeOf (UML::AssociationClass) and
    Helper.isConnectionDef (this)
endif)

```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConnectionDefinition::ownedRelationship () : Relationship [0..*]`

```

(src.memberEnd->select( m | m.type.ocIsKindOf(UML::UseCase)) ->isEmpty()) and
(let this: UML::Association = src.ocAsType(UML::Association) in
if this.ocIsUndefined() then
    false
else
    this.isDerived and
    not this.ocIsTypeOf(UML::AssociationClass) and
    Helper.isConnectionDef(this)
endif)

```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConnectionDefinition::ownedRelationship () : Relationship [0..\*]

```

self.ocAsType(AssociationCommon_Mapping).ownedRelationship()
->including(AssociationMetadataUsageMembership_Mapping.getMapped(from))

```

### 7.7.12.2.21 End\_Mapping

#### Description

The mapping class is the abstract base class of mapping classes for properties that are defined by association ends.

#### General Mappings

PropertyCommon\_Mapping

#### Mapping Source

Property

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```

src.ocIsKindOf(UML::Property) and
not src.ocAsType(UML::Property).association.ocIsUndefined()

```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]

```
self.oclAsType(AssociationCommon_Mapping).ownedRelationship()  
->including(AssociationMetadataUsageMembership_Mapping.getMapped(from))
```

#### 7.7.12.2.23 CrossSubsetting\_Mapping

**[SYSML2 -498](#): The approved Issue KERML\_-18 requires the transformation specification to be adjusted**

##### Description

Creates a subsetting relationship.

##### General Mappings

UniqueMapping  
ToSubsetting\_Init

##### Mapping Source

Property

##### Mapping Target

CrossSubsetting

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- CrossSubsetting::subsettingFeature () : Feature [1]  
NonOwnedEnd\_Mapping.getMapped(from)

#### 7.7.12.2.24 End\_Mapping

##### Description

The mapping class is the abstract base class of mapping classes for properties that are defined by association ends.

##### General Mappings

PropertyCommon\_Mapping

##### Mapping Source

Property

##### Mapping Target

true

#### 7.7.12.2.22 EndMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

StructuralFeatureMembership\_Mapping

##### Mapping Source

Property

##### Mapping Target

EndFeatureMembership

##### Owned Mappings

(none)

#### 7.7.12.2.23 EndToSubsettedFeature\_Mapping

##### Description

The mapping class creates a feature element for the UML4SysML::ConnectorEnd mapping.

##### General Mappings

PropertyCommon\_Mapping

##### Mapping Source

Property

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
let property: UML::Property = src.oclAsType(UML::Property) in
not property.association.oclIsUndefined()
and property.association.ownedEnd->excludes(property)
```

##### Mapping rules

Feature

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.ocIsKindOf(UML::Property) and  
not src.ocIsType(UML::Property).association.ocIsUndefined()
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::isEnd () : Boolean [1]

true

## 7.7.12.2.25 EndMembership\_Mapping

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

StructuralFeatureMembership\_Mapping

### Mapping Source

Property

### Mapping Target

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

## 7.7.12.2.26 EndToSubsettedFeature\_Mapping

### Description

The mapping class creates a feature element for the UML4SysML::ConnectorEnd mapping.

### General Mappings

PropertyCommon\_Mapping

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
let chain: OrderedSet (KerML::FeatureChaining) =  
    OrderedSet { EndToSubsettedFeatureChaining_Mapping.getMapped (from) } in  
chain->including (MultiplicityMembership_Mapping.getMapped (from))
```

#### 7.7.12.2.24 EndToSubsettedFeatureChaining\_Mapping

##### Description

The mapping class creates a feature chaining element for the UML4SysML::ConnectorEnd mapping.

##### General Mappings

GenericToRelationship\_Mapping

##### Mapping Source

Property

##### Mapping Target

FeatureChaining

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::declaredName () : String [0..1]

```
'featureChain'
```

- FeatureChaining::chainingFeature () : Feature [1]

```
from
```

#### 7.7.12.2.25 NonOwnedEndSubsetting\_Mapping

##### Description

Creates a subsetting relationship.

##### General Mappings

GenericToSubsetting\_Mapping

## Mapping Source

Property

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
let property: UML::Property = src.oclAsType(UML::Property) in
not property.association.oclIsUndefined()
and property.association.ownedEnd->excludes(property)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
let chain: OrderedSet(KerML::FeatureChaining) =
    OrderedSet{EndToSubsettedFeatureChaining_Mapping.getMapped(from)} in
chain->including(MultiplicityMembership_Mapping.getMapped(from))
```

### 7.7.12.2.27 EndToSubsettedFeatureChaining\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

The mapping class creates a feature chaining element for the UML4SysML::ConnectorEnd mapping.

## General Mappings

ToRelationship\_Init  
Mapping

## Mapping Source

Property

## Mapping Target

FeatureChaining

## Owned Mappings

(none)





## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChaining::declaredName () : String [0..1]`  
`'featureChain'`
- `FeatureChaining::chainingFeature () : Feature [1]`  
`from`

### 7.7.12.2.28 MultiplicityReferenceUsage\_Mapping

**[SYSML2 -498](#): The approved Issue KERML\_-18 requires the transformation specification to be adjusted**

## Description

Creates a reference usage.

## General Mappings

UniqueMapping  
ToReferenceUsage\_Init

## Mapping Source

Property

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{MultiplicityMembership_Factory.create(from.lower, from.upper) }`

## Mapping Source

Property

## Mapping Target

Subsetting

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subsetting::subsettingFeature () : Feature [1]  
from

### 7.7.12.2.26 NonOwnedEndToSubsettingFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

## Mapping Source

Property

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.ocIsKindOf(UML::Property) and  
not src.ocIsType(UML::Property).association.ocIsUndefined()
```

## Mapping rules

### 7.7.12.2.29 NonOwnedEndSubsetting\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a subsetting relationship.

#### General Mappings

ToSubsetting\_Init  
Mapping

#### Mapping Source

Property

#### Mapping Target

Subsetting

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Subsetting::subsettingFeature () : Feature [1]

from

### 7.7.12.2.30 NonOwnedEndToSubsettingFeatureMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

Property

#### Mapping Target

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`EndToSubsettedFeature_Mapping.getMapped(from)`

#### 7.7.12.2.27 NonOwnedEnd\_Mapping

##### Description

The mapping class maps UML4SysML::Property elements that are not owned by an association to a SysML v2 Feature element.

##### General Mappings

End\_Mapping

##### Mapping Source

Property

##### Mapping Target

Feature

##### Owned Mappings

- `nonOwnedEndTyping : NonOwnedEndFeatureTyping_Mapping`

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set{MultiplicityMembership_Mapping.getMapped(from),`  
`nonOwnedEndTyping.to,`  
`NonOwnedEndSubsettingMembership_Mapping.getMapped(from),`  
`NonOwnedEndToSubsettedFeatureMembership_Mapping.getMapped(from) }`  
`->union(from.qualifier`  
`->collect(q | ElementFeatureMembership_Mapping.getMapped(q)) ->asSet())`
- `Feature::declaredName () : String [0..1]`  
`'nonOwnedEnd'`

#### 7.7.12.2.28 NonOwnedEndMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.ocIsKindOf(UML::Property) and  
not src.ocAsType(UML::Property).association.ocIsUndefined()
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`EndToSubsettedFeature_Mapping.getMapped(from)`

## 7.7.12.2.31 NonOwnedEnd\_Mapping

### Description

The mapping class maps UML4SysML::Property elements that are not owned by an association to a SysML v2 Feature element.

### General Mappings

End\_Mapping  
UniqueMapping

### Mapping Source

Property

### Mapping Target

Feature

### Owned Mappings

- nonOwnedEndTyping : NonOwnedEndFeatureTyping\_Mapping

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::declaredName () : String [0..1]

## General Mappings

EndMembership\_Mapping

## Mapping Source

Property

## Mapping Target

EndFeatureMembership

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.oclIsKindOf(UML::Property)
and not src.oclAsType(UML::Property).association.oclIsUndefined()
and src.oclAsType(UML::Property).association.ownedEnd->excludes(src)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`NonOwnedEnd_Mapping.getMapped(from)`

### 7.7.12.2.29 NonOwnedEndSubsettingMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToOwningMembership\_Mapping

#### Mapping Source

Property

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

'nonOwnedEnd'

- Feature::ownedRelationship () : Relationship [0..\*]

```
Set{MultiplicityMembership_Mapping.getMapped(from),
nonOwnedEndTyping.to,
NonOwnedEndSubsettingMembership_Mapping.getMapped(from),
NonOwnedEndToSubsettedFeatureMembership_Mapping.getMapped(from)}
->union(from.qualifier
->collect(q | ElementFeatureMembership_Mapping.getMapped(q))>asSet())
```

### 7.7.12.2.32 NonOwnedEndMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

EndMembership\_Mapping

#### Mapping Source

Property

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.ocIsKindOf(UML::Property)
and not src.ocAsType(UML::Property).association.ocIsUndefined()
and src.ocAsType(UML::Property).association.ownedEnd->excludes(src)
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]

```
NonOwnedEnd_Mapping.getMapped(from)
```

### 7.7.12.2.33 NonOwnedEndSubsettingMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a membership relationship for *memberElement()*.

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`NonOwnedEndSubsetting_Mapping.getMapped (from)`

### 7.7.12.2.30 NonOwnedEndFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

StructuralFeatureToFeatureTyping\_Mapping

#### Mapping Source

Property

#### Mapping Target

FeatureTyping

#### Owned Mappings

- `nonOwnedEnd : NonOwnedEnd_Mapping`

### 7.7.12.2.31 OwnedEnd\_Mapping

#### Description

The mapping class maps `UML4SysML::Property` elements that are owned by an association to a SysML v2 Feature element.

#### General Mappings

End\_Mapping  
NamedElementMain\_Mapping

#### Mapping Source

Property

#### Mapping Target

Feature

#### Owned Mappings



## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

Property

## Mapping Target

OwningMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`NonOwnedEndSubsetting_Mapping.getMapped(from)`

### 7.7.12.2.34 NonOwnedEndFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

StructuralFeatureToFeatureTyping\_Mapping  
UniqueMapping

## Mapping Source

Property

## Mapping Target

FeatureTyping

## Owned Mappings

- nonOwnedEnd : NonOwnedEnd\_Mapping

## Applicable filters

(none)

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
let p: UML::Property = src.oclAsType(UML::Property) in
not p.oclIsUndefined() and
(not p.association.oclIsUndefined()
 and p.association.ownedEnd->includes(p)) and
(not p.association.memberEnd
->select( m | (not m.type.oclIsUndefined())
 and m.type.oclIsTypeOf(UML::UseCase)) ->notEmpty())
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **Feature::ownedRelationship () : Relationship [0..\*]**

```
let qualifiers: Set(KerML::FeatureMembership) =
  from.qualifier
  ->collect(q | ElementFeatureMembership_Mapping.getMapped(q)) ->asSet() in
let typing: KerML::FeatureTyping =
  StructuralFeatureToFeatureTyping_Mapping.getMapped(from) in
let subsetting: Set(KerML::Subsetting) =
  from.subsettedProperty
  ->collect(p | PropertySubsetting_Mapping.getMapped(from, p)) ->asSet() in
let subsettingMultiplicityTyping: Set(KerML::Relationship) =
  subsetting->union(if typing.oclIsUndefined() then
    Set{MultiplicityMembership_Mapping.getMapped(from)}
  else
    Set{MultiplicityMembership_Mapping.getMapped(from), typing}
  endif) ->asSet() in
let relationships: Set(KerML::Relationship) = qualifiers->union(
  if from.defaultValue.oclIsTypeOf(UML::OpaqueExpression) then
    subsettingMultiplicityTyping
    ->including(ElementOwningMembership_Mapping.getMapped(from.defaultValue))
  else
    subsettingMultiplicityTyping
  endif) in

if from.defaultValue.oclIsUndefined() then
  relationships
else
  relationships->including(
    if from.defaultValue.oclIsTypeOf(UML::OpaqueExpression) then
      DefaultValueOpaqueExpression_Mapping.getMapped(from.defaultValue)
    else
      DefaultValue_Mapping.getMapped(from.defaultValue)
    endif)
endif
```

#### 7.7.12.2.32 OwnedEndMembership\_Mapping

##### Description

### 7.7.12.2.35 OwnedEnd\_Mapping

#### Description

The mapping class maps UML4SysML::Property elements that are owned by an association to a SysML v2 Feature element.

#### General Mappings

End\_Mapping  
NamedElementMain\_Mapping

#### Mapping Source

Property

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
let p: UML::Property = src.oclAsType(UML::Property) in
not p.oclIsUndefined() and
(not p.association.oclIsUndefined()
  and p.association.ownedEnd->includes(p)) and
(not p.association.memberEnd
->select( m | (not m.type.oclIsUndefined())
  and m.type.oclIsTypeOf(UML::UseCase))->notEmpty())
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
let qualifiers: Set(KerML::FeatureMembership) =
  from.qualifier
->collect(q | ElementFeatureMembership_Mapping.getMapped(q))->asSet() in
let typing: KerML::FeatureTyping =
  StructuralFeatureToFeatureTyping_Mapping.getMapped(from) in
let subsetting: Set(KerML::Subsetting) =
  from.subsettedProperty
->collect(p | PropertySubsetting_Mapping.getMapped(from, p))->asSet() in
let subsettingMultiplicityTyping: Set(KerML::Relationship) =
  subsetting->union(if typing.oclIsUndefined() then
    Set{MultiplicityMembership_Mapping.getMapped(from)}
  else
    Set{MultiplicityMembership_Mapping.getMapped(from), typing}
  endif)->asSet() in
```

Creates a membership relationship for *memberElement()*.

### General Mappings

EndMembership\_Mapping

### Mapping Source

Property

### Mapping Target

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.oclIsKindOf(UML::Property)
and not src.oclAsType(UML::Property).association.oclIsUndefined()
and src.oclAsType(UML::Property).association.ownedEnd->includes(src)
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
OwnedEnd\_Mapping.getMapped(from)

## 7.7.12.2.33 Port\_Mapping

### Description

A UML4SysML::Port that is typed by an interface block is mapped to a SysML v2 PortUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
port sysMLv1Port : SysMLv1InterfaceBlock;
port def SysMLv1InterfaceBlock
```

### General Mappings

PropertyCommon\_Mapping  
NamedElementMain\_Mapping

### Mapping Source

```

let relationships: Set(KerML::Relationship) = qualifiers->union(
  if from.defaultValue.oclIsTypeOf(UML::OpaqueExpression) then
    subsettingMultiplicityTyping
    ->including(ElementOwningMembership_Mapping.getMapped(from.defaultValue))
  else
    subsettingMultiplicityTyping
  endif) in

if from.defaultValue.oclIsUndefined() then
  relationships
else
  relationships->including(
    if from.defaultValue.oclIsTypeOf(UML::OpaqueExpression) then
      DefaultValueOpaqueExpression_Mapping.getMapped(from.defaultValue)
    else
      DefaultValue_Mapping.getMapped(from.defaultValue)
    endif)
endif

```

### 7.7.12.2.36 OwnedEndMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

EndMembership\_Mapping

#### Mapping Source

Property

#### Mapping Target

EndFeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```

src.ocIsKindOf(UML::Property)
and not src.ocIsType(UML::Property).association.ocIsUndefined()
and src.ocIsType(UML::Property).association.ownedEnd->includes(src)

```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
OwnedEnd\_Mapping.getMapped(from)

Port

### Mapping Target

PortUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.oclIsTypeOf(UML::Port) and
not Helper.hasStereotypeApplied(src.owner,
'SysML::ConstraintBlocks::ConstraintBlock' ) then
    let p: UML::Port = src.oclAsType(UML::Port) in
        if p.type.oclIsUndefined() then
            false
        else
            true
        endif
    else
        false
    endif
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

## 7.7.12.2.34 PortUntyped\_Mapping

### Description

A UML4SysML::Port that is untyped is mapped to a SysML v2 PortUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
port sysMLv1Port;
```

### General Mappings

PropertyUntyped\_Mapping

### Mapping Source

Port

### Mapping Target

PortUsage

### Owned Mappings

### 7.7.12.2.37 Port\_Mapping

#### Description

A UML4SysML::Port that is typed by an interface block is mapped to a SysML v2 PortUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
port sysMLv1Port : SysMLv1InterfaceBlock;  
port def SysMLv1InterfaceBlock
```

#### General Mappings

PropertyCommon\_Mapping  
NamedElementMain\_Mapping

#### Mapping Source

Port

#### Mapping Target

PortUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.oclIsTypeOf(UML::Port) and  
not Helper.hasStereotypeApplied(src.owner,  
'SysML::ConstraintBlocks::ConstraintBlock' ) then  
  let p: UML::Port = src.oclAsType(UML::Port) in  
    if p.type.oclIsUndefined() then  
      false  
    else  
      true  
    endif  
else  
  false  
endif
```

#### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.12.2.38 PortUntyped\_Mapping

#### Description

A UML4SysML::Port that is untyped is mapped to a SysML v2 PortUsage.

(none)

### 7.7.12.2.35 PropertyToFeatureChaining\_Mapping

#### Description

The mapping class creates the SysML v2 FeatureChaining for the UML4SysML::Property mapping.

#### General Mappings

GenericToRelationship\_Mapping

#### Mapping Source

Property

#### Mapping Target

FeatureChaining

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]  
`ElementMain_Mapping.getMapped(from)`

### 7.7.12.2.36 QualifierMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

StructuralFeatureMembership\_Mapping

#### Mapping Source

StructuralFeature

#### Mapping Target

FeatureMembership

#### Owned Mappings



The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
port sysMLv1Port;
```

### General Mappings

PropertyUntyped\_Mapping

### Mapping Source

Port

### Mapping Target

PortUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### 7.7.12.2.39 PropertyToFeatureChaining\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the SysML v2 FeatureChaining for the UML4SysML::Property mapping.

### General Mappings

ToRelationship\_Init  
Mapping

### Mapping Source

Property

### Mapping Target

FeatureChaining

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

(none)

## 7.7.13 UseCases

This chapter lists all mapping specifications of UML4SysML::UseCases model elements.

### 7.7.13.1 Overview

**Table 18.** List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Actor	ItemDefinition
Extend	not mapped; see next section
ExtensionPoint	not mapped; see next section
Include	IncludeUseCaseUsage
UseCase	UseCaseDefinition

The following table gives an overview of which SysML v2 elements the UML4SysML::UseCases elements are transformed with which mapping class. The mapping details are in [7.7.13.3](#).

The justifications for the elements without mapping are given in [7.7.13.2](#).

### 7.7.13.2 UML4SysML::UseCases elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 19.** List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
Extend	The semantics of the UML4SysML::Extend relationship is not supported by SysML v2.
ExtensionPoint	The semantics of the UML4SysML::Extend relationship is not supported by SysML v2 Therefore, UML4SysML::ExtensionPoint is also not covered by the transformation.

### 7.7.13.3 Mapping Specifications

#### 7.7.13.3.1 Actor\_Mapping

##### Description

A UML4SysML::Actor is mapped to a SysML v2 **ItemDefinition**. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
item def SysMLv1Actor;
```

##### General Mappings

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChaining::chainingFeature () : Feature [1]`  
`ElementMain_Mapping.getMapped(from)`

#### 7.7.12.2.40 QualifierMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

StructuralFeatureMembership\_Mapping

##### Mapping Source

StructuralFeature

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

### 7.7.13 UseCases

#### 7.7.13.1 Overview

[SYSML2 -329: Mapping overview tables are wrong](#)

Table 17. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Actor	PartDefinition
Extend	not mapped; see next section
ExtensionPoint	not mapped; see next section
Include	IncludeUseCaseUsage
UseCase	UseCaseDefinition

#### 7.7.13.2 UML4SysML::UseCases elements not mapped

ElementMain\_Mapping  
BehavioredClassifier\_Mapping

### Mapping Source

Actor

### Mapping Target

ItemDefinition

### Owned Mappings

(none)

## 7.7.13.3.2 Include\_Mapping

### Description

A UML4SysML::Include is mapped to a SysML v2 IncludeUseCaseUsage. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
use case def SysMLv1UseCase1 {  
    include use case : SysMLv1UseCase2;  
}  
use case def SysMLv1UseCase2;
```

### General Mappings

GenericToOccurrenceUsage\_Mapping  
NamedElementMain\_Mapping

### Mapping Source

Include

### Mapping Target

IncludeUseCaseUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- IncludeUseCaseUsage::ownedRelationship () : Relationship [0..\*]

**Table 18. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
Extend	The semantics of the UML4SysML::Extend relationship is not supported by SysML v2.
ExtensionPoint	The semantics of the UML4SysML::Extend relationship is not supported by SysML v2 Therefore, UML4SysML::ExtensionPoint is also not covered by the transformation.

### 7.7.13.3 Mapping Specifications

#### 7.7.13.3.1 Actor\_Mapping

##### **SYSML2\_-314: Actor should be mapped to a PartDefinition**

##### Description

A UML4SysML::Actor is mapped to a SysML v2 **PartDefinition**. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Actor;
```

##### General Mappings

ElementMain\_Mapping  
BehavioredClassifier\_Mapping

##### Mapping Source

Actor

##### Mapping Target

**PartDefinition**

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.13.3.2 Include\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

A UML4SysML::Include is mapped to a SysML v2 IncludeUseCaseUsage. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
use case def SysMLv1UseCase1 {
    include use case : SysMLv1UseCase2;
```

```

    Set{IncludeFeatureTyping_Mapping.getMapped(from),
    ReturnParameterFeatureMembership_Factory.create(),
    EmptySubjectMembership_Factory.create()}
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())

```

### 7.7.13.3.3 IncludeFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**Generic**ToFeatureTyping\_Mapping

#### Mapping Source

Include

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

from.addition

### 7.7.13.3.4 UseCase\_Mapping

#### Description

A UML4SysML::UseCase is mapped to a SysML v2 UseCaseDefinition. The expected SysML v2 textual syntax of a mapped UML4SysML::UseCase with a defined subject is as follows.

```

use case def SysMLv1UseCase {
    subject subject_SysMLv1Block : SysMLv1Block;
}
part def SysMLv1Block;

```

Currently, only one use case subject is supported by the mapping class. Since the UML4SysML::Extend relationship is not considered by the SysML v1 to SysML v2 transformation, the extension points of a use case are also not mapped.

#### General Mappings

```
}  
use case def SysMLv1UseCase2;
```

## General Mappings

ToOccurrenceUsage\_Init  
NamedElementMain\_Mapping

## Mapping Source

Include

## Mapping Target

IncludeUseCaseUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- IncludeUseCaseUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{IncludeFeatureTyping_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create(),  
EmptySubjectMembership_Factory.create()}  
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
```

### 7.7.13.3 IncludeFeatureTyping\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

Include

## Mapping Target

FeatureTyping

BehavioredClassifier\_Mapping  
NamedElementMain\_Mapping

### Mapping Source

UseCase

### Mapping Target

UseCaseDefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- UseCaseDefinition::ownedRelationship () : Relationship [0..\*]

```
let properties : Set(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Property) and
    e.ocIsAsType(UML::Property).association.ocIsUndefined()) in
let actors : Set(UML::Property) =
  UML::Association.allInstances()
  ->collect(m | m.memberEnd)
  ->flatten()
  ->select(m | m.type = from)->collect(a | a.owningAssociation)
  ->collect(p | p.memberEnd->select(m | not (m.type = from)))->flatten() in
let extensionPoints : Sequence(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::ExtensionPoint)) in
let extend : Sequence(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Extend)) in
let include : Sequence(UML::Element) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Include)) in
let elements : Set(UML::Element) =
  (((from.ownedElement-properties) - extensionPoints) - extend) - include) in
let relationships : Sequence(KerML::Relationship) =
  elements->collect(e | ElementOwningMembership_Mapping.getMapped(e))
  ->union(properties->collect(e | PropertyMembership_Mapping.getMapped(e)))
  ->including(UseCaseSubjectMembership_Mapping.getMapped(from))
  ->including(UseCaseObjectiveMembership_Mapping.getMapped(from))
  ->including(CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from))
  ->union(actors->collect(e | UseCaseActorMembership_Mapping.getMapped(e))) in
if from.classifierBehavior.ocIsUndefined() then
  relationships
else
  relationships
  ->including(BehavioredClassifierFeatureMembership_Mapping.getMapped(from))
endif
```



## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`from.addition`

### 7.7.13.3.4 UseCase\_Mapping

#### Description

A UML4SysML::UseCase is mapped to a SysML v2 UseCaseDefinition. The expected SysML v2 textual syntax of a mapped UML4SysML::UseCase with a defined subject is as follows.

```
use case def SysMLv1UseCase {  
  subject subject_SysMLv1Block : SysMLv1Block;  
}  
part def SysMLv1Block;
```

Currently, only one use case subject is supported by the mapping class. Since the UML4SysML::Extend relationship is not considered by the SysML v1 to SysML v2 transformation, the extension points of a use case are also not mapped.

#### General Mappings

BehavioeredClassifier\_Mapping  
NamedElementMain\_Mapping

#### Mapping Source

UseCase

#### Mapping Target

UseCaseDefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

### 7.7.13.3.5 UseCaseActor\_Mapping

#### Description

The mapping class creates the PartUsage representing an actor of the use case.

#### General Mappings

**Generic**ToPartUsage\_Mapping

#### Mapping Source

Property

#### Mapping Target

PartUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **PartUsage::declaredName () : String [0..1]**  
`from.name`
- **PartUsage::ownedRelationship () : Relationship [0..\*]**  
`Set { UseCaseActorFeatureTyping_Mapping.getMapped (from) }`

### 7.7.13.3.6 UseCaseActorFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**Generic**ToFeatureTyping\_Mapping

#### Mapping Source

Property

#### Mapping Target

FeatureTyping

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- UseCaseDefinition::ownedRelationship () : Relationship [0..\*]

```

let properties : Set(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Property) and
        e.ocIsAsType(UML::Property).association.ocIsUndefined()) in
let actors : Set(UML::Property) =
    UML::Association.allInstances()
    ->collect(m | m.memberEnd)
    ->flatten()
    ->select(m | m.type = from)->collect(a | a.owningAssociation)
    ->collect(p | p.memberEnd->select(m | not (m.type = from)))->flatten() in
let extensionPoints : Sequence(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::ExtensionPoint)) in
let extend : Sequence(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Extend)) in
let include : Sequence(UML::Element) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Include)) in
let elements : Set(UML::Element) =
    (((from.ownedElement-properties) - extensionPoints) - extend) - include) in
let relationships : Sequence(KerML::Relationship) =
    elements->collect(e | ElementOwningMembership_Mapping.getMapped(e))
    ->union(properties->collect(e | PropertyMembership_Mapping.getMapped(e)))
    ->including(UseCaseSubjectMembership_Mapping.getMapped(from))
    ->including(UseCaseObjectiveMembership_Mapping.getMapped(from))
    ->including(CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from))
    ->union(actors->collect(e | UseCaseActorMembership_Mapping.getMapped(e))) in
if from.classifierBehavior.ocIsUndefined() then
    relationships
else
    relationships
    ->including(BehavoredClassifierFeatureMembership_Mapping.getMapped(from))
endif

```

### 7.7.13.3.5 UseCaseActor\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

The mapping class creates the PartUsage representing an actor of the use case.

##### **General Mappings**

ToPartUsage\_Init  
Mapping

##### **Mapping Source**

Property

##### **Mapping Target**

PartUsage

##### **Owned Mappings**

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

`from.type`

### 7.7.13.3.7 UseCaseActorMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

`GenericToActorMembership_Mapping`

#### Mapping Source

Property

#### Mapping Target

ActorMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActorMembership::ownedMemberParameter () : Feature [1]`

`UseCaseActor_Mapping.getMapped(from)`

### 7.7.13.3.8 UseCaseEmptySubjectReferenceUsage\_Mapping

#### Description

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PartUsage::ownedRelationship () : Relationship [0..*]`  
`Set { UseCaseActorFeatureTyping_Mapping.getMapped (from) }`
- `PartUsage::declaredName () : String [0..1]`  
`from.name`

### 7.7.13.3.6 UseCaseActorFeatureTyping\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

ToFeatureTyping\_Init  
Mapping

#### Mapping Source

Property

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`from.type`

The mapping class creates an "empty" ReferenceUsage for the subject, if the subject is not given at the SysML v1 UseCase element.

### General Mappings

**Generic**ToReferenceUsage\_Mapping

### Mapping Source

UseCase

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

## 7.7.13.3.9 UseCaseObjectiveMembership\_Mapping

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

**Generic**ToObjectiveMembership\_Mapping

### Mapping Source

UseCase

### Mapping Target

ObjectiveMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ObjectiveMembership::ownedMemberFeature () : Feature [1]  
`UseCaseObjectiveRequirementUsage_Mapping.getMapped(from)`

### 7.7.13.3.7 UseCaseActorMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToActorMembership\_Init  
Mapping

#### Mapping Source

Property

#### Mapping Target

ActorMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActorMembership::ownedMemberParameter () : Feature [1]  
`UseCaseActor_Mapping.getMapped(from)`

### 7.7.13.3.8 UseCaseEmptySubjectReferenceUsage\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

The mapping class creates an "empty" ReferenceUsage for the subject, if the subject is not given at the SysML v1 UseCase element.

#### General Mappings

ToReferenceUsage\_Init  
Mapping

#### Mapping Source

UseCase

#### Mapping Target

### 7.7.13.3.10 UseCaseObjectiveRequirementUsage\_Mapping

#### Description

The mapping class creates the RequirementUsage element for the use case objective. The element is not set by an element from the SysML v1 UseCase.

#### General Mappings

GenericToRequirementUsage\_Mapping

#### Mapping Source

UseCase

#### Mapping Target

RequirementUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RequirementUsage::ownedRelationship () : Relationship [0..\*]

```
Set { UseCaseObjectiveSubjectMembership_Mapping.getMapped(from) ,  
CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from) }
```

### 7.7.13.3.11 UseCaseObjectiveSubjectMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToSubjectMembership\_Mapping

#### Mapping Source

UseCase

#### Mapping Target

SubjectMembership

#### Owned Mappings



ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

#### 7.7.13.3.9 UseCaseObjectiveMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToObjectiveMembership\_Init  
Mapping

### Mapping Source

UseCase

### Mapping Target

ObjectiveMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ObjectiveMembership::ownedMemberFeature () : Feature [1]  
`UseCaseObjectiveRequirementUsage_Mapping.getMapped(from)`

#### 7.7.13.3.10 UseCaseObjectiveRequirementUsage\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the RequirementUsage element for the use case objective. The element is not set by an element from the SysML v1 UseCase.



## General Mappings

ToRequirementUsage\_Init  
Mapping

## Mapping Source

UseCase

## Mapping Target

RequirementUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RequirementUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{UseCaseObjectiveSubjectMembership_Mapping.getMapped(from),  
CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)}
```

### 7.7.13.3.11 UseCaseObjectiveSubjectMembership\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToSubjectMembership\_Init  
Mapping

## Mapping Source

UseCase

## Mapping Target

SubjectMembership

## Owned Mappings

(none)

## Applicable filters

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SubjectMembership::ownedMemberParameter () : Feature [1]  
`UseCaseEmptySubjectReferenceUsage_Mapping.getMapped(from)`

### 7.7.13.3.12 UseCaseSubjectFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

GenericToFeatureTyping\_Mapping

#### Mapping Source

UseCase

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`if from.subject->size() > 0 then from.subject->get(0) else invalid endif`

### 7.7.13.3.13 UseCaseSubjectMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `SubjectMembership::ownedMemberParameter () : Feature [1]`  
`UseCaseEmptySubjectReferenceUsage_Mapping.getMapped(from)`

#### 7.7.13.3.12 UseCaseSubjectFeatureTyping\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

UseCase

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`if from.subject->size() > 0 then from.subject->get(0) else invalid endif`

#### 7.7.13.3.13 UseCaseSubjectMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a membership relationship for *memberElement()*.

## General Mappings

GenericToSubjectMembership\_Mapping

## Mapping Source

UseCase

## Mapping Target

SubjectMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SubjectMembership::ownedMemberParameter () : Feature [1]  

```
if from.subject->size() > 0 then
    UseCaseSubjectReferenceUsage_Mapping.getMapped(from)
else
    UseCaseEmptySubjectReferenceUsage_Mapping.getMapped(from)
endif
```

### 7.7.13.3.14 UseCaseSubjectReferenceUsage\_Mapping

#### Description

The mapping class creates the ReferenceUsage element for the subject.

## General Mappings

UseCaseEmptySubjectReferenceUsage\_Mapping

## Mapping Source

UseCase

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

## General Mappings

ToSubjectMembership\_Init  
Mapping

## Mapping Source

UseCase

## Mapping Target

SubjectMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SubjectMembership::ownedMemberParameter () : Feature [1]  

```
if from.subject->size() > 0 then
    UseCaseSubjectReferenceUsage_Mapping.getMapped(from)
else
    UseCaseEmptySubjectReferenceUsage_Mapping.getMapped(from)
endif
```

### 7.7.13.3.14 UseCaseSubjectReferenceUsage\_Mapping

#### Description

The mapping class creates the ReferenceUsage element for the subject.

## General Mappings

UseCaseEmptySubjectReferenceUsage\_Mapping

## Mapping Source

UseCase

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set { UseCaseSubjectFeatureTyping_Mapping.getMapped (from) }`
- `ReferenceUsage::declaredName () : String [0..1]`  
`'subject_' + from.subject->get (0) .name`

## 7.7.14 Values

This chapter lists all mapping specifications of UML4SysML::Values model elements.

### 7.7.14.1 Overview

**Table 20. List of all mappings**

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Duration	not mapped; see next section
DurationConstraint	ConstraintDefinition
DurationInterval	not mapped; see next section
DurationObservation	not mapped; see next section
Expression	OperatorExpression
Interval	not mapped; see next section
IntervalConstraint	not mapped; see next section
LiteralBoolean	LiteralBoolean
LiteralInteger	LiteralInteger
LiteralNull	NullExpression
LiteralReal	LiteralRational
LiteralString	LiteralString
LiteralUnlimitedNatural	LiteralInteger
OpaqueExpression	CalculationUsage
StringExpression	not mapped; see next section
TimeConstraint	ConstraintDefinition
TimeExpression	TriggerInvocationExpression
TimeInterval	not mapped; see next section
TimeObservation	not mapped; see next section



(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set { UseCaseSubjectFeatureTyping_Mapping.getMapped (from) }`
- `ReferenceUsage::declaredName () : String [0..1]`  
`'subject_' + from.subject->get (0) .name`

## 7.7.14 Values

### 7.7.14.1 Overview

**SYSML2 -329: Mapping overview tables are wrong**

**Table 19. List of all mappings**

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Duration	<a href="#">Expression</a>
DurationConstraint	ConstraintDefinition
DurationInterval	<a href="#">Expression</a>
DurationObservation	not mapped; see next section
Expression	OperatorExpression <a href="#">Expression</a>
Interval	<a href="#">Expression</a>
IntervalConstraint	<a href="#">ConstraintDefinition</a>
LiteralBoolean	LiteralBoolean
LiteralInteger	LiteralInteger
LiteralNull	NullExpression
LiteralReal	LiteralRational
LiteralString	LiteralString
LiteralUnlimitedNatural	<a href="#">LiteralInfinity</a>
OpaqueExpression	CalculationUsage
StringExpression	<a href="#">OperatorExpression</a> <a href="#">Expression</a>
TimeConstraint	ConstraintDefinition
TimeExpression	<a href="#">Expression</a>
TimeInterval	<a href="#">Expression</a>
TimeObservation	not mapped; see next section

The following table gives an overview of which SysML v2 elements the UML4SysML::Values elements are transformed with which mapping class. The mapping details are in [7.7.14.3](#).

The justifications for the elements without mapping are given in [7.7.14.2](#).

### 7.7.14.2 UML4SysML::Values elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 21. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
Duration	Mapping is not specified yet.
DurationConstraint	Mapping is not specified yet.
DurationInterval	Mapping is not specified yet.
DurationObservation	Mapping is not specified yet.
Interval	Mapping is not specified yet.
IntervalConstraint	Mapping is not specified yet.
StringExpression	Mapping is not specified yet.
TimeConstraint	Mapping is not specified yet.
TimeInterval	Mapping is not specified yet.
TimeObservation	Mapping is not specified yet.

### 7.7.14.3 Mapping Specifications

#### 7.7.14.3.1 EqualOperatorExpressionFeature\_Mapping

##### Description

The mapping class creates the feature element for the equal operator.

##### General Mappings

GenericToFeature\_Mapping

##### Mapping Source

TypedElement

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

### 7.7.14.2 UML4SysML::Values elements not mapped

Table 20. List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
Duration	Mapping is not specified yet.
DurationConstraint	Mapping is not specified yet.
DurationInterval	Mapping is not specified yet.
DurationObservation	Mapping is not specified yet.
Interval	Mapping is not specified yet.
IntervalConstraint	Mapping is not specified yet.
StringExpression	Mapping is not specified yet.
TimeConstraint	Mapping is not specified yet.
TimeInterval	Mapping is not specified yet.
TimeObservation	Mapping is not specified yet.

### 7.7.14.3 Mapping Specifications

#### 7.7.14.3.1 EqualOperatorExpressionFeature\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates the feature element for the equal operator.

#### General Mappings

ToFeature **Init**  
Mapping

#### Mapping Source

TypedElement

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set {EqualOperatorExpressionFeatureValue_Mapping.getMapped (from) }
```

#### 7.7.14.3.2 EqualOperatorExpressionFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

`GenericToFeatureValue_Mapping`

##### Mapping Source

`TypedElement`

##### Mapping Target

`FeatureValue`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
CommonFeatureReferenceExpression_Mapping.getMapped (from)
```

#### 7.7.14.3.3 EqualOperatorExpressionOperandParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

`GenericToParameterMembership_Mapping`

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set{EqualOperatorExpressionFeatureValue_Mapping.getMapped(from) }
```

### 7.7.14.3.2 EqualOperatorExpressionFeatureValue\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a feature value relationship.

#### General Mappings

ToFeatureValue\_Init  
Mapping

#### Mapping Source

TypedElement

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
CommonFeatureReferenceExpression_Mapping.getMapped(from)
```

### 7.7.14.3.3 EqualOperatorExpressionOperandParameterMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToParameterMembership\_Init  
Mapping

## Mapping Source

TypedElement

## Mapping Target

ParameterMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`EqualOperatorExpressionFeature_Mapping.getMapped(from)`
- ParameterMembership::visibility () : VisibilityKind [1]  
`KerML::VisibilityKind::private`

### 7.7.14.3.4 Expression\_Mapping

#### Description

A UML4SysML::Expression element is mapped to a SysML v2 OperatorExpression element.

#### General Mappings

`GenericToExpression_Mapping`  
`NamedElementMain_Mapping`

## Mapping Source

Expression

## Mapping Target

OperatorExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping Source

TypedElement

## Mapping Target

ParameterMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ParameterMembership::visibility () : VisibilityKind [1]`  
`KerML::VisibilityKind::private`
- `ParameterMembership::ownedMemberParameter () : Feature [1]`  
`EqualOperatorExpressionFeature_Mapping.getMapped(from)`

### 7.7.14.3.4 Expression\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

## Description

A UML4SysML::Expression element is mapped to a SysML v2 OperatorExpression element.

## General Mappings

ToExpression\_Init  
NamedElementMain\_Mapping

## Mapping Source

Expression

## Mapping Target

OperatorExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OperatorExpression::operator () : String [1]`

`from.symbol`

### 7.7.14.3.5 ExpressionElse\_Mapping

#### Description

A `UML4SysML::Expression` element with operator "else" is mapped to a SysML v2 `TextualRepresentation` element with language set to "SysMLv1" and body set to "else".

#### General Mappings

`Expression_Mapping`

#### Mapping Source

`Expression`

#### Mapping Target

`OperatorExpression`

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.symbol = 'else'
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OperatorExpression::ownedRelationship () : Relationship [0..*]`

```
self.oclAsType (ElementMain_Mapping).ownedRelationship()->including (ExpressionElseMembership_
```

### 7.7.14.3.6 ExpressionElseMembership\_Mapping

#### Description

Creates the membership relationship for the textual representation for the else guard condition specification.

#### General Mappings



## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OperatorExpression::operator () : String [1]`

`from.symbol`

### 7.7.14.3.5 ExpressionElse\_Mapping

#### Description

A `UML4SysML::Expression` element with operator "else" is mapped to a SysML v2 `TextualRepresentation` element with language set to "SysMLv1" and body set to "else".

#### General Mappings

`Expression_Mapping`

#### Mapping Source

`Expression`

#### Mapping Target

`OperatorExpression`

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.symbol = 'else'
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OperatorExpression::ownedRelationship () : Relationship [0..*]`

```
self.oclAsType (ElementMain_Mapping).ownedRelationship ()->including (ExpressionElseMembership_Mapping)
```

### 7.7.14.3.6 ExpressionElseMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates the membership relationship for the textual representation for the else guard condition specification.

#### General Mappings

**Generic**ToOwningMembership\_Mapping

**Mapping Source**

Expression

**Mapping Target**

OwningMembership

**Owned Mappings**

(none)

**Applicable filters**

(none)

**Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ExpressionElseSpecification_Mapping.getMapped(from)`

**7.7.14.3.7 ExpressionElseSpecification\_Mapping**

**Description**

Creates the textual representation for the else guard condition specification.

**General Mappings**

**Generic**ToTextualRepresentation\_Mapping

**Mapping Source**

Expression

**Mapping Target**

TextualRepresentation

**Owned Mappings**

(none)

**Applicable filters**

(none)

**Mapping rules**

ToOwningMembership\_Init  
Mapping

#### Mapping Source

Expression

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ExpressionElseSpecification_Mapping.getMapped(from)`

### 7.7.14.3.7 ExpressionElseSpecification\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates the textual representation for the else guard condition specification.

#### General Mappings

ToTextualRepresentation\_Init  
Mapping

#### Mapping Source

Expression

#### Mapping Target

TextualRepresentation

#### Owned Mappings

(none)

#### Applicable filters

(none)

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TextualRepresentation::body () : String [1]`  
`'else'`
- `TextualRepresentation::language () : String [1]`  
`'SysMLv1'`

#### 7.7.14.3.8 LiteralBoolean\_Mapping

##### Description

The mapping class maps UML4SysML::LiteralBoolean to SysML v2 LiteralBoolean.

##### General Mappings

LiteralSpecificationCommon\_Mapping

##### Mapping Source

LiteralBoolean

##### Mapping Target

LiteralBoolean

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `LiteralBoolean::value () : Boolean [1]`  
`from.value`

#### 7.7.14.3.9 LiteralInteger\_Mapping

##### Description

The mapping class maps UML4SysML::LiteralInteger to SysML v2 LiteralInteger.

##### General Mappings

LiteralSpecificationCommon\_Mapping

##### Mapping Source

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `TextualRepresentation::language () : String [1]`  
`'SysMLv1'`
- `TextualRepresentation::body () : String [1]`  
`'else'`

### 7.7.14.3.8 LiteralBoolean\_Mapping

#### Description

The mapping class maps UML4SysML::LiteralBoolean to SysML v2 LiteralBoolean.

#### General Mappings

LiteralSpecificationCommon\_Mapping

#### Mapping Source

LiteralBoolean

#### Mapping Target

LiteralBoolean

#### Owned Mappings

(none)

#### Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `LiteralBoolean::value () : Boolean [1]`  
`from.value`

### 7.7.14.3.9 LiteralInteger\_Mapping

#### Description

The mapping class maps UML4SysML::LiteralInteger to SysML v2 LiteralInteger.

#### General Mappings

LiteralSpecificationCommon\_Mapping

LiteralInteger

### Mapping Target

LiteralInteger

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralInteger::value () : Integer [1]  
from.value

#### 7.7.14.3.10 LiteralNull\_Mapping

##### Description

The mapping class maps UML4SysML::LiteralNull to SysML v2 NullExpression.

##### General Mappings

LiteralSpecificationCommon\_Mapping

##### Mapping Source

LiteralNull

##### Mapping Target

NullExpression

##### Owned Mappings

(none)

#### 7.7.14.3.11 LiteralReal\_Mapping

##### Description

The mapping class maps UML4SysML::LiteralReal to SysML v2 LiteralRational.

##### General Mappings

LiteralSpecificationCommon\_Mapping

##### Mapping Source

### Mapping Source

LiteralInteger

### Mapping Target

LiteralInteger

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralInteger::value () : Integer [1]  
from.value

### 7.7.14.3.10 LiteralNull\_Mapping

#### Description

The mapping class maps UML4SysML::LiteralNull to SysML v2 NullExpression.

#### General Mappings

LiteralSpecificationCommon\_Mapping

### Mapping Source

LiteralNull

### Mapping Target

NullExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### 7.7.14.3.11 LiteralReal\_Mapping

#### Description

The mapping class maps UML4SysML::LiteralReal to SysML v2 LiteralRational.

LiteralReal

### Mapping Target

LiteralRational

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralRational::value () : Real [1]

`from.value`

## 7.7.14.3.12 LiteralSpecificationCommon\_Mapping

### Description

The mapping class is the abstract base class for all concrete UML4SysML::LiteralSpecification mappings.

### General Mappings

ValueSpecification\_Mapping

### Mapping Source

LiteralSpecification

### Mapping Target

LiteralExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralExpression::ownedRelationship () : Relationship [0..\*]



## General Mappings

LiteralSpecificationCommon\_Mapping

## Mapping Source

LiteralReal

## Mapping Target

LiteralRational

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralRational::value () : Real [1]

from.value

### 7.7.14.3.12 LiteralSpecificationCommon\_Mapping

#### Description

The mapping class the is abstract base class for all concrete UML4SysML::LiteralSpecification mappings.

## General Mappings

ValueSpecification\_Mapping

## Mapping Source

LiteralSpecification

## Mapping Target

LiteralExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

```

let ownerships: Set(SYSML2::Relationship) =
  self.oclAsType(ElementMain_Mapping).ownedRelationship()
  ->including(CommonReturnParameterFeatureMembership_Mapping.getMapped(from)) in
if from.type.oclIsUndefined() then
  ownerships
else
  ownerships->including(LiteralSpecificationTyping_Mapping.getMapped(from))
endif

```

### 7.7.14.3.13 LiteralSpecificationFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

TypedElementFeatureTyping\_Mapping

#### Mapping Source

LiteralSpecification

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

### 7.7.14.3.14 LiteralString\_Mapping

#### Description

The mapping class maps UML4SysML::LiteralString to the SysML v2 LiteralString.

#### General Mappings

LiteralSpecificationCommon\_Mapping

#### Mapping Source

LiteralString

#### Mapping Target

LiteralString

#### Owned Mappings

(none)

#### Applicable filters

(none)

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `LiteralExpression::ownedRelationship () : Relationship [0..*]`

```
let ownerships: Set(SYSML2::Relationship) =
    self.oclAsType(ElementMain_Mapping).ownedRelationship()
    ->including(CommonReturnParameterFeatureMembership_Mapping.getMapped(from)) in
if from.type.oclIsUndefined() then
    ownerships
else
    ownerships->including(LiteralSpecificationTyping_Mapping.getMapped(from))
endif
```

#### 7.7.14.3.13 LiteralSpecificationFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

TypedElementFeatureTyping\_Mapping

##### Mapping Source

LiteralSpecification

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

#### 7.7.14.3.14 LiteralString\_Mapping

##### Description

The mapping class maps UML4SysML::LiteralString to the SysML v2 LiteralString.

##### General Mappings

LiteralSpecificationCommon\_Mapping

##### Mapping Source

LiteralString

##### Mapping Target

LiteralString

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralString::value () : String [1]

```
if from.value.oclIsUndefined() then '' else from.value endif
```

### 7.7.14.3.15 LiteralUnlimitedUnbounded\_Mapping

#### Description

The mapping class maps UML4SysML::LiteralUnlimited to SysML v2 LiteralInfinity if it is the unlimited value.

#### General Mappings

LiteralUnlimitedInteger\_Mapping

#### Mapping Source

LiteralUnlimitedNatural

#### Mapping Target

LiteralInfinity

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(from.value = -1)
```

#### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.14.3.16 LiteralUnlimitedInteger\_Mapping

#### Description

The mapping class maps UML4SysML::LiteralUnlimited to SysML v2 LiteralInteger if it is not the unlimited value.

#### General Mappings

LiteralSpecificationCommon\_Mapping

#### Mapping Source

LiteralUnlimitedNatural

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `LiteralString::value () : String [1]`  
`if from.value.oclIsUndefined() then '' else from.value endif`

### 7.7.14.3.15 LiteralUnlimitedUnbounded\_Mapping

#### Description

The mapping class maps UML4SysML::LiteralUnlimited to SysML v2 LiteralInfinity if it is the unlimited value.

#### General Mappings

LiteralUnlimitedInteger\_Mapping

#### Mapping Source

LiteralUnlimitedNatural

#### Mapping Target

LiteralInfinity

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(from.value = -1)
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.7.14.3.16 LiteralUnlimitedInteger\_Mapping

#### Description

The mapping class maps UML4SysML::LiteralUnlimited to SysML v2 LiteralInteger if it is not the unlimited value.

#### General Mappings

### Mapping Target

LiteralInteger

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralInteger::value () : Integer [1]

from.value

## 7.7.14.3.17 OpaqueExpressionAsValue\_Mapping

### Description

The mapping class maps a UML4SysML::OpaqueExpression if it is used as a value to a SysML v2 FeatureChainExpression.

### General Mappings

GenericToExpression\_Mapping

### Mapping Source

OpaqueExpression

### Mapping Target

FeatureChainExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChainExpression::ownedRelationship () : Relationship [0..\*]

LiteralSpecificationCommon\_Mapping

#### Mapping Source

LiteralUnlimitedNatural

#### Mapping Target

LiteralInteger

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- LiteralInteger::value () : Integer [1]  
from.value

### 7.7.14.3.17 OpaqueExpressionAsValue\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class maps a UML4SysML::OpaqueExpression if it is used as a value to a SysML v2 FeatureChainExpression.

##### General Mappings

ToExpression\_Init  
Mapping

#### Mapping Source

OpaqueExpression

#### Mapping Target

FeatureChainExpression

#### Owned Mappings

(none)

#### Applicable filters

(none)

```
Set{OpaqueExpressionParameterMembership_Mapping.getMapped(from),
CommonReturnParameterFeatureMembership_Mapping.getMapped(from)}
```

### 7.7.14.3.18 OpaqueExpression\_Mapping

#### Description

A UML4SysML::OpaqueExpression element is mapped to a SysMLv2 CalculationUsage element.. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
calc sysMLv1OpaqueExpression {
    return result : ScalarValues::Integer;
    language "Built-in Math"
    /*
    * result = 42 + 23;
    */
}
```

#### General Mappings

CommonAction\_Mapping  
ValueSpecification\_Mapping

#### Mapping Source

OpaqueExpression

#### Mapping Target

CalculationUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- CalculationUsage::ownedRelationship () : Relationship [0..\*]

```
Set{OpaqueExpressionMembership_Mapping.getMapped(from),
OpaqueExpressionReferenceUsageReturnParameterMembership_Mapping.getMapped(from)}
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
```

### 7.7.14.3.19 OpaqueExpressionFeature\_Mapping

#### Description

The mapping class creates the feature of the FeatureChainExpression.



## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChainExpression::ownedRelationship () : Relationship [0..*]`

```
Set{OpaqueExpressionParameterMembership_Mapping.getMapped(from),  
CommonReturnParameterFeatureMembership_Mapping.getMapped(from)}
```

### 7.7.14.3.18 OpaqueExpression\_Mapping

#### Description

A `UML4SysML::OpaqueExpression` element is mapped to a `SysMLv2 CalculationUsage` element.. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
calc sysMLv1OpaqueExpression {  
    return result : ScalarValues::Integer;  
    language "Built-in Math"  
    /*  
    * result = 42 + 23;  
    */  
}
```

#### General Mappings

`CommonAction_Mapping`  
`ValueSpecification_Mapping`

#### Mapping Source

`OpaqueExpression`

#### Mapping Target

`CalculationUsage`

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.owner.ocIsKindOf(UML::TimeExpression) then  
    not src.owner.owner.ocIsKindOf(UML::TimeEvent)  
else  
    true  
endif
```

## Mapping rules

## General Mappings

GenericToFeature\_Mapping

## Mapping Source

OpaqueExpression

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  

```
Set{OpaqueExpressionFeatureValue_Mapping.getMapped(from) ,  
  OpaqueExpressionFeatureFeatureMembership_Mapping.getMapped(from) }
```

### 7.7.14.3.20 OpaqueExpressionFeatureFeature\_Mapping

#### Description

The mapping class creates the Feature of the FeatureReferenceExpression.

## General Mappings

GenericToFeature\_Mapping

## Mapping Source

OpaqueExpression

## Mapping Target

Feature

## Owned Mappings

(none)

### 7.7.14.3.21 OpaqueExpressionFeatureFeatureMembership\_Mapping

#### Description

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- CalculationUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{OpaqueExpressionMembership_Mapping.getMapped(from),  
  OpaqueExpressionReferenceUsageReturnParameterMembership_Mapping.getMapped(from)}  
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
```

#### 7.7.14.3.19 OpaqueExpressionFeature\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates the feature of the FeatureChainExpression.

##### General Mappings

ToFeature\_Init  
Mapping

##### Mapping Source

OpaqueExpression

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  

```
Set{OpaqueExpressionFeatureValue_Mapping.getMapped(from),  
  OpaqueExpressionFeatureFeatureMembership_Mapping.getMapped(from)}
```

#### 7.7.14.3.20 OpaqueExpressionFeatureFeature\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates the Feature of the FeatureReferenceExpression.

##### General Mappings

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

**Generic**ToFeatureMembership\_Mapping

### Mapping Source

OpaqueExpression

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`OpaqueExpressionFeatureFeature_Mapping.getMapped (from)`

## 7.7.14.3.22 OpaqueExpressionFeatureValue\_Mapping

### Description

Creates a feature value relationship.

### General Mappings

**Generic**ToFeatureValue\_Mapping

### Mapping Source

OpaqueExpression

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

ToFeature\_Init  
Mapping

#### Mapping Source

OpaqueExpression

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.7.14.3.21 OpaqueExpressionFeatureFeatureMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

OpaqueExpression

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
    OpaqueExpressionFeatureFeature\_Mapping.getMapped(from)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
OpaqueExpressionFeatureValueExpression_Mapping.getMapped(from)
```

### 7.7.14.3.23 OpaqueExpressionFeatureValueExpression\_Mapping

#### Description

The mapping class creates the value of the `FeatureChainExpression` that is a `FeatureReferenceExpression`.

#### General Mappings

`GenericToExpression_Mapping`

#### Mapping Source

`OpaqueExpression`

#### Mapping Target

`FeatureReferenceExpression`

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set { OpaqueExpressionFeatureValueExpressionMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

### 7.7.14.3.24 OpaqueExpressionFeatureValueExpressionMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

`GenericToMembership_Mapping`

#### Mapping Source

#### 7.7.14.3.22 OpaqueExpressionFeatureValue\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature value relationship.

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

OpaqueExpression

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
OpaqueExpressionFeatureValueExpression_Mapping.getMapped(from)
```

#### 7.7.14.3.23 OpaqueExpressionFeatureValueExpression\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class creates the value of the FeatureChainExpression that is a FeatureReferenceExpression.

##### General Mappings

ToExpression\_Init  
Mapping

##### Mapping Source

OpaqueExpression

##### Mapping Target

OpaqueExpression

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]

from

## 7.7.14.3.25 OpaqueExpressionMembership\_Mapping

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

GenericToOwningMembership\_Mapping

### Mapping Source

OpaqueExpression

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]



FeatureReferenceExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureReferenceExpression::ownedRelationship () : Relationship [0..\*]  

```
Set{OpaqueExpressionFeatureValueExpressionMembership_Mapping.getMapped(from) ,  
ReturnParameterFeatureMembership_Factory.create() }
```

#### 7.7.14.3.24 OpaqueExpressionFeatureValueExpressionMembership\_Mapping

[SYSML2 -220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToMembership\_Init  
Mapping

### Mapping Source

OpaqueExpression

### Mapping Target

Membership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Membership::memberElement () : Element [1]  

```
from
```

`OpaqueExpressionSpecification_Mapping.getMapped(from)`

#### 7.7.14.3.26 OpaqueExpressionParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic** ToParameterMembership\_Mapping

##### Mapping Source

OpaqueExpression

##### Mapping Target

ParameterMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]

`OpaqueExpressionFeature_Mapping.getMapped(from)`

#### 7.7.14.3.27 OpaqueExpressionReferenceUsageReturnParameterMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic** ToReturnParameterMembership\_Mapping

##### Mapping Source

OpaqueExpression

##### Mapping Target

ReturnParameterMembership

##### Owned Mappings

#### 7.7.14.3.25 OpaqueExpressionMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToOwningMembership\_Init  
Mapping

##### Mapping Source

OpaqueExpression

##### Mapping Target

OwningMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`OpaqueExpressionSpecification_Mapping.getMapped (from)`

#### 7.7.14.3.26 OpaqueExpressionParameterMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

ToParameterMembership\_Init  
Mapping

##### Mapping Source

OpaqueExpression

##### Mapping Target

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReturnParameterMembership::ownedMemberParameter () : Feature [1]  

```
if from.type.ocliIsUndefined() then
    OpaqueExpressionReferenceUsageUntyped_Mapping.getMapped(from)
else
    OpaqueExpressionReferenceUsage_Mapping.getMapped(from)
endif
```

### 7.7.14.3.28 OpaqueExpressionReferenceUsage\_Mapping

#### Description

The mapping class creates the return parameter reference usage of the calculation usage.

#### General Mappings

**Generic**ToReferenceUsage\_Mapping

#### Mapping Source

OpaqueExpression

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{OpaqueExpressionReferenceUsageFeatureTyping_Mapping.getMapped(from) }
```
- ReferenceUsage::direction () : FeatureDirectionKind [0..1]  

```
KerML::FeatureDirectionKind::_out'
```

ParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ParameterMembership::ownedMemberParameter () : Feature [1]  
`OpaqueExpressionFeature_Mapping.getMapped(from)`

### 7.7.14.3.27 OpaqueExpressionReferenceUsageReturnParameterMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToReturnParameterMembership\_Init  
Mapping

### Mapping Source

OpaqueExpression

### Mapping Target

ReturnParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReturnParameterMembership::ownedMemberParameter () : Feature [1]  
`if from.type.ocIsUndefined() then`  
`OpaqueExpressionReferenceUsageUntyped_Mapping.getMapped(from)`

#### 7.7.14.3.29 OpaqueExpressionReferenceUsageFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

TypedElementFeatureTyping\_Mapping

##### Mapping Source

OpaqueExpression

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

#### 7.7.14.3.30 OpaqueExpressionReferenceUsageUntyped\_Mapping

##### Description

The mapping class creates the return parameter reference usage of the calculation usage, if the UML4SysML::OpaqueExpression is untyped.

##### General Mappings

GenericToReferenceUsage\_Mapping

##### Mapping Source

OpaqueExpression

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

```

else
    OpaqueExpressionReferenceUsage_Mapping.getMapped(from)
endif

```

#### 7.7.14.3.28 OpaqueExpressionReferenceUsage\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### **Description**

The mapping class creates the return parameter reference usage of the calculation usage.

#### **General Mappings**

ToReferenceUsage\_Init  
Mapping

#### **Mapping Source**

OpaqueExpression

#### **Mapping Target**

ReferenceUsage

#### **Owned Mappings**

(none)

#### **Applicable filters**

(none)

#### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
`Set{OpaqueExpressionReferenceUsageFeatureTyping_Mapping.getMapped(from) }`
- ReferenceUsage::direction () : FeatureDirectionKind [0..1]  
`KerML::FeatureDirectionKind::_'out'`

#### 7.7.14.3.29 OpaqueExpressionReferenceUsageFeatureTyping\_Mapping

#### **Description**

Creates a feature typing relationship owned by the element *typedFeature()*.

#### **General Mappings**

TypedElementFeatureTyping\_Mapping

#### **Mapping Source**

```
KerML::FeatureDirectionKind::_out'
```

### 7.7.14.3.31 OpaqueExpressionSpecification\_Mapping

#### Description

The mapping class creates the specification of the calculation usage based on the language and body of the UML4SysML::OpaqueExpression.

#### General Mappings

GenericToTextualRepresentation\_Mapping

#### Mapping Source

OpaqueExpression

#### Mapping Target

TextualRepresentation

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TextualRepresentation::body () : String [1]  

```
if from.body->size() = 0 then invalid else from.body.get(0) endif
```
- TextualRepresentation::language () : String [1]  

```
if from.language->size() = 0 then invalid else from.language.get(0) endif
```

### 7.7.14.3.32 TimeExpression\_Mapping

#### Description

A UML4SysML::TimeExpression is mapped to a SysML v2 TriggerInvocationExpression. The details of the mapping are not specified yet.

#### General Mappings

ValueSpecification\_Mapping

#### Mapping Source

TimeExpression



OpaqueExpression

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

## 7.7.14.3.30 OpaqueExpressionReferenceUsageUntyped\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the return parameter reference usage of the calculation usage, if the UML4SysML::OpaqueExpression is untyped.

### General Mappings

ToReferenceUsage\_Init  
Mapping

### Mapping Source

OpaqueExpression

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

KerML::FeatureDirectionKind::\_out'

## 7.7.14.3.31 OpaqueExpressionSpecification\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)



## Description

The mapping class creates the specification of the calculation usage based on the language and body of the UML4SysML::OpaqueExpression.

## General Mappings

ToTextualRepresentation\_Init  
Mapping

## Mapping Source

OpaqueExpression

## Mapping Target

TextualRepresentation

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TextualRepresentation::language () : String [1]  

```
if from.language->size() = 0 then invalid else from.language.get(0) endif
```
- TextualRepresentation::body () : String [1]  

```
if from.body->size() = 0 then invalid else from.body.get(0) endif
```

### 7.7.14.3.32 TimeExpression\_Mapping

## Description

A UML4SysML::TimeExpression is mapped to a SysML v2 Expression. The details of the mapping are not specified yet.

## General Mappings

ValueSpecification\_Mapping

## Mapping Source

TimeExpression

## Mapping Target

Expression

## Mapping Target

TriggerInvocationExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- TriggerInvocationExpression::kind () : TriggerKind [1]  
SysMLv2::TriggerKind::at

### 7.7.14.3.33 ValueSpecification\_Mapping

## Description

The mapping class is the abstract base class of all mapping classes for special value specifications.

## General Mappings

NamedElementMain\_Mapping

GenericToExpression\_Mapping

## Mapping Source

ValueSpecification

## Mapping Target

Expression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Expression::ownedRelationship () : Relationship [0..\*]

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not src.owner.ocIsKindOf(UML::TimeEvent)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **Expression::ownedRelationship () : Relationship [0..\*]**

```
let ownedComments : Set(KerML::Relationship) =
  from.ownedComment->reject(c | c.annotatedElement->includes(from))
  ->collect(c| CommentOwnership_Mapping.getMapped(c)) ->asSet() in
let expression : Set(KerML::Relationship) = if from.expr.ocIsUndefined() then
  Set{}
else
  Set{ElementOwningMembership_Mapping.getMapped(from.expr)}
endif in
(if from.type.ocIsUndefined() then
  Set{CommonReturnParameterFeatureMembership_Mapping.getMapped(from)}
else
  Set{LiteralSpecificationTyping_Mapping.getMapped(from),
    CommonReturnParameterFeatureMembership_Mapping.getMapped(from)}
endif)
->union(ownedComments)
->union(expression)
```

### 7.7.14.3.33 ValueSpecification\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

The mapping class is the abstract base class of all mapping classes for special value specifications.

## General Mappings

NamedElementMain\_Mapping  
ToExpression\_Init

## Mapping Source

ValueSpecification

## Mapping Target

Expression

## Owned Mappings

```

    (if from.type.oclIsUndefined() then
      Set{CommonReturnParameterFeatureMembership_Mapping.getMapped(from)}
    else
      Set{LiteralSpecificationTyping_Mapping.getMapped(from),
        CommonReturnParameterFeatureMembership_Mapping.getMapped(from)}
    endif) -> union(self.oclAsType(ElementMain_Mapping).ownedRelationship())

```

## 7.8 Mappings from SysML v1.7 stereotypes

### 7.8.1 Overview

The following subclauses of Mappings from SysML v1.7 stereotypes are organized according to the main packages of SysML v1.

### 7.8.2 Activities

This chapter lists all mapping specifications of SysML::Activities model elements.

#### 7.8.2.1 Overview

**Table 22. List of all mappings**

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Continuous	MetadataUsage
ControlOperator	
Discrete	MetadataUsage
NoBuffer	
Optional	
Overwrite	
Probability	MetadataUsage
Rate	MetadataUsage

The following table gives an overview of which SysML v2 elements the SysML::Activities elements are transformed with which mapping class. The mapping details are specified in [7.8.2.3](#).

The justifications for the elements without mapping are given in [7.8.2.2](#).

#### 7.8.2.2 SysML::Activities elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 23. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
ControlOperator	The concept that an action can control other actions is not supported by SysML v2.
NoBuffer	Mapping is not specified yet.

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Expression::ownedRelationship () : Relationship [0..\*]  

```
(if from.type.oclIsUndefined() then
    Set{CommonReturnParameterFeatureMembership_Mapping.getMapped(from)}
else
    Set{LiteralSpecificationTyping_Mapping.getMapped(from),
        CommonReturnParameterFeatureMembership_Mapping.getMapped(from)}
endif) -> union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
```

## 7.8 Mappings from SysML v1.7 stereotypes

### 7.8.1 Overview

The following subclauses of Mappings from SysML v1.7 stereotypes are organized according to the main packages of SysML v1.

### 7.8.2 Activities

#### 7.8.2.1 Overview

[SYSML2\\_-329: Mapping overview tables are wrong](#)

Table 21. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Continuous	MetadataUsage
ControlOperator	
Discrete	MetadataUsage
NoBuffer	
Optional	
Overwrite	
Probability	MetadataUsage
Rate	MetadataUsage

#### 7.8.2.2 SysML::Activities elements not mapped

Table 22. List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
ControlOperator	The concept that an action can control other actions is not supported by SysML v2.

SysML v1 Concept	Rationale
Optional	The stereotype states that the lower multiplicity of the parameter is 0. Since the multiplicity of the parameter is transformed, the additional statement that the parameter is optional is redundant. Therefore, the stereotype is not considered in the transformation.
Overwrite	Mapping is not specified yet.

### 7.8.2.3 Mapping Specifications

#### 7.8.2.3.1 ProbabilityMetadataUsage\_Mapping

##### Description

A SysML::Activities::Probability is mapped to a SysML v2 MetadataUsage owned by the appropriate target element of the UML4SysML::ActivityEdge or UML4SysML::ParameterSet.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action def SysMLv1Activity {
    action sysMLv1Action1;
    succession sysMLv1ControlFlow1 first sysMLv1Action1 then sysMLv1Action2 {
        @SysMLv1Library::ProbabilityData {probability = 0.42;}
    }
    action sysMLv1Action2;
}

```

##### General Mappings

GenericToMetadataUsage\_Mapping

##### Mapping Source

Element

##### Mapping Target

MetadataUsage

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

##### Mapping rules



SysML v1 Concept	Rationale
NoBuffer	Mapping is not specified yet.
Optional	The stereotype states that the lower multiplicity of the parameter is 0. Since the multiplicity of the parameter is transformed, the additional statement that the parameter is optional is redundant. Therefore, the stereotype is not considered in the transformation.
Overwrite	Mapping is not specified yet.

### 7.8.2.3 Mapping Specifications

#### 7.8.2.3.1 ProbabilityMetadataUsage\_Mapping

##### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

A SysML::Activities::Probability is mapped to a SysML v2 MetadataUsage owned by the appropriate target element of the UML4SysML::ActivityEdge or UML4SysML::ParameterSet.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

action def SysMLv1Activity {
  action sysMLv1Action1;
  succession sysMLv1ControlFlow1 first sysMLv1Action1 then sysMLv1Action2 {
    @SysMLv1Library::ProbabilityData {probability = 0.42;}
  }
  action sysMLv1Action2;
}

```

##### General Mappings

ToMetadataUsage\_Init  
Mapping

##### Mapping Source

Element

##### Mapping Target

MetadataUsage

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ProbabilityMetadataUsageFeatureTyping_Mapping.getMapped(from),  
ProbabilityMetadataUsageFeatureMembership_Mapping.getMapped(from)}
```

### 7.8.2.3.2 ProbabilityMetadataUsageFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

Element

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
ProbabilityMetadataUsageReferenceUsage_Mapping.getMapped(from)
```

### 7.8.2.3.3 ProbabilityMetadataUsageFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**Generic**ToFeatureTyping\_Mapping

#### Mapping Source

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ProbabilityMetadataUsageFeatureTyping_Mapping.getMapped(from),  
ProbabilityMetadataUsageFeatureMembership_Mapping.getMapped(from)}
```

### 7.8.2.3.2 ProbabilityMetadataUsageFeatureMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_[Init](#)  
Mapping

##### Mapping Source

Element

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
ProbabilityMetadataUsageReferenceUsage_Mapping.getMapped(from)
```

### 7.8.2.3.3 ProbabilityMetadataUsageFeatureTyping\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Element

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ProbabilityData')
```

## 7.8.2.3.4 ProbabilityMetadataUsageReferenceUsage\_Mapping

### Description

Creates a reference usage.

### General Mappings

**Generic**ToReferenceUsage\_Mapping

### Mapping Source

Element

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_**Init**  
Mapping

### Mapping Source

Element

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ProbabilityData')
```

### 7.8.2.3.4 ProbabilityMetadataUsageReferenceUsage\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a reference usage.

### General Mappings

ToReferenceUsage\_**Init**  
Mapping

### Mapping Source

Element

### Mapping Target

ReferenceUsage

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{ProbabilityMetadataUsageReferenceUsageRedefinition_Mapping.getMapped(from),  
ProbabilityMetadataUsageReferenceUsageFeatureValue_Mapping.getMapped(from)}
```

### 7.8.2.3.5 ProbabilityMetadataUsageReferenceUsageFeatureValue\_Mapping

#### Description

Creates a feature value relationship.

#### General Mappings

**Generic**ToFeatureValue\_Mapping

#### Mapping Source

Element

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
let probability : OclAny =  
Helper.getTagValue(from, 'SysML::Activities::Probability', 'probability') in  
LiteralRational_Factory.create(probability)
```

### 7.8.2.3.6 ProbabilityMetadataUsageReferenceUsageRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ProbabilityMetadataUsageReferenceUsageRedefinition_Mapping.getMapped(from),  
ProbabilityMetadataUsageReferenceUsageFeatureValue_Mapping.getMapped(from)}
```

### 7.8.2.3.5 ProbabilityMetadataUsageReferenceUsageFeatureValue\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a feature value relationship.

## General Mappings

ToFeatureValue\_[Init](#)  
Mapping

## Mapping Source

Element

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

## Mapping rules

## GenericToRedefinition\_Mapping

### Mapping Source

Element

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ProbabilityData::probability')
```

## 7.8.2.3.7 ProbabilityOwningMembership\_Mapping

### Description

Creates a owning membership relationship for *ownedMemberElement()*.

### General Mappings

## GenericToOwningMembership\_Mapping

### Mapping Source

Element

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters



In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
let probability : OclAny =
  Helper.getTagValue(from, 'SysML::Activities::Probability', 'probability') in
  LiteralRational_Factory.create(probability)
```

#### 7.8.2.3.6 ProbabilityMetadataUsageReferenceUsageRedefinition\_Mapping

##### **SysML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

###### **General Mappings**

ToRedefinition\_Init  
Mapping

###### **Mapping Source**

Element

###### **Mapping Target**

Redefinition

###### **Owned Mappings**

(none)

###### **Applicable filters**

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

###### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::AttributeUsage.allInstances()
->any(m | m.qualifiedName = 'SysMLv1Library::ProbabilityData::probability')
```

#### 7.8.2.3.7 ProbabilityOwningMembership\_Mapping

##### **SysML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`

```
ProbabilityMetadataUsage_Mapping.getMapped(from)
```

### 7.8.2.3.8 RateMetadataUsage\_Mapping

#### Description

A `SysML::Activities::Rate` and the specializations `SysML::Activities::Discrete` and `SysML::Activities::Continuous` are mapped to a SysML v2 `MetadataUsage` owned by the appropriate target element of the `UML4SysML::ActivityEdge` or `UML4SysML::Parameter`.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
succession flow sysMLv1ObjectFlow of SysMLv1Block
  from sysMLv1Action1.outputValue to sysMLv1Action1.inputValue {
    @SysMLv1Library::RateData {isDiscrete = true;}
  }
```

The mapping of the rate instance value is not supported yet.

### General Mappings

#### GenericToMetadataUsage\_Mapping

#### Mapping Source

Element

#### Mapping Target

MetadataUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

Creates a owning membership relationship for *ownedMemberElement()*.

## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

Element

## Mapping Target

OwningMembership

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Probability')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ProbabilityMetadataUsage_Mapping.getMapped(from)`

### 7.8.2.3.8 RateMetadataUsage\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

A SysML::Activities::Rate and the specializations SysML::Activities::Discrete and SysML::Activities::Continuous are mapped to a SysML v2 MetadataUsage owned by the appropriate target element of the UML4SysML::ActivityEdge or UML4SysML::Parameter.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
succession flow sysMLv1ObjectFlow of SysMLv1Block
  from sysMLv1Action1.outputValue to sysMLv1Action1.inputValue {
    @SysMLv1Library::RateData {isDiscrete = true;}
  }
```

The mapping of the rate instance value is not supported yet.

## General Mappings

```

Helper.hasStereotypeApplied(src, 'SysML::Activities::Rate')
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')

```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

```

let relationships : Set(KerML::Relationship) =
  Set{RateMetadataUsageFeatureTyping_Mapping.getMapped(from)} in
if Helper.hasStereotypeApplied(from, 'SysML::Activities::Discrete') then
  relationships
->including(
  RateMetadataUsageDiscreteFeatureMembership_Mapping.getMapped(from))
else if Helper.hasStereotypeApplied(from, 'SysML::Activities::Continuous') then
  relationships
->including(
  RateMetadataUsageContinuousFeatureMembership_Mapping.getMapped(from))
else
  relationships
endif
endif

```

### 7.8.2.3.9 RateMetadataUsageContinuousFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

Element

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```

Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')

```

#### Mapping rules

ToMetadataUsage\_Init  
Mapping

### Mapping Source

Element

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Rate')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

```
let relationships : Set(KerML::Relationship) =  
    Set{RateMetadataUsageFeatureTyping_Mapping.getMapped(from)} in  
if Helper.hasStereotypeApplied(from, 'SysML::Activities::Discrete') then  
    relationships  
->including(  
        RateMetadataUsageDiscreteFeatureMembership_Mapping.getMapped(from))  
else if Helper.hasStereotypeApplied(from, 'SysML::Activities::Continuous') then  
    relationships  
->including(  
        RateMetadataUsageContinuousFeatureMembership_Mapping.getMapped(from))  
else  
    relationships  
endif  
endif
```

#### 7.8.2.3.9 RateMetadataUsageContinuousFeatureMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
RateMetadataUsageContinuousReferenceUsage_Mapping.getMapped(from)
```

#### 7.8.2.3.10 RateMetadataUsageFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

##### Mapping Source

Element

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Rate')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
LiteralBoolean_Factory.create(true)
```

#### 7.8.2.3.11 RateMetadataUsageContinuousReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

**Generic**ToReferenceUsage\_Mapping

### Mapping Source

Element

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
RateMetadataUsageContinuousReferenceUsage_Mapping.getMapped(from)
```

### 7.8.2.3.10 RateMetadataUsageFeatureValue\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_Init  
Mapping

### Mapping Source

Element

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

## Mapping Source

Element

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set {RateMetadataUsageContinuousReferenceUsageRedefinition_Mapping.getMapped(from),  
RateMetadataUsageFeatureValue_Mapping.getMapped(from) }
```

### 7.8.2.3.12 RateMetadataUsageContinuousReferenceUsageRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

**Generic**ToRedefinition\_Mapping

## Mapping Source

Element

## Mapping Target

Redefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:



```

Helper.hasStereotypeApplied(src, 'SysML::Activities::Rate')
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')

```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
LiteralBoolean_Factory.create(true)
```

### 7.8.2.3.11 RateMetadataUsageContinuousReferenceUsage\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates a reference usage.

#### General Mappings

ToReferenceUsage\_Init  
Mapping

#### Mapping Source

Element

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```

Set{RateMetadataUsageContinuousReferenceUsageRedefinition_Mapping.getMapped(from) ,
RateMetadataUsageFeatureValue_Mapping.getMapped(from) }

```

### 7.8.2.3.12 RateMetadataUsageContinuousReferenceUsageRedefinition\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::RateData::isContinuous')
```

#### 7.8.2.3.13 RateMetadataUsageDiscreteFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

Element

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
RateMetadataUsageDiscreteReferenceUsage_Mapping.getMapped(from)
```

#### 7.8.2.3.14 RateMetadataUsageDiscreteReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

## Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

## General Mappings

ToRedefinition\_Init  
Mapping

## Mapping Source

Element

## Mapping Target

Redefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- *Redefinition::redefinedFeature () : Feature [1]*

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::RateData::isContinuous')
```

### 7.8.2.3.13 RateMetadataUsageDiscreteFeatureMembership\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

Element

## Mapping Target

## GenericToReferenceUsage\_Mapping

### Mapping Source

Element

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set { RateMetadataUsageDiscreteReferenceUsageRedefinition_Mapping.getMapped(from) ,  
RateMetadataUsageFeatureValue_Mapping.getMapped(from) }
```

## 7.8.2.3.15 RateMetadataUsageDiscreteReferenceUsageRedefinition\_Mapping

### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

## GenericToRedefinition\_Mapping

### Mapping Source

Element

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`RateMetadataUsageDiscreteReferenceUsage_Mapping.getMapped(from)`

#### 7.8.2.3.14 RateMetadataUsageDiscreteReferenceUsage\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a reference usage.

### General Mappings

ToReferenceUsage\_Init  
Mapping

### Mapping Source

Element

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

### Mapping rules

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::RateData::isDiscrete')
```

#### 7.8.2.3.16 RateMetadataUsageFeatureTyping\_Mapping

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

**Generic**ToFeatureTyping\_Mapping

### Mapping Source

Element

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Rate')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::RateData')
```

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{RateMetadataUsageDiscreteReferenceUsageRedefinition_Mapping.getMapped(from),
RateMetadataUsageFeatureValue_Mapping.getMapped(from)}
```

### 7.8.2.3.15 RateMetadataUsageDiscreteReferenceUsageRedefinition\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

##### General Mappings

ToRedefinition\_Init  
Mapping

##### Mapping Source

Element

##### Mapping Target

Redefinition

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::AttributeUsage.allInstances()
->any(m | m.qualifiedName = 'SysMLv1Library::RateData::isDiscrete')
```

### 7.8.2.3.16 RateMetadataUsageFeatureTyping\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### 7.8.2.3.17 RateOwningMembership\_Mapping

#### Description

Creates a owning membership relationship for *ownedMemberElement()*.

#### General Mappings

**Generic**ToOwningMembership\_Mapping

#### Mapping Source

Element

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Rate')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`RateMetadataUsage_Mapping.getMapped(from)`

### 7.8.2.3.18 Model Libraries

#### 7.8.2.3.18.1 ControlValues

##### 7.8.2.3.18.1.1 ControlValueKind

The enumeration ControlValueKind is mapped to the SysML v2 enumeration definition SysMLv1Library::Enumerations::ControlValueKind (see [7.3.2](#)).

## 7.8.3 Allocations

This chapter lists all mapping specifications of SysML::Allocations model elements.



## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

Element

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Rate')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::RateData')
```

### 7.8.2.3.17 RateOwningMembership\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Creates a owning membership relationship for *ownedMemberElement()*.

## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

Element

## Mapping Target

OwningMembership

### 7.8.3.1 Overview

**Table 24.** List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Allocate	AllocationUsage
AllocateActivityPartition	

The following table gives an overview of which SysML v2 elements the SysML::Allocations elements are transformed with which mapping class. The mapping details are in [7.8.3.3](#).

The justifications for the elements without mapping are given in [7.8.3.2](#).

### 7.8.3.2 SysML::Allocations elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 25.** List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
AllocateActivityPartition	Mapping is not specified yet.

### 7.8.3.3 Mapping Specifications

#### 7.8.3.3.1 Allocation\_Mapping

##### Description

A SysML::Allocations::Allocate is mapped to a SysML v2 AllocationDefinition if it is an allocation between definition elements.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
    action sysMLv1Action;
}
part def SysMLv1Block {
    part sysMLv1PartProperty : AnotherSysMLv1Block;
}
part def AnotherSysMLv1Block;

// Allocation of definition
allocation def SysMLv1Allocation {
    end :>> source : SysMLv1Activity;
    end :>> target : SysMLv1Block;
}

// Allocation of usage
allocation def {
    end :>> source : SysMLv1Activity;
    end :>> target : SysMLv1Block;
    allocate source.sysMLv1Action to target.sysMLv1PartProperty;
}

// Allocation of usage to definition
```

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Activities::Rate')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Continuous')  
or Helper.hasStereotypeApplied(src, 'SysML::Activities::Discrete')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`RateMetadataUsage_Mapping.getMapped(from)`

### 7.8.2.3.18 Model Libraries

#### 7.8.2.3.18.1 ControlValues

##### 7.8.2.3.18.1.1 ControlValueKind

The enumeration `ControlValueKind` is mapped to the SysML v2 enumeration definition `SysMLv1Library::Enumerations::ControlValueKind` (see [7.3.2](#)).

## 7.8.3 Allocations

### 7.8.3.1 Overview

[SYSML2\\_-329](#): Mapping overview tables are wrong

Table 23. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Allocate	AllocationUsage
AllocateActivityPartition	

### 7.8.3.2 SysML::Allocations elements not mapped

Table 24. List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
AllocateActivityPartition	Mapping is not specified yet.

### 7.8.3.3 Mapping Specifications

#### 7.8.3.3.1 Allocation\_Mapping

##### Description

A `SysML::Allocations::Allocate` is mapped to a SysML v2 `AllocationDefinition` if it is an allocation between definition elements.

```

allocation def {
    end :>> source : SysMLv1Activity;
    end :>> target : SysMLv1Block;
    allocate source.sysMLv1Action to target;
}

```

## General Mappings

Abstraction\_Mapping

## Mapping Source

Abstraction

## Mapping Target

AllocationDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(Helper.hasStereotypeApplied(src, 'SysML::Allocations::Allocate'))
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- AllocationDefinition::ownedRelationship () : Relationship [0..\*]

```

let relationships : Set(KerML::Relationship) =
    Set{AllocationSourceFeatureMembership_Mapping.getMapped(from.client.get(0)),
        AllocationTargetFeatureMembership_Mapping.getMapped(from.supplier.get(0))}
    ->union(self.oclAsType(ElementMain_Mapping).ownedRelationship()) in
if from.client.get(0).oclIsKindOf(UML::Type) then
    relationships
else
    relationships->including(AllocationUsageFeatureMembership_Mapping.getMapped(from))
endif

```

### 7.8.3.3.2 AllocationFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

**Generic**ToFeatureMembership\_Mapping

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
action def SysMLv1Activity {
    action sysMLv1Action;
}
part def SysMLv1Block {
    part sysMLv1PartProperty : AnotherSysMLv1Block;
}
part def AnotherSysMLv1Block;

// Allocation of definition
allocation def SysMLv1Allocation {
    end :>> source : SysMLv1Activity;
    end :>> target : SysMLv1Block;
}

// Allocation of usage
allocation def {
    end :>> source : SysMLv1Activity;
    end :>> target : SysMLv1Block;
    allocate source.sysMLv1Action to target.sysMLv1PartProperty;
}
// Allocation of usage to definition
allocation def {
    end :>> source : SysMLv1Activity;
    end :>> target : SysMLv1Block;
    allocate source.sysMLv1Action to target;
}
```

## General Mappings

Abstraction\_Mapping

### Mapping Source

Abstraction

### Mapping Target

AllocationDefinition

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(Helper.hasStereotypeApplied(src, 'SysML::Allocations::Allocate'))
```

### Mapping rules

### Mapping Source

NamedElement

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`AllocationSourceReferenceUsage_Mapping.getMapped(from)`

### 7.8.3.3.3 AllocationFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**Generic**ToFeatureTyping\_Mapping

### Mapping Source

NamedElement

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- AllocationDefinition::ownedRelationship () : Relationship [0..\*]

```
let relationships : Set(KerML::Relationship) =
    Set{AllocationSourceFeatureMembership_Mapping.getMapped(from.client.get(0)),
        AllocationTargetFeatureMembership_Mapping.getMapped(from.supplier.get(0))}
    ->union(self.oclAsType(ElementMain_Mapping).ownedRelationship()) in
if from.client.get(0).oclIsKindOf(UML::Type) then
    relationships
else
    relationships->including(AllocationUsageFeatureMembership_Mapping.getMapped(from))
endif
```

### 7.8.3.3.2 AllocationFeatureMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

NamedElement

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
AllocationSourceReferenceUsage\_Mapping.getMapped(from)

### 7.8.3.3.3 AllocationFeatureTyping\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  

```

if from.ocIsKindOf (UML::Type) then
    from
else
    from.owner
endif

```

#### 7.8.3.3.4 AllocationReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

`GenericToReferenceUsage_Mapping`  
UniqueMapping

##### Mapping Source

NamedElement

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::isEnd () : Boolean [1]`  

```

true

```
- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  

```

Set { AllocationFeatureTyping_Mapping.getMapped (from) ,
AllocationSourceReferenceUsageRedefinition_Mapping.getMapped (from) }

```

#### 7.8.3.3.5 AllocationSourceReferenceUsageRedefinition\_Mapping

##### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.



### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

NamedElement

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
if from.ocIsKindOf(UML::Type) then
  from
else
  from.owner
endif
```

#### 7.8.3.3.4 AllocationReferenceUsage\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a reference usage.

### General Mappings

ToReferenceUsage\_Init  
UniqueMapping

### Mapping Source

NamedElement

### Mapping Target

## General Mappings

GenericToRedefinition\_Mapping

### Mapping Source

NamedElement

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  

```
SYSMML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'Allocations::Allocation::source')
```

## 7.8.3.3.6 AllocationTargetFeatureMembership\_Mapping

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

GenericToFeatureMembership\_Mapping

### Mapping Source

NamedElement

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::isEnd () : Boolean [1]  
`true`
- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
`Set{AllocationFeatureTyping_Mapping.getMapped(from) ,  
AllocationSourceReferenceUsageRedefinition_Mapping.getMapped(from) }`

#### 7.8.3.3.5 AllocationSourceReferenceUsageRedefinition\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

ToRedefinition\_Init

### Mapping Source

NamedElement

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
AllocationTargetReferenceUsage_Mapping.getMapped(from)
```

### 7.8.3.3.7 AllocationTargetReferenceUsage\_Mapping

#### Description

Creates a reference usage.

#### General Mappings

`GenericToReferenceUsage_Mapping`

UniqueMapping

#### Mapping Source

NamedElement

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::isEnd () : Boolean [1]`

```
true
```

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{AllocationFeatureTyping_Mapping.getMapped(from) ,  
AllocationTargetReferenceUsageRedefinition_Mapping.getMapped(from) }
```

### 7.8.3.3.8 AllocationTargetReferenceUsageRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SYSML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'Allocations::Allocation::source')
```

#### 7.8.3.3.6 AllocationTargetFeatureMembership\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_[Init](#)

##### Mapping Source

NamedElement

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
AllocationTargetReferenceUsage_Mapping.getMapped(from)
```

#### 7.8.3.3.7 AllocationTargetReferenceUsage\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a reference usage.

##### General Mappings

ToReferenceUsage\_[Init](#)

UniqueMapping

## GenericToRedefinition\_Mapping

### Mapping Source

NamedElement

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  

```
SYSMML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'Allocations::Allocation::target')
```

## 7.8.3.3.9 AllocationUsage\_Mapping

### Description

A SysML::Allocations::Allocate is mapped to a SysML v2 AllocationUsage owned by a AllocationDefinition if a usage element is source or target of the allocation relationship.

### General Mappings

## GenericToUsage\_Mapping

### Mapping Source

Abstraction

### Mapping Target

AllocationUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

### Mapping Source

NamedElement

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::isEnd () : Boolean [1]  
`true`
- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
`Set{AllocationFeatureTyping_Mapping.getMapped(from),  
AllocationTargetReferenceUsageRedefinition_Mapping.getMapped(from)}`

#### 7.8.3.3.8 AllocationTargetReferenceUsageRedefinition\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

ToRedefinition\_Init

### Mapping Source

NamedElement

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- AllocationUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{AllocationUsageSourceEndFeatureMembership_Mapping.getMapped(from.client.get(0)),  
AllocationUsageTargetEndFeatureMembership_Mapping.getMapped(from.target.get(0))}
```

#### 7.8.3.3.10 AllocationUsageEndFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToEndFeatureMembership\_Mapping

##### Mapping Source

NamedElement

##### Mapping Target

EndFeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  

```
AllocationUsageSourceFeature_Mapping.getMapped(from)
```

#### 7.8.3.3.11 AllocationUsageFeature\_Mapping

##### Description

Creates a feature element as an end of the allocation usage relationship.

##### General Mappings

**Generic**ToFeature\_Mapping

##### Mapping Source

NamedElement



## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::ReferenceUsage.allInstances()  
->any(m | m.qualifiedName = 'Allocations::Allocation::target')
```

### 7.8.3.3.9 AllocationUsage\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

A `SysML::Allocations::Allocate` is mapped to a SysML v2 `AllocationUsage` owned by a `AllocationDefinition` if a usage element is source or target of the allocation relationship.

##### General Mappings

`ToUsage_Init`  
Mapping

##### Mapping Source

Abstraction

##### Mapping Target

`AllocationUsage`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `AllocationUsage::ownedRelationship () : Relationship [0..*]`

```
Set{AllocationUsageSourceEndFeatureMembership_Mapping.getMapped(from.client.get(0)),  
AllocationUsageTargetEndFeatureMembership_Mapping.getMapped(from.target.get(0))}
```

### 7.8.3.3.10 AllocationUsageEndFeatureMembership\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
Set {AllocationUsageSourceFeatureSubsetting_Mapping.getMapped(from) }
```

### 7.8.3.3.12 AllocationUsageFeatureChaining\_Mapping

#### Description

Creates the first feature chaining element for the subsetting feature for the feature element which represents an end of the allocation usage relationship.

#### General Mappings

**Generic**ToFeatureChaining\_Mapping

#### Mapping Source

NamedElement

#### Mapping Target

FeatureChaining

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]

```
AllocationSourceReferenceUsage_Mapping.getMapped(from)
```

## General Mappings

ToEndFeatureMembership\_Init  
Mapping

## Mapping Source

NamedElement

## Mapping Target

EndFeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`AllocationUsageSourceFeature_Mapping.getMapped(from)`

### 7.8.3.3.11 AllocationUsageFeature\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a feature element as an end of the allocation usage relationship.

## General Mappings

ToFeature\_Init  
Mapping

## Mapping Source

NamedElement

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters



(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set{AllocationUsageSourceFeatureSubsetting_Mapping.getMapped(from) }
```

#### 7.8.3.3.12 AllocationUsageFeatureChaining\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates the first feature chaining element for the subsetting feature for the feature element which represents an end of the allocation usage relationship.

### General Mappings

ToFeatureChaining\_Init  
Mapping

### Mapping Source

NamedElement

### Mapping Target

FeatureChaining

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChaining::chainingFeature () : Feature [1]`

```
AllocationSourceReferenceUsage_Mapping.getMapped(from)
```

#### 7.8.3.3.13 AllocationUsageFeatureChainingChainedFeature\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

### 7.8.3.3.13 AllocationUsageFeatureChainingChainedFeature\_Mapping

#### Description

Creates the second feature chaining element for the subsetting feature for the feature element which represents an end of the allocation usage relationship.

#### General Mappings

GenericToFeatureChaining\_Mapping

#### Mapping Source

NamedElement

#### Mapping Target

FeatureChaining

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]  
from

### 7.8.3.3.14 AllocationUsageFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

FeatureMembership

#### Owned Mappings

Creates the second feature chaining element for the subsetting feature for the feature element which represents an end of the allocation usage relationship.

### General Mappings

ToFeatureChaining\_Init  
Mapping

### Mapping Source

NamedElement

### Mapping Target

FeatureChaining

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]  
from

### 7.8.3.3.14 AllocationUsageFeatureMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

Abstraction

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
AllocationUsage_Mapping.getMapped(from)
```

### 7.8.3.3.15 AllocationUsageFeatureSubsetting\_Mapping

#### Description

Creates a subsetting relationship.

#### General Mappings

GenericToReferenceSubsetting\_Mapping

#### Mapping Source

NamedElement

#### Mapping Target

ReferenceSubsetting

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::ownedRelatedElement () : Element [0..\*]

```
if from.ocIsKindOf(UML::Type) then
  Set{}
else
  Set{AllocationUsageSourceFeatureSubsettingFeature_Mapping.getMapped(from)}
endif
```

### 7.8.3.3.16 AllocationUsageFeatureSubsettingFeature\_Mapping

#### Description



### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
AllocationUsage_Mapping.getMapped(from)
```

#### 7.8.3.3.15 AllocationUsageFeatureSubsetting\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a subsetting relationship.

### General Mappings

ToReferenceSubsetting\_Init  
Mapping

### Mapping Source

NamedElement

### Mapping Target

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::ownedRelatedElement () : Element [0..\*]  

```
if from.ocIsKindOf(UML::Type) then
    Set{}
else
    Set{AllocationUsageSourceFeatureSubsettingFeature_Mapping.getMapped(from) }
endif
```

Creates the subsetting feature for the feature element which represents an end of the allocation usage relationship.

### General Mappings

**Generic**ToFeature\_Mapping

### Mapping Source

NamedElement

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  

```
Set{AllocationUsageSourceFeatureChaining_Mapping.getMapped(from) ,  
AllocationUsageFeatureChainingChainedFeature_Mapping.getMapped(from) }
```

### 7.8.3.3.17 AllocationUsageTargetEndFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

**Generic**ToEndFeatureMembership\_Mapping

### Mapping Source

NamedElement

### Mapping Target

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

### 7.8.3.3.16 AllocationUsageFeatureSubsettingFeature\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates the subsetting feature for the feature element which represents an end of the allocation usage relationship.

#### General Mappings

ToFeature\_[Init](#)  
Mapping

#### Mapping Source

NamedElement

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  

```
Set{AllocationUsageSourceFeatureChaining_Mapping.getMapped(from),  
AllocationUsageFeatureChainingChainedFeature_Mapping.getMapped(from)}
```

### 7.8.3.3.17 AllocationUsageTargetEndFeatureMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToEndFeatureMembership\_[Init](#)

#### Mapping Source

NamedElement

#### Mapping Target

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`  
`AllocationUsageTargetFeature_Mapping.getMapped(from)`

#### 7.8.3.3.18 AllocationUsageTargetFeature\_Mapping

##### Description

Creates a feature element as an end of the allocation usage relationship.

##### General Mappings

`GenericToFeature_Mapping`

##### Mapping Source

`NamedElement`

##### Mapping Target

`Feature`

##### Owned Mappings

(none)

##### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`  
`Set {AllocationUsageTargetFeatureSubsetting_Mapping.getMapped(from) }`

#### 7.8.3.3.19 AllocationUsageTargetFeatureChaining\_Mapping

##### Description

Creates the first feature chaining element for the subsetting feature for the feature element which represents an end of the allocation usage relationship.

##### General Mappings

`GenericToFeatureChaining_Mapping`

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`AllocationUsageTargetFeature_Mapping.getMapped (from)`

#### 7.8.3.3.18 AllocationUsageTargetFeature\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature element as an end of the allocation usage relationship.

### General Mappings

ToFeature\_Init

### Mapping Source

NamedElement

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]  
`Set {AllocationUsageTargetFeatureSubsetting_Mapping.getMapped (from) }`

### Mapping Source

NamedElement

### Mapping Target

FeatureChaining

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChaining::chainingFeature () : Feature [1]`  
`AllocationTargetReferenceUsage_Mapping.getMapped (from)`

### 7.8.3.3.20 AllocationUsageTargetFeatureSubsetting\_Mapping

#### Description

Creates a subsetting relationship.

#### General Mappings

`GenericToReferenceSubsetting_Mapping`

#### Mapping Source

NamedElement

#### Mapping Target

ReferenceSubsetting

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

### 7.8.3.3.19 AllocationUsageTargetFeatureChaining\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates the first feature chaining element for the subsetting feature for the feature element which represents an end of the allocation usage relationship.

#### General Mappings

ToFeatureChaining\_Init

#### Mapping Source

NamedElement

#### Mapping Target

FeatureChaining

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]  
`AllocationTargetReferenceUsage_Mapping.getMapped(from)`

### 7.8.3.3.20 AllocationUsageTargetFeatureSubsetting\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a subsetting relationship.

#### General Mappings

ToReferenceSubsetting\_Init

#### Mapping Source

NamedElement

#### Mapping Target

ReferenceSubsetting

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceSubsetting::ownedRelatedElement () : Element [0..*]`

```
if from.ocIsKindOf(UML::Type) then
    Set{}
else
    Set{AllocationUsageTargetFeatureSubsettingFeature_Mapping.getMapped(from)}
endif
```

#### 7.8.3.3.21 AllocationUsageTargetFeatureSubsettingFeature\_Mapping

##### Description

Creates the subsetting feature for the feature element which represents an end of the allocation usage relationship.

##### General Mappings

`GenericToFeature_Mapping`

##### Mapping Source

`NamedElement`

##### Mapping Target

`Feature`

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set{AllocationUsageTargetFeatureChaining_Mapping.getMapped(from),
AllocationUsageFeatureChainingChainedFeature_Mapping.getMapped(from)}
```

#### 7.8.4 Blocks

This chapter lists all mapping specifications of `SysML::Blocks` model elements.



## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::ownedRelatedElement () : Element [0..\*]

```
if from.ocIsKindOf(UML::Type) then
    Set{}
else
    Set{AllocationUsageTargetFeatureSubsettingFeature_Mapping.getMapped(from)}
endif
```

### 7.8.3.3.21 AllocationUsageTargetFeatureSubsettingFeature\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates the subsetting feature for the feature element which represents an end of the allocation usage relationship.

## General Mappings

ToFeature Init

## Mapping Source

NamedElement

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

### 7.8.4.1 Overview

**Table 26.** List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
AdjunctProperty	
BindingConnector	BindingConnectorAsUsage
Block	PartDefinition PartDefinition
BoundReference	
ClassifierBehaviorProperty	
ConnectorProperty	
DistributedProperty	
EndPathMultiplicity	
NestedConnectorEnd	
ParticipantProperty	
PropertySpecificType	
ValueType	AttributeDefinition

The following table gives an overview of which SysML v2 elements the SysML::Blocks elements are transformed with which mapping class. The mapping details are in [7.8.4.3](#)

SysML v1 defines special property concepts, but they are not stereotypes or metamodel elements and thus do not all have an explicit mapping class. The following table shows how they are mapped.

SysML v1 Property Concept	SysML v2 Element	Main Mapping Class
Property typed by a Class or Interface	OccurrenceUsage with isComposite=false	PropertyTypedByClassInterface_Mapping
Part Property	PartUsage with isComposite=true	PartProperty_Mapping
Value Property	AttributeUsage with isComposite=true	Attribute_Mapping
ConstraintProperty	AssertConstraintUsage	not defined yet
ReferenceProperty typed by a Block	PartUsage with isComposite=false	PartProperty_Mapping
ReferenceProperty typed by a ValueType	AttributeUsage with isComposite=false	Attribute_Mapping
ReferenceProperty typed by Class or Interface	OccurrenceUsage with isComposite=false	PropertyTypedByClassInterface_Mapping

The justifications for the elements without mapping are given in [7.8.4.2](#).

```
Set{AllocationUsageTargetFeatureChaining_Mapping.getMapped(from),
AllocationUsageFeatureChainingChainedFeature_Mapping.getMapped(from)}
```

## 7.8.4 Blocks

### 7.8.4.1 Overview

**[SYSML2\\_-329](#): Mapping overview tables are wrong**

**Table 25.** List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
AdjunctProperty	
BindingConnector	BindingConnectorAsUsage
Block	PartDefinition PartDefinition
BoundReference	
ClassifierBehaviorProperty	
ConnectorProperty	
DistributedProperty	
EndPathMultiplicity	
NestedConnectorEnd	
ParticipantProperty	
PropertySpecificType	
ValueType	AttributeDefinition

### 7.8.4.2 SysML::Blocks elements not mapped

**Table 26.** List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
AdjunctProperty	The concept of adjunct properties is not needed in SysML v2, where the principal of the adjunct property can be used directly in the appropriate place.
BoundReference	Mapping is not specified yet.
ClassifierBehaviorProperty	The classifier behavior is already mapped to a property which also plays the role of the classifier behavior property. Therefore, there is no explicit mapping of a classifier behavior property.
ConnectorProperty	The connector property is a special case of an adjunct property and is not mapped, just like the adjunct property.
DirectedRelationshipPropertyPath	The stereotype is abstract is therefore not mapped. The concept of the DirectedRelationshipPropertyPath is included in the SysML v2 language.
DistributedProperty	Mapping is not specified yet.

### 7.8.4.2 SysML::Blocks elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 27. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
AdjunctProperty	The concept of adjunct properties is not needed in SysML v2, where the principal of the adjunct property can be used directly in the appropriate place.
BoundReference	Mapping is not specified yet.
ClassifierBehaviorProperty	The classifier behavior is already mapped to a property which also plays the role of the classifier behavior property. Therefore, there is no explicit mapping of a classifier behavior property.
ConnectorProperty	The connector property is a special case of an adjunct property and is not mapped, just like the adjunct property.
DirectedRelationshipPropertyPath	The stereotype is abstract is therefore not mapped. The concept of the DirectedRelationshipPropertyPath is included in the SysML v2 language.
DistributedProperty	Mapping is not specified yet.
ElementPropertyPath	The stereotype is abstract is therefore not mapped. The concept of the ElementPropertyPath is included in the SysML v2 language.
EndPathMultiplicity	Mapping is not specified yet.
NestedConnectorEnd	The concept of NestedConnectorEnd is already included in the SysML v2 language. It is not required to do an explicit mapping.
ParticipantProperty	Mapping is not specified yet.
PropertySpecificType	Mapping is not specified yet.

### 7.8.4.3 Mapping Specifications

#### 7.8.4.3.1 AssociationBlock\_Mapping

##### Description

An AssociationBlock is mapped to a SysML v2 ConnectionDefinition.

The SysML::Blocks::ParticipantProperties transformation is not defined yet. Therefore, the mapping is currently identical with the mapping of UML4SysML::AssociationClass.

##### General Mappings

AssociationClass\_Mapping

SysML v1 Concept	Rationale
ElementPropertyPath	The stereotype is abstract is therefore not mapped. The concept of the ElementPropertyPath is included in the SysML v2 language.
EndPathMultiplicity	Mapping is not specified yet.
NestedConnectorEnd	The concept of NestedConnectorEnd is already included in the SysML v2 language. It is not required to do an explicit mapping.
ParticipantProperty	Mapping is not specified yet.
PropertySpecificType	Mapping is not specified yet.

### 7.8.4.3 Mapping Specifications

#### 7.8.4.3.1 AssociationBlock\_Mapping

##### Description

An AssociationBlock is mapped to a SysML v2 ConnectionDefinition.

The SysML::Blocks::ParticipantProperties transformation is not defined yet. Therefore, the mapping is currently identical with the mapping of UML4SysML::AssociationClass.

##### General Mappings

AssociationClass\_Mapping

##### Mapping Source

AssociationClass

##### Mapping Target

ConnectionDefinition

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Blocks::Block')
```

##### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

#### 7.8.4.3.2 BindingConnector\_Mapping

##### Description

## Mapping Source

AssociationClass

## Mapping Target

ConnectionDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Blocks::Block')
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.8.4.3.2 BindingConnector\_Mapping

#### Description

A SysML::Blocks::BindingConnector is mapped to a SysML v2 BindingConnectorAsUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1 {
    part sysMLv1PartProperty1 : SysMLv1Block2;
    part sysMLv1PartProperty2 : SysMLv1Block2;

    binding sysMLv1BindingConnector
        bind sysMLv1PartProperty1 = sysMLv1PartProperty2;
}
part def SysMLv1Block2;
```

## General Mappings

Connector\_Mapping

## Mapping Source

Connector

## Mapping Target

BindingConnectorAsUsage

## Owned Mappings

A SysML::Blocks::BindingConnector is mapped to a SysML v2 BindingConnectorAsUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1 {
    part sysMLv1PartProperty1 : SysMLv1Block2;
    part sysMLv1PartProperty2 : SysMLv1Block2;

    binding sysMLv1BindingConnector
        bind sysMLv1PartProperty1 = sysMLv1PartProperty2;
}
part def SysMLv1Block2;
```

## General Mappings

Connector\_Mapping

### Mapping Source

Connector

### Mapping Target

BindingConnectorAsUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Blocks::BindingConnector')
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

## 7.8.4.3.3 Block\_Mapping

### Description

A SysML::Blocks::Block is mapped to a SysML v2 PartDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part definition SysMLv1Block;
```

## General Mappings

Class\_Mapping

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Blocks::BindingConnector')
```

#### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.8.4.3.3 Block\_Mapping

#### Description

A SysML::Blocks::Block is mapped to a SysML v2 PartDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part definition SysMLv1Block;
```

#### General Mappings

Class\_Mapping

#### Mapping Source

Class

#### Mapping Target

PartDefinition

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not src.ocIsInstanceOf(UML::AssociationClass)
and Helper.hasStereotypeApplied(src, 'SysML::Blocks::Block')
and not Helper.hasStereotypeApplied(src, 'SysML::ConstraintBlocks::ConstraintBlock')
and not Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::InterfaceBlock')
```

#### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.



## Mapping Source

Class

## Mapping Target

PartDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not src.oclIsTypeOf(UML::AssociationClass)
  and Helper.hasStereotypeApplied(src, 'SysML::Blocks::Block')
  and not Helper.hasStereotypeApplied(src, 'SysML::ConstraintBlocks::ConstraintBlock')
  and not Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::InterfaceBlock')
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.8.4.3.4 EncapsulatedBlock\_Mapping

#### Description

A SysML::Block with *isEncapsulated=true* is mapped to a SysML v2 PartDefinition, and, additionally, gets a metadata feature defined by the SysML v1 library which represents the SysML v1 isEncapsulated property.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1EncapsulatedBlock {
  @SysMLv1Library::BlockData {isEncapsulated = true;}
}
```

## General Mappings

Block\_Mapping

## Mapping Source

Class

## Mapping Target

PartDefinition

## Owned Mappings

(none)

## Applicable filters

#### 7.8.4.3.4 EncapsulatedBlock\_Mapping

##### Description

A SysML::Block with *isEncapsulated=true* is mapped to a SysML v2 PartDefinition, and, additionally, gets a metadata feature defined by the SysML v1 library which represents the SysML v1 isEncapsulated property.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1EncapsulatedBlock {
  @SysMLv1Library::BlockData {isEncapsulated = true;}
}
```

##### General Mappings

Block\_Mapping

##### Mapping Source

Class

##### Mapping Target

PartDefinition

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not src.oclIsTypeOf(UML::AssociationClass) and
  Helper.hasStereotypeApplied(src, 'SysML::Blocks::Block') and
  not Helper.hasStereotypeApplied(src, 'SysML::ConstraintBlocks::ConstraintBlock') and
  not Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::InterfaceBlock') and
  Helper.getTagValue(src, 'SysML::Blocks::Block', 'isEncapsulated')
```

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PartDefinition::ownedRelationship () : Relationship [0..\*]

```
let toElementFMS: Set(UML::Element) =
  from.ownedElement->select(e | e.oclIsKindOf(UML::Property) and
    (e.oclAsType(UML::Property).redefinedProperty->size() = 0)) in
let redefinedAttributes: Set(UML::Element) =
  from.ownedElement->select(e | from.oclIsKindOf(UML::DataType) and
    (e.oclAsType(UML::Property).redefinedProperty->size() > 0)) in
let generalizations : Set(UML::Generalization) =
```

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
not src.oclIsTypeOf(UML::AssociationClass) and
  Helper.hasStereotypeApplied(src, 'SysML::Blocks::Block') and
  not Helper.hasStereotypeApplied(src, 'SysML::ConstraintBlocks::ConstraintBlock') and
  not Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::InterfaceBlock') and
  Helper.getTagValue(src, 'SysML::Blocks::Block', 'isEncapsulated')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **PartDefinition::ownedRelationship () : Relationship [0..\*]**

```
let toElementFMS: Set(UML::Element) =
  from.ownedElement->select(e | e.oclIsKindOf(UML::Property) and
    (e.oclAsType(UML::Property).redefinedProperty->size() = 0)) in
let redefinedAttributes: Set(UML::Element) =
  from.ownedElement->select(e | from.oclIsKindOf(UML::DataType) and
    (e.oclAsType(UML::Property).redefinedProperty->size() > 0)) in
let generalizations : Set(UML::Generalization) =
  from.ownedElement->select(e | e.oclIsKindOf(UML::Generalization)) in
let toElementOMS: Set(UML::Element) =
  (((from.ownedElement - toElementFMS) - redefinedAttributes) -
    generalizations) in
let relationships: Sequence(UML::Element) =
  toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS
  ->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(redefinedAttributes
  ->collect(e | AttributeRedefinedMembership_Mapping.getMapped(e)))
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e)))
->including(EncapsulatedBlockMetadataMembership_Mapping.getMapped(from)) in
if from.classifierBehavior.oclIsUndefined() then
  relationships
else
  relationships
  ->append(BehavioredClassifierFeatureMembership_Mapping.getMapped(from))
endif
```

### 7.8.4.3.5 EncapsulatedBlockMetadataMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToOwningMembership\_Init  
Mapping

#### Mapping Source

Class

```

    from.ownedElement->select(e | e.ocIsKindOf(UML::Generalization)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - redefinedAttributes) -
    generalizations) in
let relationships: Sequence(UML::Element) =
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS
    ->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(redefinedAttributes
    ->collect(e | AttributeRedefinedMembership_Mapping.getMapped(e)))
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e)))
->including(EncapsulatedBlockMetadataMembership_Mapping.getMapped(from)) in
if from.classifierBehavior.ocIsUndefined() then
    relationships
else
    relationships
    ->append(BehavioredClassifierFeatureMembership_Mapping.getMapped(from))
endif

```

#### 7.8.4.3.5 EncapsulatedBlockMetadataMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic**ToOwningMembership\_Mapping

##### Mapping Source

Class

##### Mapping Target

OwningMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement() : Element [1]  
 EncapsulatedBlockMetadata\_Mapping.getMapped(from)

#### 7.8.4.3.6 EncapsulatedBlockMetadata\_Mapping

##### Description

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`EncapsulatedBlockMetadata_Mapping.getMapped(from)`

### 7.8.4.3.6 EncapsulatedBlockMetadata\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the metadata for the property SysML::Blocks::Block::isEncapsulated.

### General Mappings

ToMetadataUsage\_Init  
Mapping

### Mapping Source

Class

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

The mapping class creates the metadata for the property SysML::Blocks::Block::isEncapsulated.

### General Mappings

**Generic**ToMetadataUsage\_Mapping

### Mapping Source

Class

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

```
Set { EncapsulatedBlockMetadataFeatureTyping_Mapping.getMapped(from) ,  
      EncapsulatedBlockMetadataFeatureMembership_Mapping.getMapped(from) }
```

#### 7.8.4.3.7 EncapsulatedBlockMetadataFeatureMembership\_Mapping

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

**Generic**ToFeatureMembership\_Mapping

### Mapping Source

Class

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

```
Set{EncapsulatedBlockMetadataFeatureTyping_Mapping.getMapped(from) ,  
EncapsulatedBlockMetadataFeatureMembership_Mapping.getMapped(from) }
```

#### 7.8.4.3.7 EncapsulatedBlockMetadataFeatureMembership\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

Class

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]

```
EncapsulatedBlockMetadataReferenceUsage_Mapping.getMapped(from)
```

#### 7.8.4.3.8 EncapsulatedBlockMetadataFeatureTyping\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

ToFeatureTyping\_Init  
Mapping

##### Mapping Source

Class

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [0..1]`  
`EncapsulatedBlockMetadataReferenceUsage_Mapping.getMapped(from)`

#### 7.8.4.3.8 EncapsulatedBlockMetadataFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

`GenericToFeatureTyping_Mapping`

##### Mapping Source

Class

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`SysML2::MetadataDefinition.allInstances()`  
`->any(m | m.qualifiedName = 'SysMLv1Library::BlockData')`

#### 7.8.4.3.9 EncapsulatedBlockMetadataReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

`GenericToReferenceUsage_Mapping`



### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::BlockData')
```

### 7.8.4.3.9 EncapsulatedBlockMetadataReferenceUsage\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a reference usage.

### General Mappings

ToReferenceUsage\_Init  
Mapping

### Mapping Source

Class

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

### Mapping Source

Class

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { EncapsulatedBlockMetadataRedefinition_Mapping.getMapped (from) ,  
      EncapsulatedBlockMetadataFeatureValue_Mapping.getMapped (from) }
```

#### 7.8.4.3.10 EncapsulatedBlockMetadataFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

### Mapping Source

Class

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

```
Set{EncapsulatedBlockMetadataRedefinition_Mapping.getMapped(from),  
EncapsulatedBlockMetadataFeatureValue_Mapping.getMapped(from)}
```

#### 7.8.4.3.10 EncapsulatedBlockMetadataFeatureValue\_Mapping

**[SYSML2 -220](#): Replace Generic mapping classes by Initializers**

##### Description

Creates a feature value relationship.

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

Class

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
LiteralBoolean_Factory.create(true)
```

#### 7.8.4.3.11 EncapsulatedBlockMetadataRedefinition\_Mapping

**[SYSML2 -220](#): Replace Generic mapping classes by Initializers**

##### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

##### General Mappings

ToRedefinition\_Init  
Mapping

##### Mapping Source

Class

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
LiteralBoolean_Factory.create(true)
```

#### 7.8.4.3.11 EncapsulatedBlockMetadataRedefinition\_Mapping

##### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

##### General Mappings

**Generic**ToRedefinition\_Mapping

##### Mapping Source

Class

##### Mapping Target

Redefinition

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::BlockData::isEncapsulated')
```

#### 7.8.4.3.12 PartProperty\_Mapping

##### Description

A UML4SysML::Property which is typed by a block is mapped to a SysML::PartUsage. The derived property Property::isComposite is directly mapped to PartUsage::isComposite.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1 {  
    part sysMLv1PartProperty1 : SysMLv1Block2;  
    ref part sysMLv1ReferencedPartProperty2 : SysMLv1Block2;
```

## Mapping Target

Redefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  
`SysML2::AttributeUsage.allInstances()`  
`->any(m | m.qualifiedName = 'SysMLv1Library::BlockData::isEncapsulated')`

### 7.8.4.3.12 FlowPropertyPart\_Mapping

#### **SysML2\_-76: Transformation does not cover SysMLv1::FlowProperty**

#### **Description**

A `UML4SysML::Property` which is typed by a block and to which the SysML v1 stereotype `FlowProperty` has been applied is mapped as in the general mapping class `PartProperty_Mapping` but the target feature is always referential and the flow direction specified in the stereotype `FlowProperty` is considered.

#### **General Mappings**

`PartProperty_Mapping`

#### **Mapping Source**

`Property`

#### **Mapping Target**

`PartUsage`

#### **Owned Mappings**

(none)

#### **Applicable filters**

This mapping applies only if the following (OCL) condition implemented by the operation `filter(src : Element) : Boolean` is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::FlowProperty')
and not src.type.ocIsUndefined()
and src.type.ocIsKindOf(UML::Class)
```

```
}  
part def SysMLv1Block2;
```

## General Mappings

PropertyTypedByClassInterface\_Mapping

## Mapping Source

Property

## Mapping Target

PartUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.ocIsKindOf(UML::Property) and not src.ocIsKindOf(UML::Port) then  
    let p: UML::Property = src.ocAsType(UML::Property) in  
        not p.type.ocIsUndefined() and  
        Helper.hasStereotypeApplied(p.type, 'SysML::Blocks::Block') and  
        (p.association.ocIsUndefined() or p.association.ownedEnd->excludes(p))  
else  
    false  
endif
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.8.4.3.13 Model Libraries

#### 7.8.4.3.13.1 PrimitiveValueTypes

The SysML v1 model library PrimitiveValueTypes contains primitive types that are mapped to the appropriate scalar values in SysML v2.

##### 7.8.4.3.13.1.1 Boolean

The SysML v1 primitive type Boolean is mapped to the SysML v2 ScalarValues::Boolean element.

##### 7.8.4.3.13.1.2 Complex

The SysML v1 primitive type Complex is mapped to the SysML v2 ScalarValues::Complex element.

##### 7.8.4.3.13.1.3 Integer

The SysML v1 primitive type Integer is mapped to the SysML v2 ScalarValues::Integer element.

```
and Helper.hasStereotypeApplied(src.type, 'SysML::Blocks::Block')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PartUsage::direction () : FeatureDirectionKind [0..1]`  

```
Helper.getFlowDirectionKind(  
  Helper.getTagValue(from,  
    'SysML::Ports&Flows::FlowProperty', 'direction'))
```
- `PartUsage::isComposite () : Boolean [1]`  

```
false
```

### 7.8.4.3.13 PartProperty\_Mapping

#### Description

A UML4SysML::Property which is typed by a block is mapped to a SysML::PartUsage. The derived property Property::isComposite is directly mapped to PartUsage::isComposite.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part def SysMLv1Block1 {  
  part sysMLv1PartProperty1 : SysMLv1Block2;  
  ref part sysMLv1ReferencedPartProperty2 : SysMLv1Block2;  
}  
part def SysMLv1Block2;
```

#### General Mappings

PropertyTypedByClassInterface\_Mapping

#### Mapping Source

Property

#### Mapping Target

PartUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

#### 7.8.4.3.13.1.4 Number

The SysML v1 primitive type Number is abstract. Therefore, no mapping is defined for it.

#### 7.8.4.3.13.1.5 Real

The SysML v1 primitive type Real is mapped to the SysML v2 ScalarValues::Real element.

#### 7.8.4.3.13.1.6 String

The SysML v1 primitive type String is mapped to the SysML v2 ScalarValues::String element.

#### 7.8.4.3.13.2 UnitAndQuantityKind

The SysML v1 model library UnitAndQuantityKind contains the blocks Unit and QuantityKind.

##### 7.8.4.3.13.2.1 QuantityKind

The mapping of the SysML v1 QuantityKind element is not specified yet.

##### 7.8.4.3.13.2.2 Unit

The mapping of the SysML v1 QuantityKind element is not specified yet.

#### 7.8.4.3.14 ValueType\_Mapping

##### Description

A SysML::Blocks::ValueType is mapped to a SysML v2 AttributeDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
attribute definition SysMLv1ValueType;
```

##### General Mappings

DataType\_Mapping

##### Mapping Source

DataType

##### Mapping Target

AttributeDefinition

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:



```

if src.ocIsKindOf(UML::Property) and not src.ocIsKindOf(UML::Port) then
  let p: UML::Property = src.ocAsType(UML::Property) in
  not p.type.ocIsUndefined() and
  Helper.hasStereotypeApplied(p.type, 'SysML::Blocks::Block') and
  (p.association.ocIsUndefined() or p.association.ownedEnd->excludes(p))
else
  false
endif

```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.8.4.3.14 Model Libraries

#### 7.8.4.3.14.1 PrimitiveValueTypes

The SysML v1 model library PrimitiveValueTypes contains primitive types that are mapped to the appropriate scalar values in SysML v2.

##### 7.8.4.3.14.1.1 Boolean

The SysML v1 primitive type Boolean is mapped to the SysML v2 ScalarValues::Boolean element.

##### 7.8.4.3.14.1.2 Complex

The SysML v1 primitive type Complex is mapped to the SysML v2 ScalarValues::Complex element.

##### 7.8.4.3.14.1.3 Integer

The SysML v1 primitive type Integer is mapped to the SysML v2 ScalarValues::Integer element.

##### 7.8.4.3.14.1.4 Number

The SysML v1 primitive type Number is abstract. Therefore, no mapping is defined for it.

##### 7.8.4.3.14.1.5 Real

The SysML v1 primitive type Real is mapped to the SysML v2 ScalarValues::Real element.

##### 7.8.4.3.14.1.6 String

The SysML v1 primitive type String is mapped to the SysML v2 ScalarValues::String element.

#### 7.8.4.3.14.2 UnitAndQuantityKind

The SysML v1 model library UnitAndQuantityKind contains the blocks Unit and QuantityKind.

##### 7.8.4.3.14.2.1 QuantityKind

The mapping of the SysML v1 QuantityKind element is not specified yet.

##### 7.8.4.3.14.2.2 Unit

The mapping of the SysML v1 QuantityKind element is not specified yet.

### 7.8.4.3.15 ValueType\_Mapping

#### Description

```
Helper.hasStereotypeApplied(from, 'SysML::Blocks::ValueType')
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

## 7.8.5 ConstraintBlocks

This chapter lists all mapping specifications of SysML::ConstraintBlocks model elements.

### 7.8.5.1 Overview

Table 28. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
ConstraintBlock	ConstraintDefinition

The following table gives an overview of which SysML v2 elements the SysML::ConstraintBlocks elements are transformed with which mapping class. The mapping details are in [7.8.5.2](#).

### 7.8.5.2 Mapping Specifications

#### 7.8.5.2.1 ConstraintBlock\_Mapping

##### Description

A SysML::ConstraintBlocks::ConstraintBlock is mapped to a SysML v2 ConstraintDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
onstraint def SysMLv1ConstraintBlock {
  in attribute a : ScalarValues::Integer;
  in attribute b : ScalarValues::Integer;
  in attribute c : ScalarValues::Integer;

  constraint constraintExpression {
    language "OCL2.0"
    /*
     * c == a + b
     */
  }
}
```

## General Mappings

Class\_Mapping

### Mapping Source

Class

### Mapping Target

ConstraintDefinition

A SysML::Blocks::ValueType is mapped to a SysML v2 AttributeDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
attribute definition SysMLv1ValueType;
```

## General Mappings

DataType\_Mapping

## Mapping Source

DataType

## Mapping Target

AttributeDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(from, 'SysML::Blocks::ValueType')
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

## 7.8.5 ConstraintBlocks

### 7.8.5.1 Overview

[SYSML2\\_-329: Mapping overview tables are wrong](#)

Table 27. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
ConstraintBlock	ConstraintDefinition

### 7.8.5.2 Mapping Specifications

#### 7.8.5.2.1 ConstraintBlock\_Mapping

##### Description

A SysML::ConstraintBlocks::ConstraintBlock is mapped to a SysML v2 ConstraintDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::ConstraintBlocks::ConstraintBlock')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConstraintDefinition::ownedRelationship () : Relationship [0..*]`

```
let generalizations : Set(UML::Generalization) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Generalization)) in
let toElementFMS : Set(UML::Element) =
    from.ownedElement
    ->select(e | e.ocIsKindOf(UML::Property) or e.ocIsKindOf(UML::Constraint)) in
let toElementOMS : Set(UML::Element) =
    (from.ownedElement - generalizations) - toElementFMS in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e)))
->including(CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from))
```

### 7.8.5.2.2 ConstraintParameter\_Mapping

#### Description

The mapping class maps SysML v1 constraint parameter to SysML v2 attribute usages.

#### General Mappings

PropertyCommon\_Mapping  
NamedElementMain\_Mapping

#### Mapping Source

Property

#### Mapping Target

AttributeUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```

onstraint def SysMLv1ConstraintBlock {
    in attribute a : ScalarValues::Integer;
    in attribute b : ScalarValues::Integer;
    in attribute c : ScalarValues::Integer;

    constraint constraintExpression {
        language "OCL2.0"
        /*
        * c == a + b
        */
    }
}

```

## General Mappings

Class\_Mapping

## Mapping Source

Class

## Mapping Target

ConstraintDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::ConstraintBlocks::ConstraintBlock')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConstraintDefinition::ownedRelationship () : Relationship [0..\*]

```

let generalizations : Set(UML::Generalization) =
    from.ownedElement->select(e | e.oclIsKindOf(UML::Generalization)) in
let toElementFMS : Set(UML::Element) =
    from.ownedElement
    ->select(e | e.oclIsKindOf(UML::Property) or e.oclIsKindOf(UML::Constraint)) in
let toElementOMS: Set(UML::Element) =
    (from.ownedElement - generalizations) - toElementFMS in
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e)))
->including(CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from))

```

### 7.8.5.2.2 ConstraintParameter\_Mapping

#### Description

```

if src.oclIsKindOf(UML::Property) and
Helper.hasStereotypeApplied(src.owner, 'SysML::ConstraintBlocks::ConstraintBlock') then
  let p: UML::Property = src.oclAsType(UML::Property) in
    if p.type.oclIsUndefined() then
      false
    else
      true
    endif
  else
    false
endif

```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

## 7.8.6 Model Elements

This chapter lists all mapping specifications of SysML::ModelElements model elements.

### 7.8.6.1 Overview

**Table 29. List of all mappings**

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Conform	
ElementGroup	Package
Expose	
Problem	Comment
Rationale	Comment
Stakeholder	ItemDefinition
View	
Viewpoint	

The following table gives an overview of which SysML v2 elements the SysML::ModelElements elements are transformed with which mapping class. The mapping details are in [7.8.6.3](#).

The justifications for the elements without mapping are given in [7.8.6.2](#).

### 7.8.6.2 SysML::ModelElements elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 30. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
Conform	Mapping is not specified yet.
Expose	Mapping is not specified yet.
View	Mapping is not specified yet.

The mapping class maps SysML v1 constraint parameter to SysML v2 attribute usages.

### General Mappings

PropertyCommon\_Mapping  
NamedElementMain\_Mapping

### Mapping Source

Property

### Mapping Target

AttributeUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
if src.ocIsKindOf(UML::Property) and
Helper.hasStereotypeApplied(src.owner, 'SysML::ConstraintBlocks::ConstraintBlock') then
  let p: UML::Property = src.ocAsType(UML::Property) in
    if p.type.ocIsUndefined() then
      false
    else
      true
    endif
  else
    false
endif
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

## 7.8.6 Model Elements

### 7.8.6.1 Overview

**[SYSML2\\_-329: Mapping overview tables are wrong](#)**

Table 28. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Conform	
ElementGroup	Package
Expose	
Problem	Comment
Rationale	Comment

### 7.8.6.3 Mapping Specifications

#### 7.8.6.3.1 ProblemRationaleMetadataFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

Comment

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]  
`ProblemRationaleMetadataReferenceUsage_Mapping.getMapped(from)`

#### 7.8.6.3.2 ProblemRationaleMetadataFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

**Generic**ToFeatureTyping\_Mapping

##### Mapping Source

Comment

##### Mapping Target

FeatureTyping

##### Owned Mappings



SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Stakeholder	ItemDefinition
View	
Viewpoint	

### 7.8.6.2 SysML::ModelElements elements not mapped

Table 29. List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
Conform	Mapping is not specified yet.
Expose	Mapping is not specified yet.
View	Mapping is not specified yet.

### 7.8.6.3 Mapping Specifications

#### 7.8.6.3.1 ProblemRationaleMetadataFeatureMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

Comment

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [0..1]  
`ProblemRationaleMetadataReferenceUsage_Mapping.getMapped(from)`

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
if Helper.hasStereotypeApplied(from, 'SysML::ModelElements::Problem') then
  SysML2::MetadataDefinition.allInstances()
  ->any(m | m.qualifiedName = 'ModelingMetadata::Issue')
else if Helper.hasStereotypeApplied(from, 'SysML::ModelElements::Rationale') then
  SysML2::MetadataDefinition.allInstances()
  ->any(m | m.qualifiedName = 'ModelingMetadata::Rationale')
else invalid endif endif
```

### 7.8.6.3.3 ProblemRationaleMetadataReferenceUsage\_Mapping

#### Description

Creates a reference usage.

#### General Mappings

**Generic**ToReferenceUsage\_Mapping

#### Mapping Source

Comment

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ProblemRationaleMetadataRedefinition_Mapping.getMapped(from),
ProblemRationaleMetadataFeatureValue_Mapping.getMapped(from) }
```

### 7.8.6.3.2 ProblemRationaleMetadataFeatureTyping\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

ToFeatureTyping\_Init  
Mapping

#### Mapping Source

Comment

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
if Helper.hasStereotypeApplied(from, 'SysML::ModelElements::Problem') then
  SYSML2::MetadataDefinition.allInstances()
  ->any(m | m.qualifiedName = 'ModelingMetadata::Issue')
else if Helper.hasStereotypeApplied(from, 'SysML::ModelElements::Rationale') then
  SYSML2::MetadataDefinition.allInstances()
  ->any(m | m.qualifiedName = 'ModelingMetadata::Rationale')
else invalid endif endif
```

### 7.8.6.3.3 ProblemRationaleMetadataReferenceUsage\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a reference usage.

#### General Mappings

ToReferenceUsage\_Init  
Mapping

#### 7.8.6.3.4 ProblemRationaleMetadataFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

**Generic**ToFeatureValue\_Mapping

##### Mapping Source

Comment

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  
`LiteralString_Factory.create(from.body)`

#### 7.8.6.3.5 ProblemRationaleMetadataMembership\_Mapping

##### Description

Creates a membership relationship for *memberElement()*.

##### General Mappings

**Generic**ToOwningMembership\_Mapping

##### Mapping Source

Comment

##### Mapping Target

OwningMembership

##### Owned Mappings

(none)

### Mapping Source

Comment

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{ProblemRationaleMetadataRedefinition_Mapping.getMapped(from),  
ProblemRationaleMetadataFeatureValue_Mapping.getMapped(from) }
```

### 7.8.6.3.4 ProblemRationaleMetadataFeatureValue\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_[Init](#)  
Mapping

### Mapping Source

Comment

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`ProblemRationaleMetadataUsage_Mapping.getMapped(from)`

### 7.8.6.3.6 Concern\_Mapping

#### Description

The concern comments of a SysML::ModelElements::Stakeholder or a SysML::ModelElements::Viewpoint are mapped to SysML v2 ConcernUsages. The concern comments of the stakeholder are mapped to ConcernUsages which reference the stakeholder item definition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
item def SysMLv1Stakeholder {  
    @SysMLv1Library::StakeholderData {isStakeholder = true;}  
}  
concern concernCommentXMI_ID {  
    doc /* concern string */  
    stakeholder : SysMLv1Stakeholder;  
}
```

#### General Mappings

Comment\_Mapping

#### Mapping Source

Comment

#### Mapping Target

ConcernUsage

#### Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(not Helper.hasStereotypeApplied(src, 'SysML::ModelElements::ElementGroup')) and  
(UML::Classifier.allInstances())
```

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`LiteralString_Factory.create (from.body)`

#### 7.8.6.3.5 ProblemRationaleMetadataMembership\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a membership relationship for *memberElement()*.

###### **General Mappings**

ToOwningMembership\_Init  
Mapping

###### **Mapping Source**

Comment

###### **Mapping Target**

OwningMembership

###### **Owned Mappings**

(none)

###### **Applicable filters**

(none)

###### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`ProblemRationaleMetadataUsage_Mapping.getMapped (from)`

#### 7.8.6.3.6 Concern\_Mapping

###### **Description**

The concern comments of a SysML::ModelElements::Stakeholder or a SysML::ModelElements::Viewpoint are mapped to SysML v2 ConcernUsages. The concern comments of the stakeholder are mapped to ConcernUsages which reference the stakeholder item definition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

->select(s |
    Helper.hasStereotypeApplied(s, 'SysML::ModelElements::Stakeholder'))
->collect(c |
    Helper.getTagValue(c, 'SysML::ModelElements::Stakeholder', 'concernList'))
->flatten()
->includes(src) or
(UML::Classifier.allInstances()
->select(s |
    Helper.hasStereotypeApplied(s, 'SysML::ModelElements::Viewpoint'))
->collect(c |
    Helper.getTagValue(c, 'SysML::ModelElements::Viewpoint', 'concernList'))
->flatten()->includes(src))

```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConcernUsage::ownedRelationship () : Relationship [0..\*]

```

let toStakeholderMS : Set(UML::Classifier) =
    UML::Classifier.allInstances()
    ->select(s |
        Helper.hasStereotypeApplied(s, 'SysML::ModelElements::Stakeholder'))
    ->select(s |
        Helper.getTagValue(s, 'SysML::ModelElements::Stakeholder', 'concernList')
        ->flatten()->includes(from))->asSet() in
toStakeholderMS
->including(
    CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from))
->including(EmptySubjectMembership_Factory.create())
->union(self.oclAsType(Comment_Mapping).ownedRelationship())

```

### 7.8.6.3.7 ConcernDocumentation\_Mapping

#### Description

The mapping class creates the documentation element with the body string of the UML4SysML::Comment model element representing a concern.

#### General Mappings

**Generic**ToDocumentation\_Mapping

#### Mapping Source

Comment

#### Mapping Target

Documentation

#### Owned Mappings



```

item def SysMLv1Stakeholder {
    @SysMLv1Library::StakeholderData {isStakeholder = true;}
}
concern concernCommentXMI_ID {
    doc /* concern string */
    stakeholder : SysMLv1Stakeholder;
}

```

## General Mappings

Comment\_Mapping

## Mapping Source

Comment

## Mapping Target

ConcernUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```

(not Helper.hasStereotypeApplied(src, 'SysML::ModelElements::ElementGroup')) and
((UML::Classifier.allInstances()
->select(s |
    Helper.hasStereotypeApplied(s, 'SysML::ModelElements::Stakeholder'))
->collect(c |
    Helper.getTagValue(c, 'SysML::ModelElements::Stakeholder', 'concernList'))
->flatten()
->includes(src)) or
(UML::Classifier.allInstances()
->select(s |
    Helper.hasStereotypeApplied(s, 'SysML::ModelElements::Viewpoint'))
->collect(c |
    Helper.getTagValue(c, 'SysML::ModelElements::Viewpoint', 'concernList'))
->flatten()->includes(src)))

```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConcernUsage::ownedRelationship () : Relationship [0..\*]

```

let toStakeholderMS : Set(UML::Classifier) =
    UML::Classifier.allInstances()
->select(s |
    Helper.hasStereotypeApplied(s, 'SysML::ModelElements::Stakeholder'))

```

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Documentation::body () : String [1]

`from.body`

### 7.8.6.3.8 ConcernOwningMembership\_Mapping

#### Description

Creates a owning membership relationship for *ownedMemberElement()*.

#### General Mappings

**Generic**ToOwningMembership\_Mapping

#### Mapping Source

Comment

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

`ConcernDocumentation_Mapping.getMapped(from)`

### 7.8.6.3.9 ConcernStakeholderMembership\_Mapping

#### Description

```

->select(s |
    Helper.getTagValue(s, 'SysML::ModelElements::Stakeholder', 'concernList')
->flatten()->includes(from))->asSet() in
toStakeholderMS
->including(
    CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from))
->including(EmptySubjectMembership_Factory.create())
->union(self.oclAsType(Comment_Mapping).ownedRelationship())

```

### 7.8.6.3.7 ConcernDocumentation\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

The mapping class creates the documentation element with the body string of the UML4SysML::Comment model element representing a concern.

##### **General Mappings**

ToDocumentation\_Init  
Mapping

##### **Mapping Source**

Comment

##### **Mapping Target**

Documentation

##### **Owned Mappings**

(none)

##### **Applicable filters**

(none)

##### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Documentation::body () : String [1]

from.body

### 7.8.6.3.8 ConcernOwningMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

Creates a membership relationship for *memberElement()*.

### General Mappings

**Generic**ToParameterMembership\_Mapping

### Mapping Source

Classifier

### Mapping Target

StakeholderMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- StakeholderMembership::ownedMemberParameter () : Feature [1]

`ConcernStakeholderPartUsage_Mapping.getMapped (from)`

### 7.8.6.3.10 ConcernStakeholderPartUsage\_Mapping

#### Description

In SysML v1, the stakeholder element has concerns. In SysML v2, the Concern element has stakeholders. This mapping class creates a PartUsage of the type of the stakeholder for the concern element.

### General Mappings

**Generic**ToPartUsage\_Mapping

### Mapping Source

Classifier

### Mapping Target

PartUsage

### Owned Mappings

(none)

### Applicable filters

Creates a owning membership relationship for *ownedMemberElement()*.

### General Mappings

ToOwningMembership\_Init  
Mapping

### Mapping Source

Comment

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ConcernDocumentation_Mapping.getMapped(from)`

### 7.8.6.3.9 ConcernStakeholderMembership\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToParameterMembership\_Init  
Mapping

### Mapping Source

Classifier

### Mapping Target

StakeholderMembership

### Owned Mappings

(none)

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PartUsage::ownedRelationship () : Relationship [0..*]`

```
Set { ConcernStakeholderPartUsageFeatureTyping_Mapping.getMapped (from) ,  
      ConcernStakeholderPartUsageOwningMembership_Mapping.getMapped (from) }
```

#### 7.8.6.3.11 ConcernStakeholderPartUsageFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

**Generic**ToFeatureTyping\_Mapping

##### Mapping Source

Classifier

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
from
```

#### 7.8.6.3.12 ConcernStakeholderPartUsageOwningMembership\_Mapping

##### Description

Creates a owning membership relationship for *ownedMemberElement()*.

##### General Mappings

**Generic**ToOwningMembership\_Mapping

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- StakeholderMembership::ownedMemberParameter () : Feature [1]  
`ConcernStakeholderPartUsage_Mapping.getMapped(from)`

### 7.8.6.3.10 ConcernStakeholderPartUsage\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

In SysML v1, the stakeholder element has concerns. In SysML v2, the Concern element has stakeholders. This mapping class creates a PartUsage of the type of the stakeholder for the concern element.

## General Mappings

ToPartUsage\_Init  
Mapping

## Mapping Source

Classifier

## Mapping Target

PartUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PartUsage::ownedRelationship () : Relationship [0..\*]  
`Set{ConcernStakeholderPartUsageFeatureTyping_Mapping.getMapped(from),  
ConcernStakeholderPartUsageOwningMembership_Mapping.getMapped(from)}`

### 7.8.6.3.11 ConcernStakeholderPartUsageFeatureTyping\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Mapping Source

Classifier

## Mapping Target

OwningMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ConcernStakeholderPartUsageFeature_Mapping.getMapped (from)`

### 7.8.6.3.13 ConcernStakeholderPartUsageFeature\_Mapping

#### Description

The mapping class creates a feature element for the concern stakeholder part usage.

#### General Mappings

**Generic**ToFeature\_Mapping

## Mapping Source

Classifier

## Mapping Target

Multiplicity

## Owned Mappings

(none)

### 7.8.6.3.14 ElementGroup\_Mapping

#### Description

A SysML::ModelElements::ElementGroup element is mapped to a SysML v2 Package with membership import relationships representing the grouping.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.



## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

Classifier

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

from

### 7.8.6.3.12 ConcernStakeholderPartUsageOwningMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a owning membership relationship for *ownedMemberElement()*.

## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

Classifier

## Mapping Target

OwningMembership

## Owned Mappings



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`ConcernStakeholderPartUsageFeature_Mapping.getMapped(from)`

### 7.8.6.3.13 ConcernStakeholderPartUsageFeature\_Mapping

**SysML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates a feature element for the concern stakeholder part usage.

#### General Mappings

ToFeature\_Init  
Mapping

#### Mapping Source

Classifier

#### Mapping Target

Multiplicity

#### Owned Mappings

(none)

#### Applicable filters

(none)

### 7.8.6.3.14 ElementGroup\_Mapping

#### Description

A `SysML::ModelElements::ElementGroup` element is mapped to a SysML v2 Package with membership import relationships representing the grouping.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
package ElementGroupModel {  
    part def SysMLv1Block1;  
    attribute def SysMLv1ValueType;
```

```

package ElementGroupModel {
  part def SysMLv1Block1;
  attribute def SysMLv1ValueType;
  part def SysMLv1Block2 {
    part sysMLv1PartProperty:SysMLv1Block1;
  }
}

package SysMLv1ElementGroup {
  import ElementGroupModel::SysMLv1Block1;
  import ElementGroupModel::SysMLv1ValueType;
  import ElementGroupModel::SysMLv1Block2::sysMLv1PartProperty;

  @SysMLv1Library::ElementGroupData {criterion = "criterion string";}
}

```

## General Mappings

Comment\_Mapping

## Mapping Source

Comment

## Mapping Target

Package

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::ModelElements::ElementGroup')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Package::declaredName () : String [0..1]

```
Helper.getTagValueAsString(from, 'SysML::ModelElements::ElementGroup', 'name')
```

- Package::ownedRelationship () : Relationship [0..\*]

```

let elements : Set(KerML::Relationahip) =
  Helper.getTagValueAsElementColl(from,
    'SysML::ModelElements::ElementGroup', 'member')
  ->collect(e | CommonElementImport_Mapping.getMapped(e)) in
elements->including(ElementGroupMetadaMembership_Mapping.getMapped(from))
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())

```

```

    part def SysMLv1Block2 {
      part sysMLv1PartProperty:SysMLv1Block1;
    }
  }

package SysMLv1ElementGroup {
  import ElementGroupModel::SysMLv1Block1;
  import ElementGroupModel::SysMLv1ValueType;
  import ElementGroupModel::SysMLv1Block2::sysMLv1PartProperty;

  @SysMLv1Library::ElementGroupData {criterion = "criterion string";}
}

```

## General Mappings

Comment\_Mapping

## Mapping Source

Comment

## Mapping Target

Package

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::ModelElements::ElementGroup')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Package::declaredName () : String [0..1]  
 Helper.getTagValueAsString(from, 'SysML::ModelElements::ElementGroup', 'name')
- Package::ownedRelationship () : Relationship [0..\*]

```

let elements : Set(KerML::Relationahip) =
  Helper.getTagValueAsElementColl(from,
    'SysML::ModelElements::ElementGroup', 'member')
  ->collect(e | CommonElementImport_Mapping.getMapped(e)) in
elements->including(ElementGroupMetadaMembership_Mapping.getMapped(from))
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())

```

### 7.8.6.3.15 ElementGroupMetadaMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### 7.8.6.3.15 ElementGroupMetadaMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToOwningMembership\_Mapping

#### Mapping Source

Comment

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ElementGroupMetadataUsage_Mapping.getMapped (from)`

### 7.8.6.3.16 ElementGroupMetadataFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

Comment

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

Comment

## Mapping Target

OwningMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ElementGroupMetadataUsage_Mapping.getMapped(from)`

### 7.8.6.3.16 ElementGroupMetadataFeatureMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

Comment

## Mapping Target

FeatureMembership

## Owned Mappings

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`ElementGroupMetadataReferenceUsage_Mapping.getMapped(from)`

#### 7.8.6.3.17 ElementGroupMetadataFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

**Generic** `ToFeatureTyping_Mapping`

##### Mapping Source

Comment

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`SysML2::MetadataDefinition.allInstances()`  
`->any(m | m.qualifiedName = 'SysMLv1Library::ElementGroupData')`

#### 7.8.6.3.18 ElementGroupMetadataFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`ElementGroupMetadataReferenceUsage_Mapping.getMapped(from)`

### 7.8.6.3.17 ElementGroupMetadataFeatureTyping\_Mapping

**SysML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

ToFeatureTyping\_Init  
Mapping

#### Mapping Source

Comment

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`SysML2::MetadataDefinition.allInstances()`  
`->any(m | m.qualifiedName = 'SysMLv1Library::ElementGroupData')`

### 7.8.6.3.18 ElementGroupMetadataFeatureValue\_Mapping

**SysML2\_-220: Replace Generic mapping classes by Initializers**

## GenericToFeatureValue\_Mapping

### Mapping Source

Comment

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
let criterion: String = Helper.getTagValueAsString(from, 'SysML::ModelElements::ElementGroup')
LiteralString_Factory.create(criterion)
```

## 7.8.6.3.19 ElementGroupMetadataRedefinition\_Mapping

### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

## GenericToRedefinition\_Mapping

### Mapping Source

Comment

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

## Description

Creates a feature value relationship.

## General Mappings

ToFeatureValue\_Init  
Mapping

## Mapping Source

Comment

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
let criterion: String = Helper.getTagValueAsString(from, 'SysML::ModelElements::ElementGroup')
LiteralString_Factory.create(criterion)
```

### 7.8.6.3.19 ElementGroupMetadataRedefinition\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

## General Mappings

ToRedefinition\_Init  
Mapping

## Mapping Source

Comment

## Mapping Target

Redefinition

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **Redefinition::redefinedFeature () : Feature [1]**

```
let m : SYSML2::Membership =
  SYSML2::AttributeUsage.allInstances()
  ->collect(dt | dt.owningRelationship)
  ->select(r | r.ocIsKindOf(SYSML2::Membership))
  ->any(m | m.memberName = 'criterion') in
if (m.ocIsUndefined()) then
  invalid
else
  m.memberElement
endif
```

### 7.8.6.3.20 ElementGroupMetadataReferenceUsage\_Mapping

#### Description

Creates a reference usage.

#### General Mappings

**Generic**ToReferenceUsage\_Mapping

#### Mapping Source

Comment

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- **ReferenceUsage::ownedRelationship () : Relationship [0..\*]**

```
Set{ElementGroupMetadataRedefinition_Mapping.getMapped(from),
ElementGroupMetadataFeatureValue_Mapping.getMapped(from)}
```

### 7.8.6.3.21 ElementGroupMetadataUsage\_Mapping

#### Description

The mapping class creates the metadata usage element for the SysML::ModelElements::ElementGroup mapping.

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
let m : SYSML2::Membership =
  SYSML2::AttributeUsage.allInstances()
  ->collect(dt | dt.owningRelationship)
  ->select(r | r.ocIsKindOf(SYSML2::Membership))
  ->any(m | m.memberName = 'criterion') in
if (m.ocIsUndefined()) then
  invalid
else
  m.memberElement
endif
```

### 7.8.6.3.20 ElementGroupMetadataReferenceUsage\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a reference usage.

## General Mappings

ToReferenceUsage\_Init  
Mapping

## Mapping Source

Comment

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

## General Mappings

**Generic**ToMetadataUsage\_Mapping

### Mapping Source

Comment

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { ElementGroupMetadataFeatureTyping_Mapping.getMapped (from) ,  
      ElementGroupMetadataFeatureMembership_Mapping.getMapped (from) }
```

## 7.8.6.3.22 ProblemRationale\_Mapping

### Description

The mapping class combines the mapping of SysML::ModelElements::Problem and SysML::ModelElements::Rationale. The SysML::ModelElements::Problem is mapped to the library element ModelingMetadata::Issue and the SysML::ModelElements::Rationale is mapped to ModelingMetadata::Rationale.

The expected SysML v2 textual syntax of the mapping is as follows.

```
@ModelingMetadata::Issue {text = "This is a problem statement";}  
@ModelingMetadata::Rationale {text = "This is a rationale statement";}
```

## General Mappings

Comment\_Mapping

### Mapping Source

Comment

### Mapping Target

Comment

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set {ElementGroupMetadataRedefinition_Mapping.getMapped (from) ,`  
`ElementGroupMetadataFeatureValue_Mapping.getMapped (from) }`

#### 7.8.6.3.21 ElementGroupMetadataUsage\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class creates the metadata usage element for the SysML::ModelElements::ElementGroup mapping.

##### General Mappings

ToMetadataUsage\_Init  
Mapping

##### Mapping Source

Comment

##### Mapping Target

MetadataUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `MetadataUsage::ownedRelationship () : Relationship [0..*]`  
`Set {ElementGroupMetadataFeatureTyping_Mapping.getMapped (from) ,`  
`ElementGroupMetadataFeatureMembership_Mapping.getMapped (from) }`

#### 7.8.6.3.22 ProblemRationale\_Mapping

##### Description

The mapping class combines the mapping of SysML::ModelElements::Problem and SysML::ModelElements::Rationale. The SysML::ModelElements::Problem is mapped to the library element ModelingMetadata::Issue and the SysML::ModelElements::Rationale is mapped to ModelingMetadata::Rationale.

The expected SysML v2 textual syntax of the mapping is as follows.

```
@ModelingMetadata::Issue {text = "This is a problem statement";}
```

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(not Helper.hasStereotypeApplied(src, 'SysML::ModelElements::ElementGroup')) and  
(Helper.hasStereotypeApplied(src, 'SysML::ModelElements::Problem') or  
Helper.hasStereotypeApplied(src, 'SysML::ModelElements::Rationale'))
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Comment::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()  
->including(ProblemRationaleMetadataMembership_Mapping.getMapped(from))
```

### 7.8.6.3.23 ProblemRationaleMetadataRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

GenericToRedefinition\_Mapping

#### Mapping Source

Comment

#### Mapping Target

Redefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]



```
@ModelingMetadata::Rationale {text = "This is a rationale statement";}
```

### General Mappings

Comment\_Mapping

### Mapping Source

Comment

### Mapping Target

Comment

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(not Helper.hasStereotypeApplied(src, 'SysML::ModelElements::ElementGroup')) and  
(Helper.hasStereotypeApplied(src, 'SysML::ModelElements::Problem') or  
Helper.hasStereotypeApplied(src, 'SysML::ModelElements::Rationale'))
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Comment::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()  
->including(ProblemRationaleMetadataMembership_Mapping.getMapped(from))
```

#### 7.8.6.3.23 ProblemRationaleMetadataRedefinition\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

ToRedefinition\_Init  
Mapping

### Mapping Source

Comment

### Mapping Target

```

if Helper.hasStereotypeApplied(from, 'SysML::ModelElements::Problem') then
  SysML2::AttributeUsage.allInstances()
  ->any(m | m.qualifiedName = 'ModelingMetadata::Issue::text')
else if Helper.hasStereotypeApplied(from, 'SysML::ModelElements::Rationale') then
  SysML2::AttributeUsage.allInstances()
  ->any(m | m.qualifiedName = 'ModelingMetadata::Rationale::text')
else
  invalid
endif
endif

```

#### 7.8.6.3.24 ProblemRationaleMetadataUsage\_Mapping

##### Description

The mapping class creates the metadata usage element for the SysML::ModelElements::Problem and SysML::ModelElements::Rationale transformation target.

##### General Mappings

**Generic** ToMetadataUsage\_Mapping

##### Mapping Source

Comment

##### Mapping Target

MetadataUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

```

Set{ ProblemRationaleMetadataFeatureTyping_Mapping.getMapped(from),
  ProblemRationaleMetadataFeatureMembership_Mapping.getMapped(from) }

```

#### 7.8.6.3.25 Stakeholder\_Mapping

##### Description

A SysML::ModelElements::Stakeholder is mapped to a SysML v2 ItemDefinition with metadata to tag it as a stakeholder. The concern comments of the stakeholder are mapped to ConcernUsages which reference the stakeholder item definition.

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
if Helper.hasStereotypeApplied(from, 'SysML::ModelElements::Problem') then
  SysML2::AttributeUsage.allInstances()
  ->any(m | m.qualifiedName = 'ModelingMetadata::Issue::text')
else if Helper.hasStereotypeApplied(from, 'SysML::ModelElements::Rationale') then
  SysML2::AttributeUsage.allInstances()
  ->any(m | m.qualifiedName = 'ModelingMetadata::Rationale::text')
else
  invalid
endif
endif
```

#### 7.8.6.3.24 ProblemRationaleMetadataUsage\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the metadata usage element for the SysML::ModelElements::Problem and SysML::ModelElements::Rationale transformation target.

### General Mappings

ToMetadataUsage\_Init  
Mapping

### Mapping Source

Comment

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
item def SysMLv1Stakeholder {@SysMLv1Library::StakeholderData {isStakeholder = true;}}
concern concernCommentXMI_ID {
  doc /* concern string */
  stakeholder : SysMLv1Stakeholder;
}
```

## General Mappings

Class\_Mapping

### Mapping Source

Class

### Mapping Target

ItemDefinition

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::ModelElements::Stakeholder')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ItemDefinition::ownedRelationship () : Relationship [0..\*]

```
let toElementFMS: Set(UML::Element) =
  from.ownedElement
  ->select(e | (e.ocIsKindOf(UML::Property) and
    (e.ocAsType(UML::Property).redefinedProperty->size() = 0)) or
    e.ocIsKindOf(UML::Operation)) in
let redefinedAttributes: Set(UML::Element) =
  from.ownedElement
  ->select(e | from.ocIsKindOf(UML::DataType) and
    (e.ocAsType(UML::Property).redefinedProperty->size() > 0)) in
let generalizations : Set(UML::Generalization) =
  from.ownedElement
  ->select(e | e.ocIsKindOf(UML::Generalization)) in
let constraints : Set(UML::Constraint) =
  UML::Constraint.allInstances()
  ->select( c | c.constrainedElement->includes(from)) in
let toElementOMS: Set(UML::Element) =
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ProblemRationaleMetadataFeatureTyping_Mapping.getMapped(from),  
ProblemRationaleMetadataFeatureMembership_Mapping.getMapped(from)}
```

### 7.8.6.3.25 Stakeholder\_Mapping

#### Description

A SysML::ModelElements::Stakeholder is mapped to a SysML v2 ItemDefinition with metadata to tag it as a stakeholder. The concern comments of the stakeholder are mapped to ConcernUsages which reference the stakeholder item definition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
item def SysMLv1Stakeholder {@SysMLv1Library::StakeholderData {isStakeholder = true;}}  
concern concernCommentXMI_ID {  
    doc /* concern string */  
    stakeholder : SysMLv1Stakeholder;  
}
```

#### General Mappings

Class\_Mapping

#### Mapping Source

Class

#### Mapping Target

ItemDefinition

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::ModelElements::Stakeholder')
```

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ItemDefinition::ownedRelationship () : Relationship [0..\*]

```

        (((from.ownedElement - toElementFMS) - redefinedAttributes) -
        generalizations) in
let relationships: Sequence(KerML::Relationship) =
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(constraints
        ->collect(e | ConstrainedElementFeatureMembership_Mapping.getMapped(e)))
->union(redefinedAttributes
        ->collect(e | AttributeRedefinedMembership_Mapping.getMapped(e)))
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e)))
->including(StakeholderMetadataOwningMembership_Mapping.getMapped(from)) in
if from.classifierBehavior.oclIsUndefined() then
    relationships
else
    relationships->append(BehavioredClassifierFeatureMembership_Mapping.getMapped(from))
endif

```

### 7.8.6.3.26 StakeholderMetadataUsage\_Mapping

#### Description

The mapping class creates the metadata usage element for the SysML::ModelElements::Stakeholder mapping.

#### General Mappings

**Generic**ToMetadataUsage\_Mapping

#### Mapping Source

Classifier

#### Mapping Target

MetadataUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]

```

Set{StakeholderMetadataFeatureTyping_Mapping.getMapped(from),
StakeholderMetadataFeatureMembership_Mapping.getMapped(from)}

```

### 7.8.6.3.27 StakeholderMetadataFeatureMembership\_Mapping

#### Description

```

let toElementFMS: Set(UML::Element) =
    from.ownedElement
    ->select(e | (e.ocIsKindOf(UML::Property) and
        (e.ocIsType(UML::Property).redefinedProperty->size() = 0)) or
        e.ocIsKindOf(UML::Operation)) in
let redefinedAttributes: Set(UML::Element) =
    from.ownedElement
    ->select(e | from.ocIsKindOf(UML::DataType) and
        (e.ocIsType(UML::Property).redefinedProperty->size() > 0)) in
let generalizations : Set(UML::Generalization) =
    from.ownedElement
    ->select(e | e.ocIsKindOf(UML::Generalization)) in
let constraints : Set(UML::Constraint) =
    UML::Constraint.allInstances()
    ->select( c | c.constrainedElement->includes(from)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - redefinedAttributes) -
        generalizations) in
let relationships: Sequence(KerML::Relationship) =
    toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
    ->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
    ->union(constraints
        ->collect(e | ConstrainedElementFeatureMembership_Mapping.getMapped(e)))
    ->union(redefinedAttributes
        ->collect(e | AttributeRedefinedMembership_Mapping.getMapped(e)))
    ->union(generalizations->collect(e | Generalization_Mapping.getMapped(e)))
    ->including(StakeholderMetadataOwningMembership_Mapping.getMapped(from)) in
if from.classifierBehavior.ocIsUndefined() then
    relationships
else
    relationships->append(BehavoredClassifierFeatureMembership_Mapping.getMapped(from))
endif

```

### 7.8.6.3.26 StakeholderMetadataUsage\_Mapping

#### SYSML2 -220: Replace Generic mapping classes by Initializers

##### Description

The mapping class creates the metadata usage element for the SysML::ModelElements::Stakeholder mapping.

##### General Mappings

ToMetadataUsage\_Init  
Mapping

##### Mapping Source

Classifier

##### Mapping Target

MetadataUsage

##### Owned Mappings

(none)

##### Applicable filters

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

**Generic**ToFeatureMembership\_Mapping

### Mapping Source

Classifier

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`StakeholderMetadataReferenceUsage_Mapping.getMapped(from)`

## 7.8.6.3.28 StakeholderMetadataFeatureTyping\_Mapping

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

**Generic**ToFeatureTyping\_Mapping

### Mapping Source

Classifier

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)



(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `MetadataUsage::ownedRelationship () : Relationship [0..*]`  
`Set{StakeholderMetadataFeatureTyping_Mapping.getMapped(from) ,  
StakeholderMetadataFeatureMembership_Mapping.getMapped(from) }`

#### 7.8.6.3.27 StakeholderMetadataFeatureMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_[Init](#)  
Mapping

### Mapping Source

Classifier

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`StakeholderMetadataReferenceUsage_Mapping.getMapped(from)`

#### 7.8.6.3.28 StakeholderMetadataFeatureTyping\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::StakeholderData')
```

### 7.8.6.3.29 StakeholderMetadataOwningMembership

#### Description

Creates a owning membership relationship for *ownedMemberElement()*.

#### General Mappings

`GenericToOwningMembership_Mapping`

#### Mapping Source

Classifier

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`

```
StakeholderMetadataUsage_Mapping.getMapped(from)
```

### 7.8.6.3.30 StakeholderMetadataReferenceUsage\_Mapping

#### Description

Creates a reference usage.

#### General Mappings

`GenericToReferenceUsage_Mapping`

#### Mapping Source

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

Classifier

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::StakeholderData')
```

### 7.8.6.3.29 StakeholderMetadataOwningMembership

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a owning membership relationship for *ownedMemberElement()*.

## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

Classifier

## Mapping Target

OwningMembership

## Owned Mappings

(none)

## Applicable filters

Classifier

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { StakeholderMetadataReferenceUsageRedefinition_Mapping.getMapped (from) ,  
      StakeholderMetadataReferenceUsageFeatureValue_Mapping.getMapped (from) }
```

#### 7.8.6.3.31 StakeholderMetadataReferenceUsageFeatureValue\_Mapping

### Description

Creates a feature value relationship.

### General Mappings

GenericToFeatureValue\_Mapping

### Mapping Source

Classifier

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`  
`StakeholderMetadataUsage_Mapping.getMapped(from)`

#### 7.8.6.3.30 StakeholderMetadataReferenceUsage\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a reference usage.

### General Mappings

`ToReferenceUsage_Init`  
`Mapping`

### Mapping Source

Classifier

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set { StakeholderMetadataReferenceUsageRedefinition_Mapping.getMapped(from) ,`  
`StakeholderMetadataReferenceUsageFeatureValue_Mapping.getMapped(from) }`

#### 7.8.6.3.31 StakeholderMetadataReferenceUsageFeatureValue\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

### Description

Creates a feature value relationship.

```
LiteralBoolean_Factory.create(true)
```

### 7.8.6.3.32 StakeholderMetadataReferenceUsageRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

GenericToRedefinition\_Mapping

#### Mapping Source

Classifier

#### Mapping Target

Redefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::StakeholderData::isStakeholder')
```

### 7.8.6.3.33 Viewpoint\_Mapping

#### Description

A SysML::ModelElements::Viewpoint is mapped to a SysML v2 ViewDefinition with an owned SysML v2 ViewpointUsage. In SysML v1, the viewpoint combines the purpose and stakeholder concerns as well as presentation information. This is covered by a SysML v2 ViewDefinition with owned SysML v2 ViewpointUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
view def SysMLv1Viewpoint {  
  viewpoint sysMLv1Viewpoint {  
    frame concern1XmiID1;  
    frame concern2XmiID2;  
    metadata SysMLv1Library::ViewpointData {  
      languages = ("language1", "language2");  
      presentations = ("presentation1", "presentation2");  
    }  
  }  
}
```

## General Mappings

ToFeatureValue\_Init  
Mapping

## Mapping Source

Classifier

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  
`LiteralBoolean_Factory.create(true)`

### 7.8.6.3.32 StakeholderMetadataReferenceUsageRedefinition\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

## General Mappings

ToRedefinition\_Init  
Mapping

## Mapping Source

Classifier

## Mapping Target

Redefinition

## Owned Mappings

(none)

## Applicable filters

```

        require constraint {
            doc /* thisIsThePurpose */
        }
    }
    satisfy sysMLv1Viewpoint;
    rendering {
        action : SysMLv1ViewpointMethodBehavior1;
        action : SysMLv1ViewpointMethodBehavior2;
    }
}
action def SysMLv1ViewpointMethodBehavior1;
action def SysMLv1ViewpointMethodBehavior2;

item def SysMLv1Stakeholder {@SysMLv1Library::StakeholderData {isStakeholder = true;}}

concern concern1XmiID1 {
    doc /* Concern1 */
    stakeholder : SysMLv1Stakeholder;
}
concern concern2XmiID2 {
    doc /* Concern2 */
    stakeholder : SysMLv1Stakeholder;
}

```

## General Mappings

Class\_Mapping

### Mapping Source

Class

### Mapping Target

ViewDefinition

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::ModelElements::Viewpoint')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ViewDefinition::ownedRelationship () : Relationship [0..\*]

```
let toElementFMS: Set(UML::Element) =
```



(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::StakeholderData::isStakeholder')
```

### 7.8.6.3.33 Viewpoint\_Mapping

#### Description

A `SysML::ModelElements::Viewpoint` is mapped to a SysML v2 `ViewDefinition` with an owned SysML v2 `ViewpointUsage`. In SysML v1, the viewpoint combines the purpose and stakeholder concerns as well as presentation information. This is covered by a SysML v2 `ViewDefinition` with owned SysML v2 `ViewpointUsage`.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
view def SysMLv1Viewpoint {  
  viewpoint sysMLv1Viewpoint {  
    frame concern1XmiID1;  
    frame concern2XmiID2;  
    metadata SysMLv1Library::ViewpointData {  
      languages = ("language1", "language2");  
      presentations = ("presentation1", "presentation2");  
    }  
    require constraint {  
      doc /* thisIsThePurpose */  
    }  
  }  
  satisfy sysMLv1Viewpoint;  
  rendering {  
    action : SysMLv1ViewpointMethodBehavior1;  
    action : SysMLv1ViewpointMethodBehavior2;  
  }  
}  
action def SysMLv1ViewpointMethodBehavior1;  
action def SysMLv1ViewpointMethodBehavior2;  
  
item def SysMLv1Stakeholder {@SysMLv1Library::StakeholderData {isStakeholder = true;}}  
  
concern concern1XmiID1 {  
  doc /* Concern1 */  
  stakeholder : SysMLv1Stakeholder;  
}  
concern concern2XmiID2 {  
  doc /* Concern2 */  
  stakeholder : SysMLv1Stakeholder;  
}
```

## General Mappings

### Class\_Mapping

```

        from.ownedElement->select(e | (e.ocIsKindOf(UML::Property) and
            (e.ocIsType(UML::Property).redefinedProperty->size() = 0)) or
            e.ocIsKindOf(UML::Comment)) in
let redefinedAttributes: Set(UML::Element) =
    from.ownedElement->select(e | from.ocIsKindOf(UML::DataType) and
        (e.ocIsType(UML::Property).redefinedProperty->size() > 0)) in
let generalizations : Set(UML::Generalization) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Generalization)) in
let toElementOMS: Set(UML::Element) =
    (((from.ownedElement - toElementFMS) - redefinedAttributes) -
        generalizations) in
let relationships: Sequence(UML::Element) =
toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(redefinedAttributes
    ->collect(e | AttributeRedefinedMembership_Mapping.getMapped(e)))
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e)))
->including(ViewpointViewpointUsageFeatureMembership_Mapping.getMapped(from))
->including(ViewpointSatisfyFeatureMembership_Mapping.getMapped(from))
->including(ViewpointRenderingFeatureMembership_Mapping.getMapped(from))
->including(
    CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)) in
if from.classifierBehavior.ocIsUndefined() then
    relationships
else
    relationships
    ->append(BehavioredClassifierFeatureMembership_Mapping.getMapped(from))
endif

```

### 7.8.6.3.34 ViewpointConcernReferenceSubsetting\_Mapping

#### Description

Creates a subsetting relationship.

#### General Mappings

**Generic**ToReferenceSubsetting\_Mapping

#### Mapping Source

Comment

#### Mapping Target

ReferenceSubsetting

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

## Mapping Source

Class

## Mapping Target

ViewDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::ModelElements::Viewpoint')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ViewDefinition::ownedRelationship () : Relationship [0..\*]

```
let toElementFMS: Set(UML::Element) =
  from.ownedElement->select(e | (e.ocIsKindOf(UML::Property) and
    (e.ocAsType(UML::Property).redefinedProperty->size() = 0)) or
    e.ocIsKindOf(UML::Comment)) in
let redefinedAttributes: Set(UML::Element) =
  from.ownedElement->select(e | from.ocIsKindOf(UML::DataType) and
    (e.ocAsType(UML::Property).redefinedProperty->size() > 0)) in
let generalizations : Set(UML::Generalization) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Generalization)) in
let toElementOMS: Set(UML::Element) =
  (((from.ownedElement - toElementFMS) - redefinedAttributes) -
    generalizations) in
let relationships: Sequence(UML::Element) =
  toElementOMS->collect(e | ElementOwningMembership_Mapping.getMapped(e))
->union(toElementFMS->collect(e | ElementFeatureMembership_Mapping.getMapped(e)))
->union(redefinedAttributes
  ->collect(e | AttributeRedefinedMembership_Mapping.getMapped(e)))
->union(generalizations->collect(e | Generalization_Mapping.getMapped(e)))
->including(ViewpointViewpointUsageFeatureMembership_Mapping.getMapped(from))
->including(ViewpointSatisfyFeatureMembership_Mapping.getMapped(from))
->including(ViewpointRenderingFeatureMembership_Mapping.getMapped(from))
->including(
  CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)) in
if from.classifierBehavior.ocIsUndefined() then
  relationships
else
  relationships
  ->append(BehavoredClassifierFeatureMembership_Mapping.getMapped(from))
endif
```

### 7.8.6.3.34 ViewpointConcernReferenceSubsetting\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]

from

#### 7.8.6.3.35 ViewpointConcernUsage\_Mapping

##### Description

The mapping class creates the concern usage element for the SysML::ModelElements::Viewpoint mapping.

##### General Mappings

GenericToRequirementUsage\_Mapping

##### Mapping Source

Comment

##### Mapping Target

ConcernUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConcernUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ViewpointConcernReferenceSubsetting_Mapping.getMapped(from),  
EmptySubjectMembership_Factory.create(),  
CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)}
```

#### 7.8.6.3.36 ViewpointConstraintUsage\_Mapping

##### Description

The mapping class creates the constraint usage element for the SysML::ModelElements::Viewpoint mapping.

##### General Mappings

GenericToConstraintUsage\_Mapping

##### Mapping Source

### Description

Creates a subsetting relationship.

### General Mappings

ToReferenceSubsetting\_Init  
Mapping

### Mapping Source

Comment

### Mapping Target

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]

from

### 7.8.6.3.35 ViewpointConcernUsage\_Mapping

**SysML2 -220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the concern usage element for the SysML::ModelElements::Viewpoint mapping.

### General Mappings

ToRequirementUsage\_Init  
Mapping

### Mapping Source

Comment

### Mapping Target

ConcernUsage

### Owned Mappings

Class

### Mapping Target

ConstraintUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConstraintUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ViewpointConstraintUsageOwningMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

## 7.8.6.3.37 ViewpointConstraintUsageDocumentation\_Mapping

### Description

The mapping class creates the documentation element for the SysML::ModelElements::Viewpoint mapping.

### General Mappings

**Generic**ToDocumentation\_Mapping

### Mapping Source

Class

### Mapping Target

Documentation

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Documentation::body () : String [1]

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConcernUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{ViewpointConcernReferenceSubsetting_Mapping.getMapped(from),  
EmptySubjectMembership_Factory.create(),  
CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)}
```

### 7.8.6.3.36 ViewpointConstraintUsage\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates the constraint usage element for the SysML::ModelElements::Viewpoint mapping.

#### General Mappings

ToConstraintUsage\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

ConstraintUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConstraintUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{ViewpointConstraintUsageOwningMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

```
Helper.getTagValueAsString(from, 'SysML::ModelElements::Viewpoint', 'purpose')
```

### 7.8.6.3.38 ViewpointConstraintUsageOwningMembership\_Mapping

#### Description

Creates a owning membership relationship for *ownedMemberElement()*.

#### General Mappings

GenericToOwningMembership\_Mapping

#### Mapping Source

Class

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

```
ViewpointConstraintUsageDocumentation_Mapping.getMapped(from)
```

### 7.8.6.3.39 ViewpointFramedConcernMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

Comment

#### Mapping Target

FramedConcernMembership

#### Owned Mappings



### 7.8.6.3.37 ViewpointConstraintUsageDocumentation\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

The mapping class creates the documentation element for the SysML::ModelElements::Viewpoint mapping.

#### General Mappings

ToDocumentation\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

Documentation

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Documentation::body () : String [1]  
`Helper.getTagValueAsString(from, 'SysML::ModelElements::Viewpoint', 'purpose')`

### 7.8.6.3.38 ViewpointConstraintUsageOwningMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a owning membership relationship for *ownedMemberElement()*.

#### General Mappings

ToOwningMembership\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FramedConcernMembership::ownedMemberFeature () : Feature [1]

`ViewpointConcernUsage_Mapping.getMapped(from)`

### 7.8.6.3.40 ViewpointLanguagesMetadataFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

Class

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

`ViewpointLanguagesMetadataReferenceUsage_Mapping.getMapped(from)`

### 7.8.6.3.41 ViewpointLanguagesMetadataFeatureValue\_Mapping

#### Description

Creates a feature value relationship.

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ViewpointConstraintUsageDocumentation_Mapping.getMapped (from)`

### 7.8.6.3.39 ViewpointFramedConcernMembership\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

Comment

### Mapping Target

FramedConcernMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FramedConcernMembership::ownedMemberFeature () : Feature [1]  
`ViewpointConcernUsage_Mapping.getMapped (from)`

## General Mappings

**Generic**ToFeatureValue\_Mapping

## Mapping Source

Class

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
ViewpointLanguagesMetadataOperatorExpression_Mapping.getMapped(from)
```

### 7.8.6.3.42 ViewpointLanguagesMetadataRedefinition\_Mapping

## Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

## General Mappings

**Generic**ToRedefinition\_Mapping

## Mapping Source

Class

## Mapping Target

Redefinition

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

#### 7.8.6.3.40 ViewpointLanguagesMetadataFeatureMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

Class

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`ViewpointLanguagesMetadataReferenceUsage_Mapping.getMapped (from)`

#### 7.8.6.3.41 ViewpointLanguagesMetadataFeatureValue\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature value relationship.

##### General Mappings

ToFeatureValue\_Init  
Mapping

##### Mapping Source

Class

##### Mapping Target

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ViewpointData::languages')
```

#### 7.8.6.3.43 ViewpointLanguagesMetadataReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

**Generic**ToReferenceUsage\_Mapping

##### Mapping Source

Class

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{ViewpointLanguagesMetadataRedefinition_Mapping.getMapped(from),  
ViewpointLanguagesMetadataFeatureValue_Mapping.getMapped(from) }
```

#### 7.8.6.3.44 ViewpointMetadataFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

**Generic**ToFeatureTyping\_Mapping

##### Mapping Source

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
ViewpointLanguagesMetadataOperatorExpression_Mapping.getMapped(from)
```

#### 7.8.6.3.42 ViewpointLanguagesMetadataRedefinition\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

ToRedefinition\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

Redefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]

```
SYSML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ViewpointData::languages')
```





#### 7.8.6.3.43 ViewpointLanguagesMetadataReferenceUsage\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a reference usage.

##### General Mappings

ToReferenceUsage\_Init  
Mapping

##### Mapping Source

Class

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{ViewpointLanguagesMetadataRedefinition_Mapping.getMapped(from) ,  
ViewpointLanguagesMetadataFeatureValue_Mapping.getMapped(from) }
```

#### 7.8.6.3.44 ViewpointMetadataFeatureTyping\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

ToFeatureTyping\_Init  
Mapping

##### Mapping Source

Class

##### Mapping Target

**Class**

### **Mapping Target**

FeatureTyping

### **Owned Mappings**

(none)

### **Applicable filters**

(none)

### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ViewpointData')
```

## **7.8.6.3.45 ViewpointLanguagesMetadataOperatorExpression\_Mapping**

### **Description**

The mapping class creates the operator expression for the list of languages of the SysML::ModelElements::Viewpoint mapping.

### **General Mappings**

**Generic**ToOperatorExpression\_Mapping

### **Mapping Source**

Class

### **Mapping Target**

OperatorExpression

### **Owned Mappings**

(none)

### **Applicable filters**

(none)

### **Mapping rules**

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ViewpointData')
```

### 7.8.6.3.45 ViewpointLanguagesMetadataOperatorExpression\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the operator expression for the list of languages of the SysML::ModelElements::Viewpoint mapping.

### General Mappings

ToOperatorExpression\_Init  
Mapping

### Mapping Source

Class

### Mapping Target

OperatorExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OperatorExpression::operator () : String [1]

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OperatorExpression::operator () : String [1]`

`, '`

- `OperatorExpression::ownedRelationship () : Relationship [0..*]`

```
Helper.getTagValueAsStringColl(from, 'SysML::ModelElements::Viewpoint', 'language')  
->collect(e | StringParameterMembership_Factory.create(e))
```

#### 7.8.6.3.46 ViewpointMetadataOwningMembership\_Mapping

##### Description

Creates a owning membership relationship for *ownedMemberElement()*.

##### General Mappings

**Generic**ToOwningMembership\_Mapping

##### Mapping Source

Class

##### Mapping Target

OwningMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`

```
ViewpointMetadataUsage_Mapping.getMapped(from)
```

#### 7.8.6.3.47 ViewpointMetadataUsage\_Mapping

##### Description

The mapping class creates the metadata usage element for the SysML::ModelElements::Viewpoint mapping.

##### General Mappings

**Generic**ToMetadataUsage\_Mapping

' , '

- `OperatorExpression::ownedRelationship () : Relationship [0..*]`

```
Helper.getTagValueAsStringColl (from, 'SysML::ModelElements::Viewpoint', 'language')  
->collect (e | StringParameterMembership_Factory.create (e))
```

#### 7.8.6.3.46 ViewpointMetadataOwningMembership\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

Creates a owning membership relationship for *ownedMemberElement()*.

###### **General Mappings**

ToOwningMembership\_Init  
Mapping

###### **Mapping Source**

Class

###### **Mapping Target**

OwningMembership

###### **Owned Mappings**

(none)

###### **Applicable filters**

(none)

###### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `OwningMembership::ownedMemberElement () : Element [1]`

```
ViewpointMetadataUsage_Mapping.getMapped (from)
```

#### 7.8.6.3.47 ViewpointMetadataUsage\_Mapping

##### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

###### **Description**

The mapping class creates the metadata usage element for the SysML::ModelElements::Viewpoint mapping.

###### **General Mappings**

ToMetadataUsage\_Init  
Mapping

## Mapping Source

Class

## Mapping Target

MetadataUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{ViewpointMetadataFeatureTyping_Mapping.getMapped(from),  
ViewpointLanguagesMetadataFeatureMembership_Mapping.getMapped(from),  
ViewpointPresentationsMetadataFeatureMembership_Mapping.getMapped(from)}
```

### 7.8.6.3.48 ViewpointPresentationsMetadataFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

Class

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

### Mapping Source

Class

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{ViewpointMetadataFeatureTyping_Mapping.getMapped(from),  
ViewpointLanguagesMetadataFeatureMembership_Mapping.getMapped(from),  
ViewpointPresentationsMetadataFeatureMembership_Mapping.getMapped(from) }
```

### 7.8.6.3.48 ViewpointPresentationsMetadataFeatureMembership\_Mapping

#### SYSML2 -220: Replace Generic mapping classes by Initializers

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

Class

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

`ViewpointPresentationsMetadataReferenceUsage_Mapping.getMapped(from)`

#### **7.8.6.3.49 ViewpointPresentationsMetadataFeatureValue\_Mapping**

##### **Description**

Creates a feature value relationship.

##### **General Mappings**

`GenericToFeatureValue_Mapping`

##### **Mapping Source**

Class

##### **Mapping Target**

FeatureValue

##### **Owned Mappings**

(none)

##### **Applicable filters**

(none)

##### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

`ViewpointPresentationsMetadataOperatorExpression_Mapping.getMapped(from)`

#### **7.8.6.3.50 ViewpointPresentationsMetadataOperatorExpression\_Mapping**

##### **Description**

The mapping class creates the operator expression for the list of presentations of the `SysML::ModelElements::Viewpoint` mapping.

##### **General Mappings**

`GenericToOperatorExpression_Mapping`

##### **Mapping Source**

Class



In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

`ViewpointPresentationsMetadataReferenceUsage_Mapping.getMapped(from)`

#### 7.8.6.3.49 ViewpointPresentationsMetadataFeatureValue\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature value relationship.

##### General Mappings

`ToFeatureValue_Init`  
Mapping

##### Mapping Source

Class

##### Mapping Target

FeatureValue

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

`ViewpointPresentationsMetadataOperatorExpression_Mapping.getMapped(from)`

#### 7.8.6.3.50 ViewpointPresentationsMetadataOperatorExpression\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

The mapping class creates the operator expression for the list of presentations of the `SysML::ModelElements::Viewpoint` mapping.

##### General Mappings

### Mapping Target

OperatorExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OperatorExpression::ownedRelationship () : Relationship [0..\*]  

```
Helper.getTagValueAsStringColl(from,  
    'SysML::ModelElements::Viewpoint', 'presentation')  
->collect(e | StringParameterMembership_Factory.create(e))
```
- OperatorExpression::operator () : String [1]  

```
' , '
```

#### 7.8.6.3.51 ViewpointPresentationsMetadataRedefinition\_Mapping

##### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

##### General Mappings

GenericToRedefinition\_Mapping

##### Mapping Source

Class

##### Mapping Target

Redefinition

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

ToOperatorExpression\_Init  
Mapping

### Mapping Source

Class

### Mapping Target

OperatorExpression

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OperatorExpression::ownedRelationship () : Relationship [0..\*]  

```
Helper.getTagValueAsStringColl (from,  
    'SysML::ModelElements::Viewpoint', 'presentation')  
->collect (e | StringParameterMembership_Factory.create (e))
```
- OperatorExpression::operator () : String [1]  

```
' , '
```

### 7.8.6.3.51 ViewpointPresentationsMetadataRedefinition\_Mapping

**SysML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

### General Mappings

ToRedefinition\_Init  
Mapping

### Mapping Source

Class

### Mapping Target

Redefinition

### Owned Mappings

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::ViewpointData::presentations')
```

#### 7.8.6.3.52 ViewpointPresentationsMetadataReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

**Generic**ToReferenceUsage\_Mapping

##### Mapping Source

Class

##### Mapping Target

ReferenceUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{ViewpointPresentationsMetadataRedefinition_Mapping.getMapped(from),  
ViewpointPresentationsMetadataFeatureValue_Mapping.getMapped(from) }
```

#### 7.8.6.3.53 ViewpointRenderingFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  
`SysML2::AttributeUsage.allInstances()`  
`->any(m | m.qualifiedName = 'SysMLv1Library::ViewpointData::presentations')`

### 7.8.6.3.52 ViewpointPresentationsMetadataReferenceUsage\_Mapping

#### SysML2\_-220: Replace Generic mapping classes by Initializers

#### Description

Creates a reference usage.

#### General Mappings

ToReferenceUsage\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{ViewpointPresentationsMetadataRedefinition_Mapping.getMapped(from) ,`  
`ViewpointPresentationsMetadataFeatureValue_Mapping.getMapped(from) }`

Class

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`ViewpointRenderingUsage_Mapping.getMapped(from)`

## 7.8.6.3.54 ViewpointRenderingUsage\_Mapping

### Description

The mapping class creates the rendering usage element for the SysML::ModelElements::Viewpoint mapping class.

### General Mappings

GenericToPartUsage\_Mapping

### Mapping Source

Class

### Mapping Target

RenderingUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RenderingUsage::ownedRelationship () : Relationship [0..\*]

### 7.8.6.3.53 ViewpointRenderingFeatureMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`ViewpointRenderingUsage_Mapping.getMapped(from)`

### 7.8.6.3.54 ViewpointRenderingUsage\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

The mapping class creates the rendering usage element for the SysML::ModelElements::Viewpoint mapping class.

#### General Mappings

ToPartUsage\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

```

    from.ownedOperation
->select( o | Helper.hasStereotypeApplied(o, 'Create') )
->collect( e |
    ViewpointRenderingUsageActionUsageFeatureMembership_Mapping.getMapped(e) )

```

### 7.8.6.3.55 ViewpointRenderingUsageActionUsage\_Mapping

#### Description

The mapping class creates the action usage element for the rendering usage element for the SysML::ModelElements::Viewpoint mapping class.

#### General Mappings

GenericToActionUsage\_Mapping

#### Mapping Source

Class

#### Mapping Target

ActionUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ActionUsage::ownedRelationship () : Relationship [0..\*]  
Set{ViewpointRenderingUsageActionUsageFeatureTyping\_Mapping.getMapped(from) }

### 7.8.6.3.56 ViewpointRenderingUsageActionUsageFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

Class

#### Mapping Target



RenderingUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RenderingUsage::ownedRelationship () : Relationship [0..\*]

```
from.ownedOperation
->select( o | Helper.hasStereotypeApplied(o, 'Create') )
->collect( e |
    ViewpointRenderingUsageActionUsageFeatureMembership_Mapping.getMapped(e) )
```

### 7.8.6.3.55 ViewpointRenderingUsageActionUsage\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

The mapping class creates the action usage element for the rendering usage element for the SysML::ModelElements::Viewpoint mapping class.

### General Mappings

ToActionUsage\_Init  
Mapping

### Mapping Source

Class

### Mapping Target

ActionUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`ViewpointRenderingUsageActionUsage_Mapping.getMapped(from)`

### 7.8.6.3.57 ViewpointRenderingUsageActionUsageFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

**Generic**ToFeatureTyping\_Mapping

#### Mapping Source

Class

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

### 7.8.6.3.58 ViewpointRequirementConstraintMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

Class

#### Mapping Target

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ActionUsage::ownedRelationship () : Relationship [0..*]`

```
Set{ViewpointRenderingUsageActionUsageFeatureTyping_Mapping.getMapped(from) }
```

#### 7.8.6.3.56 ViewpointRenderingUsageActionUsageFeatureMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

Class

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
ViewpointRenderingUsageActionUsage_Mapping.getMapped(from)
```

#### 7.8.6.3.57 ViewpointRenderingUsageActionUsageFeatureTyping\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

ToFeatureTyping\_Init  
Mapping

RequirementConstraintMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RequirementConstraintMembership::ownedMemberFeature () : Feature [1]

`ViewpointConstraintUsage_Mapping.getMapped(from)`

### 7.8.6.3.59 ViewpointSatisfyFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

Class

#### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

`ViewpointSatisfyRequirementUsage_Mapping.getMapped(from)`

### Mapping Source

Class

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

## 7.8.6.3.58 ViewpointRequirementConstraintMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a membership relationship for *memberElement()*.

### General Mappings

ToFeatureMembership\_Init  
Mapping

### Mapping Source

Class

### Mapping Target

RequirementConstraintMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RequirementConstraintMembership::ownedMemberFeature () : Feature [1]  
ViewpointConstraintUsage\_Mapping.getMapped(from)

## 7.8.6.3.59 ViewpointSatisfyFeatureMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### 7.8.6.3.60 ViewpointSatisfyRequirementUsage\_Mapping

#### Description

The mapping class creates the satisfy requirement usage element for the SysML::ModelElements::Viewpoint mapping.

#### General Mappings

**Generic**ToRequirementUsage\_Mapping

#### Mapping Source

Class

#### Mapping Target

SatisfyRequirementUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SatisfyRequirementUsage::ownedRelationship () : Relationship [0..\*]

```
Set{ViewpointSatisfyRequirementUsageReferenceSubsetting_Mapping.getMapped(from),  
EmptySubjectMembership_Factory.create(),  
ReturnParameterFeatureMembership_Factory.create() }
```

### 7.8.6.3.61 ViewpointSatisfyRequirementUsageReferenceSubsetting\_Mapping

#### Description

Creates a subsetting relationship.

#### General Mappings

**Generic**ToReferenceSubsetting\_Mapping

#### Mapping Source

Class

#### Mapping Target

ReferenceSubsetting

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

Class

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
ViewpointSatisfyRequirementUsage\_Mapping.getMapped(from)

### 7.8.6.3.60 ViewpointSatisfyRequirementUsage\_Mapping

#### SysML2 -220: Replace Generic mapping classes by Initializers

## Description

The mapping class creates the satisfy requirement usage element for the SysML::ModelElements::Viewpoint mapping.

## General Mappings

ToRequirementUsage\_Init  
Mapping

## Mapping Source

Class

## Mapping Target

SatisfyRequirementUsage

## Owned Mappings

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceSubsetting::referencedFeature () : Feature [1]`  
`ViewpointViewpointUsage_Mapping.getMapped(from)`

### 7.8.6.3.62 ViewpointViewpointUsage\_Mapping

#### Description

The mapping class creates the embedded viewpoint usage for the SysML::ModelElements::Viewpoint mapping.

#### General Mappings

GenericToUsage\_Mapping

#### Mapping Source

Class

#### Mapping Target

ViewpointUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ViewpointUsage::ownedRelationship () : Relationship [0..*]`  

```
Helper.getTagValueAsElementColl(  
    from, 'SysML::ModelElements::Viewpoint', 'concernList')  
->collect(e | ViewpointFramedConcernMembership_Mapping.getMapped(e))  
->including(ViewpointMetadataOwningMembership_Mapping.getMapped(from))  
->including(EmptySubjectMembership_Factory.create())  
->including(ViewpointRequirementConstraintMembership_Mapping.getMapped(from))
```



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SatisfyRequirementUsage::ownedRelationship () : Relationship [0..\*]  

```
Set{ViewpointSatisfyRequirementUsageReferenceSubsetting_Mapping.getMapped(from),  
EmptySubjectMembership_Factory.create(),  
ReturnParameterFeatureMembership_Factory.create() }
```

### 7.8.6.3.61 ViewpointSatisfyRequirementUsageReferenceSubsetting\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

#### Description

Creates a subsetting relationship.

#### General Mappings

ToReferenceSubsetting\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

ReferenceSubsetting

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  

```
ViewpointViewpointUsage_Mapping.getMapped(from)
```

- ViewpointUsage::declaredName () : String [0..1]

```
from.name.substring(1,1).toLowerCase() + from.name.substring(2, from.name.size())
```

### 7.8.6.3.63 ViewpointViewpointUsageFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

GenericToFeatureMembership\_Mapping

#### Mapping Source

Class

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
ViewpointViewpointUsage_Mapping.getMapped(from)
```

## 7.8.7 PortsAndFlows

This chapter lists all mapping specifications of SysML::PortsAndFlows model elements.

### 7.8.7.1 Overview

Table 31. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
AcceptChangeStructuralFeatureEventAction	AcceptActionUsage
AddFlowPropertyValueOnNestedPortAction	
ChangeStructuralFeatureEvent	
DirectedFeature	PerformActionUsage
FlowProperty	

### 7.8.6.3.62 ViewpointViewpointUsage\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

The mapping class creates the embedded viewpoint usage for the SysML::ModelElements::Viewpoint mapping.

#### General Mappings

ToUsage\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

ViewpointUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ViewpointUsage::ownedRelationship () : Relationship [0..\*]  

```
Helper.getTagValueAsElementColl(  
    from, 'SysML::ModelElements::Viewpoint', 'concernList')  
->collect(e | ViewpointFramedConcernMembership_Mapping.getMapped(e))  
->including(ViewpointMetadataOwningMembership_Mapping.getMapped(from))  
->including(EmptySubjectMembership_Factory.create())  
->including(ViewpointRequirementConstraintMembership_Mapping.getMapped(from))
```
- ViewpointUsage::declaredName () : String [0..1]  

```
from.name.substring(1,1).toLowerCase() + from.name.substring(2, from.name.size())
```

### 7.8.6.3.63 ViewpointViewpointUsageFeatureMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
FullPort	PartUsage
InterfaceBlock	PortDefinition
InvocationOnNestedPortAction	
ItemFlow	
ProxyPort	
TriggerOnNestedPort	
~InterfaceBlock	PortDefinition

The following table gives an overview of which SysML v2 elements the SysML::Ports&Flows elements are transformed with which mapping class. The mapping details are in [7.8.7.3](#).

The justifications for the elements without mapping are given in [7.8.7.2](#).

### 7.8.7.2 SysML::Ports&Flows elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 32. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
AddFlowPropertyValueOnNestedPortAction	Mapping is not specified yet.
ChangeStructuralFeatureEvent	Mapping is not specified yet.
FlowProperty	Mapping is not specified yet.
InvocationOnNestedPortAction	Mapping is not specified yet.
TriggerOnNestedPort	Mapping is not specified yet.

### 7.8.7.3 Mapping Specifications

#### 7.8.7.3.1 AcceptChangeStructuralFeatureEventAction\_Mapping

##### Description

The SysML::PortsAndFlows::AcceptChangeStructuralFeatureEventAction element is mapped to SysML v2 AcceptActionUsage. The details of the mapping are not defined yet.

##### General Mappings

AcceptEventAction\_Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

AcceptActionUsage

ToFeatureMembership\_Init  
Mapping

## Mapping Source

Class

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
ViewpointViewpointUsage\_Mapping.getMapped(from)

## 7.8.7 PortsAndFlows

### 7.8.7.1 Overview

**SYSML2 -76: Transformation does not cover SysMLv1::FlowProperty**  
**SYSML2 -329: Mapping overview tables are wrong**

Table 30. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
AcceptChangeStructuralFeatureEventAction	AcceptActionUsage
AddFlowPropertyValueOnNestedPortAction	
ChangeStructuralFeatureEvent	
DirectedFeature	PerformActionUsage
FlowProperty	AttributeUsage OccurrenceUsage ReferenceUsage PartUsage
FullPort	PartUsage
InterfaceBlock	PortDefinition
InvocationOnNestedPortAction	
ItemFlow	
ProxyPort	

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src,  
'SysML::Ports&Flows::AcceptChangeStructuralFeatureEventAction')
```

## Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.8.7.3.2 CommonFullPort\_Mapping

#### Description

The abstract mapping class is the base class of the mapping classes for the SysML::Ports&Flows::FullPort mappings.

#### General Mappings

PropertyCommon\_Mapping

#### Mapping Source

Port

#### Mapping Target

PartUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PartUsage::ownedRelationship () : Relationship [0..\*]

```
let typings: Set(KerML::FeatureTyping) = if from.type.ocIsUndefined() then  
    Set{}  
else  
    Set{StructuralFeatureToFeatureTyping_Mapping.getMapped(from)}  
endif in
```

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
TriggerOnNestedPort	
~InterfaceBlock	PortDefinition

### 7.8.7.2 SysML::Ports&Flows elements not mapped

**SYSML2\_-76: Transformation does not cover SysMLv1::FlowProperty**

**Table 31.** List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
AddFlowPropertyValueOnNestedPortAction	Mapping is not specified yet.
ChangeStructuralFeatureEvent	Mapping is not specified yet.
InvocationOnNestedPortAction	Mapping is not specified yet.
TriggerOnNestedPort	Mapping is not specified yet.

### 7.8.7.3 Mapping Specifications

**SYSML2\_-345: Chapter 7.8.7.3.3 FeatureDirectionKind is empty**

**SYSML2\_-346: Chapter 7.8.7.3.4 is empty**

#### 7.8.7.3.1 AcceptChangeStructuralFeatureEventAction\_Mapping

##### Description

The SysML::PortsAndFlows::AcceptChangeStructuralFeatureEventAction element is mapped to SysML v2 AcceptActionUsage. The details of the mapping are not defined yet.

##### General Mappings

AcceptEventAction\_Mapping

##### Mapping Source

AcceptEventAction

##### Mapping Target

AcceptActionUsage

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src,
'SysML::Ports&Flows::AcceptChangeStructuralFeatureEventAction')
```

##### Mapping rules

```

let subsettings: Set(KerML::Subsetting) = from.subsettedProperty
  ->collect(p | PropertySubsetting_Mapping.getMapped(from, p))->asSet() in
let defaultValue: Set(KerML::OwningMembership) =
if from.defaultValue.oclIsUndefined() then
  Set{}
else
  Set{DefaultValue_Mapping.getMapped(from)}
endif in
typings->union(subsettings)->union(defaultValue)
->including(MultiplicityMembership_Mapping.getMapped(from))->asSet()
->including(FullPortMetadataOwningMembership_Mapping.getMapped(from))

```

### 7.8.7.3.3 FeatureDirectionKind

### 7.8.7.3.4 FlowDirectionKind

### 7.8.7.3.5 FullPort\_Mapping

#### Description

A SysML::Ports&Flows::FullPort element is mapped to a part usage in SysML v2 with metadata that marks the part usage as a full port. The metadata is defined in the SysML v1 library for SysML v2.

The mapping class FullPortUntyped\_Mapping does the same for full ports that have no type.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

part sysMLv1FullPort : SysMLv1Block {SysMLv1Library::PortData {isFullPort = true;}}

```

#### General Mappings

Port\_Mapping

CommonFullPort\_Mapping

#### Mapping Source

Port

#### Mapping Target

PartUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```

(not src.type.oclIsUndefined()) and
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::FullPort')

```

#### Mapping rules



The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

### 7.8.7.3.2 CommonFullPort\_Mapping

#### Description

The abstract mapping class is the base class of the mapping classes for the SysML::Ports&Flows::FullPort mappings.

#### General Mappings

PropertyCommon\_Mapping

#### Mapping Source

Port

#### Mapping Target

PartUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PartUsage::ownedRelationship () : Relationship [0..\*]

```
let typings: Set(KerML::FeatureTyping) = if from.type.ocIsUndefined() then
  Set{}
else
  Set{StructuralFeatureToFeatureTyping_Mapping.getMapped(from)}
endif in
let subsettings: Set(KerML::Subsetting) = from.subsettedProperty
  ->collect(p | PropertySubsetting_Mapping.getMapped(from, p))->asSet() in
let defaultValue: Set(KerML::OwningMembership) =
if from.defaultValue.ocIsUndefined() then
  Set{}
else
  Set{DefaultValue_Mapping.getMapped(from)}
endif in
typings->union(subsettings)->union(defaultValue)
->including(MultiplicityMembership_Mapping.getMapped(from))->asSet()
->including(FullPortMetadataOwningMembership_Mapping.getMapped(from))
```

### 7.8.7.3.3 ConjugatedPortDefinition\_Mapping

**SYSML2 -199: InterfaceBlock mapped to PortDefinition, but ConjugatedPortDefinition is not generated**

**SYSML2 -220: Replace Generic mapping classes by Initializers**

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

#### 7.8.7.3.6 FullPortMetadata\_Mapping

##### Description

Create the metadata usage element to annotate a port with the information that its SysML v1 mapping source element is a SysML v1 full port element.

##### General Mappings

GenericToMetadataUsage\_Mapping

##### Mapping Source

Port

##### Mapping Target

MetadataUsage

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { FullPortMetadataFeatureTyping_Mapping.getMapped(from) ,  
      FullPortMetadataFeatureMembership_Mapping.getMapped(from) }
```

#### 7.8.7.3.7 FullPortMetadataFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

GenericToFeatureMembership\_Mapping

##### Mapping Source

Port

##### Mapping Target

FeatureMembership

## Description

A SysML::Ports&Flows::InterfaceBlock element is mapped to a SysML v2 ConjugatedPortDefinition owned by the PortDefinition that is the target element of the main mapping of the SysML::Ports&Flows::InterfaceBlock.

## General Mappings

ToClassifier\_Init  
Mapping

## Mapping Source

Class

## Mapping Target

ConjugatedPortDefinition

## Owned Mappings

- portConjugation : PortConjugation\_Mapping

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::InterfaceBlock')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConjugatedPortDefinition::ownedRelationship () : Relationship [0..\*]

```
Set{portConjugation.to}
```

### 7.8.7.3.4 FlowProperty\_Mapping

#### **SYSML2\_-76: Transformation does not cover SysMLv1::FlowProperty**

## Description

A UML4SysML::Property which satisfies the filter condition of PropertyTypedByClassInterface\_Mapping and to which the SysML v1 stereotype FlowProperty has been applied is mapped as in the general mapping class PropertyTypedByClassInterface\_Mapping but the target feature is always referential and the flow direction specified in the stereotype FlowProperty is considered.

## General Mappings

PropertyTypedByClassInterface\_Mapping

## Mapping Source

Property



## Mapping Target

OccurrenceUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::FlowProperty')
and ((not src.type.ocIsUndefined())
and (src.type.ocIsKindOf(UML::Class)
or src.type.ocIsKindOf(UML::Interface)))
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OccurrenceUsage::direction () : FeatureDirectionKind [0..1]  

```
Helper.getFlowDirectionKind(Helper.getTagValue(from,
'SysML::Ports&Flows::FlowProperty', 'direction'))
```
- OccurrenceUsage::isComposite () : Boolean [1]  

```
false
```

### 7.8.7.3.5 FlowPropertyAttribute\_Mapping

#### **SYSML2 -76: Transformation does not cover SysMLv1::FlowProperty**

## Description

A UML4SysML::Property which satisfies the filter condition of Attribute\_Mapping and to which the SysML v1 stereotype FlowProperty has been applied is mapped as in the general mapping class Attribute\_Mapping with consideration of the flow direction specified in the stereotype FlowProperty.

## General Mappings

Attribute\_Mapping

## Mapping Source

Property

## Mapping Target

AttributeUsage

## Owned Mappings

(none)



### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::FlowProperty')
and (not src.type.ocIsUndefined() and src.type.ocIsKindOf(UML::DataType))
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `AttributeUsage::direction () : FeatureDirectionKind [0..1]`

```
Helper.getFlowDirectionKind(Helper.getTagValue(from,
'SysML::Ports&Flows::FlowProperty', 'direction'))
```

#### 7.8.7.3.6 FlowPropertyUntyped\_Mapping

#### **SysML2\_-76: Transformation does not cover SysMLv1::FlowProperty**

### Description

A UML4SysML::Property which satisfies the filter condition of PropertyUntyped\_Mapping and to which the SysML v1 stereotype FlowProperty has been applied is mapped as in the general mapping class PropertyUntyped\_Mapping but the target feature is always referential and the flow direction specified in the stereotype FlowProperty is considered.

### General Mappings

PropertyUntyped\_Mapping

### Mapping Source

Property

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::FlowProperty')
and src.type.ocIsUndefined()
and not Helper.hasStereotypeApplied(src.owner, 'SysML::ConstraintBlocks::ConstraintBlock')
```

### Mapping rules





In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::isComposite () : Boolean [1]`  
`false`
- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`Helper.getFlowDirectionKind (Helper.getTagValue (from,  
'SysML::Ports&Flows::FlowProperty', 'direction'))`

### 7.8.7.3.7 FullPort\_Mapping

#### Description

A SysML::Ports&Flows::FullPort element is mapped to a part usage in SysML v2 with metadata that marks the part usage as a full port. The metadata is defined in the SysML v1 library for SysML v2.

The mapping class FullPortUntyped\_Mapping does the same for full ports that have no type.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part sysMLv1FullPort : SysMLv1Block {SysMLv1Library::PortData {isFullPort = true;}}
```

#### General Mappings

Port\_Mapping  
CommonFullPort\_Mapping

#### Mapping Source

Port

#### Mapping Target

PartUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
(not src.type.oclIsUndefined()) and  
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::FullPort')
```

#### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.



### 7.8.7.3.8 FullPortMetadata\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Create the metadata usage element to annotate a port with the information that its SysML v1 mapping source element is a SysML v1 full port element.

#### General Mappings

ToMetadataUsage\_Init  
Mapping

#### Mapping Source

Port

#### Mapping Target

MetadataUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { FullPortMetadataFeatureTyping_Mapping.getMapped (from) ,  
      FullPortMetadataFeatureMembership_Mapping.getMapped (from) }
```

### 7.8.7.3.9 FullPortMetadataFeatureMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

Port

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`

```
FullPortMetadataReferenceUsage_Mapping.getMapped(from)
```

### 7.8.7.3.8 FullPortMetadataFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

`GenericToFeatureTyping_Mapping`

#### Mapping Source

Port

#### Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::PortData')
```

### 7.8.7.3.9 FullPortMetadataOwningMembership\_Mapping

#### Description

### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`FullPortMetadataReferenceUsage_Mapping.getMapped(from)`

### 7.8.7.3.10 FullPortMetadataFeatureTyping\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

Port

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

Creates a owning membership relationship for *ownedMemberElement()*.

### General Mappings

**Generic**ToOwningMembership\_Mapping

### Mapping Source

Port

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

`FullPortMetadata_Mapping.getMapped (from)`

### 7.8.7.3.10 FullPortMetadataReferenceUsage\_Mapping

#### Description

Creates a reference usage.

### General Mappings

**Generic**ToReferenceUsage\_Mapping

### Mapping Source

Port

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

```

SYSML2::MetadataDefinition.allInstances()
->any(m | m.qualifiedName = 'SysMLv1Library::PortData')

```

### 7.8.7.3.11 FullPortMetadataOwningMembership\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a owning membership relationship for *ownedMemberElement()*.

##### General Mappings

ToOwningMembership\_Init  
Mapping

##### Mapping Source

Port

##### Mapping Target

OwningMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
FullPortMetadata\_Mapping.getMapped(from)

### 7.8.7.3.12 FullPortMetadataReferenceUsage\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a reference usage.

##### General Mappings

ToReferenceUsage\_Init  
Mapping

##### Mapping Source

Port

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set { FullPortMetadataReferenceUsageRedefinition_Mapping.getMapped (from) ,  
      FullPortMetadataReferenceUsageFeatureValue_Mapping.getMapped (from) }
```

### 7.8.7.3.11 FullPortMetadataReferenceUsageFeatureValue\_Mapping

#### Description

Creates a feature value relationship.

#### General Mappings

`GenericToFeatureValue_Mapping`

#### Mapping Source

Port

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
LiteralBoolean_Factory.create (true)
```

### 7.8.7.3.12 FullPortMetadataReferenceUsageRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

`GenericToRedefinition_Mapping`

#### Mapping Source



### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set{FullPortMetadataReferenceUsageRedefinition_Mapping.getMapped(from) ,  
FullPortMetadataReferenceUsageFeatureValue_Mapping.getMapped(from) }
```

### 7.8.7.3.13 FullPortMetadataReferenceUsageFeatureValue\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature value relationship.

### General Mappings

ToFeatureValue\_Init  
Mapping

### Mapping Source

Port

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

Port

### Mapping Target

Redefinition

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  

```
SYSMML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::PortData::isFullPort')
```

#### 7.8.7.3.13 FullPortUntyped\_Mapping

##### Description

A `SysML::Ports&Flows::FullPort` element is mapped to a part usage in SysML v2 with metadata that marks the part usage as a full port. The metadata is defined in the SysML v1 library for SysML v2.

The mapping class `FullPort_Mapping` does the same for full ports with a type.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part sysMLv1FullPort {SysMLv1Library::PortData {isFullPort = true;}}
```

##### General Mappings

PortUntyped\_Mapping

CommonFullPort\_Mapping

##### Mapping Source

Port

##### Mapping Target

PartUsage

##### Owned Mappings

(none)

```
LiteralBoolean_Factory.create(true)
```

#### 7.8.7.3.14 FullPortMetadataReferenceUsageRedefinition\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

###### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

###### General Mappings

ToRedefinition\_Init  
Mapping

###### Mapping Source

Port

###### Mapping Target

Redefinition

###### Owned Mappings

(none)

###### Applicable filters

(none)

###### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::PortData::isFullPort')
```

#### 7.8.7.3.15 FullPortUntyped\_Mapping

###### Description

A SysML::Ports&Flows::FullPort element is mapped to a part usage in SysML v2 with metadata that marks the part usage as a full port. The metadata is defined in the SysML v1 library for SysML v2.

The mapping class FullPort\_Mapping does the same for full ports with a type.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
part sysMLv1FullPort {SysMLv1Library::PortData {isFullPort = true;}}
```

###### General Mappings

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.type.oclIsUndefined() and  
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::FullPort')
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

#### 7.8.7.3.14 InterfaceBlock\_Mapping

##### Description

A SysML::Ports&Flows::InterfaceBlock element is mapped to a SysML v2 PortDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
port def SysMLv1InterfaceBlock;
```

##### General Mappings

Block\_Mapping

##### Mapping Source

Class

##### Mapping Target

PortDefinition

##### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::InterfaceBlock')
```

### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

#### 7.8.7.3.15 InterfaceBlockConjugated\_Mapping

##### Description

PortUntyped\_Mapping  
CommonFullPort\_Mapping

#### Mapping Source

Port

#### Mapping Target

PartUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
src.type.ocIsUndefined() and  
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::FullPort')
```

#### Mapping rules

The mapping class only has inherited rules. See the mapping classes in the general mapping section for details.

#### 7.8.7.3.16 InterfaceBlock\_Mapping

**SysML2 -199: InterfaceBlock mapped to PortDefinition, but ConjugatedPortDefinition is not generated**

#### Description

A SysML::Ports&Flows::InterfaceBlock element is mapped to a SysML v2 PortDefinition.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
port def SysMLv1InterfaceBlock;
```

#### General Mappings

Block\_Mapping

#### Mapping Source

Class

#### Mapping Target

PortDefinition

#### Owned Mappings

(none)

A SysML::Ports&Flows::~InterfaceBlock element is mapped to a SysML v2 PortDefinition. The SysML v1 constraints ensure that the port definition is compatible with the appropriate port definition, which is the target of the mapping of the original interface block. Instead of the special tilde symbol, the port definition name gets a "c" symbol as a prefix. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
port def cSysMLv1InterfaceBlock;
```

## General Mappings

InterfaceBlock\_Mapping

## Mapping Source

Class

## Mapping Target

PortDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::~InterfaceBlock')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PortDefinition::declaredName () : String [0..1]  
`'c' + from.name.substring(2,from.name.size())`

### 7.8.7.3.16 OperationDirectedFeature\_Mapping

#### Description

The mapping class sets the direction of the perform action usage if the SysML v1 mapping source operation has the stereotype SysML::Ports&Flows::DirectedFeature applied.

## General Mappings

Operation\_Mapping

## Mapping Source

Operation

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::InterfaceBlock')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PortDefinition::ownedRelationship () : Relationship [0..*]`

```
self.oclAsType(Block_Mapping).ownedRelationship()->including(InterfaceBlockOwningMembership_M
```

### 7.8.7.3.17 InterfaceBlockConjugated\_Mapping

#### Description

A SysML::Ports&Flows::~~InterfaceBlock element is mapped to a SysML v2 PortDefinition. The SysML v1 constraints ensure that the port definition is compatible with the appropriate port definition, which is the target of the mapping of the original interface block. Instead of the special tilde symbol, the port definition name gets a "c" symbol as a prefix. The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
port def cSysMLv1InterfaceBlock;
```

#### General Mappings

InterfaceBlock\_Mapping

#### Mapping Source

Class

#### Mapping Target

PortDefinition

#### Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::~~InterfaceBlock')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PortDefinition::declaredName () : String [0..1]`





```
'c' + from.name.substring(2,from.name.size())
```

### 7.8.7.3.18 InterfaceBlockOwningMembership\_Mapping

**SYSML2 -199:** InterfaceBlock mapped to PortDefinition, but ConjugatedPortDefinition is not generated

**SYSML2 -220:** Replace Generic mapping classes by Initializers

#### Description

Creates a owning membership relationship for *ownedMemberElement()*.

#### General Mappings

ToOwningMembership\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`ConjugatedPortDefinition_Mapping.getMapped(from)`

### 7.8.7.3.19 OperationDirectedFeature\_Mapping

#### Description

The mapping class sets the direction of the perform action usage if the SysML v1 mapping source operation has the stereotype SysML::Ports&Flows::DirectedFeature applied.

#### General Mappings

Operation\_Mapping

#### Mapping Source

Operation

## Mapping Target

PerformActionUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::DirectedFeature')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PerformActionUsage::direction () : FeatureDirectionKind [0..1]  

```
Helper.getKerMLFeatureDirectionKind(  
  Helper.getTagValueAsElement(  
    from, 'SysML::Ports&Flows::DirectedFeature', 'featureDirection'  
  )  
)
```

## 7.8.8 Requirements

This chapter lists all mapping specifications of SysML::Requirements model elements.

### 7.8.8.1 Overview

Table 33. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Copy	
DeriveReq	ConnectionUsage
Refine	Dependency
Requirement	RequirementUsage
Satisfy	SatisfyRequirementUsage
TestCase	VerificationCaseDefinition
Trace	Dependency
Verify	RequirementVerificationMembership

The following table gives an overview of which SysML v2 elements the SysML::Requirements elements are transformed with which mapping class. The mapping details are in [7.8.8.3](#).

The justifications for the elements without mapping are given in [7.8.8.2](#).

## Mapping Target

PerformActionUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Ports&Flows::DirectedFeature')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- PerformActionUsage::direction () : FeatureDirectionKind [0..1]

```
Helper.getKerMLFeatureDirectionKind(  
  Helper.getTagValueAsElement(  
    from, 'SysML::Ports&Flows::DirectedFeature', 'featureDirection'  
  )  
)
```

### 7.8.7.3.20 PortConjugation\_Mapping

**SYSML2\_-199: InterfaceBlock mapped to PortDefinition, but ConjugatedPortDefinition is not generated**

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

Creates a PortConjugation between a PortDefinition and a ConjugatedPortDefinition element.

## General Mappings

ToConjugation\_Init  
Mapping

## Mapping Source

Class

## Mapping Target

PortConjugation

## Owned Mappings

- conjugatedPortDefinition : ConjugatedPortDefinition\_Mapping

## Applicable filters

(none)

### 7.8.8.2 SysML::Requirements elements not mapped

In this section, missing transformation rules of SysML v1 elements to SysML v2 are justified for each individual element in the following table.

**Table 34. List of SysML v1 elements not mapped of this section**

SysML v1 Concept	Rationale
Copy	The copy relationship is not covered by SysML v2.

### 7.8.8.3 Mapping Specifications

#### 7.8.8.3.1 DeriveReq Mapping

##### Description

A SysML::Requirements::DeriveReq relationship is mapped to a SysML v2 DerivationConnections::Derivation model library element.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
requirement <'id1'> SysMLv1Requirement {
    doc /*
        * requirement text
        */
}
requirement <'id2'> SysMLv1RequirementDerived {
    doc /*
        * requirement text
        */
}
connection : DerivationConnections::Derivation
    connect SysMLv1RequirementDerived to SysMLv1Requirement;
```

##### General Mappings

Abstraction Mapping

GenericToConnectionUsage Mapping

##### Mapping Source

Abstraction

##### Mapping Target

ConnectionUsage

##### Owned Mappings

(none)

##### Applicable filters

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `PortConjugation::conjugatedType () : Type [1]`  
`conjugatedPortDefinition.to`
- `PortConjugation::originalPortDefinition () : Type [1]`  
`from`

## 7.8.8 Requirements

### 7.8.8.1 Overview

**[SYSML2\\_-329](#): Mapping overview tables are wrong**

Table 32. List of all mappings

SysML v1 Abstract Syntax/Stereotype	SysML v2 Abstract Syntax
Copy	
DeriveReq	ConnectionUsage
Refine	Dependency
Requirement	RequirementUsage
Satisfy	SatisfyRequirementUsage
TestCase	VerificationCaseDefinition
Trace	Dependency
Verify	RequirementVerificationMembership

### 7.8.8.2 SysML::Requirements elements not mapped

Table 33. List of SysML v1 elements not mapped of this section

SysML v1 Concept	Rationale
Copy	The copy relationship is not covered by SysML v2.

### 7.8.8.3 Mapping Specifications

#### 7.8.8.3.1 DeriveReq\_Mapping

**[SYSML2\\_-220](#): Replace Generic mapping classes by Initializers**

#### Description

A SysML::Requirements::DeriveReq relationship is mapped to a SysML v2 DerivationConnections::Derivation model library element.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Requirements::DeriveReq')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ConnectionUsage::ownedRelationship () : Relationship [0..*]`

```
Set{DeriveReqFeatureTyping_Mapping.getMapped(from),  
DeriveReqSourceEndFeatureMembership_Mapping.getMapped(from),  
DeriveReqTargetEndFeatureMembership_Mapping.getMapped(from)}  
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())
```

#### 7.8.8.3.2 DeriveReqFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

**GenericToFeatureTyping\_Mapping**

##### Mapping Source

Dependency

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SysML2::ConnectionDefinition.allInstances()  
->any(m | m.qualifiedName = 'DerivationConnections::Derivation')
```

#### 7.8.8.3.3 DeriveReqSourceEndFeatureMembership\_Mapping

##### Description

```

requirement <'id1'> SysMLv1Requirement {
    doc /*
        * requirement text
        */
}
requirement <'id2'> SysMLv1RequirementDerived {
    doc /*
        * requirement text
        */
}
connection : DerivationConnections::Derivation
    connect SysMLv1RequirementDerived to SysMLv1Requirement;

```

## General Mappings

Abstraction\_Mapping  
ToConnectionUsage\_[Init](#)

## Mapping Source

Abstraction

## Mapping Target

ConnectionUsage

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Requirements::DeriveReq')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ConnectionUsage::ownedRelationship () : Relationship [0..\*]  

```

Set{DeriveReqFeatureTyping_Mapping.getMapped(from),
DeriveReqSourceEndFeatureMembership_Mapping.getMapped(from),
DeriveReqTargetEndFeatureMembership_Mapping.getMapped(from)}
->union(self.oclAsType(ElementMain_Mapping).ownedRelationship())

```

### 7.8.8.3.2 DeriveReqFeatureTyping\_Mapping

[SYSML2 -220](#): Replace Generic mapping classes by Initializers

## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

**Generic**ToEndFeatureMembership\_Mapping

### Mapping Source

Dependency

### Mapping Target

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`DeriveReqSourceFeature_Mapping.getMapped(from)`

### 7.8.8.3.4 DeriveReqSourceFeature\_Mapping

#### Description

The mapping class creates the source feature of the ConnectionUsage relationship for the mapping of the SysML v1 deriveReq relationship.

### General Mappings

**Generic**ToFeature\_Mapping

### Mapping Source

Dependency

### Mapping Target

Feature

### Owned Mappings

(none)

### Applicable filters



ToFeatureTyping\_Init  
Mapping

### Mapping Source

Dependency

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]

```
SYSML2::ConnectionDefinition.allInstances()  
->any(m | m.qualifiedName = 'DerivationConnections::Derivation')
```

### 7.8.8.3.3 DeriveReqSourceEndFeatureMembership\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToEndFeatureMembership\_Init  
Mapping

### Mapping Source

Dependency

### Mapping Target

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set { DeriveReqSourceFeatureReferenceSubsetting_Mapping.getMapped (from) }
```

#### 7.8.8.3.5 DeriveReqSourceFeatureReferenceSubsetting\_Mapping

##### Description

Creates a subsetting relationship.

##### General Mappings

`GenericToReferenceSubsetting_Mapping`

##### Mapping Source

Dependency

##### Mapping Target

ReferenceSubsetting

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceSubsetting::referencedFeature () : Feature [1]`

```
from.client->any (c | true)
```

#### 7.8.8.3.6 DeriveReqTargetEndFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

`GenericToEndFeatureMembership_Mapping`

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`

`DeriveReqSourceFeature_Mapping.getMapped (from)`

### 7.8.8.3.4 DeriveReqSourceFeature\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

#### Description

The mapping class creates the source feature of the ConnectionUsage relationship for the mapping of the SysML v1 `deriveReq` relationship.

#### General Mappings

`ToFeature_Init`  
Mapping

#### Mapping Source

Dependency

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

`Set {DeriveReqSourceFeatureReferenceSubsetting_Mapping.getMapped (from) }`

### 7.8.8.3.5 DeriveReqSourceFeatureReferenceSubsetting\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a subsetting relationship.

#### General Mappings

## Mapping Source

Dependency

## Mapping Target

EndFeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- EndFeatureMembership::ownedMemberFeature () : Feature [1]  
`DeriveReqTargetFeature_Mapping.getMapped(from)`

### 7.8.8.3.7 DeriveReqTargetFeature\_Mapping

#### Description

The mapping class creates the target feature of the ConnectionUsage relationship for the mapping of the SysML v1 deriveReq relationship.

#### General Mappings

**Generic**ToFeature\_Mapping

#### Mapping Source

Dependency

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

ToReferenceSubsetting\_Init  
Mapping

### Mapping Source

Dependency

### Mapping Target

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  
`from.client->any(c | true)`

### 7.8.8.3.6 DeriveReqTargetEndFeatureMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

### General Mappings

ToEndFeatureMembership\_Init  
Mapping

### Mapping Source

Dependency

### Mapping Target

EndFeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set{DeriveReqTargetFeatureReferenceSubsetting_Mapping.getMapped(from) }
```

### 7.8.8.3.8 DeriveReqTargetFeatureReferenceSubsetting\_Mapping

#### Description

Creates a subsetting relationship.

#### General Mappings

`GenericToReferenceSubsetting_Mapping`

#### Mapping Source

Dependency

#### Mapping Target

ReferenceSubsetting

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceSubsetting::referencedFeature () : Feature [1]`

```
from.supplier->any(c | true)
```

### 7.8.8.3.9 Refine\_Mapping

#### Description

A `SysML::Requirements::Refine` relationship is mapped to a SysML v2 Dependency relationship annotated with a metadata usage tagging it as a former SysML v1 refine relationship.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
requirement <'idl'> SysMLv1Requirement {
    doc /*
        * requirement text
        */
}
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `EndFeatureMembership::ownedMemberFeature () : Feature [1]`

`DeriveReqTargetFeature_Mapping.getMapped(from)`

### 7.8.8.3.7 DeriveReqTargetFeature\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

#### Description

The mapping class creates the target feature of the ConnectionUsage relationship for the mapping of the SysML v1 deriveReq relationship.

#### General Mappings

ToFeature\_Init  
Mapping

#### Mapping Source

Dependency

#### Mapping Target

Feature

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

`Set{DeriveReqTargetFeatureReferenceSubsetting_Mapping.getMapped(from) }`

### 7.8.8.3.8 DeriveReqTargetFeatureReferenceSubsetting\_Mapping

**[SYSML2 -220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a subsetting relationship.

#### General Mappings

```

use case def SysMLv1UseCase;

dependency from SysMLv1UseCase to SysMLv1Requirement {
    @SysMLv1Library::RefineData {isRefine = true;}
}

```

## General Mappings

Abstraction\_Mapping

## Mapping Source

Abstraction

## Mapping Target

Dependency

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Requirements::Refine')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Dependency::ownedRelationship () : Relationship [0..\*]

```

self.oclAsType (ElementMain_Mapping).ownedRelationship()
->including (RefineAnnotation_Mapping.getMapped (from))

```

### 7.8.8.3.10 RefineAnnotation\_Mapping

#### Description

The mapping class creates the annotation relationship for the SysML::Requirements::Refine mapping.

## General Mappings

GenericToAnnotation\_Mapping

## Mapping Source

Abstraction

## Mapping Target



ToReferenceSubsetting\_Init  
Mapping

### Mapping Source

Dependency

### Mapping Target

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceSubsetting::referencedFeature () : Feature [1]  
`from.supplier->any(c | true)`

## 7.8.8.3.9 Refine\_Mapping

### Description

A SysML::Requirements::Refine relationship is mapped to a SysML v2 Dependency relationship annotated with a metadata usage tagging it as a former SysML v1 refine relationship.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
requirement <'idl'> SysMLv1Requirement {  
    doc /*  
        * requirement text  
        */  
}  
use case def SysMLv1UseCase;  
  
dependency from SysMLv1UseCase to SysMLv1Requirement {  
    @SysMLv1Library::RefinedData {isRefine = true;}  
}
```

### General Mappings

Abstraction\_Mapping

### Mapping Source

Abstraction

Annotation

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Annotation::annotatingElement () : AnnotatingElement [1]`  
`RefineMetadataUsage_Mapping.getMapped(from)`

### 7.8.8.3.11 RefineMetadataFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

**Generic**ToFeatureMembership\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

FeatureMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`RefineMetadataReferenceUsage_Mapping.getMapped(from)`

## Mapping Target

Dependency

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Requirements::Refine')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Dependency::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()  
->including(RefineAnnotation_Mapping.getMapped(from))
```

### 7.8.8.3.10 RefineAnnotation\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

## Description

The mapping class creates the annotation relationship for the SysML::Requirements::Refine mapping.

## General Mappings

ToAnnotation\_**Init**  
Mapping

## Mapping Source

Abstraction

## Mapping Target

Annotation

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

### 7.8.8.3.12 RefineMetadataReferenceUsage\_Mapping

#### Description

Creates a reference usage.

#### General Mappings

**Generic**ToReferenceUsage\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set { RefineMetadataReferenceUsageRedefinition_Mapping.getMapped (from) ,  
      RefineMetadataReferenceUsageFeatureValue_Mapping.getMapped (from) }
```

### 7.8.8.3.13 RefineMetadataReferenceUsageFeatureValue\_Mapping

#### Description

Creates a feature value relationship.

#### General Mappings

**Generic**ToFeatureValue\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

FeatureValue

#### Owned Mappings

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Annotation::annotatingElement () : AnnotatingElement [1]`  
`RefineMetadataUsage_Mapping.getMapped (from)`

#### 7.8.8.3.11 RefineMetadataFeatureMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

ToFeatureMembership\_Init  
Mapping

##### Mapping Source

Abstraction

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`RefineMetadataReferenceUsage_Mapping.getMapped (from)`

#### 7.8.8.3.12 RefineMetadataReferenceUsage\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

##### Description

Creates a reference usage.

##### General Mappings

ToReferenceUsage\_Init  
Mapping

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

```
LiteralBoolean_Factory.create(true)
```

### 7.8.8.3.14 RefineMetadataReferenceUsageRedefinition\_Mapping

#### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

#### General Mappings

GenericToRedefinition\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

Redefinition

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Redefinition::redefinedFeature () : Feature [1]

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::RefineData::isRefine')
```

### 7.8.8.3.15 RefineMetadataUsage\_Mapping

#### Description

## Mapping Source

Abstraction

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]

```
Set{RefineMetadataReferenceUsageRedefinition_Mapping.getMapped(from) ,  
RefineMetadataReferenceUsageFeatureValue_Mapping.getMapped(from) }
```

### 7.8.8.3.13 RefineMetadataReferenceUsageFeatureValue\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

Creates a feature value relationship.

## General Mappings

ToFeatureValue\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

Create the metadata usage element to annotate a dependency relationship with the information that its SysML v1 mapping source element is a SysML v1 refine relationship.

### General Mappings

GenericToMetadataUsage\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

MetadataUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { RefineMetadataUsageFeatureTyping_Mapping.getMapped (from) ,  
      RefineMetadataFeatureMembership_Mapping.getMapped (from) }
```

### 7.8.8.3.16 RefineMetadataUsageFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

GenericToFeatureTyping\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters



In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`  
`LiteralBoolean_Factory.create(true)`

#### 7.8.8.3.14 RefineMetadataReferenceUsageRedefinition\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

##### General Mappings

ToRedefinition\_Init  
Mapping

##### Mapping Source

Abstraction

##### Mapping Target

Redefinition

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  
`SysML2::AttributeUsage.allInstances()`  
`->any(m | m.qualifiedName = 'SysMLv1Library::RefineData::isRefine')`

#### 7.8.8.3.15 RefineMetadataUsage\_Mapping

##### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

Create the metadata usage element to annotate a dependency relationship with the information that its SysML v1 mapping source element is a SysML v1 refine relationship.

##### General Mappings



ToMetadataUsage\_Init  
Mapping

### Mapping Source

Abstraction

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { RefineMetadataUsageFeatureTyping_Mapping.getMapped (from) ,  
      RefineMetadataFeatureMembership_Mapping.getMapped (from) }
```

#### 7.8.8.3.16 RefineMetadataUsageFeatureTyping\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

ToFeatureTyping\_Init  
Mapping

### Mapping Source

Abstraction

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::RefineData')
```

### 7.8.8.3.17 Requirement\_Mapping

#### Description

A `SysML::Requirement` is mapped to a SysML v2 `RequirementUsage`.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
requirement <'id1'> SysMLv1Requirement {  
    doc /*  
        * requirement text  
    */  
  
    requirement <'id2'> SysMLv1NestedRequirement {  
        doc /*  
            * requirement text  
        */  
    }  
}
```

#### General Mappings

NamedElementMain\_Mapping

**GenericToRequirementUsage\_Mapping**

#### Mapping Source

Class

#### Mapping Target

RequirementUsage

#### Owned Mappings

(none)

#### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.isRequirement(src)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::RefineData')
```

### 7.8.8.3.17 Requirement\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

##### Description

A `SysML::Requirement` is mapped to a SysML v2 `RequirementUsage`.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
requirement <'id1'> SysMLv1Requirement {  
  doc /*  
      * requirement text  
  */  
  
  requirement <'id2'> SysMLv1NestedRequirement {  
    doc /*  
        * requirement text  
    */  
  }  
}
```

##### General Mappings

NamedElementMain\_Mapping  
ToRequirementUsage\_Init

##### Mapping Source

Class

##### Mapping Target

RequirementUsage

##### Owned Mappings

(none)

##### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.isRequirement(src)
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RequirementUsage::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType (ElementMain_Mapping).ownedRelationship()  
->including (CommonReturnParameterReferenceUsageMembership_Mapping.getMapped (from))  
->including (RequirementDocumentationMembership_Mapping.getMapped (from))  
->including (RequirementSubjectMembership_Mapping.getMapped (from))
```

- RequirementUsage::reqId () : String [1]

```
let stereotype: UML::Stereotype = Helper.getRequirementStereotype (from) in  
Helper.getTagValueAsString (from, stereotype.qualifiedName, 'id')
```

### 7.8.8.3.18 RequirementDocumentation\_Mapping

#### Description

The mapping class creates a Comment contained in a Requirement which contains the SysML::Requirements::AbstractRequirement::text property.

#### General Mappings

GenericToDocumentation\_Mapping

#### Mapping Source

Class

#### Mapping Target

Documentation

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Documentation::body () : String [1]

```
let stereotype: UML::Stereotype = Helper.getRequirementStereotype (from) in  
Helper.getTagValueAsString (from, stereotype.qualifiedName, 'text')
```

### 7.8.8.3.19 RequirementDocumentationMembership\_Mapping

#### Description

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RequirementUsage::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()  
->including(CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from))  
->including(RequirementDocumentationMembership_Mapping.getMapped(from))  
->including(RequirementSubjectMembership_Mapping.getMapped(from))
```

- RequirementUsage::reqId () : String [1]

```
let stereotype: UML::Stereotype = Helper.getRequirementStereotype(from) in  
Helper.getTagValueAsString(from, stereotype.qualifiedName, 'id')
```

### 7.8.8.3.18 RequirementDocumentation\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

## Description

The mapping class creates a Comment contained in a Requirement which contains the SysML::Requirements::AbstractRequirement::text property.

## General Mappings

ToDocumentation\_Init  
Mapping

## Mapping Source

Class

## Mapping Target

Documentation

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Documentation::body () : String [1]

```
let stereotype: UML::Stereotype = Helper.getRequirementStereotype(from) in  
Helper.getTagValueAsString(from, stereotype.qualifiedName, 'text')
```

Creates a membership relationship for *memberElement()*.

### General Mappings

**Generic**ToOwningMembership\_Mapping

### Mapping Source

Class

### Mapping Target

OwningMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`RequirementDocumentation_Mapping.getMapped(from)`

## 7.8.8.3.20 RequirementSubject\_Mapping

### Description

The mapping class creates the subject reference usage element of the requirement. It is not used since the concept does not exist SysML v1.

### General Mappings

**Generic**ToReferenceUsage\_Mapping

### Mapping Source

Class

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters



### 7.8.8.3.19 RequirementDocumentationMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ToOwningMembership\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`RequirementDocumentation_Mapping.getMapped(from)`

### 7.8.8.3.20 RequirementSubject\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

The mapping class creates the subject reference usage element of the requirement. It is not used since the concept does not exist SysML v1.

#### General Mappings

ToReferenceUsage\_Init  
Mapping

#### Mapping Source

Class

#### Mapping Target

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_'in'`

#### 7.8.8.3.21 RequirementSubjectMembership\_Mapping

##### Description

The subject is not used, because it is not a SysML v1 concept, but must be created for a SysML v2 requirement.

##### General Mappings

**Generic**ToParameterMembership\_Mapping

##### Mapping Source

Class

##### Mapping Target

SubjectMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `SubjectMembership::ownedMemberParameter () : Feature [0..1]`  
`RequirementSubject_Mapping.getMapped(from)`

#### 7.8.8.3.22 Satisfy\_Mapping

##### Description

A SysML::Requirements::Satisfy relationship is mapped to a SysML v2 SatisfyRequirementUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::direction () : FeatureDirectionKind [0..1]

KerML::FeatureDirectionKind::\_in'

### 7.8.8.3.21 RequirementSubjectMembership\_Mapping

#### SysML2\_-220: Replace Generic mapping classes by Initializers

### Description

The subject is not used, because it is not a SysML v1 concept, but must be created for a SysML v2 requirement.

### General Mappings

ToParameterMembership\_Init  
Mapping

### Mapping Source

Class

### Mapping Target

SubjectMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SubjectMembership::ownedMemberParameter () : Feature [0..1]

RequirementSubject\_Mapping.getMapped(from)

```

// satisfy relationship from a block
part def SysMLv1Block {
    part sysMLv1PartProperty;
}
requirement <'ReqId1'> SysMLv1Requirement { doc /* requirement text */ }

ref :SysMLv1Block = all SysMLv1Block {
    satisfy requirement SysMLv1Requirement by self;
}

// satisfy relationship from a part property
satisfy SysMLv1Requirement by sysMLv1BlockUsage.sysMLv1PartProperty {
    sysMLv1BlockUsage : SysMLv1Block;
}

```

## General Mappings

GenericToOccurrenceUsage\_Mapping

Abstraction\_Mapping

### Mapping Source

Abstraction

### Mapping Target

SatisfyRequirementUsage

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```

let satisfy: UML::Abstraction = src.oclAsType(UML::Abstraction) in
    if satisfy.oclIsUndefined() then
        false
    else
        Helper.hasStereotypeApplied(satisfy, 'SysML::Requirements::Satisfy')
    endif

```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SatisfyRequirementUsage::ownedRelationship () : Relationship [0..\*]

```

let relationships : Set(KerML::Relationship) =
    self.oclAsType(ElementMain_Mapping).ownedRelationship()
->including(SatisfyFeatureTyping_Mapping.getMapped(from))
->including(SatisfySubjectSubjectMembership_Mapping.getMapped(from))

```

### 7.8.8.3.22 Satisfy\_Mapping

#### **SysML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

A SysML::Requirements::Satisfy relationship is mapped to a SysML v2 SatisfyRequirementUsage.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
// satisfy relationship from a block
part def SysMLv1Block {
    part sysMLv1PartProperty;
}
requirement <'ReqId1'> SysMLv1Requirement { doc /* requirement text */ }

ref :SysMLv1Block = all SysMLv1Block {
    satisfy requirement SysMLv1Requirement by self;
}

// satisfy relationship from a part property
satisfy SysMLv1Requirement by sysMLv1BlockUsage.sysMLv1PartProperty {
    sysMLv1BlockUsage : SysMLv1Block;
}
```

##### **General Mappings**

ToOccurrenceUsage\_Init  
Abstraction\_Mapping

##### **Mapping Source**

Abstraction

##### **Mapping Target**

SatisfyRequirementUsage

##### **Owned Mappings**

(none)

##### **Applicable filters**

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
let satisfy: UML::Abstraction = src.oclAsType(UML::Abstraction) in
    if satisfy.oclIsUndefined() then
        false
    else
        Helper.hasStereotypeApplied(satisfy, 'SysML::Requirements::Satisfy')
    endif
```

##### **Mapping rules**

```

->including(CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)) in
if from.client->any(c | true).oclIsKindOf(UML::Property) then
    relationships
->including(SatisfyReferenceUsageFeatureMembership_Mapping.getMapped(from))
else
    relationships
endif

```

### 7.8.8.3.23 SatisfyReferenceUsage\_Mapping

#### Description

Creates a reference usage.

#### General Mappings

GenericToReferenceUsage\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

ReferenceUsage

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```

Set{SatisfyReferenceUsageFeatureTyping_Mapping.getMapped(from)}

```
- ReferenceUsage::declaredName () : String [0..1]  

```

from.client
->any(c | true).owner.name.substring(1,1).toLowerCase()
+ from.client
->any(c | true).owner.name.
substring(2,from.client->any(c | true).owner.name.size())
+ 'SatisfyClientUsage'

```

### 7.8.8.3.24 SatisfyReferenceUsageFeatureMembership\_Mapping

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SatisfyRequirementUsage::ownedRelationship () : Relationship [0..\*]

```
let relationships : Set(KerML::Relationship) =
    self.oclAsType(ElementMain_Mapping).ownedRelationship()
->including(SatisfyFeatureTyping_Mapping.getMapped(from))
->including(SatisfySubjectSubjectMembership_Mapping.getMapped(from))
->including(CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from)) in
if from.client->any(c | true).oclIsKindOf(UML::Property) then
    relationships
->including(SatisfyReferenceUsageFeatureMembership_Mapping.getMapped(from))
else
    relationships
endif
```

### 7.8.8.3.23 SatisfyReferenceUsage\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

##### **Description**

Creates a reference usage.

##### **General Mappings**

ToReferenceUsage\_Init  
Mapping

##### **Mapping Source**

Abstraction

##### **Mapping Target**

ReferenceUsage

##### **Owned Mappings**

(none)

##### **Applicable filters**

(none)

##### **Mapping rules**

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  
Set{SatisfyReferenceUsageFeatureTyping\_Mapping.getMapped(from)}
- ReferenceUsage::declaredName () : String [0..1]

## General Mappings

**Generic**ToFeatureMembership\_Mapping

## Mapping Source

Abstraction

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]  
`SatisfyReferenceUsage_Mapping.getMapped(from)`

### 7.8.8.3.25 SatisfySubjectReferenceUsage\_Mapping

## Description

Creates a reference usage.

## General Mappings

**Generic**ToReferenceUsage\_Mapping

## Mapping Source

Abstraction

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules



```

from.client
->any(c | true).owner.name.substring(1,1).toLowerCase()
+ from.client
->any(c | true).owner.name.
substring(2,from.client->any(c | true).owner.name.size())
+ 'SatisfyClientUsage'

```

### 7.8.8.3.24 SatisfyReferenceUsageFeatureMembership\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

#### General Mappings

ToFeatureMembership\_Init  
Mapping

#### Mapping Source

Abstraction

#### Mapping Target

FeatureMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureMembership::ownedMemberFeature () : Feature [1]

```
SatisfyReferenceUsage_Mapping.getMapped(from)
```

### 7.8.8.3.25 SatisfySubjectReferenceUsage\_Mapping

**[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)**

#### Description

Creates a reference usage.

#### General Mappings

ToReferenceUsage\_Init  
Mapping

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`

```
KerML::FeatureDirectionKind::_in'
```

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`

```
Set{SatisfySubjectReferenceUsageFeatureValue_Mapping.getMapped(from) }
```

### 7.8.8.3.26 SatisfySubjectReferenceUsageValue\_Mapping

#### Description

The mapping class create the feature reference expression for the subject of the SatisfyRequirementUsage element.

#### General Mappings

`GenericToFeatureReferenceExpression_Mapping`

#### Mapping Source

Abstraction

#### Mapping Target

FeatureReferenceExpression

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set{SatisfySubjectReferenceUsageValueOwningMembership_Mapping.getMapped(from) ,  
ReturnParameterFeatureMembership_Factory.create() }
```

### 7.8.8.3.27 SatisfySubjectReferenceUsageValueFeature\_Mapping

#### Description

The mapping class creates the feature element for the feature reference expression of the subject of the SatisfyRequirementUsage element.

#### General Mappings

`GenericToFeature_Mapping`

## Mapping Source

Abstraction

## Mapping Target

ReferenceUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set{SatisfySubjectReferenceUsageFeatureValue_Mapping.getMapped(from) }`
- `ReferenceUsage::direction () : FeatureDirectionKind [0..1]`  
`KerML::FeatureDirectionKind::_in'`

### 7.8.8.3.26 SatisfySubjectReferenceUsageValue\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

The mapping class create the feature reference expression for the subject of the SatisfyRequirementUsage element.

## General Mappings

ToFeatureReferenceExpression\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

FeatureReferenceExpression

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping Source

Abstraction

## Mapping Target

Feature

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Feature::ownedRelationship () : Relationship [0..\*]

```
Set { SatisfySubjectReferenceUsageFeatureChaining_Mapping.getMapped (from) ,  
      SatisfySubjectReferenceUsageValueFeatureChainingProperty_Mapping.getMapped (from) }
```

### 7.8.8.3.28 SatisfySubjectReferenceUsageFeatureChaining\_Mapping

#### Description

The mapping class creates the feature chaining element from SysML v2 SatisfyRequirementUsage's reference usage element.

#### General Mappings

**Generic**ToFeatureChaining\_Mapping

## Mapping Source

Abstraction

## Mapping Target

FeatureChaining

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureReferenceExpression::ownedRelationship () : Relationship [0..*]`

```
Set{SatisfySubjectReferenceUsageValueOwningMembership_Mapping.getMapped(from),  
ReturnParameterFeatureMembership_Factory.create() }
```

### 7.8.8.3.27 SatisfySubjectReferenceUsageValueFeature\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

The mapping class creates the feature element for the feature reference expression of the subject of the `SatisfyRequirementUsage` element.

##### General Mappings

ToFeature\_[Init](#)  
Mapping

##### Mapping Source

Abstraction

##### Mapping Target

Feature

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Feature::ownedRelationship () : Relationship [0..*]`

```
Set{SatisfySubjectReferenceUsageFeatureChaining_Mapping.getMapped(from),  
SatisfySubjectReferenceUsageValueFeatureChainingProperty_Mapping.getMapped(from) }
```

### 7.8.8.3.28 SatisfySubjectReferenceUsageFeatureChaining\_Mapping

#### [SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

##### Description

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChaining::chainingFeature () : Feature [1]`

```
SatisfyReferenceUsage_Mapping.getMapped(from)
```

#### 7.8.8.3.29 SatisfySubjectReferenceUsageValueFeatureChainingProperty\_Mapping

##### Description

The mapping class creates the feature chaining element from the source element of the SysML v1 satisfy relationship.

##### General Mappings

`GenericToFeatureChaining_Mapping`

##### Mapping Source

Abstraction

##### Mapping Target

FeatureChaining

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChaining::chainingFeature () : Feature [1]`

```
from.client->any(c | true)
```

#### 7.8.8.3.30 SatisfySubjectReferenceUsageFeatureValue\_Mapping

##### Description

Creates a feature value relationship.

##### General Mappings

`GenericToFeatureValue_Mapping`

##### Mapping Source

Abstraction

The mapping class creates the feature chaining element from SysML v2 SatisfyRequirementUsage's reference usage element.

### General Mappings

ToFeatureChaining\_Init  
Mapping

### Mapping Source

Abstraction

### Mapping Target

FeatureChaining

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureChaining::chainingFeature () : Feature [1]  
`SatisfyReferenceUsage_Mapping.getMapped(from)`

### 7.8.8.3.29 SatisfySubjectReferenceUsageValueFeatureChainingProperty\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the feature chaining element from the source element of the SysML v1 satisfy relationship.

### General Mappings

ToFeatureChaining\_Init  
Mapping

### Mapping Source

Abstraction

### Mapping Target

FeatureChaining

### Owned Mappings

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]

`SatisfySubjectReferenceUsageValue_Mapping.getMapped(from)`

### 7.8.8.3.31 SatisfySubjectReferenceUsageValueOwningMembership\_Mapping

#### Description

Creates a owning membership relationship for *ownedMemberElement()*.

#### General Mappings

**Generic**ToOwningMembership\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

OwningMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]

`SatisfySubjectReferenceUsageValueFeature_Mapping.getMapped(from)`



(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureChaining::chainingFeature () : Feature [1]`

```
from.client->any(c | true)
```

### 7.8.8.3.30 SatisfySubjectReferenceUsageFeatureValue\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature value relationship.

#### General Mappings

ToFeatureValue\_Init  
Mapping

#### Mapping Source

Abstraction

#### Mapping Target

FeatureValue

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
SatisfySubjectReferenceUsageValue_Mapping.getMapped(from)
```

### 7.8.8.3.31 SatisfySubjectReferenceUsageValueOwningMembership\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

### 7.8.8.3.32 SatisfySubjectSubjectMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

GenericToSubjectMembership\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

SubjectMembership

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- SubjectMembership::ownedMemberParameter () : Feature [1]  
SatisfySubjectReferenceUsage\_Mapping.getMapped(from)

### 7.8.8.3.33 SatisfyFeatureTyping\_Mapping

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

GenericToFeatureTyping\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

## Description

Creates a owning membership relationship for *ownedMemberElement()*.

## General Mappings

ToOwningMembership\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

OwningMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- OwningMembership::ownedMemberElement () : Element [1]  
`SatisfySubjectReferenceUsageValueFeature_Mapping.getMapped(from)`

### 7.8.8.3.32 SatisfySubjectSubjectMembership\_Mapping

#### **SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a membership relationship for *memberElement()*.

## General Mappings

ToSubjectMembership\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

SubjectMembership

## Owned Mappings

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`from.supplier->any(s | true)`

#### 7.8.8.3.34 SatisfyReferenceUsageFeatureTyping\_Mapping

##### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

##### General Mappings

**Generic**ToFeatureTyping\_Mapping

##### Mapping Source

Abstraction

##### Mapping Target

FeatureTyping

##### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`from.client->any(c | true).owner`

#### 7.8.8.3.35 TestCaseActivity\_Mapping

##### Description

A SysML::Requirements::TestCase applied to an activity is mapped to a SysML v2 VerificationCaseDefinition element.

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `SubjectMembership::ownedMemberParameter () : Feature [1]`  
`SatisfySubjectReferenceUsage_Mapping.getMapped (from)`

### 7.8.8.3.33 SatisfyFeatureTyping\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

#### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

#### General Mappings

ToFeatureTyping\_Init  
Mapping

#### Mapping Source

Abstraction

#### Mapping Target

FeatureTyping

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureTyping::type () : Type [1]`  
`from.supplier->any (s | true)`

### 7.8.8.3.34 SatisfyReferenceUsageFeatureTyping\_Mapping

[SYSML2\\_-220: Replace Generic mapping classes by Initializers](#)

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
verification def SysMLv1ActivityTestCase {
    return verdict : VerificationCases::VerdictKind;
}
```

## General Mappings

ActivityAsDefinition\_Mapping

### Mapping Source

Activity

### Mapping Target

VerificationCaseDefinition

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Requirements::TestCase')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- VerificationCaseDefinition::ownedRelationship () : Relationship [0..\*]

```
let relationships : Set(KerML::Relationship) =
    Helper.activityOwnedRelationship(from) in
let verdictParameter : Set(UML::Parameter) =
    from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter) and
    (e.ocIsType(UML::Parameter).type.name = 'VerdictKind')) in
let parameters : Set(UML::Parameter) =
    ((from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter))) -
    verdictParameter) in
let verifyRelationships : Set(UML::Abstraction) =
    from.clientDependency
    ->select( v |
        Helper.hasStereotypeApplied(v, 'SysML::Requirements::Verify')) in
relationships
->union(parameters->collect(p | ParameterMembership_Mapping.getMapped(p)))
->union(verdictParameter
    ->collect(vp |
        TestCaseActivityReturnParameterMembership_Mapping.getMapped(vp)))
->including(EmptySubjectMembership_Factory.create())
```

## Description

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  
`from.client->any(c | true).owner`

### 7.8.8.35 TestCaseActivity\_Mapping

## Description

A SysML::Requirements::TestCase applied to an activity is mapped to a SysML v2 VerificationCaseDefinition element.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
verification def SysMLv1ActivityTestCase {  
    return verdict : VerificationCases::VerdictKind;  
}
```

## General Mappings

ActivityAsDefinition\_Mapping

## Mapping Source

Activity

```
->including(EmptyObjectiveMembership_Factory.create())
->union(verifyRelationships->collect(v | Verify_Mapping.getMapped(v)))
```

### 7.8.8.3.36 TestCaseActivityReturnParameterMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ParameterMembership\_Mapping

#### Mapping Source

Parameter

#### Mapping Target

ReturnParameterMembership

#### Owned Mappings

(none)

### 7.8.8.3.37 TestCaseVerifyObjectiveMembership\_Mapping

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ownedMemberFeature () : Feature [1]

```
TestCaseVerifyObjectiveRequirementUsage_Mapping.getMapped(from)
```

### 7.8.8.3.38 TestCaseVerifyObjectiveRequirementUsage\_Mapping

#### Description

The mapping class creates the objective requirements usage of the SysML v2 **test** case.

#### General Mappings

No general mappings.

#### Mapping Source

Abstraction

#### Mapping Target

No target element.



## Mapping Target

VerificationCaseDefinition

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Requirements::TestCase')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- VerificationCaseDefinition::ownedRelationship () : Relationship [0..\*]

```
let relationships : Set(KerML::Relationship) =
  Helper.activityOwnedRelationship(from) in
let verdictParameter : Set(UML::Parameter) =
  from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter) and
    (e.ocIsType(UML::Parameter).type.name = 'VerdictKind')) in
let parameters : Set(UML::Parameter) =
  ((from.ownedElement->select(e | e.ocIsKindOf(UML::Parameter))) -
    verdictParameter) in
let verifyRelationships : Set(UML::Abstraction) =
  from.clientDependency
  ->select( v |
    Helper.hasStereotypeApplied(v, 'SysML::Requirements::Verify')) in
relationships
->union(parameters->collect(p | ParameterMembership_Mapping.getMapped(p)))
->union(verdictParameter
  ->collect(vp |
    TestCaseActivityReturnParameterMembership_Mapping.getMapped(vp)))
->including(EmptySubjectMembership_Factory.create())
->including(EmptyObjectiveMembership_Factory.create())
->union(verifyRelationships->collect(v | Verify_Mapping.getMapped(v)))
```

### 7.8.8.36 TestCaseActivityReturnParameterMembership\_Mapping

#### Description

Creates a membership relationship for *memberElement()*.

#### General Mappings

ParameterMembership\_Mapping

#### Mapping Source

Parameter

#### Mapping Target



ReturnParameterMembership

### Owned Mappings

(none)

### Applicable filters

(none)

## 7.8.8.3.37 TestCaseVerifyObjectiveMembership\_Mapping

[SYSML2 -4: Incomplete description of TestCaseVerifyObjectiveMembership\\_Mapping](#)

### Description

Creates a the objective membership relationship.

### General Mappings

UniqueMapping  
ToFeatureMembership\_Init

### Mapping Source

Abstraction

### Mapping Target

ObjectiveMembership

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ObjectiveMembership::ownedMemberFeature () : Feature [1]`  
`TestCaseVerifyObjectiveRequirementUsage_Mapping.getMapped(from)`

## 7.8.8.3.38 TestCaseVerifyObjectiveRequirementUsage\_Mapping

[SYSML2 -4: Incomplete description of TestCaseVerifyObjectiveMembership\\_Mapping](#)

### Description

The mapping class creates the objective requirements usage of the SysML v2 `verification` case.

### General Mappings

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ownedRelationship () : Relationship [0..*]`  
`Set{Verify_Mapping.getMapped(from) }`

### 7.8.8.3.39 TestCaseVerifyRequirementUsageReferenceSubsetting\_Mapping

#### Description

Creates a subsetting relationship.

#### General Mappings

GenericToSubsetting\_Mapping

#### Mapping Source

Abstraction

#### Mapping Target

ReferenceSubsetting

#### Owned Mappings

(none)

#### Applicable filters

(none)

#### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceSubsetting::referencedFeature () : Feature [1]`  
`from.supplier->get(0)`

### 7.8.8.3.40 TestCaseVerifyRequirementUsage\_Mapping

#### Description

ToRequirementUsage\_Init  
UniqueMapping

### Mapping Source

Abstraction

### Mapping Target

RequirementUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RequirementUsage::ownedRelationship () : Relationship [0..\*]  
Set{Verify\_Mapping.getMapped(from) }

## 7.8.8.3.39 TestCaseVerifyRequirementUsageReferenceSubsetting\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a subsetting relationship.

### General Mappings

ToSubsetting\_Init  
Mapping

### Mapping Source

Abstraction

### Mapping Target

ReferenceSubsetting

### Owned Mappings

(none)

### Applicable filters

(none)

The mapping class creates the requirements usage of the SysML v2 test case for the verify relationship.

## General Mappings

GenericToUsage\_Mapping

## Mapping Source

Abstraction

## Mapping Target

RequirementUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RequirementUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { TestCaseVerifyRequirementUsageReferenceSubsetting_Mapping.getMapped(from),  
EmptySubjectMembership_Factory.create(),  
CommonReturnParameterReferenceUsageMembership_Mapping.getMapped(from) }
```

### 7.8.8.3.41 Trace\_Mapping

#### Description

A SysML::Requirements::Trace relationship is mapped to a SysML v2 Dependency relationship annotated with a metadata usage tagging it as a former SysML v1 trace relationship.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
requirement <'id1'> SysMLv1Requirement1 {  
    doc /*  
        * requirement text  
    */  
}  
requirement <'id2'> SysMLv1Requirement2 {  
    doc /*  
        * requirement text  
    */  
}  
dependency from SysMLv1Requirement1 to SysMLv1Requirement2 {  
    @SysMLv1Library::TraceData {isTrace = true;}  
}
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceSubsetting::referencedFeature () : Feature [1]`  
`from.supplier->get (0)`

### 7.8.8.3.40 TestCaseVerifyRequirementUsage\_Mapping

#### [SYSML2 -220: Replace Generic mapping classes by Initializers](#)

## Description

The mapping class creates the requirements usage of the SysML v2 test case for the verify relationship.

## General Mappings

`ToUsage_Init`  
Mapping

## Mapping Source

Abstraction

## Mapping Target

RequirementUsage

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `RequirementUsage::ownedRelationship () : Relationship [0..*]`  
`Set { TestCaseVerifyRequirementUsageReferenceSubsetting_Mapping.getMapped (from),`  
`EmptySubjectMembership_Factory.create (),`  
`CommonReturnParameterReferenceUsageMembership_Mapping.getMapped (from) }`

### 7.8.8.3.41 Trace\_Mapping

## Description

A SysML::Requirements::Trace relationship is mapped to a SysML v2 Dependency relationship annotated with a metadata usage tagging it as a former SysML v1 trace relationship.

## General Mappings

Abstraction\_Mapping

## Mapping Source

Abstraction

## Mapping Target

Dependency

## Owned Mappings

(none)

## Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Requirements::Trace')
```

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Dependency::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()  
->including(TraceAnnotation_Mapping.getMapped(from))
```

### 7.8.8.3.42 TraceAnnotation\_Mapping

#### Description

The mapping class creates the annotation relationship for the SysML::Requirements::Trace mapping.

## General Mappings

**Generic**ToAnnotation\_Mapping

## Mapping Source

Abstraction

## Mapping Target

Annotation

## Owned Mappings

(none)



The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
requirement <'id1'> SysMLv1Requirement1 {
    doc /*
        * requirement text
        */
}
requirement <'id2'> SysMLv1Requirement2 {
    doc /*
        * requirement text
        */
}
dependency from SysMLv1Requirement1 to SysMLv1Requirement2 {
    @SysMLv1Library::TraceData {isTrace = true;}
}
```

## General Mappings

Abstraction\_Mapping

### Mapping Source

Abstraction

### Mapping Target

Dependency

### Owned Mappings

(none)

### Applicable filters

This mapping applies only if the following (OCL) condition implemented by the operation *filter(src : Element) : Boolean* is verified:

```
Helper.hasStereotypeApplied(src, 'SysML::Requirements::Trace')
```

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Dependency::ownedRelationship () : Relationship [0..\*]

```
self.oclAsType(ElementMain_Mapping).ownedRelationship()
->including(TraceAnnotation_Mapping.getMapped(from))
```

#### 7.8.8.3.42 TraceAnnotation\_Mapping

#### **SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

The mapping class creates the annotation relationship for the SysML::Requirements::Trace mapping.

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Annotation::annotatingElement () : AnnotatingElement [1]`  
`TraceMetadataUsage_Mapping.getMapped (from)`

#### 7.8.8.3.43 TraceMetadataFeatureMembership\_Mapping

##### Description

Creates a feature membership relationship for *ownedMemberFeature()*.

##### General Mappings

**Generic**ToFeatureMembership\_Mapping

##### Mapping Source

Abstraction

##### Mapping Target

FeatureMembership

##### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`TraceMetadataReferenceUsage_Mapping.getMapped (from)`

#### 7.8.8.3.44 TraceMetadataReferenceUsage\_Mapping

##### Description

Creates a reference usage.

##### General Mappings

## General Mappings

ToAnnotation\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

Annotation

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- Annotation::annotatingElement () : AnnotatingElement [1]  
`TraceMetadataUsage_Mapping.getMapped (from)`

### 7.8.8.3.43 TraceMetadataFeatureMembership\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a feature membership relationship for *ownedMemberFeature()*.

## General Mappings

ToFeatureMembership\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

FeatureMembership

## Owned Mappings

(none)

## Applicable filters

## GenericToReferenceUsage\_Mapping

### Mapping Source

Abstraction

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- ReferenceUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { TraceMetadataReferenceUsageRedefinition_Mapping.getMapped (from) ,  
TraceMetadataReferenceUsageFeatureValue_Mapping.getMapped (from) }
```

## 7.8.8.3.45 TraceMetadataReferenceUsageFeatureValue\_Mapping

### Description

Creates a feature value relationship.

### General Mappings

## GenericToFeatureValue\_Mapping

### Mapping Source

Abstraction

### Mapping Target

FeatureValue

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureMembership::ownedMemberFeature () : Feature [1]`  
`TraceMetadataReferenceUsage_Mapping.getMapped (from)`

#### 7.8.8.3.44 TraceMetadataReferenceUsage\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a reference usage.

### General Mappings

ToReferenceUsage\_Init  
Mapping

### Mapping Source

Abstraction

### Mapping Target

ReferenceUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `ReferenceUsage::ownedRelationship () : Relationship [0..*]`  
`Set {TraceMetadataReferenceUsageRedefinition_Mapping.getMapped (from) ,`  
`TraceMetadataReferenceUsageFeatureValue_Mapping.getMapped (from) }`

#### 7.8.8.3.45 TraceMetadataReferenceUsageFeatureValue\_Mapping

**SYSML2\_-220: Replace Generic mapping classes by Initializers**

### Description

Creates a feature value relationship.

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `FeatureValue::value () : Expression [1]`

```
LiteralBoolean_Factory.create(true)
```

#### 7.8.8.3.46 TraceMetadataReferenceUsageRedefinition\_Mapping

##### Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

##### General Mappings

**Generic**ToRedefinition\_Mapping

##### Mapping Source

Abstraction

##### Mapping Target

Redefinition

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::TraceData::isTrace')
```

#### 7.8.8.3.47 TraceMetadataUsage\_Mapping

##### Description

Create the metadata usage element to annotate a dependency relationship with the information that its SysML v1 mapping source element is a SysML v1 trace relationship.

##### General Mappings

**Generic**ToMetadataUsage\_Mapping

##### Mapping Source

## General Mappings

ToFeatureValue\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

FeatureValue

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureValue::value () : Expression [1]  
`LiteralBoolean_Factory.create(true)`

### 7.8.8.3.46 TraceMetadataReferenceUsageRedefinition\_Mapping

**SYSML2 -220: Replace Generic mapping classes by Initializers**

## Description

Creates a redefinition relationship for the *redefiningFeature()* and the *redefinedFeature()*.

## General Mappings

ToRedefinition\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

Redefinition

## Owned Mappings

(none)

## Applicable filters

Abstraction

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- MetadataUsage::ownedRelationship () : Relationship [0..\*]  

```
Set { TraceMetadataUsageFeatureTyping_Mapping.getMapped (from) ,  
TraceMetadataFeatureMembership_Mapping.getMapped (from) }
```

## 7.8.8.3.48 TraceMetadataUsageFeatureTyping\_Mapping

### Description

Creates a feature typing relationship owned by the element *typedFeature()*.

### General Mappings

GenericToFeatureTyping\_Mapping

### Mapping Source

Abstraction

### Mapping Target

FeatureTyping

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]



(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `Redefinition::redefinedFeature () : Feature [1]`  

```
SysML2::AttributeUsage.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::TraceData::isTrace')
```

#### 7.8.8.3.47 TraceMetadataUsage\_Mapping

##### **SysML2 -220: Replace Generic mapping classes by Initializers**

### Description

Create the metadata usage element to annotate a dependency relationship with the information that its SysML v1 mapping source element is a SysML v1 trace relationship.

### General Mappings

ToMetadataUsage\_Init  
Mapping

### Mapping Source

Abstraction

### Mapping Target

MetadataUsage

### Owned Mappings

(none)

### Applicable filters

(none)

### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- `MetadataUsage::ownedRelationship () : Relationship [0..*]`  

```
Set{TraceMetadataUsageFeatureTyping_Mapping.getMapped(from),  
TraceMetadataFeatureMembership_Mapping.getMapped(from)}
```

#### 7.8.8.3.48 TraceMetadataUsageFeatureTyping\_Mapping

##### **SysML2 -220: Replace Generic mapping classes by Initializers**

### Description

```

SYSML2::MetadataDefinition.allInstances()
->any(m | m.qualifiedName = 'SysMLv1Library::TraceData')

```

#### 7.8.8.3.49 Verify\_Mapping

##### Description

A SysML::Requirements::Verify relationship is mapped to a SysML v2 RequirementVerificationMembership relationship.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```

requirement <'idl'> SysMLv1Requirement {
    doc /*
        * requirement text
        */
}
verification def SysMLv1TestCase {
    objective objective_SysMLv1TestCase {
        verify SysMLv1Requirement;
    }
    return verdict : VerificationCases::VerdictKind;
}

```

##### General Mappings

**Generic**ToRelationship\_Mapping

##### Mapping Source

Abstraction

##### Mapping Target

RequirementVerificationMembership

##### Owned Mappings

(none)

##### Applicable filters

(none)

##### Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RequirementVerificationMembership::ownedRelatedElement () : Element [0..\*]  
Set{TestCaseVerifyRequirementUsage\_Mapping.getMapped(from) }

#### 7.8.8.3.50 Model Libraries

Creates a feature typing relationship owned by the element *typedFeature()*.

## General Mappings

ToFeatureTyping\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

FeatureTyping

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- FeatureTyping::type () : Type [1]  

```
SysML2::MetadataDefinition.allInstances()  
->any(m | m.qualifiedName = 'SysMLv1Library::TraceData')
```

### 7.8.8.3.49 Verify\_Mapping

#### **SysML2 -220: Replace Generic mapping classes by Initializers**

## Description

A SysML::Requirements::Verify relationship is mapped to a SysML v2 RequirementVerificationMembership relationship.

The following shows an example of what the textual SysML v2 syntax of the result of the transformation may look like.

```
requirement <'idl'> SysMLv1Requirement {  
  doc /*  
    * requirement text  
  */  
}  
verification def SysMLv1TestCase {  
  objective objective_SysMLv1TestCase {  
    verify SysMLv1Requirement;  
  }  
  return verdict : VerificationCases::VerdictKind;  
}
```

#### **7.8.8.3.50.1 Verdicts**

##### **7.8.8.3.50.1.1 VerdictKind**

The enumeration VerdictKind is mapped to the SysML v2 VerificationCases::VerdictKind model library element.

## General Mappings

ToRelationship\_Init  
Mapping

## Mapping Source

Abstraction

## Mapping Target

RequirementVerificationMembership

## Owned Mappings

(none)

## Applicable filters

(none)

## Mapping rules

In addition to the inherited rules, the following lists the mapping class specific mapping rules for the target element properties.

- RequirementVerificationMembership::ownedRelatedElement () : Element [0..\*]  
`Set{TestCaseVerifyRequirementUsage_Mapping.getMapped(from) }`

### 7.8.8.3.50 Model Libraries

#### 7.8.8.3.50.1 Verdicts

##### 7.8.8.3.50.1.1 VerdictKind

The enumeration VerdictKind is mapped to the SysML v2 VerificationCases::VerdictKind model library element.