

SDMX 3.0 web services cheat sheet, v2.0.0

Legend: **Mandatory path parameter** / **Optional path parameter** / **Query string parameter** (all optional)

Data queries: https://host/data/context/agency/id/version/key?c&updatedAfter&firstNObservations&lastNObservations&attributes&measures&dimensionAtObservation&includeHistory&offset&limit&sort		Default	Multi
context	The context of data retrieval: datastructure , dataflow , provisionagreement	*	Y
agency	Agency maintaining the artefact (e.g.: BIS)	*	Y
id	Context ID (e.g.: CBS)	*	Y
version	Artefact version (e.g.: 1.0.0)	*	Y
key	Key of the series to be returned (e.g: D.NOK.EUR.SP00.A). Wildcarding supported (e.g: D.*.EUR.SP00.A).	*	Y
c	Filter by component values (e.g. c[REF_AREA]=CH) with support for operators (e.g. c[TIME_PERIOD]=ge:2000)		Y
updatedAfter	Retrieves what changed since supplied timestamp. Must be percent-encoded (e.g.: 2009-05-15T14%3A15%3A00%2B01%3A00)		N
firstNObservations	Maximum number of observations starting from the first observation		N
lastNObservations	Maximum number of observations counting back from the most recent observation		N
dimensionAtObservation	Id of the dimension at the observation level		N
attributes	The attributes to be returned: dsd , msd , dataset , series , obs , all , none , {attribute_id}	dsd	Y
measures	The measures to be returned: all , none , {measure_id}	all	Y
includeHistory	Whether to return vintages	false	N
offset	The number of observations to skip before beginning to return observations	0	N
limit	The maximum number of observations to be returned		N
sort	The order in which the observations must be returned (e.g. TIME_PERIOD:desc)		N

Data validity queries: https://host/schema/context/agency/id/version?dimensionAtObservation&explicitMeasure		Default	Multi
context	The context of data retrieval: datastructure , dataflow , provisionagreement		N
agency	Agency maintaining the artefact (e.g.: ECB)		N
artefact	Artefact ID (e.g.: EXR)		N
version	Artefact version (e.g.: 1.0.0)	*	N
dimensionAtObservation	Id of the dimension at the observation level		N

Data availability queries: https://host/availability/context/agency/id/version/key/componentId?c&updatedAfter&references&mode		Default	Multi
context	The context of data retrieval: <code>datastructure</code> , <code>dataflow</code> , <code>provisionagreement</code>	*	N
agency	Agency maintaining the artefact (e.g.: ECB)	*	Y
artefact	Artefact ID (e.g.: EXR)	*	Y
version	Artefact version (e.g.: 1.0.0)	*	Y
key	Key of the series to be returned (e.g: D.NOK.EUR.SP00.A). Wildcarding supported (e.g: D.*.EUR.SP00.A).	*	Y
componentId	The id of the dimension for which to obtain availability information	*	Y
c	Filter by component values (e.g. c[REF_AREA]=CH) with support for operators (e.g. c[TIME_PERIOD]=ge:2000)		Y
updatedAfter	Retrieves what changed since supplied timestamp. Must be percent-encoded (e.g.: 2009-05-15T14%3A15%3A00%2B01%3A00)		N
references	References to be returned: <code>odelist</code> , <code>datastructure</code> , <code>conceptscheme</code> , <code>dataflow</code> , <code>dataprovidersscheme</code> , <code>none</code> , <code>all</code>	none	Y
mode	The resolution mode: <code>exact</code> , <code>available</code>	exact	N

Structure queries: https://host/structure/type/agency/id/version/item?detail&references		Default	Multi
type	The type of structure: <code>datastructure</code> , <code>metadatastructure</code> , <code>categoryscheme</code> , <code>conceptscheme</code> , <code>odelist</code> , <code>hierarchy</code> , <code>hierarchyassociation</code> , <code>valuelist</code> , <code>agency</code> , <code>agency</code> , <code>dataprovidersscheme</code> , <code>dataconsumerscheme</code> , <code>organisationunitscheme</code> , <code>dataflow</code> , <code>metadataflow</code> , <code>reportingtaxonomy</code> , <code>provisionagreement</code> , <code>structuremap</code> , <code>representationmap</code> , <code>conceptschememap</code> , <code>categoryschememap</code> , <code>organisationschememap</code> , <code>reportingtaxonomymap</code> , <code>process</code> , <code>categorisation</code> , <code>dataconstraint</code> , <code>metadataconstraint</code> , <code>structure</code> , <code>transformationscheme</code> , <code>rulesetscheme</code> , <code>userdefinedoperatorscheme</code> , <code>customtypescheme</code> , <code>namepersonalisationscheme</code> , <code>vtlmappingscheme</code>	*	N
agency	Agency maintaining the artefact (e.g.: SDMX)	*	Y
id	Artefact ID (e.g.: CL_FREQ)	*	Y
version	Artefact version (e.g.: 1.0.0)	~	Y
item	ID of the item to be returned.	*	Y
detail	Amount of information: <code>allstubs</code> , <code>referencestubs</code> , <code>allcompletestubs</code> , <code>referencecompletestubs</code> , <code>referencepartial</code> , <code>raw</code> , <code>partialraw</code> , <code>full</code>	full	N
references	References to be returned: <code>none</code> , <code>parents</code> , <code>parentsandsiblings</code> , <code>ancestors</code> , <code>children</code> , <code>descendants</code> , <code>all</code> , <code>a resource type</code>	none	Y

Metadata queries:

https://host/metadata/metadataset/provider/id/version?detail or
https://host/metadata/metadataflow/agency/id/version/provider?detail or
https://host/metadata/structure/type/agency/id/version/provider?detail

		Default	Multi
provider	The provider of metadata	*	Y
agency	Agency maintaining the artefact (e.g.: ECB)	*	Y
id	Artefact ID (e.g.: EXR)	*	Y
version	Artefact version (e.g.: 1.0.0)	*	Y
type	The structure type (cf. Structure queries)	*	N
detail	The amount of information to be returned: full, allstubs	full	N

Useful HTTP headers

If-Modified-Since	Get the data only if something has changed (If-None-Match is an alternative)
Accept	Select the desired format
Accept-Encoding	Compress the response
Accept-Language	Select the desired language

Supported formats

SDMX-ML Data	application/vnd.sdmx.data+xml;version=3.0.0
SDMX-JSON Data	application/vnd.sdmx.data+json;version=2.0.0
SDMX-CSV Data	application/vnd.sdmx.data+csv;version=2.0.0
SDMX-ML Structure	application/vnd.sdmx.structure+xml;version=3.0.0
SDMX-JSON Structure	application/vnd.sdmx.structure+json;version=2.0.0
SDMX-ML Metadata	application/vnd.sdmx.metadata+xml;version=2.0.0
SDMX-JSON Metadata	application/vnd.sdmx.metadata+json;version=2.0.0
SDMX-CSV Metadata	application/vnd.sdmx.metadata+csv;version=2.0.0

Period formats

Daily/Business	YYYY-MM-DD
Weekly	YYYY-W[01-53]
Monthly	YYYY-MM
Quarterly	YYYY-Q[1-4]
Semi-annual	YYYY-S[1-2]
Annual	YYYY

Useful response codes

200 (OK)	Life is good
204 (No content)	No results. Mostly harmless, especially if you used <code>updatedAfter</code>
304 (No change)	No change since the timestamp supplied in the If-Modified-Since header
400 (Syntax error)	Your query checking you must
401 (Login needed)	Only available on a need to know basis
406 (Invalid format)	Not a supported format. No worries, SDMX is all you need
413 (Results too large)	You know greed is a sin, right?
414 (URI too long)	Write short sentences
422 (Semantic error)	The syntax of the query is OK but it makes no sense anyway. Tolerated only on April Fools
500 (Server error)	Someone somewhere is having a bad day
501 (Not implemented)	Feature coming soon in a web service near you
503 (Unavailable)	Try again later.

Special characters

*	All
+	Latest stable version
~	Latest version (whether stable, draft or unversioned)
,	Or
.	Subpart operator
+	Multivalues attribute

Operators for component-based queries

eq	Equal
ne	Not equal
lt	Less than
le	Less than or equal to
gt	Greater than
ge	Greater than or equal to
co	Contains
nc	Does not contain
sw	Starts with
ew	Ends with
nd	And
or	Or

Tips and tricks

- **Trust but verify!** Check the identity of the web service by connecting over https.
- **Know your mime type!** Specify the output format you want, using the **HTTP Accept** header. Else, the web service will determine the format and this choice may change over time (for example, when new versions of SDMX are released).
- **Laziness is a virtue!** Don't lose time, resources and bandwidth processing the response if nothing has changed! Use the **updatedAfter** parameter if you can handle deltas, or the **If-Modified-Since** header otherwise.
- **Travel light!** Compress the response, using the **HTTP Accept-Encoding** header.
- **The answer is 42.** Or not. Check the status code of the response. It's not always 200 (or 42).
- **Read The Fine Manual.** Check the SDMX RESTful specification (Section 7): http://sdmx.org/?page_id=10
- **Contact us!** You think a killer feature is missing? Drop us a line at twg@sdmx.org.