SQL Code with Internal Documentation

```
-- PHASE 1 - INITIAL EXPLORATION: UNDERSTAND SCHEMA & TABLES
-- ============================================================

-- Query #1: List all tables in the database
SELECT TABLE_NAME, TABLE_TYPE
FROM INFORMATION_SCHEMA.TABLES
WHERE TABLE_SCHEMA = 'dbo'
ORDER BY TABLE_NAME;

-- Query #2: Count rows in each table
SELECT
    t.NAME AS TableName,
    p.rows AS RowCount
FROM sys.tables t
INNER JOIN sys.partitions p ON t.object_id = p.object_id
WHERE p.index_id IN (0, 1)
ORDER BY p.rows DESC;

-- Query #3: Examine the structure of a specific table
-- Replace 'YourTableName' with the actual table name
SELECT
    COLUMN_NAME,
    DATA_TYPE,
    CHARACTER_MAXIMUM_LENGTH,
    IS_NULLABLE,
    COLUMN_DEFAULT
FROM INFORMATION_SCHEMA.COLUMNS
WHERE TABLE_NAME = 'YourTableName'
ORDER BY ORDINAL_POSITION;

-- Query #4: Check for primary keys and foreign keys
SELECT
    tc.TABLE_NAME,
    tc.CONSTRAINT_NAME,
    tc.CONSTRAINT_TYPE,
    kcu.COLUMN_NAME
FROM INFORMATION_SCHEMA.TABLE_CONSTRAINTS tc
JOIN INFORMATION_SCHEMA.KEY_COLUMN_USAGE kcu
    ON tc.CONSTRAINT_NAME = kcu.CONSTRAINT_NAME
WHERE tc.CONSTRAINT_TYPE IN ('PRIMARY KEY', 'FOREIGN KEY')
ORDER BY tc.TABLE_NAME, tc.CONSTRAINT_TYPE;

-- Query #5: Sample data from a table (first 10 rows)
SELECT TOP 10 *
FROM YourTableName;

-- Query #6: Check for NULL values in key columns
SELECT
    COUNT(*) AS TotalRows,
    COUNT(CustomerID) AS NonNullCustomerID,
    COUNT(*) - COUNT(CustomerID) AS NullCustomerID,
    COUNT(OrderDate) AS NonNullOrderDate,
    COUNT(*) - COUNT(OrderDate) AS NullOrderDate
FROM Orders;

-- Query #7: Identify duplicate records
SELECT
    CustomerID,
    OrderDate,
    COUNT(*) AS DuplicateCount
FROM Orders
GROUP BY CustomerID, OrderDate
HAVING COUNT(*) > 1
ORDER BY DuplicateCount DESC;

-- Query #8: Get basic statistics for numeric columns
SELECT
    MIN(OrderAmount) AS MinAmount,
    MAX(OrderAmount) AS MaxAmount,
    AVG(OrderAmount) AS AvgAmount,
    STDEV(OrderAmount) AS StdDevAmount,
    SUM(OrderAmount) AS TotalAmount
FROM Orders;

-- Query #9: Check date ranges in temporal columns
SELECT
    MIN(OrderDate) AS EarliestOrder,
    MAX(OrderDate) AS LatestOrder,
    DATEDIFF(DAY, MIN(OrderDate), MAX(OrderDate)) AS DaysSpan
FROM Orders;

-- Query #10: Examine categorical columns
SELECT
    Status,
    COUNT(*) AS StatusCount,
    CAST(COUNT(*) * 100.0 / SUM(COUNT(*)) OVER() AS DECIMAL(5,2)) AS Percentage
FROM Orders
GROUP BY Status
ORDER BY StatusCount DESC;

-- Query #11: Find orphaned records (foreign key violations)
SELECT o.*
FROM Orders o
LEFT JOIN Customers c ON o.CustomerID = c.CustomerID
WHERE c.CustomerID IS NULL;

-- Query #12: Check for duplicate primary keys
SELECT
    PrimaryKeyColumn,
    COUNT(*) AS DuplicateCount
FROM YourTableName
GROUP BY PrimaryKeyColumn
HAVING COUNT(*) > 1;

-- Query #13: Get table size information
EXEC sp_spaceused 'YourTableName';

-- Query #14: Find all indexes on a table
SELECT
    i.name AS IndexName,
    i.type_desc AS IndexType,
    i.is_unique AS IsUnique,
    i.is_primary_key AS IsPrimaryKey,
    STRING_AGG(c.name, ', ') AS IndexedColumns
FROM sys.indexes i
JOIN sys.index_columns ic ON i.object_id = ic.object_id AND i.index_id = ic.index_id
JOIN sys.columns c ON ic.object_id = c.object_id AND ic.column_id = c.column_id
WHERE i.object_id = OBJECT_ID('YourTableName')
GROUP BY i.name, i.type_desc, i.is_unique, i.is_primary_key;

-- Query #15: Check for recently modified records
SELECT *
FROM YourTableName
WHERE ModifiedDate >= DATEADD(DAY, -7, GETDATE())
ORDER BY ModifiedDate DESC;

-- Query #16: Examine text/varchar columns for data quality issues
SELECT
    ColumnName,
    LEN(ColumnName) AS Length,
    ASCII(LEFT(ColumnName, 1)) AS FirstCharASCII,
    ASCII(RIGHT(ColumnName, 1)) AS LastCharASCII
FROM YourTableName
WHERE LEN(ColumnName) < 3
   OR ColumnName LIKE '% %'
   OR ColumnName LIKE '%[^a-zA-Z0-9 ]%';

-- Query #17: Get column statistics for query optimization
DBCC SHOW_STATISTICS('YourTableName', 'IndexName');

-- Query #18: Find tables without primary keys
SELECT t.TABLE_NAME
FROM INFORMATION_SCHEMA.TABLES t
LEFT JOIN INFORMATION_SCHEMA.TABLE_CONSTRAINTS tc
    ON t.TABLE_NAME = tc.TABLE_NAME
    AND tc.CONSTRAINT_TYPE = 'PRIMARY KEY'
WHERE t.TABLE_TYPE = 'BASE TABLE'
  AND tc.CONSTRAINT_NAME IS NULL;

-- Query #19: Create a data dictionary
SELECT
    t.TABLE_NAME,
    c.COLUMN_NAME,
    c.DATA_TYPE,
    c.CHARACTER_MAXIMUM_LENGTH,
    c.IS_NULLABLE,
    c.COLUMN_DEFAULT,
    ISNULL(ep.value, '') AS ColumnDescription
FROM INFORMATION_SCHEMA.TABLES t
JOIN INFORMATION_SCHEMA.COLUMNS c ON t.TABLE_NAME = c.TABLE_NAME
LEFT JOIN sys.extended_properties ep
    ON ep.major_id = OBJECT_ID(t.TABLE_SCHEMA + '.' + t.TABLE_NAME)
    AND ep.minor_id = c.ORDINAL_POSITION
    AND ep.name = 'MS_Description'
WHERE t.TABLE_TYPE = 'BASE TABLE'
ORDER BY t.TABLE_NAME, c.ORDINAL_POSITION;

-- Query #20: Check referential integrity
SELECT
    fk.name AS ForeignKeyName,
    tp.name AS ParentTable,
    cp.name AS ParentColumn,
    tr.name AS ReferencedTable,
    cr.name AS ReferencedColumn
FROM sys.foreign_keys fk
JOIN sys.tables tp ON fk.parent_object_id = tp.object_id
JOIN sys.tables tr ON fk.referenced_object_id = tr.object_id
JOIN sys.foreign_key_columns fkc ON fk.object_id = fkc.constraint_object_id
JOIN sys.columns cp ON fkc.parent_column_id = cp.column_id AND fkc.parent_object_id = cp.object_id
JOIN sys.columns cr ON fkc.referenced_column_id = cr.column_id AND fkc.referenced_object_id = cr.object_id;

-- ============================================================
-- END OF PHASE 1
-- ============================================================

-- PHASE 2 - DATA CLEANING & PREPARATION
-- ============================================================

-- Query #21: Handle NULL values with COALESCE and ISNULL
SELECT
    CustomerID,
    COALESCE(FirstName, '') AS FirstName,
    COALESCE(LastName, '') AS LastName,
    COALESCE(Email, 'no-email@unknown.com') AS Email,
    ISNULL(PhoneNumber, 'N/A') AS PhoneNumber,
    COALESCE(MiddleName, FirstName, 'Unknown') AS DisplayName
FROM Customers;

-- Query #22: Remove duplicate records using ROW_NUMBER
WITH DuplicateCTE AS (
    SELECT
        *,
        ROW_NUMBER() OVER (
            PARTITION BY CustomerID, OrderDate, OrderAmount
            ORDER BY OrderID
        ) AS RowNum
    FROM Orders
)
DELETE FROM DuplicateCTE
WHERE RowNum > 1;

-- Query #23: Standardize text data (trim, upper, lower)
SELECT
    CustomerID,
    TRIM(FirstName) AS FirstName,
    UPPER(TRIM(LastName)) AS LastName,
    LOWER(TRIM(Email)) AS Email,
    REPLACE(REPLACE(PhoneNumber, '-', ''), ' ', '') AS CleanPhone
FROM Customers;

-- Query #24: Fix inconsistent date formats
SELECT
    OrderID,
    OrderDate AS OriginalDate,
    TRY_CONVERT(DATE, OrderDate, 101) AS ParsedDate_MMDDYYYY,
    TRY_CONVERT(DATE, OrderDate, 103) AS ParsedDate_DDMMYYYY,
    TRY_CONVERT(DATE, OrderDate, 120) AS ParsedDate_ISO
FROM Orders
WHERE TRY_CONVERT(DATE, OrderDate) IS NULL;

-- Query #25: Remove outliers using IQR method
WITH Quartiles AS (
    SELECT
        PERCENTILE_CONT(0.25) WITHIN GROUP (ORDER BY OrderAmount) OVER() AS Q1,
        PERCENTILE_CONT(0.75) WITHIN GROUP (ORDER BY OrderAmount) OVER() AS Q3
    FROM Orders
),
IQR AS (
    SELECT
        Q1,
        Q3,
        Q3 - Q1 AS IQR,
        Q1 - 1.5 * (Q3 - Q1) AS LowerBound,
        Q3 + 1.5 * (Q3 - Q1) AS UpperBound
    FROM Quartiles
)
SELECT o.*
FROM Orders o
CROSS JOIN IQR
WHERE o.OrderAmount BETWEEN IQR.LowerBound AND IQR.UpperBound;

-- Query #26: Create a cleaned view of the data
CREATE VIEW vw_CleanOrders AS
SELECT
    o.OrderID,
    o.CustomerID,
    COALESCE(c.FirstName + ' ' + c.LastName, 'Unknown') AS CustomerName,
    o.OrderDate,
    o.OrderAmount,
    CASE
        WHEN o.OrderAmount < 0 THEN 0
        ELSE o.OrderAmount
    END AS CleanAmount,
    UPPER(TRIM(o.Status)) AS Status
FROM Orders o
LEFT JOIN Customers c ON o.CustomerID = c.CustomerID
WHERE o.OrderDate IS NOT NULL;

-- Query #27: Split delimited data into separate rows
SELECT
    ProductID,
    ProductName,
    TRIM(value) AS Category
FROM Products
CROSS APPLY STRING_SPLIT(Categories, ',');

-- Query #28: Pivot data from rows to columns
SELECT
    CustomerID,
    [2022] AS Orders2022,
    [2023] AS Orders2023,
    [2024] AS Orders2024
FROM (
    SELECT CustomerID, YEAR(OrderDate) AS OrderYear, OrderID
    FROM Orders
) AS SourceTable
PIVOT (
    COUNT(OrderID)
    FOR OrderYear IN ([2022], [2023], [2024])
) AS PivotTable;

-- Query #29: Unpivot data from columns to rows
SELECT
    ProductID,
    Quarter,
    Revenue
FROM ProductSales
UNPIVOT (
    Revenue FOR Quarter IN (Q1_Revenue, Q2_Revenue, Q3_Revenue, Q4_Revenue)
) AS UnpivotTable;

-- Query #30: Create a calculated/derived column
SELECT
    OrderID,
    OrderAmount,
    TaxRate,
    OrderAmount * TaxRate AS TaxAmount,
    OrderAmount * (1 + TaxRate) AS TotalWithTax,
    CASE
        WHEN OrderAmount >= 1000 THEN 'Large'
        WHEN OrderAmount >= 500 THEN 'Medium'
        ELSE 'Small'
    END AS OrderSize
FROM Orders;

-- Query #31: Validate email format
SELECT
    CustomerID,
    Email,
    CASE
        WHEN Email LIKE '%_@__%.__%' AND Email NOT LIKE '% %' THEN 'Valid'
        ELSE 'Invalid'
    END AS EmailStatus
FROM Customers;

-- Query #32: Create a numeric bucketing/binning column
SELECT
    CustomerID,
    TotalSpent,
    NTILE(4) OVER (ORDER BY TotalSpent) AS SpendQuartile,
    NTILE(10) OVER (ORDER BY TotalSpent) AS SpendDecile
FROM (
    SELECT CustomerID, SUM(OrderAmount) AS TotalSpent
    FROM Orders
    GROUP BY CustomerID
) AS CustomerSpend;

-- Query #33: Fill forward missing values (last observation carried forward)
SELECT
    EventID,
    EventTime,
    SensorValue,
    COALESCE(
        SensorValue,
        LAG(SensorValue, 1) IGNORE NULLS OVER (ORDER BY EventTime),
        LAG(SensorValue, 2) IGNORE NULLS OVER (ORDER BY EventTime)
    ) AS FilledValue
FROM SensorReadings;

-- Query #34: Export cleaned data to a temporary table
SELECT *
INTO #CleanedOrders
FROM vw_CleanOrders
WHERE OrderDate >= '2023-01-01';

-- ============================================================
-- END OF PHASE 2
-- ============================================================

-- PHASE 3 - ANALYTICAL QUERIES
-- ============================================================

-- Query #35: Calculate running totals and moving averages
SELECT
    OrderDate,
    DailyRevenue,
    SUM(DailyRevenue) OVER (ORDER BY OrderDate ROWS UNBOUNDED PRECEDING) AS RunningTotal,
    AVG(DailyRevenue) OVER (ORDER BY OrderDate ROWS BETWEEN 6 PRECEDING AND CURRENT ROW) AS MovingAvg7Day,
    AVG(DailyRevenue) OVER (ORDER BY OrderDate ROWS BETWEEN 29 PRECEDING AND CURRENT ROW) AS MovingAvg30Day
FROM (
    SELECT OrderDate, SUM(OrderAmount) AS DailyRevenue
    FROM Orders
    GROUP BY OrderDate
) AS DailySales;

-- Query #36: Year-over-year comparison
SELECT
    MONTH(OrderDate) AS Month,
    SUM(CASE WHEN YEAR(OrderDate) = 2023 THEN OrderAmount ELSE 0 END) AS Revenue2023,
    SUM(CASE WHEN YEAR(OrderDate) = 2024 THEN OrderAmount ELSE 0 END) AS Revenue2024,
    SUM(CASE WHEN YEAR(OrderDate) = 2024 THEN OrderAmount ELSE 0 END) -
    SUM(CASE WHEN YEAR(OrderDate) = 2023 THEN OrderAmount ELSE 0 END) AS YoYChange
FROM Orders
GROUP BY MONTH(OrderDate)
ORDER BY Month;

-- Query #37: Customer RFM (Recency, Frequency, Monetary) analysis
WITH RFM AS (
    SELECT
        CustomerID,
        DATEDIFF(DAY, MAX(OrderDate), GETDATE()) AS Recency,
        COUNT(DISTINCT OrderID) AS Frequency,
        SUM(OrderAmount) AS Monetary
    FROM Orders
    GROUP BY CustomerID
),
RFM_Scores AS (
    SELECT
        CustomerID,
        Recency,
        Frequency,
        Monetary,
        NTILE(5) OVER (ORDER BY Recency DESC) AS R_Score,
        NTILE(5) OVER (ORDER BY Frequency ASC) AS F_Score,
        NTILE(5) OVER (ORDER BY Monetary ASC) AS M_Score
    FROM RFM
)
SELECT
    *,
    CONCAT(R_Score, F_Score, M_Score) AS RFM_Segment
FROM RFM_Scores;

-- Query #38: Cohort analysis (monthly retention)
WITH FirstPurchase AS (
    SELECT
        CustomerID,
        MIN(DATEFROMPARTS(YEAR(OrderDate), MONTH(OrderDate), 1)) AS CohortMonth
    FROM Orders
    GROUP BY CustomerID
),
Activity AS (
    SELECT
        o.CustomerID,
        DATEFROMPARTS(YEAR(o.OrderDate), MONTH(o.OrderDate), 1) AS ActivityMonth,
        fp.CohortMonth,
        DATEDIFF(MONTH, fp.CohortMonth, DATEFROMPARTS(YEAR(o.OrderDate), MONTH(o.OrderDate), 1)) AS MonthsSinceCohort
    FROM Orders o
    JOIN FirstPurchase fp ON o.CustomerID = fp.CustomerID
)
SELECT
    CohortMonth,
    MonthsSinceCohort,
    COUNT(DISTINCT CustomerID) AS ActiveCustomers
FROM Activity
GROUP BY CohortMonth, MonthsSinceCohort
ORDER BY CohortMonth, MonthsSinceCohort;

-- Query #39: Market basket analysis (products frequently bought together)
SELECT
    a.ProductID AS Product_A,
    b.ProductID AS Product_B,
    COUNT(*) AS TimesBoughtTogether
FROM OrderItems a
JOIN OrderItems b
    ON a.OrderID = b.OrderID
    AND a.ProductID < b.ProductID
GROUP BY a.ProductID, b.ProductID
HAVING COUNT(*) >= 10
ORDER BY TimesBoughtTogether DESC;

-- Query #40: Funnel analysis
SELECT
    COUNT(DISTINCT SessionID) AS TotalSessions,
    COUNT(DISTINCT CASE WHEN PageType = 'ProductView' THEN SessionID END) AS ViewedProduct,
    COUNT(DISTINCT CASE WHEN PageType = 'AddToCart' THEN SessionID END) AS AddedToCart,
    COUNT(DISTINCT CASE WHEN PageType = 'Checkout' THEN SessionID END) AS StartedCheckout,
    COUNT(DISTINCT CASE WHEN PageType = 'Purchase' THEN SessionID END) AS Purchased
FROM WebEvents;

-- Query #41: Detect anomalies using standard deviation
WITH Stats AS (
    SELECT
        AVG(DailyCount) AS Mean,
        STDEV(DailyCount) AS StdDev
    FROM (
        SELECT OrderDate, COUNT(*) AS DailyCount
        FROM Orders
        GROUP BY OrderDate
    ) AS Daily
)
SELECT
    d.OrderDate,
    d.DailyCount,
    s.Mean,
    s.StdDev,
    (d.DailyCount - s.Mean) / s.StdDev AS ZScore
FROM (
    SELECT OrderDate, COUNT(*) AS DailyCount
    FROM Orders
    GROUP BY OrderDate
) d
CROSS JOIN Stats s
WHERE ABS((d.DailyCount - s.Mean) / s.StdDev) > 2;

-- Query #42: Create a pivot table dynamically
DECLARE @cols NVARCHAR(MAX), @query NVARCHAR(MAX);

SELECT @cols = STRING_AGG(QUOTENAME(Status), ',')
FROM (SELECT DISTINCT Status FROM Orders) AS Statuses;

SET @query = '
SELECT CustomerID, ' + @cols + '
FROM (
    SELECT CustomerID, Status, OrderID
    FROM Orders
) AS SourceTable
PIVOT (
    COUNT(OrderID)
    FOR Status IN (' + @cols + ')
) AS PivotTable;';

EXEC sp_executesql @query;

-- Query #43: Calculate customer lifetime value (CLV)
SELECT
    CustomerID,
    FirstOrderDate,
    LastOrderDate,
    DATEDIFF(MONTH, FirstOrderDate, LastOrderDate) + 1 AS CustomerMonths,
    TotalRevenue,
    TotalRevenue / (DATEDIFF(MONTH, FirstOrderDate, LastOrderDate) + 1) AS AvgMonthlyRevenue,
    TotalRevenue / (DATEDIFF(MONTH, FirstOrderDate, LastOrderDate) + 1) * 36 AS Projected3YearCLV
FROM (
    SELECT
        CustomerID,
        MIN(OrderDate) AS FirstOrderDate,
        MAX(OrderDate) AS LastOrderDate,
        SUM(OrderAmount) AS TotalRevenue
    FROM Orders
    GROUP BY CustomerID
) AS CustomerStats
WHERE DATEDIFF(MONTH, FirstOrderDate, LastOrderDate) > 0;

-- Query #44: Gap and island analysis (find consecutive sequences)
WITH Numbered AS (
    SELECT
        CustomerID,
        OrderDate,
        ROW_NUMBER() OVER (PARTITION BY CustomerID ORDER BY OrderDate) AS RN,
        DATEADD(DAY, -ROW_NUMBER() OVER (PARTITION BY CustomerID ORDER BY OrderDate), OrderDate) AS GroupKey
    FROM Orders
)
SELECT
    CustomerID,
    MIN(OrderDate) AS StreakStart,
    MAX(OrderDate) AS StreakEnd,
    COUNT(*) AS StreakLength
FROM Numbered
GROUP BY CustomerID, GroupKey
HAVING COUNT(*) >= 3
ORDER BY StreakLength DESC;

-- ============================================================
-- END OF PHASE 3
-- ============================================================

-- PHASE 4 - STORED PROCEDURES & AUTOMATION
-- ============================================================

-- Query #45: Create a stored procedure with parameters
CREATE PROCEDURE sp_GetCustomerOrders
    @CustomerID INT,
    @StartDate DATE = NULL,
    @EndDate DATE = NULL
AS
BEGIN
    SET NOCOUNT ON;

    SELECT
        o.OrderID,
        o.OrderDate,
        o.OrderAmount,
        o.Status
    FROM Orders o
    WHERE o.CustomerID = @CustomerID
      AND (@StartDate IS NULL OR o.OrderDate >= @StartDate)
      AND (@EndDate IS NULL OR o.OrderDate <= @EndDate)
    ORDER BY o.OrderDate DESC;
END;

-- Query #46: Create a stored procedure with error handling
CREATE PROCEDURE sp_SafeDeleteOrder
    @OrderID INT
AS
BEGIN
    SET NOCOUNT ON;

    BEGIN TRY
        BEGIN TRANSACTION;

        DELETE FROM OrderItems WHERE OrderID = @OrderID;
        DELETE FROM Orders WHERE OrderID = @OrderID;

        COMMIT TRANSACTION;
        PRINT 'Order deleted successfully.';
    END TRY
    BEGIN CATCH
        IF @@TRANCOUNT > 0
            ROLLBACK TRANSACTION;

        DECLARE @ErrorMessage NVARCHAR(4000) = ERROR_MESSAGE();
        RAISERROR(@ErrorMessage, 16, 1);
    END CATCH;
END;

-- Query #47: Create a trigger for audit logging
CREATE TRIGGER trg_OrderAudit
ON Orders
AFTER UPDATE
AS
BEGIN
    SET NOCOUNT ON;

    INSERT INTO OrderAuditLog (OrderID, ChangedColumn, OldValue, NewValue, ChangedBy, ChangedDate)
    SELECT
        i.OrderID,
        'Status',
        d.Status,
        i.Status,
        SYSTEM_USER,
        GETDATE()
    FROM inserted i
    JOIN deleted d ON i.OrderID = d.OrderID
    WHERE i.Status <> d.Status;
END;

-- Query #48: Create a scheduled job (SQL Server Agent)
EXEC msdb.dbo.sp_add_job
    @job_name = 'Daily_Data_Refresh';

EXEC msdb.dbo.sp_add_jobstep
    @job_name = 'Daily_Data_Refresh',
    @step_name = 'Refresh_Materialized_Views',
    @subsystem = 'TSQL',
    @command = 'EXEC sp_RefreshAllViews;';

EXEC msdb.dbo.sp_add_schedule
    @schedule_name = 'Daily_2AM',
    @freq_type = 4,
    @freq_interval = 1,
    @active_start_time = 020000;

EXEC msdb.dbo.sp_attach_schedule
    @job_name = 'Daily_Data_Refresh',
    @schedule_name = 'Daily_2AM';

-- Query #49: Create a temporary table for intermediate results
CREATE TABLE #TopCustomers (
    CustomerID INT,
    TotalSpent DECIMAL(18,2),
    OrderCount INT
);

INSERT INTO #TopCustomers
SELECT TOP 100
    CustomerID,
    SUM(OrderAmount),
    COUNT(*)
FROM Orders
GROUP BY CustomerID
ORDER BY SUM(OrderAmount) DESC;

SELECT * FROM #TopCustomers;

DROP TABLE #TopCustomers;

-- Query #50: Create a table-valued function
CREATE FUNCTION fn_GetOrdersByDateRange
(
    @StartDate DATE,
    @EndDate DATE
)
RETURNS TABLE
AS
RETURN
(
    SELECT
        OrderID,
        CustomerID,
        OrderDate,
        OrderAmount
    FROM Orders
    WHERE OrderDate BETWEEN @StartDate AND @EndDate
);

-- Usage:
SELECT * FROM fn_GetOrdersByDateRange('2024-01-01', '2024-12-31');

-- Query #51: Create a scalar function
CREATE FUNCTION fn_CalculateDiscount
(
    @OrderAmount DECIMAL(18,2),
    @CustomerTier VARCHAR(20)
)
RETURNS DECIMAL(18,2)
AS
BEGIN
    DECLARE @Discount DECIMAL(18,2);

    SET @Discount = CASE
        WHEN @CustomerTier = 'Gold' THEN @OrderAmount * 0.15
        WHEN @CustomerTier = 'Silver' THEN @OrderAmount * 0.10
        WHEN @CustomerTier = 'Bronze' THEN @OrderAmount * 0.05
        ELSE 0
    END;

    RETURN @Discount;
END;

-- Query #52: Create a view for reporting
CREATE VIEW vw_MonthlySalesReport
AS
SELECT
    YEAR(OrderDate) AS SalesYear,
    MONTH(OrderDate) AS SalesMonth,
    DATENAME(MONTH, OrderDate) AS MonthName,
    COUNT(DISTINCT CustomerID) AS UniqueCustomers,
    COUNT(OrderID) AS TotalOrders,
    SUM(OrderAmount) AS TotalRevenue,
    AVG(OrderAmount) AS AvgOrderValue
FROM Orders
GROUP BY YEAR(OrderDate), MONTH(OrderDate), DATENAME(MONTH, OrderDate);

-- Query #53: Create an index for performance optimization
CREATE NONCLUSTERED INDEX IX_Orders_CustomerID_OrderDate
ON Orders (CustomerID, OrderDate)
INCLUDE (OrderAmount, Status);

-- Query #54: Create a filtered index
CREATE NONCLUSTERED INDEX IX_Orders_Active
ON Orders (OrderDate)
WHERE Status = 'Active';

-- Query #55: Create a columnstore index for analytics
CREATE NONCLUSTERED COLUMNSTORE INDEX IX_Orders_Columnstore
ON Orders (OrderID, CustomerID, OrderDate, OrderAmount, Status);

-- Query #56: Update statistics and rebuild indexes
UPDATE STATISTICS Orders WITH FULLSCAN;

ALTER INDEX ALL ON Orders REBUILD;

-- Query #57: Create a database snapshot
CREATE DATABASE MyDatabase_Snapshot
ON (NAME = MyDatabase_Data, FILENAME = 'C:\Snapshots\MyDatabase_Snapshot.ss')
AS SNAPSHOT OF MyDatabase;

-- Query #58: Implement row-level security
CREATE FUNCTION fn_SecurityPredicate(@SalesRep AS VARCHAR(50))
RETURNS TABLE
WITH SCHEMABINDING
AS
RETURN SELECT 1 AS fn_result
WHERE @SalesRep = USER_NAME() OR USER_NAME() = 'dbo';

CREATE SECURITY POLICY SalesFilter
ADD FILTER PREDICATE dbo.fn_SecurityPredicate(SalesRep)
ON dbo.Orders
WITH (STATE = ON);

-- Query #59: Create a linked server query
SELECT *
FROM [LinkedServer].[RemoteDatabase].[dbo].[RemoteTable];

-- Query #60: Export data to CSV using BCP
EXEC xp_cmdshell 'bcp "SELECT * FROM MyDatabase.dbo.Orders" queryout "C:\Exports\Orders.csv" -c -t, -T -S localhost';

-- Query #61: Import data from CSV using BULK INSERT
BULK INSERT Orders_Staging
FROM 'C:\Imports\orders_new.csv'
WITH (
    FIELDTERMINATOR = ',',
    ROWTERMINATOR = '\n',
    FIRSTROW = 2,
    TABLOCK
);

-- Query #62: Create a data quality monitoring procedure
CREATE PROCEDURE sp_DataQualityReport
AS
BEGIN
    SET NOCOUNT ON;

    SELECT 'Orders' AS TableName, 'NULL CustomerID' AS Issue, COUNT(*) AS IssueCount
    FROM Orders WHERE CustomerID IS NULL
    UNION ALL
    SELECT 'Orders', 'Negative Amount', COUNT(*)
    FROM Orders WHERE OrderAmount < 0
    UNION ALL
    SELECT 'Orders', 'Future Date', COUNT(*)
    FROM Orders WHERE OrderDate > GETDATE()
    UNION ALL
    SELECT 'Orders', 'Duplicate OrderID', COUNT(*) - COUNT(DISTINCT OrderID)
    FROM Orders
    UNION ALL
    SELECT 'Customers', 'Missing Email', COUNT(*)
    FROM Customers WHERE Email IS NULL OR Email = '';
END;

-- Query #63: Create a temporal table (system-versioned)
CREATE TABLE Employees
(
    EmployeeID INT PRIMARY KEY,
    Name NVARCHAR(100),
    Department NVARCHAR(50),
    Salary DECIMAL(18,2),
    ValidFrom DATETIME2 GENERATED ALWAYS AS ROW START,
    ValidTo DATETIME2 GENERATED ALWAYS AS ROW END,
    PERIOD FOR SYSTEM_TIME (ValidFrom, ValidTo)
)
WITH (SYSTEM_VERSIONING = ON (HISTORY_TABLE = dbo.EmployeesHistory));

-- Query #64: Query historical data
SELECT *
FROM Employees
FOR SYSTEM_TIME AS OF '2024-06-01';

-- Query #65: Create a recursive CTE for hierarchical data
WITH OrgChart AS (
    SELECT EmployeeID, Name, ManagerID, 0 AS Level
    FROM Employees
    WHERE ManagerID IS NULL
    UNION ALL
    SELECT e.EmployeeID, e.Name, e.ManagerID, o.Level + 1
    FROM Employees e
    JOIN OrgChart o ON e.ManagerID = o.EmployeeID
)
SELECT * FROM OrgChart ORDER BY Level, Name;

-- Query #66: Create a partitioned table
CREATE PARTITION FUNCTION pf_OrderDate (DATE)
AS RANGE RIGHT FOR VALUES ('2022-01-01', '2023-01-01', '2024-01-01');

CREATE PARTITION SCHEME ps_OrderDate
AS PARTITION pf_OrderDate ALL TO ([PRIMARY]);

CREATE TABLE Orders_Partitioned
(
    OrderID INT,
    OrderDate DATE,
    CustomerID INT,
    OrderAmount DECIMAL(18,2)
) ON ps_OrderDate(OrderDate);

-- Query #67: Implement full-text search
CREATE FULLTEXT CATALOG ftCatalog AS DEFAULT;

CREATE FULLTEXT INDEX ON Products(ProductName, Description)
KEY INDEX PK_Products
WITH STOPLIST = SYSTEM;

SELECT * FROM Products
WHERE CONTAINS(ProductName, 'wireless AND keyboard');

-- Query #68: Create a custom aggregate function (CLR)
-- Step 1: Enable CLR
EXEC sp_configure 'clr enabled', 1;
RECONFIGURE;

-- Step 2: Create assembly (after compiling the .dll)
CREATE ASSEMBLY MyAggregates
FROM 'C:\Assemblies\MyAggregates.dll'
WITH PERMISSION_SET = SAFE;

CREATE AGGREGATE dbo.Median(@value FLOAT)
RETURNS FLOAT
EXTERNAL NAME MyAggregates.[Median];

-- Query #69: Create a data masking policy
ALTER TABLE Customers
ALTER COLUMN Email ADD MASKED WITH (FUNCTION = 'email()');

ALTER TABLE Customers
ALTER COLUMN PhoneNumber ADD MASKED WITH (FUNCTION = 'partial(0,"XXX-XXX-",4)');

-- Query #70: Create a resource governor pool
CREATE RESOURCE POOL ReportingPool
WITH (MAX_CPU_PERCENT = 25, MAX_MEMORY_PERCENT = 25);

CREATE WORKLOAD GROUP ReportingGroup
USING ReportingPool;

-- ============================================================
-- END OF PHASE 4
-- ============================================================

-- PHASE 5 - ADVANCED TECHNIQUES & OPTIMIZATION
-- ============================================================

-- Query #71: Use window functions for ranking
SELECT
    CustomerID,
    OrderAmount,
    ROW_NUMBER() OVER (ORDER BY OrderAmount DESC) AS RowNum,
    RANK() OVER (ORDER BY OrderAmount DESC) AS Rank,
    DENSE_RANK() OVER (ORDER BY OrderAmount DESC) AS DenseRank,
    PERCENT_RANK() OVER (ORDER BY OrderAmount) AS PercentRank
FROM Orders;

-- Query #72: Use LAG and LEAD for time-series comparisons
SELECT
    OrderDate,
    DailyRevenue,
    LAG(DailyRevenue, 1) OVER (ORDER BY OrderDate) AS PrevDayRevenue,
    LEAD(DailyRevenue, 1) OVER (ORDER BY OrderDate) AS NextDayRevenue,
    DailyRevenue - LAG(DailyRevenue, 1) OVER (ORDER BY OrderDate) AS DayOverDayChange
FROM (
    SELECT OrderDate, SUM(OrderAmount) AS DailyRevenue
    FROM Orders
    GROUP BY OrderDate
) AS Daily;

-- Query #73: Use FIRST_VALUE and LAST_VALUE
SELECT
    CustomerID,
    OrderDate,
    OrderAmount,
    FIRST_VALUE(OrderAmount) OVER (PARTITION BY CustomerID ORDER BY OrderDate) AS FirstOrderAmount,
    LAST_VALUE(OrderAmount) OVER (PARTITION BY CustomerID ORDER BY OrderDate
        ROWS BETWEEN UNBOUNDED PRECEDING AND UNBOUNDED FOLLOWING) AS LastOrderAmount
FROM Orders;

-- Query #74: Use NTILE for customer segmentation
SELECT
    CustomerID,
    TotalSpent,
    NTILE(4) OVER (ORDER BY TotalSpent) AS Quartile,
    CASE NTILE(4) OVER (ORDER BY TotalSpent)
        WHEN 4 THEN 'Top 25%'
        WHEN 3 THEN 'Upper Middle'
        WHEN 2 THEN 'Lower Middle'
        WHEN 1 THEN 'Bottom 25%'
    END AS SpendSegment
FROM (
    SELECT CustomerID, SUM(OrderAmount) AS TotalSpent
    FROM Orders
    GROUP BY CustomerID
) AS CustomerSpend;

-- Query #75: Use CROSS APPLY for top-N per group
SELECT
    c.CustomerID,
    c.FirstName,
    c.LastName,
    t.OrderID,
    t.OrderDate,
    t.OrderAmount
FROM Customers c
CROSS APPLY (
    SELECT TOP 3 OrderID, OrderDate, OrderAmount
    FROM Orders o
    WHERE o.CustomerID = c.CustomerID
    ORDER BY OrderAmount DESC
) t;

-- Query #76: Use OUTER APPLY with a table-valued function
SELECT
    c.CustomerID,
    c.FirstName,
    c.LastName,
    d.DiscountAmount
FROM Customers c
OUTER APPLY fn_GetOrdersByDateRange('2024-01-01', '2024-12-31') d
WHERE d.CustomerID = c.CustomerID;

-- Query #77: Use GROUPING SETS for multi-level aggregation
SELECT
    Region,
    ProductCategory,
    SUM(OrderAmount) AS TotalRevenue
FROM Orders
GROUP BY GROUPING SETS (
    (Region, ProductCategory),
    (Region),
    (ProductCategory),
    ()
);

-- Query #78: Use ROLLUP for hierarchical subtotals
SELECT
    Region,
    City,
    SUM(OrderAmount) AS TotalRevenue
FROM Orders
GROUP BY ROLLUP (Region, City);

-- Query #79: Use CUBE for all dimension combinations
SELECT
    Region,
    ProductCategory,
    SUM(OrderAmount) AS TotalRevenue
FROM Orders
GROUP BY CUBE (Region, ProductCategory);

-- Query #80: Use PIVOT with dynamic column generation
DECLARE @cols NVARCHAR(MAX), @query NVARCHAR(MAX);

SELECT @cols = STRING_AGG(QUOTENAME(Region), ',')
FROM (SELECT DISTINCT Region FROM Orders) AS Regions;

SET @query = '
SELECT *
FROM (
    SELECT Region, YEAR(OrderDate) AS OrderYear, OrderAmount
    FROM Orders
) AS SourceTable
PIVOT (
    SUM(OrderAmount)
    FOR Region IN (' + @cols + ')
) AS PivotTable;';

EXEC sp_executesql @query;

-- Query #81: Use UNPIVOT to normalize wide data
SELECT
    ProductID,
    Quarter,
    Revenue
FROM ProductSales
UNPIVOT (
    Revenue FOR Quarter IN (Q1_Revenue, Q2_Revenue, Q3_Revenue, Q4_Revenue)
) AS UnpivotTable;

-- Query #82: Use MERGE for upsert operations
MERGE INTO TargetTable AS t
USING SourceTable AS s
    ON t.ID = s.ID
WHEN MATCHED AND t.LastModified < s.LastModified THEN
    UPDATE SET
        t.Name = s.Name,
        t.Value = s.Value,
        t.LastModified = s.LastModified
WHEN NOT MATCHED BY TARGET THEN
    INSERT (ID, Name, Value, LastModified)
    VALUES (s.ID, s.Name, s.Value, s.LastModified)
WHEN NOT MATCHED BY SOURCE THEN
    DELETE
OUTPUT $action, inserted.*, deleted.*;

-- Query #83: Use OUTPUT clause to capture changes
DELETE FROM Orders
OUTPUT deleted.OrderID, deleted.CustomerID, deleted.OrderAmount, GETDATE()
INTO DeletedOrdersLog
WHERE OrderDate < '2020-01-01';

-- Query #84: Use recursive CTE to traverse a graph
WITH
```