

# INDEX

---

Note: Page references in *italics* refer to figures and tables.

## A

Acceleration derivatives, 81

Accelerometers, 33–34

Actuator saturation, *612*, 612–616, *613*

Adaptive control. *See* Miniature aerial vehicles, adaptive control with application

Aerodynamic angles, defined, 75–77, 76

Aerodynamic coefficients

defined, 68

measurement and estimation, 82

Aerodynamic derivatives

acceleration derivatives, 81

defined, 80

overview, 80–82, 121

Aileron-rudder interconnect (ARI), 316

Aircraft dynamic behavior, 205–213

interpretation of aircraft transfer

functions, 208–213, *209*, *210*, *211*

modal decomposition applied to aircraft dynamics, 205–208

Aircraft modeling, 63–141

aerodynamic coefficient measurement and estimation, 82

aerodynamic derivatives, 80–82

axes and angles, 75–77, 76

basic aerodynamics and, *64*, 64–75, *66*, *70*, *72*, *74*

component buildup, 83

data handling, *100*, 100–101

drag coefficient, 83, 83–86, 85

force and moment coefficients, 79–80

forces and moments, defined, 77–79, 78

lift coefficient, 86–90, 88, 89

linear models and stability

derivatives, 116–137, *121*, *124*, *130*, *131*, *132*, *135*, *136*

model building, overview, 63–64

nonlinear aircraft model, 108–116, *111*

Aircraft modeling, (*Continued*)

- pitching moment, 94–96, 95, 96
- pitching moment, control effects, 96–97
- problems, 139–141
- rolling moment, 91–93, 92
- rolling moment, control effects, 93–94, 94
- sideforce coefficient, 90, 90–91
- static analysis, 101–108, 102
- yaw, defined, 93
- yawing moment, 97–99, 98, 99

## Aircraft models for simulation, 179–184

- simple longitudinal model, 179–180
- simulation issues, 179
- six-degree-of-freedom nonlinear aircraft model, 180–184, 182–183, 184
- See also* Miniature aerial vehicles, modeling and simulation

## Airfoil section aerodynamics

- aircraft configurations, 73–75, 74
- airfoil, defined, 64, 64
- finite wings and, 71–73, 72
- overview, 64, 64–71, 66, 70

## Altitude hold/Mach hold, 329–332, 330, 332, 333

## American Institute of Aeronautics and Astronautics (AIAA), 75

## Angle of attack, 65, 75–77, 76, 88, 89

## Angular velocity vector, 1–2, 17

## Anhedral angle, 92

## Area rule, 84

## AscTec Pelican (quadrotor)

- miniature aerial vehicles, modeling and simulation, 654, 654–655, 655
- quadrotor, defined, 624

## simulation example, neural network adaptive control, 689–690, 689, 690

## Autonomy, of miniature aerial vehicles, 625

## Autopilot design

- altitude hold/Mach hold, 329–332, 330, 332, 333
- automatic landing systems, 333–339, 334, 335, 338, 339
- autopilot navigational modes, 343, 343–344

designing with modern techniques (*See* Linear quadratic regulator (LQR) with output feedback)

## function of automatic control systems and, 256–257

## historical perspective, 250–254

## need for automatic control systems and, 254–256, 255, 256

## overview, 322

## pitch-attitude hold, 322–328, 323, 325, 328, 329

## roll-angle-hold autopilots, 339–342, 340, 341

## turn coordination and turn compensation, 342

*See also* Classical control design

## Axial force, 77

**B**

## Back side of power curve, 194

## Bending-mode filter, 295

## Bilinear transformation, 588–590

## Bode plots, 164

## Body-axes equations, 109–111, 111

## Body-fixed coordinate system, 76

## Boeing, 252–253

## Bound vector, 3

# C

Camber line, 65

Cartesian/polar coordinate conversions, 29–31

Cascaded systems, adaptive control for, 677, 680

Celestial longitude, 26

Centrifugal force, 22

Centripetal acceleration, 20

Chord line, 65

Classical control design, 250–376

aircraft rigid-body modes, 257–274, 264, 273, 274

autopilot, 322–344, 323, 325, 328, 329, 330, 332, 333, 334, 335, 338, 339, 340, 341, 343

closed-loop control, 276, 278, 281, 283, 288–296, 291, 293, 378

control augmentation systems, 303–322, 304, 307, 308, 310, 311, 313, 314, 317, 321

feedback control and, 213, 217, 226

functions of automatic control systems, 256–257

handling qualities requirements, 274–287, 275, 280, 281, 282, 284, 285, 286

historical perspective, 250–254

limitations of, 378

need for automatic control systems, 254–256, 255, 256

nonlinear simulation, 344–371, 346, 347, 349, 350, 351, 352, 353, 355, 356, 357, 359, 360, 362, 363, 364, 365, 368, 369, 370, 371

overview, 250

problems, 374–376

stability augmentation, 287, 287–303, 291, 293, 295, 296, 299, 302, 303

Closed-loop dynamics, classical design techniques, 381–396, 393, 395, 397

Closed-loop feedback equations, 214, 214–219, 215, 217, 218, 219

Command, tracking a. *See* Tracking a command

Companion form, of linear state equations, 149

Compensation, feedback control and, 224–226

Compressibility effects, 69

Conditional stability, 223

Coning angle, 640–641

Constrained feedback matrix, 429–430, 435, 436

Continuous controller design

discretization of continuous controllers, 588–598, 594, 595, 596, 597

modified continuous design, 598–611, 599, 600, 601, 603, 605, 606, 607, 610, 611

overview, 584

*See also* Digital control

Control augmentation systems (CASs) defined, 257

lateral-directional control augmentation, 315–322, 317, 321

normal acceleration CASs, 308–315, 310, 311, 313, 314

overview, 303–304

pitch-rate CASs, 304, 304–308, 307, 308

Control feel, 283

Control gains, modern control design and, 378–379

Coordinate rotations, 7–16

cross-product matrix, 8

direct cosine matrix (DCM), overview, 8–10

eigenvalues and eigenvectors, 14–15

Euler rotations and DCM, 11–13

Euler's rotation theorem, 15–16

- Coordinate rotations, (*Continued*)
  - linear transformations, 13–14
  - scalar product, 7
- Coordinate system, defined, 3
- Coordination perception parameter, 280
- Coriolis acceleration, 20–22
- Critical Mach number, 69
- Cross-product matrix, 5, 8
- Cross-wind force, 77
- Cruise missiles, 623
- D**
- Data handling, efficiency of, 100, 100–101
- Decoupling
  - decoupled linear state equations, 126–128
  - of nonlinear equations/3-DOF
    - longitudinal model, 115–116
- De Havilland Comet, 252
- Department of Defense World Geodetic System 1984 (WGS-84)
  - defined, 23–25, 24
- Earth Gravitational Model 1996 (EGM96), 32
- Derivative of a vector, 16–17
- Derivatives. *See* Aerodynamic derivatives
- Derivative weighting, 430–431
- Deyst filter, 547
- Digital control, 584–622
  - defined, 381
  - discretization of continuous
    - controllers, 588–598, 594, 595, 596, 597
  - implementation considerations, 611–618, 612, 613, 616, 618, 619
  - modified continuous design, 598–611, 599, 600, 601, 603, 605, 606, 607, 610, 611
  - overview, 584–585
  - problems, 620–622
  - simulation of digital controllers, 585, 585–588, 586
- Dihedral angle, 92
- Dihedral derivative, 93, 136
- Dimensionless stability derivatives, 128–131, 130, 131
- Direct cosine matrix (DCM)
  - eigenvalues and eigenvectors, 14–15
  - Euler's rotation theorem, 11–13, 15–16
  - linear transformations, 13–14
  - overview, 8–10
  - from quaternion, 53
  - quaternion from, 53–54
- Direct-lift control, 253
- Discrete-time transition matrix, 152
- Dot product, 5
- Drag
  - defined, 65–66
  - drag coefficient, 70, 83, 83–86, 85
  - drag divergence Mach number, 69
  - drag due to lift, 83
  - drag polar, 86
- Dumping derivative, 81
- Dutch roll mode
  - classical control design and, 267–269, 286
  - yaw stiffness derivative and, 136–137
- Dynamic compensator, for
  - eigenstructure assignment, 392–393
- Dynamic inversion, 477–491
  - for linear systems, 477–487, 479, 484, 485
  - model reference adaptive control
    - based on, 665–668, 666 (*See also* Miniature aerial vehicles, adaptive control with application)
  - for nonlinear systems, 487–491, 488, 490, 491
  - overview, 380–381, 477
- Dynamic lift, 80
- Dynamic modes/stability, 67

Dynamic pressure, 68  
 Dynamic regulator design, using  
   separation principle, 550–554,  
   552

## E

Earth, spheroid model of. *See* Geodesy  
 Earth-centered-Earth-fixed (ECEF)  
   system, 25–26  
 Earth-centered-inertial (ECI) system,  
   25–26  
 Earth Gravitational Model 1996  
   (EGM96) (WGS-84), 32  
 Eccentricity, 25  
 Efficiency factor, 84  
 Eigenvalues/eigenvectors  
   defined, 14–15  
   eigenstructure assignment by full  
     state feedback, 387–390  
   eigenstructure assignment by output  
     feedback, 391–396, 393, 395,  
     397  
   modal decomposition, 152–153  
   *See also* Modern design techniques  
 Electric motor modeling, 647–648  
 Elevator control power, 96  
 Equation of Coriolis, 17–19, 18, 45  
 Euler angle kinematics, 19–20  
 Euler integration, 2, 171  
 Euler kinematical equations, defined,  
   120  
 Euler rotations, 11–13  
 Euler's rotation theorem, 15–16  
 Evans, W. R., 226, 251

## F

F-16  
   aircraft dynamic behavior (example),  
     208–210, 209  
   dynamic inversion design for linear  
     F-16 longitudinal dynamics  
       (example), 481–487  
   linearization, 203–205

LQR design for F-16 lateral regulator  
   (example), 407  
   modern design techniques and, 377,  
     381, 407–408, 424, 435, 439,  
     442, 481–487  
   mode variation, 272–274,  
     273, 274  
   singular-value plots for F-16  
     dynamics (example), 509–511,  
     510  
   six-degree-of-freedom nonlinear  
     aircraft model (example),  
     180–184, 182–183, 184  
 Feedback control design, 213–240  
   closed-loop equations, 214, 214–219,  
     215, 217, 218, 219  
   frequency-domain design, 233–240,  
     234, 235, 236, 237, 238,  
     239, 241  
   overview, 213, 213–214  
   robust output feedback design,  
     525–529, 528  
 SISO root-locus design, 226,  
   226–233, 229, 231, 232  
 stability, 221–224, 223  
 steady-state error and system type,  
   219–221  
 types of compensation, 224–226  
 Feedback linearization, dynamic  
   inversion and, 381  
 Feedback linearization loop, 479  
 Finite wings, 71–73, 72  
 Fixed-pitch propeller nomenclature, 636  
 Flare control, 357–371  
   automatic flare control (example),  
     358–360, 359, 360  
   overview, 357, 357–358  
   roll-angle steering control system  
     (example), 361–362, 362, 363,  
     364, 365  
   simulation of a controller with  
     limiters (example), 365–371,  
     368, 369, 370, 371

## Flat-Earth equations

- defined, 1
- matrix form, 41–43

## Flattening, 25

## Forces and moments

- aerodynamic coefficient measurement and estimation, 82
- aerodynamic derivatives, 80–82
- on aircraft from flapping rotor, 644–645
- axes and angles, 75–77, 76
- basic aerodynamics and, 64, 64–75, 66, 70, 72, 74
- component buildup, 83
- data handling, 100, 100–101
- defined, 77–79, 78
- drag coefficient, 83, 83–86, 85
- force and moment coefficients, 79–80
- lift coefficient, 86–90, 88, 89
- linearization of force equations, 119–123, 121
- linearization of moment equations, 123–126, 124
- pitching moment, 94–96, 95, 96
- pitching moment, control effects, 96–97
- propeller/rotor forces and moments, 630, 630–639, 632, 633, 634, 635, 637
- rolling moment, 91–94, 92, 94
- sideforce coefficient, 90, 90–91
- static analysis, 101–108, 102
- wind- or stability-axes equations, 111–115
- yawing moment, 97–99, 98, 99

## Frame of reference, defined, 3

## Freestream Mach number, 68–69

## Free vector, defined, 3

## Frequency-domain design, 233–240, 234, 235, 236, 237, 238, 239, 241

## Frequency-domain performance specifications, 511–524, 513, 516, 522, 523

## Frequency-response specifications, handling qualities requirements, 278–279

**G**

## Geocentric coordinates, 26

## Geodesy, 23–34

## Cartesian/polar coordinate

## conversions, 29–31

## defined, 1

## Earth-related coordinate

## transformations, 31

## frames, Earth-centered coordinates,

## latitude and longitude, 25–27

## geodetic coordinates, 26, 26–27

## gravitation and accelerometers, 33–34

## gravitation and gravity, 31–33

## local coordinate systems, 27

## overview, 23

## radii of curvature, 27–28

## shape of the Earth and Department of

## Defense World Geodetic System

## 1984 (WGS-84), 23–25, 24

## trigonometric relationships for the spheroid, 29

## Geoid, 24

## Glide-slope coupler, 446, 446–455, 453, 454–455

## Global Positioning System (GPS), 24

## Gravitation, 23–34

## accelerometers and, 33–34

## defined, 1, 31–33

## Earth's gravitational field, defined, 23

## geoid, 24

*See also* Geodesy

## Greenwich Hour Angle (GHA), 31

## Gyroscopic moments, 638–639

**H**

## Hamilton, Sir William Rowan, 44, 45

## Handling qualities requirements, 274–287

background, 274–276, 275  
control feel, 283  
frequency-response specifications,  
278–279  
military flying qualities specifications,  
283  
pole-zero specifications, 276–278  
requirements based on human  
operator models, 280–282, 281,  
282  
speed stability, 283  
time-response specifications,  
279–280, 280  
Horizontal tail, 103–104  
Human operator describing function,  
280–281  
Hypersonic vehicles, history of,  
252–254

## I

Induced drag, 83  
Inertia coupling, 251, 315  
Inertial frame, defined, 3  
Inertial Navigation System (INS), 55  
Initial-value problem, 170  
Interference drag, 83  
Internal combustion engine modeling,  
646–647  
Irreversible control system, 256

## J

Jacobian matrices  
defined, 120  
for linearization, 199, 202, 203–205

## K

Kalman filter, 529–554  
derivation of, 540–547  
developing, 537–538  
dynamic regulator design using  
separation principle, 550–554,  
552

estimation of angle of attack in gust  
noise (example), 547–550, 548  
observer design problem and,  
530–537, 531  
overview, 381, 529–530  
probability theory and, 538–540, 539  
Kalman gain, 471–473  
Kinematic coupling, 315  
Kinematics and dynamics of aircraft  
motion, 1–62  
geodesy, coordinate systems, gravity,  
23–34, 24, 26  
kinematics, defined, 3  
matrix operations on vector  
coordinates, 7–16, 9  
overview, 1–3  
Poisson's kinematical equations  
(PKEs), 44–45  
quaternions, 45–58, 57  
rigid-body dynamics, 34–43  
rotational kinematics, 16–20, 18, 21  
vector operations, 3–7, 7

## L

Lag compensator, 232  
Landing systems, automatic, 333–339,  
334, 335, 338, 339  
Langley, Samuel Pierpont, 623  
Laplace transform (LT), 153–154  
Lateral-directional coefficients, 79  
Lateral-directional control  
augmentation, 315–322, 317,  
321  
Lateral-directional dimensionless  
derivatives, 136, 136–137  
Lateral-directional stability  
augmentation/yaw damper,  
294–303, 295, 296, 299, 300,  
302, 303  
Lateral-directional transfer functions  
accuracy of, 271–272  
algebraic derivation of, 266–267  
Latitude, 25–27

- Lead compensation, 225
- Life coefficient, 70
- Life-curve slope, 70
- Life-over-drag ratio, 71
- Lift
  - defined, 65–66
  - direct-lift control, 253
  - drag due to lift, 83
  - dynamic lift, 80
  - lift coefficient, 86–90, 88, 89
  - lift-curve slope, 132–133
  - vortex lift, 73–75
- Limit cycle, 176–178, 178
- Limited authority adaptive control, 673–679, 674, 677, 679
- Linear and time invariant (LTI) state equations
  - defined, 150
  - Laplace transform (LT) solution of, 153–154
  - time domain of, 150–152
- Linearization
  - algebraic compared to numerical linearization, 202–203
  - algorithm, 200–202, 201
  - of F-16 model, 203–205
  - numerical linearization, 199–205, 201, 204, 205
  - theory of, 199–200
- Linear models and stability derivatives
  - decoupled linear state equations, 126–128
  - dimensionless stability and control derivatives, 128–131, 130, 131
  - lateral-directional dimensionless derivatives, 136, 136–137
  - linearization, 119–126, 121, 124
  - longitudinal dimensionless derivatives, 131–135, 132, 135
  - overview, 116–117
  - singular points and steady-state flight, 117–118
- Linear multistep methods (LMMs), 170, 173–174, 175
- Linear quadratic Gaussian/loop transfer recovery (LQG/LTR), 554–577
  - for dynamic regulator, 551
  - Gaussian, defined, 546
  - guaranteed robustness of LQR, 554–558, 557, 558
  - loop transfer recovery, 558–577, 560, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576
  - overview, 501, 554–555
- Linear quadratic regulator (LQR) with full state feedback, 470–476
  - guaranteed closed-loop stability, 473–476
  - overview, 470–471
  - Riccati equation and Kalman gain, 471–473
  - state feedback relevance, 471, 473
- Linear quadratic regulator (LQR) with output feedback, 397–413
  - determining optimal feedback gain, 402–405
  - overview, 397–398
  - quadratic performance index, 398–399
  - selection of PI weighting matrices, 405–413, 411, 412
  - solution of LQR problem, 399–402, 403, 404
- Linear state equation, 2
- Linear transformations, 13–14
- Local geocentric system (c-system), 28
- Lockheed X-7, 252
- Longitude, 25–27
- Longitudinal coefficients, 79
- Longitudinal dimensionless derivatives, 131–135, 132, 135, 136
- Longitudinal pitch pointing control, 393–396



Longitudinal transfer functions and  
modes, algebraic derivation of,  
258–259

Loop transfer function

feedback control, 215–217,  
222

robust design and LGQ/LTR,  
558–577, 560, 565, 566, 567,  
568, 569, 570, 571, 572, 573,  
574, 575, 576

*See also* Classical control design;  
Modeling, design, and simulation  
tools

## M

Mach-hold autopilot, 329–332, 330,  
332, 333

Mach number, 68–69

MATLAB

adaptive control, 670, 675  
classical control design, 290, 292,  
294, 299, 305, 312, 319, 324,  
344, 353  
dynamic inversion design, 477, 481,  
483, 489, 491  
feedback control, 216, 223, 228, 235  
(*See also* Feedback control  
design)

Kalman filter, 569

simulation tools, 176, 179, 181, 190,  
195

Mean line, 65

Meridian radius of curvature, 27–28

Miniature aerial vehicles, adaptive  
control with application,  
664–713

adaptive controller, defined, 664  
limited authority adaptive control,  
673–679, 674, 677, 678, 679  
model reference adaptive control  
based on dynamic inversion,  
665–668, 666

neural network adaptive control, 668,  
668–673, 672

neural network adaptive control  
(example), 679–708, 680, 689,  
690, 691, 692, 693, 694, 695,  
696, 697, 698, 699, 700, 701,  
702, 703, 704, 705, 706, 707, 708

overview, 664–665

Miniature aerial vehicles, modeling and  
simulation, 623–663

historical perspective, 623–624

modeling rotor flapping, 640,  
640–645, 641, 643

motor modeling, 645–648, 647

overview, 623–625

problems, 661–663

propeller/rotor forces and moments,  
630, 630–639, 632, 633, 634,  
635, 637

propellers vs. rotors, 625–630, 626,  
627, 628, 629

quadrotor model, 654, 654–655, 655  
small aerobatic airplane model, 648,  
648–653, 649, 651, 652, 653

small helicopter model, 655–659,  
656, 657, 658, 660

Mission adaptive wing, 75

Modal decomposition

applied to aircraft dynamics, 205–208  
classical design techniques and,  
384–387

state-space models and, 152–153

Model building. *See* Aircraft modeling

Model-following design (modern design  
techniques), 455–470

explicit model-following control,  
456–461, 461

implicit model-following control,  
461–470, 464, 465, 468, 469

model following, defined,  
380

overview, 455

- Modeling, design, and simulation tools,  
142–249  
aircraft dynamic behavior, 205–213,  
209, 210, 211  
aircraft models for simulations,  
179–184, 180, 184, 185  
feedback control, 213, 213–240, 214,  
215, 217, 218, 219, 221, 223,  
226, 229, 231, 232, 234, 235,  
236, 237, 238, 239, 241  
numerical linearization, 199–205,  
201, 204, 205  
numerical solution of state equations,  
170–178, 176, 178  
overview, 142–143, 143  
problems, 243–249  
state-space models, overview,  
144–154, 145, 146, 148, 149,  
150  
steady-state flight, 185–199, 189,  
190, 192, 193, 194, 195, 196,  
197, 198  
transfer function models, 155–170,  
158, 161, 162, 165, 167, 168, 169  
*See also* Aircraft modeling; Miniature  
aerial vehicles, modeling and  
simulation
- Modern design techniques, 377–499  
assignment of closed-loop dynamics,  
381–396, 393, 395, 397  
dynamic inversion design, 477–491,  
479, 484, 485, 488, 490, 491  
fundamental design problems,  
379–381  
limitations of classical control, 378  
linear quadratic design with full state  
feedback, 470–476, 473  
linear quadratic regulator with output  
feedback, 397–413, 403, 404,  
411, 412  
model-following design, 455–470,  
461, 464, 465, 468, 469  
modifying performance index,  
428–455, 433, 436, 437, 438,  
440, 441, 442, 445, 446, 453,  
454, 455  
overview, 377–378  
philosophy of, 378–379  
problems, 495–499  
tracking a command, 413–428, 414,  
417, 422, 423, 427  
*See also* Miniature aerial vehicles,  
adaptive control with application
- Moment equations. *See* Forces and  
moments
- Motor modeling (miniature aerial  
vehicles), 645–648
- Multiple-input, multiple-output  
(MIMO) systems  
defined, 143  
feedback control, 217–218  
modern control techniques, 379
- Multivariable Bode plot, 506–511, 508,  
510
- Multivariable frequency-domain  
analysis, 502–525  
frequency-domain performance  
specifications, 511–524, 513,  
516, 522, 523  
multivariable Bode plot, 506–511,  
508, 510  
overview, 502  
robustness bounds for plant parameter  
variations, 524–525  
sensitivity and cosensitivity,  
502–506, 503, 504
- Multivariable wing leveler, 442,  
442–446, 445
- N**
- National Imagery and Mapping Agency  
(NIMA), 24
- Natural mode, 195
- Navigational modes, autopilot, 343,  
343–344

- Neural network adaptive control
  - adaptive guidance and flight control
    - system applied to rotorcraft flight control (example), 679–689, 680
  - overview, 668–669
  - quadrotor simulation, 689–690, 689, 690
  - small helicopter simulation, 690–697, 691, 692, 693, 694, 701, 702, 703, 704, 705, 706, 707, 708
  - universal approximation theorem, 669–673, 672
- Neutral point, 107–108
- Nonlinear aircraft model
  - body-axes equations, 109–111, 111
  - decoupling of nonlinear
    - equations/3-DOF longitudinal model, 115–116
  - overview, 108–109
  - wind- or stability-axes equations, 111–115
- Nonlinear simulation, 344–371
  - flare control, 357, 357–371, 359, 360, 362, 363, 364, 365, 368, 369, 370, 371
  - lateral-directional CAS nonlinear simulation (example), 347, 347–353, 349, 350, 351, 352, 353
  - overview, 344
  - pitch-rate CAS nonlinear simulation (example), 344–347, 346
  - simulation of automatic landing, 353–356, 355, 356, 357
- Nonlinear state equation, 144–145
- Normal acceleration control
  - augmentation systems (CASs), 308–315, 310, 311, 313, 314, 423, 423–428, 427
- Normal force, 77
- North-East-down (NED) system, 11
- Numerical linearization, 199–205
- Nyquist, H., 222
- Nyquist-D contour, 222–224, 223
- O**
- Oblate-rotating-Earth 6-DoF equations, 54–58, 57
- Observer canonical form, of linear state equations, 149
- Optimal control model (OCM), 282
- Ordinary differential equations (ODEs), 143, 143, 144. *See also* State-space models
- Output equation, 144–145
- Output feedback design. *See* Feedback control design
- P**
- Padé approximants, 605
- Parasite drag, 83
- Performance index (PI) modification, 428–455
  - constrained feedback matrix, 429–430, 435, 436
  - derivative weighting, 430–431
  - glide-slope coupler, 446, 446–455, 453, 454–455
  - integral-squared PI, 379–380
  - multivariable wing leveler, 442, 442–446, 445
  - overview, 428–429
  - PI overview, 377–378
  - pitch-rate control system using LQ design, 438, 438–441, 439, 441
  - quadratic PI, 398–399
  - time-dependent weighting, 431–435, 433, 437, 437–438, 440–441
  - See also* Modern design techniques
- Phase-lead compensation, 225
- Phase portrait, 178
- Phugoid approximation, 261–265, 264, 284
- Pilot opinion rating scales, 275

Pitch-attitude hold, 322–328, 323, 325, 328, 329

Pitch-axis stability augmentation, 287–294, 291, 293

Pitch damping derivative, 133–134

Pitching moment

- coefficient, 70
- control effects, 96–97
- overview, 70, 94–96, 95, 96
- static stability analysis and, 102, 102, 104–107

Pitch-rate control augmentation systems (CASs), 304, 304–308, 307, 308, 526–529, 528

Pitch-rate control system, using LQ

- design, 438, 438–441, 439, 441

Pitch stability, 265–266

Pitch stiffness derivative, 133

Poisson's kinematical equations (PKEs)

- equation of Coriolis, 45
- overview, 44–45

Poles, transfer function models, 155–157, 158

Pole-zero specifications, classical

- control design, 276–278

Power spectral density function (PSDF), 219

Prandtl-Glauert correction factor, 72

Prandtl's lifting line theory, 72

Pressure altitude, 329

Prime vertical radius of curvature, 28

Principle of the argument, 222

Probability theory, Kalman filter and, 538–540, 539

Propellers

- fixed-pitch propeller nomenclature, 636
- propeller/rotor forces and moments, 630, 630–639, 632, 633, 634, 635, 637
- rotors vs., 625–630, 626, 627, 628, 629

Proportional plus integral (PI) compensator, 225

Pseudocontrol hedging (PCH), 674–677, 675, 677, 679

Pseudovectors, 4

## Q

Quadratic-lag circuit, 163, 165

Quadratic performance index, 398–399

Quadrotor

- defined, 624

- quadrotor model, 654, 654–655, 655

- simulation example, neural network adaptive control, 689–691, 690, 691

Quaternions

- from direction cosine matrix, 53–54

- direction cosine matrix from, 53

- initializing, 51–52

- oblate-rotating-Earth 6-DoF equations, 54–58, 57

- overview, 45–46

- quaternion coordinate rotation, 49–50

- quaternion kinematical equations, 50–51

- quaternion properties, 47–48

- vector rotation by, 48–49

## R

Radii of curvature, 27–28

Rate-of-climb (ROC) constraint, 186, 187

Regulator applications, 214

Regulator problem, 379–380

Relative wind, 43

Remnant, 280

Resonance, 158–159

Reynolds number, 68–69, 70–71, 625

Riccati equation, 471–473

Rigid-body dynamics

- angular motion, 35–39

- overview, 34–35

- translational motion of the center of mass, 39–43
- Rigid-body modes, 257–274
  - accuracy of lateral-mode
    - approximations, 271–272
  - accuracy of short-period and phugoid
    - approximations, 263–265, 264
  - algebraic derivation of
    - lateral-directional transfer functions, 266–267
  - algebraic derivation of longitudinal
    - transfer functions and modes, 258–259
  - dutch roll approximation, 267–269
  - mode variation from nonlinear model, 272–274, 273, 275
  - overview, 257
  - phugoid approximation, 261–263
  - pitch stability, 265–266
  - short-period approximation, 259–261
  - spiral and roll subsidence
    - approximations, 269–270
  - spiral stability, 270–271
- Rigidity, defined, 1
- Robust design
  - linear Gaussian quadratic/loop
    - transfer recovery, 554–577, 557, 558, 560, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576
  - linear quadratic Gaussian/loop
    - transfer recovery (LQG/LTR), 501
  - multivariable frequency-domain
    - analysis, 502–525, 503, 504, 508, 510, 513, 514, 516, 522, 523
  - observers and Kalman filter, 529–554, 531, 537, 539, 546, 548, 552
  - overview, 377, 381, 500–502 (*See also* Modern design techniques)
  - problems, 580–583
  - robust output feedback design, 525–529, 528
- Roll-angle-hold autopilots, 339–342, 340, 341
- Roll control derivatives, 93
- Roll damping derivative, 137
- Rolling mode, 269–270, 285
- Rolling moment
  - control effects, 93–94, 94
  - overview, 91–93, 92
- Root-locus design, 226, 226–233, 229, 231, 232
- Rotational kinematics
  - angular velocity as a vector, 17
  - derivative of a vector, 16–17
  - Euler angle kinematics, 19–20
  - overview, 16
  - vector derivatives and rotation, 17–19, 18
- Rotation of vector
  - defined, 6–7, 7
  - quaternion coordinate rotation, 49–50
  - by quaternions, 48–49
- Rotors
  - forces and moments on aircraft from flapping rotor, 644–645
  - modeling rotor flapping, 640, 640–645, 641, 643
  - propeller/rotor forces and moments, 630, 630–639, 632, 633, 634, 635, 637
  - propellers vs., 625–630, 626, 627, 628, 629
  - quadrotor, defined, 624
  - quadrotor model, 654, 654–655, 655
- Runge-Kutta (RK) methods, 170–172, 174–175, 585–588
- S**
  - Scalar product, 7
  - Separation principle, 550–554, 552
  - Short-period mode, 195, 259–261, 263–265, 264, 284–285

- Sideforce coefficient, 90, 90–91
- Sideslip angle, 75–77, 76. *See also*
  - Rolling moment
- Sign convention, for control surfaces, 184, 184, 288
- Simulation. *See* Miniature aerial vehicles, modeling and simulation; Modeling, design, and simulation tools
- Single-input, single-output (SISO) systems
  - defined, 143
  - feedback control, 215–217, 219
  - root-locus design, 226, 226–233, 229, 231, 232
  - SISO transfer function, 157–160
- Six-degrees-of-freedom (6-DoF) equations
  - defined, 16
  - Euler angle kinematics, 19
  - F-16 aircraft model for simulation (example), 180–184, 182–183, 184
  - quaternion, 54–58, 57
  - rigid-body dynamics, 34, 40, 42–43
  - translational kinematics, 20
- Skin friction, 65
- Small aerobatic airplane model, 648, 648–653, 649, 651, 652, 653
- Small helicopter
  - miniature aerial vehicles, modeling and simulation, 655–659, 656, 657, 658, 660
  - simulation example, neural network adaptive control, 691–698, 692, 693, 694, 695, 702, 703, 704, 705, 706, 707, 708
- Speed damping derivative, 135
- Speed stability, 283
- Sperry, Elmer, 339
- Sperry Gyroscope Company, 250
- Spiral mode, 208, 269–270, 285
- Spiral stability, 270–271
- Spoilers, 94
- Stability
  - feedback control and, 221, 221–224, 223
  - numerical algorithms and, 174
  - stability-axes coordinate system, 76
  - stability-axes equations, 111–115
  - stabilizer bars on rotors, 628, 643, 643–644
  - stable equilibrium, 66
- Stability augmentation systems (SASs), 287–303
  - defined, 257
  - designing with modern techniques (*See* Linear quadratic regulator (LQR) with output feedback)
  - lateral-directional stability
    - augmentation/yaw damper, 294–303, 295, 296, 299, 300, 302, 303
  - overview, 287
  - pitch-axis stability augmentation, 287–294, 291, 293
  - stability augmentation, defined, 252
- Stalled (airfoil), 70
- Standard atmosphere model, 67–68
- State feedback, LQR with, 470–476, 473
- State-space models, 144–154
  - classical design techniques and, 382–384
  - Laplace transform (LT) solution of LTI state equations, 153–154
  - modal decomposition, 152–153
  - models of mechanical and electrical systems, 144–147, 145, 146
  - nonlinear state and output equations, 144–145
  - ordinary differential equations (ODEs), 143, 143, 144
  - reduction of differential equations to state-space form, 147–150, 148, 149, 150

- time-domain solution of LTI state equations, 150–152
- See also* Modeling, design, and simulation tools
- State variables
  - overview, 2–3
  - state-variable model, 378
- Static coefficients, 80
- Static stability analysis
  - defined, 101
  - effect of horizontal tail, 103–104
  - neutral point, 107–108
  - static equilibrium, 101–103, 102
  - static stability analysis in pitch, 104–107
- Steady-state flight, 185–199
  - feedback and steady-state error, 219–221
  - flight simulation (examples), 195–199, 196, 197, 198
  - overview, 185–187
  - rate-of-climb constraint, 186, 187
  - steady state, defined, 546
  - trim algorithm, 188–192, 189, 190, 192
  - trimmed conditions for studying aircraft dynamics, 193, 193–194, 194, 195
  - turn coordination constraint, 187–188
- Stiff system, 174
- Strapdown equation, 45
- Streamlines, 64, 64
- Supersonic wave drag, 72
- T**
- Tail efficiency factor, 97
- Tangent-plane coordinate system, 27
- Target drones, 623
- Taylor series, 119, 170–173, 199–202, 605
- Terrain-following, terrain avoidance (TFTA) autopilot, 343
- Terrestrial longitude, 26
- 3-DOF longitudinal model, 115–116
- Thrust coefficient, 79, 87
- Thrust/torque, of propeller/rotor, 630, 631–639, 632, 633, 634, 635, 637
- Time-dependent weighting, 431–435, 433, 437, 437–438, 440–441
- Time-domain design technique, 399
- Time-history simulation, 175–178, 176
- Time step T, 170
- Tip path plane equations, of motion, 640–642
- Tracker applications, 214
- Tracker problem, 380
- Tracking a command, 413–428
  - determining optimal feedback gain, 422–428, 423, 427
  - LQ formulation of tracker problem, 416–420, 417
  - overview, 413–415, 414
  - solution of LQ tracker problem, 420–421, 422
  - tracker with desired structure, 415–416
- Transfer function models, 155–170
  - examples and standard forms, 160–163, 161
  - frequency response, 163–167, 165
  - poles and zeros, 155–157, 158
  - SISO transfer function, 157–160
  - time response, 167–170, 168, 169

Translational kinematics  
 acceleration relative to Earth,  
     22–23  
 overview, 20  
 velocity and acceleration in moving  
     frames, 20–22, 21

Transonic drag rise, 73

Transonic flow, 69

Trigonometric relationships for  
 spheroid, 29

Trim algorithm (for steady-state flight)  
 flowchart, 189  
 overview, 188–192, 189, 190, 192  
 for 3-DoF aircraft model, 189  
 trimmed conditions for studying  
     aircraft dynamics, 193, 193–194,  
     194, 195

Trimmed coefficients, 82

Tuck derivative, 134–135

Turbulence, 65

Turn coordination constraint,  
     187–188

Turn coordination/turn compensation,  
     342

Tustin's approximation, 588–590

**U**

Unity feedback, 214

Universal approximation theorem,  
     669–673, 672

Unmanned aircraft. *See* Miniature aerial  
 vehicles, modeling and  
 simulation

Unstable equilibrium, 67

Unsteady aerodynamic effects, 80

Untrimmed coefficients, 82

U.S. Department of Defense World  
 Geodetic System 1984 (WGS-84)  
 defined, 23–25, 24  
 Earth Gravitational Model 1996  
 (EGM96), 32

U.S. space shuttle, history of, 253

**V**

Van der Pol equation,  
     176–178, 178

Vector analysis  
 angular velocity vector, 1–2  
 matrix operations on vector  
     coordinates, 7–16  
 rotation of a vector, 6–7, 7  
 vector, defined, 3  
 vector operations, definitions and  
     notation, 3–4  
 vector properties, 4–6

Vector state equations, 39–41

Velocity feedforward, 479

Vertical take-off and landing (VTOL)  
 aircraft, 624

VOR-hold (VHF Omni Range)  
 autopilot, 343

Vortex lift, 73–75

Vortex sheet, 71

**W**

Wave drag, 83

Wetted area, 65

WGS. *See* Department of Defense  
 World Geodetic System 1984  
 (WGS-84)

Whitcomb, R. T., 84

Wind-axes equations,  
     111–115

Wing planform parameters,  
     72, 72–75

**Y**

Yamaha RMAX (small helicopter)  
 modeling and simulation,  
     655–659, 656, 657,  
     658, 660  
 simulation example, neural network  
 adaptive control, 691–698, 692,  
 693, 694, 695, 702, 703, 704,  
 705, 706, 707, 708



Yaw damping derivative,  
137  
Yawing moment  
control effects, 99  
overview, 97–99, 98, 99  
yaw, defined, 93  
yaw damping derivative,  
98  
Yaw stiffness derivative,  
136  
Yeager, Charles, 251

**Z**

Zero-order hold (ZUH), 585, 601–603,  
605  
Zeros  
pole-zero specifications, classical  
control design, 276–278  
Zeros, transfer function models,  
155–157, 158  
Zivco Edge 540T (small aerobatic  
airplane model), 648, 648–653,  
649, 651, 652, 653