## 6ES7215-1BG40-0XB0

### CPU 1215C, AC/DC/RLY, 14DI/10DO/2AI/2AO

| Product details | Technical data | CAx data |

**Technical data**



(https://www.automation.siemens.com/bilddb/index.aspx?

objKey=G_ST70_XX_00916)

SIMATIC S7-1200, CPU 1215C, compact CPU, AC/DC/relay, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 ... AI 0-10 V DC, 2 AO 0-20 mA DC, Power supply: AC 85-264 V AC at 47-63 Hz, Program/data memory 125 KB

**General information**

| | |
|---|---|
| Product type designation | CPU 1215C AC/DC/relay |
| Engineering with | |
| ● Programming package | STEP 7 V17 or higher |

**Supply voltage**

| | |
|---|---|
| Rated value (AC) | |
| ● 120 V AC | Yes |
| ● 230 V AC | Yes |
| permissible range, lower limit (AC) | 85 V |
| permissible range, upper limit (AC) | 265 V |
| Line frequency | |
| ● permissible range, lower limit | 47 Hz |
| ● permissible range, upper limit | 63 Hz |

**Input current**

| | |
|---|---|
| Current consumption (rated value) | 100 mA at 120 V AC; 50 mA at 240 V AC |
| Current consumption, max. | 300 mA at 120 V AC; 150 mA at 240 V AC |
| Inrush current, max. | 20 A; at 264 V |
| I²t | 0.8 A²·s |

**Output current**

| | |
|---|---|
| for backplane bus (5 V DC), max. | 1 600 mA; Max. 5 V DC for SM and CM |

**Encoder supply**

| | |
|---|---|
| 24 V encoder supply | |
| ● 24 V | 20.4 to 28.8V |

**Power loss**

| | |
|---|---|
| Power loss, typ. | 14 W |

**Memory**

| | |
|---|---|
| Work memory | |
| ● integrated | 125 kbyte |
| ● expandable | No |
| Load memory | |
| ● integrated | 4 Mbyte |
| ● Plug-in (SIMATIC Memory Card), max. | with SIMATIC memory card |
| Backup | |
| ● present | Yes |
| ● maintenance-free | Yes |
| ● without battery | Yes |

**CPU processing times**

| | |
|---|---|
| for bit operations, typ. | 0.08 µs; / instruction |
| for word operations, typ. | 1.7 µs; / instruction |
| for floating point arithmetic, typ. | 2.3 µs; / instruction |

**CPU-blocks**

| | |
|---|---|
| Number of blocks (total) | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| OB | |
| ● Number, max. | Limited only by RAM for code |

**Data areas and their retentivity**

| | |
|---|---|
| Retentive data area (incl. timers, counters, flags), max. | 14 kbyte |
| Flag | |
| ● Size, max. | 8 kbyte; Size of bit memory address area |
| Local data | |
| ● per priority class, max. | 16 kbyte; Priority class 1 (program cycle): 16 KB, priority class 2 to 26: 6 KB |

**Address area**

| | |
|---|---|
| Process image | |
| ● Inputs, adjustable | 1 kbyte |
| ● Outputs, adjustable | 1 kbyte |

**Hardware configuration**

| | |
|---|---|
| Number of modules per system, max. | 3 comm. modules, 1 signal board, 8 signal modules |

**Time of day**

| | |
|---|---|
| ● Hardware clock (real-time) | Yes |
| ● Backup time | 480 h; Typical |
| ● Deviation per day, max. | ±60 s/month at 25 °C |

**Digital inputs**

| | |
|---|---|
| Number of digital inputs | 14; Integrated |
| ● of which inputs usable for technological functions | 6; HSC (High Speed Counting) |
| Source/sink input | Yes |
| Number of simultaneously controllable inputs | |
| all mounting positions | |
| — up to 40 °C, max. | 14 |
| Input voltage | |
| ● Rated value (DC) | 24 V |
| ● for signal "0" | 5 V DC at 1 mA |
| ● for signal "1" | 15 V DC at 2.5 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four |
| — at "0" to "1", min. | 0.2 ms |
| — at "0" to "1", max. | 12.8 ms |
| for interrupt inputs | |
| — parameterizable | Yes |
| for technological functions | |
| — parameterizable | Single phase: 3 @ 100 kHz & 3 @ 30 kHz, differential: 3 @ 80 kHz & 3 @ 30 kHz |
| Cable length | |
| ● shielded, max. | 500 m; 50 m for technological functions |
| ● unshielded, max. | 300 m; for technological functions: No |

**Digital outputs**

| | |
|---|---|
| Number of digital outputs | 10; Relays |
| Switching capacity of the outputs | |
| ● with resistive load, max. | 2 A |
| ● on lamp load, max. | 30 W with DC, 200 W with AC |
| Output delay with resistive load | |
| ● "0" to "1", max. | 10 ms; max. |
| ● "1" to "0", max. | 10 ms; max. |
| Relay outputs | |
| ● Number of relay outputs | 10 |
| ● Number of operating cycles, max. | mechanically 10 million, at rated load voltage 100 000 |
| Cable length | |
| ● shielded, max. | 500 m |
| ● unshielded, max. | 150 m |

**Analog inputs**

| | |
|---|---|
| Number of analog inputs | 2 |
| Input ranges | |
| ● Voltage | Yes |
| Input ranges (rated values), voltages | |
| ● 0 to +10 V | Yes |
| — Input resistance (0 to 10 V) | ≥100k ohms |
| Cable length | |
| ● shielded, max. | 100 m; twisted and shielded |

**Analog outputs**

| | |
|---|---|
| Number of analog outputs | 2 |
| Output ranges, current | |
| ● 0 to 20 mA | Yes |

**Analog value generation for the inputs**

| | |
|---|---|
| Integration and conversion time/resolution per channel | |
| ● Resolution with overrange (bit including sign), max. | 10 bit |
| ● Integration time, parameterizable | Yes |
| ● Conversion time (per channel) | 625 µs |

**Encoder**

| | |
|---|---|
| Connectable encoders | |
| ● 2-wire sensor | Yes |

**1. Interface**

| | |
|---|---|
| Isolated | Yes |
| automatic detection of transmission rate | Yes |
| Autonegotiation | Yes |
| Autocrossing | Yes |
| Interface types | |
| ● RJ 45 (Ethernet) | Yes |
| ● Number of ports | 2 |
| ● integrated switch | Yes |
| Protocols | |
| ● PROFINET IO Controller | Yes |
| ● PROFINET IO Device | Yes |
| ● SIMATIC communication | Yes |
| ● Open IE communication | Yes; Optionally also encrypted |
| ● Web server | Yes |
| ● Media redundancy | Yes |
| PROFINET IO Controller | |
| ● Transmission rate, max. | 100 Mbit/s |
| Services | |
| — PG/OP communication | Yes; encryption with TLS V1.3 pre-selected |
| — Isochronous mode | No |
| — IRT | No |
| — PROFIenergy | No |
| — Prioritized startup | Yes |
| — Number of IO devices with prioritized startup, max. | 16 |
| — Number of connectable IO Devices, max. | 16 |
| — Number of connectable IO Devices for RT, max. | 16 |

| | |
|---|---|
| — Activation/deactivation of IO Devices | Yes |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8 |
| — Updating time | The minimum value of the update time also depends on the communication component set for PROFINET IO, on the numb IO devices and the quantity of configured user data. |

**PROFINET IO Device**

| | |
|---|---|
| Services | |
| — PG/OP communication | Yes; encryption with TLS V1.3 pre-selected |
| — Isochronous mode | No |
| — IRT | No |
| — PROFIenergy | Yes |
| — Shared device | Yes |
| — Number of IO Controllers with shared device, max. | 2 |

**Protocols**

| | |
|---|---|
| Supports protocol for PROFINET IO | Yes |
| PROFIBUS | Yes; CM 1243-5 (master) or CM 1242-5 (slave) required |
| OPC UA | Yes; OPC UA Server |
| AS-Interface | Yes; CM 1243-2 required |
| Protocols (Ethernet) | |
| ● TCP/IP | Yes |
| ● DHCP | No |
| ● SNMP | Yes |
| ● DCP | Yes |
| ● LLDP | Yes |
| Redundancy mode | |
| Media redundancy | |
| — MRP | Yes; as MRP redundancy manager and/or MRP client |
| Open IE communication | |
| ● TCP/IP | Yes |
| — Data length, max. | 8 kbyte |
| ● ISO-on-TCP (RFC1006) | Yes |
| — Data length, max. | 8 kbyte |
| ● UDP | Yes |
| — Data length, max. | 1 472 byte |
| Web server | |
| ● supported | Yes |
| ● User-defined websites | Yes |
| OPC UA | |
| ● Runtime license required | Yes; "Basic" license required |
| ● OPC UA Server | Yes; data access (read, write, subscribe), method call, runtime license required |
| — Application authentication | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256 |
| — User authentication | "anonymous" or by user name & password |
| — Number of sessions, max. | 10 |
| — Number of subscriptions per session, max. | 50 |
| — Sampling interval, min. | 100 ms |
| — Publishing interval, min. | 200 ms |
| — Number of server methods, max. | 20 |
| — Number of monitored items, max. | 1 000 |
| — Number of server interfaces, max. | 2 |
| — Number of nodes for user-defined server interfaces, max. | 2 000 |
| Further protocols | |
| ● MODBUS | Yes |

**Communication functions**

| | |
|---|---|
| S7 communication | |
| ● supported | Yes |
| ● as server | Yes |
| ● as client | Yes |
| ● User data per job, max. | See online help (S7 communication, user data size) |
| Number of connections | |
| ● overall | PG Connections: 4 reserved / 4 max; HMI Connections: 12 reserved / 18 max; S7 Connections: 8 reserved / 14 max; Open User Connections: 8 reserved / 14 max; Web Connections: 2 reserved / 30 max; OPC UA Connections: 0 reserved / 10 ma Total Connections: 34 reserved / 64 max |

**Test commissioning functions**

| | |
|---|---|
| Status/control | |
| ● Status/control variable | Yes |
| ● Variables | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| Forcing | |
| ● Forcing | Yes |
| Diagnostic buffer | |
| ● present | Yes |
| Traces | |
| ● Number of configurable Traces | 2 |
| ● Memory size per trace, max. | 512 kbyte |

**Interrupts/diagnostics/status information**

| | |
|---|---|
| Diagnostics indication LED | |
| ● RUN/STOP LED | Yes |
| ● ERROR LED | Yes |
| ● MAINT LED | Yes |

**Integrated Functions**

| | |
|---|---|
| Frequency measurement | Yes |
| controlled positioning | Yes |
| Number of position-controlled positioning axes, max. | 8 |
| Number of positioning axes via pulse-direction interface | Up to 4 with SB 1222 |
| PID controller | Yes |
| Number of alarm inputs | 4 |

**Potential separation**

| | |
|---|---|
| Potential separation digital inputs | |
| ● Potential separation digital inputs | 500V AC for 1 minute |
| ● between the channels, in groups of | 1 |

| | |
|---|---|
| ● between the channels | No |
| ● between the channels, in groups of | 2 |

**EMC**

| | |
|---|---|
| Interference immunity against discharge of static electricity | |
|   ● Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 | Yes |
|     — Test voltage at air discharge | 8 kV |
|     — Test voltage at contact discharge | 6 kV |
| Interference immunity to cable-borne interference | |
|   ● Interference immunity on supply lines acc. to IEC 61000-4-4 | Yes |
|   ● Interference immunity on signal cables acc. to IEC 61000-4-4 | Yes |
| Interference immunity against voltage surge | |
|   ● Interference immunity on supply lines acc. to IEC 61000-4-5 | Yes |
| Interference immunity against conducted variable disturbance induced by high-frequency fields | |
|   ● Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 | Yes |
| Emission of radio interference acc. to EN 55 011 | |
|   ● Limit class A, for use in industrial areas | Yes; Group 1 |
|   ● Limit class B, for use in residential areas | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011 |

**Standards, approvals, certificates**

| | |
|---|---|
| CE mark | Yes |
| UL approval | Yes |
| cULus | Yes |
| FM approval | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| Marine approval | Yes |

**Ambient conditions**

| | |
|---|---|
| Free fall | |
|   ● Fall height, max. | 0.3 m; five times, in product package |
| Ambient temperature during operation | |
|   ● min. | -20 °C |
|   ● max. | 60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertica or 10 at 55 °C horizontal or 45 °C vertical |
|   ● horizontal installation, min. | -20 °C |
|   ● horizontal installation, max. | 60 °C |
|   ● vertical installation, min. | -20 °C |
|   ● vertical installation, max. | 50 °C |
| Ambient temperature during storage/transportation | |
|   ● min. | -40 °C |
|   ● max. | 70 °C |
| Air pressure acc. to IEC 60068-2-13 | |
|   ● Operation, min. | 795 hPa |
|   ● Operation, max. | 1 080 hPa |
|   ● Storage/transport, min. | 660 hPa |
|   ● Storage/transport, max. | 1 080 hPa |
| Altitude during operation relating to sea level | |
|   ● Installation altitude, min. | -1 000 m |
|   ● Installation altitude, max. | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
| Relative humidity | |
|   ● Operation, max. | 95 %; no condensation |
| Vibrations | |
|   ● Vibration resistance during operation acc. to IEC 60068-2-6 | 2 g (m/s²) wall mounting, 1 g (m/s²) DIN rail |
|   ● Operation, tested according to IEC 60068-2-6 | Yes |
| Shock testing | |
|   ● tested according to IEC 60068-2-27 | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms |
| Pollutant concentrations | |
|   ● SO2 at RH < 60% without condensation | S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free |

**Configuration**

| | |
|---|---|
| Programming | |
|   Programming language | |
|     — LAD | Yes |
|     — FBD | Yes |
|     — SCL | Yes |
| Know-how protection | |
|   ● User program protection/password protection | Yes |
|   ● Copy protection | Yes |
|   ● Block protection | Yes |
| Access protection | |
|   ● protection of confidential configuration data | Yes |
|   ● Protection level: Write protection | Yes |
|   ● Protection level: Read/write protection | Yes |
|   ● Protection level: Complete protection | Yes |
| Cycle time monitoring | |
|   ● adjustable | Yes |

**Dimensions**

| | |
|---|---|
| Width | 130 mm |
| Height | 100 mm |
| Depth | 75 mm |

**Weights**

| | |
|---|---|
| Weight, approx. | 550 g |
| **last modified:** | 4/12/2021 |

---

Technical data for the product is also available in the following languages:

> German
> French
> Italian
> Spanish
> Chinese
> Russian

**Requests and feedback**

What do you want to do?

- You have a technical question / problem: Ask the Technical Support
  > Create support request

- You want to discuss in our forum and exchange experiences with other users
  > Go to the Forum (/tf/us/en)

- You want to create CAx data for one or more products
  > Go to the CAx download manager

- You would like to send us feedback on this Product
  > Provide feedback

Note: The feedback always refers to the current product. Your message will be sent to the editors in the online support. You will receive an answer from us in a few days if your feedback requires it. If everything clear to us, we will no longer answer you.