

Simultaneous Evolution of Morphology and Locomotion of Soft Robots by Novelty Search

Georgios Methenitis

UvA, ACT

June 27, 2014

Introduction

Soft Robots

- ▶ Inspired by nature
- ▶ Completely soft bodies
- ▶ Capable of developing new kinds of locomotion



Soft robots can be actuated through air pressure tubes, environmental changes (temperature, pressure), even explosions.


Related Material



VoxCad Simulator [2]

- ▶ Created by Jonathan Hiller and Hod Lipson
- ▶ Voxel modeling and analyzing software


- ▶ Lattice
- ▶ Voxels
- ▶ Structure
- ▶ Materials



Related Work I

Evolving virtual creatures [5]

- ▶ Rigid body parts, joints
- ▶ Evolution of the morphology and the control




Evolving a diversity of virtual creatures through novelty search and local competition [4]

- ▶ Same experimental framework
- ▶ Novelty < Fitness
- ▶ Novelty search with global competition has the best average fitness.

Related Work II


Evolving soft robots with multiple materials and a powerful generative encoding. [1]

- ▶ Generative encoding, Compositional pattern-producing network, CPPN.
- ▶ Neuroevolution of augmenting topologies, NEAT.



Compositional pattern-producing network [7]

- ▶ Similar to artificial neural networks
- ▶ Different set of activation functions



- ▶ Produce symmetrical and repetitive patterns
- ▶ Appropriate for problems with geometrical structure

NeuroEvolution through Augmented Topologies (NEAT) [6]


Some key points of this method are:

- ▶ Evolving neural network topologies along with weights
- ▶ Crossover between different topologies
- ▶ Structural innovation through speciation (New species have time to improve)

Novelty Search

What novelty means:

- ▶ Traditionally fitness measures how good an individual is (Objective function).
- ▶ Objective function can prevent evolution reaching the global maximum.
- ▶ Thus we can abandon the objective.
- ▶ Try finding novelty in behavior space.
- ▶ Random?



Research Topics

- ▶ Gravity
 - ▶ Performance under different conditions of gravity
- ▶ Novelty search
 - ▶ Performance, in respect to the original fitness
 - ▶ Performance, in behavior space
 - ▶ Behavior, what is a good behavior metric?
- ▶ Other evolutionary algorithms
 - ▶ Genetic algorithm with direct coding
 - ▶ Random generative encoding
 - ▶ Covariance Matrix Adaptation Evolution Strategy (CMA-ES)
 - ▶ Differential Evolution (jDE)
- ▶ Can we evolve CPPNs with other evolutionary algorithms?

Things completed so far...

- ▶ Replication of the results from [1]
- ▶ Generative random encoding
- ▶ Simple genetic algorithm
- ▶ Own implementation of CPPN-NEAT experiment (HyperNEAT C++ library)
- ▶ Novelty search
- ▶ Competition between species (novelty, fitness)

Generative Random Encoding

Only two parameters can change in this encoding.

1. The probability of adding a new voxel into the structure.
2. The probability that the new voxel introduced will use the same kind of material as its connection.

We start with a random voxel inserted into the lattice.

- ▶ Choose whether a new voxel is going to be inserted.
- ▶ Choose randomly its connection.
- ▶ Choose its material.
- ▶ Iterate

Simple genetic algorithm

- ▶ GAlib C++ library
- ▶ Each genome is represented by a stream of real numbers in $[0, 1]$.
- ▶ The length of this stream is equal to:

$$l = n \times (m + 1)$$

, where n , is the number of total voxels and m is the number of materials.

- ▶ For a lattice's dimensions of $10 \times 10 \times 10$ and 4 materials the length of the genome is 5000.
- ▶ Simple genetic algorithm fails to produce locomotion.
- ▶ No structure knowledge.

CPPN-NEAT

- ▶ HyperNEAT C++
- ▶ Each genome is represented by a CPPN.
- ▶ This CPPN is queried for each input coordinate to output the existence and the type of the material.
- ▶ NEAT evolves these CPPNs.
- ▶ In each generation, speciation. Population is split into species, new species can survive easier than old.

CPPN-NEAT with Novelty Search [3]

- ▶ Same code base
- ▶ Novelty takes the place of fitness
- ▶ Novel individuals stored in a list
- ▶ For each new individual in the population, check its novelty in respect to the stored novel individuals.
 - ▶ Minimum distance from a novel individual
 - ▶ Average distance from K nearest individuals
- ▶ Store novel enough individuals

Behavior

Behavior types used are:


- ▶ Trajectory 3D, 2D
- ▶ Pace
- ▶ Voxels touching ground
- ▶ Kinetic energy
- ▶ Maximum pressure

Behavior similarity can be computed:

- ▶ Absolute difference between normalized trajectories
- ▶ Cross-correlation of discrete Fourier transformation


Primilinary results I

$5 \times 5 \times 5$




Primilinary results II

... same experiment, more stable simulation settings, 5 runs



Primilinary results III

... same settings but size: $10 \times 10 \times 10$



References I



Nick Cheney, Robert MacCurdy, Jeff Clune, and Hod Lipson.
Unshackling evolution: evolving soft robots with multiple materials and a powerful generative encoding.
In Proceeding of the fifteenth annual conference on Genetic and evolutionary computation conference, pages 167–174.
ACM, 2013.



Jonathan Hiller and Hod Lipson.
Dynamic simulation of soft heterogeneous objects.
arXiv preprint arXiv:1212.2845, 2012.



Joel Lehman and Kenneth O Stanley.
Abandoning objectives: Evolution through the search for novelty alone.
Evolutionary computation, 19(2):189–223, 2011.

References II



Joel Lehman and Kenneth O Stanley.

Evolving a diversity of virtual creatures through novelty search and local competition.

In Proceedings of the 13th annual conference on Genetic and evolutionary computation, pages 211–218. ACM, 2011.



Karl Sims.

Evolving virtual creatures.

In Proceedings of the 21st annual conference on Computer graphics and interactive techniques, pages 15–22. ACM, 1994.



Kenneth Stanley and Risto Miikkulainen.

Evolving neural networks through augmenting topologies.

Evolutionary computation, 10(2):99–127, 2002.

References III



Kenneth O Stanley.

Compositional pattern producing networks: A novel abstraction of development.

Genetic programming and evolvable machines, 8(2):131–162, 2007.