



- NOTAS
- 1 - Reservatório d'água com capacidade para 1000 litros atende aos artigos 10 e 11 do decreto 12.342/78.
 - 2 - Serviço de coleta de lixo a cargo da Prefeitura Municipal.
 - 3 - Energia elétrica a cargo da RGE
 - 4 - Água e esgoto a cargo da Samae
 - 5 - Água pluvial destinada à guia e sarjetas.
 - 6 - Paredes internas e externas com 0,15 m de dimensão.
 - 7 - Não existe árvore defronte o imóvel.
 - 8 - Deverá ser reservado 2% da área do lote para drenagem de águas (LC 132/05)

- ESPAÇIALIZAÇÃO
- TÉRREO:
- 01 ESCRITÓRIO
 - GALPÃO
 - 06 VAGAS PARA GARAGEM
 - 02 BANHEIROS
 - 02 VESTIÁRIOS
- SUPERIOR:
- 01 ESCRITÓRIO
 - 02 BANHEIROS

Máquina	Alimentação	Especificações
Printer YSP10	Single-phase AC 200 to 230V +/- 20V	https://global.yamaha-motor.com/business/smt/printer/ysp10/spec/
Conveyor	220 VAC / 60Hz / Monofásico 120W	https://www.allpoint.com.br/transportador-de-inspecao-e-conexao.html
Panasonic pick and place AM100	3-phase AC 200 / 220 V ± 10 V, AC 380 / 400 / 420 / 480 V ± 20 V 2.0 kVA	https://na.panasonic.com/us/factory-equipment-solutions/electronics-assembly-manufacturing-technologies/surface-mount-technology-smt/am100-single-beam-single-head-placement
Reflow oven Point reflow 12 zonas	5 linhas, 3 fases 380V 50/60Hz 68kW	https://www.allpoint.com.br/forno-de-refusao-point-reflow-12-zonas.html
Wave solder tnw33-36ex/et	AC220V $\pm 10\%$ -50/60Hz-3 ϕ 34kVA 95A	https://www.tamuracorp.com/products/electronic_chemicals/category/fa_systems/w_solder/tnw.html
AOI	100-120 V, 16A / 200-240V, 8A Single Phase	https://www.vitrox.com/vision-technology-machine-system/optical-inspection-system-aoi-v510i-se-spec.php
Bancada de uso geral	220V - 1980W	