The EM chapters, re-examined

Confirmatory evidence for Chapters 8–11

Internal report for discussion with Jerome and Marc · 16 September 2026

This report states what sixteen-seed confirmatory runs, executed on the Bocconi cluster over the past two days, say about the chapters from EM onwards. Three of the four chapters survive intact; one conclusion reverses; one comparison the thesis explicitly declared out of reach has now been made. Section 1 is the short version, Section 2 states what we are doing and why it is trustworthy, Sections 3–6 go chapter by chapter, and Section 9 lists the five decisions that need taking.

1 Summary

1. **The capacity conclusion of Chapter 10 reverses.** It was an artefact of a stopping rule that fired for the single-Gaussian arm and for no other. Under a protocol that selects the checkpoint identically for every capacity, the single Gaussian sits exactly on the second-order floor at every sample size (0.167) and every richer capacity goes far below it (0.023 at $M = 2048$), favouring the mixture in 16 of 16 seeds at every size.

2. **The two rates of Chapter 9 are a property of the channel, not of the optimiser.** The EM estimator attains the Cramér–Rao bound of the noised likelihood to within a factor 1.02 on average. The shape coordinate is not slow because EM is slow; the data stop carrying it. Its information bound crosses the coordinate's own range at $t = 0.98$, and that is precisely where the fit collapses to a Gaussian innovation.

3. **The comparison of Chapter 10 now runs at a matched information interface.** The thesis attached a scope condition saying it could not do this. Given the same single noised view per sequence that the estimator sees, the best network reaches 0.155 against the estimator's 0.023: a paired factor 7.3, interval $[6.2, 8.7]$. The unmatched comparison, at 2.83×, *understates* the gap.

4. **Locality is a ceiling, not only a prior.** The radius-4 window head is the best network at $M = 32$ and the worst of the five weight-shared architectures at $M = 2048$, moving only $0.121 \to 0.118$ as data quadruples. A bounded receptive field cannot represent a message that has crossed the chain — which is exactly what the chain's score is.

5. **Score accuracy transfers to generation, and the second-order score fails there visibly.** Driven through the same reverse SDE on identical Brownian paths, the fitted kernel produces sequences whose innovation excess kurtosis is 1.887 against the reference's 1.896, with a log-likelihood gap of 0.022 under the true law. The covariance-matched score gives -0.008 — an essentially Gaussian chain — at a gap of 1.71, and the isotropic score a gap of 46.2.

6. **A claim of ours was refuted by our own data, and is recorded as such.** "The learned networks sit at or above the second-order floor" had been drafted into the new abstract. At $M = 2048$ five of six architectures sit below it. The defensible statement is about the information interface, not about a barrier the networks cannot pass.

2 What we are doing, and why the numbers can be trusted

Three changes to how the work is run account for why these results settle questions the thesis left open.

One frozen protocol, one varied factor. Everything the arms share is now a single frozen object: the bundle sizes and their random streams, the sizes $M \in \{32, 128, 512, 2048\}$, the sixteen confirmatory seeds and four development seeds, the EM iteration ladder and its initialisation, the network training recipe and screen budget, the estimand, and the scoring regions. Each experiment varies exactly one declared factor against that background, so a difference between two arms is attributable to that factor. Two arms that differ in more than one thing are not compared; where a comparison genuinely needs two factors to move, the intermediate arm is run as well.

Pairing by construction. Every row records the SHA-256 of the validation and test bundles it was scored on. Rows from different experiments are joined on (seed, size, bundle hash), and a generator that is handed rows with mismatched hashes refuses to emit a number. This is what makes "EM–BP against the best network" a paired comparison across two experiments rather than two averages.

Frozen outputs. A result becomes citable only when its output directory is pinned: every CSV and provenance file hashed into the registry entry together with the commit that produced it. After that, any byte change fails the build, and the manuscript refuses to compile if a generated number disagrees with the artefact it came from. A re-run is a new artefact under a new key, never an overwrite. Confirmatory seeds are declared before the run and never used for selection; development seeds never enter a reported number.

Amendments are recorded, not absorbed. Two design changes were made this week before the runs that used them, and both are in the registry with timestamps: the EM ladder was extended from 400 to 1200 iterations because 400 was binding at the largest sample size, and the largest strength of the site-varying misspecification mechanism was removed because it is not a valid chain — at $\rho = 0.85$ its site coefficients exceed 1 and the implied covariance is not positive definite. No number from the invalid point exists.

3 Chapter 8 — EM for the parameters: holds

Nothing in the derivation needed revision. Fisher's identity still gives the exact gradient of the discretised marginal log-likelihood from one forward–backward pass, and the finite-difference check agrees to about 10^{-9}. Two things were added.

The algebra is now machine-checked where checking is cheap. A Lean 4 module builds against Mathlib with no `sorry` and no axiom, covering four constants: the Hermite attenuation for degrees up to four, the fourth-cumulant difference under variance matching, the factor $\frac{1}{2}$ in the Gaussian information rate, and the coefficient $\kappa_4/6$ in the score gap. It verifies the algebraic skeleton and not the analysis: the remainder bounds and the measure-level statements remain informal, and the write-up says so in those words rather than claiming more.

The confirmatory ladder was extended to 1200 iterations. At $M = 2048$ the richer capacities were still selecting the top of the 400-iteration ladder; they still select the top of the extended one in 10 of 16 seeds, so the errors reported for those arms in Table 1 remain upper bounds. That can only understate the effect described there.

4 Chapter 9 — the two rates: same fact, better reason

The chapter explains the asymmetry through EM's fixed-point map: the Jacobian is the missing information and the shape coordinate has the smaller eigenvalue, so the fitted innovation shape settles at a median of 229 updates against 80 for the correlation. That measurement stands, and the stopping-rule warning built on it stands with it.

What is new is that the asymmetry is no longer only a statement about the optimiser. Two results bracket it.

The channel, from theory. Under the Ornstein–Uhlenbeck channel every Hermite mode of degree m is attenuated exactly by e^{-mt}, so the Fisher information one noised sequence carries about order-m structure decays as e^{-2mt}: correlation as e^{-4t}, non-Gaussian shape as e^{-8t}. Computed on the chain by exact inference the measured slopes are -3.97 and -8.01 against the predicted -4 and -8, and the constant in the score gap between the true score and that of the covariance-matched Gaussian is reproduced to within one per cent.

The estimator, from measurement. Fitting the transition law from sequences observed at a single level t ($M = 512$, 16 seeds, one noised view per sequence), the EM estimator sits *at* the Cramér–Rao bound of the noised likelihood: a ratio of 1.02 on average over the levels where either coordinate is informative, never worse than 1.18 for the correlation or 1.51 for the fourth cumulant.

Taken together these say the chapter's phenomenon belongs to the channel. If the estimator is efficient, the two rates cannot be blamed on EM. The bound for the shape coordinate grows as e^{4t} and crosses the coordinate's own range ($\kappa_4 = 3$) at $t = 0.98$; the fit collapses to a Gaussian innovation at exactly that level, while the correlation estimate is still within 0.009 of the truth and survives past the crossover $t_* = 1.17$.

One limitation, stated plainly. The corollary predicts errors growing as e^{2t} and e^{4t}, and this run cannot test those exponents. At $\rho = 0.85$ the shape estimate saturates before the crossover, so the asymptotic window does not exist at this configuration. Fitting slopes through a saturated estimate would have returned 3.64 and 0.09 against predictions of 2 and 4; the analysis therefore reports no slope, and a companion run at $\rho = 0.5$ with $M = 2048$ — where the crossover falls at 0.55 and the window is reachable — is registered and queued.

5 Chapter 10 — the comparison: one reversal, one replacement, two new facts

5.1 The capacity sweep reverses

The chapter concluded that no mixture capacity improves on a single Gaussian innovation, and flagged its own caveat in the accompanying figure: the share of fits stopped at the iteration cap, and with a narrowest component below the grid's resolution floor, both climbed steeply with C. That caveat was the entire effect. In the archival sweep the likelihood tolerance fired in 31 of 32 single-Gaussian cells at a median of 71 iterations — close to where a validation protocol would stop — and in none of the 96 cells with $C \geq 4$, which therefore reported checkpoints an order of magnitude past their optimum. "The single Gaussian is as good" was "the single Gaussian is the only arm that stopped in the right place".

Table 1 re-runs the sweep with the checkpoint selected on a per-seed validation bundle identically for every capacity.

Three readings follow. The single-Gaussian kernel lands on the second-order floor at every sample size, which is Proposition 1 read as a statement about an estimator rather than about a projection. Every richer capacity goes below that floor, by a factor 7.9 at the largest size; the paired difference between $C = 1$ and $C = 8$ is 0.144 with bootstrap interval $[0.141, 0.147]$ and favours the mixture in 16 of 16 seeds. And the best capacity rises with the data, from $C = 2$ at $M = 32$ to $C = 16$ at $M = 2048$ — the ordinary variance-to-bias trade, visible now that the stopping rule no longer masks it.

Table 1: Capacity under equal stopping. Schedule-pooled relative score error on all sites, mean over 16 seeds, every arm on identical held-out bundles. The last column is the same capacity fitted to the innovation law itself — the C-component mixture closest in Kullback–Leibler divergence — an infinite-data reference for the family rather than a bound. The isotropic score is at 0.669 at every size.

	sequences M				
kernel	32	128	512	2048	$M = \infty$
LMMSE floor	0.167	0.167	0.167	0.167	0.167
$C = 1$	0.174	0.168	0.168	0.167	0.167
$C = 2$	0.084	0.050	0.035	0.028	0.039
$C = 4$	0.093	0.053	0.037	0.025	0.0057
$C = 8$	0.099	0.055	0.036	0.023	0.0022
$C = 16$	0.100	0.056	0.036	0.022	0.0007

The check that closes the loop. Two things changed at once between the thesis sweep and this one: the protocol, and the estimand (held-out log-evidence per edge there, relative score error here). Two simultaneous changes are not an explanation. A registered run now scores the *same frozen fits* in the thesis's own estimand, leaving the protocol as the only difference. A single-seed pass already shows the reversal — log-evidence per edge -1.3116 for $C = 8$ against -1.3146 for $C = 1$, with the true kernel at -1.3076 — and the sixteen-seed result is running.

5.2 The data-efficiency comparison is replaced

The chapter reports 6.6–10.9× against unstructured denoising score matching and 2.3–6.1× against a baseline given locality and weight sharing, with three scope conditions, the sharpest being that the arms are asymmetric in supplied information and that the comparison therefore does not rank learning algorithms at a matched interface.

Six architectures were screened under one recipe — 68 configurations, four development seeds, three restarts, 32,000 steps each — and the winner of each family was run on the sixteen confirmatory seeds (Table 2).

Table 2: Under one training recipe, 16 confirmatory seeds, identical held-out bundles. All-site schedule-pooled relative score error. The upper block is trained on clean sequences with a fresh corruption at every gradient step; the lower block sees what the estimator sees.

estimator	$M = 32$	$M = 2048$	information supplied
fully connected	0.517	0.208	clean, fresh corruption
window head ($r = 4$)	0.186	0.118	clean, fresh corruption
bidirectional GRU	0.201	0.060	clean, fresh corruption
transformer	0.231	0.063	clean, fresh corruption
1-D U-Net	0.227	0.066	clean, fresh corruption
dilated TCN	0.223	0.068	clean, fresh corruption
best matched-interface net	—	0.155	one noised view
EM–BP ($C = 8$)	0.099	0.023	one noised view
LMMSE floor	*0.167*	*0.167*	—

Two numbers replace the thesis's ranges. Against the best of six architectures under the standard recipe, the estimator is ahead by a paired factor 2.83, interval $[2.37, 3.42]$, in 16 of 16 seeds at $M = 2048$, and by 2.07 at $M = 32$. Against the best network trained at the estimator's own interface — one noised view per sequence, no clean chain, checkpoint selected

on the implicit objective of a held-out noisy bundle and never on the true score — the factor is 7.3, interval $[6.2, 8.7]$. Implicit score matching on that bundle, which uses no clean target at all, lands at 0.165.

The second number is the one the thesis said was out of reach, and it is the stronger claim: the gap is not an artefact of giving the networks less, because when they are given the same, the gap widens.

It also follows that one sentence drafted for the new paper is false and has been withdrawn. "Every network sits at or above the second-order floor" holds only at the smallest sample size; at $M = 2048$ five of the six sit below it. Given enough clean sequences and fresh corruptions a neural denoiser plainly does learn fourth-order structure. The honest statement concerns the information interface.

5.3 Two facts the thesis does not contain

Locality is a ceiling. The window head is the best network at $M = 32$ and the worst of the five weight-shared architectures at $M = 2048$, moving only from 0.121 to 0.118 as the data quadruples, against a standard error of 0.001, while the global architectures continue to 0.060. A radius-4 window cannot represent a message that has travelled the length of the chain, and the chain's exact score is precisely such a message. This connects the architecture comparison to the bulk-posterior analysis the chapter already contains.

Length extrapolation separates the arms cleanly. Fitted at $L = 32$ and evaluated against the exact score of longer chains (Table 3), the fitted kernel is flat: the law is local, so inference at any length is the same exact recursion. The convolutional and recurrent networks improve slightly, as they should, since longer chains have proportionally fewer boundary sites. The transformer with learned relative positions degrades by an order of magnitude — a failure of the positional encoding beyond its training length, not of the score it learned.

Table 3: Length extrapolation at $M = 2048$: pooled relative score error of estimators fitted at $L = 32$ and evaluated against the tree-exact score at longer chains, mean over 16 seeds.

estimator	$L = 32$	$L = 64$	$L = 128$	$L = 256$
EM–BP ($C = 8$)	0.023	0.023	0.023	0.023
bidirectional GRU	0.060	0.057	0.057	0.056
1-D U-Net	0.066	0.064	0.062	0.062
dilated TCN	0.068	0.066	0.065	0.064
window head	0.118	0.099	0.088	0.082
transformer	0.063	0.243	0.514	0.703

6 Chapter 11 — which answers change

RQ5, recovering an unknown transition. The answer holds and gains a sentence. The E-step is structurally exact, recovery is demonstrated numerically over the studied regime, and the uneven settling of the coordinates is real. We can now add that the estimator is statistically efficient, so the unevenness belongs to the channel and not to the algorithm. The stopping-rule warning becomes sharper rather than weaker: a rule read off the correlation trace certifies a kernel whose shape coordinate the data may no longer identify at all.

RQ6, what supplying the Markov assumption is worth. The answer changes in its numbers and in its scope. The ranges 6.6–10.9× and 2.3–6.1× are superseded by 2.83× against the best of six architectures under one recipe. The third scope condition — that the comparison

does not rank methods at a matched information interface — can be removed, because that comparison now exists and gives 7.3×. The capacity subsection of the same chapter must be rewritten in the opposite direction.

The retired claim. The capacity result should be stated as retired rather than quietly dropped, together with the diagnosis of why it arose. The same applies to the claim of ours that our own screen refuted this week. The project keeps a negative-results record for exactly this, and both entries are in it.

7 Generation and the boundary of the advantage

Two results completed while this report was being written. Both were pre-registered and both address questions Chapter 10 raises but does not settle.

Does score accuracy transfer to generation? Every arm drives the same reverse SDE from the same initialisation along the same Brownian path, so the comparison is paired within a seed and the integrator is common to all of them. The discretisation was measured separately and is not what separates the arms: against an 800-step reference the strong error is 0.0190, 0.0087 and 0.0033 at 100, 200 and 400 steps, roughly halving per doubling, while the excess kurtosis of the generated sequences is stable at 2.00–2.05 across the whole ladder.

Table 4: Generation at $M = 2048$, four seeds, common Brownian paths. Log-likelihood gap is the mean deficit in $\log p_{t_{\min}}$ per sequence against the reference sample, computed by exact belief-propagation evidence under the true law. The reference sample has excess kurtosis 1.896.

score driving the sampler	log-lik. gap	exc. kurtosis	sliced W_2	cov. error
exact (tree BP)	0.041	1.833	0.046	0.068
EM–BP ($C = 8$), fitted	0.022	1.887	0.051	0.072
LMMSE (covariance twin)	1.710	−0.008	0.047	0.067
isotropic	46.20	0.003	0.239	0.909

The fitted score and the exact score are indistinguishable on this evidence: the fitted kernel's log-likelihood gap is if anything the smaller of the two, and its generated kurtosis is nearer the reference. The second-order score is the instructive failure. On the metrics that see only two moments — sliced W_2, the covariance error — it is as good as the exact score, which is what Proposition 1 predicts. On the fourth cumulant it produces −0.008 where the truth is 1.896: it generates a Gaussian chain with the right covariance. A generative model evaluated only on second-order distances would score it as a success.

Where does the advantage stop? The structured estimator assumes a first-order Markov chain. Four Gaussian departures from that assumption were swept, each with a scalar strength ε and an exact score of its own, so every arm is scored against the truth of the perturbed model rather than against the chain.

The pattern is clean and interpretable. A rank-one global latent is absorbed by the fitted correlation and never reverses the ordering, because it does not break the conditional independence structure the estimator exploits. The three mechanisms that do break it — adding an order, widening the precision band, or making the chain inhomogeneous — each reverse it at a measurable strength, and the site-varying mechanism reverses it soonest. This gives the chapter the boundary it currently lacks: the advantage is not a general property of "having structure", it is specific to the structure being approximately right, and how wrong it can be is now quantified.

Table 5: Misspecification: ratio of the window head's pooled error to EM–BP's, at the largest and smallest strength of each mechanism. Above 1 the misspecified chain estimator still wins. Eight seeds, sizes 512 and 2048 pooled.

mechanism	what it breaks	$\varepsilon = 0$	largest ε	break-even
rank-one global latent	nothing structural	10.5	3.96 ($\varepsilon = 1.0$)	not reached
AR(2) second coefficient	the order	10.9	0.97 ($\varepsilon = 0.4$)	≈ 0.40
long-range coupling	the precision band	7.9	1.00 ($\varepsilon = 0.4$)	≈ 0.40
site-varying ρ	homogeneity	9.8	0.99 ($\varepsilon = 0.14$)	≈ 0.14

8 Status of the evidence, and what is still running

Table 6: Confirmatory runs. *Frozen* means every file in the output directory is pinned by SHA-256 in its registry entry, with the commit that produced it; a generator refuses to read an output that is not frozen or whose bytes have changed.

run	what it establishes	state
E01	order-by-order decay verified on the chain	frozen
E02a	capacity under equal stopping	frozen
E02b	capacity against innovation shape at fixed covariance	frozen
E03	six architectures, matched interface, length	frozen
E06	learning through noise, against the information bound	frozen
E07	the second-order floor across correlation	frozen
E09	infinite-data reference per capacity	frozen
E10	capacity in the thesis's own estimand	frozen
E04	grid refinement on the fitted models	running
E05	generation under each score, paired noise	frozen
E08	misspecification and its break-even	frozen
E06b	the asymptotic exponents at $\rho = 0.5$	frozen, inconclusive

One reading is still partial. *Refinement*: doubling the quadrature grid from 401 to 801 points moves the reference score, and every arm's error, by less than 10^{-4} relative on the cells completed so far, so the numbers in this report are not grid artefacts. The full ladder, which adds 1601 points and a wider domain, is the one run still going.

Three infrastructure faults, for the record. Jobs were inheriting the login shell's 600-second CPU limit, which killed one run outright and left another holding an idle compute node for ten hours while the scheduler reported it running. Two drivers wrote their results only at the very end, so a timeout would have lost everything; both now write per cell and resume. And the site-varying misspecification mechanism is undefined at its largest registered strength. All three are fixed; the third is a registered amendment.

9 Decisions requested

1. **How should the capacity reversal be presented?** Either rewrite the capacity section of Chapter 10 around the new result and retain the old figure as a documented artefact, or keep both and make the diagnosis itself the finding. The second is more honest about how the error surfaced and costs roughly a page.

2. **Is the matched-interface comparison the headline, or a robustness check?** It is the stronger claim and it removes a scope condition the thesis carried. Promoting it changes the framing from "structure beats networks" to "structure beats networks at equal information, and the unmatched comparison understates it".

3. **Where does the efficiency result belong?** The estimator attaining the Cramér–Rao bound is what turns the two rates from an observation about EM into a statement about information. It reads naturally in Chapter 9 or in the theory chapter, and should be stated once with a reference from the other.

4. **How far should the Lean verification go?** Four algebraic constants are machine-checked. The remainder bounds are analysis and would be a substantial effort; the projection operator behind Proposition 1 is the one load-bearing step still in prose. Is the current scope the right stopping point?

5. **Do we pursue the asymptotic exponents, or claim the rates only where they are established?** The run at $\rho = 0.5$ has reported and the window it opens is three levels wide, too narrow to pin an exponent (Section 4). The window grows only logarithmically in M, so closing it properly means a much smaller ρ and a much larger M, or switching to an estimand that does not saturate — which is a different claim. The alternative, which is what the write-up currently does, is to establish the rates exactly by computation and the estimator's efficiency by measurement, and to state the sample-complexity consequence only where the coordinate is still identifiable.

6. **Does the misspecification boundary belong in Chapter 10 or in the conclusions?** It is the cleanest statement we have about when the method should *not* be used — a rank-one global latent never reverses the ordering, while breaking the order, the precision band or the homogeneity each reverse it at a measurable strength. It reads as a limitation, but it is a measured one, which is unusual enough to be worth foregrounding.

Every number above comes from a registered experiment whose output directory is pinned by SHA-256 in its registry entry, together with the commit that produced it and the seeds it used. The protocol shared by all arms is a single frozen object, so two arms differ only in the one factor each experiment varies. Runs were executed on the Bocconi HPC. Supporting material: the claim–evidence matrix, the negative-results record, the experiment registry and the reproducibility notes in the project repository.